

ATA100



Images
Specifications

AIS Class A Transponder Communication and Safety at Sea

- Compact single unit solution with full colour display
- Colour coastline map
- Compliant with EU Inland Waterways standard
- Radar and Target list displays
- Selectable chart orientation
- Incoming message & alarm display
- Alarm output for AIS SART, MOB and EPIRB detection
- Surface mount and bracket mount options
- Supplied with GPS antenna
- Continuous self-testing with alarm notifications
- Simple to use
- Message sending functionality
- Compliant to regulations
- WiFi and USB interfaces for PC & tablet connection
- Pilot plug
- Waterproof to IPx7
- Isolated alarm relay contacts
- Programmable for up to 30 MOB units
- Simple installation

The ATA100 AIS Transponder is a fully compliant Class A transceiver designed to complement the existing range of maritime safety equipment from Ocean Signal. Used as an aid to collision-avoidance, the ATA100 combines the trusted technology and fluid product design that have become synonymous with Ocean Signal products.

This compact, single unit solution is capable of exchanging dynamic and static ship data with other AIS systems. Real time marine traffic information is continuously interpreted using a powerful internal processing engine and displayed on a 7" full-colour, rapid-response LCD. The coastline map view and radar view have various orientation display options allowing for user preference whilst a standard target list display gives immediate detailed listings of nearby vessels which can be sorted to the owner's desire.

The AIS message-sending functionality is simple to use, ensuring safety related messages can be quickly delivered or received by the user with very little effort. An instant message and alarm function provides immediate notification of any potential problems or hazards including the deployment of Ocean Signal's MOB1, the world's smallest Man Overboard AIS/DSC device. It is also compatible with all other AIS Man Overboard devices including ACR's AISLink MOB.

Dynamic data such as location, speed over ground and course over ground is calculated automatically using the integrated 99-channel GPS receiver, while the static and voyage related data such as MMSI, call sign and name, type of ship, destination, ETA etc. is easily programmed into the AIS transponder via a user-friendly menu interface.

This single unit solution to meet AIS requirements ensures a minimal use of bridge space and its surface or free standing mounting options allow for easy installation into almost any position or location. It also includes multiple connectivity options including WiFi, USB port, serial and Pilot plug.

The ATA100 AIS Transponder Class A unit from Ocean Signal meets the requirements of the EU MED (Wheelmark) Directive and USCG/FCC regulations.

It also complies with the EU Inland Waterways standard, administered by the CCNR.

The following statement is for US customers only: This device has not been authorized as required by the rules of the Federal Communications Commission. This device is not, and may not be, offered for sale or lease, or sold or leased, until authorization is obtained.

Whilst every effort has been made to ensure the information in this leaflet is accurate, products and specifications may be changed without notice.



Purchase

Find a Stockist (<http://oceansignal.com/stockists/>)

Product Selection (<http://oceansignal.com/comparison/>)

Share



(<https://twitter.com/oceansignal>)

/OceanSignal

/Ocean-

Signal

/245523582147931)



Transmit Power	12.5/1 Watts
Frequency Range	156.025 – 162.025MHz
AIS Modulation	GMSK: BT 0.4
DSC Modulation	FSK: Mod Index 2

AIS RX1 & RX2	156.025 – 162.025MHz
DSC	156.525MHz
Sensitivity	-107dBm for 20% PER

Temperature Range	-15°C to +55°C / 5°F to 131°F
Waterproof	IPx7 (1metre for 30mins)
Supply Voltage Range	9.6V to 31.2V

	High sensitivity
Channels	99 acquisition / 33 tracking

Serial Ports	IEC61162-1 & -2, 3 Rx only, 3 Rx/Tx / Pilot plug / USB / WiFi IEC802.11 bgn
Blue Switch Input	Isolated
Alarm Relay	Normally Open / Normally closed: 2A max

IEC61933-2, IEC60945, IEC62288

< E101V (<http://oceansignal.com/products/e101v/>)

Privacy Policy (<http://oceansignal.com/privacy-policy/>) Sitemap (<http://oceansignal.com/sitemap/>)

in
(https://www.linkedin.com
f /company
twitter /compa
(https://www.linkedin.com
https://www.instagram.com
/OceanSignal) beansignaltd/