



Satellite Qualitative Test – Configuration 5



Satellite Qualitative Test – Configuration 7



Satellite Qualitative Test – Configuration 8



Position Acquisition Time and Position Accuracy Test – Configuration 5 – A.3.8.2.2



Position Acquisition Time and Position Accuracy Test – Configuration 7 – A.3.8.2.1



Position Acquisition Time and Position Accuracy Test – Configuration 8 – A.3.8.2.2



Moffset Test – Configuration 8



UTC Test – Configuration 8



SECTION 5

ACCREDITATION, DISCLAIMERS AND COPYRIGHT

5.1 ACCREDITATION, DISCLAIMERS AND COPYRIGHT



This report relates only to the actual item/items tested.

Our UKAS Accreditation does not cover opinions and interpretations and any expressed are outside the scope of our UKAS Accreditation.

Results of tests not covered by our UKAS Accreditation Schedule are marked NUA (Not UKAS Accredited).

This report must not be reproduced, except in its entirety, without the written permission of TÜV SÜD

© 2022 TÜV SÜD

ANNEX A

ADDITIONAL TEST OF THE GNSS RECEIVER UPDATE INTERVAL

Additional Test of the GNSS Receiver Update Interval

Specification

Cospas-Sarsat T.007, Clause A.2.7
IEC 61097-2:2021, Clause 5.7 (a)
MSC.471(101), Clause A.4.1

Equipment Under Test and Modification State

RLB-44 S/N: TA000006 - Modification State 2 (RLS Protocol)

Date of Test

17 May 2022 – 19 May 2022

Test Equipment Used

The major items of test equipment used for the above tests are identified in the Test Equipment section below.

Laboratory Environmental Conditions

Ambient Temperature 22.4 – 22.7°C
Relative Humidity 46.8 – 53.9%

Test Results

Encoded Position Data Update Interval – Verification:

Locations: Continues movement at 60 Mph around the M25 ①		
Parameter	Update interval	Limit
0 h to 2 h – Minimum	04:07	≤ 05:00
0 h to 2 h – Maximum	05:04*	≤ 05:00
2 h to 6 h – Minimum	04:07	≤ 05:00
2 h to 6 h – Maximum	05:04*	≤ 05:00
6 h to 9 h – Minimum	04:08	≤ 05:00
6 h to 9 h – Maximum	05:04*	≤ 05:00
Assessment	Result	Limit
Results indicate that data changes as per C/S T.001 4.5.5.4 (Y/N)	Y	-
Results indicate that data changes as per manufacturer's update scheme (Y/N)	Y	-

① Input from GPS simulator

The EUT was provided a simulated scenario which represented a continuously moving vehicle travelling at a constant speed of 60 mph around the M25 motorway in the UK.

*NOTE: Clause 5.7 (a) of IEC 61097-2:2021 says "(MSC.471(101)/A.4.1) the GNSS position fix shall be updated at intervals of no more than 5 min and shall then be encoded into the next 406 MHz and AIS transmissions;

NOTE If the GNSS position fix is obtained within 2 s of the next 406 MHz or AIS transmission, it is acceptable to delay updating the position until the next transmission."

*NOTE: Refer to manufacturer document 921S-04094 Cospas-Sarsat Beacon Update rate.

Deviation: This test differs from the A.3.8.3 Long Test in Section 2.12 above as the EUT was provided a simulated scenario which involved a continuously moving GNSS location travelling at a constant 60 mph, whereas the test in Section 2.12 changes locations every 2 minutes and the location steps are either 2.225 km or 3.105 km.

Summary

The reason for the additional test is that although the Beacon passes the requirements in C/S T.001 the test in T.007 A.3.8.3 does not demonstrate a GNSS position update rate of no more than 5 minutes as required by IEC61097-2 Ed 4. The IEC specification requires the requirement to be demonstrated by the results within the Cospas-Sarsat T.007 test report.

Cospas-Sarsat T.007 clause A.3.8.3 does not allow for the EUT to demonstrate the GNSS update rate required by IEC61097-2 Ed 4 because the T.007 test is related to the encoded position rather than the GNSS receiver update interval.

Refer also to the Ocean Signal Limited paper reference 921S-04094 Issue 1.4 Cospas-Sarsat Beacon Encoded Update Rate.

The results presented above demonstrate that the Manufacturer's declared operating GNSS update rate of 4 minutes 30 seconds is consistent with the results of the test: furthermore the results conform to the requirement of no more than the 5 minute period stated in IEC 61097-2 ed 4, clause 5.7.

Test Equipment

Additional Test of the GNSS Receiver Update Interval					
Beacon Tester	WS Technologies	BT 100S	87	-	TU
Directional Coupler	Narda	3022	503	-	O/P Mon
Spectrum Analyser	Agilent Technologies	E4407B	1154	12	20-Dec-2022
Hygrometer	Rotronic	I-1000	1897	12	26-Nov-2022
Signal Generator	Marconi	2031	2015	12	31-Mar-2023
Termination (50ohm, 1W)	Suhner	50ohm 1W	3080	12	04-May-2023
Antenna (DRG Horn)	ETS-Lindgren	3115	3125	12	15-Oct-2022
Charge Amplifier	Endevco	133	3480	12	25-Nov-2022
Power Meter	Rohde & Schwarz	NRP	3491	12	29-Nov-2022
Wideband Power Sensor, 50MHz - 18GHz	Rohde & Schwarz	NRP-Z81	3492	12	29-Nov-2022
Termination (50ohm)	Meca	405-1	3518	-	TU
GPS Simulator	Spirent	GSS7000	4978	12	21-Jul-2022
Cable (18 GHz)	Rosenberger	LU7-036-1000	5025	-	O/P Mon
Cable (18 GHz)	Rosenberger	LU7-036-1000	5026	-	O/P Mon
Cable (18 GHz)	Rosenberger	LU7-036-2000	5039	12	20-Oct-2022
Attenuator 30dB 10w	Pasternack	NPE7010-30	5929	12	21-Apr-2023