

MPE Evaluation Report

Applicant Asiatelco Technologies Co.
FCC ID XYO-AN99
Product GPS TRACKER
Brand ATEL
Model AN99
Report No. EFTA25090351-IE-03-M1V2
Issue Date December 16, 2025

Eurofins TA Technology (Shanghai) Co., Ltd. tested the above equipment in accordance with the requirements in **FCC 47 CFR Part 1 §1.1310, §2.1091**. The test results show that the equipment tested can demonstrate compliance with the requirements as documented in this report.



Prepared by: Wei Fangying



Approved by: Xu Kai

Eurofins TA Technology (Shanghai) Co., Ltd.

Building 3, No.145, Jintang Rd, Pudong Shanghai, P.R.China

TEL: +86-021-50791141/2/3

FAX: +86-021-50791141/2/3-8000

Version	Revision Description	Issue Date
Rev.0	Initial issue of report.	November 17, 2025
Rev.1	Updated data. Updated information.	December 4, 2025
Rev.2	Updated data.	December 16, 2025
Note: This revised report (Report No.: EFTA25090351-IE-03-M1V2) supersedes and replaces the previously issued report (Report No.: EFTA25090351-IE-03-M1). Please discard or destroy the previously issued report and dispose of it accordingly.		

Table of Contents

1	Test Laboratory	4
1.1	Notes of the Test Report.....	4
1.2	Test Facility.....	4
1.3	Testing Location.....	4
1.4	Laboratory Environment	4
2	Description of Equipment Under Test	5
3	Maximum Tune up and Antenna Gain	6
4	MPE Limit.....	8
5	RF Exposure Evaluation Result.....	10
	ANNEX A: The EUT Appearance	11

1 Test Laboratory

1.1 Notes of the Test Report

This report shall not be reproduced in full or partial, without the written approval of **Eurofins TA Technology (Shanghai) Co., Ltd.** The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. Measurement Uncertainties were not taken into account and are published for informational purposes only. This report is written to support regulatory compliance of the applicable standards stated above.

1.2 Test Facility

FCC (Designation number: CN1179, Test Firm Registration Number: 446626)

Eurofins TA Technology (Shanghai) Co., Ltd. has been listed on the US Federal Communications Commission list of test facilities recognized to perform measurements.

1.3 Testing Location

Company: Eurofins TA Technology (Shanghai) Co., Ltd.
Address: Building 3, No.145, Jintang Rd, Pudong Shanghai, P.R.China
City: Shanghai
Post code: 201201
Country: P. R. China
Contact: Xu Kai
Telephone: +86-021-50791141/2/3
Fax: +86-021-50791141/2/3-8000
Website: <https://www.eurofins.com/electrical-and-electronics>
E-mail: Kain.Xu@cpt.eurofinscn.com

1.4 Laboratory Environment

Temperature	Min. = 18°C, Max. = 25°C
Relative humidity	Min. = 20%, Max. = 80%
Ground system resistance	< 0.5 Ω
Ambient noise is checked and found very low and in compliance with requirement of standards. Reflection of surrounding objects is minimized and in compliance with requirement of standards.	

2 Description of Equipment Under Test

Client Information

Applicant	Asiatelco Technologies Co.
Applicant address	#289 Bisheng Road, Building-8, 3F, Zhang jiang Hi-Tech Park, Pudong, Shanghai, 201204China
Manufacturer	Asiatelco Technologies Co.
Manufacturer address	#289 Bisheng Road, Building-8, 3F, Zhang jiang Hi-Tech Park, Pudong, Shanghai, 201204China

General Technologies

EUT Description			
Model	AN99		
SN	E25270006165		
Hardware Version	P1		
Software Version	5.6.11.41		
Frequency	Band	TX (MHz)	RX (MHz)
	GSM 850	824 ~ 849	869 ~ 894
	GSM 1900	1850 ~ 1910	1930 ~ 1990
	LTE Band 2	1850 ~ 1910	1930 ~ 1990
	LTE Band 4	1710 ~ 1755	2110 ~ 2155
	LTE Band 5	824 ~ 849	869 ~ 894
	LTE Band 7	2500 ~ 2570	2620 ~ 2690
	LTE Band 66	1710 ~ 1780	2110 ~ 2180
	Wi-Fi 2.4G	2400 ~ 2483.5	2400 ~ 2483.5
	Bluetooth LE	2400 ~ 2483.5	2400 ~ 2483.5
EUT Accessory			
Battery 1	Manufacturer: Fujian Nanping Nanfu new energy Co., LTD. Model: LR63S1P-2P		
Date of Testing	September 25, 2025 ~ November 7, 2025		
Date of Sample Received	September 25, 2025		
Note: 1. The EUT is sent from the applicant to Eurofins TA and the information of the EUT is declared by the applicant. 2. All indications of Pass/Fail in this report are opinions expressed by Eurofins TA Technology (Shanghai) Co., Ltd. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only.			

3 Maximum Tune up and Antenna Gain

The numeric gain (G) of the antenna with a gain specified in dB is determined by
Numeric gain (G)=10[^] (antenna gain/10)

According to specification 3GPP TS 51.010, the maximum power of the GSM can do the power reduction for the multi-slot. The allowed power reduction in the multi-slot configuration is as following:

Number of timeslots in uplink assignment	Permissible nominal reduction of maximum output power (dB)
1	0
2	0 to 3,0
3	1,8 to 4,8
4	3,0 to 6,0

Each Tx slots maximum tune up use the most strictest factor for evaluation by making calculation.

Band		Burst-Averaged output power (adjusted for tune up) (dBm)	Division Factors	Frame-Averaged output power (adjusted for tune up) (dBm)
GSM850	GSM	36.000	-9.03	26.970
	1 Txslot	36.000	-9.03	26.970
	2 Txslots	36.000	-6.02	29.980
	3 Txslots	34.200	-4.26	29.940
	4 Txslots	33.000	-3.01	29.990
GSM1900	GSM	33.000	-9.03	23.970
	1 Txslot	33.000	-9.03	23.970
	2 Txslots	33.000	-6.02	26.980
	3 Txslots	31.200	-4.26	26.940
	4 Txslots	30.000	-3.01	26.990

Note:

Division Factors

To average the power, the division factor is as follows:

1Txslot = 1 transmit time slot out of 8 time slots

=> conducted power divided by (8/1) => -9.03 dB

2Txslots = 2 transmit time slots out of 8 time slots

=> conducted power divided by (8/2) => -6.02 dB

3Txslots = 3 transmit time slots out of 8 time slots

=> conducted power divided by (8/3) => -4.26 dB

4Txslots = 4 transmit time slots out of 8 time slots

=> conducted power divided by (8/4) => -3.01 dB

Band	Maximum Tune up Power		Antenna Gain (dBi)	Numeric Gain
	(dBm)	(mW)		
GSM850	29.990	997.700	3.47	2.22
GSM1900	26.990	500.035	3.20	2.09
LTE Band 2	25.700	371.535	3.20	2.09
LTE Band 4	25.700	371.535	5.21	3.32
LTE Band 5	25.700	371.535	3.47	2.22
LTE Band 7	25.700	371.535	3.63	2.31
LTE Band 66	25.700	371.535	5.21	3.32
Wi-Fi 2.4G	14.000	0.025	1.09	1.29
Bluetooth LE	4.000	0.003	1.46	1.40

4 MPE Limit

According to section 1.1310 of FCC 47 CFR Part 1, limits for maximum permissible exposure (MPE) are as following.

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(i) LIMITS FOR OCCUPATIONAL/CONTROLLED EXPOSURE				
0.3-3.0	614	1.63	*(100)	≤6
3.0-30	1842/f	4.89/f	*(900/f ²)	<6
30-300	61.4	0.163	1.0	<6
300-1,500			f/300	<6
1,500-100,000			5	<6
(ii) LIMITS FOR GENERAL POPULATION/UNCONTROLLED EXPOSURE				
0.3-1.34	614	1.63	*(100)	<30
1.34-30	824/f	2.19/f	*(180/f ²)	<30
30-300	27.5	0.073	0.2	<30
300-1,500			f/1500	<30
1,500-100,000			1.0	<30

*f = frequency in MHz. * = Plane-wave equivalent power density.*

Note1. Occupational/controlled limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. Limits for occupational/controlled exposure also apply in situations when an individual is transient through a location where occupational / controlled limits apply provided he or she is made aware of the potential for exposure.

Note2: General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or can not exercise control over their exposure.

The maximum permissible exposure for 1500~100,000MHz is 1.0. So

Band	The Maximum Permissible Exposure (mW/cm ²)
GSM850	0.549
GSM1900	1.000
LTE Band 2	1.000

LTE Band 4	1.000
LTE Band 5	0.549
LTE Band 7	1.000
LTE Band 66	1.000
Wi-Fi 2.4GHz	1.000
Bluetooth LE	1.000

5 RF Exposure Evaluation Result

RF exposure evaluation method is based on KDB 447498 D01, this calculation is based on the conducted power, maximum power and antenna gain with provides the minimum separation distance. The formula shown below is from OET Bulletin 65 Edition 97-01 Per KDB 447498 D01:

$$S = PG / 4\pi R^2$$

Where: S = power density (in appropriate units, e.g. mW/cm²)

P = Time-average maximum tune up procedure (in appropriate units, e.g., mW)

G = the numeric gain of the antenna

R = distance to the center of radiation of the antenna (20 cm = limit for MPE)

Band	Maximum Tune up (dBm)	Antenna Gain (dBi)	Maximum EIRP (dBm)	PG (mW)	Result (mW/cm ²)	Limit Value (mW/cm ²)	The MPE Ratio
GSM850	29.990	3.47	33.460	2218.196	0.441	0.549	0.804
GSM1900	26.990	3.20	30.190	1044.720	0.208	1.000	0.208
LTE Band 2	25.700	3.20	28.900	776.247	0.154	1.000	0.154
LTE Band 4	25.700	5.21	30.910	1233.105	0.245	1.000	0.245
LTE Band 5	25.700	3.47	29.170	826.038	0.164	0.549	0.299
LTE Band 7	25.700	3.63	29.330	857.038	0.171	1.000	0.171
LTE Band 66	25.700	5.21	30.910	1233.105	0.245	1.000	0.245
Wi-Fi 2.4GHz	14.000	1.09	15.090	32.285	0.006	1.000	0.006
Bluetooth LE	4.000	1.46	5.460	3.516	0.001	1.000	0.001
Note: R = 20cm $\pi = 3.1416$ The MPE Ratio = Mac Result÷Limit Value							

This device supports simultaneous transmission via WWAN and Wi-Fi 2.4GHz and Bluetooth.

So, the simultaneous transmitting antenna pairs as below:

TER = WWAN Antenna MPE Ratio + Wi-Fi 2.4GHz Antenna MPE Ratio + Bluetooth Antenna MPE Ratio = 0.804 + 0.006 + 0.001 = 0.811 < 1

Note: For transmitters, minimum separation distance is 20cm, even if calculations indicate MPE distance is less.

ANNEX A: The EUT Appearance

The EUT Appearance are submitted separately.

*****END OF REPORT *****