

TEST REPORT

Application No.: SZCR2601000162AT
Applicant: SKULLCANDY, INC.
Address of Applicant: 1640 Redstone Center Drive, Suite 115A Park City, UT 84098, United States of America
Manufacturer: SKULLCANDY, INC.
Address of Manufacturer: 1640 Redstone Center Drive, Suite 115A Park City, UT 84098, United States of America
Equipment Under Test (EUT):
EUT Name: Session 360
Model No.: S8STS
Trade Mark:  Skullcandy
FCC ID: Y22-S8STS
Standard(s) : 47 CFR Part 15, Subpart C 15.247
Date of Receipt: 2026-01-11
Date of Test: 2026-01-16 to 2026-01-30
Date of Issue: 2026-02-05

Test Result:	Pass*
---------------------	--------------

* In the configuration tested, the EUT complied with the standards specified above.

Keny Xu

Keny Xu
EMC Laboratory Manager



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/2

Report No.: SZCR260100016203

Page: 2 of 69

Revision Record				
Version	Chapter	Date	Modifier	Remark
01		2026-02-05		Original

Authorized for issue by:				
		Tree Zhan		
		Tree Zhan/Project Engineer		
		Eric Fu		
		Eric Fu/Reviewer		



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch / 深圳分公司 / 检验检测专用章

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

2 Test Summary

Radio Spectrum Technical Requirement				
Item	Standard	Method	Requirement	Result
Antenna Requirement	47 CFR Part 15, Subpart C 15.247	N/A	47 CFR Part 15, Subpart C 15.203 & 15.247(b)(4)	Pass

Radio Spectrum Matter Part				
Item	Standard	Method	Requirement	Result
Conducted Emissions at AC Power Line (150kHz-30MHz)	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2020) Section 6.2	47 CFR Part 15, Subpart C 15.207	Pass
Radiated Emissions which fall in the restricted bands		ANSI C63.10 (2020) Section 6.10.5	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass
Radiated Spurious Emissions Below 1GHz		ANSI C63.10 (2020) Section 6.4,6.5	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass
Radiated Spurious Emissions Above 1GHz		ANSI C63.10 (2020) Section 6.6	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass
Conducted Peak Output Power		ANSI C63.10 (2020) Section 11.9.1	47 CFR Part 15, Subpart C 15.247(b)(3)	Pass
Minimum 6dB Bandwidth		ANSI C63.10 (2020) Section 11.8.1	47 CFR Part 15, Subpart C 15.247a(2)	Pass
Power Spectrum Density		ANSI C63.10 (2020) Section 11.10.2	47 CFR Part 15, Subpart C 15.247(e)	Pass
Conducted Band Edges Measurement		ANSI C63.10 (2020) Section 6.10.4	47 CFR Part 15, Subpart C 15.247(d)	Pass
Conducted Spurious Emissions		ANSI C63.10 (2020) Section 11.11	47 CFR Part 15, Subpart C 15.247(d)	Pass



3 Contents

	Page
1 Cover Page	1
2 Test Summary	3
3 Contents	4
4 General Information.....	6
4.1 Details of E.U.T.	6
4.2 Description of Support Units	6
4.3 Measurement Uncertainty	6
4.4 Test Location	7
4.5 Test Facility.....	7
4.6 Deviation from Standards	7
4.7 Abnormalities from Standard Conditions	7
5 Equipment List	8
6 Radio Spectrum Technical Requirement.....	11
6.1 Antenna Requirement	11
6.1.1 Test Requirement:	11
6.1.2 Conclusion	11
7 Radio Spectrum Matter Test Results	12
7.1 Conducted Emissions at AC Power Line (150kHz-30MHz)	12
7.1.1 E.U.T. Operation	12
7.1.2 Test Mode Description	12
7.1.3 Test Setup Diagram	13
7.1.4 Measurement Procedure and Data	13
7.2 Radiated Emissions which fall in the restricted bands	16
7.2.1 E.U.T. Operation	16
7.2.2 Test Mode Description	16
7.2.3 Test Setup Diagram	17
7.2.4 Measurement Procedure and Data	18
7.3 Radiated Spurious Emissions Below 1GHz.....	23
7.3.1 E.U.T. Operation	23
7.3.2 Test Mode Description	23
7.3.3 Test Setup Diagram	24
7.3.4 Measurement Procedure and Data	24
7.4 Radiated Spurious Emissions Above 1GHz	27
7.4.1 E.U.T. Operation	27
7.4.2 Test Mode Description	27
7.4.3 Test Setup Diagram	28
7.4.4 Measurement Procedure and Data	29
7.5 Conducted Peak Output Power	36
7.5.1 E.U.T. Operation	36



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/2

Report No.: SZCR260100016203

Page: 5 of 69

7.5.2	Test Mode Description	36
7.5.3	Test Setup Diagram	37
7.5.4	Measurement Procedure and Data	37
7.6	Minimum 6dB Bandwidth	38
7.6.1	E.U.T. Operation	38
7.6.2	Test Mode Description	38
7.6.3	Test Setup Diagram	38
7.6.4	Measurement Procedure and Data	38
7.7	Power Spectrum Density	39
7.7.1	E.U.T. Operation	39
7.7.2	Test Mode Description	39
7.7.3	Test Setup Diagram	39
7.7.4	Measurement Procedure and Data	39
7.8	Conducted Band Edges Measurement	40
7.8.1	E.U.T. Operation	40
7.8.2	Test Mode Description	40
7.8.3	Test Setup Diagram	41
7.8.4	Measurement Procedure and Data	41
7.9	Conducted Spurious Emissions	42
7.9.1	E.U.T. Operation	42
7.9.2	Test Mode Description	42
7.9.3	Test Setup Diagram	43
7.9.4	Measurement Procedure and Data	43
8	Test Setup Photo	44
9	EUT Constructional Details (EUT Photos)	44
10	Appendix	45



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Inspection & Testing Services Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

4 General Information

4.1 Details of E.U.T.

Power supply:	DC 3.7V 1200mAh which can be charged from USB-C port.
Cable(s):	USB cable: 48mm unshielded
Cable Loss (for RF conducted test):	0.7dB
Operation Frequency:	2402MHz to 2480MHz
Modulation Type:	GFSK
Number of Channels:	40
Channel Spacing:	2MHz
Antenna Type:	Pattern Antenna
Antenna Gain:	2.77dBi

Remark: The information in this section is provided by the applicant or manufacturer, SGS is not liable to the accuracy, suitability, reliability or/and integrity of the information.

4.2 Description of Support Units

Description	Manufacturer	Model No.	Serial No.
Adapter	Apple	A2244	REF. No.SEA05D14G

4.3 Measurement Uncertainty

Test Item	Measurement Uncertainty
Conducted Emissions at AC Power Line (150kHz-30MHz)	$\pm 3.2\text{dB}$
Radiated Emissions which fall in the restricted bands	$\pm 6.0\text{dB}$ (Below 1GHz); $\pm 4.6\text{dB}$ (Above 1GHz)
Radiated Spurious Emissions Below 1GHz	$\pm 6.0\text{dB}$ for 3m; $\pm 5.0\text{dB}$ for 10m
Radiated Spurious Emissions Above 1GHz	$\pm 4.6\text{dB}$ (1-18GHz); $\pm 4.8\text{dB}$ (18-40GHz)
Conducted Peak Output Power	$\pm 0.4\text{dB}$
Minimum 6dB Bandwidth	$\pm 0.3\%$
Power Spectrum Density	$\pm 0.4\text{dB}$
Conducted Band Edges Measurement	$\pm 2.7\text{dB}$
Conducted Spurious Emissions	$\pm 2.7\text{dB}$

Remark:

The U_{lab} (lab Uncertainty) is less than $U_{\text{CISPR/ETSI}}$ (CISPR/ETSI Uncertainty), so the test results

- compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/2

Report No.: SZCR260100016203

Page: 7 of 69

4.4 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China. 518057.

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594

No tests were sub-contracted.

4.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

• A2LA (Certificate No. 3816.01)

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

• VCCI (Member No. 1937)

The 3m Fully-anechoic chamber for above 1GHz, 10m Semi-anechoic chamber for below 1GHz, Shielded Room for Mains Port Conducted Interference Measurement and Telecommunication Port Conducted Interference Measurement of SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen EMC laboratory have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-20026, R-14188, C-12383 and T-11153 respectively.

• FCC –Designation Number: CN1336

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized as an accredited testing laboratory.

Designation Number: CN1336. Test Firm Registration Number: 787754.

• Innovation, Science and Economic Development Canada

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized by ISED as an accredited testing laboratory.

CAB identifier: CN0006.

IC#: 4620C.

4.6 Deviation from Standards

None

4.7 Abnormalities from Standard Conditions

None



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch EMC Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.ssgroup.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

5 Equipment List

Conducted Emissions at AC Power Line (150kHz-30MHz)					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
Shielding Room	ZhongYu Electron	GB-88	SEM001-06	2025-05-07	2028-05-06
EMI Test Receiver	Rohde&Schwarz	ESR	SZ-WRG-M-047	2025-12-15	2026-12-14
Measurement Software	AUDIX	e3 V8.2014-6-27a	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM024-01	2025-07-05	2026-07-04
LISN	Rohde&Schwarz	ENV216	SEM007-01	2025-07-25	2026-07-24
LISN	ETS-LINDGREN	3816/2	SEM007-02	2025-03-03	2026-03-02

Radiated Emissions which fall in the restricted bands					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
3m Fully-Anechoic Chamber	AUDIX	N/A	SEM001-02	2025-05-07	2028-05-06
Signal Analyzer	Rohde & Schwarz	FSV40	SEM008-04	2025-03-04	2026-03-03
Horn Antenna	Rohde&Schwarz	HF907	SEM003-07	2025-07-22	2026-07-21
Microwave system amplifier	Agilent	83017A	SEM005-25	2025-09-10	2026-09-09
Measurement Software	AUDIX	e3 V8.2014-6-27	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM026-01	2025-07-05	2026-07-04
Broad-Band Horn Antenna	Schwarzbeck	BBHA 9170	SEM003-15	2025-07-22	2027-07-21
Pre-Amplifier	Compliance Directions Systems Inc.	PAP-2640-50	SEM005-08	2025-03-21	2026-03-20



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch (SZEMC) EMC Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/2

Report No.: SZCR260100016203

Page: 9 of 69

Radiated Spurious Emissions Below 1GHz					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
10m Semi-Anechoic Chamber	SAEMC	FSAC1018	SEM001-03	2025-03-21	2026-03-20
MXE EMI receiver	KEYSIGHT	N9038A	SEM004-16	2025-07-25	2026-07-24
Trilog-Broadband Antenna	Schwarzbeck	VULB9168	SEM003-18	2025-08-29	2027-08-28
Pre-amplifier	Sonoma Instrument Co	310N	SEM005-04	2025-03-04	2027-02-01
Loop Antenna	ETS-Lindgren	6502	SEM003-08	2025-11-17	2027-11-16
Measurement Software	AUDIX	e3 V8.2014-6-27	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM029-01	2025-07-05	2026-07-04

Radiated Spurious Emissions Above 1GHz					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
3m Fully-Anechoic Chamber	AUDIX	N/A	SEM001-02	2025-05-07	2028-05-06
Signal Analyzer	Rohde & Schwarz	FSV40	SEM008-04	2025-03-04	2026-03-03
Horn Antenna	Rohde&Schwarz	HF907	SEM003-07	2025-07-22	2026-07-21
Microwave system amplifier	Agilent	83017A	SEM005-25	2025-09-10	2026-09-09
Measurement Software	AUDIX	e3 V8.2014-6-27	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM026-01	2025-07-05	2026-07-04
Broad-Band Horn Antenna	Schwarzbeck	BBHA 9170	SEM003-15	2025-07-22	2027-07-21
Pre-Amplifier	Compliance Directions Systems Inc.	PAP-2640-50	SEM005-08	2025-03-21	2026-03-20

RF Conducted Test					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
Power Sensor	TST PASS	TSPS2023R	SEM009-26	2025-03-04	2026-03-03
Power Sensor	KEYSIGHT	U2021XA	SEM009-16	2025-03-04	2026-03-03
DC Power Supply	Chroma	62012P-80-60	SEM011-11	2025-07-24	2026-07-23
MXA Signal Analyzer	KEYSIGHT	N9020A	SEM004-19	2025-03-04	2026-03-03
Measurement Software	TST PASS	TST PASS V2.0	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM031-01	2025-07-05	2026-07-04
Attenuator	Huber+Suhner	6620_SMA-50-1	SEM021-09	2025-03-03	2026-03-02



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch (SZEMC) Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/2

Report No.: SZCR260100016203

Page: 10 of 69

General used equipment					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
Humidity/ Temperature Indicator	deli	8838	SEM002-32	2025-07-23	2026-07-22
Humidity/ Temperature Indicator	deli	8838	SEM002-33	2025-07-23	2026-07-22
Barometer	Changchun Meteorological Industry Factory	DYM3	SEM002-01	2025-03-03	2026-03-02



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

6 Radio Spectrum Technical Requirement

6.1 Antenna Requirement

6.1.1 Test Requirement:

47 CFR Part 15, Subpart C 15.203 & 15.247(b)(4)

6.1.2 Conclusion

15.203 requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

EUT Antenna:

The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is 2.77dBi.

Antenna location: Refer to internal photos



7 Radio Spectrum Matter Test Results

7.1 Conducted Emissions at AC Power Line (150kHz-30MHz)

Test Requirement 47 CFR Part 15, Subpart C 15.207
 Test Method: ANSI C63.10 (2020) Section 6.2
 Test Engineer: Mason Wu

Limit:

Frequency of emission(MHz)	Conducted limit(dBμV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50
*Decreases with the logarithm of the frequency.		
Detector: Peak for pre-scan (9kHz resolution bandwidth) 0.15M to 30MHz		

7.1.1 E.U.T. Operation

Operating Environment:

Temperature: 23.4 °C Humidity: 42.5 % RH Atmospheric Pressure: 1020 mbar

7.1.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	02	TX mode(1Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Pre-scan	03	TX mode(2Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.




SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/2

Report No.: SZCR260100016203

Page: 14 of 69

Test Mode: 02; Line: Live line



Site : Shielding Room
Condition: Line
Job No. : 00162AT/00163AT
Test mode: 02

	Freq	Cable Loss	LISN Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB	dBuV	dBuV	dBuV	dB	
1	0.2174	0.07	9.63	27.02	36.72	62.92	-26.20	QP
2	0.2174	0.07	9.63	10.34	20.04	52.92	-32.88	Average
3 *	0.3083	0.08	9.63	24.18	33.89	60.02	-26.13	QP
4	0.3083	0.08	9.63	9.55	19.26	50.02	-30.76	Average
5	1.0653	0.11	9.67	15.22	25.00	56.00	-31.00	QP
6	1.0653	0.11	9.67	5.02	14.80	46.00	-31.20	Average
7	1.5274	0.12	9.70	5.65	15.47	56.00	-40.53	QP
8	1.5274	0.12	9.70	-0.73	9.09	46.00	-36.91	Average
9	4.5494	0.14	9.95	16.90	26.99	56.00	-29.01	QP
10 *	4.5494	0.14	9.95	7.79	17.88	46.00	-28.12	Average
11	5.3050	0.14	10.04	19.38	29.56	60.00	-30.44	QP
12	5.3050	0.14	10.04	9.81	19.99	50.00	-30.01	Average



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch (Shenzhen EMC Laboratory)

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com


SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/2

Report No.: SZCR260100016203

Page: 15 of 69

Test Mode: 02; Line: Neutral Line



Site : Shielding Room
Condition: Neutral
Job No. : 00162AT/00163AT
Test mode: 02

	Freq	Cable Loss	LISN Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB	dBuV	dBuV	dBuV	dB	
1	0.2139	0.07	9.66	26.40	36.13	63.05	-26.92	QP
2	0.2139	0.07	9.66	11.03	20.76	53.05	-32.29	Average
3 *	0.3100	0.08	9.63	24.75	34.46	59.97	-25.51	QP
4	0.3100	0.08	9.63	11.49	21.20	49.97	-28.77	Average
5	0.9582	0.11	9.66	13.72	23.49	56.00	-32.51	QP
6	0.9582	0.11	9.66	5.67	15.44	46.00	-30.56	Average
7	1.6105	0.12	9.70	6.01	15.83	56.00	-40.17	QP
8	1.6105	0.12	9.70	0.38	10.20	46.00	-35.80	Average
9	4.5254	0.14	9.95	17.28	27.37	56.00	-28.63	QP
10 *	4.5254	0.14	9.95	7.90	17.99	46.00	-28.01	Average
11	5.1937	0.14	10.04	19.73	29.91	60.00	-30.09	QP
12	5.1937	0.14	10.04	8.90	19.08	50.00	-30.92	Average



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Testing Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

7.2 Radiated Emissions which fall in the restricted bands

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209
 Test Method: ANSI C63.10 (2020) Section 6.10.5
 Measurement Distance: 3m
 Test Engineer: Logic Wang

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

7.2.1 E.U.T. Operation

Operating Environment:


Temperature: 23.5 °C Humidity: 56.3 % RH Atmospheric Pressure: 1020 mbar

7.2.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	02	TX mode(1Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	03	TX mode(2Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.



7.2.3 Test Setup Diagram



30MHz-1GHz

Above 1GHz



7.2.4 Measurement Procedure and Data


- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.

Remark 1: Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor

Remark 2: For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.




BLE_1M_TX_CH_00_Horizontal-Peak



Site : chamber
Condition: 3m HORIZONTAL
Job No : 00162AT\00163AT
Mode : 2402 Band edge
BLE

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark	Aux Factor
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1	2359.170	16.09	29.10	32.80	35.85	48.24	74.00	-25.76	Peak	0.00
2	2390.000	16.13	29.10	32.78	33.31	45.76	74.00	-28.24	Peak	0.00
3 p	2402.000	16.15	29.09	32.77	89.89	102.36	74.00	28.36	Peak	0.00


BLE_1M_TX_CH_00_Horizontal-Avg



Site : chamber
Condition: 3m HORIZONTAL
Job No : 00162AT\00163AT
Mode : 2402 Band edge
BLE

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark	Aux Factor
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1	2379.150	16.12	29.10	32.79	22.57	35.00	54.00	-19.00	Average	0.00
2	2390.000	16.13	29.10	32.78	22.23	34.68	54.00	-19.32	Average	0.00
3 q	2402.000	16.15	29.09	32.77	89.51	101.98	54.00	47.98	Average	0.00


BLE_1M_TX_CH_00_Vertical-Peak



Site : chamber
Condition: 3m VERTICAL
Job No : 00162AT\00163AT
Mode : 2402 Band edge
BLE

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark	Aux Factor
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1	2377.530	16.12	29.10	32.79	35.86	47.49	74.00	-26.51	Peak	0.00
2	2390.000	16.13	29.10	32.78	33.46	45.91	74.00	-28.09	Peak	0.00
3 p	2402.000	16.15	29.09	32.77	83.55	96.02	74.00	22.02	Peak	0.00

BLE_1M_TX_CH_00_Vertical-Avg




Site : chamber
Condition: 3m VERTICAL
Job No : 00162AT\00163AT
Mode : 2402 Band edge
BLE

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark	Aux Factor
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1	2347.402	16.07	29.06	32.80	22.68	35.01	54.00	-18.99	Average	0.00
2	2390.000	16.13	29.10	32.78	22.13	34.58	54.00	-19.42	Average	0.00
3 q	2402.000	16.15	29.09	32.77	83.49	95.96	54.00	41.96	Average	0.00




BLE_1M_TX_CH_39_Horizontal-Peak



Site : chamber
Condition: 3m HORIZONTAL
Job No : 00162AT\00163AT
Mode : 2480 Band edge
BLE

Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark	Aux Factor
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1 p 2480.000	16.27	28.90	32.73	89.29	101.73	74.00	27.73	Peak	0.00
2 2483.500	16.28	28.90	32.73	37.41	49.86	74.00	-24.14	Peak	0.00
3 2485.095	16.28	28.90	32.73	40.86	53.31	74.00	-20.69	Peak	0.00


BLE_1M_TX_CH_39_Horizontal-Avg



Site : chamber
Condition: 3m HORIZONTAL
Job No : 00162AT\00163AT
Mode : 2480 Band edge
BLE

Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark	Aux Factor
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1 q 2480.000	16.27	28.90	32.73	88.78	101.22	74.00	27.22	Average	0.00
2 2483.500	16.28	28.90	32.73	25.81	37.46	74.00	-36.54	Average	0.00
3 2483.921	16.28	28.90	32.73	25.14	37.59	74.00	-36.41	Average	0.00


BLE_1M_TX_CH_39_Vertical-Peak



Site : chamber
Condition: 3m VERTICAL
Job No : 00162AT\00163AT
Mode : 2480 Band edge
BLE

Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark	Aux Factor
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1 p 2480.000	16.27	28.90	32.73	84.27	96.71	74.00	22.71	Peak	0.00
2 2483.500	16.28	28.90	32.73	34.09	46.54	74.00	-27.46	Peak	0.00
3 2484.345	16.28	28.90	32.73	36.81	49.26	74.00	-24.74	Peak	0.00

BLE_1M_TX_CH_39_Vertical-Avg




Site : chamber
Condition: 3m VERTICAL
Job No : 00162AT\00163AT
Mode : 2480 Band edge
BLE

Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark	Aux Factor
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1 q 2480.000	16.27	28.90	32.73	83.82	96.26	74.00	22.26	Average	0.00
2 2483.500	16.28	28.90	32.73	22.82	35.27	74.00	-38.73	Average	0.00
3 2483.846	16.28	28.90	32.73	22.93	35.38	74.00	-38.62	Average	0.00




BLE_2M_TX_CH_00_Horizontal-Peak



Site : chamber
Condition: 3m HORIZONTAL
Job No : 00162AT\00163AT
Mode : 2402 Band edge
BLE

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark	Aux Factor
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1	2353.778	16.08	29.10	32.80	35.82	48.20	74.00	-25.80	Peak	0.00
2	2390.000	16.13	29.10	32.78	33.42	45.87	74.00	-28.13	Peak	0.00
3 p	2402.000	16.15	29.09	32.77	89.83	102.30	74.00	28.30	Peak	0.00


BLE_2M_TX_CH_00_Horizontal-Avg



Site : chamber
Condition: 3m HORIZONTAL
Job No : 00162AT\00163AT
Mode : 2402 Band edge
BLE

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark	Aux Factor
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1	2337.673	16.05	28.93	32.81	23.49	35.66	54.00	-18.34	Average	0.00
2	2390.000	16.13	29.10	32.78	22.65	35.10	54.00	-18.90	Average	0.00
3 q	2402.000	16.15	29.09	32.77	88.30	100.77	54.00	46.77	Average	0.00


BLE_2M_TX_CH_00_Vertical-Peak



Site : chamber
Condition: 3m VERTICAL
Job No : 00162AT\00163AT
Mode : 2402 Band edge
BLE

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark	Aux Factor
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1	2376.329	16.11	29.10	32.79	35.30	47.72	74.00	-26.28	Peak	0.00
2	2390.000	16.13	29.10	32.78	33.71	46.16	74.00	-27.84	Peak	0.00
3 p	2402.000	16.15	29.09	32.77	83.50	95.97	74.00	21.97	Peak	0.00

BLE_2M_TX_CH_00_Vertical-Avg




Site : chamber
Condition: 3m VERTICAL
Job No : 00162AT\00163AT
Mode : 2402 Band edge
BLE

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark	Aux Factor
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1	2352.282	16.08	29.10	32.80	23.19	35.57	54.00	-18.43	Average	0.00
2	2390.000	16.13	29.10	32.78	22.38	34.83	54.00	-19.17	Average	0.00
3 q	2402.000	16.15	29.09	32.77	82.00	94.47	54.00	40.47	Average	0.00




BLE_2M_TX_CH_39_Horizontal-Peak



Site : chamber
Condition: 3m HORIZONTAL
Job No : 00162AT\00163AT
Mode : 2480 Band edge
BLE

Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark	Aux Factor
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1 p 2480.000	16.27	28.90	32.73	89.28	101.72	74.00	27.72	Peak	0.00
2 2483.500	16.28	28.90	32.73	40.09	52.54	74.00	-21.46	Peak	0.00
3 2483.921	16.28	28.90	32.73	38.24	50.69	74.00	-23.31	Peak	0.00


BLE_2M_TX_CH_39_Horizontal-Avg



Site : chamber
Condition: 3m HORIZONTAL
Job No : 00162AT\00163AT
Mode : 2480 Band edge
BLE

Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark	Aux Factor
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1 q 2480.000	16.27	28.90	32.73	87.51	99.95	54.00	45.95	Average	0.00
2 2483.500	16.28	28.90	32.73	29.50	41.95	54.00	-12.05	Average	0.00
3 2483.896	16.28	28.90	32.73	27.04	39.49	54.00	-14.51	Average	0.00


BLE_2M_TX_CH_39_Vertical-Peak



Site : chamber
Condition: 3m VERTICAL
Job No : 00162AT\00163AT
Mode : 2480 Band edge
BLE

Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark	Aux Factor
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1 p 2480.000	16.27	28.90	32.73	64.43	96.87	74.00	22.87	Peak	0.00
2 2483.500	16.28	28.90	32.73	36.42	48.87	74.00	-25.13	Peak	0.00
3 2483.846	16.28	28.90	32.73	36.01	48.46	74.00	-25.54	Peak	0.00

BLE_2M_TX_CH_39_Vertical-Avg



Site : chamber
Condition: 3m VERTICAL
Job No : 00162AT\00163AT
Mode : 2480 Band edge
BLE

Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark	Aux Factor
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1 q 2480.000	16.27	28.90	32.73	82.73	95.17	54.00	41.17	Average	0.00
2 2483.500	16.28	28.90	32.73	24.75	37.20	54.00	-16.80	Average	0.00
3 2483.821	16.28	28.90	32.73	23.83	36.28	54.00	-17.72	Average	0.00



7.3 Radiated Spurious Emissions Below 1GHz

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209
 Test Method: ANSI C63.10 (2020) Section 6.4,6.5
 Measurement Distance: 10m
 Test Engineer: Ted Wu

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
960-1000	500	3

Note

1: The emission limits for the ranges 9-90 kHz and 110-490 kHz are based on measurements employing a linear average detector.

2. At frequencies below 1GHz, measurements may be performed at a distance different to specified in the regulations.

Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor+ Aux Factor (if applicable)

The aux factor needs to be added when measurements are performed at a distance other than the limit distance provided.

EX. Below 30MHz, Aux Factor = 40 dB/decade of distance, the aux factor is $40\log(3/300) = -80\text{dB}$ (for 3m test distance).

EX. Above 30MHz, Aux Factor = 20 dB/decade of distance, the aux factor is $20\log(10/3) = 10.46\text{dB}$ (for 10m test distance).

7.3.1 E.U.T. Operation

Operating Environment:


Temperature: 23.6 °C Humidity: 46.5 % RH Atmospheric Pressure: 1020 mbar

7.3.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	02	TX mode(1Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Pre-scan	03	TX mode(2Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.



7.3.3 Test Setup Diagram



7.3.4 Measurement Procedure and Data

- For below 1GHz, the EUT was placed on the top of a rotating table 0.8m above the ground at a semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3m or 10m away from the interference-receiving antenna, which was mounted on the variable-height antenna tower.
- The antenna height is varied from 1m to 4m above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1m to 4m (for the test frequency of below 30MHz, the antenna was tuned to heights 1m) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using quasi-peak method as specified and then reported in a data sheet.
- Test the EUT in the lowest channel, the middle channel, the Highest channel.
- The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- Repeat above procedures until all frequencies measured was complete.

Remark:

- Scan from 9kHz to 30MHz, the disturbance below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only below points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.
- The disturbance below 1GHz was very low and the harmonics were the highest point could be found when testing, so only the worst-case test curve is displayed.




SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/2

Report No.: SZCR260100016203

Page: 25 of 69

Test Mode: 02; Polarity: Horizontal



Condition: 10m HORIZONTAL
Job No. : 00162AT/00163AT
Test Mode: 02

	Freq	Read Level	Ant Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	49.187	26.52	18.10	0.25	32.40	12.47	29.50	-17.03	QP
2	78.413	30.14	13.69	0.49	32.50	11.82	29.50	-17.68	QP
3	154.279	26.51	17.92	0.63	32.50	12.56	33.00	-20.44	QP
4	329.039	31.51	18.38	1.27	32.47	18.69	35.60	-16.91	QP
5	782.345	29.13	26.48	2.52	32.45	25.68	35.60	-9.92	QP
6 pp	935.546	27.48	27.97	2.73	31.82	26.36	35.60	-9.24	QP




SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Inspection & Testing Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Test Mode: 02; Polarity: Vertical



Condition: 10m VERTICAL

Job No. : 00162AT/00163AT

Test Mode: 02

		Read	Ant	Cable	Preamp		Limit	Over	
	Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	37.945	30.77	16.70	0.12	32.40	15.19	29.50	-14.31	QP
2	pp 71.581	33.61	15.55	0.35	32.48	17.03	29.50	-12.47	QP
3	104.903	34.85	13.89	0.74	32.50	16.98	33.00	-16.02	QP
4	126.772	33.19	15.96	0.68	32.50	17.33	33.00	-15.67	QP
5	341.979	33.10	18.46	1.31	32.45	20.42	35.60	-15.18	QP
6	968.934	27.24	27.84	2.80	31.65	26.23	44.40	-18.17	QP



7.4 Radiated Spurious Emissions Above 1GHz

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209
 Test Method: ANSI C63.10 (2020) Section 6.6
 Measurement Distance: 3m
 Test Engineer: Logic Wang

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
Above 1000	500	3

Note:

At Above 18GHz, measurements may be performed at a distance shorter than that specified in the regulations

Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor+ Aux Factor (if applicable)

The aux factor needs to be added when measurements are performed at a distance other than the limit distance provided.

EX. Above 18GHz, Aux Factor = 20 dB/decade of distance, the aux factor is $20\log(1/3) = -9.54\text{dB}$ (for 1m test distance).

7.4.1 E.U.T. Operation

Operating Environment:


Temperature: 23.5 °C Humidity: 56.3 % RH Atmospheric Pressure: 1020 mbar

7.4.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	02	TX mode(1Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	03	TX mode(2Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.



7.4.3 Test Setup Diagram



Above 1GHz



7.4.4 Measurement Procedure and Data


- a. For above 1GHz, the EUT was placed on the top of a rotating table 1.5m above the ground at a 3m fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. The EUT was set 3m away from the interference-receiving antenna from 1GHz to 18GHz, and 1m away from the interference-receiving antenna above 18GHz.
- b. The interference-receiving antenna was mounted on the variable-height antenna tower, with its boresight facing the EUT throughout the test.
- c. The antenna height is varied from 1m to 4m above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1m to 4m and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- g. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- h. Repeat above procedures until all frequencies measured was complete.

Remark:

1. Scan from 1GHz to 10th harmonic of the highest frequency or 40 GHz, whichever is lower.
2. As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.
3. For the frequency above 18GHz, testing had been executed under all test modes, only the worst-case test curve is displayed in the report.
4. For devices with multiple operating modes, measurements on the middle channel is used to determine the worst-case mode(s). Only the worst-case mode with the highest output power and the mode with the highest output power spectral density for each modulation family (e.g., OFDM and direct sequence spread spectrum) is recorded in the test report.




BLE_1M_TX_CH_00_Horizontal-Peak



Site : chamber
Condition: 3m HORIZONTAL
Job No : 00162AT\00163AT
Mode : 2402 TX RSE
BLE

Freq	Cable	Ant	Preamp	Read	Level	Limit	Over	Aux
MHz	Loss	Factor	Factor	Level	dBuV/m	dBuV/m	Limit	Factor
dB	dB/m	dB	dB	dBuV	dBuV/m	dBuV/m	dB	dB
1 4804.000	7.41	34.32	54.22	52.77	40.28	74.00	-33.72 Peak	0.00
2 6408.754	8.88	35.58	53.15	52.58	43.89	74.00	-30.11 Peak	0.00
3 7206.000	8.50	35.70	53.18	53.01	44.03	74.00	-29.97 Peak	0.00
4 9608.000	10.74	37.42	53.35	49.93	44.74	74.00	-29.26 Peak	0.00
5 13957.530	10.97	39.62	52.91	49.76	47.44	74.00	-26.56 Peak	0.00
6 p17844.590	11.41	43.90	52.48	48.74	51.57	74.00	-22.43 Peak	0.00


BLE_1M_TX_CH_00_Horizontal-Avg



Site : chamber
Condition: 3m HORIZONTAL
Job No : 00162AT\00163AT
Mode : 2402 TX RSE
BLE

Freq	Cable	Ant	Preamp	Read	Level	Limit	Over	Aux
MHz	Loss	Factor	Factor	Level	dBuV/m	dBuV/m	Limit	Factor
dB	dB/m	dB	dB	dBuV	dBuV/m	dBuV/m	dB	dB
1 4804.000	7.41	34.32	54.22	45.79	33.30	54.00	-20.70 Average	0.00
2 6071.417	8.92	35.04	53.11	45.94	36.79	54.00	-17.21 Average	0.00
3 7206.000	8.50	35.70	53.18	45.01	36.03	54.00	-17.97 Average	0.00
4 9608.000	10.74	37.42	53.35	44.15	38.96	54.00	-15.04 Average	0.00
5 13957.530	10.97	39.62	52.91	43.03	40.71	54.00	-13.29 Average	0.00
6 q17793.090	11.38	43.89	52.50	41.52	44.29	54.00	-9.71 Average	0.00


BLE_1M_TX_CH_00_Vertical-Peak



Site : chamber
Condition: 3m VERTICAL
Job No : 00162AT\00163AT
Mode : 2402 TX RSE
BLE

Freq	Cable	Ant	Preamp	Read	Level	Limit	Over	Aux
MHz	Loss	Factor	Factor	Level	dBuV/m	dBuV/m	Limit	Factor
dB	dB/m	dB	dB	dBuV	dBuV/m	dBuV/m	dB	dB
1 4804.000	7.41	34.32	54.22	53.21	40.72	74.00	-33.28 Peak	0.00
2 6995.172	8.56	35.71	53.20	53.54	44.61	74.00	-29.39 Peak	0.00
3 7206.000	8.50	35.70	53.18	53.23	44.25	74.00	-29.75 Peak	0.00
4 9608.000	10.74	37.42	53.35	50.13	44.94	74.00	-29.06 Peak	0.00
5 13957.530	10.97	39.62	52.91	49.93	47.61	74.00	-26.39 Peak	0.00
6 p17436.710	11.17	43.40	52.68	49.00	51.69	74.00	-22.31 Peak	0.00

BLE_1M_TX_CH_00_Vertical-Avg




Site : chamber
Condition: 3m VERTICAL
Job No : 00162AT\00163AT
Mode : 2402 TX RSE
BLE

Freq	Cable	Ant	Preamp	Read	Level	Limit	Over	Aux
MHz	Loss	Factor	Factor	Level	dBuV/m	dBuV/m	Limit	Factor
dB	dB/m	dB	dB	dBuV	dBuV/m	dBuV/m	dB	dB
1 4804.000	7.41	34.32	54.22	46.29	33.80	54.00	-20.20 Average	0.00
2 6088.991	8.92	35.06	53.11	46.15	37.04	54.00	-16.96 Average	0.00
3 7206.000	8.50	35.70	53.18	44.85	35.87	54.00	-18.13 Average	0.00
4 9608.000	10.74	37.42	53.35	44.37	39.18	54.00	-14.82 Average	0.00
5 13957.530	10.97	39.62	52.91	43.07	41.05	54.00	-12.95 Average	0.00
6 q17741.740	11.35	43.84	52.53	42.25	44.91	54.00	-9.09 Average	0.00




BLE_1M_TX_CH_19_Horizontal-Peak



Site : chamber
Condition: 3m HORIZONTAL
Job No : 00162AT\00163AT
Mode : 2440 TX RSE
BLE

Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark	Aux Factor
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1 4880.000	7.47	34.62	54.21	52.69	40.57	74.00	-33.43	Peak	0.00
2 6071.417	8.92	35.04	53.11	53.74	44.59	74.00	-29.41	Peak	0.00
3 7320.000	8.46	35.70	53.17	51.80	42.79	74.00	-31.21	Peak	0.00
4 9760.000	10.69	37.38	53.29	51.58	46.36	74.00	-27.64	Peak	0.00
5 13957.530	10.97	39.62	52.91	49.93	47.61	74.00	-26.39	Peak	0.00
6 p17690.530	11.32	43.78	52.55	49.66	52.21	74.00	-21.79	Peak	0.00


BLE_1M_TX_CH_19_Horizontal-Avg



Site : chamber
Condition: 3m HORIZONTAL
Job No : 00162AT\00163AT
Mode : 2440 TX RSE
BLE

Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark	Aux Factor
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1 4880.000	7.47	34.62	54.21	45.59	33.47	54.00	-20.53	Average	0.00
2 6088.991	8.92	35.08	53.11	45.00	35.89	54.00	-18.11	Average	0.00
3 7320.000	8.46	35.70	53.17	44.63	35.62	54.00	-18.38	Average	0.00
4 9760.000	10.69	37.38	53.29	44.98	39.76	54.00	-14.24	Average	0.00
5 13957.530	10.97	39.62	52.91	43.33	41.01	54.00	-12.99	Average	0.00
6 q17793.090	11.38	43.89	52.50	41.75	44.52	54.00	-9.48	Average	0.00


BLE_1M_TX_CH_19_Vertical-Peak



Site : chamber
Condition: 3m VERTICAL
Job No : 00162AT\00163AT
Mode : 2440 TX RSE
BLE

Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark	Aux Factor
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1 4880.000	7.47	34.62	54.21	51.60	39.48	74.00	-34.52	Peak	0.00
2 6322.136	8.90	34.96	53.13	53.28	44.01	74.00	-29.99	Peak	0.00
3 7320.000	8.46	35.70	53.17	52.17	43.16	74.00	-30.84	Peak	0.00
4 9760.000	10.69	37.38	53.29	50.53	45.31	74.00	-28.69	Peak	0.00
5 13957.530	10.97	39.62	52.91	50.83	48.51	74.00	-25.49	Peak	0.00
6 p17793.090	11.38	43.89	52.50	49.48	52.25	74.00	-21.75	Peak	0.00

BLE_1M_TX_CH_19_Vertical-Avg




Site : chamber
Condition: 3m VERTICAL
Job No : 00162AT\00163AT
Mode : 2440 TX RSE
BLE

Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark	Aux Factor
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1 4880.000	7.47	34.62	54.21	45.43	33.31	54.00	-20.69	Average	0.00
2 5932.638	8.83	34.67	53.17	46.49	36.82	54.00	-17.18	Average	0.00
3 7320.000	8.46	35.70	53.17	44.76	35.75	54.00	-18.25	Average	0.00
4 9760.000	10.69	37.38	53.29	43.86	38.64	54.00	-15.36	Average	0.00
5 13957.530	10.97	39.62	52.91	43.76	41.44	54.00	-12.56	Average	0.00
6 q17793.090	11.38	43.89	52.50	41.60	44.37	54.00	-9.63	Average	0.00




BLE_1M_TX_CH_39_Horizontal-Peak



Site : chamber
Condition: 3m HORIZONTAL
Job No : 00162AT\00163AT
Mode : 2480 TX RSE
BLE

Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark	Aux Factor
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1 4960.000	7.53	34.56	54.20	52.36	40.25	74.00	-33.75	Peak	0.00
2 5949.811	8.86	34.70	53.15	54.41	44.82	74.00	-29.18	Peak	0.00
3 7440.000	8.43	35.96	53.15	53.51	44.75	74.00	-29.25	Peak	0.00
4 9920.000	10.64	37.30	53.23	52.58	47.29	74.00	-26.71	Peak	0.00
5 13957.530	10.97	39.62	52.91	50.18	47.86	74.00	-26.14	Peak	0.00
6 p17690.530	11.32	43.78	52.55	49.13	51.68	74.00	-22.32	Peak	0.00


BLE_1M_TX_CH_39_Horizontal-Avg



Site : chamber
Condition: 3m HORIZONTAL
Job No : 00162AT\00163AT
Mode : 2480 TX RSE
BLE

Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark	Aux Factor
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1 4960.000	7.53	34.56	54.20	45.32	33.21	54.00	-20.79	Average	0.00
2 6756.708	8.71	35.21	53.18	45.45	36.19	54.00	-17.81	Average	0.00
3 7440.000	8.43	35.96	53.15	45.79	37.03	54.00	-16.97	Average	0.00
4 9920.000	10.64	37.30	53.23	43.98	38.69	54.00	-15.31	Average	0.00
5 13957.530	10.97	39.62	52.91	43.01	40.69	54.00	-13.31	Average	0.00
6 q17793.890	11.38	43.89	52.50	41.76	44.53	54.00	-9.47	Average	0.00


BLE_1M_TX_CH_39_Vertical-Peak



Site : chamber
Condition: 3m VERTICAL
Job No : 00162AT\00163AT
Mode : 2480 TX RSE
BLE

Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark	Aux Factor
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1 4960.000	7.53	34.56	54.20	52.70	40.59	74.00	-33.41	Peak	0.00
2 6071.417	8.92	35.04	53.11	53.08	43.93	74.00	-30.07	Peak	0.00
3 7440.000	8.43	35.96	53.15	53.46	44.70	74.00	-29.30	Peak	0.00
4 9920.000	10.64	37.30	53.23	52.00	46.71	74.00	-27.29	Peak	0.00
5 13957.530	10.97	39.62	52.91	50.29	47.97	74.00	-26.03	Peak	0.00
6 p17588.560	11.25	43.58	52.60	49.66	51.89	74.00	-22.11	Peak	0.00

BLE_1M_TX_CH_39_Vertical-Avg




Site : chamber
Condition: 3m VERTICAL
Job No : 00162AT\00163AT
Mode : 2480 TX RSE
BLE

Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark	Aux Factor
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1 4960.000	7.53	34.56	54.20	45.50	33.39	54.00	-20.61	Average	0.00
2 5967.033	8.88	34.77	53.13	46.38	36.90	54.00	-17.10	Average	0.00
3 7440.000	8.43	35.96	53.15	47.26	38.50	54.00	-15.50	Average	0.00
4 9920.000	10.64	37.30	53.23	43.74	38.45	54.00	-15.55	Average	0.00
5 13957.530	10.97	39.62	52.91	43.10	40.78	54.00	-13.22	Average	0.00
6 q17741.740	11.35	43.84	52.53	42.15	44.81	54.00	-9.19	Average	0.00




BLE_2M_TX_CH_00_Horizontal-Peak



Site : chamber
Condition: 3m HORIZONTAL
Job No : 00162AT\00163AT
Mode : 2402 TX RSE
BLE

Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark	Aux Factor
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1 4804.000	7.41	34.32	54.22	52.10	39.61	74.00	-34.39	Peak	0.00
2 6602.265	8.81	35.30	53.16	53.38	44.33	74.00	-29.67	Peak	0.00
3 7206.000	8.50	35.70	53.18	52.66	43.68	74.00	-30.32	Peak	0.00
4 9608.000	10.74	37.42	53.35	50.10	44.91	74.00	-29.09	Peak	0.00
5 13957.530	10.97	39.62	52.91	51.51	49.19	74.00	-24.81	Peak	0.00
6 p17639.470	11.28	43.68	52.58	48.81	51.19	74.00	-22.81	Peak	0.00


BLE_2M_TX_CH_00_Horizontal-Avg



Site : chamber
Condition: 3m HORIZONTAL
Job No : 00162AT\00163AT
Mode : 2402 TX RSE
BLE

Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark	Aux Factor
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1 4804.000	7.41	34.32	54.22	45.61	33.12	54.00	-20.88	Average	0.00
2 5949.811	8.86	34.70	53.15	45.95	36.36	54.00	-17.64	Average	0.00
3 7206.000	8.50	35.70	53.18	44.95	35.97	54.00	-18.03	Average	0.00
4 9608.000	10.74	37.42	53.35	43.29	38.10	54.00	-15.90	Average	0.00
5 13957.530	10.97	39.62	52.91	43.27	40.95	54.00	-13.05	Average	0.00
6 q17793.090	11.38	43.89	52.50	41.29	44.06	54.00	-9.94	Average	0.00


BLE_2M_TX_CH_00_Vertical-Peak



Site : chamber
Condition: 3m VERTICAL
Job No : 00162AT\00163AT
Mode : 2402 TX RSE
BLE

Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark	Aux Factor
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1 4804.000	7.41	34.32	54.22	53.55	41.06	74.00	-32.94	Peak	0.00
2 6855.063	8.65	35.51	53.19	52.89	43.86	74.00	-30.14	Peak	0.00
3 7206.000	8.50	35.70	53.18	51.84	42.86	74.00	-31.14	Peak	0.00
4 9608.000	10.74	37.42	53.35	50.24	45.05	74.00	-28.95	Peak	0.00
5 13957.530	10.97	39.62	52.91	49.85	47.53	74.00	-26.47	Peak	0.00
6 p17793.090	11.38	43.89	52.50	49.06	51.83	74.00	-22.17	Peak	0.00

BLE_2M_TX_CH_00_Vertical-Avg




Site : chamber
Condition: 3m VERTICAL
Job No : 00162AT\00163AT
Mode : 2402 TX RSE
BLE

Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark	Aux Factor
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1 4804.000	7.41	34.32	54.22	46.61	34.12	54.00	-19.88	Average	0.00
2 6995.172	8.56	35.71	53.20	44.99	36.06	54.00	-17.94	Average	0.00
3 7206.000	8.50	35.70	53.18	45.03	36.05	54.00	-17.95	Average	0.00
4 9608.000	10.74	37.42	53.35	42.73	37.54	54.00	-16.46	Average	0.00
5 13957.530	10.97	39.62	52.91	44.33	42.01	54.00	-11.99	Average	0.00
6 q17741.740	11.35	43.84	52.53	41.72	44.38	54.00	-9.62	Average	0.00




BLE_2M_TX_CH_19_Horizontal-Peak



Site : chamber
Condition: 3m HORIZONTAL
Job No : 00162AT\00163AT
Mode : 2440 TX RSE
BLE

Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark	Aux Factor
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1 4880.000	7.47	34.62	54.21	53.50	41.38	74.00	-32.62	Peak	0.00
2 6106.616	8.92	35.07	53.11	53.64	44.52	74.00	-29.48	Peak	0.00
3 7320.000	8.46	35.70	53.17	51.80	42.79	74.00	-31.21	Peak	0.00
4 9760.000	10.69	37.38	53.29	51.33	46.11	74.00	-27.89	Peak	0.00
5 13957.530	10.97	39.62	52.91	50.21	47.89	74.00	-26.11	Peak	0.00
6 p17793.090	11.38	43.89	52.50	48.73	51.50	74.00	-22.50	Peak	0.00


BLE_2M_TX_CH_19_Horizontal-Avg



Site : chamber
Condition: 3m HORIZONTAL
Job No : 00162AT\00163AT
Mode : 2440 TX RSE
BLE

Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark	Aux Factor
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1 4880.000	7.47	34.62	54.21	45.57	33.45	54.00	-20.55	Average	0.00
2 6106.616	8.92	35.07	53.11	45.49	36.37	54.00	-17.63	Average	0.00
3 7320.000	8.46	35.70	53.17	44.59	35.58	54.00	-18.42	Average	0.00
4 9760.000	10.69	37.38	53.29	45.54	40.32	54.00	-13.68	Average	0.00
5 13957.530	10.97	39.62	52.91	43.42	41.10	54.00	-12.90	Average	0.00
6 q17436.710	11.17	43.40	52.68	42.75	44.64	54.00	-9.36	Average	0.00


BLE_2M_TX_CH_19_Vertical-Peak



Site : chamber
Condition: 3m VERTICAL
Job No : 00162AT\00163AT
Mode : 2440 TX RSE
BLE

Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark	Aux Factor
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1 4880.000	7.47	34.62	54.21	52.99	40.87	74.00	-33.13	Peak	0.00
2 5932.638	8.83	34.67	53.17	52.98	43.31	74.00	-30.69	Peak	0.00
3 7320.000	8.46	35.70	53.17	52.27	43.26	74.00	-30.74	Peak	0.00
4 9760.000	10.69	37.38	53.29	50.88	45.66	74.00	-28.34	Peak	0.00
5 13957.530	10.97	39.62	52.91	51.17	48.85	74.00	-25.15	Peak	0.00
6 p17844.590	11.41	43.90	52.48	49.35	52.18	74.00	-21.82	Peak	0.00

BLE_2M_TX_CH_19_Vertical-Avg




Site : chamber
Condition: 3m VERTICAL
Job No : 00162AT\00163AT
Mode : 2440 TX RSE
BLE

Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark	Aux Factor
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1 4880.000	7.47	34.62	54.21	46.44	34.32	54.00	-19.68	Average	0.00
2 6414.167	8.89	35.29	53.14	45.44	36.48	54.00	-17.52	Average	0.00
3 7320.000	8.46	35.70	53.17	45.62	36.61	54.00	-17.39	Average	0.00
4 9760.000	10.69	37.38	53.29	44.38	39.16	54.00	-14.84	Average	0.00
5 13957.530	10.97	39.62	52.91	43.19	40.87	54.00	-13.13	Average	0.00
6 q17844.590	11.41	43.90	52.48	42.33	45.16	54.00	-8.84	Average	0.00




BLE_2M_TX_CH_39_Horizontal-Peak



Site : chamber
Condition: 3m HORIZONTAL
Job No : 00162AT\00163AT
Mode : 2480 TX RSE
BLE

Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark	Aux Factor
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1 4960.000	7.53	34.56	54.20	52.44	40.33	74.00	-33.67	Peak	0.00
2 6071.417	8.92	35.04	53.11	52.96	43.81	74.00	-30.19	Peak	0.00
3 7440.000	8.43	35.96	53.15	53.48	44.72	74.00	-29.28	Peak	0.00
4 9920.000	10.64	37.30	53.23	50.38	45.09	74.00	-28.91	Peak	0.00
5 13957.530	10.97	39.62	52.91	50.40	48.00	74.00	-25.92	Peak	0.00
6 p17386.380	11.15	43.36	52.70	50.13	51.94	74.00	-22.06	Peak	0.00


BLE_2M_TX_CH_39_Horizontal-Avg



Site : chamber
Condition: 3m HORIZONTAL
Job No : 00162AT\00163AT
Mode : 2480 TX RSE
BLE

Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark	Aux Factor
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1 4960.000	7.53	34.56	54.20	46.08	33.97	54.00	-20.03	Average	0.00
2 6470.026	8.88	35.54	53.15	45.18	36.45	54.00	-17.55	Average	0.00
3 7440.000	8.43	35.96	53.15	45.94	37.18	54.00	-16.82	Average	0.00
4 9920.000	10.64	37.30	53.23	45.12	39.83	54.00	-14.17	Average	0.00
5 13957.530	10.97	39.62	52.91	43.04	40.72	54.00	-13.28	Average	0.00
6 q17487.180	11.19	43.40	52.65	42.43	44.37	54.00	-9.63	Average	0.00


BLE_2M_TX_CH_39_Vertical-Peak



Site : chamber
Condition: 3m VERTICAL
Job No : 00162AT\00163AT
Mode : 2480 TX RSE
BLE

Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark	Aux Factor
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1 4960.000	7.53	34.56	54.20	52.34	40.23	74.00	-33.77	Peak	0.00
2 6195.508	8.91	34.72	53.12	53.28	43.79	74.00	-30.21	Peak	0.00
3 7440.000	8.43	35.96	53.15	53.72	44.96	74.00	-29.04	Peak	0.00
4 9920.000	10.64	37.30	53.23	51.06	46.57	74.00	-27.43	Peak	0.00
5 13957.530	10.97	39.62	52.91	50.34	48.02	74.00	-25.98	Peak	0.00
6 p17639.470	11.28	43.68	52.58	50.04	52.42	74.00	-21.58	Peak	0.00

BLE_2M_TX_CH_39_Vertical-Avg



Site : chamber
Condition: 3m VERTICAL
Job No : 00162AT\00163AT
Mode : 2480 TX RSE
BLE

Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark	Aux Factor
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1 4960.000	7.53	34.56	54.20	45.28	33.17	54.00	-20.83	Average	0.00
2 6995.172	8.56	35.71	53.20	45.76	36.83	54.00	-17.17	Average	0.00
3 7440.000	8.43	35.96	53.15	45.74	36.98	54.00	-17.02	Average	0.00
4 9920.000	10.64	37.30	53.23	44.73	39.44	54.00	-14.56	Average	0.00
5 13957.530	10.97	39.62	52.91	43.45	41.13	54.00	-12.87	Average	0.00
6 q17639.470	11.28	43.68	52.58	42.17	44.55	54.00	-9.45	Average	0.00



7.5 Conducted Peak Output Power

Test Requirement 47 CFR Part 15, Subpart C 15.247(b)(3)

Test Method: ANSI C63.10 (2020) Section 11.9.1

Test Engineer: Linvo Ding

Limit:

Frequency range(MHz)	Output power of the intentional radiator(watt)
902-928	1 for ≥ 50 hopping channels
	0.25 for $25 \leq$ hopping channels < 50
	1 for digital modulation
2400-2483.5	1 for ≥ 75 non-overlapping hopping channels
	0.125 for all other frequency hopping systems
	1 for digital modulation
5725-5850	1 for frequency hopping systems and digital modulation

7.5.1 E.U.T. Operation

Operating Environment:


Temperature: 24.0 °C Humidity: 47.7 % RH Atmospheric Pressure: 1020 mbar

7.5.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	02	TX mode(1Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	03	TX mode(2Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.



7.5.3 Test Setup Diagram



7.5.4 Measurement Procedure and Data

Note: Since the verify power the same operating range bandwidth and smaller power can be covered by the higher power.

Please Refer to Appendix for Details



7.6 Minimum 6dB Bandwidth

Test Requirement 47 CFR Part 15, Subpart C 15.247a(2)

Test Method: ANSI C63.10 (2020) Section 11.8.1

Test Engineer: Linvo Ding

Limit:

≥500 kHz

7.6.1 E.U.T. Operation

Operating Environment:

Temperature: 24.0 °C


Humidity: 47.7 % RH

Atmospheric Pressure: 1020 mbar

7.6.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	02	TX mode(1Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	03	TX mode(2Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.

7.6.3 Test Setup Diagram



7.6.4 Measurement Procedure and Data

Please Refer to Appendix for Details

7.7 Power Spectrum Density

Test Requirement 47 CFR Part 15, Subpart C 15.247(e)

Test Method: ANSI C63.10 (2020) Section 11.10.2

Test Engineer: Linvo Ding

Limit:

≤8dBm in any 3 kHz band during any time interval of continuous transmission

7.7.1 E.U.T. Operation

Operating Environment:

Temperature: 24.0 °C


Humidity: 47.7 % RH

Atmospheric Pressure: 1020 mbar

7.7.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	02	TX mode(1Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	03	TX mode(2Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.

7.7.3 Test Setup Diagram



7.7.4 Measurement Procedure and Data

Please Refer to Appendix for Details

7.8 Conducted Band Edges Measurement

Test Requirement 47 CFR Part 15, Subpart C 15.247(d)
 Test Method: ANSI C63.10 (2020) Section 6.10.4
 Test Engineer: Linvo Ding

Limit:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

7.8.1 E.U.T. Operation

Operating Environment:


Temperature: 24.0 °C Humidity: 47.7 % RH Atmospheric Pressure: 1020 mbar

7.8.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	02	TX mode(1Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	03	TX mode(2Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.



7.8.3 Test Setup Diagram



7.8.4 Measurement Procedure and Data

Please Refer to Appendix for Details

7.9 Conducted Spurious Emissions

Test Requirement 47 CFR Part 15, Subpart C 15.247(d)

Test Method: ANSI C63.10 (2020) Section 11.11

Test Engineer: Linvo Ding

Limit:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

7.9.1 E.U.T. Operation

Operating Environment:

Temperature: 24.0 °C

Humidity: 47.7 % RH


Atmospheric Pressure: 1020 mbar

7.9.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	02	TX mode(1Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	03	TX mode(2Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.



7.9.3 Test Setup Diagram



7.9.4 Measurement Procedure and Data

Please Refer to Appendix for Details

8 Test Setup Photo

Refer to Appendix - Test Setup Photo for SZCR2601000162AT

9 EUT Constructional Details (EUT Photos)

Refer to External and Internal Photos for SZCR2601000162AT

10 Appendix

1. Duty Cycle


1.1 Test Result

1.1.1 Ant1


Ant1							
Mode	TX Type	Frequency (MHz)	T_on (ms)	Period (ms)	Duty Cycle (%)	Duty Cycle Correction Factor (dB)	Max. DC Variation (%)
1M	SISO	2402	0.379	0.625	60.64	2.17	0.03
		2440	0.380	0.625	60.80	2.16	0.00
		2480	0.380	0.625	60.80	2.16	0.00
2M	SISO	2402	0.195	0.625	31.20	5.06	0.03
		2440	0.196	0.625	31.36	5.04	0.00
		2480	0.196	0.625	31.36	5.04	0.00

1.2 Test Graph


1.2.1 Ant1




1M_HCH_2480MHz_Ant1_NTNV




2M_LCH_2402MHz_Ant1_NTNV



2M_MCH_2440MHz_Ant1_NTNV



2M_HCH_2480MHz_Ant1_NTNV



2. Bandwidth

2.1 Test Result

2.1.1 OBW

Mode	TX Type	Frequency (MHz)	ANT	99% Occupied Bandwidth (MHz)		Verdict
				Result	Limit	
1M	SISO	2402	1	1.046	/	Pass
		2440	1	1.045	/	Pass
		2480	1	1.046	/	Pass
2M	SISO	2402	1	2.085	/	Pass
		2440	1	2.084	/	Pass
		2480	1	2.084	/	Pass


2.1.2 6dB BW

Mode	TX Type	Frequency (MHz)	ANT	6dB Bandwidth (MHz)		Verdict
				Result	Limit	
1M	SISO	2402	1	0.711	≥ 0.5	Pass
		2440	1	0.710	≥ 0.5	Pass
		2480	1	0.710	≥ 0.5	Pass
2M	SISO	2402	1	1.244	≥ 0.5	Pass
		2440	1	1.249	≥ 0.5	Pass
		2480	1	1.251	≥ 0.5	Pass



2.2 Test Graph

2.2.1 OBW




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com


SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch (Shenzhen EMC Laboratory)

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com


1M_HCH_2480MHz_Ant1_NTNV




2M_LCH_2402MHz_Ant1_NTNV




2M_MCH_2440MHz_Ant1_NTNV




2M_HCH_2480MHz_Ant1_NTNV




2.2.2 6dB BW




1M_HCH_2480MHz_Ant1_NTNV




2M_LCH_2402MHz_Ant1_NTNV



2M_MCH_2440MHz_Ant1_NTNV



2M_HCH_2480MHz_Ant1_NTNV



3. Maximum Conducted Output Power

3.1 Test Result

3.1.1 Power

Mode	TX Type	Frequency (MHz)	Maximum Peak Conducted Output Power (dBm)		Verdict
			ANT1	Limit	
1M	SISO	2402	7.19	<=30	Pass
		2440	7.05	<=30	Pass
		2480	7.10	<=30	Pass
2M	SISO	2402	7.17	<=30	Pass
		2440	7.03	<=30	Pass
		2480	7.07	<=30	Pass

Note1: Antenna Gain: Ant1: 2.77dBi;

4. Maximum Power Spectral Density

4.1 Test Result


4.1.1 PSD

Mode	TX Type	Frequency (MHz)	Maximum PSD (dBm)		Verdict
			ANT1	Limit	
1M	SISO	2402	6.41	<=8	Pass
		2440	6.26	<=8	Pass
		2480	6.30	<=8	Pass
2M	SISO	2402	5.98	<=8	Pass
		2440	5.80	<=8	Pass
		2480	5.87	<=8	Pass

Note1: Antenna Gain: Ant1: 2.77dBi;

4.2 Test Graph


4.2.1 PSD




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com


1M_HCH_2480MHz_Ant1_NTNV




2M_LCH_2402MHz_Ant1_NTNV



2M_MCH_2440MHz_Ant1_NTNV



2M_HCH_2480MHz_Ant1_NTNV



5. Unwanted Emissions In Non-restricted Frequency Bands

5.1 Test Result

5.1.1 Ref

Mode	TX Type	Frequency (MHz)	ANT	Level of Reference (dBm)
1M	SISO	2402	1	6.42
		2440	1	6.26
		2480	1	6.30
2M	SISO	2402	1	5.97
		2440	1	5.84
		2480	1	5.87

Note1: Refer to FCC Part 15.247 (d) and ANSI C63.10-2020, the channel contains the maximum PSD level was used to establish the reference level.


5.1.2 CSE

Mode	TX Type	Frequency (MHz)	ANT	Level of Reference (dBm)	Limit (dBm)	Verdict
1M	SISO	2402	1	6.42	-13.58	Pass
		2440	1	6.42	-13.58	Pass
		2480	1	6.42	-13.58	Pass
2M	SISO	2402	1	5.97	-14.03	Pass
		2440	1	5.97	-14.03	Pass
		2480	1	5.97	-14.03	Pass


Note1: Refer to FCC Part 15.247 (d) and ANSI C63.10-2020, the channel contains the maximum PSD level was used to establish the reference level.

5.2 Test Graph


5.2.1 Ref




1M_HCH_2480MHz_Ant1_NTNV




2M_LCH_2402MHz_Ant1_NTNV




2M_MCH_2440MHz_Ant1_NTNV




2M_HCH_2480MHz_Ant1_NTNV




5.2.2 CSE




1M_MCH_2440MHz_Ant1_NTNV




1M_HCH_2480MHz_Ant1_NTNV




1M_HCH_2480MHz_Ant1_NTNV




2M_LCH_2402MHz_Ant1_NTNV




2M_LCH_2402MHz_Ant1_NTNV




2M_MCH_2440MHz_Ant1_NTNV



2M_HCH_2480MHz_Ant1_NTNV



2M_HCH_2480MHz_Ant1_NTNV



- End of the Report -

