



Compliance Testing, LLC

Previously Flom Test Lab

EMI, EMC, RF Testing Experts Since 1963

toll-free: (866) 311-3268

fax: (480) 926-3598

<http://www.ComplianceTesting.com>

info@ComplianceTesting.com

Test Report

Prepared for: SecureALL Coporation

Model: SA-ODL

Description: Electronic door reader/lock

Serial Number: 00002

FCC ID: Y29-SA-ODL

To

FCC Part 1.1310

Date of Issue: May 4, 2020

On the behalf of the applicant:

**SecureALL Coporation
900 Lafayette St Suite 202
Santa Clara, CA 95050**

Attention of:

**Arun Sharma,
Ph: (408)246-6227
Email: arun.sharma@secureallcorp.com**

**Prepared By
Compliance Testing, LLC
1724 S. Nevada Way
Mesa, AZ 85204
(480) 926-3100 phone / (480) 926-3598 fax
www.compliancetesting.com
Project No: p2030012**

**Poona Saber
Project Test Engineer**

This report may not be reproduced, except in full, without written permission from Compliance Testing
All results contained herein relate only to the sample tested



Test Report Revision History

Revision	Date	Revised By	Reason for Revision
1.0	May 4, 2020	Poona Saber	Original Document



ILAC / A2LA

Compliance Testing, LLC, has been accredited in accordance with the recognized International Standard ISO/IEC 17025:2005. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer joint ISO-ILAC-IAF Communiqué dated January 2009)

The tests results contained within this test report all fall within our scope of accreditation, unless below

Please refer to <http://www.compliancetesting.com/labscope.html> for current scope of accreditation.

Testing Certificate Number: **2152.01**



FCC Site Reg. #349717

IC Site Reg. #2044A-2

Non-accredited tests contained in this report:

N/A

EUT Description

Model: SA-ODL

Description: Electronic door reader/lock

Serial Number: 00002

Additional Information: SA-ODL is a battery-operated device wireless lock t, using 4 AA dry cells. The device communicates with a router device on a 2.4 GHz ISM band with operating frequency range of 2400-2480 MHz.

Its transceiver employs DSSS communication and at any given time radio connects to one of the following two antennas that it utilizes:

- 1- Outside Antenna which is a vertically polarized array antenna with +3.5 dBi gain
- 2- Inside Antenna which is a vertically polarized cavity backed slot antenna with 2 dBi gain



MPE Evaluation

This is a Fixed device used in Uncontrolled Exposure environment.

Limits Controlled Exposure 47 CFR 1.1310 Table 1, (A)

0.3-3.0 MHz:	Limit [mW/cm ²] = 100
3.0-30 MHz:	Limit [mW/cm ²] = (900/f ²)
30-300 MHz:	Limit [mW/cm ²] = 1.0
300-1500 MHz:	Limit [mW/cm ²] = f/300
1500-100,000 MHz	Limit [mW/cm ²] = 5

Limits Uncontrolled Exposure 47 CFR 1.1310 Table 1, (B)

0.3-1.234 MHz:	Limit [mW/cm ²] = 100
1.34-30 MHz:	Limit [mW/cm ²] = (180/f ²)
30-300 MHz:	Limit [mW/cm ²] = 0.2
300-1500 MHz:	Limit [mW/cm ²] = f/1500
1500-100,000 MHz	Limit [mW/cm ²] = 1.0

Test Data

Test Frequency, MHz	2405
Power, Conducted, mW (P)	3.58
Antenna Gain Isotropic	3.5 dBi
Antenna Gain Numeric (G)	2.23
Antenna Type	Array antenna
Distance (R)	20 cm

$S = \frac{P * G}{4\pi r^2}$
Power Density (S) mw/cm ²

Power Density (S) = 0.00158
Limit = (from above table) = 1

The device is compliant with the requirement MPE limit for uncontrolled exposure.

END OF TEST REPORT