



Shenzhen Huatongwei International Inspection Co., Ltd.

Keji S, 12th, Road, Hi-tech Industrial Park, Shenzhen, Guangdong, China

Phone: 86-755-26748099

Fax: 86-755-26748089

http://www.szhtw.com.cn



FCC PART 22/24 TEST REPORT

FCC Part 22 /Part 24

Report Reference No. : TRE1309000501 R/C: 18013

FCC ID. : Y2L00004

Compiled by

(position+printed name+signature)... : File administrators Jerome Luo

Supervised by

(position+printed name+signature)... : Test Engineer Yuchao Wang

Approved by

(position+printed name+signature)... : Manager Wenliang Li

Date of issue. : Oct 14, 2013

Testing Laboratory Name : Shenzhen Huatongwei International Inspection Co., Ltd

Address. : Keji Nan No.12 Road, Hi-tech Park, Shenzhen, China

Applicant's name : Boly Media Communications (Asia) Co., Ltd.

Address. : WORKSHOP B9,6/F,BLOCK B,CAMBRIDGE PLAZA NO.188 SAN WAN ROAD, SHEUNG SHUI,N.T.,HONG KONG

Test specification :

Standard :

FCC Part 22: PUBLIC MOBILE SERVICES

FCC Part 24: PERSONAL COMMUNICATIONS SERVICES

TRF Originator : Shenzhen Huatongwei International Inspection CO., Ltd

Master TRF : Dated 2006-06

Shenzhen Huatongwei International Inspection Co., Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Huatongwei International Inspection Co., Ltd is acknowledged as copyright owner and source of the material. Shenzhen Huatongwei International Inspection Co., Ltd takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test item description : MMS/GPRS Security Camera

Trade Mark : BOLYGUARD/SCOUTGUARD

Manufacturer : Boly Media Communications (shenzhen) Co., Ltd.

Model/Type reference : BG500L

Listed Models : BG500K/BG500L-HD/BG500K-HD

Ratings : DC 5.00V Adapter from AC120V/60Hz

Modulation : GMSK for GSM/EDGE

GPRS/ EGPRS Class : 12

GPRS operation mode : Class B

Frequency : GSM 850/PCS1900

Result : **Positive**

TEST REPORT

Test Report No. : TRE1309000501	Oct 14, 2013
	Date of issue

Equipment under Test : MMS/GPRS Security Camera

Model /Type : BG500L

Listed Models : BG500K/BG500L-HD/BG500K-HD

Applicant : **Boly Media Communications (Asia) Co., Ltd.**

Address : WORKSHOP B9,6/F,BLOCK B,CAMBRIDGE PLAZA
NO.188 SAN WAN ROAD, SHEUNG SHUI,N.T.,HONG
KONG

Manufacturer : **Boly Media Communications (shenzhen) Co., Ltd.**

Address : 2F,Shanshui Building B,Yungu Innovation Industrial
park,NO.1183,Liuxian Blvd, Nanshan
District,Shenzhen..Guangdong,China

Test Result according to the standards on page 4:	Positive
--	-----------------

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

Contents

<u>1.</u>	<u>TEST STANDARDS</u>	<u>4</u>
<u>2.</u>	<u>SUMMARY</u>	<u>5</u>
2.1.	General Remarks	5
2.2.	Product Description	5
2.3.	Equipment under Test	5
2.4.	Short description of the Equipment under Test (EUT)	5
2.5.	EUT Configuration	6
2.6.	EUT operation mode	6
2.7.	EUT configuration	6
2.8.	Related Submittal(s) / Grant (s)	6
2.9.	Modifications	6
2.10.	Note	6
<u>3.</u>	<u>TEST ENVIRONMENT</u>	<u>7</u>
3.1.	Address of the test laboratory	7
3.2.	Test Facility	7
3.3.	Environmental conditions	8
3.4.	Configuration of Tested System	8
3.5.	Statement of the measurement uncertainty	8
3.6.	Test Description	9
3.7.	Equipments Used during the Test	9
<u>4.</u>	<u>TEST CONDITIONS AND RESULTS</u>	<u>11</u>
4.1.	Conducted Emissions Test (Not Applicable)	11
4.2.	OUTPUT POWER	15
4.3.	Transmitter Radiated Spurious Emssion	19
4.4.	OCCUPIED BANDWIDTH	23
4.5.	EMISSION BANDWIDTH	31
4.6.	BAND EDGE COMPLIANCE	39
4.7.	Spurious Emssion on Antenna Port	45
4.8.	Frequency Stability Test	68
<u>5.</u>	<u>TEST SETUP PHOTOS OF THE EUT</u>	<u>70</u>
<u>6.</u>	<u>EXTERNAL AND INTERNAL PHOTOS OF THE EUT</u>	<u>72</u>

1. TEST STANDARDS

The tests were performed according to following standards:

[FCC Part 22 \(10-1-12 Edition\)](#): PRIVATE LAND MOBILE RADIO SERVICES.

[FCC Part 24\(10-1-12 Edition\)](#): PUBLIC MOBILE SERVICES

[TIA/EIA 603 D June 2010](#): Land Mobile FM or PM Communications Equipment Measurement and Performance Standards.

[47 CFR FCC Part 15 Subpart B](#): - Unintentional Radiators

[FCC Part 2](#): FREQUENCY ALLOCA-TIONS AND RADIO TREATY MAT-TERS; GENERAL RULES AND REG-ULATIONS

[KDB971168 D01:2011](#) Procedures for Compliance Measurement of the Fundamental Emission Power of Licensed Wideband (> 1 MHz) Digital Transmission Systems

[ANSI C63.4:2009](#) Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz

2. SUMMARY

2.1. General Remarks

Date of receipt of test sample	:	Sep 01, 2013
Testing commenced on	:	Sep 01, 2013
Testing concluded on	:	Oct 14, 2013

2.2. Product Description

The **Boly Media Communications (Shenzhen) Co., Ltd.**'s Model: BG500L or the "EUT" as referred to in this report; more general information as follows, for more details, refer to the user's manual of the EUT.

Name of EUT	MMS/GPRS Security Camera
Model Number	BG500L/ BG500K/BG500L-HD/BG500K-HD
FCC ID	Y2L00004
Modulation Type	GFSK for GPRS/EDGE
Antenna Type	External
GSM/EDGE/GPRS	Supported GPRS and EGPRS
Extreme temp. Tolerance	-30°C to +60°C
Extreme vol. Limits	4.25VDC to 5.75VDC (nominal: 5.00VDC)
GSM/GPRS Operation Frequency Band	GSM 850/ PCS 1900
GSM Release Version	R99
GPRS operation mode	Class B
GPRS Multislot Class	12
EGPRS Multislot Class	12

2.3. Equipment under Test

Power supply system utilised

Power supply voltage	:	☐ 120V / 60 Hz	☐ 115V / 60Hz
		☐ 12 V DC	☐ 24 V DC
		☒ Other (specified in blank below)	

DC 5.00V Adapter from AC120V/60Hz

Test frequency list

Modulation Type	Test Channel	Channel Number	Test Frequency
GPRS850/EDGE850	Low	128	824.20 MHz
	Middle	188	836.60 MHz
	High	251	848.80 MHz
GPRS1900/EDGE1900	Low	512	1850.20 MHz
	Middle	661	1880.00 MHz
	High	810	1909.80 MHz

2.4. Short description of the Equipment under Test (EUT)

The Equipment Under Test (EUT) is a MMS/GPRS Security Camera with GPRS/EGPRS and 433.92MHz receiver function and integrated antenna. Manual and specifications of the EUT were provided to fulfil the test. Samples undergoing test were selected by the Client.

2.5. EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commission's requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

2.6. EUT operation mode

The EUT has been tested under typical operating condition and The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

2.7. EUT configuration

The following peripheral devices and interface cables were connected during the measurement:

● - supplied by the manufacturer

○ - supplied by the lab

○	Power Cable	Length (m) :	/
		Shield :	/
		Detachable :	/
○	Multimeter	Manufacturer :	/
		Model No. :	/

2.8. Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended for **FCC ID:Y2L00004** filing to comply with FCC Part 22H and FCC Part 24E Rules

2.9. Modifications

No modifications were implemented to meet testing criteria.

2.10. Note

- The EUT is a MMS/GPRS Security Camera with GPRS/EDGE and 433.92MHz receiver function, The functions of the EUT listed as below:

	Test Standards	Reference Report
GPRS/EDGE	FCC Part 22/FCC Part 24	TRE1309000501
433.92MHz Receiver	FCC Part 15B	TRE1309000502
USB	FCC Part 15B	TRE1309000503
MPE	FCC Part 2.1091(d)	TRE1309000504

3. TEST ENVIRONMENT

3.1. Address of the test laboratory

Shenzhen Huatongwei International Inspection Co., Ltd
Keji Nan No.12 Road, Hi-tech Park, Shenzhen, China
Phone: 86-755-26715686 Fax: 86-755-26748089

The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.4 (2009) and CISPR Publication 22.

3.2. Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

CNAS-Lab Code: L1225

Shenzhen Huatongwei International Inspection Co., Ltd has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC 17025: 2005 General Requirements) for the Competence of Testing and Calibration Laboratories, Date of Registration: Mar 01, 2012. Valid time is until Feb 28, 2015.

A2LA-Lab Cert. No. 2243.01

Shenzhen Huatongwei International Inspection Co., Ltd, EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing. Valid time is until Sept 30, 2015.

FCC-Registration No.: 662850

Shenzhen Huatongwei International Inspection Co., Ltd, EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files. Registration 662850, Renewal date June 01, 2015.

IC-Registration No.: 5377

The 3m Alternate Test Site of Shenzhen Huatongwei International Inspection Co., Ltd has been registered by Certification and Engineering Bureau of Industry Canada for the performance of radiated measurements with Registration No. 5377 on Jan 25, 2011. Valid time is until Jan 24, 2014

ACA

Shenzhen Huatongwei International Inspection Co., Ltd, EMC Laboratory can also perform testing for the Australian C-Tick mark as a result of our A2LA accreditation.

VCCI

The 3m Semi-anechoic chamber (12.2m×7.95m×6.7m) and Shielded Room (8m×4m×3m) of Shenzhen Huatongwei International Inspection Co., Ltd has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-2484. Date of Registration: December 20, 2009. Valid time is until December 19, 2013.

Main Ports Conducted Interference Measurement of Shenzhen Huatongwei International Inspection Co., Ltd has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: C-2726. Date of Registration: December 20, 2009. Valid time is until December 19, 2013.

DNV

Shenzhen Huatongwei International Inspection Co Ltd has been found to comply with the requirements of DNV towards subcontractor of EMC and safety testing services in conjunction with the EMC and Low voltage Directives and in the voluntary field. The acceptance is based on a formal quality Audit and follow-ups according to relevant parts of ISO/IEC Guide 17025(2005), in accordance with the requirements of the DNV Laboratory Quality Manual towards subcontractors. Valid time is until Aug 24, 2016.

3.3. Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature:	15-35 ° C
Humidity:	30-60 %
Atmospheric pressure:	950-1050mbar

3.4. Configuration of Tested System

Fig. 2-1 Configuration of Tested System




Table 2-1 Equipment Used in Tested System

Adapter:

MODEL:GEO101U-052000W
 INPUT:100-240V~50/60Hz 0.3A
 OUTPUT: DC 5.0V 2.0A
 Power Cable: 150cm
 ◇ Shielded ◆ Unshielded

3.5. Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 „Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements“ and is documented in the Shenzhen Huatongwei International Inspection Co., Ltd quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for Shenzhen Huatongwei laboratory is reported:

Test Items	Measurement Uncertainty	Notes
Frequency stability	25 Hz	(1)
Transmitter power conducted	0.57 dB	(1)
Transmitter power Radiated	2.20 dB	(1)
Conducted spurious emission 9KHz-12.75 GHz	1.60 dB	(1)
Conducted Emission 9KHz-30MHz	3.39 dB	(1)
Radiated Emission 30~1000MHz	4.24 dB	(1)
Radiated Emissio 1~18GHz	5.16 dB	(1)
Radiated Emissio 18-40GHz	5.54 dB	(1)
Occupied Bandwidth	-----	(1)
Emission Mask	-----	(1)
Modulation Characteristic	-----	(1)
Transmitter Frequency Behavior	-----	(1)

- (1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=1.96.

3.6. Test Description

Test Items	Clause in FCC rules	Verdict
Conducted Emission	15.107/15.207	PASS
Output Power	22.913(a)/24.232(c)	PASS
Radiated Spurious Emission	2.1051/22.917/24.238	PASS
Frequency Stability	2.1055/24.235	PASS
Occupied Bandwidth	2.1049(h)(i)	PASS
Emission Bandwidth	22.917(b)/24.238(b)	PASS
Band Edge Compliance	22.917(b)/24.238(b)	PASS
Conducted Spurious Emission	2.1057/22.917/24.238	PASS

3.7. Equipments Used during the Test

Output Power(Conducted) & Occupied Bandwidth & Emission Bandwidth & Band Edge Compliance & Conducted Spurious Emission					
No.	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.
1	UNIVERSAL RADIO COMMUNICATION	Rohde&Schwarz	CMU200	112012	2012/10/27
2	Spectrum Analyzer	Rohde&Schwarz	FSU26	201141	2012/10/27
3	Splitter	Mini-Circuit	ZAPD-4	400059	2012/10/27

Frequency Stability					
No.	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.
1	UNIVERSAL RADIO COMMUNICATION	Rohde&Schwarz	CMU200	112012	2012/10/27
2	Spectrum Analyzer	Rohde&Schwarz	FSU26	201141	2012/10/27
3	Climate Chamber	ESPEC	EL-10KA	05107008	2012/10/27
4	Splitter	Mini-Circuit	ZAPD-4	400059	2012/10/27

Output Power (Radiated) & Radiated Spurious Emission					
No.	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.
1	UNIVERSAL RADIO COMMUNICATION	Rohde&Schwarz	CMU200	112012	2012/10/27
2	Spectrum Analyzer	Rohde&Schwarz	FSU26	201141	2012/10/27
3	HORN ANTENNA	ShwarzBeck	9120D	1012	2012/10/27
4	HORN ANTENNA	ShwarzBeck	9120D	1011	2012/10/27
5	Ultra-Broadband Antenna	ShwarzBeck	VULB9163	538	2012/10/27
6	Ultra-Broadband Antenna	ShwarzBeck	VULB9163	539	2012/10/27
7	TURNTABLE	MATURO	TT2.0	----	N/A
8	ANTENNA MAST	MATURO	TAM-4.0-P	----	N/A
9	EMI Test Software	Audix	E3	N/A	N/A
10	EMI Test Receiver	Rohde&Schwarz	ESIB 26	100009	2012/10/27
11	RF Test Panel	Rohde&Schwarz	TS / RSP	335015/ 0017	N/A
12	High pass filter	Compliance Direction systems	BSU-6	34202	2012/10/27
13	Splitter	Mini-Circuit	ZAPD-4	400059	2012/10/27
14	Horn Antenna	SCHWARZBECK	BBHA9170	25841	2012/10/27
15	Horn Antenna	SCHWARZBECK	BBHA9170	25842	2012/10/27
16	Preamplifier	ShwarzBeck	BBV 9718	BBV 9718	2012/10/27
17	Broadband Preamplifier	ShwarzBeck	BBV743	9743-0079	2012/10/27
18	Signal Generator	Rohde&Schwarz	SMF100A	101932	2012/10/27
19	Amplifier	Compliance Direction systems	PAP1-4060	120	2012/10/27

Conducted Disturbance					
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal.
1	EMI Test Receiver	Rohde&Schwarz	ESCI	100106	2012/10/27
2	Artificial Mains	Rohde&Schwarz	ESH2-Z5	100028	2012/10/27
3	Pulse Limiter	Rohde&Schwarz	ESHSZ2	100044	2012/10/27
4	EMI Test Software	Rohde&Schwarz	ESK1	N/A	N/A
5	Universal Radio Communication Tester	Rohde&Schwarz	CMU200	112012	2012/10/27

The calibration interval was one year.


4. TEST CONDITIONS AND RESULTS

4.1. Conducted Emissions Test

TEST APPLICABLE

The EUT was tested according to ANSI C63.4 - 2009. The frequency spectrum from 0.15 MHz to 30 MHz was investigated. The LISN used was 50 ohm / 50 u Henry as specified by section 5.1 of ANSI C63.4 - 2009. Cables and peripherals were moved to find the maximum emission levels for each frequency.

TEST CONFIGURATION



TEST PROCEDURE

- 1 The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. The EUT is a tabletop system; a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.4-2009.
- 2 Support equipment, if needed, was placed as per ANSI C63.4-2009.
- 3 All I/O cables were positioned to simulate typical actual usage as per ANSI C63.4-2009.
- 4 If a EUT received DC power from the adapter, the adapter received AC120V/60Hz power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
- 5 All support equipments received AC power from a second LISN, if any.
- 6 The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7 Analyzer / Receiver scanned from 150 KHz to 30MHz for emissions in each of the test modes.
- 8 During the above scans, the emissions were maximized by cable manipulation.

Conducted Power Line Emission Limit

For unintentional device, according to § 15.107(a) Line Conducted Emission Limits is as following :


Frequency (MHz)	Maximum RF Line Voltage (dBμV)			
	CLASS A		CLASS B	
	Q.P.	Ave.	Q.P.	Ave.
0.15 - 0.50	79	66	66-56*	56-46*
0.50 - 5.00	73	60	56	46
5.00 - 30.0	73	60	60	50

* Decreasing linearly with the logarithm of the frequency

For intentional device, according to §15.207(a) Line Conducted Emission Limit is same as above table.

TEST RESULTS**For GSM850****SCAN TABLE: "Voltage (9K-30M)FIN"**

Short Description: 150K-30M Voltage

**MEASUREMENT RESULT: "HTW1014314_fin"**

10/14/2013 3:18PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.406500	46.20	10.1	58	11.5	QP	L1	GND
0.411000	45.30	10.1	58	12.3	QP	L1	GND
0.501000	39.00	10.1	56	17.0	QP	L1	GND
0.519000	41.80	10.1	56	14.2	QP	L1	GND
0.847500	41.00	10.2	56	15.0	QP	L1	GND
2.085000	38.30	10.3	56	17.7	QP	L1	GND


MEASUREMENT RESULT: "HTW1014314_fin2"

10/14/2013 3:18PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.411000	28.10	10.1	48	19.5	AV	L1	GND
0.451500	29.50	10.1	47	17.3	AV	L1	GND
0.514500	30.50	10.1	46	15.5	AV	L1	GND
0.568500	28.80	10.1	46	17.2	AV	L1	GND
0.789000	26.20	10.2	46	19.8	AV	L1	GND
0.852000	25.40	10.2	46	20.6	AV	L1	GND

SCAN TABLE: "Voltage (9K-30M)FIN"

Short Description: 150K-30M Voltage

**MEASUREMENT RESULT: "HTW1014315_fin"**

10/14/2013 3:22PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.415500	40.60	10.1	58	16.9	QP	N	GND
0.420000	42.30	10.1	57	15.1	QP	N	GND
0.505500	38.70	10.1	56	17.3	QP	N	GND
0.519000	37.10	10.1	56	18.9	QP	N	GND
0.852000	35.50	10.2	56	20.5	QP	N	GND
2.085000	33.50	10.3	56	22.5	QP	N	GND

MEASUREMENT RESULT: "HTW1014315_fin2"


10/14/2013 3:22PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.397500	32.10	10.1	48	15.8	AV	N	GND
0.429000	19.40	10.1	47	27.9	AV	N	GND
0.510000	28.50	10.1	46	17.5	AV	N	GND
0.568500	26.30	10.1	46	19.7	AV	N	GND
0.798000	22.70	10.2	46	23.3	AV	N	GND
1.891500	21.00	10.3	46	25.0	AV	N	GND

For PCS1900

SCAN TABLE: "Voltage (9K-30M)FIN"

Short Description: 150K-30M Voltage



MEASUREMENT RESULT: "HTW1014316_fin"

10/14/2013 3:24PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.420000	42.30	10.1	57	15.1	QP	N	GND
0.510000	39.00	10.1	56	17.0	QP	N	GND
0.550500	31.80	10.1	56	24.2	QP	N	GND
0.807000	33.30	10.2	56	22.7	QP	N	GND
1.896000	33.00	10.3	56	23.0	QP	N	GND
2.085000	33.30	10.3	56	22.7	QP	N	GND


MEASUREMENT RESULT: "HTW1014316_fin2"

10/14/2013 3:24PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.397500	31.60	10.1	48	16.3	AV	N	GND
0.456000	26.90	10.1	47	19.9	AV	N	GND
0.514500	28.30	10.1	46	17.7	AV	N	GND
0.568500	26.50	10.1	46	19.5	AV	N	GND
0.802500	22.00	10.2	46	24.0	AV	N	GND
0.852000	22.80	10.2	46	23.2	AV	N	GND

SCAN TABLE: "Voltage (9K-30M)FIN"

Short Description: 150K-30M Voltage



MEASUREMENT RESULT: "HTW1014317_fin"

10/14/2013 3:27PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.420000	47.70	10.1	57	9.7	QP	L1	GND
0.510000	43.80	10.1	56	12.2	QP	L1	GND
0.564000	41.40	10.1	56	14.6	QP	L1	GND
0.847500	41.00	10.2	56	15.0	QP	L1	GND
1.261500	37.30	10.3	56	18.7	QP	L1	GND
1.882500	38.00	10.3	56	18.0	QP	L1	GND

MEASUREMENT RESULT: "HTW1014317_fin2"


10/14/2013 3:27PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.397500	32.70	10.1	48	15.2	AV	L1	GND
0.424500	29.60	10.1	47	17.8	AV	L1	GND
0.510000	29.80	10.1	46	16.2	AV	L1	GND
0.564000	27.50	10.1	46	18.5	AV	L1	GND
0.843000	24.50	10.2	46	21.5	AV	L1	GND
1.189500	25.90	10.3	46	20.1	AV	L1	GND

For Camera

SCAN TABLE: "Voltage (9K-30M) FIN"

Short Description: 150K-30M Voltage



MEASUREMENT RESULT: "HTW1014318_fin"

10/14/2013 3:29PM

Frequency MHz	Level dBuV	Transd dB	Limit dBuV	Margin dB	Detector	Line	PE
0.420000	47.90	10.1	57	9.5	QP	L1	GND
0.510000	43.80	10.1	56	12.2	QP	L1	GND
0.847500	40.40	10.2	56	15.6	QP	L1	GND
1.203000	38.90	10.3	56	17.1	QP	L1	GND
2.071500	36.50	10.3	56	19.5	QP	L1	GND


MEASUREMENT RESULT: "HTW1014318_fin2"

10/14/2013 3:29PM

Frequency MHz	Level dBuV	Transd dB	Limit dBuV	Margin dB	Detector	Line	PE
0.397500	32.50	10.1	48	15.4	AV	L1	GND
0.424500	30.10	10.1	47	17.3	AV	L1	GND
0.510000	30.60	10.1	46	15.4	AV	L1	GND
0.519000	28.90	10.1	46	17.1	AV	L1	GND
0.861000	24.90	10.2	46	21.1	AV	L1	GND
2.026500	23.60	10.3	46	22.4	AV	L1	GND

SCAN TABLE: "Voltage (9K-30M) FIN"

Short Description: 150K-30M Voltage



MEASUREMENT RESULT: "HTW1014319_fin"

10/14/2013 3:32PM

Frequency MHz	Level dBuV	Transd dB	Limit dBuV	Margin dB	Detector	Line	PE
0.424500	43.10	10.1	57	14.3	QP	N	GND
0.514500	38.10	10.1	56	17.9	QP	N	GND
0.852000	35.60	10.2	56	20.4	QP	N	GND
1.131000	34.60	10.3	56	21.4	QP	N	GND
1.869000	33.70	10.3	56	22.3	QP	N	GND
2.863500	30.10	10.3	56	25.9	QP	N	GND

MEASUREMENT RESULT: "HTW1014319_fin2"

10/14/2013 3:32PM

Frequency MHz	Level dBuV	Transd dB	Limit dBuV	Margin dB	Detector	Line	PE
0.438000	15.10	10.1	47	32.0	AV	N	GND
0.451500	25.00	10.1	47	21.8	AV	N	GND
0.510000	26.80	10.1	46	19.2	AV	N	GND
0.573000	25.70	10.1	46	20.3	AV	N	GND
0.793500	23.30	10.2	46	22.7	AV	N	GND
0.856500	22.10	10.2	46	23.9	AV	N	GND


4.2. OUTPUT POWER

TEST APPLICABLE

During the process of testing, the EUT was controlled via Rhode & Schwarz Digital Radio Communication tester (CMU-200) to ensure max power transmission and proper modulation. This result contains output power and EIRP measurements for the EUT. In all cases, output power is within the specified limits.

4.2.1. Conducted Output Power

TEST CONFIGURATION



TEST PROCEDURE

1. The EUT was set up for the max output power with pseudo random data modulation.
2. The power was measured with Rhode & Schwarz Spectrum Analyzer FSU (peak)
3. These measurements were done at 3 frequencies, 1850.20 MHz, 1880.00 MHz and 1909.80 MHz for PCS1900 band; 824.20 MHz, 836.60 MHz and 848.80 MHz for GSM850 band. (bottom, middle and top of operational frequency range).

TEST CONDITION

RBW	VBW	Sweep Time	Span
1MHz	3MHz	300ms	10MHz

GSM850				
Function	Power step	Nominal Peak output power (dBm)	Power & Multislot class	Operation class
GPRS	3	33dBm(2W)	12	B
EGPRS	3	33dBm(2W)	12	B

PCS1900				
Function	Power step	Nominal Peak output power (dBm)	Power & Multislot class	Operation class
GPRS	3	30dBm(1W)	12	B
EGPRS	3	30dBm(1W)	12	B

TEST RESULTS

GPRS850(GMSK,1Slot)		
Frequency (MHz)	Power Step	Output Power (dBm)
824.20	3	31.62
836.60	3	32.37
848.80	3	32.46

EGPRS850(GMSK,1Slot)		
Frequency (MHz)	Power Step	Output Power (dBm)
824.20	3	30.96
836.60	3	31.82
848.80	3	32.06

GPRS1900(GMSK,1Slot)		
Frequency (MHz)	Power Step	Output Power (dBm)
1850.20	3	29.75
1880.00	3	29.97
1909.80	3	28.68

EGPRS1900(GMSK,1Slot)		
Frequency (MHz)	Power Step	Output Power (dBm)
1850.20	3	29.72
1880.00	3	29.93
1909.80	3	28.59


4.2.2. Radiated Output Power

TEST DESCRIPTION

This is the test for the maximum radiated power from the EUT.

Rule Part 24.232(c) specifies, "Mobile/portable stations are limited to 2 watts e.i.r.p. Peak power" and 24.232(e) specifies that "Peak transmit power must be measured over any interval of continuous transmission using instrumentation calibrated in terms of an rms-equivalent voltage." Rule Part 22.913(a) specifies "The ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 Watts."

TEST CONFIGURATION



TEST PROCEDURE

1. EUT was placed on a 1.50 meter high non-conductive stand at a 3 meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT for emission measurements. The height of receiving antenna is 1.50m. Detected emissions were maximized at each frequency by rotating the EUT through 360° and adjusting the receiving antenna polarization. The radiated emission measurements of all transmit frequencies in three channels (High, Middle, Low) were measured with peak detector.
2. A log-periodic antenna or double-ridged waveguide horn antenna shall be substituted in place of the EUT. The log-periodic antenna will be driven by a signal generator and the level will be adjusted till the same power value on the spectrum analyzer or receiver. The level of the spurious emissions can be calculated through the level of the signal generator, cable loss, the gain of the substitution antenna and the reading of the spectrum analyzer or receiver.
3. The EUT is then put into continuously transmitting mode at its maximum power level during the test. Set Test Receiver or Spectrum RBW=1MHz, VBW=3MHz, And the maximum value of the receiver should be recorded as (P_r).
4. The EUT shall be replaced by a substitution antenna. In the chamber, an substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power (P_{Mea}) is applied to the input of the substitution antenna, and adjust the level of the signal generator output until the value of the receiver reach the previously recorded (P_r). The power of signal source (P_{Mea}) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.
5. A amplifier should be connected to the Signal Source output port. And the cable should be connect between the Amplifier and the Substitution Antenna. The cable loss (P_{cl}), the Substitution Antenna Gain (G_a) and the Amplifier Gain (P_{Ag}) should be recorded after test.
The measurement results are obtained as described below:

$$\text{Power(EIRP)} = P_{Mea} - P_{Ag} - P_{cl} - G_a$$

We used SMF100A microwave signal generator which signal level can up to 33dBm, so we not used power Amplifier for substitution test; The measurement results are amend as described below:

$$\text{Power(EIRP)} = P_{Mea} - P_{cl} - G_a$$
6. This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15 dBi) and known input power.
7. ERP can be calculated from EIRP by subtracting the gain of the dipole, $ERP = EIRP - 2.15\text{dBi}$.

TEST LIMIT

According to 22.913(a) and 24.232(c), the ERP should be not exceed following table limits:

GPRS850,EDGE850		
Function	Power Step	Burst Peak ERP (dBm)
GPRS	3	$\leq 38.45\text{dBm}$ (7W)
EGPRS	3	$\leq 38.45\text{dBm}$ (7W)

GPRS1900,EDGE1900		
Function	Power Step	Burst Peak EIRP (dBm)
GPRS	3	$\leq 33\text{dBm}$ (2W)
EGPRS	3	$\leq 33\text{dBm}$ (2W)

TEST RESULTS

GPRS850						
Frequency (MHz)	P_{Mea} (dBm)	P_{cl} (dB)	G_a Antenna Gain (dB)	Correction (dB)	ERP (dBm)	Polarization
824.20	25.17	1.56	8.45	2.15	29.91	H
836.60	25.75	1.50	8.45	2.15	30.55	H
848.80	25.05	1.67	8.39	2.15	29.62	H
824.20	25.30	1.56	8.45	2.15	30.04	V
836.60	26.09	1.50	8.45	2.15	30.89	V
848.80	25.21	1.67	8.39	2.15	29.78	V

EGPRS850						
Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain (dB)	Correction (dB)	ERP (dBm)	Polarization
824.20	25.03	1.56	8.45	2.15	29.77	H
836.60	25.30	1.50	8.45	2.15	30.10	H
848.80	24.91	1.67	8.39	2.15	29.48	H
824.20	25.22	1.56	8.45	2.15	29.96	V
836.60	25.75	1.50	8.45	2.15	30.55	V
848.80	25.11	1.67	8.39	2.15	29.68	V

GPRS1900						
Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain (dB)	Correction (dB)	EIRP (dBm)	Polarization
1850.20	23.88	3.52	8.35	2.15	28.71	H
1880.00	24.58	3.61	8.29	2.15	29.26	H
1909.80	23.18	3.67	8.37	2.15	27.88	H
1850.20	24.16	3.52	8.35	2.15	28.99	V
1880.00	25.15	3.61	8.29	2.15	29.83	V
1909.80	23.31	3.67	8.37	2.15	28.01	V


EGPRS1900						
Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain (dB)	Correction (dB)	EIRP (dBm)	Polarization
1850.20	23.80	3.52	8.35	2.15	28.63	H
1880.00	24.51	3.61	8.29	2.15	29.19	H
1909.80	23.07	3.67	8.37	2.15	27.77	H
1850.20	23.97	3.52	8.35	2.15	28.80	V
1880.00	25.02	3.61	8.29	2.15	29.70	V
1909.80	23.16	3.67	8.37	2.15	27.86	V

4.3. Transmitter Radiated Spurious Emission

TEST APPLICABLE

According to the TIA/EIA 603D:2010 test method, The Receiver or Spectrum was scanned from 30 MHz to the 10th harmonic of the highest frequency generated within the equipment, which is the transmitted carrier that can be as high as 1910 MHz. The resolution bandwidth is set as outlined in Part 24.238 and Part 22.917. The spectrum is scanned with the mobile station transmitting at carrier frequencies that pertain to low, mid and high channels of PCS1900 and GSM850.

TEST CONFIGURATION



TEST PROCEDURE

1. EUT was placed on a 1.50 meter high non-conductive stand at a 3 meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT for emission measurements. The height of receiving antenna is 1.50m. Detected emissions were maximized at each frequency by rotating the EUT through 360° and adjusting the receiving antenna polarization. The radiated emission measurements of all transmit frequencies in three channels (High, Middle, Low) were measured with peak detector.
2. A log-periodic antenna or double-ridged waveguide horn antenna shall be substituted in place of the EUT. The log-periodic antenna will be driven by a signal generator and the level will be adjusted till the same power value on the spectrum analyzer or receiver. The level of the spurious emissions can be calculated through the level of the signal generator, cable loss, the gain of the substitution antenna and the reading of the spectrum analyzer or receiver.

3. The EUT is then put into continuously transmitting mode at its maximum power level during the test. Set Test Receiver or Spectrum RBW=1MHz, VBW=3MHz, And the maximum value of the receiver should be recorded as (P_r).
4. The EUT shall be replaced by a substitution antenna. In the chamber, an substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power (P_{Mea}) is applied to the input of the substitution antenna, and adjust the level of the signal generator output until the value of the receiver reach the previously recorded (P_r). The power of signal source (P_{Mea}) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.
5. A amplifier should be connected to the Signal Source output port. And the cable should be connect between the Amplifier and the Substitution Antenna. The cable loss (P_{cl}), the Substitution Antenna Gain (G_a) and the Amplifier Gain (P_{Ag}) should be recorded after test.
The measurement results are obtained as described below:
 $Power(EIRP) = P_{Mea} - P_{Ag} - P_{cl} + G_a$
6. This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15 dBi) and known input power.
7. ERP can be calculated from EIRP by subtracting the gain of the dipole, $ERP = EIRP - 2.15dBi$.
8. In order to make sure test results more clearly, we set frequency range and sweep time for difference frequency range as follows table:

Working Frequency	Subrange (GHz)	RBW	VBW	Sweep time (s)
850MHz	0.03~1	100KHz	300KHz	10
	1-2	1 MHz	3 MHz	2
	2~5	1 MHz	3 MHz	3
	5~8	1 MHz	3 MHz	3
	8~10	1 MHz	3 MHz	3
1900MHz	0.03~1	100KHz	300KHz	10
	1-2	1 MHz	3 MHz	2
	2~5	1 MHz	3 MHz	3
	5~8	1 MHz	3 MHz	3
	8~11	1 MHz	3 MHz	3
	11~14	1 MHz	3 MHz	3
	14~18	1 MHz	3 MHz	3
	18~20	1 MHz	3 MHz	2

TEST LIMITS

According to 24.238 and 22.917 specify that the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

The specification that emissions shall be attenuated below the transmitter power (P) by at least $43 + 10 \log(P)$ dB, translates in the relevant power range (1 to 0.001 W) to -13 dBm. At 1 W the specified minimum attenuation becomes 43 dB and relative to a 30 dBm (1 W) carrier becomes a limit of -13 dBm. At 0.001 W (0 dBm) the minimum attenuation is 13 dB, which again yields a limit of -13 dBm. In this way a translation of the specification from relative to absolute terms is carried out.

Frequency	Channel	Frequency Range	Verdict
GSM 850MHz	Low	30MHz-10GHz	PASS
	Middle	30MHz-10GHz	PASS
	High	30MHz-10GHz	PASS
GSM 1900MHz	Low	30MHz-20GHz	PASS
	Middle	30MHz-20GHz	PASS
	High	30MHz-20GHz	PASS

GPRS850							
Channel Number: 128				Test Frequency: 824.20 MHz			
Frequency (MHz)	P _{Mea} (dBm)	Path Loss	Antenna Gain	Correction (dB)	Peak ERP(dBm)	Limit (dBm)	Polarization
2472.57	-21.49	4.32	6.77	2.15	-21.19	-13.00	H
3294.35	-25.41	4.55	12.25	2.15	-19.86	-13.00	H
4942.65	-31.87	4.70	12.92	2.15	-25.80	-13.00	H
2472.57	-20.02	4.32	6.77	2.15	-19.72	-13.00	V
3294.35	-22.43	4.55	12.25	2.15	-16.88	-13.00	V
4115.67	-29.47	4.59	12.76	2.15	-23.45	-13.00	V

GPRS850							
Channel Number: 190				Test Frequency: 836.60 MHz			
Frequency (MHz)	P _{Mea} (dBm)	Path Loss	Antenna Gain	Correction (dB)	Peak ERP(dBm)	Limit (dBm)	Polarization
3342.00	-28.58	4.55	12.25	2.15	-23.03	-13.00	H
4182.70	-27.58	4.59	12.76	2.15	-21.56	-13.00	H
5014.14	-26.10	4.78	12.88	2.15	-20.15	-13.00	H
3342.00	-26.33	4.55	12.25	2.15	-20.78	-13.00	V
4182.70	-24.68	4.59	12.76	2.15	-18.66	-13.00	V
5014.14	-25.35	4.78	12.88	2.15	-19.40	-13.00	V

GPRS850							
Channel Number: 251				Test Frequency: 848.80 MHz			
Frequency (MHz)	P _{Mea} (dBm)	Path Loss	Antenna Gain	Correction (dB)	Peak ERP(dBm)	Limit (dBm)	Polarization
2547.01	-25.08	4.29	6.83	2.15	-24.69	-13.00	H
3390.34	-28.57	4.58	12.59	2.15	-22.71	-13.00	H
4232.20	-24.18	4.59	12.76	2.15	-18.16	-13.00	H
2547.01	-21.59	4.29	6.83	2.15	-21.20	-13.00	V
3390.34	-25.63	4.58	12.59	2.15	-19.77	-13.00	V
4232.20	-23.01	4.59	12.76	2.15	-16.99	-13.00	V

GPRS1900							
Channel Number: 512				Test Frequency: 1850.20 MHz			
Frequency (MHz)	P _{Mea} (dBm)	Path Loss	Antenna Gain	Correction (dB)	Peak ERP(dBm)	Limit (dBm)	Polarization
3701.26	-30.26	4.55	12.34	2.15	-24.62	-13.00	H
5550.08	-24.66	5.05	13.53	2.15	-18.33	-13.00	H
7402.15	-26.48	4.64	11.60	2.15	-21.67	-13.00	H
3701.26	-27.48	4.55	12.34	2.15	-21.84	-13.00	V
5550.08	-22.55	5.05	13.53	2.15	-16.22	-13.00	V
7402.15	-24.57	4.64	11.60	2.15	-19.76	-13.00	V

GPRS1900							
Channel Number: 661				Test Frequency: 1880.00 MHz			
Frequency (MHz)	P _{Mea} (dBm)	Path Loss	Antenna Gain	Correction (dB)	Peak ERP(dBm)	Limit (dBm)	Polarization
3761.51	-31.58	4.55	12.40	2.15	-25.88	-13.00	H
5642.28	-27.81	4.96	13.60	2.15	-21.32	-13.00	H
7521.96	-25.71	4.71	11.89	2.15	-20.68	-13.00	H
3761.51	-28.41	4.55	12.40	2.15	-22.71	-13.00	V
5642.28	-23.51	4.96	13.60	2.15	-17.02	-13.00	V
7521.96	-23.78	4.71	11.89	2.15	-18.75	-13.00	V

GPRS1900							
Channel Number: 810				Test Frequency: 1909.80 MHz			
Frequency (MHz)	P _{Mea} (dBm)	Path Loss	Antenna Gain	Correction (dB)	Peak ERP(dBm)	Limit (dBm)	Polarization
3820.18	-28.91	4.51	12.43	2.15	-23.14	-13.00	H
5731.56	-26.35	4.90	13.61	2.15	-19.79	-13.00	H
7638.25	-29.92	4.78	12.00	2.15	-24.85	-13.00	H
3820.18	-26.53	4.51	12.43	2.15	-20.76	-13.00	V
5731.56	-22.79	4.90	13.61	2.15	-16.23	-13.00	V
7638.25	-25.81	4.78	12.00	2.15	-20.74	-13.00	V

Note: 1. In general, the worse case attenuation requirement shown above was applied.


3. *** means that the emission level is too low to be measured or at least 20 dB down than the limit.

4.4. OCCUPIED BANDWIDTH

TEST APPLICABLE

Similar to conducted emissions; occupied bandwidth measurements are only provided for selected frequencies in order to reduce the amount of submitted data. Data were taken at the extreme and mid frequencies of PCS1900 band and GSM850 band. The table below lists the measured 99% BW.

TEST CONFIGURATION




TEST PROCEDURE

1. The EUT was set up for the max output power with pseudo random data modulation;
2. The Occupied bandwidth was measured with Rhode & Schwarz Spectrum Analyzer FSU (peak);
3. Set RBW=5KHz,VBW=50KHz,Span=500KHz,SWT=20ms;
4. Set SPA Max hold. Mark peak, Set 99% Occupied Bandwidth
5. These measurements were done at 3 frequencies, 1850.20 MHz, 1880.00 MHz and 1909.80 MHz for PCS1900 band; 824.20MHz, 836.60 MHz and 848.80 MHz for GSM850 band. (low, middle and high of operational frequency range).

TEST RESULTS


GPRS850				
Channel Number	Frequency (MHz)	Occupied Bandwidth (99% BW) (kHz)	Refer to Plot	Verdict
128	824.20	244.39	Plot 4.4.1 A	PASS
190	836.60	248.40	Plot 4.4.1 B	PASS
251	848.80	241.99	Plot 4.4.1 C	PASS

EGPRS850				
Channel Number	Frequency (MHz)	Occupied Bandwidth (99% BW) (kHz)	Refer to Plot	Verdict
128	824.20	241.99	Plot 4.4.2 A	PASS
190	836.60	244.39	Plot 4.4.2 B	PASS
251	848.80	245.19	Plot 4.4.2 C	PASS




Date: 9.SEP.2013 11:46:24

(Plot 4.4.1 A: Channel 128: 824.20MHz @ GPRS850)




Date: 9.SEP.2013 11:47:27

(Plot 4.4.1 B: Channel 190: 836.60MHz @ GPRS850)




Date: 9.SEP.2013 11:48:59

(Plot 4.4.1 C: Channel 251: 848.80MHz @ GPRS850)




Date: 9.SEP.2013 15:16:41

(Plot 4.4.2 A: Channel 128: 824.20MHz @ EGPRS850)



Date: 9.SEP.2013 15:15:44

(Plot 4.4.2 B: Channel 190: 836.60MHz @ EGPRS850)




Date: 9.SEP.2013 15:15:11

(Plot 4.4.2 C: Channel 251: 848.80MHz @ EGPRS850)


GPRS1900				
Channel Number	Frequency (MHz)	Occupied Bandwidth (99% BW) (kHz)	Refer to Plot	Verdict
512	1850.20	245.99	Plot 4.4.3 A	PASS
661	1880.00	245.99	Plot 4.4.3 B	PASS
810	1909.80	244.39	Plot 4.4.3 C	PASS

EGPRS1900				
Channel Number	Frequency (MHz)	Occupied Bandwidth (99% BW) (kHz)	Refer to Plot	Verdict
512	1850.20	243.59	Plot 4.4.4 A	PASS
661	1880.00	244.39	Plot 4.4.4 B	PASS
810	1909.80	245.19	Plot 4.4.4 C	PASS




Date: 9.SEP.2013 13:24:32

(Plot 4.4.3 A: Channel 512:1820.20MHz @ GPRS1900)




Date: 9.SEP.2013 13:26:40

(Plot 4.4.3 B: Channel 661:1880.00MHz @ GPRS1900)




Date: 9.SEP.2013 13:29:07

(Plot 4.4.3 C: Channel 810:1909.80MHz @ GPRS1900)




Date: 9.SEP.2013 14:50:33

(Plot 4.4.5 A: Channel 512:1820.20MHz @ EGPRS1900)



Date: 9.SEP.2013 14:48:26

(Plot 4.4.5 B: Channel 661:1880.00MHz @ EGPRS1900)



Date: 9.SEP.2013 14:46:07


(Plot 4.4.5 C: Channel 810:1909.80MHz @ EGPRS1900)

4.5. EMISSION BANDWIDTH

TEST APPLICABLE

Similar to conducted emissions; occupied bandwidth measurements are only provided for selected frequencies in order to reduce the amount of submitted data. Data were taken at the extreme and mid frequencies of PCS1900 band and GSM850 band. The table below lists the measured -26dBc BW.

TEST CONFIGURATION




TEST PROCEDURE

1. The EUT was set up for the max output power with pseudo random data modulation;
2. The Occupied bandwidth was measured with Rhode & Schwarz Spectrum Analyzer FSU (peak);
3. Set RBW=5KHz,VBW=50KHz,Span=500KHz,SWT=20ms;
4. Set SPA Max hold. Mark peak, Set -26dBc Occupied Bandwidth
5. These measurements were done at 3 frequencies, 1850.20 MHz, 1880.00 MHz and 1909.80 MHz for PCS1900 band; 824.20MHz, 836.60 MHz and 848.80 MHz for GSM850 band. (low, middle and high of operational frequency range).

TEST RESULTS


GPRS850				
Channel Number	Frequency (MHz)	Occupied Bandwidth (-26dBc BW) (kHz)	Refer to Plot	Verdict
128	824.20	314.10	Plot 4.5.1 A	PASS
190	836.60	309.29	Plot 4.5.1 B	PASS
251	848.80	319.71	Plot 4.5.1 C	PASS

EGPRS850				
Channel Number	Frequency (MHz)	Occupied Bandwidth (-26dBc BW) (kHz)	Refer to Plot	Verdict
128	824.20	314.10	Plot 4.5.2 A	PASS
190	836.60	313.30	Plot 4.5.2 B	PASS
251	848.80	314.10	Plot 4.5.2 C	PASS




Date: 9.SEP.2013 11:51:39

(Plot 4.5.1 A: Channel 128: 824.20MHz @ GPRS850)




Date: 9.SEP.2013 11:50:47

(Plot 4.5.1 B: Channel 190: 836.60MHz @ GPRS850)




Date: 9.SEP.2013 11:49:57

(Plot 4.5.1 C: Channel 251: 848.80MHz @ GPRS850)




Date: 9.SEP.2013 15:17:07

(Plot 4.5.2 A: Channel 128: 824.20MHz @ EGPRS850)



Date: 9.SEP.2013 15:17:37

(Plot 4.5.2 B: Channel 190: 836.60MHz @ EGPRS850)




Date: 9.SEP.2013 15:18:12

(Plot 4.5.2 C: Channel 251: 848.80MHz @ EGPRS850)


GPRS1900				
Channel Number	Frequency (MHz)	Occupied Bandwidth (-26dBc BW) (kHz)	Refer to Plot	Verdict
512	1850.20	319.71	Plot 4.5.3 A	PASS
661	1880.00	318.11	Plot 4.5.3 B	PASS
810	1909.80	314.90	Plot 4.5.3 C	PASS

EGPRS1900				
Channel Number	Frequency (MHz)	Occupied Bandwidth (-26dBc BW) (kHz)	Refer to Plot	Verdict
512	1850.20	318.90	Plot 4.5.4 A	PASS
661	1880.00	317.31	Plot 4.5.4 B	PASS
810	1909.80	314.10	Plot 4.5.4 C	PASS




Date: 9.SEP.2013 13:09:01

(Plot 4.5.3 A: Channel 512:1820.20MHz @ GPRS1900)




Date: 9.SEP.2013 13:12:02

(Plot 4.5.3 B: Channel 661:1880.00MHz @ GPRS1900)




Date: 9.SEP.2013 13:11:14

(Plot 4.5.3 C: Channel 810:1909.80MHz @ GPRS1900)




Date: 9.SEP.2013 14:51:15

(Plot 4.5.4 A: Channel 512:1820.20MHz @ EGPRS1900)



Date: 9.SEP.2013 14:51:52

(Plot 4.5.4 B: Channel 661:1880.00MHz @ EGPRS1900)



Date: 9.SEP.2013 14:52:17


(Plot 4.5.4 C: Channel 810:1909.80MHz @ EGPRS1900)

4.6. BAND EDGE COMPLIANCE

TEST APPLICABLE

During the process of testing, the EUT was controlled via Rhode & Schwarz Digital Radio Communication tester (CMU-200) to ensure max power transmission and proper modulation.

TEST CONFIGURATION




TEST PROCEDURE

1. The EUT was set up for the max output power with pseudo random data modulation;
2. The power was measured with Rhode & Schwarz Spectrum Analyzer FSU (peak);
3. Set RBW=5KHz,VBW=50KHz,Span=1MHz,SWT=300ms;
4. These measurements were done at 3 frequencies, 1850.20 MHz, 1880.00 MHz and 1909.80 MHz for PCS1900 band; 824.20 MHz, 836.60 MHz and 848.80 MHz for GSM850 band. (low middle and high of operational frequency range).

TEST RESULTS


GPRS850						
Channel Number	Frequency (MHz)	Measurement Results		Limit (dBm)	Refer to Plot	Verdict
		Frequency (MHz)	Values (dBm)			
128	824.20	823.99	-13.86	-13.00	Plot 4.6.1 A	PASS
251	848.80	849.02	-13.44	-13.00	Plot 4.6.1 B	PASS

EGPRS850						
Channel Number	Frequency (MHz)	Measurement Results		Limit (dBm)	Refer to Plot	Verdict
		Frequency (MHz)	Values (dBm)			
128	824.20	823.97	-13.33	-13.00	Plot 4.6.2 A	PASS
251	848.80	849.02	-13.68	-13.00	Plot 4.6.2 B	PASS




Date: 9.SEP.2013 11:56:54

(Plot 4.6.1 A: Channel 128: 824.20MHz @ GPRS850)




Date: 9.SEP.2013 12:00:13

(Plot 4.6.1 B: Channel 251: 848.80MHz @ GPRS850)



Date: 9.SEP.2013 15:23:51

(Plot 4.6.2 A: Channel 128: 824.20MHz @ EGPRS850)




Date: 9.SEP.2013 15:22:53

(Plot 4.6.2 B: Channel 251: 848.80MHz @ EGPRS850)


GPRS1900						
Channel Number	Frequency (MHz)	Measurement Results		Limit (dBm)	Refer to Plot	Verdict
		Frequency (MHz)	Values (dBm)			
512	1850.20	1849.99	-13.83	-13.00	Plot 4.6.3 A	PASS
810	1909.80	1910.00	-14.03	-13.00	Plot 4.6.3 B	PASS

EGPRS1900						
Channel Number	Frequency (MHz)	Measurement Results		Limit (dBm)	Refer to Plot	Verdict
		Frequency (MHz)	Values (dBm)			
512	1850.20	1849.99	-13.48	-13.00	Plot 4.6.4 A	PASS
810	1909.80	1910.00	-13.71	-13.00	Plot 4.6.4 B	PASS




Date: 9.SEP.2013 15:37:34

(Plot 4.6.3 A: Channel 512: 1950.20MHz @ GPRS1900)




Date: 9.SEP.2013 15:39:37

(Plot 4.6.3 B: Channel 810: 1909.80MHz @ GPRS1900)



Date: 9.SEP.2013 15:35:26

(Plot 4.6.4 A: Channel 512: 1850.20MHz @ EGPRS1900)



Date: 9.SEP.2013 15:34:19

(Plot 4.6.4 B: Channel 810: 1909.80MHz @ EGPRS1900)


4.7. Spurious Emission on Antenna Port

TEST APPLICABLE

The following steps outline the procedure used to measure the conducted emissions from the EUT.

1. Determine frequency range for measurements: From CFR 2.1057 the spectrum should be investigated from the lowest radio frequency generated in the equipment up to at least the 10th harmonic of the carrier frequency. For the equipment of PCS1900 band, this equates to a frequency range of 30 MHz to 19.1 GHz, data taken from 30 MHz to 20 GHz. For GSM850, data taken from 30 MHz to 10 GHz.
2. The sweep time is set automatically by instrument itself. That should be the optimal sweep time for the span and the RBW. If the sweep time is too short, that is sweep is too fast, the sweep result is not accurate; if the sweep time is too long, that is sweep is too low, some frequency components may be lost. The instrument will give a optimal sweep time according the selected span and RBW.
3. The procedure to get the conducted spurious emission is as follows:
The trace mode is set to MaxHold to get the highest signal at each frequency;
Wait 25 seconds;
Get the result.
4. Determine EUT transmit frequencies: below outlines the band edge frequencies pertinent to conducted emissions testing.

TEST CONFIGURATION



TEST PROCEDURE

1. The EUT was set up for the max output power with pseudo random data modulation;
2. The power was measured with Rhode & Schwarz Spectrum Analyzer FSU (peak);
3. These measurements were done at 3 frequencies, 1850.20 MHz, 1880.00 MHz and 1909.80 MHz for PCS1900 band; 824.20 MHz, 836.60 MHz and 848.80 MHz for GSM850 band. (bottom, middle and top of operational frequency range).

TEST LIMIT

Part 24.238 and Part 22.917 specify that the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

The specification that emissions shall be attenuated below the transmitter power (P) by at least $43 + 10 \log(P)$ dB, translates in the relevant power range (1 to 0.001 W) to -13 dBm. At 1 W the specified minimum attenuation becomes 43 dB and relative to a 30 dBm (1 W) carrier becomes a limit of -13 dBm. At 0.001 W (0 dBm) the minimum attenuation is 13 dB, which again yields a limit of -13 dBm. In this way a translation of the specification from relative to absolute terms is carried out.

TEST RESULTS

GPRS850						
Channel Number: 128		Test Frequency: 824.20 MHz			Test Mode: Traffic	
Start Frequency (MHz)	Stop Frequency (MHz)	Measurement Results		Limit (dBm)	Refer to Plot	Verdict
		Frequency (MHz)	Values (dBm)			
30	1000	***	***	-13.00	Plot 4.7.1 A1	PASS
1000	2500	1649.04	-31.98	-13.00	Plot 4.7.1 A2	PASS
2500	7500	3237.18	-40.74	-13.00	Plot 4.7.1 A3	PASS
7500	10000	8317.31	-40.97	-13.00	Plot 4.7.1 A4	PASS


GPRS850						
Channel Number: 190		Test Frequency: 836.60 MHz			Test Mode: Traffic	
Start Frequency (MHz)	Stop Frequency (MHz)	Measurement Results		Limit (dBm)	Refer to Plot	Verdict
		Frequency (MHz)	Values (dBm)			
30	1000	***	***	-13.00	Plot 4.7.2 A1	PASS
1000	2500	1673.08	-32.06	-13.00	Plot 4.7.2 A2	PASS
2500	7500	2508.01	-30.08	-13.00	Plot 4.7.2 A3	PASS
7500	10000	8874.20	-41.21	-13.00	Plot 4.7.2 A4	PASS

GPRS850						
Channel Number: 251		Test Frequency: 848.80 MHz			Test Mode: Traffic	
Start Frequency (MHz)	Stop Frequency (MHz)	Measurement Results		Limit (dBm)	Refer to Plot	Verdict
		Frequency (MHz)	Values (dBm)			
30	1000	***	***	-13.00	Plot 4.7.3 A1	PASS
1000	2500	1697.12	-33.90	-13.00	Plot 4.7.3 A2	PASS
2500	7500	2540.06	-30.00	-13.00	Plot 4.7.3 A3	PASS
7500	10000	7724.36	-40.95	-13.00	Plot 4.7.3 A4	PASS

GPRS850						
Test Mode: Idle						
Start Frequency (MHz)	Stop Frequency (MHz)	Measurement Results		Limit (dBm)	Refer to Plot	Verdict
		Frequency (MHz)	Values (dBm)			
30	1000	87.52	-40.19	-13.00	Plot 4.7.4 A1	PASS
1000	2500	2478.37	-40.45	-13.00	Plot 4.7.4 A2	PASS
2500	7500	3493.59	-40.45	-13.00	Plot 4.7.4 A3	PASS
7500	10000	7764.42	-40.73	-13.00	Plot 4.7.4 A4	PASS


Note: 1. In general, the worse case attenuation requirement shown above was applied.

2. *** means that the emission level is too low to be measured or at least 20 dB down than the limit.




Date: 9.SEP.2013 15:25:22

(Plot 4.7.1 A1: Channel 128: 824.20MHz @ Traffic @ GSM850)




Date: 9.SEP.2013 15:25:48

(Plot 4.7.1 A2: Channel 128: 824.20MHz @ Traffic @ GSM850)




Date: 9.SEP.2013 15:26:09

(Plot 4.7.1 A3: Channel 128: 824.20MHz @ Traffic @ GSM850)




Date: 9.SEP.2013 15:26:27

(Plot 4.7.1 A4: Channel 128: 824.20MHz @ Traffic @ GSM850)




Date: 9.SEP.2013 15:26:59

(Plot 4.7.2 A1: Channel 190: 836.60MHz @ Traffic @ GSM850)




Date: 9.SEP.2013 15:27:27

(Plot 4.7.2 A2: Channel 190: 836.60MHz @ Traffic @ GSM850)




Date: 9.SEP.2013 15:27:48

(Plot 4.7.2 A3: Channel 190: 836.60MHz @ Traffic @ GSM850)




Date: 9.SEP.2013 15:28:03

(Plot 4.7.2 A4: Channel 190: 836.60MHz @ Traffic @ GSM850)




Date: 9.SEP.2013 15:28:33

(Plot 4.7.3 A1: Channel 251: 848.80MHz @ Traffic @ GSM850)




Date: 9.SEP.2013 15:28:45

(Plot 4.7.3 A2: Channel 251: 848.80MHz @ Traffic @ GSM850)




Date: 9.SEP.2013 15:29:00

(Plot 4.7.3 A3: Channel 251: 848.80MHz @ Traffic @ GSM850)




Date: 9.SEP.2013 15:29:23

(Plot 4.7.3 A4: Channel 251: 848.80MHz @ Traffic @ GSM850)




Date: 9.SEP.2013 15:29:55

(Plot 4.7.4 A1: Idle @ GSM850)




Date: 9.SEP.2013 15:30:18

(Plot 4.7.4 A2: Idle @ GSM850)



Date: 9.SEP.2013 15:30:39

(Plot 4.7.4 A3: Idle @ GSM850)



Date: 9.SEP.2013 15:30:53

(Plot 4.7.4 A4: Idle @ GSM850)

PCS1900						
Channel Number: 512		Test Frequency: 1850.20 MHz			Test Mode: Traffic	
Start Frequency (MHz)	Stop Frequency (MHz)	Measurement Results		Limit (dBm)	Refer to Plot	Verdict
		Frequency (MHz)	Values (dBm)			
30	1000	42.44	-38.16	-13.00	Plot 4.7.5 A1	PASS
1000	2500	***	***	-13.00	Plot 4.7.5 A2	PASS
2500	7500	3565.71	-37.86	-13.00	Plot 4.7.5 A3	PASS
7500	10000	7792.47	-38.86	-13.00	Plot 4.7.5 A4	PASS
10000	15000	13565.71	-38.76	-13.00	Plot 4.7.5 A5	PASS
15000	20000	15426.78	-38.51	-13.00	Plot 4.7.5 A6	PASS


PCS1900						
Channel Number: 661		Test Frequency: 1880.00 MHz			Test Mode: Traffic	
Start Frequency (MHz)	Stop Frequency (MHz)	Measurement Results		Limit (dBm)	Refer to Plot	Verdict
		Frequency (MHz)	Values (dBm)			
30	1000	39.33	-37.69	-13.00	Plot 4.7.6 A1	PASS
1000	2500	***	***	-13.00	Plot 4.7.6 A2	PASS
2500	7500	3509.62	-38.39	-13.00	Plot 4.7.6 A3	PASS
7500	10000	8553.69	-38.55	-13.00	Plot 4.7.6 A4	PASS
10000	15000	14270.83	-38.99	-13.00	Plot 4.7.6 A5	PASS
15000	20000	18092.95	-38.45	-13.00	Plot 4.7.6 A6	PASS

PCS1900						
Channel Number: 810		Test Frequency: 1909.80 MHz			Test Mode: Traffic	
Start Frequency (MHz)	Stop Frequency (MHz)	Measurement Results		Limit (dBm)	Refer to Plot	Verdict
		Frequency (MHz)	Values (dBm)			
30	1000	42.44	-38.79	-13.00	Plot 4.7.7 A1	PASS
1000	2500	***	***	-13.00	Plot 4.7.7 A2	PASS
2500	7500	3349.36	-37.92	-13.00	Plot 4.7.7 A3	PASS
7500	10000	9739.58	-38.16	-13.00	Plot 4.7.7 A4	PASS
10000	15000	14615.38	-38.58	-13.00	Plot 4.7.7 A5	PASS
15000	20000	17395.83	-38.14	-13.00	Plot 4.7.7 A6	PASS

PCS1900						
Test Mode: Idle						
Start Frequency (MHz)	Stop Frequency (MHz)	Measurement Results		Limit (dBm)	Refer to Plot	Verdict
		Frequency (MHz)	Values (dBm)			
30	1000	40.88	-39.48	-13.00	Plot 4.7.8 A1	PASS
1000	2500	2487.98	-38.15	-13.00	Plot 4.7.8 A2	PASS
2500	7500	3509.62	-38.17	-13.00	Plot 4.7.8 A3	PASS
7500	10000	8605.77	-39.11	-13.00	Plot 4.7.8 A4	PASS
10000	15000	10873.40	-39.04	-13.00	Plot 4.7.8 A5	PASS
15000	20000	16907.05	-38.24	-13.00	Plot 4.7.8 A6	PASS


Note: 1. In general, the worse case attenuation requirement shown above was applied.

2. *** means that the emission level is too low to be measured or at least 20 dB down than the limit.




Date: 9.SEP.2013 13:34:42

(Plot 4.7.5 A1: Channel 512: 1850.20MHz @ Traffic @ PCS1900)




Date: 9.SEP.2013 13:35:23

(Plot 4.7.5 A2: Channel 512: 1850.20MHz @ Traffic @ PCS1900)




Date: 9.SEP.2013 13:35:51

(Plot 4.7.5 A3: Channel 512: 1850.20MHz @ Traffic @ PCS1900)




Date: 9.SEP.2013 13:36:15

(Plot 4.7.5 A4: Channel 512: 1850.20MHz @ Traffic @ PCS1900)




Date: 9.SEP.2013 13:37:02

(Plot 4.7.5 A5: Channel 512: 1850.20MHz @ Traffic @ PCS1900)




Date: 9.SEP.2013 13:37:28

(Plot 4.7.5 A6: Channel 512: 1850.20MHz @ Traffic @ PCS1900)




Date: 9.SEP.2013 13:37:55

(Plot 4.7.6 A1: Channel 661: 1880.00MHz @ Traffic @ PCS1900)




Date: 9.SEP.2013 13:38:57

(Plot 4.7.6 A2: Channel 661: 1880.00MHz @ Traffic @ PCS1900)




Date: 9.SEP.2013 13:39:24

(Plot 4.7.6 A3: Channel 661: 1880.00MHz @ Traffic @ PCS1900)




Date: 9.SEP.2013 13:39:46

(Plot 4.7.6 A4: Channel 661: 1880.00MHz @ Traffic @ PCS1900)




Date: 9.SEP.2013 13:40:06

(Plot 4.7.6 A5: Channel 661: 1880.00MHz @ Traffic @ PCS1900)




Date: 9.SEP.2013 13:40:22

(Plot 4.7.6 A6: Channel 661: 1880.00MHz @ Traffic @ PCS1900)




Date: 9.SEP.2013 13:40:54

(Plot 4.7.7 A1: Channel 810: 1909.80MHz @ Traffic @ PCS1900)




Date: 9.SEP.2013 13:41:28

(Plot 4.7.7 A2: Channel 810: 1909.80MHz @ Traffic @ PCS1900)




Date: 9.SEP.2013 13:41:52

(Plot 4.7.7 A3: Channel 810: 1909.80MHz @ Traffic @ PCS1900)




Date: 9.SEP.2013 13:42:46

(Plot 4.7.7 A4: Channel 810: 1909.80MHz @ Traffic @ PCS1900)




Date: 9.SEP.2013 13:43:13

(Plot 4.7.7 A5: Channel 810: 1909.80MHz @ Traffic @ PCS1900)




Date: 9.SEP.2013 13:43:38

(Plot 4.7.7 A6: Channel 810: 1909.80MHz @ Traffic @ PCS1900)




Date: 9.SEP.2013 13:45:21

(Plot 4.7.8 A1: Idle @ PCS1900)




Date: 9.SEP.2013 13:45:44

(Plot 4.7.8 A2: Idle @ PCS1900)




Date: 9.SEP.2013 13:46:04

(Plot 4.7.8 A3: Idle @ PCS1900)




Date: 9.SEP.2013 13:46:21

(Plot 4.7.8 A4: Idle @ PCS1900)



Date: 9.SEP.2013 13:46:38

(Plot 4.7.8 A5: Idle @ PCS1900)



Date: 9.SEP.2013 13:46:57

(Plot 4.7.8 A6: Idle @ PCS1900)

4.8. Frequency Stability Test

TEST APPLICABLE


1. According to FCC Part 2 Section 2.1055 (a)(1), the frequency stability shall be measured with variation of ambient temperature from -30°C to +50°C centigrade.
2. According to FCC Part 2 Section 2.1055 (d) (2), for battery powered equipment, the frequency stability shall be measured with reducing primary supply voltage to the battery operating end point, which is specified by the manufacture.
3. Vary primary supply voltage from 85 to 115 percent of the nominal value for other than hand carried voltage equipment and the end voltage point was 4.22V.

TEST PROCEDURE

In order to measure the carrier frequency under the condition of AFC lock, it is necessary to make measurements with the EUT in a "call mode". This is accomplished with the use of R&S CMU200 DIGITAL RADIO COMMUNICATION TESTER.

1. Measure the carrier frequency at room temperature;
2. Subject the EUT to overnight soak at -30°C;
3. With the EUT, powered via nominal voltage, connected to the CMU200 and in a simulated call on middle channel of PCS 1900 and GSM850, measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming;
4. Repeat the above measurements at 10°C increments from -30°C to +50°C. Allow at least 0.5 hours at each temperature, unpowered, before making measurements;
5. Remeasure carrier frequency at room temperature with nominal voltage. Vary supply voltage from minimum voltage to maximum voltage, in 0.1Volt increments remeasuring carrier frequency at each voltage. Pause at nominal voltage for 0.5 hours unpowered, to allow any self-heating to stabilize, before continuing;
6. Subject the EUT to overnight soak at +50°C;
7. With the EUT, powered via nominal voltage, connected to the CMU200 and in a simulated call on the centre channel, measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming;
8. Repeat the above measurements at 10°C increments from +50°C to -30°C. Allow at least 0.5 hours at each temperature, unpowered, before making measurements;
9. At all temperature levels hold the temperature to +/- 0.5°C during the measurement procedure;

TEST CONFIGURATION



TEST LIMITS

For Hand carried battery powered equipment

According to the JTC standard the frequency stability of the carrier shall be accurate to within 0.1 ppm of the received frequency from the base station. This accuracy is sufficient to meet Sec. 24.235, Frequency Stability.

The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. As this transceiver is considered "Hand carried, battery powered equipment" Section 2.1055(d)(2) applies. This requires that the lower voltage for frequency stability testing be specified by the manufacturer. This transceiver is specified to operate with an input voltage of between 3.5VDC and 4.20VDC, with a nominal voltage of 3.70VDC. Operation above or below these voltage limits is prohibited by transceiver software in order to prevent improper operation as well as to protect components from overstress. These voltages represent a tolerance of -10 % and +12.5 %. For the purposes of measuring frequency stability these voltage limits are to be used.

For equipment powered by primary supply voltage

According to the JTC standard the frequency stability of the carrier shall be accurate to within 0.1 ppm of the received frequency from the base station. This accuracy is sufficient to meet Sec. 24.235, Frequency Stability. The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. For this EUT section 2.1055(d)(1) applies. This requires varying primary supply voltage from 85 to 115 percent of the nominal value for other than hand carried battery equipment.


TEST RESULTS

Remark: we tested both GPRS and EDGE(GMSK) mode and recorded worst case at GPRS mode.

GPRS850					
DC Power	Temperature (°C)	Frequency error(Hz)	Frequency error(ppm)	Limit (ppm)	Verdict
5.00	25	41	0.049	0.10	PASS
4.25	25	59	0.071	0.10	PASS
5.75	25	-36	0.043	0.10	PASS
5.00	-30	-17	0.020	0.10	PASS
5.00	-20	50	0.060	0.10	PASS
5.00	-10	28	0.033	0.10	PASS
5.00	0	-17	0.020	0.10	PASS
5.00	10	41	0.049	0.10	PASS
5.00	20	39	0.047	0.10	PASS
5.00	30	23	0.027	0.10	PASS
5.00	40	-22	0.026	0.10	PASS
5.00	50	-22	0.026	0.10	PASS

GPRS1900					
DC Power	Temperature (°C)	Frequency error(Hz)	Frequency error(ppm)	Limit (ppm)	Verdict
5.00	20	56	0.030	0.10	PASS
4.25	20	47	0.025	0.10	PASS
5.75	20	-52	0.028	0.10	PASS
5.00	-30	47	0.025	0.10	PASS
5.00	-20	23	0.012	0.10	PASS
5.00	-10	35	0.019	0.10	PASS
5.00	0	-23	0.012	0.10	PASS
5.00	10	35	0.019	0.10	PASS
5.00	20	47	0.025	0.10	PASS
5.00	30	-49	0.026	0.10	PASS
5.00	40	29	0.015	0.10	PASS
5.00	50	20	0.011	0.10	PASS

5. Test Setup Photos of the EUT





6. External and Internal Photos of the EUT


External photos of the EUT













Internal Photos














.....End of Report.....