InterLab®

Final Report on

N-Com M5
FCC ID Y6MNCOM9
IC: 9455A-NCOM9

Report Reference: MDE_REDOX_1401_FCCc
acc. Title 47 CFR chapter I part 15 subpart C

Date: February 17, 2015

Test Laboratory:
7 layers AG
Borsigstrasse 11
40880 Ratingen
Germany

DAkkS
Deutsche
Akkreditierungsstelle
D-PL-12140-01-01

Note:
The following test results relate only to the devices specified in this document. This report shall not be reproduced in parts without the written approval of the test laboratory.

1 Administrative Data

1.1 Project Data

Project Responsible:	Imad Hjije
Date Of Test Report:	2015/01/13
Date of first test:	2014/12/09
Date of last test:	2014/12/09

1.2 Applicant Data

Company Name: Nolangroup s.p.a.

Street:	via Terzi di S.Agata 2
City:	24030 Brembate di sopra
Country:	Italy

Contact Person: Mr. Claudio Corollo

Phone:	+39 035 602 285
Fax:	+39 035 602 261
E-Mail:	c.corollo@nolan.it

1.3 Test Laboratory Data

The following list shows all places and laboratories involved for test result generation:

7 layers DE

Company Name :	7 layers AG
Street :	Borsigstrasse 11
City :	40880 Ratingen
Country :	Germany
Contact Person :	Mr. Michael Albert
Phone :	+49 2102 749 201
Fax :	+49 2102 749 444
E Mail :	Michael.Albert@7Layers.com

Laboratory Details

Lab ID	*Identification*	*Responsible*	*Accreditation Info*
Lab 1	Regulatory Bluetooth RF Test Solution	Mr. Jimmy Chatheril Mr. Sören Berentzen	DAkkS-Registration no. D-PL-12140-01-01

1.4 Signature of the Testing Responsible

Imad Hjije

Imad Hjije
responsible for tests performed in: Lab 1

1.5 Signature of the Accreditation Responsible

B. Retka [B. RETKA]

Accreditation scope responsible person
responsible for Lab 1

2 Test Object Data

2.1 General OUT Description

The following section lists all OUTs (Object's Under Test) involved during testing.

OUT: N-Com M5

Manufacturer:

Company Name:	Please see applicant data
Contact Person:	-

Parameter List:

Parameter name	*Value*
AC Power Supply	120 (V)
Antenna Gain	0 (dBi)
DC Power Supply	3.7 (V)
highest channel (BT)	2480 (MHz)
lowest channel (BT)	2402 (MHz)
mid channel (BT)	2441 (MHz)

2.2 Detailed Description of OUT Samples

Sample : ac01

OUT Identifier	N-Com M5		
Sample Description	C-duplicated 2014-12-09 10:58:55		
HW Status	1.0		
SW Status	1.0		
Low Voltage	3.3 V	*Low Temp.*	-20 °C
High Voltage	4.2 V	*High Temp.*	60 °C
Nominal Voltage	3.7 V	*Normal Temp.*	23 °C

2.3 OUT Features

Features for OUT: N-Com M5
FCC ID Y6MNCOM9
IC: 9455A-NCOM9

Designation	*Description*	*Allowed Values*	*Supported Value(s)*
Features for scope: FCC_v2			
AC	The OUT is powered by or connected to AC Mains		
BT	EUT supports Bluetooth data rate of 1 Mbps with GFSK modulation in the band 2400 MHz - 2483.5 MHz		
EDR2	EUT supports Bluetooth using data rate of 2 Mbps with PI/4 DQPSK modulation in the band 2400 MHz - 2483.5 MHz		
EDR3	EUT supports Bluetooth using data rate of 3 Mbps with 8DPSK modulation in the band 2400 MHz - 2483.5 MHz		
Iant	Integral Antenna: permanent fixed antenna, which may be built-in, designed as an indispensable part of the equipment		
TantC	temporary antenna connector, which may be only built-in for testing, designed as an example part of the equipment		

2.4 Setups used for Testing

For each setup a relation is given to determine if and which samples and auxiliary equipment is used. The left side list all OUT samples and the right side lists all auxiliary equipment for the given setup.

Setup No.	*List of OUT samples*		*List of auxiliary equipment*	
	Sample No.	*Sample Description*	*AE No.*	*AE Description*
AC01_Setup				
	Sample: ac01	C-duplicated 2014-12-09 10:58:55		

3 Results

3.1 General

Documentation of tested devices:	Available at the test laboratory.
Interpretation of the test results:	The results of the inspection are described on the following pages, where 'Conformity' or 'Passed' means that the certification criteria were verified and that the tested device is conform to the applied standard. In cases where 'Declaration' is printed, the required documents are available in the manufacturers product documentation. In cases where 'not applicable' is printed, the test case requirements are not relevant to the specific equipment implementation.
Note:	1. All tests are performed under environmental conditions within the requirements of the specifications. Environmental conditions are available at the laboratory. 2. The device is a hands-free kit containing a BT and BTLE Transceiver operating in the 2.4 GHz ISM band. 3. This report focuses only on the BTLE part. Results of "radiated spurious emissions" and "Conducted emissions (AC power line)" are included in the report "MDE_REDOX_1401_FCCa".

3.2 List of the Applicable Body

(Body for Scope: FCC_v2)

Designation	*Description*
FCC47CFRChIPART15c247RADIO FREQUENCY DEVICES	Subpart C - Intentional Radiators; 15.247 Operation within the bands 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz.

3.3 List of Test Specification

Test Specification:	**FCC part 2 and 15**
Version	10-1-13 Edition
Title:	PART 2 - GENERAL RULES AND REGULATIONS PART 15 - RADIO FREQUENCY DEVICES

3.4 Summary

Test Case Identifier / Name Test (condition)	*Result*	*Date of Test*	*Lab Ref.*	*Setup*
15c.10 Power density §15.247 (e)				
15c.10; Frequency = Low/Mid/High	Passed	2014/12/09	Lab 1	AC01_Setup
15c.11 6dB Bandwidth §15.247 (a) (2)				
15c.11; Frequency = Low/Mid/High	Passed	2014/12/09	Lab 1	AC01_Setup
15c.4 Peak power output §15.247 (b) (1)				
15c.4; Peak power output Summary	Passed	2014/12/09	Lab 1	AC01_Setup
15c.5 Spurious RF conducted emissions §15.247 (d)				
15c.5; = BT transmit mode: Low/Mid/High Frequency	Passed	2014/12/09	Lab 1	AC01_Setup
15c.6 Band edge compliance §15.247 (d)				
15c.6; Band edge compliance Summary	Passed	2014/12/09	Lab 1	AC01_Setup

3.5 Detailed Results

3.5.1 15c.10 Power density §15.247 (e)

Test: 15c.10; Frequency = Low/Mid/High

Result:	Passed
Setup No.:	AC01_Setup
Date of Test:	2014/12/09 13:55
Body:	FCC47CFRChIPART15c247RADIO FREQUENCY DEVICES
Test Specification:	FCC part 2 and 15

Detailed Results:

TEST CONDITIONS	Maximum Spectral Power Density (RMS) (including antenna gain and correction factor)		
	lowest frequency	mid frequency	highest frequency
Bluetooth Low Energy (GFSK)	2402 MHz	2441 MHz	2480 MHz
	-8.54	-7.54	-7.42
	per 1 MHz	per 1 MHz	per 1 MHz



Date: 2.OCT.2014 10:30:33



Date: 2.OCT.2014 10:28:14



Date: 2.OCT.2014 10:20:24

3.5.2 15c.11 6dB Bandwidth §15.247 (a) (2)

Test: 15c.11; Frequency = Low/Mid/High

Result:	Passed
Setup No.:	AC01_Setup
Date of Test:	2014/12/09 13:51
Body:	FCC47CFRChIPART15c247RADIO FREQUENCY DEVICES
Test Specification:	FCC part 2 and 15

Detailed Results:

Modulation	Frequency	6dB Bandwidth KHz
GFSK	2402 MHz	707.7
	2426 MHz	
	2440 MHz	712
	2480 MHz	716.4



Date: 2.OCT.2014 10:33:30



Date: 2.OCT.2014 10:36:07



Date: 2.OCT.2014 10:38:03

3.5.3 15c.4 Peak power output §15.247 (b) (1)

Test: 15c.4; Peak power output Summary

Result:	Passed
Setup No.:	AC01_Setup
Date of Test:	2014/12/09 13:49
Body:	FCC47CFRChIPART15c247RADIO FREQUENCY DEVICES
Test Specification:	FCC part 2 and 15

Detailed Results:

		Conducted Transmitter Power					
		2402 MHz		2440 MHz		2480 MHz	
Modulation	**Conditions**	Output Power (dBm)	Output Power (mW)	Output Power (dBm)	Output Power (mW)	Output Power (dBm)	Output Power (mW)
GFSK	TN, VN	7.44	5.55	8.34	6.82	8.35	6.84

Max Conducted Output Power (FSK Modulation)	**8.35**	**dBm**	**6.84**	**mW**
EIRP Conducted	**8.35**	**dBm**	**6.84**	**mW**

Antena Gain (dBi)	**0**



Date: 2.OCT.2014 09:58:56



Date: 2.OCT.2014 10:08:06



Date: 2.OCT.2014 10:13:59

3.5.4 15c.5 Spurious RF conducted emissions §15.247 (d)

Test: 15c.5; = BT transmit mode: Low/Mid/High Frequency

Result:	Passed
Setup No.:	AC01_Setup
Date of Test:	2014/12/09 13:56
Body:	FCC47CFRChIPART15c247RADIO FREQUENCY DEVICES
Test Specification:	FCC part 2 and 15

Detailed Results:

Frequency range 30 MHz - 26 GHz			BT transmit using 1 Mbps with GFSK modulation		
Channel (MHz)	**Frequency of emission MHz**	**Measured value dBm**	**Reference value dBm**	**Limit dBm**	**Margin to limit dB**
2402	**	-45.45	6.82	-13.18	32.27
2440	**	-46.46	7.78	-12.17	34.30
2480	**	-46.15	8.34	-11.66	34.49

**** No Peaks found within 20 dB of limit line.**



Title: spurious emissions
Comment A: CH B: 2402 MHz
Date: 19.SEP.2014 07:20:33

3.5.5 15c.6 Band edge compliance §15.247 (d)

Test: 15c.6; Band edge compliance Summary

Result:	Passed
Setup No.:	AC01_Setup
Date of Test:	2014/12/09 13:53
Body:	FCC47CFRChIPART15c247RADIO FREQUENCY DEVICES
Test Specification:	FCC part 2 and 15

Detailed Results:

Modulation	Frequency MHz	Measured value dBm	Reference value dBm	Limit dBm	Margin to limit dB
GFSK	2400	-42.35	6.82	-13.18	29.17
GFSK	2484	-51.14	8.34	-11.66	39.48



Title: Band Edge Compliance
Comment A: CH B: 2402 MHz
Date: 19.SEP.2014 07:08:36



Title: Band Edge Compliance
Comment A: CH M2: 2440 MHz
Date: 19.SEP.2014 07:33:40



Title: Band Edge Compliance
Comment A: CH T:2480 MHz
Date: 19.SEP.2014 07:54:33

4 Test Equipment Details

4.1 List of Used Test Equipment

The calibration, hardware and software states are shown for the testing period.

Test Equipment Multimeter 12

Lab ID:	**Lab 1**
Description:	Ex-Tech 520
Serial Number:	05157876

Single Devices for Multimeter 12

Single Device Name	*Type*	*Serial Number*	*Manufacturer*	
Digital Multimeter 12 (Multimeter)	EX520	05157876	Extech Instruments Corp.	
	Calibration Details		*Last Execution*	*Next Exec.*
	Customized calibration		2013/12/04	2015/12/03

Test Equipment Regulatory Bluetooth RF Test Solution

Lab ID:	**Lab 1**
Description:	Regulatory Bluetooth RF Tests
Type:	Bluetooth RF
Serial Number:	001

Single Devices for Regulatory Bluetooth RF Test Solution

Single Device Name	*Type*	*Serial Number*	*Manufacturer*	
ADU 200 Relay Box 7	Relay Box	A04380	Ontrak Control Systems Inc.	
Bluetooth Signalling Unit CBT	CBT	100302	Rohde & Schwarz GmbH & Co.KG	
	Calibration Details		*Last Execution*	*Next Exec.*
	Standard calibration		2014/08/29	2015/08/28
Power Meter NRVD	NRVD	832025/059		
	Calibration Details		*Last Execution*	*Next Exec.*
	Standard calibration		2014/08/29	2015/08/28
Power Sensor NRV Z1 A	PROBE	832279/013		
	Calibration Details		*Last Execution*	*Next Exec.*
	Standard calibration		2014/08/28	2015/08/27
Power Supply	NGSM 32/10	2725		
	Calibration Details		*Last Execution*	*Next Exec.*
	Standard calibration		2013/06/20	2015/06/19
Rubidium Frequency Normal MFS	Datum MFS	002	Datum GmbH	
	Calibration Details		*Last Execution*	*Next Exec.*
	Standard calibration		2014/08/29	2015/08/28
Signal Analyser FSIQ26	1119.6001.26	832695/007	Rohde & Schwarz GmbH & Co.KG	
Vector Signal Generator SMIQ03B	SMIQ03B	832870/017		
	Calibration Details		*Last Execution*	*Next Exec.*
	Standard calibration		2013/06/21	2016/06/20

Test Equipment Shielded Room 07

Lab ID:	**Lab 1**
Description:	Shielded Room 4m x 6m

Test Equipment T/H Logger 15

Lab ID:	**Lab 1**
Description:	Lufft Opus10
Serial Number:	13985

Single Devices for T/H Logger 15

Single Device Name	*Type*	*Serial Number*	*Manufacturer*	
ThermoHygro Datalogger 15 (Environ)	Opus10 THI (8152.00)	13985	Lufft Mess- und Regeltechnik GmbH	
	Calibration Details		*Last Execution*	*Next Exec.*
	Customized calibration		2013/01/07	2015/02/24

Test Equipment Temperature Chamber 01

Lab ID:	**Lab 1**
Manufacturer:	see single devices
Description:	Temperature Chamber KWP 120/70
Type:	Weiss
Serial Number:	see single devices

Single Devices for Temperature Chamber 01

Single Device Name	*Type*	*Serial Number*	*Manufacturer*	
Temperature Chamber Weiss 01	KWP 120/70	59226012190010	Weiss Umwelttechnik GmbH	
	Calibration Details		*Last Execution*	*Next Exec.*
	Customized calibration		2014/03/12	2016/03/11

5 Annex

5.1 Additional Information for Report

Summary of Test Results

The EUT complied with all performed tests as listed in the summary section of this report.

Technical Report Summary

Type of Authorization :

Certification for an Intentional Radiator (Frequency Hopping Spread Spectrum).

Applicable FCC Rules

Prepared in accordance with the requirements of FCC Rules and Regulations as listed in 47 CFR Ch.1 Parts 2 and 15. The following subparts are applicable to the results in this test report

Part 2, Subpart J - Equipment Authorization Procedures, Certification

Part 15, Subpart C – Intentional Radiators

§ 15.201 Equipment authorization requirement

§ 15.207 Conducted limits

§ 15.209 Radiated emission limits; general requirements

§ 15.247 Operation within the bands 902-928 MHz, 2400-2483.5 MHz and 5725-5850 MHz

additional documents

The tests were selected and performed with reference to the FCC Public Notice DA 00-705, released March 30, 2000. Instead of applying ANSI C63.4-1992 which is referenced in the FCC Public Note, the newer ANSI C63.4-2009 is applied.

Description of Methods of Measurements

Conducted emissions (AC power line)

Standard FCC Part 15, Subpart C

The test was performed according to: ANSI C 63.4,

Test Description

The test set-up was made in accordance to the general provisions of ANSI C 63.4.

The Equipment Under Test (EUT) was setup in a shielded room to perform the conducted emissions measurements in a typical installation configuration. The EUT was powered from 50µH || 50 Ohm Line Impedance Stabilization Network (LISN). The LISN's unused connections were terminated with 50 Ohm loads. The measurement procedure consists of two steps. It is implemented into the EMI test software ES-K1 from R&S.

Step 1: Preliminary scan
Intention of this step is, to determine the conducted EMI-profile of the EUT.
EMI receiver settings:
- Detector: Peak - Maxhold
- Frequency range: 150 kHz – 30 MHz
- Frequency steps: 5 kHz
- IF–Bandwidth: 9 kHz
- Measuring time / Frequency step: 20 ms
- Measurement on phase + neutral lines of the power cords

On basis of this preliminary scan the highest amplitudes and the corresponding frequencies relative to the limit are identified. Emissions above the limit and emissions which are in the 10 dB range below the limit are considered.

Step 2: Final measurement
Intention of this step is, to determine the highest emissions with the settings defined in the test specification for the frequencies identified in step 1.
EMI receiver settings:
- Detector: Quasi-Peak
- IF - Bandwidth: 9 kHz
- Measuring time: 1 s / frequency

At each frequency determined in step 1, four measurements are performed in the following combinations:
1) Neutral lead - reference ground (PE grounded)
2) Phase lead - reference ground (PE grounded)
3) Neutral lead - reference ground (PE floating)
4) Phase lead - reference ground (PE floating)

The highest value is reported.

Test Requirements / Limits

FCC Part 15, Subpart C, §15.207

Frequency Range (MHz)	QP Limit (dBµV)	AV Limit (dBµV)
0.15 – 0.5	66 to 56	56 to 46
0.5 – 5	56	46
5 – 30	60	50

Used conversion factor: Limit (dBµV) = 20 log (Limit (µV)/1µV).

Peak power output

Standard FCC Part 15, Subpart C

The test was performed according to: FCC §15.31

Test Description

The Equipment Under Test (EUT) was set up to perform the output power measurements. The resolution bandwidth for measuring the output power was set to 3 MHz. The reference level of the spectrum analyzer was set higher than the output power of the EUT. The EUT was connected to the spectrum analyzer via a short coax cable with a known loss.

Test Requirements / Limits

FCC Part 15, Subpart C, §15.247 (b) (1)
(b) The maximum peak conducted output power of the intentional radiator shall not exceed the following:
(1) For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt.

Used conversion factor: Limit (dBm) = 10 log (Limit (W)/1mW)
==> Maximum Output Power: 30 dBm

Spurious RF conducted emissions

Standard FCC Part 15, Subpart C

The test was performed according to: FCC §15.31

Test Description

The Equipment Under Test (EUT) was set up to perform the spurious emissions measurements.
The EUT was connected to spectrum analyzer via a short coax cable with a known loss.
Analyzer settings:
- Detector: Peak-Maxhold
- Frequency range: 30 – 25000 MHz
- Resolution Bandwidth (RBW): 100 kHz
- Video Bandwidth (VBW): 300 kHz
- Sweep Time: 330 s

The reference value for the measurement of the spurious RF conducted emissions is determined during the test "band edge compliance" (cf. chapter 3.6). This value is used to calculate the 20 dBc limit.

Test Requirements / Limits

FCC Part 15, Subpart C, §15.247 (c)
In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power

---

Spurious radiated emissions

Standard FCC Part 15, Subpart C

The test was performed according to: ANSI C 63.4,

Test Description

The test set-up was made in accordance to the general provisions of ANSI C63.4–2009.
The Equipment Under Test (EUT) was set up on a non-conductive table 1.0 x 2.0 m in the semi-anechoic chamber. The influence of the EUT support table that is used between 30–1000 MHz was evaluated.
The test was performed at the distance of 3 m between the EUT and the receiving antenna. The measurement procedure is implemented into the EMI test software ES-K1 from R&S. The radiated emissions measurements were made in a typical installation configuration. Exploratory tests are performed at 3 orthogonal axes to determine the worst-case orientation of a body-worn or handheld EUT. The final test on all kind of EUTs is performed at 2 axes. A pre-check is also performed while the EUT is powered from both AC and DC (battery) power in order to find the worst-case operating condition.

1. Measurement up to 30 MHz
The test set-up was made in accordance to the general provisions of ANSI C63.4.
The Equipment Under Test (EUT) was set up on a non-conductive table in the anechoic chamber.
The radiated emissions measurements were made in a typical installation configuration.
The measurement procedure is implemented into the EMI test software ES-K1 from R&S.
The Loop antenna HFH2-Z2 is used.
Step 1: pre-measurement
- Anechoic chamber
- Antenna distance: 10 m
- Detector: Peak-Maxhold
- Frequency range: 0.009 – 0.15 and 0.15 – 30 MHz
- Frequency steps: 0.1 kHz and 5 kHz
- IF–Bandwidth: 0.2 kHz and 10 kHz
- Measuring time / Frequency step: 100 ms

Intention of this step is, to determine the radiated EMI-profile of the EUT. Afterwards the relevant emissions for the final measurement are identified.
Step 2: final measurement

For the relevant emissions determined in step 1, an additional measurement with the following settings will be performed. Intention of this step is to find the maximum emission level.
- Open area test side
- Antenna distance: according to the Standard
- Detector: Quasi-Peak
- Frequency range: 0.009 – 30 MHz
- Frequency steps: measurement at frequencies detected in step 1
- IF–Bandwidth: 200 Hz – 10 kHz
- Measuring time / Frequency step: 100 ms

2. Measurement above 30 MHz and up to 1 GHz

Step 1: Preliminary scan

Preliminary test to identify the highest amplitudes relative to the limit.

Settings for step 1:
- Detector: Peak-Maxhold
- Frequency range: 30 – 1000 MHz
- Frequency steps: 60 kHz
- IF–Bandwidth: 120 kHz
- Measuring time / Frequency step: 100 µs (BT Timing 1.25 ms)
- Turntable angle range: –180 to +180°
- Turntable step size: 90°
- Height variation range: 1 – 3 m
- Height variation step size: 2 m
- Polarisation: Horizontal + Vertical

Intention of this step is, to determine the radiated EMI-profile of the EUT. Afterwards the relevant emissions for the final measurement are identified.

Step 2: second measurement

For the relevant emissions determined in step 1, an additional measurement with the following settings will be performed. Intention of this step is, to find out the approximate turntable angle and antenna height for each frequency.
- Detector: Peak – Maxhold
- Measured frequencies: in step 1 determined frequencies
- IF – Bandwidth: 120 kHz
- Measuring time: 100 ms
- Turntable angle range: –180 to +180°
- Turntable step size: 45°
- Height variation range: 1 – 4 m
- Height variation step size: 0.5 m
- Polarisation: horizontal + vertical

After this step the EMI test system has determined the following values for each frequency (of step 1):
- Frequency
- Azimuth value (of turntable)
- Antenna height

The last two values have now the following accuracy:
- Azimuth value (of turntable): 45°
- Antenna height: 0.5 m

Step 3: final measurement

In this step the accuracy of the turntable azimuth and antenna height will be improved. This is necessary to find out the maximum value of every frequency.

For each frequency, which was determined the turntable azimuth and antenna height will be adjusted. The turntable azimuth will be slowly varied by +/–22.5° around this value. During this action the value of emission is continuously measured. The turntable azimuth at the highest emission will be recorded and adjusted. In this position the antenna height is also slowly varied by +/–25 cm around the antenna height determined. During this action the value of emission is also continuously measured. The antenna height of the highest emission will also be recorded and adjusted.
- Detector: Peak – Maxhold
- Measured frequencies: in step 1 determined frequencies
- IF – Bandwidth: 120 kHz
- Measuring time: 100 ms
- Turntable angle range: –22.5° to +22.5° around the determined value
- Height variation range: –0.25 m to +0.25 m around the determined value

Step 4: final measurement with QP detector

With the settings determined in step 3, the final measurement will be performed:

EMI receiver settings for step 4:
- Detector: Quasi-Peak (< 1 GHz)
- Measured frequencies: in step 1 determined frequencies
- IF – Bandwidth: 120 kHz
- Measuring time: 1 s

3. Measurement above 1 GHz
The following modifications apply to the measurement procedure for the frequency range above 1 GHz:
The measurement distance was reduced to 1 m. The results were extrapolated by the extrapolation factor of 20 dB/decade (inverse linear-distance for field strength measurements, inverse linear-distance squared for the power reference level measurements). Due to the fact that in this frequency range a double ridged wave guided horn antenna (up to 18 GHz) and a horn antenna (18–25 GHz) are used, the steps 2–4 are omitted. Step 1 was performed with one height of the receiving antenna only.
EMI receiver settings:
- Detector: Peak, Average
- IF Bandwidth = 1 MHz

After the measurement a plot will be generated which contains a diagram with the results of the preliminary scan and a chart with the frequencies and values of the results of the final measurement.
For the enhanced data rate packets the test is performed as worst-case-check in order to verify that emissions have a comparable level as found at basic data rate. Typically, the measurement for these packets is performed in the frequency range 1 to 8 GHz but it depends on the emissions found during the test for the basic data rate. Please refer to the results for the used frequency range.

Test Requirements / Limits

FCC Part 15, Subpart C, §15.247 (d)
... In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

FCC Part 15, Subpart C, §15.209, Radiated Emission Limits

Frequency in MHz	Limit (µV/m)	Measurement distance (m)	Limit(dBµV/m @10m)
0.009 – 0.49	2400/F(kHz)	300	Limit (dBµV/m)+30dB
0.49 – 1.705	24000/F(kHz)	30	Limit (dBµV/m)+10dB
1.705 - 30	30	30	Limit (dBµV/m)+10dB

Frequency in MHz	Limit (µV/m)	Measurement distance (m)	Limit (dBµV/m)
30 - 88	100	3	40.0
88 - 216	150	3	43.5
216 - 960	200	3	46.0
above 960	500	3	54.0

§15.35(b)
..., there is also a limit on the radio frequency emissions, as measured using instrumentation with a peak detector function, corresponding to 20 dB above the maximum permitted average limit....

Used conversion factor: Limit (dBµV/m) = 20 log (Limit (µV/m)/1µV/m)

Band edge compliance

Standard FCC Part 15, Subpart C

The test was performed according to: ANSI C 63.4, FCC §15.31

Test Description

The procedure to show compliance with the band edge requirement is divided into two measurements: 1. Show compliance of the lower band edge by a conducted measurement and 2. show compliance of the higher band edge by a radiated and conducted measurement.

For the first measurement the EUT is set to transmit on the lowest channel (2402 MHz). The lower band edge is 2400 MHz.
Analyzer settings:
- Detector: Peak
- RBW= 100 kHz
- VBW= 300 kHz

For the second measurement the EUT is set to transmit on the highest channel (2480 MHz). The higher band edge is 2483.5 MHz.
Analyzer settings for conducted measurement:
- Detector: Peak
- RBW= 100 kHz
- VBW= 300 kHz

EMI receiver settings:
- Detector: Peak, Average
- IF Bandwidth = 1 MHz

Test Requirements / Limits

FCC Part 15.247 (d)
"In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.
...
Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c))."

For the measurement of the lower band edge the RF power at the band edge shall be "at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power..."

For the measurement of the higher band edge the limit is "specified in Section 15.209(a)".

Power density

Standard FCC Part 15, 10-1-11 Subpart C

The test was performed according to: FCC §15.31

Test Description

The EUT was connected to spectrum analyzer via a short coax cable with a known loss.

Analyzer settings:
- Detector: Peak-Maxhold
- Resolution Bandwidth (RBW): 3 kHz
- Video Bandwidth (VBW): 30 kHz
- Sweep Time: Coupled

Test Requirements / Limits

FCC Part 15, Subpart C, §15.247 (e)

For digitally modulated systems, the peak power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.
…
The same method of determining the conducted output power shall be used to determine the power spectral density.

6-dB bandwidth

Standard FCC Part 15, 10-1-11 Subpart C

The test was performed according to: FCC §15.31

Test Description

The Equipment Under Test (EUT) was setup to perform the occupied bandwidth measurements.

The reference level is the level of the highest amplitude signal observed from the transmitter at either the fundamental frequency or first-order modulation products in all typical modes of operation, including the unmodulated carrier, even if atypical.
The results recorded were measured with the modulation which produce the worst-case (widest) occupied bandwidth.

The EUT was connected to spectrum analyzer via a short coax cable with a known loss.
Analyzer settings:
- Resolution Bandwidth (RBW): 100 kHz
- Video Bandwidth (VBW): 300 kHz
- Span: 30 MHz

Test Requirements / Limits

FCC Part 15, Subpart C, §15.247 (a) (2)

Systems using digital modulation techniques may operate in the 902-928 MHz, 2400-2483.5 MHz and 5725-5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Used conversion factor: Output power (dBm) = 10 log (Output power (W) / 1mW)

Setup Drawings



Remark: Depending on the frequency range suitable antenna types, attenuators or preamplifiers are used.

Setup in the Anechoic chamber:
Measurements below 1 GHz: Semi-anechoic, conducting ground plane.
Measurements above 1 GHz: Fully-anechoic, absorbers on all surfaces

November, 2014

To Whom This May Concern

Correlation of measurement requirements for DTS (e.g. WLAN 2.4 GHz, BT LE) equipment from FCC and IC

DTS equipment

Measurement	FCC reference	IC reference
Conducted emissions on AC Mains	§ 15.207	RSS-Gen Issue 4: 8.8
Occupied bandwidth	§ 15.247 (a) (2)	RSS-210 Issue 8: A8.2 (a)
Peak conducted output power	§ 15.247 (b) (3), (4)	RSS-210 Issue 8: A8.4 (4)
Transmitter spurious RF conducted emissions	§ 15.247 (d)	RSS-Gen Issue 4: 6.13 / 8.9/8.10; RSS-210 Issue 8: A8.5
Transmitter spurious radiated emissions	§ 15.247 (d); § 15.209 (a)	RSS-Gen Issue 4: 6.13 / 8.9/8.10; RSS-210 Issue 8: A8.5
Band edge compliance	§ 15.247 (d)	RSS-210 Issue 8: A8.5
Power density	§ 15.247 (e)	RSS-210 Issue 8: A8.2 (b)
Antenna requirement	§ 15.203 / 15.204	RSS-Gen Issue 4: 8.3
Receiver spurious emissions	–	RSS-210 Issue 8: 2.3 RSS Gen Issue 4: 5 / 7 *)

*) Receivers are exempted from certification besides if operating in stand-alone mode in the frequency range 30–960 MHz or if these are scanner receivers.

This correlation amends the test report referenced by:
MDE_ABCDE_1234_ZZZn

6 Index

1 Administrative Data 2
1.1 Project Data 2
1.2 Applicant Data 2
1.3 Test Laboratory Data 2
1.4 Signature of the Testing Responsible 2
1.5 Signature of the Accreditation Responsible 3
2 Test Object Data 3
2.1 General OUT Description 3
2.2 Detailed Description of OUT Samples 3
2.3 OUT Features 4
2.4 Setups used for Testing 4
3 Results 5
3.1 General 5
3.2 List of the Applicable Body 5
3.3 List of Test Specification 5
3.4 Summary 6
3.5 Detailed Results 7
3.5.1 15c.10 Power density §15.247 (e) 7
3.5.2 15c.11 6dB Bandwidth §15.247 (a) (2) 11
3.5.3 15c.4 Peak power output §15.247 (b) (1) 15
3.5.4 15c.5 Spurious RF conducted emissions §15.247 (d) 19
3.5.5 15c.6 Band edge compliance §15.247 (d) 21
4 Test Equipment Details 25
4.1 List of Used Test Equipment 25
5 Annex 27
5.1 Additional Information for Report 27
6 Index 36