

RF Exposure Report

Report No.: SA170620C22

FCC ID: Y6S-IOTADV

Test Model: IoT Platform Advance

Series Model: 72201R Lumewave IoT Platform

Received Date: Apr. 26, 2017

Test Date: Apr. 27 ~ Aug. 31, 2017

Issued Date: Nov. 28, 2017

Applicant: Ionics EMS, Inc.

Address: 14 Mountain Drive, Light Industry and Science Park II, Brgy. La Mesa,
Calamba, Laguna 4027, Philippines

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan,
R.O.C.

Test Location: No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City
33383, TAIWAN (R.O.C.)



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

Table of Contents

Release Control Record	3
1 Certificate of Conformity	4
2 RF Exposure	5
2.1 Limits for Maximum Permissible Exposure (MPE).....	5
2.2 MPE Calculation Formula	5
2.3 Classification	5
3 Calculation Result of Maximum Conducted Power	6

Release Control Record

Issue No.	Description	Date Issued
SA170620C22	Original release	Nov. 28, 2017

1 Certificate of Conformity

Product: IOT PLATFORM

Brand: Ionics, Lumewave

Test Model: IoT Platform Advance

Series Model: 72201R Lumewave IoT Platform

Sample Status: Engineering sample

Applicant: Ionics EMS, Inc.

Test Date: Apr. 27 ~ Aug. 31, 2017

Standards: FCC Part 2 (Section 2.1091)
KDB 447498 D03 (January 17, 2014)
IEEE C95.1

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by :



Pettie Chen / Senior Specialist

Date:

Nov. 28, 2017

Approved by :



Ken Liu / Senior Manager

Date:

Nov. 28, 2017

2 RF Exposure

2.1 Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
Limits For General Population / Uncontrolled Exposure				
300-1500	...	...	F/1500	30
1500-100,000	...	...	1.0	30

F = Frequency in MHz

2.2 MPE Calculation Formula

$$P_d = (P_{out} * G) / (4 * \pi * r^2)$$

where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

2.3 Classification

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.

3 Calculation Result of Maximum Conducted Power

Frequency Band (MHz)	Max Power (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
WLAN					
2412-2462	21.74	-0.06	20	0.029	1
BT LE					
2402-2480	8.51	-0.06	20	0.001	1
BT EDR					
2402-2480	4.46	-0.06	20	0.001	1
RFID: 906~924MHz					
906~924	25.13	5.34	20	0.222	0.609

RFID

Mode	Electric field (dBuV/m) @3m	Electric field (dBuV/m) @0.2m	Max Power (dBm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
908MHz	92.3	115.82	-2.93	0.0001	0.605

908MHz: $92.3 + 20\log(3/0.2) = 115.82\text{dBuV/m}$

Frequency Band	Max. Power (dBm)			Total Power (dBm)	Power Limit (dBm)
	WLAN	BT LE	BT EDR		
2.4GHz	21.74	8.51	-	21.94	30
2.4GHz	21.74	-	4.46	21.82	30

CONCLUSION:

The WLAN & BT LE & RFID or WLAN & BT EDR & RFID can transmit simultaneously, the formula of calculated the MPE is:

$CPD1 / LPD1 + CPD2 / LPD2 + \dots \text{etc.} < 1$

CPD = Calculation power density

LPD = Limit of power density

$WLAN + BT LE + RFID (908\text{MHz}) + RFID (906\sim 924\text{MHz}) = 0.029 + 0.001 + 0.0001 + 0.222 = 0.2521$

$WLAN + BT EDR + RFID (908\text{MHz}) + RFID (906\sim 924\text{MHz}) = 0.029 + 0.001 + 0.0001 + 0.222 = 0.2521$

Therefore, the maximum calculation of this situation is 0.2521, which is less than the "1" limit.

---END---