

RF EXPOSURE REPORT

FOR

Applicant	:	Continental Automotive GmbH
Address	:	Philipsstrasse 1, Wetzlar, Germany 35576
Equipment under Test	:	CAR RADIO
Model No.	:	CDD7428UB-OR/19, CDD728UB-BU/19, CD7426UB-OR/19, CD726UB-BU/19
Trade Mark	:	Continental, VDO
FCC ID	:	Y7O-CDD7428UBOR
Manufacturer	:	Huizhou Foryou General Electronics Co., Ltd.
Address	:	North Shangxia Road, Dongjiang Hi-tech Industry Park, Huizhou, Guangdong Province, 516005, P R China

Issued By: Dongguan Dongdian Testing Service Co., Ltd.

Add: No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park, Dongguan
City, Guangdong Province, China, 523808

Tel: +86-0769-38826678, **E-mail:** ddt@dgddt.com, <http://www.dgddt.com>

REPORT

TABLE OF CONTENTS

	Test report declares.....	3
1.	General information	5
1.1.	Description of Equipment.....	5
1.2.	Assess laboratory.....	5
2.	RF Exposure evaluation.....	5
2.1.	Requirement.....	5
2.2.	Calculation Method	6
2.3.	Estimation Result	6

TEST REPORT DECLARE

Applicant	:	Continental Automotive GmbH
Address	:	Philipsstrasse 1,Wetzlar,Germany 35576
Equipment under Test	:	CAR RADIO
Model No.	:	CDD7428UB-OR/19, CDD728UB-BU/19, CD7426UB-OR/19, CD726UB-BU/19
Trade mark	:	Continental, VDO
Manufacturer	:	Huizhou Foryou General Electronics Co., Ltd.
Address	:	North Shangxia Road, Dongjiang Hi-tech Industry Park,Huizhou, Guangdong Province, 516005,P R China

Standard Used: KDB447498 D01 General RF Exposure Guidance v06

We Declare:

The equipment described above is assessed by Dongguan Dongdian Testing Service Co., Ltd and in the configuration assessed the equipment complied with the standards specified above. The assessed results are contained in this report and Dongguan Dongdian Testing Service Co., Ltd is assumed of full responsibility for the accuracy and completeness of these assess.

After evaluation, our opinion is that the equipment In Accordance with above standard.

Report No:	DDT-R19060306-1E7		
Date of Receipt:	Jul. 01, 2019	Date of Test:	Jul. 01, 2019 ~ Jul. 10, 2019

Prepared By:

Ella Gong

Ella Gong/Engineer

Approved By:



Damon Hu/EMC Manager

Note: This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Dongguan Dongdian Testing Service Co., Ltd.

Revision history

Rev.	Revisions	Issue Date	Revised By
---	Initial issue	Jul. 10, 2019	

1. General information

1.1. Description of Equipment

EUT* Name	: CAR RADIO
Model Number	: CDD7428UB-OR/19, CDD728UB-BU/19, CD7426UB-OR/19, CD726UB-BU/19
Difference of models	: Model CDD7428UB-OR/19 and CDD728UB-BU/19 have DAB, and CD7426UB-OR/19, CD726UB-BU/19 have no DAB, different Model have different backlight color, the difference don't influence RF performance, so choose CDD7428UB-OR/19 for testing.
EUT function description	: Please reference user manual of this device
Power supply	: DC 24V
Radio Specification	: Bluetooth V2.1
Operation frequency	: 2402MHz-2480MHz
Modulation	: GFSK, $\pi/4$ -DQPSK, 8DPSK
Data rate	: 1 Mbps, 2 Mbps, 3 Mbps
Antenna Type	: PCB Layout antenna, maximum PK gain: 0 dBi
Sample Type	: Series production

1.2. Assess laboratory

Dongguan Dongdian Testing Service Co., Ltd

Add: No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park, Dongguan City, Guangdong Province, China, 523808

Tel: +86-0769-38826678, <http://www.dgddt.com>, Email: ddt@dgddt.com

2. RF Exposure evaluation

2.1. Requirement

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with.

Limits for General Population/Uncontrolled Exposure

(B) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30

Note: f = frequency in MHz ; *Plane-wave equivalent power density

2.2. Calculation Method

$$E(\text{V/m}) = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power Density: } S(\text{mW/cm}^2) = \frac{E^2}{377}$$

E = Electric field (V/m)

P = Peak RF output power (mW)

G = EUT Antenna numeric gain (numeric)=

d = Separation distance between radiator and human body (m)

The formula can be changed to

We can change the formula to:

$$S = \frac{30 \times P \times G}{377 \times d^2} \quad \text{or, } d = \sqrt{\frac{30 \times P \times G}{377 \times S}}$$

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained.

2.3. Estimation Result

Mode	PK Output power (dBm)	Output power (mW)	Antenna Gain (dBi)	Antenna Gain (linear)	MPE Values (mW/cm ²)	MPE Limit (mW/cm ²)
Bluetooth Max power	2.87	1.94	0	1	0.00039	1

Note: The estimation distance is 20cm

Conclusion: No SAR evaluation required since transmitter power is below FCC threshold

END OF REPORT