

FCC PART 15.247


TEST REPORT

For

CLC Hong Kong Limited

2209, Concordia Plaza, North Tower, No.1 Science Museum Road, Tsim Sha Tsui East, Kowloon, Hong Kong

FCC ID: Y7WPLUMZ514

Report Type: Original Report	Product Type: Might Pro
Test Engineer:	Lion Xiao 
Report Number:	RDG150430001-00B
Report Date:	2015-05-08
Reviewed By:	Sula Huang  RF Leader
Test Laboratory:	Bay Area Compliance Laboratories Corp. (Dongguan) No.69 Pulongcun, Puxinhu Industrial Zone, Tangxia, Dongguan, Guangdong, China Tel: +86-769-86858888 Fax: +86-769-86858891 www.baclcorp.com.cn

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Dongguan). This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

TABLE OF CONTENTS

GENERAL INFORMATION.....	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
OBJECTIVE	4
RELATED SUBMITTAL(S)/GRANT(S).....	4
TEST METHODOLOGY	4
TEST FACILITY	5
SYSTEM TEST CONFIGURATION.....	6
DESCRIPTION OF TEST CONFIGURATION	6
EQUIPMENT MODIFICATIONS	6
EUT EXERCISE SOFTWARE	7
SUPPORT EQUIPMENT LIST AND DETAILS	7
EXTERNAL CABLE.....	7
BLOCK DIAGRAM OF TEST SETUP	8
SUMMARY OF TEST RESULTS	9
FCC §15.247 (i) & §1.1310 & §2.1093- RF EXPOSURE	10
APPLICABLE STANDARD	10
FCC §15.203 - ANTENNA REQUIREMENT.....	11
APPLICABLE STANDARD	11
ANTENNA CONNECTOR CONSTRUCTION	11
FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS	12
APPLICABLE STANDARD	12
MEASUREMENT UNCERTAINTY	12
EUT SETUP	12
EMI TEST RECEIVER SETUP.....	13
TEST PROCEDURE	13
CORRECTED AMPLITUDE & MARGIN CALCULATION	13
TEST EQUIPMENT LIST AND DETAILS.....	14
TEST RESULTS SUMMARY	14
TEST DATA	14
FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS.....	19
APPLICABLE STANDARD	19
MEASUREMENT UNCERTAINTY	19
EUT SETUP	19
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	20
TEST PROCEDURE	20
CORRECTED AMPLITUDE & MARGIN CALCULATION	21
TEST EQUIPMENT LIST AND DETAILS.....	21
TEST RESULTS SUMMARY	21
TEST DATA	21
FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH.....	32
APPLICABLE STANDARD	32
TEST PROCEDURE	32
TEST EQUIPMENT LIST AND DETAILS.....	32
TEST DATA	32
FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER.....	40

APPLICABLE STANDARD	40
TEST PROCEDURE	40
TEST EQUIPMENT LIST AND DETAILS.....	40
TEST DATA	40
FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE.....	42
APPLICABLE STANDARD	42
TEST PROCEDURE	42
TEST EQUIPMENT LIST AND DETAILS.....	42
TEST DATA	42
FCC §15.247(e) - POWER SPECTRAL DENSITY	47
APPLICABLE STANDARD	47
TEST PROCEDURE	47
TEST EQUIPMENT LIST AND DETAILS.....	47
TEST DATA	47

FINAL

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The *CLC Hong Kong Limited*'s product, model number: *Z514 (FCC ID: Y7WPLUMZ514)* (the "EUT") in this report was a *Might Pro*, which was measured approximately: 14.15 cm (L) x 7.35 cm (W) x 1.0 cm (H), rated input voltage: DC 3.7V rechargeable Li-ion battery or DC5V charging from adapter.

Adapter information: plum

Model: PMC43

Input: AC100-240V, 50/60Hz 0.15A

Output: DC5.0V, 1000 mA

All measurement and test data in this report was gathered from production sample serial number: 150430001 (Assigned by BACL, Dongguan). The EUT was received on 2015-04-30.

Objective

This report is prepared on behalf of *CLC Hong Kong Limited* in accordance with Part 2, Subpart J, Part 15, Subparts A, B and C of the Federal Communications Commission's rules

The tests were performed in order to determine the compliance of the EUT with FCC Part 15-Subpart C, section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Related Submittal(s)/Grant(s)

FCC Part 15B JBP submissions with FCC ID: Y7WPLUMZ514.

FCC Part 15C DSS submissions with FCC ID: Y7WPLUMZ514.

FCC Part 22H, 24E PCE submissions with FCC ID: Y7WPLUMZ514.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2009, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

All emissions measurement was performed and Bay Area Compliance Laboratories Corp. (Dongguan).

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.69 Pulongcun, Puxinhu Industrial Zone, Tangxia, Dongguan, Guangdong, China

Test site at Bay Area Compliance Laboratories Corp. (Dongguan) has been fully described in reports submitted to the Federal Communications Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on February 06, 2015. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2009.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 273710. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in testing mode, which was provided by manufacturer.
For 2.4GHz band, 11 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	7	2442
2	2417	8	2447
3	2422	9	2452
4	2427	10	2457
5	2432	11	2462
6	2437	/	/

For 802.11b, 802.11g, and 802.11n ht20 modes were tested with Channel 1, 6 and 11.

For Bluetooth LE mode, 40 channels are provided for testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	20	2442
1	2404	...	...
...	...	...	...
...	...	...	...
..	...	38	2478
19	2440	39	2480

EUT was tested with channel 0, 19 and 39.

The worst-case data rates are determined to be as follows for each mode based upon investigations by measuring the average power and PSD across all data rates bandwidths, and modulations.

Equipment Modifications

No modification was made to the EUT tested.

EUT Exercise Software

Test Mode	Test Software Version	Enginnering Mode		
802.11b	Test Frequency	2412MHz	2437MHz	2462MHz
	Data Rate	1Mbps	1Mbps	1Mbps
	Power Level Setting	22	22	22
802.11g	Test Frequency	2412MHz	2437MHz	2462MHz
	Data Rate	6Mbps	6Mbps	6Mbps
	Power Level Setting	19	19	19
802.11n ht20	Test Frequency	2412MHz	2437MHz	2462MHz
	Data Rate	MCS0	MCS0	MCS0
	Power Level Setting	17	17	17
BLE	Test Frequency	2402MHz	2440 MHz	2480MHz
	BLE	N/A	N/A	N/A


Support Equipment List and Details

Manufacturer	Description	Model	Serial Number

External Cable

Cable Description	Shielding Type	Ferrite Core	Length (m)	From Port	To
USB Cable	Yes	No	1.2	USB Port of Laptop	EUT
Earphone Cable	No	No	1.2	Audio Port of EUT	Earphone

Block Diagram of Test Setup



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
FCC §15.247 (i) & §1.1310 & §2.1093	RF Exposure	Compliance
§15.203	Antenna Requirement	Compliance
§15.207 (a)	AC Line Conducted Emissions	Compliance
§15.247(d)	Spurious Emissions at Antenna Port	Compliance
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliance
§15.247 (a)(2)	6 dB Emission Bandwidth	Compliance
§15.247(b)(3)	Maximum conducted output power	Compliance
§15.247(d)	100 kHz Bandwidth of Frequency Band Edge	Compliance
§15.247(e)	Power Spectral Density	Compliance

FCC §15.247 (i) & §1.1310 & §2.1093- RF EXPOSURE

Applicable Standard

According to §15.247(i) and §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

The SAR data please refer to the SAR report, report No.:RDG150430001-20.

FINAL

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.

Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

Antenna Connector Construction

The EUT has one integral antenna arrangement, which was permanently attached and the antenna gain is - 0.6dBi, fulfill the requirement of this section. Please refer to the EUT photos.

Result: Compliance.

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC§15.207

Measurement Uncertainty

Compliance or non-compliance with a disturbance limit shall be determined in the following manner:

If U_{lab} is less than or equal to U_{cispr} of Table 1, then:

- compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.

If U_{lab} is greater than U_{cispr} of Table 1, then:


- compliance is deemed to occur if no measured disturbance level, increased by $(U_{lab} - U_{cispr})$, exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level, increased by $(U_{lab} - U_{cispr})$, exceeds the disturbance limit.

Based on CISPR 16-4-2-2011, measurement uncertainty of conducted disturbance at mains port using AMN at Bay Area Compliance Laboratories Corp. (Dongguan) is 3.46 dB (150 kHz to 30 MHz).

Table 1 – Values of U_{cispr}

Measurement	U_{cispr}
Conducted disturbance at mains port using AMN (150 kHz to 30 MHz)	3.4 dB

EUT Setup



- Note: 1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.4-2009 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

The adapter was connected to a 120 VAC/60 Hz power source.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the adapter was connected to the first LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

Corrected Amplitude & Margin Calculation

The basic equation is as follows:

$$V_C = V_R + A_C + VDF$$

$$C_f = A_C + VDF$$

Herein,

V_C (cord. Reading): corrected voltage amplitude

V_R : reading voltage amplitude

A_C : attenuation caused by cable loss

VDF: voltage division factor of AMN

C_f : Correction Factor

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. For example, a margin of 7dB means the emission is 7dB below the maximum limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESCS 30	830245/006	2014-10-20	2015-10-20
R&S	L.I.S.N	ESH2-Z5	892107/021	2014-06-09	2015-06-09
R&S	Two-line V-network	ENV 216	3560.6550.12	2014-12-11	2015-12-11
R&S	Test Software	EMC32	Version8.53.0	N/A	N/A

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.207, with the worst margin reading of:

11.6 dB at 0.468757 MHz in the **Line** conducted mode for BLE.


Test Data**Environmental Conditions**

Temperature:	28.4 °C
Relative Humidity:	63 %
ATM Pressure:	100.3 kPa

The testing was performed by Lion Xiao on 2015-05-05.


Test Mode: Transmitting (Wi-Fi)

AC120 V, 60 Hz, Line:



Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.461346	42.3	9.000	L1	10.2	14.4	56.7	Compliance
0.536756	40.2	9.000	L1	10.1	15.8	56.0	Compliance
0.576662	36.8	9.000	L1	10.2	19.2	56.0	Compliance
0.720803	35.2	9.000	L1	10.4	20.8	56.0	Compliance
0.762149	34.2	9.000	L1	10.4	21.8	56.0	Compliance
1.548915	35.5	9.000	L1	10.4	20.5	56.0	Compliance

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.378019	24.1	9.000	L1	10.3	24.2	48.3	Compliance
0.457684	30.6	9.000	L1	10.2	16.1	46.7	Compliance
0.536756	31.0	9.000	L1	10.1	15.0	46.0	Compliance
0.614619	26.6	9.000	L1	10.3	19.4	46.0	Compliance
0.831967	25.5	9.000	L1	10.4	20.5	46.0	Compliance
1.407671	26.9	9.000	L1	10.4	19.1	46.0	Compliance


AC120 V, 60 Hz, Neutral:

Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.436318	40.1	9.000	N	10.2	17.0	57.1	Compliance
0.507637	42.7	9.000	N	10.1	13.3	56.0	Compliance
0.629488	39.5	9.000	N	10.3	16.5	56.0	Compliance
0.670921	38.3	9.000	N	10.4	17.7	56.0	Compliance
0.703777	39.3	9.000	N	10.4	16.7	56.0	Compliance
0.744147	37.3	9.000	N	10.4	18.7	56.0	Compliance

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.468757	28.9	9.000	N	10.1	17.6	46.5	Compliance
0.507637	32.6	9.000	N	10.1	13.4	46.0	Compliance
0.634524	30.5	9.000	N	10.3	15.5	46.0	Compliance
0.709407	31.0	9.000	N	10.4	15.0	46.0	Compliance
0.831967	29.9	9.000	N	10.4	16.1	46.0	Compliance
0.852094	30.2	9.000	N	10.4	15.8	46.0	Compliance


Test Mode: Transmitting (BLE)

AC120 V, 60 Hz, Line:



Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.436318	43.0	9.000	L1	10.2	14.1	57.1	Compliance
0.461346	43.1	9.000	L1	10.2	13.6	56.7	Compliance
0.507637	43.0	9.000	L1	10.1	13.0	56.0	Compliance
0.590613	41.0	9.000	L1	10.2	15.0	56.0	Compliance
0.629488	42.1	9.000	L1	10.3	13.9	56.0	Compliance
1.476605	37.5	9.000	L1	10.4	18.5	56.0	Compliance

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.274848	32.0	9.000	L1	10.3	19.0	51.0	Compliance
0.468757	34.9	9.000	L1	10.1	11.6	46.5	Compliance
0.507637	32.8	9.000	L1	10.1	13.2	46.0	Compliance
0.590613	25.6	9.000	L1	10.2	20.4	46.0	Compliance
0.624492	32.3	9.000	L1	10.3	13.7	46.0	Compliance
1.430284	30.3	9.000	L1	10.4	15.7	46.0	Compliance

AC120 V, 60 Hz, Neutral:

Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.436318	40.6	9.000	N	10.2	16.5	57.1	Compliance
0.465037	38.5	9.000	N	10.1	18.1	56.6	Compliance
0.511698	43.1	9.000	N	10.1	12.9	56.0	Compliance
0.629488	39.6	9.000	N	10.3	16.4	56.0	Compliance
0.715082	38.3	9.000	N	10.4	17.7	56.0	Compliance
0.825364	38.3	9.000	N	10.4	17.7	56.0	Compliance

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.511698	33.1	9.000	N	10.1	12.9	46.0	Compliance
0.629488	27.1	9.000	N	10.3	18.9	46.0	Compliance
0.805868	28.9	9.000	N	10.4	17.1	46.0	Compliance
0.831967	29.9	9.000	N	10.4	16.1	46.0	Compliance
0.852094	28.8	9.000	N	10.4	17.2	46.0	Compliance
0.900972	30.2	9.000	N	10.4	15.8	46.0	Compliance

FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS

Applicable Standard

FCC §15.247 (d); §15.209; §15.205;

Measurement Uncertainty

Compliance or non-compliance with a disturbance limit shall be determined in the following manner:

If U_{lab} is less than or equal to U_{cisp} of Table 2, then:

- compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.

If U_{lab} is greater than U_{cisp} of Table 2, then:

- compliance is deemed to occur if no measured disturbance level, increased by $(U_{lab} - U_{cisp})$, exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level, increased by $(U_{lab} - U_{cisp})$, exceeds the disturbance limit.

Based on CISPR 16-4-2-2011, measurement uncertainty of radiated emission at a distance of 3m at Bay Area Compliance Laboratories Corp. (Dongguan) is:

30M~200MHz: 5.0 dB

200M~1GHz: 6.2 dB

1G~6GHz: 4.45 dB


6G~18GHz: 5.23 dB


Table 2 – Values of U_{cisp}

Measurement	U_{cisp}
Radiated disturbance (electric field strength at an OATS or in a SAC) (30 MHz to 1000 MHz)	6.3 dB
Radiated disturbance (electric field strength in a FAR) (1 GHz to 6 GHz)	5.2 dB
Radiated disturbance (electric field strength in a FAR) (6 GHz to 18 GHz)	5.5 dB

EUT Setup

Below 1GHz:



Above 1GHz:

The radiated emission tests were performed in the 3 meters chamber test site, using the setup accordance with the ANSI C63.4-2009. The specification used was the FCC 15.209, and FCC 15.247 limits. The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

The adapter was connected to a 120 VAC/60 Hz power source.

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector
30 MHz – 1000 MHz	120 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1MHz	3 MHz	/	PK
	1MHz	10 Hz	/	Ave.

Test Procedure

During the radiated emission test, the adapter was connected to the first AC floor outlet.

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1 GHz, peak and Average detection modes for frequencies above 1 GHz.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Loss and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Loss} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESCI	100224	2014-05-09	2015-05-09
Sunol Sciences	Antenna	JB3	A060611-3	2014-07-28	2017-07-27
HP	Amplifier	8447E	2434A02181	2014-09-01	2015-09-01
R&S	Spectrum Analyzer	FSEM	DE31388	2014-05-09	2015-05-09
ETS LINDGREN	Horn Antenna	3115	000 527 35	2012-09-06	2015-09-06
Mini-Circuit	Amplifier	ZVA-213-S+	054201245	2015-02-19	2016-02-19
R&S	Spectrum Analyzer	FSP 38	100478	2014-05-09	2015-05-09
Ducommun Technologies	Horn Antenna	ARH-4223-02	1007726-01 1304	2014-06-16	2017-06-15
Quinstar	Amplifier	QLW-18405536-JO	15964001001	2014-09-06	2015-09-06

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Title 47, Part 15, Section 15.205, 15.209 and 15.247, with the worst margin reading of:

7.09dB at 2390 MHz in the Horizontal polarization for 802.11g Mode

Test Data

Environmental Conditions

Temperature:	24.3 °C
Relative Humidity:	63 %
ATM Pressure:	100.4 kPa

The testing was performed by Lion Xiao on 2015-05-03.

Test Mode: Transmitting

802.11b Mode

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector (PK/QP/AV)	Polar (H/V)	Factor (dB)					
Low Channel: 2412 MHz									
2412	72.03	PK	H	25.67	3.68	0.00	101.38	N/A	N/A
2412	67.87	AV	H	25.67	3.68	0.00	97.22	N/A	N/A
2412	69.4	PK	V	25.67	3.68	0.00	98.75	N/A	N/A
2412	65.71	AV	V	25.67	3.68	0.00	95.06	N/A	N/A
2390	28.68	PK	H	25.61	3.63	0.00	57.92	74.00	16.08
2390	15.67	AV	H	25.61	3.63	0.00	44.91	54.00	9.09
4824	39.91	PK	H	30.64	5.03	27.41	48.17	74.00	25.83
4824	26.91	AV	H	30.64	5.03	27.41	35.17	54.00	18.83
7236	33.55	PK	H	34.17	6.65	25.90	48.47	74.00	25.53
7236	20.2	AV	H	34.17	6.65	25.90	35.12	54.00	18.88
9648	30.34	PK	H	36.06	8.55	27.46	47.49	74.00	26.51
9648	17.72	AV	H	36.06	8.55	27.46	34.87	54.00	19.13
3921	36.89	PK	H	29.73	4.55	27.27	43.90	74.00	30.10
3921	22.18	AV	H	29.73	4.55	27.27	29.19	54.00	24.81
140.6	39.36	QP	H	13.19	1.45	21.42	32.58	43.50	10.92
Middle Channel: 2437 MHz									
2437	71.67	PK	H	25.74	3.75	0.00	101.16	N/A	N/A
2437	66.43	AV	H	25.74	3.75	0.00	95.92	N/A	N/A
2437	68.14	PK	V	25.74	3.75	0.00	97.63	N/A	N/A
2437	64.29	AV	V	25.74	3.75	0.00	93.78	N/A	N/A
4874	39.65	PK	H	30.77	5.14	27.42	48.14	74.00	25.86
4874	26.78	AV	H	30.77	5.14	27.42	35.27	54.00	18.73
7311	32.24	PK	H	34.35	6.74	25.88	47.45	74.00	26.55
7311	19.96	AV	H	34.35	6.74	25.88	35.17	54.00	18.83
9748	30.01	PK	H	36.30	8.61	27.24	47.68	74.00	26.32
9748	17.36	AV	H	36.30	8.61	27.24	35.03	54.00	18.97
3131	36.78	PK	H	27.62	6.93	27.43	43.90	74.00	30.10
3131	22.04	AV	H	27.62	6.93	27.43	29.16	54.00	24.84
3102	34.21	PK	H	27.53	6.85	27.45	41.14	74.00	32.86
3102	21.05	AV	H	27.53	6.85	27.45	27.98	54.00	26.02
140.6	39.27	QP	H	13.19	1.45	21.42	32.49	43.50	11.01
High Channel: 2462 MHz									
2462	71.42	PK	H	25.80	3.75	0.00	100.97	N/A	N/A
2462	66.98	AV	H	25.80	3.75	0.00	96.53	N/A	N/A
2462	68.55	PK	V	25.80	3.75	0.00	98.10	N/A	N/A
2462	64.46	AV	V	25.80	3.75	0.00	94.01	N/A	N/A
2483.5	31.35	PK	H	25.86	3.67	0.00	60.88	74.00	13.12
2483.5	16.75	AV	H	25.86	3.67	0.00	46.28	54.00	7.72
4924	33.27	PK	H	30.90	5.34	27.43	42.08	74.00	31.92
4924	20.41	AV	H	30.90	5.34	27.43	29.22	54.00	24.78
7386	33.05	PK	H	34.53	6.83	25.86	48.55	74.00	25.45
7386	19.59	AV	H	34.53	6.83	25.86	35.09	54.00	18.91
9848	29.65	PK	H	36.54	8.66	26.94	47.91	74.00	26.09
9848	17.26	AV	H	36.54	8.66	26.94	35.52	54.00	18.48
3693	36.43	PK	H	29.22	4.62	27.32	42.95	74.00	31.05
3693	21.79	AV	H	29.22	4.62	27.32	28.31	54.00	25.69
140.6	39.09	QP	H	13.19	1.45	21.42	32.31	43.50	11.19

802.11g Mode

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector (PK/QP/AV)	Polar (H/V)	Factor (dB)					
Low Channel: 2412 MHz									
2412	71.32	PK	H	25.67	3.68	0.00	100.67	N/A	N/A
2412	61.32	AV	H	25.67	3.68	0.00	90.67	N/A	N/A
2412	69.23	PK	V	25.67	3.68	0.00	98.58	N/A	N/A
2412	59.67	AV	V	25.67	3.68	0.00	89.02	N/A	N/A
2390	34.48	PK	H	25.61	3.63	0.00	63.72	74.00	10.28
2390	17.67	AV	H	25.61	3.63	0.00	46.91	54.00	7.09
4824	33.53	PK	H	30.64	5.03	27.41	41.79	74.00	32.21
4824	20.5	AV	H	30.64	5.03	27.41	28.76	54.00	25.24
7236	33.54	PK	H	34.17	6.65	25.90	48.46	74.00	25.54
7236	19.8	AV	H	34.17	6.65	25.90	34.72	54.00	19.28
9648	30.67	PK	H	36.06	8.55	27.46	47.82	74.00	26.18
9648	18.25	AV	H	36.06	8.55	27.46	35.40	54.00	18.60
3921	37.46	PK	H	29.73	4.55	27.27	44.47	74.00	29.53
3921	22.9	AV	H	29.73	4.55	27.27	29.91	54.00	24.09
140.6	39.48	QP	H	13.19	1.45	21.42	32.70	43.50	10.80
Middle Channel: 2437 MHz									
2437	71.85	PK	H	25.74	3.75	0.00	101.34	N/A	N/A
2437	61.94	AV	H	25.74	3.75	0.00	91.43	N/A	N/A
2437	68.92	PK	V	25.74	3.75	0.00	98.41	N/A	N/A
2437	58.32	AV	V	25.74	3.75	0.00	87.81	N/A	N/A
4874	33.31	PK	H	30.77	5.14	27.42	41.80	74.00	32.20
4874	20.29	AV	H	30.77	5.14	27.42	28.78	54.00	25.22
7311	33.21	PK	H	34.35	6.74	25.88	48.42	74.00	25.58
7311	19.64	AV	H	34.35	6.74	25.88	34.85	54.00	19.15
9748	30.33	PK	H	36.30	8.61	27.24	48.00	74.00	26.00
9748	17.89	AV	H	36.30	8.61	27.24	35.56	54.00	18.44
3102	37.22	PK	H	27.53	6.85	27.45	44.15	74.00	29.85
3102	22.63	AV	H	27.53	6.85	27.45	29.56	54.00	24.44
1362	34.23	PK	H	23.24	3.16	26.96	33.67	74.00	40.33
1362	21.68	AV	H	23.24	3.16	26.96	21.12	54.00	32.88
140.6	39.61	QP	H	13.19	1.45	21.42	32.83	43.50	10.67
High Channel: 2462 MHz									
2462	71.28	PK	H	25.80	3.75	0.00	100.83	N/A	N/A
2462	61.48	AV	H	25.80	3.75	0.00	91.03	N/A	N/A
2462	68.23	PK	V	25.80	3.75	0.00	97.78	N/A	N/A
2462	58.08	AV	V	25.80	3.75	0.00	87.63	N/A	N/A
2483.5	33.96	PK	H	25.86	3.67	0.00	63.49	74.00	10.51
2483.5	16.35	AV	H	25.86	3.67	0.00	45.88	54.00	8.12
4924	33.09	PK	H	30.90	5.34	27.43	41.90	74.00	32.10
4924	20.12	AV	H	30.90	5.34	27.43	28.93	54.00	25.07
7386	32.97	PK	H	34.53	6.83	25.86	48.47	74.00	25.53
7386	19.34	AV	H	34.53	6.83	25.86	34.84	54.00	19.16
9848	30.12	PK	H	36.54	8.66	26.94	48.38	74.00	25.62
9848	17.65	AV	H	36.54	8.66	26.94	35.91	54.00	18.09
3693	36.93	PK	H	29.22	4.62	27.32	43.45	74.00	30.55
3693	22.25	AV	H	29.22	4.62	27.32	28.77	54.00	25.23
140.6	39.84	QP	H	13.19	1.45	21.42	33.06	43.50	10.44

802.11 n ht20 Mode


Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector (PK/QP/AV)	Polar (H/V)	Factor (dB)					
Low Channel: 2412 MHz									
2412	70.68	PK	H	25.67	3.68	0.00	100.03	N/A	N/A
2412	58.32	AV	H	25.67	3.68	0.00	87.67	N/A	N/A
2412	67.22	PK	V	25.67	3.68	0.00	96.57	N/A	N/A
2412	55.59	AV	V	25.67	3.68	0.00	84.94	N/A	N/A
2390	32.67	PK	H	25.61	3.63	0.00	61.91	74.00	12.09
2390	16.17	AV	H	25.61	3.63	0.00	45.41	54.00	8.59
4824	33.04	PK	H	30.64	5.03	27.41	41.30	74.00	32.70
4824	20.34	AV	H	30.64	5.03	27.41	28.60	54.00	25.40
7236	33.32	PK	H	34.17	6.65	25.90	48.24	74.00	25.76
7236	19.83	AV	H	34.17	6.65	25.90	34.75	54.00	19.25
9648	30.39	PK	H	36.06	8.55	27.46	47.54	74.00	26.46
9648	18.06	AV	H	36.06	8.55	27.46	35.21	54.00	18.79
3921	37.35	PK	H	29.73	4.55	27.27	44.36	74.00	29.64
3921	22.54	AV	H	29.73	4.55	27.27	29.55	54.00	24.45
140.6	39.99	QP	H	13.19	1.45	21.42	33.21	43.50	10.29
Middle Channel: 2437 MHz									
2437	70.91	PK	H	25.74	3.75	0.00	100.40	N/A	N/A
2437	59.39	AV	H	25.74	3.75	0.00	88.88	N/A	N/A
2437	67.26	PK	V	25.74	3.75	0.00	96.75	N/A	N/A
2437	55.64	AV	V	25.74	3.75	0.00	85.13	N/A	N/A
4874	32.83	PK	H	30.77	5.14	27.42	41.32	74.00	32.68
4874	20.11	AV	H	30.77	5.14	27.42	28.60	54.00	25.40
7311	32.11	PK	H	34.35	6.74	25.88	47.32	74.00	26.68
7311	19.44	AV	H	34.35	6.74	25.88	34.65	54.00	19.35
9748	30.28	PK	H	36.30	8.61	27.24	47.95	74.00	26.05
9748	17.72	AV	H	36.30	8.61	27.24	35.39	54.00	18.61
3102	37.07	PK	H	27.53	6.85	27.45	44.00	74.00	30.00
3102	22.19	AV	H	27.53	6.85	27.45	29.12	54.00	24.88
3610	34.65	PK	H	29.04	4.61	27.28	41.02	74.00	32.98
3610	21.52	AV	H	29.04	4.61	27.28	27.89	54.00	26.11
140.6	39.53	QP	H	13.19	1.45	21.42	32.75	43.50	10.75
High Channel: 2462 MHz									
2462	69.99	PK	H	25.80	3.75	0.00	99.54	N/A	N/A
2462	58.54	AV	H	25.80	3.75	0.00	88.09	N/A	N/A
2462	68.13	PK	V	25.80	3.75	0.00	97.68	N/A	N/A
2462	56.36	AV	V	25.80	3.75	0.00	85.91	N/A	N/A
2483.5	30.65	PK	H	25.86	3.67	0.00	60.18	74.00	13.82
2483.5	16.32	AV	H	25.86	3.67	0.00	45.85	54.00	8.15
4924	32.72	PK	H	30.90	5.34	27.43	41.53	74.00	32.47
4924	19.98	AV	H	30.90	5.34	27.43	28.79	54.00	25.21
7386	32.76	PK	H	34.53	6.83	25.86	48.26	74.00	25.74
7386	19.2	AV	H	34.53	6.83	25.86	34.70	54.00	19.30
9848	30.01	PK	H	36.54	8.66	26.94	48.27	74.00	25.73
9848	17.47	AV	H	36.54	8.66	26.94	35.73	54.00	18.27
3693	36.81	PK	H	29.22	4.62	27.32	43.33	74.00	30.67
3693	21.88	AV	H	29.22	4.62	27.32	28.40	54.00	25.60
140.6	39.6	QP	H	13.19	1.45	21.42	32.82	43.50	10.68

BLE Mode


Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector (PK/QP/AV)	Polar (H/V)	Factor (dB)					
Low Channel: 2402 MHz									
2402	60.01	PK	H	25.65	3.66	0.00	89.32	N/A	N/A
2402	55.18	AV	H	25.65	3.66	0.00	84.49	N/A	N/A
2402	58.51	PK	V	25.65	3.66	0.00	87.82	N/A	N/A
2402	53.18	AV	V	25.65	3.66	0.00	82.49	N/A	N/A
2390	17.72	PK	H	25.61	3.63	0.00	46.96	74.00	27.04
2390	14.15	AV	H	25.61	3.63	0.00	43.39	54.00	10.61
4804	33.64	PK	H	30.59	5.06	27.41	41.88	74.00	32.12
4804	20.13	AV	H	30.59	5.06	27.41	28.37	54.00	25.63
7206	30.4	PK	H	34.09	6.61	25.91	45.19	74.00	28.81
7206	18.18	AV	H	34.09	6.61	25.91	32.97	54.00	21.03
9608	29.34	PK	H	35.96	8.53	27.55	46.28	74.00	27.72
9608	16.61	AV	H	35.96	8.53	27.55	33.55	54.00	20.45
4365	33.5	PK	H	29.83	5.00	26.92	41.41	74.00	32.59
4365	20.34	AV	H	29.83	5.00	26.92	28.25	54.00	25.75
134.76	37.08	QP	H	13.76	1.40	21.42	30.82	43.50	12.68
Middle Channel: 2440 MHz									
2440	60.17	PK	H	25.74	3.76	0.00	89.67	N/A	N/A
2440	54.81	AV	H	25.74	3.76	0.00	84.31	N/A	N/A
2440	58.11	PK	V	25.74	3.76	0.00	87.61	N/A	N/A
2440	52.66	AV	V	25.74	3.76	0.00	82.16	N/A	N/A
4880	33.72	PK	H	30.79	5.18	27.42	42.27	74.00	31.73
4880	20.82	AV	H	30.79	5.18	27.42	29.37	54.00	24.63
7320	30.83	PK	H	34.37	6.75	25.88	46.07	74.00	27.93
7320	18.62	AV	H	34.37	6.75	25.88	33.86	54.00	20.14
9760	29.56	PK	H	36.32	8.62	27.21	47.29	74.00	26.71
9760	17.15	AV	H	36.32	8.62	27.21	34.88	54.00	19.12
1437	33.84	PK	H	23.44	2.97	27.15	33.10	74.00	40.90
1437	20.91	AV	H	23.44	2.97	27.15	20.17	54.00	33.83
1176	33.5	PK	H	22.76	2.95	26.77	32.44	74.00	41.56
1176	20.24	AV	H	22.76	2.95	26.77	19.18	54.00	34.82
134.76	37.41	QP	H	13.76	1.40	21.42	31.15	43.50	12.35
High Channel: 2480 MHz									
2480	60.67	PK	H	25.85	3.68	0.00	90.20	N/A	N/A
2480	55.38	AV	H	25.85	3.68	0.00	84.91	N/A	N/A
2480	58.69	PK	V	25.85	3.68	0.00	88.22	N/A	N/A
2480	53.24	AV	V	25.85	3.68	0.00	82.77	N/A	N/A
2483.5	26.32	PK	H	25.86	3.67	0.00	55.85	74.00	18.15
2483.5	14.78	AV	H	25.86	3.67	0.00	44.31	54.00	9.69
4960	33.95	PK	H	31.00	5.34	27.43	42.86	74.00	31.14
4960	20.47	AV	H	31.00	5.34	27.43	29.38	54.00	24.62
7440	30.61	PK	H	34.66	6.89	25.97	46.19	74.00	27.81
7440	18.56	AV	H	34.66	6.89	25.97	34.14	54.00	19.86
9920	29.27	PK	H	36.71	8.71	26.66	48.03	74.00	25.97
9920	17.14	AV	H	36.71	8.71	26.66	35.90	54.00	18.10
3153	33.64	PK	H	27.69	6.93	27.41	40.85	74.00	33.15
3153	20.77	AV	H	27.69	6.93	27.41	27.98	54.00	26.02
134.76	37.5	QP	H	13.76	1.40	21.42	31.24	43.50	12.26

Conducted Spurious Emissions at Antenna Port


802.11b Low Channel




802.11b Middle Channel



802.11b High Channel




802.11g Low Channel




Marker 2 [T1]

RBW	100 kHz	RF Att	30 dB
VBW	300 kHz		
SWT	6.4 s	Unit	dB




Marker 2 [T1]


RBW	100 kHz	RF Att	30 dB
VBW	300 kHz		
SWT	6.4 s	Unit	dB



802.11n ht20 Low Channel




802.11n ht20 Middle Channel




802.11n ht20 High Channel

Fundamental




BLE Low Channel


Fundamental



BLE Middle Channel



BLE High Channel



FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH

Applicable Standard

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Test Procedure

According to KDB 558074 D01 DTS Meas Guidance v03r02 clause8.1 Option 1:

- Set RBW = 100 kHz.
- Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
- Detector = Peak.
- Trace mode = max hold.
- Sweep = auto couple.
- Allow the trace to stabilize.
- Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.



Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSEM	DE31388	2014-05-09	2015-05-09

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	24.3 °C
Relative Humidity:	63 %
ATM Pressure:	100.4 kPa


The testing was performed by Lion Xiao on 2015-05-03.

Test Mode: Transmitting


Test Result: Compliant. Please refer to the following table and plots.

Test mode	Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Limit (MHz)
802.11b	Low	2412	9.30	≥ 0.5
	Middle	2437	9.30	≥ 0.5
	High	2462	9.30	≥ 0.5
802.11g	Low	2412	16.43	≥ 0.5
	Middle	2437	16.43	≥ 0.5
	High	2462	16.43	≥ 0.5
802.11n20	Low	2412	17.72	≥ 0.5
	Middle	2437	17.64	≥ 0.5
	High	2462	17.72	≥ 0.5
BLE	Low	2402	0.745	≥ 0.5
	Middle	2440	0.741	≥ 0.5
	High	2480	0.741	≥ 0.5


802.11b Low Channel




802.11b Middle Channel




802.11b High Channel





802.11g Low Channel



802.11g Middle Channel



802.11g High Channel**802.11n ht20 Low Channel**

Ref Lvl 20 dBm Delta 1 [T1] -0.93 dB RBW 100 kHz RF Att 30 dB
 0.5 dB Offset 17.63527054 MHz SWT 10 ms Unit dBm

0.5 dB Offset

1 [T1] -9.89 dBm 2.4282244 GHz
 1 [T1] -0.93 dBm 17.63527054 MHz
 2 [T1] -4.80 dBm 2.43768136 GHz

D1 -4.8 dBm
 D2 -10.8 dBm


1MAX

Center 2.437 GHz 4 MHz/ Span 40 MHz


Date: 03.MAY 2015 15:00:54

[illegible]


BLE Low Channel



BLE Middle Channel



BLE High Channel



FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER

Applicable Standard

According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

Test Procedure

According to KDB 558074 D01 DTS Meas Guidance v03r02

1. Place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to test equipment.
3. Add a correction factor to the display.



Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Agilent	Wideband Power Sensor	N1921A	MY54210016	2014-11-03	2015-11-03
Agilent	Wideband Power Sensor	N1921A	MY54170013	2014-11-03	2015-11-03
Agilent	P-Series Power Meter	N1912A	MY5000448	2014-11-03	2015-11-03

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	24.3 °C
Relative Humidity:	63 %
ATM Pressure:	100.4 kPa

The testing was performed by Lion Xiao on 2015-05-03.

Test Mode: Transmitting (Wi-Fi)

Test Result: Compliant. Please refer to the following table.

Test mode	Channel	Frequency	Max Peak Conducted Output Power	Limit	Result
		(MHz)	(dBm)	(dBm)	
802.11b	Low	2412	16.36	30	PASS
	Middle	2437	16.13	30	PASS
	High	2462	16.07	30	PASS
802.11g	Low	2412	18.83	30	PASS
	Middle	2437	18.90	30	PASS
	High	2462	18.74	30	PASS
802.11n20	Low	2412	17.57	30	PASS
	Middle	2437	17.43	30	PASS
	High	2462	17.31	30	PASS

Test mode	Channel	Frequency	Max Conducted Average Output Power	Limit	Result
		(MHz)	(dBm)	(dBm)	
802.11b	Low	2412	15.04	30	PASS
	Middle	2437	14.92	30	PASS
	High	2462	14.89	30	PASS
802.11g	Low	2412	12.72	30	PASS
	Middle	2437	12.77	30	PASS
	High	2462	12.65	30	PASS
802.11n20	Low	2412	11.46	30	PASS
	Middle	2437	11.39	30	PASS
	High	2462	11.28	30	PASS

Test Mode: Transmitting (BLE)

Test mode	Channel	Frequency	Max Peak Conducted Output Power	Limit	Result
		(MHz)	(dBm)	(dBm)	
BLE	Low	2402	-6.53	30	PASS
	Middle	2440	-6.06	30	PASS
	High	2480	-5.65	30	PASS

FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSEM	DE31388	2014-05-09	2015-05-09

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data


Environmental Conditions



Temperature:	25.3°C
Relative Humidity:	56 %
ATM Pressure:	100.4 kPa



* The testing was performed by Lion Xiao on 2015-05-03.

Test mode: Transmitting


802.11b: Band Edge, Left Side




802.11g: Band Edge, Left Side**802.11g: Band Edge, Right Side**

802.11n ht20 Band Edge, Left Side**802.11n ht20 Band Edge, Right Side**

BLE Band Edge , Left Side



BLE Band Edge, Right Side



FCC §15.247(e) - POWER SPECTRAL DENSITY

Applicable Standard

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

Test Procedure

According to KDB 558074 D01 DTS Meas Guidance v03r02 clause10.2:

- a) Set analyzer center frequency to DTS channel center frequency.
- b) Set the span to 1.5 times the DTS bandwidth.
- c) Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- d) Set the VBW $\geq 3 \times \text{RBW}$.
- e) Detector = peak.
- f) Sweep time = auto couple.
- g) Trace mode = max hold.
- h) Allow trace to fully stabilize.
- i) Use the peak marker function to determine the maximum amplitude level within the RBW.
- j) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSEM	DE31388	2014-05-09	2015-05-09

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	25.3 °C
Relative Humidity:	56 %
ATM Pressure:	100.4kPa


* The testing was performed by Lion Xiao on 2015-05-03.

Test Mode: Transmitting


Test Result: Compliant. Please refer to the following table and plots

Test mode	Channel	Frequency (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)
802.11b	Low	2412	-17.44	≤ 8
	Middle	2437	-17.30	≤ 8
	High	2462	-17.36	≤ 8
802.11g	Low	2412	-17.49	≤ 8
	Middle	2437	-17.50	≤ 8
	High	2462	-17.47	≤ 8
802.11n20	Low	2412	-18.82	≤ 8
	Middle	2437	-18.65	≤ 8
	High	2462	-18.99	≤ 8
BLE	Low	2402	-21.84	≤ 8
	Middle	2440	-21.40	≤ 8
	High	2480	-21.18	≤ 8


Power Spectral Density, 802.11b Low Channel





Power Spectral Density, 802.11b Middle Channel




Power Spectral Density, 802.11b High Channel




Power Spectral Density, 802.11g Low Channel**Power Spectral Density, 802.11g Middle Channel**


Power Spectral Density, 802.11g High Channel




Power Spectral Density, 802.11n ht20 Low Channel




Power Spectral Density, 802.11n ht20 Middle Channel




Power Spectral Density, 802.11n ht20 High Channel




Power Spectral Density, BLE Low Channel



Power Spectral Density, BLE Middle Channel



Power Spectral Density, BLE High Channel



*****END OF REPORT*****