



RF TEST REPORT

Product Name: PCB-ElecMtrPart

Model Number: GLS-005

FCC ID: Y8E-GLS005

Issued For : Vision Metering, LLC

7 Ross Cannon St, York, South Carolina, 29745, United States

Issued By : Shenzhen LGT Test Service Co., Ltd.

Room 205, Building 13, Zone B, Zhenxiong Industrial Park,
No.177, Renmin West Road, Jinsha, Kengzi Street, Pingshan District, Shenzhen, Guangdong, China

Report Number: LGT25L386RF02

Sample Received Date: Dec. 19, 2025

Date of Test: Dec. 19, 2025 ~ Apr. 27, 2026

Date of Issue: Apr. 27, 2026

The test report is effective only with both signature and specialized stamp. This report shall not be reproduced except in full without the written approval of the Laboratory. The results in this report only apply to the tested sample.



TEST REPORT CERTIFICATION

Applicant: Vision Metering, LLC

Address: 7 Ross Cannon St, York, South Carolina, 29745, United States

Manufacturer: Vision Metering, LLC

Address: 7 Ross Cannon St, York, South Carolina, 29745, United States

Product Name: PCB-ElecMtrPart

Trademark: N/A

Model Number: GLS-005

Sample Status: Normal

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
FCC Part 15.249, Subpart C ANSI C63.10-2020	PASS

Prepared by:

Zane Shan

Zane Shan
Engineer

Approved by:

Vita Li

Vita Li
Technical Director





Table of Contents	Page
1. SUMMARY OF TEST RESULTS	5
1.1 TEST LABORATORY	6
1.2 MEASUREMENT UNCERTAINTY	6
2. GENERAL INFORMATION	7
2.1 GENERAL DESCRIPTION OF THE EUT	7
2.2 DESCRIPTION OF THE TEST MODES	8
2.3 TEST SOFTWARE AND POWER LEVEL	8
2.4 DESCRIPTION OF NECESSARY ACCESSORIES AND SUPPORT UNITS	9
2.5 EQUIPMENTS LIST	10
3. EMC EMISSION TEST	11
3.1 CONDUCTED EMISSION MEASUREMENT	11
3.2 TEST PROCEDURE	12
3.3 TEST SETUP	12
3.4 EUT OPERATING CONDITIONS	12
3.5 TEST RESULTS	12
4. RADIATED EMISSION MEASUREMENT	13
4.1 RADIATED EMISSION LIMITS	13
4.2 TEST PROCEDURE	14
4.3 TEST SETUP	15
4.4 EUT OPERATING CONDITIONS	15
4.5 FIELD STRENGTH CALCULATION	16
4.6 TEST RESULTS	17
4.7 TEST RESULTS (BAND EDGE REQUIREMENTS)	21
4.8 TEST RESULTS (EIRP REQUIREMENTS)	21
5. BANDWIDTH TEST	22
5.1 TEST PROCEDURE	22
5.2 TEST SETUP	22
5.3 EUT OPERATION CONDITIONS	22
5.4 TEST RESULTS	22
6. ANTENNA REQUIREMENT	24
6.1 STANDARD REQUIREMENT	24
6.2 EUT ANTENNA	24
APPENDIX I - MEASUREMENT PHOTOS	25



Revision History

Rev.	Issue Date	Revisions
00	Apr. 27, 2026	Initial Issue



1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:
KDB 558074 D01 Part 15.247 Meas Guidance v05r02.

FCC Part 15.249, Subpart C			
Standard Section	Test Item	Judgment	Remark
15.207	Conducted Emission	N/A	--
15.249	Radiated Spurious Emission	PASS	--
15.205	Restricted Band Edge Emission	PASS	--
15.249	20dB Bandwidth	Pass	--
15.203	Antenna Requirement	PASS	--

NOTE:

- (1) 'N/A' denotes test is not applicable in this Test Report.
- (2) All tests are according to ANSI C63.10-2020.



1.1 TEST LABORATORY

Company Name:	Shenzhen LGT Test Service Co., Ltd.
Address:	Room 205, Building 13, Zone B, Zhenxiong Industrial Park, No.177, Renmin West Road, Jinsha, Kengzi Street, Pingshan District, Shenzhen, Guangdong, China
Accreditation Certificate:	FCC Registration No.: 746540
	CAB ID: CN0136

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately **95** %.

No.	Item	Uncertainty
1	Occupied Channel Bandwidth	$\pm 0.46\%$
2	RF Output Power, Conducted	$\pm 0.71\text{dB}$
3	Power Spectral Density, Conducted	$\pm 1.57\text{dB}$
4	Unwanted Emission, Conducted	$\pm 0.63\text{dB}$
5	Conducted emission	$\pm 2.80\text{dB}$
6	All Emissions, Radiated (0.009-30MHz)	$\pm 2.16\text{dB}$
7	All Emissions, Radiated (30MHz-1GHz)	$\pm 4.61\text{dB}$
8	All Emissions, Radiated (1GHz-18GHz)	$\pm 5.49\text{dB}$
9	Temperature	$\pm 0.5^{\circ}\text{C}$
10	Humidity	$\pm 2\%$
11	Duty Cycle	$\pm 2.3\%$

Note: The measurement uncertainty is not included in the test result.



2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF THE EUT

Product Name:	PCB-ElecMtrPart	
Test Model Number:	GLS-005	
Series Number:	N/A	
Model Difference:	N/A	
Product Description:	Operation Frequency:	902.3-914.9MHz
	Modulation Type:	CSS
	Number Of Channel:	64
	Antenna Designation:	FPC Antenna
	Antenna Gain (dBi)	0.7
Channel List:	Please refer to the Note 3.	
Battery:	Capacity: 19000mAh Rated Voltage: 3.6V	
Hardware Version:	V	
Software Version:	11.0.12	
Connecting I/O Port(s):	Please refer to the Note 1.	

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User Manual.
2. The antenna information refers to the manufacturer provide report, applicable only to the tested sample identified in the report. Due to the incorrect antenna information, a series of problems such as the accuracy of the test results will be borne by the customer.
- 3.

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	902.3	17	905.5	33	908.7	49	911.9
2	902.5	18	905.7	34	908.9	50	912.1
3	902.7	19	905.9	35	909.1	51	912.3
4	902.9	20	906.1	36	909.3	52	912.5
5	903.1	21	906.3	37	909.5	53	912.7
6	903.3	22	906.5	38	909.7	54	912.9
7	903.5	23	906.7	39	909.9	55	913.1
8	903.7	24	906.9	40	910.1	56	913.3
9	903.9	25	907.1	41	910.3	57	913.5
10	904.1	26	907.3	42	910.5	58	913.7
11	904.3	27	907.5	43	910.7	59	913.9
12	904.5	28	907.7	44	910.9	60	914.1
13	904.7	29	907.9	45	911.1	61	914.3
14	904.9	30	908.1	46	911.3	62	914.5
15	905.1	31	908.3	47	911.5	63	914.7
16	905.3	32	908.5	48	911.7	64	914.9



2.2 DESCRIPTION OF THE TEST MODES

For conducted test items and radiated spurious emissions

Each of these EUT operation mode(s) or test configuration mode(s) mentioned below was evaluated respectively.

Worst Mode	Frequency (MHz)
Mode 1	902.3
Mode 2	908.5
Mode 3	914.9

Note:

(1) The measurements are performed at all Bit Rate of Transmitter, the worst data was reported.

2.3 TEST SOFTWARE AND POWER LEVEL

During testing channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level.

Test software Version	Test program: LORA	
nRF Connect for Desktop v5.2.0	Mode Or Modulation type	Power setting
	CSS Frequency Hoping	Default



2.4 DESCRIPTION OF NECESSARY ACCESSORIES AND SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Accessories Equipment

Description	Manufacturer	Model	S/N	Rating

Auxiliary Equipment

Description	Manufacturer	Model	S/N	Rating

Note:

- (1) For detachable type I/O cable should be specified the length in cm in 『Length』 column.
- (2) “YES” is means “with core”; “NO” is means “without core”.



2.5 EQUIPMENTS LIST

Radiated Test equipment					
Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Until
EMI Test Receiver	R&S	ESU8	100372	2025-03-06 2026-03-02	2026-03-05 2027-03-01
Active loop Antenna	ETS	6502	00049544	2025-03-11	2028-03-10
Spectrum Analyzer	Keysight	N9010B	MY60242508	2025-03-05 2026-03-03	2026-03-04 2027-03-02
Trilog Broadband Antenna (30M-1G)	SCHWARZBECK	VULB 9168	2705	2024-05-17	2027-05-16
Horn Antenna(1-18G)	SCHWARZBECK	3115	10SL0060	2025-03-10	2028-03-09
Horn Antenna(18-40G)	SCHWARZBECK	BBHA 9170	685	2023-10-23	2026-10-22
Pre-amplifier(30M-1G)	EMtrace	RP01A	02019	2025-03-06 2026-03-02	2026-03-05 2027-03-01
Pre-amplifier(1-26.5G)	Agilent	8449B	3008A4722	2025-03-06 2026-03-02	2026-03-05 2027-03-01
Pre-amplifier(18-40G)	SCHWARZBECK	BBV 9721	9721-019	2025-10-20	2026-10-19
Coaxial cables (9kHz-1GHz)	Juncoax	JMR600-NM NM-8M	N.A	2025-03-06 2026-03-03	2026-03-05 2027-03-02
Coaxial cables (1GHz-18GHz)	TaiHe	UCD460B-N MSM-1M9	N.A	2025-03-06 2026-03-03	2026-03-05 2027-03-02
Coaxial cables (18GHz-40GHz)	Junkosha Inc.	MWX241-05 000KMSKM S	N.A	2025-03-08 2026-03-03	2026-03-07 2027-03-02
Temperature& Humidity test chamber	AISRY	LX-1000L	171200018	2025-07-30	2026-07-29
Antenna Tower	SAEMC	BK-4AT-BS-D	SK20210930 08	N.A	N.A
Temperature & Humidity	JINGCHUANG	BT-3	N.A	2025-03-10 2026-03-05	2026-03-09 2027-03-04
Testing Software	EMC-I_V1.5.0.16_SKET				

RF Conducted Test equipment					
Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Until
Signal Analyzer	Keysight	N9020A	MY50530994	2025-03-05 2026-03-03	2026-03-04 2027-03-02
Power Sensor	R&S	NRP8S	104963	2025-03-06 2026-03-02	2026-03-05 2027-03-01
RF Automatic Test system	TST	TST PASS	293	2025-07-15	2026-07-14
MXG Vector Signal Generator	Keysight	N5182B	MY59100717	2025-03-05 2026-03-03	2026-03-04 2027-03-02
Temperature& Humidity test chamber	AISRY	LX-1000L	171200018	2025-07-30	2026-07-29
Attenuator	eastsheep	90db	N.A	2025-03-06 2026-03-02	2026-03-05 2027-03-01
Temperature & Humidity	JINGCHUANG	BT-3	N.A	2025-03-10 2026-03-05	2026-03-09 2027-03-04
Digital multimeter	MASTECH	MS8261	MBGBC8305 3	2025-03-05 2025-07-30	2026-03-04 2026-07-29
DC source	Keysight	E3634A	MY58036468	2025-03-06 2026-03-05	2026-03-05 2027-03-04
Testing Software	TST Pass_2.0.2				



3. EMC EMISSION TEST

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 POWER LINE CONDUCTED EMISSION LIMITS

The radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table.

FREQUENCY (MHz)	Conducted Emission limit (dBuV)	
	Quasi-peak	Average
0.15 -0.5	66 - 56 *	56 - 46 *
0.50 -5.0	56.00	46.00
5.0 -30.0	60.00	50.00

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of “ * ” marked band means the limitation decreases linearly with the logarithm of the frequency in the range.


The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

3.2 TEST PROCEDURE

- The EUT is 0.8 m from the horizontal ground plane and 0.4 m from the vertical ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments are powered from additional LISN(s). The LISN provides 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- LISN is at least 80 cm from the nearest part of EUT chassis.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

3.3 TEST SETUP



3.4 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

3.5 TEST RESULTS

N/A

Note: According to the electrical construction of the EUT, there is no AC terminal incorporated and no dedicated AC/DC adaptor. Therefore, this test is not applicable for this EUT.



4. RADIATED EMISSION MEASUREMENT

4.1 RADIATED EMISSION LIMITS

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on Part 15.249, Part 15.209(a) limit in the table below has to be followed.

Standard FCC 15.209

Frequencies (MHz)	Field Strength (micovolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
960~1000	500	3
Above 1000	Other:74.0 dB(μV)/m (Peak) 54.0 dB(μV)/m (Average)	3

Standard FCC 15.249

Frequency of Emission (MHz)	Field Strength of fundamental (millivolts /meter)	Field Strength of Harmonics (microvolts/meter)
900~928	50	500
2400~2483.5	50	500
5725~5875	50	500
24000~242500	250	2500

Notes:

- (1) Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in Section 15.209, whichever is the lesser attenuation.

Spectrum Parameter	Setting
Detector	Peak/AV
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB (emission in restricted band)	>20BW
VB (emission in restricted band)	=3xRB



Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~90kHz / RB 200Hz for PK & AV
	90kHz~110kHz / RB 200Hz for QP
	110kHz~490kHz / RB 200Hz for PK & AV
	490kHz~30MHz / RB 9kHz for QP
	30MHz~1000MHz / RB 120kHz for QP

4.2 TEST PROCEDURE


- The measuring distance at 3 m shall be used for measurements at frequency 0.009MHz up to 1GHz, and above 1GHz.
- The EUT was placed on the top of a rotating table 0.8 m (above 1GHz is 1.5 m) above the ground at a 3 m anechoic chamber test site. The table was rotated 360 degree to determine the position of the highest radiation.
- The height of the equipment shall be 0.8 m(above 1GHz is 1.5 m); the height of the test antenna shall vary between 1 m to 4 m. Horizontal and vertical polarization of the antenna are set to make the measurement.
- The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and QuasiPeak detector mode will be re-measured.
- If the Peak Mode measured value is compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and no additional QP Mode measurement was performed.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note:


Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported.

4.3 TEST SETUP


(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



(C) Radiated Emission Test-Up Frequency Above 1GHz



4.4 EUT OPERATING CONDITIONS

Please refer to section 3.4 of this report.



4.5 FIELD STRENGTH CALCULATION

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor (if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CL - AG$$

Where

FS = Field Strength

CL = Cable Attenuation Factor (Cable Loss)

RA = Reading Amplitude

AG = Amplifier Gain

AF = Antenna Factor

For example

Frequency	FS	RA	AF	CL	AG	Factor
(MHz)	(dB μ V/m)	(dB μ V/m)	(dB)	(dB)	(dB)	(dB)
300	40	58.1	12.2	1.6	31.9	-18.1


$$\text{Factor} = \text{AF} + \text{CL} - \text{AG}$$




4.6 TEST RESULTS

Results of Radiated Emissions (30MHz~1000MHz)

Project: LGT25L386	Test Engineer: zhangyangda
EUT: PCB-ElecMtrPart	Temperature: 23.1°C
M/N: GLS-005	Humidity: 58%RH
Test Voltage: DC 3.6V	Test Data: 2026-04-25
Test Mode: LoRa	
Note:	



No.	Frequency MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Detector	Polar
1*	46.611	7.27	20.71	27.98	40.00	-12.02	QP	Ver
2*	54.129	7.48	20.56	28.04	40.00	-11.96	QP	Ver
3*	81.289	10.00	16.50	26.50	40.00	-13.50	QP	Ver
4*	132.335	7.75	20.88	28.63	43.50	-14.87	QP	Ver
5*	210.420	10.70	17.89	28.59	43.50	-14.91	QP	Ver
6*	995.029	4.99	35.05	40.04	54.00	-13.96	QP	Ver



No.	Frequency MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Detector	Polar
1*	43.823	3.89	21.00	24.89	40.00	-15.11	QP	Hor
2*	81.289	8.46	16.50	24.96	40.00	-15.04	QP	Hor
3*	132.941	5.41	20.88	26.29	43.50	-17.21	QP	Hor
4*	155.979	4.41	22.13	26.54	43.50	-16.96	QP	Hor
5*	314.695	4.97	22.76	27.73	46.00	-18.27	QP	Hor
6*	980.236	5.27	35.12	40.39	54.00	-13.61	QP	Hor



Results of Radiated Emissions (Above 1000MHz)


Frequency (MHz)	Reading (dBμV)	Corrected Factor (dB)	Result (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector	Polarity
Low Channel (902.8 MHz)							
1804.22	56.38	-12.59	43.79	74.00	-30.21	PK	Vertical
1804.22	45.21	-12.59	32.62	54.00	-21.38	AV	Vertical
1804.17	55.31	-12.59	42.72	74.00	-31.28	PK	Horizontal
1804.17	45.26	-12.59	32.67	54.00	-21.33	AV	Horizontal
2706.46	55.04	-10.65	44.39	74.00	-29.61	PK	Vertical
2706.46	45.59	-10.65	34.94	54.00	-19.06	AV	Vertical
2706.70	54.93	-10.65	44.28	74.00	-29.72	PK	Horizontal
2706.70	45.25	-10.65	34.60	54.00	-19.40	AV	Horizontal
3608.77	57.48	-8.73	48.75	74.00	-25.25	PK	Vertical
3608.77	48.08	-8.73	39.35	54.00	-14.65	AV	Vertical
3608.89	57.94	-8.73	49.21	74.00	-24.79	PK	Horizontal
3608.89	46.97	-8.73	38.24	54.00	-15.76	AV	Horizontal
4511.23	60.08	-7.82	52.26	74.00	-21.74	PK	Vertical
4511.23	50.26	-7.82	42.44	54.00	-11.56	AV	Vertical
4511.22	60.90	-7.82	53.08	74.00	-20.92	PK	Horizontal
4511.22	50.05	-7.82	42.23	54.00	-11.77	AV	Horizontal
Middle Channel (915.6 MHz)							
1816.67	55.26	-12.59	42.67	74.00	-31.33	PK	Vertical
1816.67	45.24	-12.59	32.65	54.00	-21.35	AV	Vertical
1816.63	55.90	-12.59	43.31	74.00	-30.69	PK	Horizontal
1816.63	45.60	-12.59	33.01	54.00	-20.99	AV	Horizontal
2725.12	55.09	-10.65	44.44	74.00	-29.56	PK	Vertical
2725.12	44.12	-10.65	33.47	54.00	-20.53	AV	Vertical
2725.01	54.04	-10.65	43.39	74.00	-30.61	PK	Horizontal
2725.01	45.54	-10.65	34.89	54.00	-19.11	AV	Horizontal
3633.61	56.76	-8.73	48.03	74.00	-25.97	PK	Vertical
3633.61	48.41	-8.73	39.68	54.00	-14.32	AV	Vertical
3633.65	57.58	-8.73	48.85	74.00	-25.15	PK	Horizontal
3633.65	46.95	-8.73	38.22	54.00	-15.78	AV	Horizontal
4542.08	60.76	-7.82	52.94	74.00	-21.06	PK	Vertical
4542.08	50.46	-7.82	42.64	54.00	-11.36	AV	Vertical
4542.30	60.74	-7.82	52.92	74.00	-21.08	PK	Horizontal
4542.30	50.43	-7.82	42.61	54.00	-11.39	AV	Horizontal
High Channel (926.8 MHz)							
1828.74	55.70	-12.59	43.11	74.00	-30.89	PK	Vertical




1828.74	46.72	-12.59	34.13	54.00	-19.87	AV	Vertical
1828.87	55.91	-12.59	43.32	74.00	-30.68	PK	Horizontal
1828.87	45.59	-12.59	33.00	54.00	-21.00	AV	Horizontal
2743.39	54.25	-10.65	43.60	74.00	-30.40	PK	Vertical
2743.39	44.87	-10.65	34.22	54.00	-19.78	AV	Vertical
2743.39	54.44	-10.65	43.79	74.00	-30.21	PK	Horizontal
2743.39	45.00	-10.65	34.35	54.00	-19.65	AV	Horizontal
3658.00	57.65	-8.73	48.92	74.00	-25.08	PK	Vertical
3658.00	47.61	-8.73	38.88	54.00	-15.12	AV	Vertical
3658.19	56.86	-8.73	48.13	74.00	-25.87	PK	Horizontal
3658.19	47.09	-8.73	38.36	54.00	-15.64	AV	Horizontal
4572.62	60.67	-7.82	52.85	74.00	-21.15	PK	Vertical
4572.62	49.72	-7.82	41.90	54.00	-12.10	AV	Vertical
4572.75	60.15	-7.82	52.33	74.00	-21.67	PK	Horizontal
4572.75	50.63	-7.82	42.81	54.00	-11.19	AV	Horizontal




902.3MHz NVNT



908.5MHz NVNT



914.9MHz NVNT



Frequency (MHz)	T _{on} (ms)	Period (ms)	Duty Cycle (%)	Correction Factor (dB)	1/T (kHz)
902.3	0.204	0.312	65.38	1.85	4.9
908.5	0.204	0.312	65.38	1.85	4.9
914.9	0.204	0.312	65.38	1.85	4.9

Note: Duty Factor=20*LOG(Ton/Tp)



4.7 TEST RESULTS (BAND EDGE REQUIREMENTS)

Frequency (MHz)	Reading (dBμV)	Corrected Factor (dB)	Result (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector	Polarity
902.00	5.04	32.65	37.69	74.00	-36.31	PK	Vertical
902.00	4.72	32.65	37.37	74.00	-36.63	PK	Horizontal
928.00	7.13	33.29	40.42	74.00	-33.58	PK	Vertical
928.00	6.17	33.29	39.46	74.00	-34.54	PK	Horizontal

4.8 TEST RESULTS (EIRP REQUIREMENTS)

Frequency (MHz)	Meter Reading (dBμV/m)	Detector	Corrected Factor (dB)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polar
902.00	60.56	PK	32.75	93.31	94.00	-0.69	H
902.00	58.33	PK	32.75	91.08	94.00	-2.92	V
915.00	59.92	PK	32.86	92.78	94.00	-1.22	H
915.00	58.35	PK	32.86	91.21	94.00	-2.79	V
928.00	60.05	PK	33.12	93.17	94.00	-0.83	H
928.00	57.92	PK	33.12	91.04	94.00	-2.96	V




5. BANDWIDTH TEST

5.1 TEST PROCEDURE

- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below.
- Spectrum Setting : RBW= 30KHz, VBW $\geq$ RBW, Sweep time = Auto.

5.2 TEST SETUP



5.3 EUT OPERATION CONDITIONS

TX mode.


5.4 TEST RESULTS

Frequency (MHz)	99% OBW (KHz)	-20 dB Bandwidth (KHz)
902.3	70.492	71.05
908.5	70.242	70.56
914.9	69.875	69.82




Test Graphs


OBW NVNT 902.3MHz Ant1



OBW NVNT 908.5MHz Ant1



OBW NVNT 914.9MHz Ant1





6. ANTENNA REQUIREMENT

6.1 STANDARD REQUIREMENT

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

6.2 EUT ANTENNA

The EUT antenna is FPC Antenna. It comply with the standard requirement.



APPENDIX I - MEASUREMENT PHOTOS

Note: Please see the attached RF_Test Setup photos for FCC ID.

※※※※※END OF THE REPORT※※※※※