

FCC PART 15E TEST REPORT FOR CERTIFICATION  
On Behalf of

IAdea Corporation

Room Booking Panel

Model No.: IAD-18010A; IAD-18010L

FCC ID: Y9E-IAD-18010A

Prepared for : IAdea Corporation

3F, No.21, Lane 168, Xingshan Road, Neihu Dist. Taipei, 114  
Taiwan

Prepared By : Audix Technology (Shenzhen) Co., Ltd.

No. 6, Kefeng Road, Science & Technology Park,  
Nanshan District , Shenzhen, Guangdong, China

Tel: (0755) 26639496

Report Number : ACS-F23028

Date of Test : Jan.11~Feb.07, 2023

Date of Report : Mar.02, 2023

## TABLE OF CONTENTS

| Description                                                           | Page      |
|-----------------------------------------------------------------------|-----------|
| <b>1. SUMMARY OF STANDARDS AND RESULTS .....</b>                      | <b>5</b>  |
| 1.1. Description of Standards and Results .....                       | 5         |
| <b>2. GENERAL INFORMATION .....</b>                                   | <b>6</b>  |
| 2.1. Description of Equipment Under Test .....                        | 6         |
| 2.2. Feature of Equipment Under Test .....                            | 7         |
| 2.3. Test Information .....                                           | 8         |
| 2.4. Tested Supporting System Details .....                           | 9         |
| 2.5. Block diagram of connection between the EUT and simulators ..... | 9         |
| 2.6. Test Facility .....                                              | 10        |
| 2.7. Measurement Uncertainty (95% confidence levels, k=2) .....       | 10        |
| <b>3. POWER LINE CONDUCTED EMISSION TEST .....</b>                    | <b>11</b> |
| 3.1. Test Equipments .....                                            | 11        |
| 3.2. Block Diagram of Test Setup .....                                | 11        |
| 3.3. Power Line Conducted Emission Test Limits .....                  | 11        |
| 3.4. Configuration of EUT on Test .....                               | 11        |
| 3.5. Operating Condition of EUT .....                                 | 12        |
| 3.6. Test Procedure .....                                             | 12        |
| 3.7. Power Line Conducted Emission Test Results .....                 | 12        |
| <b>4. RADIATED EMISSION TEST .....</b>                                | <b>15</b> |
| 4.1. Test Equipments .....                                            | 15        |
| 4.2. Block Diagram of Test Setup .....                                | 16        |
| 4.3. Radiated Emission Limits .....                                   | 17        |
| 4.4. EUT Configuration on Test .....                                  | 18        |
| 4.5. Operating Condition of EUT .....                                 | 18        |
| 4.6. Test Procedure .....                                             | 18        |
| 4.7. Radiated Emission Test Results .....                             | 20        |
| <b>5. BAND EDGE COMPLIANCE TEST .....</b>                             | <b>52</b> |
| 5.1. Test Equipments .....                                            | 52        |
| 5.2. Limit .....                                                      | 52        |
| 5.3. Test Procedure .....                                             | 52        |
| 5.4. Test Results .....                                               | 52        |
| <b>6. 6dB &amp; 26dB &amp; 99% Bandwidth Test .....</b>               | <b>77</b> |
| 6.1. Test Equipments .....                                            | 77        |
| 6.2. Limit .....                                                      | 77        |
| 6.3. Test Procedure .....                                             | 77        |
| 6.4. Test Results .....                                               | 78        |
| <b>7. OUTPUT POWER TEST .....</b>                                     | <b>85</b> |
| 7.1. Test Equipments .....                                            | 85        |
| 7.2. Limit .....                                                      | 85        |
| 7.3. Test Procedure .....                                             | 85        |
| 7.4. Test Results .....                                               | 86        |
| <b>8. EQUIVALENT ISOTROPIC RADIATED POWER TEST .....</b>              | <b>90</b> |
| 8.1. Limit .....                                                      | 90        |
| 8.2. Test Procedure .....                                             | 90        |
| 8.3. Test Results .....                                               | 91        |
| <b>9. SPECTRAL DENSITY TEST .....</b>                                 | <b>92</b> |
| 9.1. Test Equipments .....                                            | 92        |
| 9.2. Limit .....                                                      | 92        |
| 9.3. Test Procedure .....                                             | 92        |

9.4. Test Results ..... 93

**10. FREQUENCY STABILITY MEASUREMENT .....97**

10.1. Test Equipments..... 97

10.2. Limit..... 97

10.3. Test Procedure..... 97

10.4. Test Result..... 98

**11. ANTENNA REQUIREMENT ..... 103**

11.1. Standard Applicable..... 103

11.2. Antenna Connected Construction ..... 103

**12. DEVIATION TO TEST SPECIFICATIONS ..... 104**

Appendix A. Photograph of Test

Appendix B. Photo of the EUT

**TEST REPORT**

Applicant : IAdea Corporation

Manufacturer : IAdea Corporation

Product : Room Booking Panel

FCC ID : Y9E-IAD-18010A

(A) Model No. : IAD-18010A; IAD-18010L

(B) Test Voltage : AC 120V/60Hz

Tested for comply with:  
FCC CFR47 Part 15 Subpart E

Test procedure used:

ANSI C63.10: 2020

KDB 789033 D02 GENERAL UNII TEST PROCEDURES NEW RULES V02R01

The device described above is tested by Audix Technology (Shenzhen) Co., Ltd. to confirm comply with all the FCC Part 15 Subpart E requirements. The test results are contained in this test report and Audix Technology (Shenzhen) Co., Ltd. is assumed full responsibility for the accuracy and completeness of these tests. Also, this report shows that the Equipment Under Test (EUT) is to be technically compliant with the FCC and IC requirements. This report contains data that are not covered by the NVLAP accreditation.

This Report is made under FCC Part 2.1075. No modifications were required during testing to bring this product into compliance.

This report applies to single evaluation of one sample of above mentioned product and shall not be reproduced in part without written approval of Audix Technology (Shenzhen) Co., Ltd.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government.

Date of Test : Jan.11~Feb.07, 2023 Report of date: Mar.02, 2023

Prepared by : Mia Zhao Reviewed by : Thomas Chen  
Mia Zhao / Assistant Thomas Chen / Assistant Manager

Approved &amp; Authorized Signer:

Signature: Sunny Lu / Manager

## 1. SUMMARY OF STANDARDS AND RESULTS

### 1.1. Description of Standards and Results

The EUT have been tested according to the applicable standards as referenced below.

| EMISSION                                 |                                                                  |         |
|------------------------------------------|------------------------------------------------------------------|---------|
| Description of Test Item                 | Standard                                                         | Results |
| Power Line Conducted Emission            | FCC Part 15: 15.207<br>FCC Part 15: 15.407(b)(6)                 | PASS    |
| Radiated Emission                        | FCC Part 15: 15.209<br>FCC Part 15: 15.205<br>FCC Part 15.407(b) | PASS    |
| Band Edge Compliance                     | FCC Part 15: 15.407(b)<br>FCC Part 15.205                        | PASS    |
| 6dB&26dB&99% Bandwidth Test              | FCC Part 15: 15.407(e)                                           | PASS    |
| Output Power Test                        | FCC Part 15: 15.407(a)(5)                                        | PASS    |
| Equivalent Isotropic Radiated Power Test | FCC Part 15: 15.407(h)(1)                                        | PASS    |
| Power Spectral Density Test              | FCC Part 15: 15.407(a)                                           | PASS    |
| Frequency Stability                      | FCC Part 15: 15.407(a)                                           | PASS    |
| Antenna requirement                      | FCC Part 15: 15.407(g)                                           | PASS    |

## 2. GENERAL INFORMATION

### 2.1. Description of Equipment Under Test

|                                         |                                                                                                                                                                                           |
|-----------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Applicant                               | IAdea Corporation                                                                                                                                                                         |
| Applicant Address                       | 3F, No.21, Lane 168, Xingshan Road, Neihu Dist. Taipei, 114 Taiwan                                                                                                                        |
| Manufacturer                            | IAdea Corporation                                                                                                                                                                         |
| Manufacturer Address                    | 3F, No.21, Lane 168, Xingshan Road, Neihu Dist. Taipei, 114 Taiwan                                                                                                                        |
| Product                                 | Room Booking Panel                                                                                                                                                                        |
| Model No.                               | IAD-18010A; IAD-18010L                                                                                                                                                                    |
| FCC ID                                  | Y9E-IAD-18010A                                                                                                                                                                            |
| AC Adapter                              | Manufacturer: Asian Power Devices Inc. Model No.: WB-24J12R<br>Input: 100-240V~50-60Hz, 0.7A Max<br>Output: DC 12V, 2.0A, 24W<br>DC Cable: Unshielded, Undetachable, 1.8m( with one core) |
| Sample Type                             | Prototype production                                                                                                                                                                      |
| Date of Receipt                         | Jan.05,2023                                                                                                                                                                               |
| Date of Test                            | Jan.11~Feb.07, 2023                                                                                                                                                                       |
| Remark: This report only for WIFI 5GHz. |                                                                                                                                                                                           |

## 2.2.Feature of Equipment Under Test

| Product Feature & Specification |                                                                                                |                              |
|---------------------------------|------------------------------------------------------------------------------------------------|------------------------------|
| Product                         | Room Booking Panel                                                                             |                              |
| Model No.                       | IAD-18010A                                                                                     |                              |
| Radio                           | IEEE802.11 a/b/g/n/ac                                                                          |                              |
| Power Source                    | <input checked="" type="checkbox"/> Commercial Power                                           | AC 100 ~ 240V, 50-60Hz, 0.7A |
|                                 | <input checked="" type="checkbox"/> External Power Source                                      | DC 12V, 2.0A, 24W            |
|                                 | <input type="checkbox"/> Lithium battery                                                       | DC V, mAh                    |
|                                 | <input type="checkbox"/> UM battery                                                            | DC V                         |
| 2.4GHz Wi-Fi                    |                                                                                                |                              |
| Support Modes                   | 802.11b/g/n20                                                                                  |                              |
| Frequency Range                 | 2412-2462MHz                                                                                   |                              |
| Type of Modulation              | 802.11b(DSSS): CCK, QPSK, BPSK;<br>802.11g/n(OFDM): 64QAM,16QAM, QPSK, BPSK                    |                              |
| Data Rate                       | 802.11b: 1/2/5.5/11 Mbps;<br>802.11g: 6/9/12/18/24/36/48/54 Mbps;<br>802.11n: up to 300Mbps    |                              |
| Channel Separation              | 5MHz                                                                                           |                              |
| 5GHz Wi-Fi                      |                                                                                                |                              |
| Support Modes                   | 802.11a/n20/n40/ac20/ac40/ac80                                                                 |                              |
| Frequency Range                 | 5180-5240MHz, 5745-5825MHz                                                                     |                              |
| Type of Modulation              | 802.11a/n (OFDM): QPSK, BPSK, 16QAM, 64QAM<br>802.11ac (OFDM): QPSK, BPSK, 16QAM, 64QAM,256QAM |                              |
| Data Rate                       | 802.11a: 6/9/12/18/24/36/48/54 Mbps;<br>802.11n: up to 300Mbps;<br>802.11ac: up to 433Mbps     |                              |
| Channel Separation              | 5MHz                                                                                           |                              |

| Antenna System    |                                                                                                                                                  |
|-------------------|--------------------------------------------------------------------------------------------------------------------------------------------------|
| Type of Antenna   | FPC Antenna                                                                                                                                      |
| Antenna Peak Gain | DTS Band (2400-2483.5MHz) Peak Gain: 2.3dBi.<br>U-NII-1 Band (5150-5250MHz) Peak Gain: 3.5dBi.<br>U-NII-3 Band (5725-5850MHz) Peak Gain: 5.1dBi. |

## 2.3.Test Information


A special test software (Ampak RFTtesttool V7.0) was used to control EUT work in Continuous TX mode(The duty cycle of the test signal is 100%), and select test channel, wireless mode and data rate.

| Tested mode, channel, and data rate information                                                                                     |                               |               |                    |
|-------------------------------------------------------------------------------------------------------------------------------------|-------------------------------|---------------|--------------------|
| Mode                                                                                                                                | data rate<br>(Mbps)(see Note) | Channel       | Frequency<br>(MHz) |
| IEEE 802.11a                                                                                                                        | 6                             | Low :CH36     | 5180               |
|                                                                                                                                     | 6                             | Middle: CH40  | 5200               |
|                                                                                                                                     | 6                             | High: CH48    | 5240               |
|                                                                                                                                     | 6                             | Low :CH149    | 5745               |
|                                                                                                                                     | 6                             | Middle: CH157 | 5785               |
|                                                                                                                                     | 6                             | High: CH165   | 5825               |
| IEEE 802.11nHT20                                                                                                                    | MCS0                          | Low :CH36     | 5180               |
|                                                                                                                                     | MCS0                          | Middle: CH40  | 5200               |
|                                                                                                                                     | MCS0                          | High: CH48    | 5240               |
|                                                                                                                                     | MCS0                          | Low :CH149    | 5745               |
|                                                                                                                                     | MCS0                          | Middle: CH157 | 5785               |
|                                                                                                                                     | MCS0                          | High: CH165   | 5825               |
| IEEE 802.11nHT40                                                                                                                    | MCS0                          | Low :CH38     | 5190               |
|                                                                                                                                     | MCS0                          | High: CH46    | 5230               |
|                                                                                                                                     | MCS0                          | Low :CH151    | 5755               |
|                                                                                                                                     | MCS0                          | High: CH159   | 5795               |
| IEEE 802.11acVHT20                                                                                                                  | MCS0                          | Low :CH36     | 5180               |
|                                                                                                                                     | MCS0                          | Middle: CH40  | 5200               |
|                                                                                                                                     | MCS0                          | High: CH48    | 5240               |
|                                                                                                                                     | MCS0                          | Low :CH149    | 5745               |
|                                                                                                                                     | MCS0                          | Middle: CH157 | 5785               |
|                                                                                                                                     | MCS0                          | High: CH165   | 5825               |
| IEEE 802.11acVHT40                                                                                                                  | MCS0                          | Low :CH38     | 5190               |
|                                                                                                                                     | MCS0                          | High: CH46    | 5230               |
|                                                                                                                                     | MCS0                          | Low :CH151    | 5755               |
|                                                                                                                                     | MCS0                          | High: CH159   | 5795               |
| IEEE 802.11acVHT80                                                                                                                  | MCS0                          | CH42          | 5210               |
|                                                                                                                                     | MCS0                          | CH155         | 5775               |
| Note: According exploratory test, EUT will have maximum output power in those data rate, so those data rate were used for all test. |                               |               |                    |

## 2.4. Tested Supporting System Details

| No. | Description | ACS No.                                                                                                                                                                  | Manufacturer | Model | Serial Number |
|-----|-------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------|-------|---------------|
| 1.  | Notebook    | N/A                                                                                                                                                                      | ACER         | ZOW   | N/A           |
|     |             | Power Cord(3C): Unshielded, Detachable, 1.8m<br>Power Adapter: Manufacturer: Lite-On, M/N: PA-1900-32<br>Data Cable: Shielded, Undetectable, 4.0m(Bond one ferrite core) |              |       |               |

## 2.5. Block diagram of connection between the EUT and simulators



**(EUT: Room Booking Panel)**

## 2.6. Test Facility

### Site Description

#### Name of Firm

: Audix Technology (Shenzhen) Co., Ltd.  
No. 6, Kefeng Road, Science & Technology Park,  
Nanshan District , Shenzhen, Guangdong, China

#### EMC Lab.

: Certificated by ISED, Canada  
Company Number: 5183A  
CAB identifier: CN0034  
Valid Date: Mar.31, 2023

: Certificated by FCC, USA  
Designation No.: CN5022  
Valid Date: Mar.31, 2023

: Accredited by NVLAP, USA  
NVLAP Code: 200372-0  
Valid Date: Mar.31, 2023

## 2.7. Measurement Uncertainty (95% confidence levels, k=2)

| Test Item                                                            | Uncertainty                                                      |
|----------------------------------------------------------------------|------------------------------------------------------------------|
| Uncertainty for Conduction emission test<br>in No. 1 Conduction      | $\pm 2.6\text{dB}(150\text{kHz to } 30\text{MHz})$               |
| Uncertainty for Radiation Emission test<br>in 3m chamber             | $\pm 3.8\text{dB}(30\sim 200\text{MHz, Polarization: H})$        |
|                                                                      | $\pm 3.8\text{dB}(30\sim 200\text{MHz, Polarization: V})$        |
|                                                                      | $\pm 4.0\text{dB}(200\text{M}\sim 1\text{GHz, Polarization: H})$ |
|                                                                      | $\pm 4.0\text{dB}(200\text{M}\sim 1\text{GHz, Polarization: V})$ |
| Uncertainty for Radiation Emission test<br>in 3m chamber(1GHz-25GHz) | $\pm 4.0\text{dB}(1\sim 6\text{GHz, Distance: } 3\text{m})$      |
|                                                                      | $\pm 4.0\text{dB}(6\sim 25\text{GHz, Distance: } 3\text{m})$     |
| Uncertainty for Radiated Spurious<br>Emission test in RF chamber     | $\pm 3.7\text{dB}(30\text{MHz}\sim 1000\text{MHz})$              |
|                                                                      | $\pm 3.3\text{dB}(1\sim 26.5\text{GHz})$                         |
| Uncertainty for Power density test                                   | $\pm 2.0\text{dB}$                                               |
| Uncertainty for Output power test                                    | $\pm 0.8\text{dB}$                                               |
| Uncertainty for Bandwidth test                                       | $\pm 83\text{kHz}$                                               |
| Uncertainty for DC power test                                        | $\pm 1\%$                                                        |
| Uncertainty for test site temperature and<br>humidity                | $\pm 0.6^{\circ}\text{C}$                                        |
|                                                                      | $\pm 3\%$                                                        |


### 3. POWER LINE CONDUCTED EMISSION TEST

#### 3.1. Test Equipments

| Item | Equipment         | Manufacturer    | Model No. | Serial No. | Last Cal. | Cal. Interval |
|------|-------------------|-----------------|-----------|------------|-----------|---------------|
| 1.   | 1# Shielding Room | AUDIX           | N/A       | N/A        | Sep.16,22 | 5 Year        |
| 2.   | EMI Test Receiver | Rohde & Schwarz | ESCI      | 100842     | Apr.07,22 | 1 Year        |
| 3.   | L.I.S.N.#1        | Rohde & Schwarz | ENV216    | 102160     | Oct.08,22 | 1 Year        |
| 4.   | L.I.S.N.#2        | Kyoritsu        | KNW-407   | 8-1628-5   | Apr.06,22 | 1 Year        |
| 5.   | RF Cable          | Eastsheep       | RG223     | 190424     | Oct.08,22 | 1Year         |
| 6.   | Terminator        | Hubersuhner     | 50Ω       | No.1       | Apr.06,22 | 1 Year        |
| 7.   | Test Software     | AUDIX           | e3        | 210616     | N/A       | N/A           |

Note: N/A means Not applicable.

#### 3.2. Block Diagram of Test Setup



□ :50Ω Terminator

#### 3.3. Power Line Conducted Emission Test Limits

| Frequency       | Maximum RF Line Voltage    |                         |
|-----------------|----------------------------|-------------------------|
|                 | Quasi-Peak Level<br>dB(μV) | Average Level<br>dB(μV) |
| 150kHz ~ 500kHz | 66 ~ 56*                   | 56 ~ 46*                |
| 500kHz ~ 5MHz   | 56                         | 46                      |
| 5MHz ~ 30MHz    | 60                         | 50                      |

Notes: 1. \* Decreasing linearly with logarithm of frequency.

2. The lower limit shall apply at the transition frequencies.

3. Emission Level (dBμV) = Factor (L.I.S.N.) (dB) + Cable Loss (dB) + Reading (Receiver) (dBμV)

#### 3.4. Configuration of EUT on Test

The following equipment are installed on Power Line Conducted Emission Test to meet the commission requirement and operating regulations in a manner which tends to maximize its emission characteristics in a normal application.

##### 3.4.1. Room Booking Panel (EUT)

Model No. : IAD-18010A

Serial No. : N/A

##### 3.4.2. Support Equipment: As Tested Supporting System Details, in Section 2.2.

### 3.5. Operating Condition of EUT

- 3.5.1. Setup the EUT as shown as Section 3.2.
- 3.5.2. Turn on the power of EUT.
- 3.5.3. PC run test software to control EUT work in Tx mode.

### 3.6. Test Procedure


The EUT was placed on a non-metallic table, 80cm above the ground plane. The EUT Power Via AC unit connected to the power mains through a line impedance stabilization network (L.I.S.N. #1). This provides a 50 ohm coupling impedance for the EUT (Please refer the block diagram of the test setup and photographs). The AC line are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to ANSI C63.10 on Conducted Emission Test.

The bandwidth of test receiver (R & S ESCI) is set at 9kHz.

The frequency range from 150kHz to 30MHz is checked.

### 3.7. Power Line Conducted Emission Test Results


**PASS.** (All emissions not reported below are too low against the prescribed limits.)



Site no :1# CE Data No :3  
 Dis./Lisn :2022 ENV216-N  
 Limit :FCC PART 15 C  
 Env./Ins. :22.7°C/49% Engineer :Sucy  
 Test Mode :WIFI 5G TX

| No | Freq (MHz) | LISN Factor (dB) | Cable Loss (dB) | Reading (dBuV) | Emission Level (dBuV) | Limits (dBuV) | Margin (dB) | Remark |
|----|------------|------------------|-----------------|----------------|-----------------------|---------------|-------------|--------|
| 1  | 0.154      | 9.60             | 0.01            | 42.90          | 52.51                 | 65.78         | 13.27       | QP     |
| 2  | 0.162      | 9.60             | 0.01            | 43.09          | 52.70                 | 65.34         | 12.64       | QP     |
| 3  | 0.190      | 9.60             | 0.01            | 39.90          | 49.51                 | 64.02         | 14.51       | QP     |
| 4  | 0.219      | 9.60             | 0.01            | 35.48          | 45.09                 | 62.88         | 17.79       | QP     |
| 5  | 0.277      | 9.60             | 0.01            | 33.41          | 43.02                 | 60.90         | 17.88       | QP     |
| 6  | 0.330      | 9.60             | 0.01            | 31.45          | 41.06                 | 59.44         | 18.38       | QP     |

Remarks: 1.Emission Level=LISN Factor+Cable Loss+Reading.  
 2.If the average limit is met when using a quasi-peak detector, the EUT shall be deemed to meet both limits and measurement with average detector is unnecessary.



Site no :1# CE Data No :4  
 Dis./Lisn :2022 ENV216-L  
 Limit :FCC PART 15 C  
 Env./Ins. :22.7°C/49% Engineer :Sucy  
 Test Mode :WIFI 5G TX

| No | Freq (MHz) | LISN Factor (dB) | Cable Loss (dB) | Reading (dBuV) | Emission Level (dBuV) | Limits (dBuV) | Margin (dB) | Remark |
|----|------------|------------------|-----------------|----------------|-----------------------|---------------|-------------|--------|
| 1  | 0.158      | 9.60             | 0.01            | 41.29          | 50.90                 | 65.56         | 14.66       | QP     |
| 2  | 0.166      | 9.60             | 0.01            | 42.41          | 52.02                 | 65.16         | 13.14       | QP     |
| 3  | 0.190      | 9.60             | 0.01            | 37.56          | 47.17                 | 64.02         | 16.85       | QP     |
| 4  | 0.198      | 9.60             | 0.01            | 37.49          | 47.10                 | 63.71         | 16.61       | QP     |
| 5  | 0.211      | 9.60             | 0.01            | 35.49          | 45.10                 | 63.18         | 18.08       | QP     |
| 6  | 0.242      | 9.60             | 0.01            | 32.05          | 41.66                 | 62.04         | 20.38       | QP     |

Remarks: 1.Emission Level=LISN Factor+Cable Loss+Reading.  
 2.If the average limit is met when using a quasi-peak detector, the EUT shall be deemed to meet both limits and measurement with average detector is unnecessary.

## 4. RADIATED EMISSION TEST

### 4.1. Test Equipments

#### 4.1.1. For frequency range 30 MHz ~1000MHz (In 3m Anechoic Chamber)

| Item | Equipment                 | Manufacturer    | Model No.   | Serial No. | Last Cal. | Cal. Interval |
|------|---------------------------|-----------------|-------------|------------|-----------|---------------|
| 1.   | 3#Chamber(NSA)            | AUDIX           | N/A         | N/A        | Aug.11,22 | 5 Year        |
| 2.   | 3#Chamber(SE)             | AUDIX           | N/A         | N/A        | Sep.16,22 | 5 Year        |
| 3.   | Signal Analyzer           | Rohde & Schwarz | FSV30       | 104050     | Apr.06,22 | 1 Year        |
| 4.   | Tri-log-Broadband Antenna | SCHWARZBECK     | VULB 9168   | 01317      | Otc.28,22 | 1 Year        |
| 5.   | NSA Cable                 | HUBER+SUHNER    | CFD400NL-LW | No.3       | Oct.09,22 | 1 Year        |
| 6.   | Coaxial Switch            | Anritsu         | MP59B       | 6201397223 | Apr.06,22 | 1 Year        |
| 7.   | EMI Test Receiver         | Rohde & Schwarz | ESR7        | 101547     | Apr.06,22 | 1 Year        |
| 8.   | Amplifier                 | HP              | 8447D       | 2944A11159 | Apr.06,22 | 1 Year        |
| 9.   | Test Software             | AUDIX           | e3          | 6.100913a  | N/A       | N/A           |

Note: N/A means Not applicable.


#### 4.1.2. For frequency range 1GHz~40GHz (In 3m Anechoic Chamber)

| Item | Equipment        | Manufacturer    | Model No.          | Serial No.  | Last Cal. | Cal. Interval |
|------|------------------|-----------------|--------------------|-------------|-----------|---------------|
| 1.   | 3mChamber(Svswr) | AUDIX           | N/A                | N/A         | Aug.09,22 | 5 Year        |
| 2.   | 3mChamber(SE)    | AUDIX           | N/A                | N/A         | Sep.16,22 | 5 Year        |
| 3.   | Signal Analyzer  | Rohde & Schwarz | FSV30              | 104050      | Apr.06,22 | 1 Year        |
| 4.   | Amplifier        | Agilent         | 83017A             | MY53270084  | Oct.09,22 | 1 Year        |
| 5.   | RF Cable         | EMCI            | EMC104-SM-SM-15000 | 190407      | Jul.01,22 | 1 Year        |
| 6.   | Test Software    | AUDIX           | e3                 | 6.100913a   | N/A       | N/A           |
| 7.   | Horn Antenna     | ETC             | MCTD 1209          | DRH15F03006 | Aug.12,22 | 1 Year        |


Note: N/A means Not applicable.

## 4.2. Block Diagram of Test Setup

For frequency range 30MHz-1000MHz



For frequency range 1GHz-40GHz



### 4.3.Radiated Emission Limits

For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

For transmitters operating in the 5.725-5.85 GHz band: All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

Unwanted emissions below 1 GHz and those emissions appearing within 15.205 restricted frequency bands must comply with the general field strength limits set forth in Section 15.209.

#### 4.3.1. 15.209 limits

| FREQUENCY<br>MHz | DISTANCE<br>Meters | FIELD STRENGTHS LIMIT                           |          |
|------------------|--------------------|-------------------------------------------------|----------|
|                  |                    | μV/m                                            | dB(μV)/m |
| 30 ~ 88          | 3                  | 100                                             | 40.0     |
| 88 ~ 216         | 3                  | 150                                             | 43.5     |
| 216 ~ 960        | 3                  | 200                                             | 46.0     |
| 960 ~ 1000       | 3                  | 500                                             | 54.0     |
| Above 1000       | 3                  | 74.0 dB(μV)/m (Peak)<br>54.0 dB(μV)/m (Average) |          |

- Remarks :
- (1) Emission Level (dBμV/m) = Reading (Receiver) (dBμV) + Antenna Factor (dB/m) + Cable Loss (dB)  
Emission Level (dBμV/m) = Reading (Spectrum) (dBμV) + Antenna Factor (dB/m) – Amp Factor (dB) + Cable Loss (dB)(above 1000MHz)
  - (2) The smaller limit shall apply at the cross point between two frequency bands.
  - (3) Distance is the distance in meters between the measuring instrument, antenna and the closest point of any part of the device or system.

#### 4.3.2. 15.205 Restricted bands of operation

| MHz                        | MHz                   | MHz             | GHz              |
|----------------------------|-----------------------|-----------------|------------------|
| 0.090 - 0.110              | 16.42 - 16.423        | 399.9 - 410     | 4.5 - 5.15       |
| <sup>1</sup> 0.495 - 0.505 | 16.69475 - 16.69525   | 608 - 614       | 5.35 - 5.46      |
| 2.1735 - 2.1905            | 16.80425 - 16.80475   | 960 - 1240      | 7.25 - 7.75      |
| 4.125 - 4.128              | 25.5 - 25.67          | 1300 - 1427     | 8.025 - 8.5      |
| 4.17725 - 4.17775          | 37.5 - 38.25          | 1435 - 1626.5   | 9.0 - 9.2        |
| 4.20725 - 4.20775          | 73 - 74.6             | 1645.5 - 1646.5 | 9.3 - 9.5        |
| 6.215 - 6.218              | 74.8 - 75.2           | 1660 - 1710     | 10.6 - 12.7      |
| 6.26775 - 6.26825          | 108 - 121.94          | 1718.8 - 1722.2 | 13.25 - 13.4     |
| 6.31175 - 6.31225          | 123 - 138             | 2200 - 2300     | 14.47 - 14.5     |
| 8.291 - 8.294              | 149.9 - 150.05        | 2310 - 2390     | 15.35 - 16.2     |
| 8.362 - 8.366              | 156.52475 - 156.52525 | 2483.5 - 2500   | 17.7 - 21.4      |
| 8.37625 - 8.38675          | 156.7 - 156.9         | 2690 - 2900     | 22.01 - 23.12    |
| 8.41425 - 8.41475          | 162.0125 - 167.17     | 3260 - 3267     | 23.6 - 24.0      |
| 12.29 - 12.293             | 167.72 - 173.2        | 3332 - 3339     | 31.2 - 31.8      |
| 12.51975 - 12.52025        | 240 - 285             | 3345.8 - 3358   | 36.43 - 36.5     |
| 12.57675 - 12.57725        | 322 - 335.4           | 3600 - 4400     | ( <sup>2</sup> ) |

#### 4.4.EUT Configuration on Test

The following equipment are installed on Power Line Conducted Emission Test to meet the commission requirement and operating regulations in a manner which tends to maximize its emission characteristics in a normal application.

##### 4.4.1. Room Booking Panel (EUT)

Model No. : IAD-18010A

Serial No. : N/A

##### 4.4.2. Support Equipment: As Tested Supporting System Details, in Section 2.2.

#### 4.5.Operating Condition of EUT

4.5.1. Setup the EUT and simulator as shown as Section 4.2.

4.5.2. Turn on the power of all equipments.

4.5.3. Let EUT work in Tx mode.

#### 4.6.Test Procedure

##### **Frequency below 30MHz:**

The EUT setup on the turn table which has 0.8 m height to the ground. The turn table rotated 360 degrees and antenna fixed to 1 m to find the maximum emission level. In order to find the maximum emission, all of the interface cables were manipulated according to ANSI C63.10 regulation.

EUT and its simulators are placed on a turn table, which is 0.8 meter high above ground for frequency 30MHz~1000MHz, 1.5 meter high above ground for frequency above 1GHz and put the absorbing with 2.4m(L)\*2.4m(W)\*0.3m(H) on the ground . The turn table can rotate 360 degrees to determine the position of the maximum emission level. Power on the EUT and let it working in test mode, then test it.EUT is set 3 meters away from the receiving antenna, which is mounted on a antenna tower. The antenna can be moved up and down between 1 meter and 4 meters to find out the maximum emission level. Broadband antenna (calibrated bilog antenna) is used as receiving antenna for frequency 30MHz~1000MHz, and the Horn antenna is used as receiving antenna for frequency above 1GHz. Both horizontal and vertical polarization of the antenna is set on Test. In order to find the maximum emission levels, all of the interface cables must be manipulated according to ANSI C63.10 on radiated emission Test.

For emissions below 1GHz and those emissions appearing within 15.205 restricted frequency bands use below procedure:

This test was performed with EUT in X, Y, Z position, and the worse case was found and reported.

The bandwidth of the EMI test receiver is set at 120kHz for frequency range from 30MHz to 1000 MHz.

Maximum Peak emission levels are measured by setting the analyzer as follows:

- (a) RBW = 1 MHz.
- (b) VBW  $\geq$  3 MHz.
- (c) Detector = Peak.
- (d) Sweep time = auto.
- (e) Trace mode = max hold.
- (f) Allow sweeps to continue until the trace stabilizes. Note that if the transmission is not continuous, the time required for the trace to stabilize will increase by a factor of approximately  $1/x$ , where  $x$  is the duty cycle. For example, at 50% duty cycle, the measurement time will increase by a factor of two relative to measurement time for continuous transmission.

Maximum Average emission levels are measured by setting the analyzer as follows:

- (a) RBW = 1 MHz.
- (b) VBW  $\geq$  3 MHz.
- (c) Detector = power averaging (rms), if  $\text{span}/(\# \text{ of points in sweep}) \leq \text{RBW}/2$ . Satisfying this condition may require increasing the number of points in the sweep or reducing the span. If the condition is not satisfied, the detector mode shall be set to peak.
- (d) Averaging type = power averaging (rms)  
As an alternative, the detector and averaging type may be set for linear voltage averaging. Some instruments require linear display mode to use linear voltage averaging. Log or dB averaging shall not be used.
- (e) Sweep time = auto.
- (f) Perform a trace average of at least 100 traces if the transmission is continuous. If the transmission is not continuous, the number of traces shall be increased by a factor of  $1/x$ , where  $x$  is the duty cycle. For example, with 50% duty cycle, at least 200 traces shall be averaged. (If a specific emission is demonstrated to be continuous—i.e., 100% duty cycle—rather than turning on and off with the transmit cycle, at least 100 traces shall be averaged.)
- (g) If tests are performed with the EUT transmitting at a duty cycle less than 98%, a correction factor shall be added to the measurement results prior to comparing to the emission limit to compute the emission level that would have been measured had the test been performed at 100% duty cycle. The correction factor is computed as follows:
  - If power averaging (rms) mode was used in step (iv) above, the correction factor is  $10 \log (1/x)$ , where  $x$  is the duty cycle. For example, if the transmit duty cycle was 50%, then 3 dB must be added to the measured emission levels.
  - If linear voltage averaging mode was used in step (iv) above, the correction factor is  $20 \log (1/x)$ , where  $x$  is the duty cycle. For example, if the transmit duty cycle was 50%, then 6 dB must be added to the measured emission levels.
  - If a specific emission is demonstrated to be continuous (100% duty cycle) rather than turning on and off with the transmit cycle, no duty cycle correction is required for that emission.

For the emissions above 1GHz and not appearing within 15.205 restricted frequency bands use below procedure:

- (1).The maximum emission at 3m distance was measured and recorded with receive antenna in both vertical and horizontal by rotating the turntable and by lowering the receive antenna.
- (2).The EUT was then removed and replaced with a substitution antenna in the same position and the substitution antenna must have the same polarization with the receive antenna.
- (3). A signal which have the same frequency obtained in step 2 was fed to the substitution, the receive antenna was raised and lowered to obtain a maximum reading at the test receiver, the level of the signal generator was adjusted until the measured field strength level in step 2 was obtained, recorded the level of the signal generator.
- (4).Repeated step 4 with both antenna polarizations
- (5).The spurious emissions is equal to the power supplied by the signal generator and corrections due to the gain of the substitution antenna and the cable loss between the signal generator and the substitution antenna. or use procedure (6).
- (6). Per KDB789033 clause H 2)d).if the test distance is 3m,the  $EIRP(dBm) = E(dB\mu V/m) - 95.2$   
Get the result of all unwanted emission outside the restricted band is less than the -27dBm/MHz.

We had checked frequency range that is 30MHz to 10<sup>th</sup> harmonic (40GHz) and no any emissions were found from 18GHz to 40GHz, so the radiated emission from 18GHz to 40GHz were not record.

#### 4.7.Radiated Emission Test Results


**PASS.**

All the emissions from 30MHz to 1 GHz were comply with 15.209 limits.

All other emission comply with 15.407 (b)(1) requirements.

Note: The emissions (9kHz~30MHz) not reported for there is no emission be found.

## Duty cycle




Note: The duty cycle of the test signal is 100%.

### Frequency: 30MHz~1GHz

Data: 3

File: E:\2023 Report Data\T\TPV\A1Z2301002-RF.EM6 (4)


Date: 2023-02-07



Site no. : 3m Chamber Data no. : 3  
 Dis. / Ant. : 3m 2022 VULB 9168-01317 Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15 C (3M)  
 Env. / Ins. : 23.1°C/56% Engineer : Abel  
 Test Mode : WIFI 5G TX

| No. | Freq.<br>(MHz) | Ant.<br>Factor<br>(dB/m) | Cable<br>Loss<br>(dB) | Reading<br>(dBuV) | Emission<br>Level<br>(dBuV/m) | Limits<br>(dBuV/m) | Margin<br>(dB) | Remark |
|-----|----------------|--------------------------|-----------------------|-------------------|-------------------------------|--------------------|----------------|--------|
| 1   | 55.220         | 19.60                    | 0.74                  | -2.28             | 18.06                         | 40.00              | 21.94          | QP     |
| 2   | 139.610        | 19.00                    | 1.18                  | 2.41              | 22.59                         | 43.50              | 20.91          | QP     |
| 3   | 241.460        | 17.63                    | 1.56                  | 8.56              | 27.75                         | 46.00              | 18.25          | QP     |
| 4   | 375.320        | 21.20                    | 1.99                  | 5.11              | 28.30                         | 46.00              | 17.70          | QP     |
| 5   | 625.580        | 26.08                    | 2.71                  | 1.86              | 30.65                         | 46.00              | 15.35          | QP     |
| 6   | 875.840        | 28.52                    | 3.36                  | 0.07              | 31.95                         | 46.00              | 14.05          | QP     |

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.  
 2. The emission levels that are 20dB below the official limit are not reported.





Site no. : 3m Chamber Data no. : 4  
 Dis. / Ant. : 3m 2022 VULB 9168-01317 Ant. pol. : VERTICAL  
 Limit : FCC PART 15 C (3M)  
 Env. / Ins. : 23.1°C/56% Engineer : Abel  
 Test Mode : WIFI 5G TX

| No. | Freq.<br>(MHz) | Ant.<br>Factor<br>(dB/m) | Cable<br>Loss<br>(dB) | Emission          |                   |                    |                |        |
|-----|----------------|--------------------------|-----------------------|-------------------|-------------------|--------------------|----------------|--------|
|     |                |                          |                       | Reading<br>(dBuV) | Level<br>(dBuV/m) | Limits<br>(dBuV/m) | Margin<br>(dB) | Remark |
| 1   | 32.910         | 18.60                    | 0.57                  | 7.39              | 26.56             | 40.00              | 13.44          | QP     |
| 2   | 56.190         | 19.60                    | 0.75                  | 10.58             | 30.93             | 40.00              | 9.07           | QP     |
| 3   | 137.670        | 18.70                    | 1.17                  | 3.33              | 23.20             | 43.50              | 20.30          | QP     |
| 4   | 263.770        | 18.20                    | 1.65                  | 4.96              | 24.81             | 46.00              | 21.19          | QP     |
| 5   | 625.580        | 26.08                    | 2.71                  | 4.74              | 33.53             | 46.00              | 12.47          | QP     |
| 6   | 875.840        | 28.52                    | 3.36                  | 0.18              | 32.06             | 46.00              | 13.94          | QP     |



Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.  
 2. The emission levels that are 20dB below the official limit are not reported.

### Frequency: 1GHz~18GHz U-NII-1 Band:



| No. | Freq.<br>(MHz) | Ant.<br>Factor<br>(dB/m) | Cable<br>Loss<br>(dB) | Reading<br>(dBuV) | Amp<br>factor<br>(dB) | Emission<br>Level<br>(dBuV/m) | Limits<br>(dBuV/m) | Margin<br>(dB) | Remark |
|-----|----------------|--------------------------|-----------------------|-------------------|-----------------------|-------------------------------|--------------------|----------------|--------|
| 1   | 5180.00        | 33.27                    | 3.47                  | 92.72             | 33.66                 | 95.80                         | -----              | -----          | Peak   |
| 2   | 10360.00       | 38.27                    | 4.91                  | 46.38             | 33.95                 | 55.61                         | 68.20              | 12.59          | Peak   |



Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading  
-Amp factor.  
2. The emission levels that are 20dB below the official  
limit are not reported.



| No. | Freq.<br>(MHz) | Ant.<br>Factor<br>(dB/m) | Cable<br>Loss<br>(dB) | Reading<br>(dBuV) | Amp<br>factor<br>(dB) | Emission<br>Level<br>(dBuV/m) | Limits<br>(dBuV/m) | Margin<br>(dB) | Remark |
|-----|----------------|--------------------------|-----------------------|-------------------|-----------------------|-------------------------------|--------------------|----------------|--------|
| 1   | 5180.00        | 33.27                    | 3.47                  | 89.40             | 33.66                 | 92.48                         | -----              | -----          | Peak   |
| 2   | 10360.00       | 38.27                    | 4.91                  | 45.51             | 33.95                 | 54.74                         | 68.20              | 13.46          | Peak   |



Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading  
-Amp factor.  
2. The emission levels that are 20dB below the official  
limit are not reported.

FCC ID: Y9E-IAD-18010A



| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark |
|-----|-------------|--------------------|-----------------|----------------|-----------------|-------------------------|-----------------|-------------|--------|
| 1   | 5200.00     | 33.30              | 3.48            | 93.87          | 33.66           | 96.99                   | 68.20           | 13.37       | Peak   |
| 2   | 10400.00    | 38.30              | 4.92            | 45.52          | 33.91           | 54.83                   | 68.20           | 13.37       | Peak   |



Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading  
 -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.



| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark |
|-----|-------------|--------------------|-----------------|----------------|-----------------|-------------------------|-----------------|-------------|--------|
| 1   | 5200.00     | 33.30              | 3.48            | 88.58          | 33.66           | 91.70                   | 68.20           | 12.22       | Peak   |
| 2   | 10400.00    | 38.30              | 4.92            | 46.67          | 33.91           | 55.98                   | 68.20           | 12.22       | Peak   |



Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading  
 -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.

FCC ID: Y9E-IAD-18010A



| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark |
|-----|-------------|--------------------|-----------------|----------------|-----------------|-------------------------|-----------------|-------------|--------|
| 1   | 5240.00     | 33.17              | 3.49            | 93.96          | 33.65           | 96.97                   | 68.20           | 13.83       | Peak   |
| 2   | 10480.00    | 38.30              | 4.95            | 44.98          | 33.86           | 54.37                   | 68.20           | 13.83       | Peak   |



Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.



| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark |
|-----|-------------|--------------------|-----------------|----------------|-----------------|-------------------------|-----------------|-------------|--------|
| 1   | 5240.00     | 33.17              | 3.49            | 89.42          | 33.65           | 92.43                   | 68.20           | 13.25       | Peak   |
| 2   | 10480.00    | 38.30              | 4.95            | 45.56          | 33.86           | 54.95                   | 68.20           | 13.25       | Peak   |



Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.

FCC ID: Y9E-IAD-18010A



| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading factor (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark |
|-----|-------------|--------------------|-----------------|-----------------------|-----------------|-------------------------|-----------------|-------------|--------|
| 1   | 5180.00     | 33.27              | 3.47            | 91.21                 | 33.66           | 94.29                   | 68.20           | 13.30       | Peak   |
| 2   | 10360.00    | 38.27              | 4.91            | 45.67                 | 33.95           | 54.90                   | 68.20           | 13.30       | Peak   |



Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.



| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading factor (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark |
|-----|-------------|--------------------|-----------------|-----------------------|-----------------|-------------------------|-----------------|-------------|--------|
| 1   | 5180.00     | 33.27              | 3.47            | 88.03                 | 33.66           | 91.11                   | 68.20           | 13.02       | Peak   |
| 2   | 10360.00    | 38.27              | 4.91            | 45.95                 | 33.95           | 55.18                   | 68.20           | 13.02       | Peak   |



Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.

FCC ID: Y9E-IAD-18010A



| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading factor (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark |
|-----|-------------|--------------------|-----------------|-----------------------|-----------------|-------------------------|-----------------|-------------|--------|
| 1   | 5200.00     | 33.30              | 3.48            | 93.34                 | 33.66           | 96.46                   | 68.20           | 13.09       | Peak   |
| 2   | 10400.00    | 38.30              | 4.92            | 45.80                 | 33.91           | 55.11                   | 68.20           | 13.09       | Peak   |



Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.



| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading factor (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark |
|-----|-------------|--------------------|-----------------|-----------------------|-----------------|-------------------------|-----------------|-------------|--------|
| 1   | 5200.00     | 33.30              | 3.48            | 87.72                 | 33.66           | 90.84                   | 68.20           | 12.68       | Peak   |
| 2   | 10400.00    | 38.30              | 4.92            | 46.21                 | 33.91           | 55.52                   | 68.20           | 12.68       | Peak   |



Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.

FCC ID: Y9E-IAD-18010A



| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading factor (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark |
|-----|-------------|--------------------|-----------------|-----------------------|-----------------|-------------------------|-----------------|-------------|--------|
| 1   | 5240.00     | 33.17              | 3.49            | 92.72                 | 33.65           | 95.73                   | 68.20           | 13.11       | Peak   |
| 2   | 10480.00    | 38.30              | 4.95            | 45.70                 | 33.86           | 55.09                   | 68.20           | 13.11       | Peak   |



Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.



| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading factor (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark |
|-----|-------------|--------------------|-----------------|-----------------------|-----------------|-------------------------|-----------------|-------------|--------|
| 1   | 5240.00     | 33.17              | 3.49            | 88.11                 | 33.65           | 91.12                   | 68.20           | 12.43       | Peak   |
| 2   | 10480.00    | 38.30              | 4.95            | 46.38                 | 33.86           | 55.77                   | 68.20           | 12.43       | Peak   |



Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.

FCC ID: Y9E-IAD-18010A



| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading factor (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark |
|-----|-------------|--------------------|-----------------|-----------------------|-----------------|-------------------------|-----------------|-------------|--------|
| 1   | 5190.00     | 33.27              | 3.47            | 85.03                 | 33.66           | 88.11                   | 68.20           | 13.41       | Peak   |
| 2   | 10380.00    | 38.28              | 4.92            | 45.52                 | 33.93           | 54.79                   | 68.20           | 13.41       | Peak   |



Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.



| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading factor (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark |
|-----|-------------|--------------------|-----------------|-----------------------|-----------------|-------------------------|-----------------|-------------|--------|
| 1   | 5190.00     | 33.27              | 3.47            | 89.11                 | 33.66           | 92.19                   | 68.20           | 11.90       | Peak   |
| 2   | 10380.00    | 38.28              | 4.92            | 47.03                 | 33.93           | 56.30                   | 68.20           | 11.90       | Peak   |



Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.

FCC ID: Y9E-IAD-18010A



| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading factor (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark |
|-----|-------------|--------------------|-----------------|-----------------------|-----------------|-------------------------|-----------------|-------------|--------|
| 1   | 5230.00     | 33.17              | 3.49            | 91.04                 | 33.65           | 94.05                   | 68.20           | 13.49       | Peak   |
| 2   | 10460.00    | 38.30              | 4.94            | 45.35                 | 33.88           | 54.71                   | 68.20           | 13.49       | Peak   |



Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.



| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading factor (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark |
|-----|-------------|--------------------|-----------------|-----------------------|-----------------|-------------------------|-----------------|-------------|--------|
| 1   | 5230.00     | 33.17              | 3.49            | 85.30                 | 33.65           | 88.31                   | 68.20           | 12.87       | Peak   |
| 2   | 10460.00    | 38.30              | 4.94            | 45.97                 | 33.88           | 55.33                   | 68.20           | 12.87       | Peak   |



Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.

FCC ID: Y9E-IAD-18010A



| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading factor (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark |
|-----|-------------|--------------------|-----------------|-----------------------|-----------------|-------------------------|-----------------|-------------|--------|
| 1   | 5180.00     | 33.27              | 3.47            | 88.88                 | 33.66           | 91.96                   | 68.20           | 13.13       | Peak   |
| 2   | 10360.00    | 38.27              | 4.91            | 45.84                 | 33.95           | 55.07                   | 68.20           | 13.13       | Peak   |



Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.



| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading factor (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark |
|-----|-------------|--------------------|-----------------|-----------------------|-----------------|-------------------------|-----------------|-------------|--------|
| 1   | 5180.00     | 33.27              | 3.47            | 94.33                 | 33.66           | 97.41                   | 68.20           | 13.47       | Peak   |
| 2   | 10360.00    | 38.27              | 4.91            | 45.50                 | 33.95           | 54.73                   | 68.20           | 13.47       | Peak   |



Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.

FCC ID: Y9E-IAD-18010A



| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading factor (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark |
|-----|-------------|--------------------|-----------------|-----------------------|-----------------|-------------------------|-----------------|-------------|--------|
| 1   | 5200.00     | 33.30              | 3.48            | 94.79                 | 33.66           | 97.91                   | 68.20           | 13.60       | Peak   |
| 2   | 10400.00    | 38.30              | 4.92            | 45.29                 | 33.91           | 54.60                   | 68.20           | 13.60       | Peak   |



Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.



| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading factor (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark |
|-----|-------------|--------------------|-----------------|-----------------------|-----------------|-------------------------|-----------------|-------------|--------|
| 1   | 5200.00     | 33.30              | 3.48            | 88.70                 | 33.66           | 91.82                   | 68.20           | 14.21       | Peak   |
| 2   | 10400.00    | 38.30              | 4.92            | 44.68                 | 33.91           | 53.99                   | 68.20           | 14.21       | Peak   |



Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.

FCC ID: Y9E-IAD-18010A



| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading factor (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark |
|-----|-------------|--------------------|-----------------|-----------------------|-----------------|-------------------------|-----------------|-------------|--------|
| 1   | 5240.00     | 33.17              | 3.49            | 89.67                 | 33.65           | 92.68                   | 68.20           | 13.98       | Peak   |
| 2   | 10480.00    | 38.30              | 4.95            | 44.83                 | 33.86           | 54.22                   | 68.20           | 13.98       | Peak   |



Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.



| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading factor (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark |
|-----|-------------|--------------------|-----------------|-----------------------|-----------------|-------------------------|-----------------|-------------|--------|
| 1   | 5240.00     | 33.17              | 3.49            | 92.77                 | 33.65           | 95.78                   | 68.20           | 13.52       | Peak   |
| 2   | 10480.00    | 38.30              | 4.95            | 45.29                 | 33.86           | 54.68                   | 68.20           | 13.52       | Peak   |



Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.

FCC ID: Y9E-IAD-18010A



| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark |
|-----|-------------|--------------------|-----------------|----------------|-----------------|-------------------------|-----------------|-------------|--------|
| 1   | 5190.00     | 33.27              | 3.47            | 90.39          | 33.66           | 93.47                   | 68.20           | 13.55       | Peak   |
| 2   | 10380.00    | 38.28              | 4.92            | 45.38          | 33.93           | 54.65                   | 68.20           | 13.55       | Peak   |



Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading  
 -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.



| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark |
|-----|-------------|--------------------|-----------------|----------------|-----------------|-------------------------|-----------------|-------------|--------|
| 1   | 5190.00     | 33.27              | 3.47            | 85.93          | 33.66           | 89.01                   | 68.20           | 13.58       | Peak   |
| 2   | 10380.00    | 38.28              | 4.92            | 45.35          | 33.93           | 54.62                   | 68.20           | 13.58       | Peak   |



Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading  
 -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.

FCC ID: Y9E-IAD-18010A



| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading factor (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark |
|-----|-------------|--------------------|-----------------|-----------------------|-----------------|-------------------------|-----------------|-------------|--------|
| 1   | 5230.00     | 33.17              | 3.49            | 87.00                 | 33.65           | 90.01                   | -----           | -----       | Peak   |
| 2   | 10460.00    | 38.30              | 4.94            | 45.68                 | 33.88           | 55.04                   | 68.20           | 13.16       | Peak   |



Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading  
 -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.



| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading factor (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark |
|-----|-------------|--------------------|-----------------|-----------------------|-----------------|-------------------------|-----------------|-------------|--------|
| 1   | 5230.00     | 33.17              | 3.49            | 89.93                 | 33.65           | 92.94                   | -----           | -----       | Peak   |
| 2   | 10460.00    | 38.30              | 4.94            | 44.65                 | 33.88           | 54.01                   | 68.20           | 14.19       | Peak   |



Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading  
 -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.

FCC ID: Y9E-IAD-18010A



| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading factor (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark |
|-----|-------------|--------------------|-----------------|-----------------------|-----------------|-------------------------|-----------------|-------------|--------|
| 1   | 5210.00     | 33.23              | 3.49            | 88.36                 | 33.66           | 91.42                   | 68.20           | 13.73       | Peak   |
| 2   | 10420.00    | 38.30              | 4.93            | 45.15                 | 33.91           | 54.47                   | 68.20           | 13.73       | Peak   |



Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.



| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading factor (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark |
|-----|-------------|--------------------|-----------------|-----------------------|-----------------|-------------------------|-----------------|-------------|--------|
| 1   | 5210.00     | 33.23              | 3.49            | 84.00                 | 33.66           | 87.06                   | 68.20           | 14.23       | Peak   |
| 2   | 10420.00    | 38.30              | 4.93            | 44.65                 | 33.91           | 53.97                   | 68.20           | 14.23       | Peak   |



Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.

### U-NII-3 Band:



| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark  |
|-----|-------------|--------------------|-----------------|----------------|-----------------|-------------------------|-----------------|-------------|---------|
| 1   | 5745.00     | 34.00              | 3.70            | 87.51          | 33.55           | 91.66                   | 54.00           | 11.20       | Peak    |
| 2   | 11490.00    | 38.12              | 5.20            | 33.08          | 33.60           | 42.80                   | 54.00           | 11.20       | Average |
| 3   | 11490.00    | 38.12              | 5.20            | 44.84          | 33.60           | 54.56                   | 74.00           | 19.44       | Peak    |



Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.



| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark  |
|-----|-------------|--------------------|-----------------|----------------|-----------------|-------------------------|-----------------|-------------|---------|
| 1   | 5745.00     | 34.00              | 3.70            | 90.04          | 33.55           | 94.19                   | 54.00           | 11.17       | Peak    |
| 2   | 11490.00    | 38.12              | 5.20            | 33.11          | 33.60           | 42.83                   | 54.00           | 11.17       | Average |
| 3   | 11490.00    | 38.12              | 5.20            | 44.67          | 33.60           | 54.39                   | 74.00           | 19.61       | Peak    |



Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.

FCC ID: Y9E-IAD-18010A



| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading factor (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark  |
|-----|-------------|--------------------|-----------------|-----------------------|-----------------|-------------------------|-----------------|-------------|---------|
| 1   | 5785.00     | 33.93              | 3.71            | 87.34                 | 33.54           | 91.44                   | 54.00           | 11.33       | Peak    |
| 2   | 11570.00    | 38.10              | 5.22            | 32.97                 | 33.62           | 42.67                   | 74.00           | 18.91       | Average |
| 3   | 11570.00    | 38.10              | 5.22            | 45.39                 | 33.62           | 55.09                   | 74.00           | 18.91       | Peak    |



Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.



| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading factor (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark  |
|-----|-------------|--------------------|-----------------|-----------------------|-----------------|-------------------------|-----------------|-------------|---------|
| 1   | 5785.00     | 33.93              | 3.71            | 89.43                 | 33.54           | 93.53                   | 54.00           | 11.20       | Peak    |
| 2   | 11570.00    | 38.10              | 5.22            | 33.10                 | 33.62           | 42.80                   | 74.00           | 19.30       | Average |
| 3   | 11570.00    | 38.10              | 5.22            | 45.00                 | 33.62           | 54.70                   | 74.00           | 19.30       | Peak    |



Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.

FCC ID: Y9E-IAD-18010A



| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading factor (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark  |
|-----|-------------|--------------------|-----------------|-----------------------|-----------------|-------------------------|-----------------|-------------|---------|
| 1   | 5825.00     | 34.10              | 3.73            | 88.43                 | 33.54           | 92.72                   | 54.00           | 11.29       | Peak    |
| 2   | 11650.00    | 38.10              | 5.23            | 33.01                 | 33.63           | 42.71                   | 54.00           | 11.29       | Average |
| 3   | 11650.00    | 38.10              | 5.23            | 44.99                 | 33.63           | 54.69                   | 74.00           | 19.31       | Peak    |



Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.



| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading factor (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark  |
|-----|-------------|--------------------|-----------------|-----------------------|-----------------|-------------------------|-----------------|-------------|---------|
| 1   | 5825.00     | 34.10              | 3.73            | 89.48                 | 33.54           | 93.77                   | 54.00           | 11.15       | Peak    |
| 2   | 11650.00    | 38.10              | 5.23            | 33.15                 | 33.63           | 42.85                   | 54.00           | 11.15       | Average |
| 3   | 11650.00    | 38.10              | 5.23            | 44.95                 | 33.63           | 54.65                   | 74.00           | 19.35       | Peak    |



Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.

FCC ID: Y9E-IAD-18010A



| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading factor (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark  |
|-----|-------------|--------------------|-----------------|-----------------------|-----------------|-------------------------|-----------------|-------------|---------|
| 1   | 5745.00     | 34.00              | 3.70            | 89.36                 | 33.55           | 93.51                   | 54.00           | 11.21       | Peak    |
| 2   | 11490.00    | 38.12              | 5.20            | 33.07                 | 33.60           | 42.79                   | 74.00           | 19.12       | Average |
| 3   | 11490.00    | 38.12              | 5.20            | 45.16                 | 33.60           | 54.88                   | 74.00           | 19.12       | Peak    |



Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.



| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading factor (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark  |
|-----|-------------|--------------------|-----------------|-----------------------|-----------------|-------------------------|-----------------|-------------|---------|
| 1   | 5745.00     | 34.00              | 3.70            | 87.12                 | 33.55           | 91.27                   | 54.00           | 11.31       | Peak    |
| 2   | 11490.00    | 38.12              | 5.20            | 32.97                 | 33.60           | 42.69                   | 74.00           | 19.14       | Average |
| 3   | 11490.00    | 38.12              | 5.20            | 45.14                 | 33.60           | 54.86                   | 74.00           | 19.14       | Peak    |



Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.

FCC ID: Y9E-IAD-18010A



| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading factor (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark  |
|-----|-------------|--------------------|-----------------|-----------------------|-----------------|-------------------------|-----------------|-------------|---------|
| 1   | 5785.00     | 33.93              | 3.71            | 89.33                 | 33.54           | 93.43                   | 54.00           | 11.16       | Peak    |
| 2   | 11570.00    | 38.10              | 5.22            | 33.14                 | 33.62           | 42.84                   | 74.00           | 18.46       | Average |
| 3   | 11570.00    | 38.10              | 5.22            | 45.84                 | 33.62           | 55.54                   | 74.00           | 18.46       | Peak    |



Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.



| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading factor (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark  |
|-----|-------------|--------------------|-----------------|-----------------------|-----------------|-------------------------|-----------------|-------------|---------|
| 1   | 5785.00     | 33.93              | 3.71            | 86.89                 | 33.54           | 90.99                   | 54.00           | 11.39       | Peak    |
| 2   | 11570.00    | 38.10              | 5.22            | 32.91                 | 33.62           | 42.61                   | 74.00           | 19.60       | Average |
| 3   | 11570.00    | 38.10              | 5.22            | 44.70                 | 33.62           | 54.40                   | 74.00           | 19.60       | Peak    |



Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.

FCC ID: Y9E-IAD-18010A



| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading factor (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark  |
|-----|-------------|--------------------|-----------------|-----------------------|-----------------|-------------------------|-----------------|-------------|---------|
| 1   | 5825.00     | 34.10              | 3.73            | 86.38                 | 33.54           | 90.67                   | 54.00           | 11.29       | Peak    |
| 2   | 11650.00    | 38.10              | 5.23            | 33.01                 | 33.63           | 42.71                   | 54.00           | 11.29       | Average |
| 3   | 11650.00    | 38.10              | 5.23            | 45.25                 | 33.63           | 54.95                   | 74.00           | 19.05       | Peak    |



Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.



| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading factor (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark  |
|-----|-------------|--------------------|-----------------|-----------------------|-----------------|-------------------------|-----------------|-------------|---------|
| 1   | 5825.00     | 34.10              | 3.73            | 88.84                 | 33.54           | 93.13                   | 54.00           | 11.14       | Peak    |
| 2   | 11650.00    | 38.10              | 5.23            | 33.16                 | 33.63           | 42.86                   | 54.00           | 11.14       | Average |
| 3   | 11650.00    | 38.10              | 5.23            | 44.77                 | 33.63           | 54.47                   | 74.00           | 19.53       | Peak    |



Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.

FCC ID: Y9E-IAD-18010A



| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading factor (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark  |
|-----|-------------|--------------------|-----------------|-----------------------|-----------------|-------------------------|-----------------|-------------|---------|
| 1   | 5755.00     | 33.97              | 3.71            | 86.39                 | 33.55           | 90.52                   | 54.00           | 11.15       | Peak    |
| 2   | 11510.00    | 38.10              | 5.20            | 33.15                 | 33.60           | 42.85                   | 54.00           | 11.15       | Average |
| 3   | 11510.00    | 38.10              | 5.20            | 45.11                 | 33.60           | 54.81                   | 74.00           | 19.19       | Peak    |



Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.



| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading factor (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark  |
|-----|-------------|--------------------|-----------------|-----------------------|-----------------|-------------------------|-----------------|-------------|---------|
| 1   | 5755.00     | 33.97              | 3.71            | 85.07                 | 33.55           | 89.20                   | 54.00           | 11.26       | Peak    |
| 2   | 11510.00    | 38.10              | 5.20            | 33.04                 | 33.60           | 42.74                   | 54.00           | 11.26       | Average |
| 3   | 11510.00    | 38.10              | 5.20            | 45.09                 | 33.60           | 54.79                   | 74.00           | 19.21       | Peak    |



Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.

FCC ID: Y9E-IAD-18010A



| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading factor (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark  |
|-----|-------------|--------------------|-----------------|-----------------------|-----------------|-------------------------|-----------------|-------------|---------|
| 1   | 5745.00     | 34.00              | 3.70            | 89.76                 | 33.55           | 93.91                   | 54.00           | 11.30       | Peak    |
| 2   | 11490.00    | 38.12              | 5.20            | 32.98                 | 33.60           | 42.70                   | 54.00           | 11.30       | Average |
| 3   | 11490.00    | 38.12              | 5.20            | 44.96                 | 33.60           | 54.68                   | 74.00           | 19.32       | Peak    |



Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.



| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading factor (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark  |
|-----|-------------|--------------------|-----------------|-----------------------|-----------------|-------------------------|-----------------|-------------|---------|
| 1   | 5745.00     | 34.00              | 3.70            | 90.72                 | 33.55           | 94.87                   | 54.00           | 11.10       | Peak    |
| 2   | 11490.00    | 38.12              | 5.20            | 33.18                 | 33.60           | 42.90                   | 54.00           | 11.10       | Average |
| 3   | 11490.00    | 38.12              | 5.20            | 45.19                 | 33.60           | 54.91                   | 74.00           | 19.09       | Peak    |



Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.

FCC ID: Y9E-IAD-18010A



| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading factor (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark  |
|-----|-------------|--------------------|-----------------|-----------------------|-----------------|-------------------------|-----------------|-------------|---------|
| 1   | 5795.00     | 33.90              | 3.72            | 87.92                 | 33.54           | 92.00                   | 54.00           | 11.09       | Peak    |
| 2   | 11590.00    | 38.10              | 5.22            | 33.21                 | 33.62           | 42.91                   | 74.00           | 18.76       | Average |
| 3   | 11590.00    | 38.10              | 5.22            | 45.54                 | 33.62           | 55.24                   | 74.00           | 18.76       | Peak    |



Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.



| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading factor (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark  |
|-----|-------------|--------------------|-----------------|-----------------------|-----------------|-------------------------|-----------------|-------------|---------|
| 1   | 5795.00     | 33.90              | 3.72            | 84.54                 | 33.54           | 88.62                   | 54.00           | 11.27       | Peak    |
| 2   | 11590.00    | 38.10              | 5.22            | 33.03                 | 33.62           | 42.73                   | 74.00           | 19.45       | Average |
| 3   | 11590.00    | 38.10              | 5.22            | 44.85                 | 33.62           | 54.55                   | 74.00           | 19.45       | Peak    |



Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.

FCC ID: Y9E-IAD-18010A



| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading factor (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark  |
|-----|-------------|--------------------|-----------------|-----------------------|-----------------|-------------------------|-----------------|-------------|---------|
| 1   | 5785.00     | 33.93              | 3.71            | 87.52                 | 33.54           | 91.62                   | 54.00           | 11.25       | Peak    |
| 2   | 11570.00    | 38.10              | 5.22            | 33.05                 | 33.62           | 42.75                   | 54.00           | 11.25       | Average |
| 3   | 11570.00    | 38.10              | 5.22            | 44.60                 | 33.62           | 54.30                   | 74.00           | 19.70       | Peak    |



Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.



| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading factor (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark  |
|-----|-------------|--------------------|-----------------|-----------------------|-----------------|-------------------------|-----------------|-------------|---------|
| 1   | 5785.00     | 33.93              | 3.71            | 89.10                 | 33.54           | 93.20                   | 54.00           | 11.18       | Peak    |
| 2   | 11570.00    | 38.10              | 5.22            | 33.12                 | 33.62           | 42.82                   | 54.00           | 11.18       | Average |
| 3   | 11570.00    | 38.10              | 5.22            | 44.97                 | 33.62           | 54.67                   | 74.00           | 19.33       | Peak    |



Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.

FCC ID: Y9E-IAD-18010A



| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark  |
|-----|-------------|--------------------|-----------------|----------------|-----------------|-------------------------|-----------------|-------------|---------|
| 1   | 5825.00     | 34.10              | 3.73            | 89.13          | 33.54           | 93.42                   | 54.00           | 11.07       | Peak    |
| 2   | 11650.00    | 38.10              | 5.23            | 33.23          | 33.63           | 42.93                   | 54.00           | 11.07       | Average |
| 3   | 11650.00    | 38.10              | 5.23            | 45.08          | 33.63           | 54.78                   | 74.00           | 19.22       | Peak    |



Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.



| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark  |
|-----|-------------|--------------------|-----------------|----------------|-----------------|-------------------------|-----------------|-------------|---------|
| 1   | 5825.00     | 34.10              | 3.73            | 87.43          | 33.54           | 91.72                   | 54.00           | 11.33       | Peak    |
| 2   | 11650.00    | 38.10              | 5.23            | 32.97          | 33.63           | 42.67                   | 54.00           | 11.33       | Average |
| 3   | 11650.00    | 38.10              | 5.23            | 45.74          | 33.63           | 55.44                   | 74.00           | 18.56       | Peak    |



Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.

FCC ID: Y9E-IAD-18010A



| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading factor (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark  |
|-----|-------------|--------------------|-----------------|-----------------------|-----------------|-------------------------|-----------------|-------------|---------|
| 1   | 5755.00     | 33.97              | 3.71            | 84.51                 | 33.55           | 88.64                   | 54.00           | 11.49       | Peak    |
| 2   | 11510.00    | 38.10              | 5.20            | 32.81                 | 33.60           | 42.51                   | 74.00           | 19.99       | Average |
| 3   | 11510.00    | 38.10              | 5.20            | 44.31                 | 33.60           | 54.01                   | 74.00           | 19.99       | Peak    |



Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.



| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading factor (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark  |
|-----|-------------|--------------------|-----------------|-----------------------|-----------------|-------------------------|-----------------|-------------|---------|
| 1   | 5755.00     | 33.97              | 3.71            | 85.88                 | 33.55           | 90.01                   | 54.00           | 11.32       | Peak    |
| 2   | 11510.00    | 38.10              | 5.20            | 32.98                 | 33.60           | 42.68                   | 74.00           | 19.89       | Average |
| 3   | 11510.00    | 38.10              | 5.20            | 44.41                 | 33.60           | 54.11                   | 74.00           | 19.89       | Peak    |



Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.

FCC ID: Y9E-IAD-18010A



| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark  |
|-----|-------------|--------------------|-----------------|----------------|-----------------|-------------------------|-----------------|-------------|---------|
| 1   | 5795.00     | 33.90              | 3.72            | 86.79          | 33.54           | 90.87                   | 54.00           | 11.19       | Peak    |
| 2   | 11590.00    | 38.10              | 5.22            | 33.11          | 33.62           | 42.81                   | 54.00           | 11.19       | Average |
| 3   | 11590.00    | 38.10              | 5.22            | 45.00          | 33.62           | 54.70                   | 74.00           | 19.30       | Peak    |



Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.



| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark  |
|-----|-------------|--------------------|-----------------|----------------|-----------------|-------------------------|-----------------|-------------|---------|
| 1   | 5795.00     | 33.90              | 3.72            | 85.33          | 33.54           | 89.41                   | 54.00           | 11.32       | Peak    |
| 2   | 11590.00    | 38.10              | 5.22            | 32.98          | 33.62           | 42.68                   | 54.00           | 11.32       | Average |
| 3   | 11590.00    | 38.10              | 5.22            | 44.81          | 33.62           | 54.51                   | 74.00           | 19.49       | Peak    |



Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.

FCC ID: Y9E-IAD-18010A



| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading factor (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark  |
|-----|-------------|--------------------|-----------------|-----------------------|-----------------|-------------------------|-----------------|-------------|---------|
| 1   | 5775.00     | 33.93              | 3.71            | 82.33                 | 33.55           | 86.42                   | 54.00           | -----       | Peak    |
| 2   | 11550.00    | 38.10              | 5.21            | 32.56                 | 33.61           | 42.26                   | 74.00           | 11.74       | Average |
| 3   | 11550.00    | 38.10              | 5.21            | 44.95                 | 33.61           | 54.65                   | 74.00           | 19.35       | Peak    |

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.



| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading factor (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark  |
|-----|-------------|--------------------|-----------------|-----------------------|-----------------|-------------------------|-----------------|-------------|---------|
| 1   | 5775.00     | 33.93              | 3.71            | 83.39                 | 33.55           | 87.48                   | 54.00           | -----       | Peak    |
| 2   | 11550.00    | 38.10              | 5.21            | 32.87                 | 33.61           | 42.57                   | 74.00           | 11.43       | Average |
| 3   | 11550.00    | 38.10              | 5.21            | 45.48                 | 33.61           | 55.18                   | 74.00           | 18.82       | Peak    |

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.

## 5. BAND EDGE COMPLIANCE TEST

### 5.1. Test Equipments

| Item | Equipment           | Manufacturer     | Model No.    | Serial No.  | Last Cal. | Cal. Interval |
|------|---------------------|------------------|--------------|-------------|-----------|---------------|
| 1.   | PXA Signal Analyzer | Agilent          | N9030A       | MY51380221  | Apr.07,22 | 1 Year        |
| 2.   | Amplifier           | Agilent          | 8449B        | 3008A00863  | Apr.06,22 | 1 Year        |
| 3.   | Horn Antenna        | ETC              | MCTD 1209    | DRH15F03006 | Aug.12,22 | 1 Year        |
| 4.   | RF Cable            | HUBER+SUHN<br>ER | SUCOFLEX-106 | 505238/6    | Apr.06,22 | 1 Year        |

### 5.2. Limit

For transmitters operating in the band 5150-5250 MHz, all emissions outside the band 5150-5250 MHz shall not exceed -27 dBm/MHz e.i.r.p.

For transmitters operating in the 5.725-5.85 GHz band: All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge..


### 5.3. Test Procedure

1. The EUT is placed on a turntable, which is 1.5m above the ground plane and worked at highest radiated power.
2. The turntable was rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emission.
4. Set the spectrum analyzer in the following setting in order to capture the lower and upper band-edges of the emission:
  - (a) PEAK: RBW=1MHz; VBW=3MHz; Sweep=AUTO
  - (b) AVERAGE: RBW=1MHz; VBW=10Hz; Sweep=AUTO
5. Per KDB789033 clause H 2)d).if the test distance is 3m,the EIRP(dBm)=E(dBuv/m)-95.2  
Get the final compare with limit.

### 5.4. Test Results

Pass (The testing data was attached in the next pages.)


### U-NII-1 Band:



Site no. : 3m Chamber Data no. : 1  
 Dis. / Ant. : 3m 2022 MCTD1209-3006 Ant. pol. : HORIZONTAL  
 Limit : FCC 15E AV  
 Env. / Ins. : 23.2°C/52.5% Engineer : Allen  
 Test Mode : 11a 5180MHz TX

| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark  |
|-----|-------------|--------------------|-----------------|----------------|-----------------|-------------------------|-----------------|-------------|---------|
| 1   | 5150.00     | 33.20              | 3.46            | 34.22          | 33.67           | 37.21                   | 54.00           | 16.79       | Average |
| 2   | 5179.47     | 33.27              | 3.47            | 82.93          | 33.66           | 86.01                   | -----           | -----       | Average |


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 2  
 Dis. / Ant. : 3m 2022 MCTD1209-3006 Ant. pol. : VERTICAL  
 Limit : FCC 15E AV  
 Env. / Ins. : 23.2°C/52.5% Engineer : Allen  
 Test Mode : 11a 5180MHz TX

| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark  |
|-----|-------------|--------------------|-----------------|----------------|-----------------|-------------------------|-----------------|-------------|---------|
| 1   | 5150.00     | 33.20              | 3.46            | 33.20          | 33.67           | 36.19                   | 54.00           | 17.81       | Average |
| 2   | 5179.47     | 33.27              | 3.47            | 78.61          | 33.66           | 81.69                   | -----           | -----       | Average |


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 3  
 Dis. / Ant. : 3m 2022 MCTD1209-3006 Ant. pol. : VERTICAL  
 Limit : FCC 15E PK U-NII-1  
 Env. / Ins. : 23.2°C/52.5% Engineer : Allen  
 Test Mode : 11a 5180MHz TX

| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark |
|-----|-------------|--------------------|-----------------|----------------|-----------------|-------------------------|-----------------|-------------|--------|
| 1   | 5150.00     | 33.20              | 3.46            | 44.93          | 33.67           | 47.92                   | 74.00           | 26.08       | Peak   |
| 2   | 5182.31     | 33.27              | 3.47            | 89.61          | 33.66           | 92.69                   | -----           | -----       | Peak   |

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 3m Chamber Data no. : 4  
 Dis. / Ant. : 3m 2022 MCTD1209-3006 Ant. pol. : HORIZONTAL  
 Limit : FCC 15E PK U-NII-1  
 Env. / Ins. : 23.2°C/52.5% Engineer : Allen  
 Test Mode : 11a 5180MHz TX

| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark |
|-----|-------------|--------------------|-----------------|----------------|-----------------|-------------------------|-----------------|-------------|--------|
| 1   | 5150.00     | 33.20              | 3.46            | 46.38          | 33.67           | 49.37                   | 74.00           | 24.63       | Peak   |
| 2   | 5181.60     | 33.27              | 3.47            | 94.14          | 33.66           | 97.22                   | -----           | -----       | Peak   |


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.

FCC ID: Y9E-IAD-18010A




| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading factor (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark |
|-----|-------------|--------------------|-----------------|-----------------------|-----------------|-------------------------|-----------------|-------------|--------|
| 1   | 5239.64     | 33.17              | 3.49            | 94.39                 | 33.65           | 97.40                   | 72.00           | 25.40       | Peak   |
| 2   | 5350.00     | 32.90              | 3.54            | 45.52                 | 33.63           | 48.33                   | 74.00           | 25.67       | Peak   |
| 3   | 5460.00     | 32.70              | 3.58            | 45.99                 | 33.61           | 48.66                   | 68.20           | 19.54       | Peak   |

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.




| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading factor (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark |
|-----|-------------|--------------------|-----------------|-----------------------|-----------------|-------------------------|-----------------|-------------|--------|
| 1   | 5238.60     | 33.17              | 3.49            | 90.23                 | 33.65           | 93.24                   | 72.00           | 21.24       | Peak   |
| 2   | 5350.00     | 32.90              | 3.54            | 46.04                 | 33.63           | 48.85                   | 74.00           | 25.15       | Peak   |
| 3   | 5460.00     | 32.70              | 3.58            | 46.16                 | 33.61           | 48.83                   | 68.20           | 19.37       | Peak   |

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.




| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading factor (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark  |
|-----|-------------|--------------------|-----------------|-----------------------|-----------------|-------------------------|-----------------|-------------|---------|
| 1   | 5238.66     | 33.17              | 3.49            | 80.61                 | 33.65           | 83.62                   | 54.00           | 29.62       | Average |
| 2   | 5350.00     | 32.90              | 3.54            | 32.75                 | 33.63           | 35.56                   | 54.00           | 18.44       | Average |
| 3   | 5460.00     | 32.70              | 3.58            | 33.01                 | 33.61           | 35.68                   | 54.00           | 18.32       | Average |

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.




| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading factor (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark  |
|-----|-------------|--------------------|-----------------|-----------------------|-----------------|-------------------------|-----------------|-------------|---------|
| 1   | 5238.66     | 33.17              | 3.49            | 84.23                 | 33.65           | 87.24                   | 54.00           | 33.24       | Average |
| 2   | 5350.00     | 32.90              | 3.54            | 32.83                 | 33.63           | 35.64                   | 54.00           | 18.36       | Average |
| 3   | 5460.00     | 32.70              | 3.58            | 33.02                 | 33.61           | 35.69                   | 54.00           | 18.31       | Average |

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.




| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark  |
|-----|-------------|--------------------|-----------------|----------------|-----------------|-------------------------|-----------------|-------------|---------|
| 1   | 5150.00     | 33.20              | 3.46            | 34.09          | 33.67           | 37.08                   | 54.00           | 16.92       | Average |
| 2   | 5180.89     | 33.27              | 3.47            | 81.97          | 33.66           | 85.05                   | ---             | ---         | Average |

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.




| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark  |
|-----|-------------|--------------------|-----------------|----------------|-----------------|-------------------------|-----------------|-------------|---------|
| 1   | 5150.00     | 33.20              | 3.46            | 33.16          | 33.67           | 36.15                   | 54.00           | 17.85       | Average |
| 2   | 5179.47     | 33.27              | 3.47            | 77.33          | 33.66           | 80.41                   | ---             | ---         | Average |

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.




| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark |
|-----|-------------|--------------------|-----------------|----------------|-----------------|-------------------------|-----------------|-------------|--------|
| 1   | 5150.00     | 33.20              | 3.46            | 48.89          | 33.67           | 47.88                   | 74.00           | 26.12       | Peak   |
| 2   | 5179.47     | 33.27              | 3.47            | 88.81          | 33.66           | 91.89                   | ---             | ---         | Peak   |

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.



| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark |
|-----|-------------|--------------------|-----------------|----------------|-----------------|-------------------------|-----------------|-------------|--------|
| 1   | 5150.00     | 33.20              | 3.46            | 45.69          | 33.67           | 48.68                   | 74.00           | 25.32       | Peak   |
| 2   | 5179.47     | 33.27              | 3.47            | 92.23          | 33.66           | 95.31                   | ---             | ---         | Peak   |


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 37  
 Dis. / Ant. : 3m 2022 MCTD1209-3006 Ant. pol. : VERTICAL  
 Limit : FCC 15E PK U-NII-1  
 Env. / Ins. : 23.2°C/52.5% Engineer : Allen  
 Test Mode : 11n20 5240MHz TX

| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading factor (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark |
|-----|-------------|--------------------|-----------------|-----------------------|-----------------|-------------------------|-----------------|-------------|--------|
| 1   | 5238.86     | 33.17              | 3.49            | 89.73                 | 33.65           | 92.74                   | 72.00           | 20.74       | Peak   |
| 2   | 5350.00     | 32.90              | 3.54            | 45.90                 | 33.63           | 48.71                   | 74.00           | 25.29       | Peak   |
| 3   | 5460.00     | 32.70              | 3.58            | 46.21                 | 33.61           | 48.88                   | 68.20           | 19.32       | Peak   |


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 38  
 Dis. / Ant. : 3m 2022 MCTD1209-3006 Ant. pol. : HORIZONTAL  
 Limit : FCC 15E PK U-NII-1  
 Env. / Ins. : 23.2°C/52.5% Engineer : Allen  
 Test Mode : 11n20 5240MHz TX

| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading factor (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark |
|-----|-------------|--------------------|-----------------|-----------------------|-----------------|-------------------------|-----------------|-------------|--------|
| 1   | 5239.38     | 33.17              | 3.49            | 92.79                 | 33.65           | 95.80                   | 72.00           | 23.80       | Peak   |
| 2   | 5350.00     | 32.90              | 3.54            | 45.23                 | 33.63           | 48.04                   | 74.00           | 25.96       | Peak   |
| 3   | 5460.00     | 32.70              | 3.58            | 45.62                 | 33.61           | 48.29                   | 68.20           | 19.91       | Peak   |


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 39  
 Dis. / Ant. : 3m 2022 MCTD1209-3006 Ant. pol. : HORIZONTAL  
 Limit : FCC 15E AV  
 Env. / Ins. : 23.2°C/52.5% Engineer : Allen  
 Test Mode : 11n20 5240MHz TX

| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading factor (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark  |
|-----|-------------|--------------------|-----------------|-----------------------|-----------------|-------------------------|-----------------|-------------|---------|
| 1   | 5240.94     | 33.17              | 3.49            | 85.27                 | 33.65           | 86.26                   | 54.00           | 32.26       | Average |
| 2   | 5350.00     | 32.90              | 3.54            | 32.80                 | 33.63           | 35.61                   | 54.00           | 18.39       | Average |
| 3   | 5460.00     | 32.70              | 3.58            | 32.95                 | 33.61           | 35.62                   | 54.00           | 18.38       | Average |


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 40  
 Dis. / Ant. : 3m 2022 MCTD1209-3006 Ant. pol. : VERTICAL  
 Limit : FCC 15E AV  
 Env. / Ins. : 23.2°C/52.5% Engineer : Allen  
 Test Mode : 11n20 5240MHz TX


| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading factor (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark  |
|-----|-------------|--------------------|-----------------|-----------------------|-----------------|-------------------------|-----------------|-------------|---------|
| 1   | 5240.94     | 33.17              | 3.49            | 79.36                 | 33.65           | 82.39                   | 54.00           | 28.39       | Average |
| 2   | 5350.00     | 32.90              | 3.54            | 32.70                 | 33.63           | 35.51                   | 54.00           | 18.49       | Average |
| 3   | 5460.00     | 32.70              | 3.58            | 32.95                 | 33.61           | 35.62                   | 54.00           | 18.38       | Average |

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.




| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark  |
|-----|-------------|--------------------|-----------------|----------------|-----------------|-------------------------|-----------------|-------------|---------|
| 1   | 5150.00     | 33.20              | 3.46            | 34.50          | 33.67           | 37.49                   | 54.00           | 16.51       | Average |
| 2   | 5192.04     | 33.30              | 3.48            | 73.39          | 33.66           | 76.51                   | ---             | ---         | Average |

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.




| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark  |
|-----|-------------|--------------------|-----------------|----------------|-----------------|-------------------------|-----------------|-------------|---------|
| 1   | 5150.00     | 33.20              | 3.46            | 36.66          | 33.67           | 39.65                   | 54.00           | 14.35       | Average |
| 2   | 5192.04     | 33.30              | 3.48            | 77.10          | 33.66           | 80.22                   | ---             | ---         | Average |

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.



| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark |
|-----|-------------|--------------------|-----------------|----------------|-----------------|-------------------------|-----------------|-------------|--------|
| 1   | 5150.00     | 33.20              | 3.46            | 48.30          | 33.67           | 51.29                   | 74.00           | 22.71       | Peak   |
| 2   | 5192.50     | 33.30              | 3.48            | 89.68          | 33.66           | 92.80                   | ---             | ---         | Peak   |


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.



| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark |
|-----|-------------|--------------------|-----------------|----------------|-----------------|-------------------------|-----------------|-------------|--------|
| 1   | 5150.00     | 33.20              | 3.46            | 45.78          | 33.67           | 48.77                   | 74.00           | 25.23       | Peak   |
| 2   | 5192.04     | 33.30              | 3.48            | 85.82          | 33.66           | 88.94                   | ---             | ---         | Peak   |

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.


FCC ID: Y9E-IAD-18010A



Site no. : 3m Chamber Data no. : 53  
 Dis. / Ant. : 3m 2022 MCTD1209-3006 Ant. pol. : VERTICAL  
 Limit : FCC 15E PK U-NII-1  
 Env. / Ins. : 23.2°C/52.5% Engineer : Allen  
 Test Mode : 11n40 5230MHz TX

| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading factor (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark |
|-----|-------------|--------------------|-----------------|-----------------------|-----------------|-------------------------|-----------------|-------------|--------|
| 1   | 5228.64     | 33.17              | 3.49            | 90.44                 | 33.65           | 93.45                   | 72.00           | 21.45       | Peak   |
| 2   | 5350.00     | 32.90              | 3.54            | 45.57                 | 33.63           | 48.38                   | 74.00           | 25.62       | Peak   |
| 3   | 5460.00     | 32.70              | 3.58            | 45.97                 | 33.61           | 48.64                   | 68.20           | 19.56       | Peak   |


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 54  
 Dis. / Ant. : 3m 2022 MCTD1209-3006 Ant. pol. : HORIZONTAL  
 Limit : FCC 15E PK U-NII-1  
 Env. / Ins. : 23.2°C/52.5% Engineer : Allen  
 Test Mode : 11n40 5230MHz TX

| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading factor (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark |
|-----|-------------|--------------------|-----------------|-----------------------|-----------------|-------------------------|-----------------|-------------|--------|
| 1   | 5228.08     | 33.17              | 3.49            | 93.83                 | 33.65           | 96.84                   | 72.00           | 24.84       | Peak   |
| 2   | 5350.00     | 32.90              | 3.54            | 44.93                 | 33.63           | 47.74                   | 74.00           | 26.26       | Peak   |
| 3   | 5460.00     | 32.70              | 3.58            | 45.26                 | 33.61           | 47.93                   | 68.20           | 20.27       | Peak   |


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 55  
 Dis. / Ant. : 3m 2022 MCTD1209-3006 Ant. pol. : HORIZONTAL  
 Limit : FCC 15E AV  
 Env. / Ins. : 23.2°C/52.5% Engineer : Allen  
 Test Mode : 11n40 5230MHz TX

| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading factor (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark  |
|-----|-------------|--------------------|-----------------|-----------------------|-----------------|-------------------------|-----------------|-------------|---------|
| 1   | 5227.24     | 33.17              | 3.49            | 81.99                 | 33.65           | 85.00                   | 72.00           | 13.00       | Average |
| 2   | 5350.00     | 32.90              | 3.54            | 32.71                 | 33.63           | 35.52                   | 54.00           | 18.48       | Average |
| 3   | 5460.00     | 32.70              | 3.58            | 32.84                 | 33.61           | 35.51                   | 54.00           | 18.49       | Average |


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 56  
 Dis. / Ant. : 3m 2022 MCTD1209-3006 Ant. pol. : VERTICAL  
 Limit : FCC 15E AV  
 Env. / Ins. : 23.2°C/52.5% Engineer : Allen  
 Test Mode : 11n40 5230MHz TX


| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading factor (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark  |
|-----|-------------|--------------------|-----------------|-----------------------|-----------------|-------------------------|-----------------|-------------|---------|
| 1   | 5226.96     | 33.17              | 3.49            | 76.59                 | 33.65           | 79.60                   | 72.00           | 7.60        | Average |
| 2   | 5350.00     | 32.90              | 3.54            | 32.66                 | 33.63           | 35.47                   | 54.00           | 18.53       | Average |
| 3   | 5460.00     | 32.70              | 3.58            | 32.81                 | 33.61           | 35.48                   | 54.00           | 18.52       | Average |

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.




| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading factor (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark  |
|-----|-------------|--------------------|-----------------|-----------------------|-----------------|-------------------------|-----------------|-------------|---------|
| 1   | 5150.00     | 33.20              | 3.46            | 33.19                 | 33.67           | 36.18                   | 54.00           | 17.82       | Average |
| 2   | 5180.89     | 33.27              | 3.47            | 79.32                 | 33.66           | 82.40                   | -----           | -----       | Average |

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.




| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading factor (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark  |
|-----|-------------|--------------------|-----------------|-----------------------|-----------------|-------------------------|-----------------|-------------|---------|
| 1   | 5150.00     | 33.20              | 3.46            | 35.14                 | 33.67           | 38.13                   | 54.00           | 15.87       | Average |
| 2   | 5181.60     | 33.27              | 3.47            | 84.65                 | 33.66           | 87.73                   | -----           | -----       | Average |

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.



| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading factor (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark |
|-----|-------------|--------------------|-----------------|-----------------------|-----------------|-------------------------|-----------------|-------------|--------|
| 1   | 5150.00     | 33.20              | 3.46            | 46.94                 | 33.67           | 49.93                   | 74.00           | 24.07       | Peak   |
| 2   | 5182.31     | 33.27              | 3.47            | 94.96                 | 33.66           | 98.04                   | -----           | -----       | Peak   |


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.



| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading factor (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark |
|-----|-------------|--------------------|-----------------|-----------------------|-----------------|-------------------------|-----------------|-------------|--------|
| 1   | 5150.00     | 33.20              | 3.46            | 44.81                 | 33.67           | 47.80                   | 74.00           | 26.20       | Peak   |
| 2   | 5183.02     | 33.27              | 3.47            | 89.31                 | 33.66           | 92.39                   | -----           | -----       | Peak   |


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.

FCC ID: Y9E-IAD-18010A




| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading factor (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark |
|-----|-------------|--------------------|-----------------|-----------------------|-----------------|-------------------------|-----------------|-------------|--------|
| 1   | 5239.38     | 33.17              | 3.49            | 94.10                 | 33.65           | 97.11                   | 72.00           | 25.11       | Peak   |
| 2   | 5350.00     | 32.90              | 3.54            | 45.29                 | 33.63           | 48.10                   | 74.00           | 25.90       | Peak   |
| 3   | 5460.00     | 32.70              | 3.58            | 44.80                 | 33.61           | 47.47                   | 68.20           | 20.73       | Peak   |

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.




| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading factor (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark |
|-----|-------------|--------------------|-----------------|-----------------------|-----------------|-------------------------|-----------------|-------------|--------|
| 1   | 5238.08     | 33.17              | 3.49            | 89.96                 | 33.65           | 92.97                   | 72.00           | 20.97       | Peak   |
| 2   | 5350.00     | 32.90              | 3.54            | 45.18                 | 33.63           | 47.99                   | 74.00           | 26.01       | Peak   |
| 3   | 5460.00     | 32.70              | 3.58            | 45.21                 | 33.61           | 47.88                   | 68.20           | 20.32       | Peak   |

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.




| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading factor (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark  |
|-----|-------------|--------------------|-----------------|-----------------------|-----------------|-------------------------|-----------------|-------------|---------|
| 1   | 5240.42     | 33.17              | 3.49            | 79.74                 | 33.65           | 82.75                   | 54.00           | 28.75       | Average |
| 2   | 5350.00     | 32.90              | 3.54            | 32.43                 | 33.63           | 35.24                   | 54.00           | 18.76       | Average |
| 3   | 5460.00     | 32.70              | 3.58            | 32.68                 | 33.61           | 35.35                   | 54.00           | 18.65       | Average |

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.




| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading factor (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark  |
|-----|-------------|--------------------|-----------------|-----------------------|-----------------|-------------------------|-----------------|-------------|---------|
| 1   | 5238.06     | 33.17              | 3.49            | 82.79                 | 33.65           | 85.80                   | 54.00           | 31.80       | Average |
| 2   | 5350.00     | 32.90              | 3.54            | 32.42                 | 33.63           | 35.23                   | 54.00           | 18.77       | Average |
| 3   | 5460.00     | 32.70              | 3.58            | 32.71                 | 33.61           | 35.38                   | 54.00           | 18.62       | Average |

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.




| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading factor (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark  |
|-----|-------------|--------------------|-----------------|-----------------------|-----------------|-------------------------|-----------------|-------------|---------|
| 1   | 5150.00     | 33.20              | 3.46            | 36.97                 | 33.67           | 39.96                   | 54.00           | 14.04       | Average |
| 2   | 5192.04     | 33.30              | 3.48            | 77.86                 | 33.66           | 80.98                   | -----           | -----       | Average |

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.




| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading factor (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark  |
|-----|-------------|--------------------|-----------------|-----------------------|-----------------|-------------------------|-----------------|-------------|---------|
| 1   | 5150.00     | 33.20              | 3.46            | 34.56                 | 33.67           | 37.55                   | 54.00           | 16.45       | Average |
| 2   | 5192.77     | 33.30              | 3.48            | 73.66                 | 33.66           | 76.78                   | -----           | -----       | Average |

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.



| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading factor (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark |
|-----|-------------|--------------------|-----------------|-----------------------|-----------------|-------------------------|-----------------|-------------|--------|
| 1   | 5150.00     | 33.20              | 3.46            | 46.55                 | 33.67           | 49.54                   | 74.00           | 24.46       | Peak   |
| 2   | 5194.23     | 33.30              | 3.48            | 85.94                 | 33.66           | 89.06                   | -----           | -----       | Peak   |


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.



| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading factor (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark |
|-----|-------------|--------------------|-----------------|-----------------------|-----------------|-------------------------|-----------------|-------------|--------|
| 1   | 5150.00     | 33.20              | 3.46            | 48.04                 | 33.67           | 51.83                   | 74.00           | 22.17       | Peak   |
| 2   | 5192.77     | 33.30              | 3.48            | 91.14                 | 33.66           | 94.26                   | -----           | -----       | Peak   |


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.

FCC ID: Y9E-IAD-18010A




| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading factor (dBuV) | Emission Level (dB) | Limits (dBuV/m) | Margin (dB) | Remark |
|-----|-------------|--------------------|-----------------|-----------------------|---------------------|-----------------|-------------|--------|
| 1   | 5227.80     | 33.17              | 3.49            | 91.26                 | 33.65               | 94.27           | -----       | Peak   |
| 2   | 5350.00     | 32.90              | 3.54            | 45.23                 | 33.63               | 48.04           | 74.00       | Peak   |
| 3   | 5460.00     | 32.70              | 3.58            | 45.46                 | 33.61               | 48.13           | 68.20       | Peak   |

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.




| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading factor (dBuV) | Emission Level (dB) | Limits (dBuV/m) | Margin (dB) | Remark |
|-----|-------------|--------------------|-----------------|-----------------------|---------------------|-----------------|-------------|--------|
| 1   | 5228.36     | 33.17              | 3.49            | 87.48                 | 33.65               | 90.49           | -----       | Peak   |
| 2   | 5350.00     | 32.90              | 3.54            | 44.42                 | 33.63               | 47.23           | 74.00       | Peak   |
| 3   | 5460.00     | 32.70              | 3.58            | 45.69                 | 33.61               | 48.36           | 68.20       | Peak   |

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.




| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading factor (dBuV) | Emission Level (dB) | Limits (dBuV/m) | Margin (dB) | Remark  |
|-----|-------------|--------------------|-----------------|-----------------------|---------------------|-----------------|-------------|---------|
| 1   | 5232.28     | 33.17              | 3.49            | 75.77                 | 33.65               | 78.78           | -----       | Average |
| 2   | 5350.00     | 32.90              | 3.54            | 32.39                 | 33.63               | 35.20           | 54.00       | Average |
| 3   | 5460.00     | 32.70              | 3.58            | 32.58                 | 33.61               | 35.25           | 54.00       | Average |

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.




| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading factor (dBuV) | Emission Level (dB) | Limits (dBuV/m) | Margin (dB) | Remark  |
|-----|-------------|--------------------|-----------------|-----------------------|---------------------|-----------------|-------------|---------|
| 1   | 5231.16     | 33.17              | 3.49            | 78.98                 | 33.65               | 81.99           | -----       | Average |
| 2   | 5350.00     | 32.90              | 3.54            | 32.48                 | 33.63               | 35.29           | 54.00       | Average |
| 3   | 5460.00     | 32.70              | 3.58            | 32.54                 | 33.61               | 35.21           | 54.00       | Average |

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.




| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading factor (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark  |
|-----|-------------|--------------------|-----------------|-----------------------|-----------------|-------------------------|-----------------|-------------|---------|
| 1   | 5150.00     | 33.20              | 3.46            | 37.94                 | 33.67           | 40.93                   | 54.00           | 13.07       | Average |
| 2   | 5207.63     | 33.23              | 3.49            | 72.69                 | 33.66           | 75.75                   | -----           | -----       | Average |

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.




| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading factor (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark  |
|-----|-------------|--------------------|-----------------|-----------------------|-----------------|-------------------------|-----------------|-------------|---------|
| 1   | 5150.00     | 33.20              | 3.46            | 35.43                 | 33.67           | 38.42                   | 54.00           | 15.58       | Average |
| 2   | 5213.79     | 33.23              | 3.49            | 69.87                 | 33.66           | 72.93                   | -----           | -----       | Average |

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.




| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading factor (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark |
|-----|-------------|--------------------|-----------------|-----------------------|-----------------|-------------------------|-----------------|-------------|--------|
| 1   | 5150.00     | 33.20              | 3.46            | 47.71                 | 33.67           | 50.70                   | 74.00           | 23.30       | Peak   |
| 2   | 5207.63     | 33.23              | 3.49            | 84.11                 | 33.66           | 87.17                   | -----           | -----       | Peak   |

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.




| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading factor (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark |
|-----|-------------|--------------------|-----------------|-----------------------|-----------------|-------------------------|-----------------|-------------|--------|
| 1   | 5150.00     | 33.20              | 3.46            | 49.06                 | 33.67           | 52.85                   | 74.00           | 21.15       | Peak   |
| 2   | 5205.32     | 33.30              | 3.48            | 87.09                 | 33.66           | 90.21                   | -----           | -----       | Peak   |

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.




| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading factor (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark |
|-----|-------------|--------------------|-----------------|-----------------------|-----------------|-------------------------|-----------------|-------------|--------|
| 1   | 5212.72     | 33.23              | 3.49            | 84.56                 | 33.66           | 87.62                   | -----           | -----       | Peak   |
| 2   | 5350.00     | 32.90              | 3.54            | 44.64                 | 33.63           | 47.45                   | 74.00           | 26.55       | Peak   |
| 3   | 5460.00     | 32.70              | 3.58            | 45.04                 | 33.61           | 47.71                   | 68.20           | 20.49       | Peak   |

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.




| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading factor (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark |
|-----|-------------|--------------------|-----------------|-----------------------|-----------------|-------------------------|-----------------|-------------|--------|
| 1   | 5216.56     | 33.23              | 3.49            | 88.04                 | 33.66           | 91.10                   | -----           | -----       | Peak   |
| 2   | 5350.00     | 32.90              | 3.54            | 45.45                 | 33.63           | 48.26                   | 74.00           | 25.74       | Peak   |
| 3   | 5460.00     | 32.70              | 3.58            | 45.87                 | 33.61           | 48.54                   | 68.20           | 19.66       | Peak   |

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.



| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading factor (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark  |
|-----|-------------|--------------------|-----------------|-----------------------|-----------------|-------------------------|-----------------|-------------|---------|
| 1   | 5206.96     | 33.30              | 3.48            | 75.30                 | 33.66           | 76.42                   | -----           | -----       | Average |
| 2   | 5350.00     | 32.90              | 3.54            | 32.74                 | 33.63           | 35.55                   | 54.00           | 18.45       | Average |
| 3   | 5460.00     | 32.70              | 3.58            | 32.67                 | 33.61           | 35.34                   | 54.00           | 18.66       | Average |


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.



| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading factor (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark  |
|-----|-------------|--------------------|-----------------|-----------------------|-----------------|-------------------------|-----------------|-------------|---------|
| 1   | 5207.60     | 33.23              | 3.49            | 70.16                 | 33.66           | 73.22                   | -----           | -----       | Average |
| 2   | 5350.00     | 32.90              | 3.54            | 32.58                 | 33.63           | 35.39                   | 54.00           | 18.61       | Average |
| 3   | 5460.00     | 32.70              | 3.58            | 32.55                 | 33.61           | 35.22                   | 54.00           | 18.78       | Average |

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.


### U-NII-3 Band:



Site no. : 3m Chamber Data no. : 1  
 Dis. / Ant. : 3m 2022 MCTD1209-3006 Ant. pol. : VERTICAL  
 Limit : FCC 15E AV  
 Env. / Ins. : 23.2°C/52.5% Engineer : Allen  
 Test Mode : 11a 5745MHz TX

| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark  |
|-----|-------------|--------------------|-----------------|----------------|-----------------|-------------------------|-----------------|-------------|---------|
| 1   | 5460.00     | 32.70              | 3.58            | 32.55          | 33.61           | 35.22                   | 54.00           | 18.78       | Average |
| 2   | 5744.38     | 34.00              | 3.70            | 78.82          | 33.55           | 82.97                   | -----           | -----       | Average |


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 2  
 Dis. / Ant. : 3m 2022 MCTD1209-3006 Ant. pol. : HORIZONTAL  
 Limit : FCC 15E AV  
 Env. / Ins. : 23.2°C/52.5% Engineer : Allen  
 Test Mode : 11a 5745MHz TX

| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark  |
|-----|-------------|--------------------|-----------------|----------------|-----------------|-------------------------|-----------------|-------------|---------|
| 1   | 5460.00     | 32.70              | 3.58            | 32.52          | 33.61           | 35.19                   | 54.00           | 18.81       | Average |
| 2   | 5744.80     | 34.00              | 3.70            | 80.31          | 33.55           | 84.46                   | -----           | -----       | Average |


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 3  
 Dis. / Ant. : 3m 2022 MCTD1209-3006 Ant. pol. : HORIZONTAL  
 Limit : FCC 15E PK U-NII-3  
 Env. / Ins. : 23.2°C/52.5% Engineer : Allen  
 Test Mode : 11a 5745MHz TX

| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark |
|-----|-------------|--------------------|-----------------|----------------|-----------------|-------------------------|-----------------|-------------|--------|
| 1   | 5460.00     | 32.70              | 3.58            | 45.34          | 33.61           | 48.01                   | 68.20           | 20.19       | Peak   |
| 2   | 5650.00     | 33.50              | 3.66            | 46.06          | 33.57           | 49.65                   | 68.20           | 18.55       | Peak   |
| 3   | 5700.00     | 33.90              | 3.68            | 46.97          | 33.56           | 50.99                   | 105.20          | 54.21       | Peak   |
| 4   | 5720.00     | 33.97              | 3.69            | 49.98          | 33.56           | 54.08                   | 110.80          | 56.72       | Peak   |
| 5   | 5725.00     | 33.97              | 3.69            | 50.34          | 33.56           | 54.44                   | 122.80          | 68.36       | Peak   |
| 6   | 5744.38     | 34.00              | 3.70            | 90.52          | 33.55           | 94.67                   | -----           | -----       | Peak   |

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 3m Chamber Data no. : 4  
 Dis. / Ant. : 3m 2022 MCTD1209-3006 Ant. pol. : VERTICAL  
 Limit : FCC 15E PK U-NII-3  
 Env. / Ins. : 23.2°C/52.5% Engineer : Allen  
 Test Mode : 11a 5745MHz TX

| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark |
|-----|-------------|--------------------|-----------------|----------------|-----------------|-------------------------|-----------------|-------------|--------|
| 1   | 5460.00     | 32.70              | 3.58            | 45.80          | 33.61           | 48.47                   | 68.20           | 19.73       | Peak   |
| 2   | 5650.00     | 33.50              | 3.66            | 45.35          | 33.57           | 48.94                   | 68.20           | 19.26       | Peak   |
| 3   | 5700.00     | 33.90              | 3.68            | 46.30          | 33.56           | 50.32                   | 105.20          | 54.88       | Peak   |
| 4   | 5720.00     | 33.97              | 3.69            | 46.93          | 33.56           | 51.03                   | 110.80          | 59.77       | Peak   |
| 5   | 5725.00     | 33.97              | 3.69            | 50.29          | 33.56           | 54.39                   | 122.80          | 68.41       | Peak   |
| 6   | 5744.38     | 34.00              | 3.70            | 89.17          | 33.55           | 93.32                   | -----           | -----       | Peak   |


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.

FCC ID: Y9E-IAD-18010A




| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading factor (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark |
|-----|-------------|--------------------|-----------------|-----------------------|-----------------|-------------------------|-----------------|-------------|--------|
| 1   | 5823.40     | 34.10              | 3.73            | 89.73                 | 33.54           | 94.02                   | 122.20          | 72.03       | Peak   |
| 2   | 5850.00     | 34.20              | 3.74            | 45.76                 | 33.53           | 50.17                   | 122.20          | 72.03       | Peak   |
| 3   | 5855.00     | 34.33              | 3.75            | 45.07                 | 33.53           | 49.62                   | 110.80          | 61.18       | Peak   |
| 4   | 5875.00     | 34.47              | 3.75            | 48.70                 | 33.53           | 49.39                   | 105.20          | 55.01       | Peak   |
| 5   | 5925.00     | 35.00              | 3.77            | 45.79                 | 33.52           | 51.04                   | 68.20           | 17.16       | Peak   |
| 6   | 7250.00     | 36.20              | 4.15            | 44.07                 | 33.88           | 50.54                   | 68.20           | 17.66       | Peak   |

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.




| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading factor (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark |
|-----|-------------|--------------------|-----------------|-----------------------|-----------------|-------------------------|-----------------|-------------|--------|
| 1   | 5823.40     | 34.10              | 3.73            | 87.98                 | 33.54           | 92.27                   | 122.20          | 72.16       | Peak   |
| 2   | 5850.00     | 34.20              | 3.74            | 45.63                 | 33.53           | 50.04                   | 122.20          | 72.16       | Peak   |
| 3   | 5855.00     | 34.33              | 3.75            | 46.04                 | 33.53           | 50.59                   | 110.80          | 60.21       | Peak   |
| 4   | 5875.00     | 34.47              | 3.75            | 44.85                 | 33.53           | 49.54                   | 105.20          | 55.66       | Peak   |
| 5   | 5925.00     | 35.00              | 3.77            | 45.38                 | 33.52           | 50.63                   | 68.20           | 17.57       | Peak   |
| 6   | 7250.00     | 36.20              | 4.15            | 44.93                 | 33.88           | 51.40                   | 68.20           | 16.80       | Peak   |

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.




| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading factor (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark  |
|-----|-------------|--------------------|-----------------|-----------------------|-----------------|-------------------------|-----------------|-------------|---------|
| 1   | 5823.40     | 34.10              | 3.73            | 75.34                 | 33.54           | 79.61                   | 54.00           | 15.61       | Average |
| 2   | 7250.00     | 36.20              | 4.15            | 31.92                 | 33.88           | 38.39                   | 54.00           | 15.61       | Average |

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.




| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading factor (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark  |
|-----|-------------|--------------------|-----------------|-----------------------|-----------------|-------------------------|-----------------|-------------|---------|
| 1   | 5825.35     | 34.10              | 3.73            | 77.40                 | 33.54           | 81.69                   | 54.00           | 15.66       | Average |
| 2   | 7250.00     | 36.20              | 4.15            | 31.87                 | 33.88           | 38.34                   | 54.00           | 15.66       | Average |

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.




| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark  |
|-----|-------------|--------------------|-----------------|----------------|-----------------|-------------------------|-----------------|-------------|---------|
| 1   | 5460.00     | 32.70              | 3.58            | 32.45          | 33.61           | 35.12                   | 54.00           | 18.88       | Average |
| 2   | 5743.54     | 34.00              | 3.70            | 80.04          | 33.55           | 84.19                   | -----           | -----       | Average |

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading  
 -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.




| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark  |
|-----|-------------|--------------------|-----------------|----------------|-----------------|-------------------------|-----------------|-------------|---------|
| 1   | 5460.00     | 32.70              | 3.58            | 32.40          | 33.61           | 35.07                   | 54.00           | 18.93       | Average |
| 2   | 5746.06     | 34.00              | 3.70            | 78.12          | 33.55           | 82.27                   | -----           | -----       | Average |

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading  
 -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.



| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark |
|-----|-------------|--------------------|-----------------|----------------|-----------------|-------------------------|-----------------|-------------|--------|
| 1   | 5460.00     | 32.70              | 3.58            | 45.14          | 33.61           | 47.81                   | 68.20           | 20.39       | Peak   |
| 2   | 5650.00     | 33.50              | 3.66            | 45.75          | 33.57           | 49.34                   | 68.20           | 18.86       | Peak   |
| 3   | 5700.00     | 33.90              | 3.68            | 45.64          | 33.56           | 49.66                   | 105.20          | 55.54       | Peak   |
| 4   | 5720.00     | 33.97              | 3.69            | 46.11          | 33.56           | 50.21                   | 110.80          | 60.59       | Peak   |
| 5   | 5725.00     | 33.97              | 3.69            | 45.39          | 33.56           | 49.49                   | 122.80          | 73.31       | Peak   |
| 6   | 5743.96     | 34.00              | 3.70            | 88.34          | 33.55           | 92.49                   | -----           | -----       | Peak   |


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading  
 -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.



| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark |
|-----|-------------|--------------------|-----------------|----------------|-----------------|-------------------------|-----------------|-------------|--------|
| 1   | 5460.00     | 32.70              | 3.58            | 46.34          | 33.61           | 49.01                   | 68.20           | 19.19       | Peak   |
| 2   | 5650.00     | 33.50              | 3.66            | 46.39          | 33.57           | 49.98                   | 68.20           | 18.22       | Peak   |
| 3   | 5700.00     | 33.90              | 3.68            | 47.10          | 33.56           | 51.12                   | 105.20          | 54.08       | Peak   |
| 4   | 5720.00     | 33.97              | 3.69            | 48.58          | 33.56           | 52.68                   | 110.80          | 58.12       | Peak   |
| 5   | 5725.00     | 33.97              | 3.69            | 54.55          | 33.56           | 58.65                   | 122.80          | 64.15       | Peak   |
| 6   | 5744.80     | 34.00              | 3.70            | 90.20          | 33.55           | 94.35                   | -----           | -----       | Peak   |

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading  
 -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.


FCC ID: Y9E-IAD-18010A



Site no. : 3m Chamber Data no. : 37  
 Dis. / Ant. : 3m 2022 MCTD1209-3006 Ant. pol. : HORIZONTAL  
 Limit : FCC 15E PK U-NII-3  
 Env. / Ins. : 23.2°C/52.5% Engineer : Allen  
 Test Mode : 11n20 5825MHz TX

| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading factor (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark |
|-----|-------------|--------------------|-----------------|-----------------------|-----------------|-------------------------|-----------------|-------------|--------|
| 1   | 5825.35     | 34.10              | 3.73            | 89.57                 | 33.54           | 93.86                   | 122.20          | 72.90       | Peak   |
| 2   | 5850.00     | 34.20              | 3.74            | 44.89                 | 33.53           | 49.30                   | 110.80          | 59.33       | Peak   |
| 3   | 5855.00     | 34.33              | 3.75            | 46.92                 | 33.53           | 51.47                   | 105.20          | 55.27       | Peak   |
| 4   | 5875.00     | 34.47              | 3.75            | 45.24                 | 33.53           | 49.93                   | 68.20           | 17.10       | Peak   |
| 5   | 5925.00     | 35.00              | 3.77            | 45.85                 | 33.52           | 51.10                   | 68.20           | 17.10       | Peak   |
| 6   | 7250.00     | 36.20              | 4.15            | 44.69                 | 33.88           | 51.16                   | 68.20           | 17.04       | Peak   |


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 38  
 Dis. / Ant. : 3m 2022 MCTD1209-3006 Ant. pol. : VERTICAL  
 Limit : FCC 15E PK U-NII-3  
 Env. / Ins. : 23.2°C/52.5% Engineer : Allen  
 Test Mode : 11n20 5825MHz TX

| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading factor (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark |
|-----|-------------|--------------------|-----------------|-----------------------|-----------------|-------------------------|-----------------|-------------|--------|
| 1   | 5823.40     | 34.10              | 3.73            | 87.40                 | 33.54           | 91.69                   | 122.20          | 72.11       | Peak   |
| 2   | 5850.00     | 34.20              | 3.74            | 45.68                 | 33.53           | 50.09                   | 110.80          | 60.54       | Peak   |
| 3   | 5855.00     | 34.33              | 3.75            | 45.71                 | 33.53           | 50.26                   | 105.20          | 55.18       | Peak   |
| 4   | 5875.00     | 34.47              | 3.75            | 45.33                 | 33.53           | 50.02                   | 68.20           | 17.45       | Peak   |
| 5   | 5925.00     | 35.00              | 3.77            | 45.50                 | 33.52           | 50.75                   | 68.20           | 17.45       | Peak   |
| 6   | 7250.00     | 36.20              | 4.15            | 43.90                 | 33.88           | 50.37                   | 68.20           | 17.83       | Peak   |


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 39  
 Dis. / Ant. : 3m 2022 MCTD1209-3006 Ant. pol. : VERTICAL  
 Limit : FCC 15E AV  
 Env. / Ins. : 23.2°C/52.5% Engineer : Allen  
 Test Mode : 11n20 5825MHz TX

| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading factor (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark  |
|-----|-------------|--------------------|-----------------|-----------------------|-----------------|-------------------------|-----------------|-------------|---------|
| 1   | 5823.40     | 34.10              | 3.73            | 76.22                 | 33.54           | 80.51                   | 54.00           | 15.57       | Average |
| 2   | 7250.00     | 36.20              | 4.15            | 31.96                 | 33.88           | 38.43                   | 54.00           | 15.57       | Average |


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 40  
 Dis. / Ant. : 3m 2022 MCTD1209-3006 Ant. pol. : HORIZONTAL  
 Limit : FCC 15E AV  
 Env. / Ins. : 23.2°C/52.5% Engineer : Allen  
 Test Mode : 11n20 5825MHz TX


| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading factor (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark  |
|-----|-------------|--------------------|-----------------|-----------------------|-----------------|-------------------------|-----------------|-------------|---------|
| 1   | 5823.40     | 34.10              | 3.73            | 76.97                 | 33.54           | 81.26                   | 54.00           | 15.64       | Average |
| 2   | 7250.00     | 36.20              | 4.15            | 31.89                 | 33.88           | 38.36                   | 54.00           | 15.64       | Average |

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.




| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark  |
|-----|-------------|--------------------|-----------------|----------------|-----------------|-------------------------|-----------------|-------------|---------|
| 1   | 5460.00     | 32.70              | 3.58            | 32.42          | 33.61           | 35.09                   | 54.00           | 18.91       | Average |
| 2   | 5752.60     | 33.97              | 3.71            | 75.34          | 33.55           | 79.47                   | -----           | -----       | Average |

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading  
 -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.




| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark  |
|-----|-------------|--------------------|-----------------|----------------|-----------------|-------------------------|-----------------|-------------|---------|
| 1   | 5460.00     | 32.70              | 3.58            | 32.36          | 33.61           | 35.03                   | 54.00           | 18.97       | Average |
| 2   | 5753.48     | 33.97              | 3.71            | 73.21          | 33.55           | 77.34                   | -----           | -----       | Average |

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading  
 -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.




| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark |
|-----|-------------|--------------------|-----------------|----------------|-----------------|-------------------------|-----------------|-------------|--------|
| 1   | 5460.00     | 32.70              | 3.58            | 44.55          | 33.61           | 47.22                   | 68.20           | 20.98       | Peak   |
| 2   | 5650.00     | 33.50              | 3.66            | 45.42          | 33.57           | 49.01                   | 68.20           | 19.19       | Peak   |
| 3   | 5700.00     | 33.90              | 3.68            | 45.73          | 33.56           | 49.75                   | 105.20          | 55.45       | Peak   |
| 4   | 5720.00     | 33.97              | 3.69            | 45.80          | 33.56           | 49.90                   | 110.80          | 60.90       | Peak   |
| 5   | 5725.00     | 33.97              | 3.69            | 46.26          | 33.56           | 50.36                   | 122.80          | 72.44       | Peak   |
| 6   | 5753.04     | 33.97              | 3.71            | 85.47          | 33.55           | 89.60                   | -----           | -----       | Peak   |

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading  
 -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.




| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark |
|-----|-------------|--------------------|-----------------|----------------|-----------------|-------------------------|-----------------|-------------|--------|
| 1   | 5460.00     | 32.70              | 3.58            | 45.31          | 33.61           | 47.96                   | 68.20           | 20.22       | Peak   |
| 2   | 5650.00     | 33.50              | 3.66            | 46.28          | 33.57           | 49.87                   | 68.20           | 18.33       | Peak   |
| 3   | 5700.00     | 33.90              | 3.68            | 45.28          | 33.56           | 49.30                   | 105.20          | 55.90       | Peak   |
| 4   | 5720.00     | 33.97              | 3.69            | 49.00          | 33.56           | 53.10                   | 110.80          | 57.70       | Peak   |
| 5   | 5725.00     | 33.97              | 3.69            | 47.06          | 33.56           | 51.16                   | 122.80          | 71.64       | Peak   |
| 6   | 5754.36     | 33.97              | 3.71            | 87.19          | 33.55           | 91.32                   | -----           | -----       | Peak   |

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading  
 -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.




| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading factor (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark |
|-----|-------------|--------------------|-----------------|-----------------------|-----------------|-------------------------|-----------------|-------------|--------|
| 1   | 5460.00     | 32.70              | 3.58            | 45.34                 | 33.61           | 48.01                   | 68.20           | 20.19       | Peak   |
| 2   | 5650.00     | 33.50              | 3.66            | 45.64                 | 33.57           | 49.23                   | 68.20           | 18.97       | Peak   |
| 3   | 5700.00     | 33.90              | 3.68            | 46.22                 | 33.56           | 50.24                   | 105.20          | 54.96       | Peak   |
| 4   | 5720.00     | 33.97              | 3.69            | 46.53                 | 33.56           | 50.63                   | 110.80          | 60.17       | Peak   |
| 5   | 5725.00     | 33.97              | 3.69            | 53.32                 | 33.56           | 57.42                   | 122.80          | 65.38       | Peak   |
| 6   | 5744.38     | 34.00              | 3.70            | 92.18                 | 33.55           | 96.33                   | -----           | -----       | Peak   |

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.




| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading factor (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark |
|-----|-------------|--------------------|-----------------|-----------------------|-----------------|-------------------------|-----------------|-------------|--------|
| 1   | 5460.00     | 32.70              | 3.58            | 45.57                 | 33.61           | 48.24                   | 68.20           | 19.96       | Peak   |
| 2   | 5650.00     | 33.50              | 3.66            | 45.72                 | 33.57           | 49.31                   | 68.20           | 18.89       | Peak   |
| 3   | 5700.00     | 33.90              | 3.68            | 45.46                 | 33.56           | 49.48                   | 105.20          | 55.72       | Peak   |
| 4   | 5720.00     | 33.97              | 3.69            | 45.68                 | 33.56           | 49.78                   | 110.80          | 61.02       | Peak   |
| 5   | 5725.00     | 33.97              | 3.69            | 46.48                 | 33.56           | 50.58                   | 122.80          | 72.22       | Peak   |
| 6   | 5745.64     | 34.00              | 3.70            | 89.48                 | 33.55           | 93.63                   | -----           | -----       | Peak   |

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.




| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading factor (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark  |
|-----|-------------|--------------------|-----------------|-----------------------|-----------------|-------------------------|-----------------|-------------|---------|
| 1   | 5460.00     | 32.70              | 3.58            | 32.60                 | 33.61           | 35.27                   | 54.00           | 18.73       | Average |
| 2   | 5744.06     | 34.00              | 3.70            | 78.71                 | 33.55           | 82.86                   | -----           | -----       | Average |

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.



| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading factor (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark  |
|-----|-------------|--------------------|-----------------|-----------------------|-----------------|-------------------------|-----------------|-------------|---------|
| 1   | 5460.00     | 32.70              | 3.58            | 32.66                 | 33.61           | 35.33                   | 54.00           | 18.67       | Average |
| 2   | 5744.38     | 34.00              | 3.70            | 79.78                 | 33.55           | 83.93                   | -----           | -----       | Average |


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 57  
 Dis. / Ant. : 3m 2022 MCTD1209-3006 Ant. pol. : HORIZONTAL  
 Limit : FCC 15E AV  
 Env. / Ins. : 23.2°C/52.5% Engineer : Allen  
 Test Mode : 11n40 5795MHz TX

| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark  |
|-----|-------------|--------------------|-----------------|----------------|-----------------|-------------------------|-----------------|-------------|---------|
| 1   | 5791.84     | 33.90              | 3.72            | 75.72          | 33.54           | 79.80                   | -----           | -----       | Average |
| 2   | 7250.00     | 36.20              | 4.15            | 33.10          | 33.88           | 39.57                   | 54.00           | 14.43       | Average |


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 58  
 Dis. / Ant. : 3m 2022 MCTD1209-3006 Ant. pol. : VERTICAL  
 Limit : FCC 15E AV  
 Env. / Ins. : 23.2°C/52.5% Engineer : Allen  
 Test Mode : 11n40 5795MHz TX

| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark  |
|-----|-------------|--------------------|-----------------|----------------|-----------------|-------------------------|-----------------|-------------|---------|
| 1   | 5791.84     | 33.90              | 3.72            | 72.20          | 33.54           | 76.28                   | -----           | -----       | Average |
| 2   | 7250.00     | 36.20              | 4.15            | 32.08          | 33.88           | 38.55                   | 54.00           | 15.45       | Average |


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 59  
 Dis. / Ant. : 3m 2022 MCTD1209-3006 Ant. pol. : VERTICAL  
 Limit : FCC 15E PK U-NII-3  
 Env. / Ins. : 23.2°C/52.5% Engineer : Allen  
 Test Mode : 11n40 5795MHz TX

| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark |
|-----|-------------|--------------------|-----------------|----------------|-----------------|-------------------------|-----------------|-------------|--------|
| 1   | 5791.84     | 33.90              | 3.72            | 85.34          | 33.54           | 89.42                   | -----           | -----       | Peak   |
| 2   | 5850.00     | 34.20              | 3.74            | 44.95          | 33.53           | 49.36                   | 122.20          | 72.84       | Peak   |
| 3   | 5855.00     | 34.33              | 3.75            | 45.28          | 33.53           | 49.83                   | 110.80          | 60.97       | Peak   |
| 4   | 5875.00     | 34.47              | 3.75            | 45.88          | 33.53           | 50.57                   | 105.20          | 54.63       | Peak   |
| 5   | 5925.00     | 35.00              | 3.77            | 45.56          | 33.52           | 50.81                   | 68.20           | 17.39       | Peak   |
| 6   | 7250.00     | 36.20              | 4.15            | 44.70          | 33.88           | 51.17                   | 68.20           | 17.03       | Peak   |


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 60  
 Dis. / Ant. : 3m 2022 MCTD1209-3006 Ant. pol. : HORIZONTAL  
 Limit : FCC 15E PK U-NII-3  
 Env. / Ins. : 23.2°C/52.5% Engineer : Allen  
 Test Mode : 11n40 5795MHz TX

| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark |
|-----|-------------|--------------------|-----------------|----------------|-----------------|-------------------------|-----------------|-------------|--------|
| 1   | 5791.84     | 33.90              | 3.72            | 87.28          | 33.54           | 91.36                   | -----           | -----       | Peak   |
| 2   | 5850.00     | 34.20              | 3.74            | 46.33          | 33.53           | 50.74                   | 122.20          | 71.46       | Peak   |
| 3   | 5855.00     | 34.33              | 3.75            | 45.33          | 33.53           | 49.88                   | 110.80          | 60.92       | Peak   |
| 4   | 5875.00     | 34.47              | 3.75            | 45.62          | 33.53           | 50.31                   | 105.20          | 54.89       | Peak   |
| 5   | 5925.00     | 35.00              | 3.77            | 45.70          | 33.52           | 50.95                   | 68.20           | 17.25       | Peak   |
| 6   | 7250.00     | 36.20              | 4.15            | 44.99          | 33.88           | 51.46                   | 68.20           | 16.74       | Peak   |


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 73  
 Dis. / Ant. : 3m 2022 MCTD1209-3006 Ant. pol. : VERTICAL  
 Limit : FCC 15E PK U-NII-3  
 Env. / Ins. : 23.2°C/52.5% Engineer : Allen  
 Test Mode : 11ac20 5825MHz TX

| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading factor (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark |
|-----|-------------|--------------------|-----------------|-----------------------|-----------------|-------------------------|-----------------|-------------|--------|
| 1   | 5823.40     | 34.10              | 3.73            | 87.55                 | 33.54           | 91.84                   | 122.20          | 72.54       | Peak   |
| 2   | 5850.00     | 34.20              | 3.74            | 45.25                 | 33.53           | 49.66                   | 122.20          | 72.54       | Peak   |
| 3   | 5855.00     | 34.33              | 3.75            | 45.87                 | 33.53           | 50.42                   | 110.80          | 60.38       | Peak   |
| 4   | 5875.00     | 34.47              | 3.75            | 45.41                 | 33.53           | 50.10                   | 105.20          | 55.10       | Peak   |
| 5   | 5925.00     | 35.00              | 3.77            | 45.52                 | 33.52           | 50.77                   | 68.20           | 17.43       | Peak   |
| 6   | 7250.00     | 36.20              | 4.15            | 43.93                 | 33.88           | 50.40                   | 68.20           | 17.80       | Peak   |


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 74  
 Dis. / Ant. : 3m 2022 MCTD1209-3006 Ant. pol. : HORIZONTAL  
 Limit : FCC 15E PK U-NII-3  
 Env. / Ins. : 23.2°C/52.5% Engineer : Allen  
 Test Mode : 11ac20 5825MHz TX

| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading factor (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark |
|-----|-------------|--------------------|-----------------|-----------------------|-----------------|-------------------------|-----------------|-------------|--------|
| 1   | 5823.40     | 34.10              | 3.73            | 89.77                 | 33.54           | 94.06                   | 122.20          | 71.89       | Peak   |
| 2   | 5850.00     | 34.20              | 3.74            | 45.90                 | 33.53           | 50.31                   | 122.20          | 71.89       | Peak   |
| 3   | 5855.00     | 34.33              | 3.75            | 44.75                 | 33.53           | 49.30                   | 110.80          | 61.50       | Peak   |
| 4   | 5875.00     | 34.47              | 3.75            | 45.71                 | 33.53           | 50.40                   | 105.20          | 54.80       | Peak   |
| 5   | 5925.00     | 35.00              | 3.77            | 45.01                 | 33.52           | 50.26                   | 68.20           | 17.94       | Peak   |
| 6   | 7250.00     | 36.20              | 4.15            | 44.04                 | 33.88           | 50.51                   | 68.20           | 17.69       | Peak   |


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 75  
 Dis. / Ant. : 3m 2022 MCTD1209-3006 Ant. pol. : HORIZONTAL  
 Limit : FCC 15E AV  
 Env. / Ins. : 23.2°C/52.5% Engineer : Allen  
 Test Mode : 11ac20 5825MHz TX

| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading factor (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark  |
|-----|-------------|--------------------|-----------------|-----------------------|-----------------|-------------------------|-----------------|-------------|---------|
| 1   | 5823.40     | 34.10              | 3.73            | 78.71                 | 33.54           | 83.00                   | 54.00           | 15.56       | Average |
| 2   | 7250.00     | 36.20              | 4.15            | 31.97                 | 33.88           | 38.44                   | 54.00           | 15.56       | Average |


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 76  
 Dis. / Ant. : 3m 2022 MCTD1209-3006 Ant. pol. : VERTICAL  
 Limit : FCC 15E AV  
 Env. / Ins. : 23.2°C/52.5% Engineer : Allen  
 Test Mode : 11ac20 5825MHz TX


| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading factor (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark  |
|-----|-------------|--------------------|-----------------|-----------------------|-----------------|-------------------------|-----------------|-------------|---------|
| 1   | 5823.40     | 34.10              | 3.73            | 75.49                 | 33.54           | 79.76                   | 54.00           | 15.63       | Average |
| 2   | 7250.00     | 36.20              | 4.15            | 31.90                 | 33.88           | 38.37                   | 54.00           | 15.63       | Average |

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.




| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading factor (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark  |
|-----|-------------|--------------------|-----------------|-----------------------|-----------------|-------------------------|-----------------|-------------|---------|
| 1   | 5460.00     | 32.70              | 3.58            | 32.35                 | 33.61           | 35.02                   | 54.00           | 18.98       | Average |
| 2   | 5753.92     | 33.97              | 3.71            | 73.33                 | 33.55           | 77.46                   | -----           | -----       | Average |

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.




| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading factor (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark  |
|-----|-------------|--------------------|-----------------|-----------------------|-----------------|-------------------------|-----------------|-------------|---------|
| 1   | 5460.00     | 32.70              | 3.58            | 32.46                 | 33.61           | 35.13                   | 54.00           | 18.87       | Average |
| 2   | 5753.48     | 33.97              | 3.71            | 74.77                 | 33.55           | 78.90                   | -----           | -----       | Average |

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.



| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading factor (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark |
|-----|-------------|--------------------|-----------------|-----------------------|-----------------|-------------------------|-----------------|-------------|--------|
| 1   | 5460.00     | 32.70              | 3.58            | 45.48                 | 33.61           | 48.15                   | 68.20           | 20.05       | Peak   |
| 2   | 5650.00     | 33.50              | 3.66            | 46.17                 | 33.57           | 49.76                   | 68.20           | 18.44       | Peak   |
| 3   | 5700.00     | 33.90              | 3.68            | 45.69                 | 33.56           | 49.71                   | 105.20          | 55.49       | Peak   |
| 4   | 5720.00     | 33.97              | 3.69            | 47.00                 | 33.56           | 51.10                   | 110.80          | 59.70       | Peak   |
| 5   | 5725.00     | 33.97              | 3.69            | 48.32                 | 33.56           | 52.42                   | 122.80          | 70.38       | Peak   |
| 6   | 5753.48     | 33.97              | 3.71            | 87.46                 | 33.55           | 91.59                   | -----           | -----       | Peak   |


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.



| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading factor (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark |
|-----|-------------|--------------------|-----------------|-----------------------|-----------------|-------------------------|-----------------|-------------|--------|
| 1   | 5460.00     | 32.70              | 3.58            | 45.98                 | 33.61           | 48.65                   | 68.20           | 19.55       | Peak   |
| 2   | 5650.00     | 33.50              | 3.66            | 46.82                 | 33.57           | 50.41                   | 68.20           | 17.79       | Peak   |
| 3   | 5700.00     | 33.90              | 3.68            | 45.19                 | 33.56           | 49.21                   | 105.20          | 55.99       | Peak   |
| 4   | 5720.00     | 33.97              | 3.69            | 45.54                 | 33.56           | 49.64                   | 110.80          | 61.16       | Peak   |
| 5   | 5725.00     | 33.97              | 3.69            | 46.05                 | 33.56           | 50.15                   | 122.80          | 72.65       | Peak   |
| 6   | 5757.44     | 33.97              | 3.71            | 85.34                 | 33.55           | 89.47                   | -----           | -----       | Peak   |

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.


FCC ID: Y9E-IAD-18010A



Site no. : 3m Chamber Data no. : 89  
 Dis. / Ant. : 3m 2022 MCTD1209-3006 Ant. pol. : VERTICAL  
 Limit : FCC 15E PK U-NII-3  
 Env. / Ins. : 23.2°C/52.5% Engineer : Allen  
 Test Mode : 11ac40 5795MHz TX

| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading factor (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark |
|-----|-------------|--------------------|-----------------|-----------------------|-----------------|-------------------------|-----------------|-------------|--------|
| 1   | 5795.82     | 33.90              | 3.72            | 64.95                 | 33.54           | 89.03                   | 122.20          | 71.00       | Peak   |
| 2   | 5850.00     | 34.20              | 3.74            | 46.79                 | 33.53           | 51.20                   | 122.20          | 71.00       | Peak   |
| 3   | 5855.00     | 34.33              | 3.75            | 46.06                 | 33.53           | 50.61                   | 110.80          | 60.19       | Peak   |
| 4   | 5875.00     | 34.47              | 3.75            | 45.22                 | 33.53           | 49.91                   | 105.20          | 55.29       | Peak   |
| 5   | 5925.00     | 35.00              | 3.77            | 44.75                 | 33.52           | 50.00                   | 68.20           | 18.20       | Peak   |
| 6   | 7250.00     | 36.20              | 4.15            | 44.39                 | 33.88           | 50.86                   | 68.20           | 17.34       | Peak   |


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 90  
 Dis. / Ant. : 3m 2022 MCTD1209-3006 Ant. pol. : HORIZONTAL  
 Limit : FCC 15E PK U-NII-3  
 Env. / Ins. : 23.2°C/52.5% Engineer : Allen  
 Test Mode : 11ac40 5795MHz TX

| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading factor (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark |
|-----|-------------|--------------------|-----------------|-----------------------|-----------------|-------------------------|-----------------|-------------|--------|
| 1   | 5791.84     | 33.90              | 3.72            | 87.02                 | 33.54           | 91.10                   | 122.20          | 72.14       | Peak   |
| 2   | 5850.00     | 34.20              | 3.74            | 45.65                 | 33.53           | 50.06                   | 122.20          | 72.14       | Peak   |
| 3   | 5855.00     | 34.33              | 3.75            | 46.28                 | 33.53           | 50.89                   | 110.80          | 59.97       | Peak   |
| 4   | 5875.00     | 34.47              | 3.75            | 45.32                 | 33.53           | 50.01                   | 105.20          | 55.19       | Peak   |
| 5   | 5925.00     | 35.00              | 3.77            | 45.48                 | 33.52           | 50.73                   | 68.20           | 17.47       | Peak   |
| 6   | 7250.00     | 36.20              | 4.15            | 44.38                 | 33.88           | 50.85                   | 68.20           | 17.35       | Peak   |


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 91  
 Dis. / Ant. : 3m 2022 MCTD1209-3006 Ant. pol. : HORIZONTAL  
 Limit : FCC 15E AV  
 Env. / Ins. : 23.2°C/52.5% Engineer : Allen  
 Test Mode : 11ac40 5795MHz TX

| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading factor (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark  |
|-----|-------------|--------------------|-----------------|-----------------------|-----------------|-------------------------|-----------------|-------------|---------|
| 1   | 5791.84     | 33.90              | 3.72            | 74.40                 | 33.54           | 79.48                   | 54.00           | 15.68       | Average |
| 2   | 7250.00     | 36.20              | 4.15            | 31.85                 | 33.88           | 38.32                   | 54.00           | 15.68       | Average |


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 92  
 Dis. / Ant. : 3m 2022 MCTD1209-3006 Ant. pol. : VERTICAL  
 Limit : FCC 15E AV  
 Env. / Ins. : 23.2°C/52.5% Engineer : Allen  
 Test Mode : 11ac40 5795MHz TX


| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading factor (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark  |
|-----|-------------|--------------------|-----------------|-----------------------|-----------------|-------------------------|-----------------|-------------|---------|
| 1   | 5791.84     | 33.90              | 3.72            | 71.50                 | 33.54           | 75.58                   | 54.00           | 15.61       | Average |
| 2   | 7250.00     | 36.20              | 4.15            | 31.92                 | 33.88           | 38.39                   | 54.00           | 15.61       | Average |

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.




| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark  |
|-----|-------------|--------------------|-----------------|----------------|-----------------|-------------------------|-----------------|-------------|---------|
| 1   | 5460.00     | 32.70              | 3.58            | 32.43          | 33.61           | 35.10                   | 54.00           | 18.90       | Average |
| 2   | 5777.20     | 33.93              | 3.71            | 68.65          | 33.55           | 72.74                   | -----           | -----       | Average |

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading  
 -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.




| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark  |
|-----|-------------|--------------------|-----------------|----------------|-----------------|-------------------------|-----------------|-------------|---------|
| 1   | 5460.00     | 32.70              | 3.58            | 32.46          | 33.61           | 35.13                   | 54.00           | 18.87       | Average |
| 2   | 5771.92     | 33.93              | 3.71            | 69.55          | 33.55           | 73.64                   | -----           | -----       | Average |

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading  
 -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.



| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark |
|-----|-------------|--------------------|-----------------|----------------|-----------------|-------------------------|-----------------|-------------|--------|
| 1   | 5460.00     | 32.70              | 3.58            | 45.62          | 33.61           | 48.49                   | 68.20           | 19.71       | Peak   |
| 2   | 5650.00     | 33.50              | 3.66            | 45.49          | 33.57           | 49.08                   | 68.20           | 19.12       | Peak   |
| 3   | 5700.00     | 33.90              | 3.68            | 46.72          | 33.56           | 50.74                   | 105.20          | 54.46       | Peak   |
| 4   | 5720.00     | 33.97              | 3.69            | 49.62          | 33.56           | 53.72                   | 110.80          | 57.08       | Peak   |
| 5   | 5725.00     | 33.97              | 3.69            | 48.55          | 33.56           | 52.65                   | 122.80          | 70.15       | Peak   |
| 6   | 5773.84     | 33.93              | 3.71            | 84.35          | 33.55           | 88.44                   | -----           | -----       | Peak   |


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading  
 -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.



| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark |
|-----|-------------|--------------------|-----------------|----------------|-----------------|-------------------------|-----------------|-------------|--------|
| 1   | 5460.00     | 32.70              | 3.58            | 45.49          | 33.61           | 48.16                   | 68.20           | 20.04       | Peak   |
| 2   | 5650.00     | 33.50              | 3.66            | 45.39          | 33.57           | 48.98                   | 68.20           | 19.22       | Peak   |
| 3   | 5700.00     | 33.90              | 3.68            | 47.19          | 33.56           | 51.21                   | 105.20          | 53.99       | Peak   |
| 4   | 5720.00     | 33.97              | 3.69            | 47.07          | 33.56           | 51.17                   | 110.80          | 59.63       | Peak   |
| 5   | 5725.00     | 33.97              | 3.69            | 47.00          | 33.56           | 51.10                   | 122.80          | 71.70       | Peak   |
| 6   | 5769.52     | 33.93              | 3.71            | 82.49          | 33.55           | 86.58                   | -----           | -----       | Peak   |

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading  
 -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.


FCC ID: Y9E-IAD-18010A



Site no. : 3m Chamber Data no. : 101  
 Dis. / Ant. : 3m 2022 MCTD1209-3006 Ant. pol. : HORIZONTAL  
 Limit : FCC 15E PK U-NII-3  
 Env. / Ins. : 23.2°C/52.5% Engineer : Allen  
 Test Mode : 11ac80 5775MHz TX

| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading factor (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark |
|-----|-------------|--------------------|-----------------|-----------------------|-----------------|-------------------------|-----------------|-------------|--------|
| 1   | 5776.84     | 33.93              | 3.71            | 83.97                 | 33.55           | 88.06                   | -----           | -----       | Peak   |
| 2   | 5850.00     | 34.20              | 3.74            | 46.28                 | 33.53           | 50.69                   | 122.20          | 71.51       | Peak   |
| 3   | 5855.00     | 34.33              | 3.75            | 47.53                 | 33.53           | 52.08                   | 110.80          | 58.72       | Peak   |
| 4   | 5875.00     | 34.47              | 3.75            | 45.73                 | 33.53           | 50.42                   | 105.20          | 54.78       | Peak   |
| 5   | 5925.00     | 35.00              | 3.77            | 45.58                 | 33.52           | 50.83                   | 68.20           | 17.37       | Peak   |
| 6   | 7250.00     | 36.20              | 4.15            | 44.21                 | 33.88           | 50.68                   | 68.20           | 17.52       | Peak   |


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 102  
 Dis. / Ant. : 3m 2022 MCTD1209-3006 Ant. pol. : VERTICAL  
 Limit : FCC 15E PK U-NII-3  
 Env. / Ins. : 23.2°C/52.5% Engineer : Allen  
 Test Mode : 11ac80 5775MHz TX

| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading factor (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark |
|-----|-------------|--------------------|-----------------|-----------------------|-----------------|-------------------------|-----------------|-------------|--------|
| 1   | 5776.78     | 33.93              | 3.71            | 82.38                 | 33.55           | 86.47                   | -----           | -----       | Peak   |
| 2   | 5850.00     | 34.20              | 3.74            | 46.66                 | 33.53           | 51.07                   | 122.20          | 71.13       | Peak   |
| 3   | 5855.00     | 34.33              | 3.75            | 45.84                 | 33.53           | 50.39                   | 110.80          | 60.41       | Peak   |
| 4   | 5875.00     | 34.47              | 3.75            | 45.62                 | 33.53           | 50.31                   | 105.20          | 54.89       | Peak   |
| 5   | 5925.00     | 35.00              | 3.77            | 45.98                 | 33.52           | 51.23                   | 68.20           | 16.97       | Peak   |
| 6   | 7250.00     | 36.20              | 4.15            | 45.15                 | 33.88           | 51.62                   | 68.20           | 16.58       | Peak   |


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 103  
 Dis. / Ant. : 3m 2022 MCTD1209-3006 Ant. pol. : VERTICAL  
 Limit : FCC 15E AV  
 Env. / Ins. : 23.2°C/52.5% Engineer : Allen  
 Test Mode : 11ac80 5775MHz TX

| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading factor (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark  |
|-----|-------------|--------------------|-----------------|-----------------------|-----------------|-------------------------|-----------------|-------------|---------|
| 1   | 5770.75     | 33.93              | 3.71            | 66.15                 | 33.55           | 70.24                   | -----           | -----       | Average |
| 2   | 7250.00     | 36.20              | 4.15            | 31.95                 | 33.88           | 38.42                   | 54.00           | 15.58       | Average |

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 104  
 Dis. / Ant. : 3m 2022 MCTD1209-3006 Ant. pol. : HORIZONTAL  
 Limit : FCC 15E AV  
 Env. / Ins. : 23.2°C/52.5% Engineer : Allen  
 Test Mode : 11ac80 5775MHz TX

| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading factor (dBuV) | Amp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark  |
|-----|-------------|--------------------|-----------------|-----------------------|-----------------|-------------------------|-----------------|-------------|---------|
| 1   | 5770.75     | 33.93              | 3.71            | 69.29                 | 33.55           | 73.36                   | -----           | -----       | Average |
| 2   | 7250.00     | 36.20              | 4.15            | 31.97                 | 33.88           | 38.44                   | 54.00           | 15.56       | Average |

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.

## 6. 6dB & 26dB & 99% Bandwidth Test

### 6.1. Test Equipments

| Item | Equipment           | Manufacturer | Model No.     | Serial No. | Last Cal. | Cal. Interval |
|------|---------------------|--------------|---------------|------------|-----------|---------------|
| 1.   | PXA Signal Analyzer | Agilent      | N9030A        | MY51380221 | Apr.07,22 | 1 Year        |
| 2.   | RF Cable            | HUBER+SUHNER | SUCOFLE X-106 | 505238/6   | Apr.06,22 | 1 Year        |

### 6.2. Limit

6dB Bandwidth should be not less than 500kHz

### 6.3. Test Procedure

#### **26dB Bandwidth:**

Use the test method described in ANSI C63.10 clause 12.4.1:

- Set RBW = approximately 1% of the emission bandwidth.
- Set the VBW > RBW.
- Detector = Peak.
- Trace mode = max hold.
- Measure the maximum width of the emission that is 26 dB down from the maximum of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.

#### **6dB Bandwidth:**

Use the test method described in 789033 D02 v02r01:

Section 15.407(e) specifies the minimum 6 dB emission bandwidth of at least 500 kHz for the band 5.725–5.85 GHz. The following procedure shall be used for measuring this bandwidth:

- Set RBW = 100 kHz.
- Set the video bandwidth (VBW)  $\geq 3$  RBW.
- Detector = Peak.
- Trace mode = max hold
- Sweep = auto couple
- Allow the trace to stabilize
- Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission

Note: The automatic bandwidth measurement capability of a spectrum analyzer or EMI receiver may be employed if it implements the functionality described in this section. For devices that use channel aggregation refer to III.A and III.C for determining emission bandwidth.

**99% Occupied bandwidth:**

Use the test method described in ANSI C63.10 Section 6.9.2:

The occupied bandwidth is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers are each equal to 0.5% of the total mean power of the given emission. The following procedure shall be used for measuring 99% power bandwidth:

- a) The instrument center frequency is set to the nominal EUT channel center frequency. The frequency span for the spectrum analyzer shall be between 1.5 times and 5.0 times the OBW.
- b) The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW, and VBW shall be approximately three times the RBW, unless otherwise specified by the applicable requirement.
- c) Set the reference level of the instrument as required, keeping the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than  $[10 \log (\text{OBW}/\text{RBW})]$  below the reference level. Specific guidance is given in 4.1.5.2.
- d) Step a) through step c) might require iteration to adjust within the specified range.
- e) Video averaging is not permitted. Where practical, a sample detection and single sweep mode shall be used. Otherwise, peak detection and max hold mode (until the trace stabilizes) shall be used.
- f) Use the 99% power bandwidth function of the instrument (if available) and report the measured bandwidth.
- g) If the instrument does not have a 99% power bandwidth function, then the trace data points are recovered and directly summed in linear power terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached; that frequency is recorded as the lower frequency. The process is repeated until 99.5% of the total is reached; that frequency is recorded as the upper frequency. The 99% power bandwidth is the difference between these two frequencies.
- h) The occupied bandwidth shall be reported by providing plot(s) of the measuring instrument display; the plot axes and the scale units per division shall be clearly labeled. Tabular data may be reported in addition to the plot(s).

**6.4. Test Results**

**U-NII-1 Band:**

|                         |                         |                          |
|-------------------------|-------------------------|--------------------------|
| EUT: Room Booking Panel |                         |                          |
| M/N: IAD-18010A         |                         |                          |
| Test date: 2023-01-11   | Pressure: 102.1±1.0 kpa | Humidity: 53.2±3.0%      |
| Tested by: Carl         | Test site: RF site      | Temperature: 22.3±0.6 °C |

**26dB bandwidth:**

| Test Mode        | Frequency (MHz) | 26dB Bandwidth (MHz) | Limit (kHz) |
|------------------|-----------------|----------------------|-------------|
| 11a              | 5180            | 20.98                | N/A         |
|                  | 5200            | 20.96                | N/A         |
|                  | 5240            | 21.05                | N/A         |
| 11n HT20         | 5180            | 21.22                | N/A         |
|                  | 5200            | 21.07                | N/A         |
|                  | 5240            | 21.20                | N/A         |
| 11n HT40         | 5190            | 39.53                | N/A         |
|                  | 5230            | 39.62                | N/A         |
| 11ac VHT20       | 5180            | 21.18                | N/A         |
|                  | 5200            | 20.96                | N/A         |
|                  | 5240            | 21.24                | N/A         |
| 11ac VHT40       | 5190            | 39.66                | N/A         |
|                  | 5230            | 39.67                | N/A         |
| 11ac VHT80       | 5210            | 80.94                | N/A         |
| Conclusion: PASS |                 |                      |             |

**99% Occupied bandwidth:**

| Test Mode        | Frequency (MHz) | 99% bandwidth (MHz) | Limit (kHz) |
|------------------|-----------------|---------------------|-------------|
| 11a              | 5180            | 16.552              | N/A         |
|                  | 5200            | 16.543              | N/A         |
|                  | 5240            | 16.530              | N/A         |
| 11n HT20         | 5180            | 17.687              | N/A         |
|                  | 5200            | 17.671              | N/A         |
|                  | 5240            | 17.696              | N/A         |
| 11n HT40         | 5190            | 36.126              | N/A         |
|                  | 5230            | 36.131              | N/A         |
| 11ac VHT20       | 5180            | 17.664              | N/A         |
|                  | 5200            | 17.665              | N/A         |
|                  | 5240            | 17.680              | N/A         |
| 11ac VHT40       | 5190            | 36.096              | N/A         |
|                  | 5230            | 36.121              | N/A         |
| 11ac VHT80       | 5210            | 75.285              | N/A         |
| Conclusion: PASS |                 |                     |             |

**U-NII-3 Band:**

|                                |                         |                          |
|--------------------------------|-------------------------|--------------------------|
| EUT: Room Booking Panel        |                         |                          |
| M/N: IAD-18010A                |                         |                          |
| Test date:<br>2023-01-11~02-06 | Pressure: 102.5±1.0 kpa | Humidity: 53.6±3.0%      |
| Tested by: Carl                | Test site: RF site      | Temperature: 22.4±0.6 °C |

**6dB bandwidth:**


| Test Mode        | Frequency (MHz) | 6dB Bandwidth (MHz) | Limit (kHz) |
|------------------|-----------------|---------------------|-------------|
| 11a              | 5745            | 15.82               | ≥500        |
|                  | 5785            | 16.30               | ≥500        |
|                  | 5825            | 15.82               | ≥500        |
| 11n HT20         | 5745            | 15.79               | ≥500        |
|                  | 5785            | 16.57               | ≥500        |
|                  | 5825            | 16.27               | ≥500        |
| 11n HT40         | 5755            | 35.34               | ≥500        |
|                  | 5795            | 35.51               | ≥500        |
| 11ac VHT20       | 5745            | 17.05               | ≥500        |
|                  | 5785            | 16.28               | ≥500        |
|                  | 5825            | 15.80               | ≥500        |
| 11ac VHT40       | 5755            | 35.34               | ≥500        |
|                  | 5795            | 35.50               | ≥500        |
| 11ac VHT80       | 5775            | 75.47               | ≥500        |
| Conclusion: PASS |                 |                     |             |


**26dB bandwidth:**


| Test Mode        | Frequency (MHz) | 26dB Bandwidth (MHz) | Limit (kHz) |
|------------------|-----------------|----------------------|-------------|
| 11a              | 5745            | 21.04                | N/A         |
|                  | 5785            | 20.99                | N/A         |
|                  | 5825            | 20.99                | N/A         |
| 11n HT20         | 5745            | 21.27                | N/A         |
|                  | 5785            | 21.33                | N/A         |
|                  | 5825            | 21.24                | N/A         |
| 11n HT40         | 5755            | 39.43                | N/A         |
|                  | 5795            | 39.36                | N/A         |
| 11ac VHT20       | 5745            | 21.32                | N/A         |
|                  | 5785            | 21.20                | N/A         |
|                  | 5825            | 21.24                | N/A         |
| 11ac VHT40       | 5755            | 39.45                | N/A         |
|                  | 5795            | 39.47                | N/A         |
| 11ac VHT80       | 5775            | 80.68                | N/A         |
| Conclusion: PASS |                 |                      |             |

**99% Occupied bandwidth:**

| Test Mode        | Frequency (MHz) | 99% bandwidth (MHz) | Limit (kHz) |
|------------------|-----------------|---------------------|-------------|
| 11a              | 5745            | 16.540              | N/A         |
|                  | 5785            | 16.529              | N/A         |
|                  | 5825            | 16.551              | N/A         |
| 11n HT20         | 5745            | 17.662              | N/A         |
|                  | 5785            | 17.688              | N/A         |
|                  | 5825            | 17.679              | N/A         |
| 11n HT40         | 5755            | 36.101              | N/A         |
|                  | 5795            | 36.101              | N/A         |
| 11ac VHT20       | 5745            | 17.696              | N/A         |
|                  | 5785            | 17.699              | N/A         |
|                  | 5825            | 17.690              | N/A         |
| 11ac VHT40       | 5755            | 36.095              | N/A         |
|                  | 5795            | 36.099              | N/A         |
| 11ac VHT80       | 5775            | 75.284              | N/A         |
| Conclusion: PASS |                 |                     |             |







## 7. OUTPUT POWER TEST

### 7.1. Test Equipments

| Item | Equipment           | Manufacturer | Model No.    | Serial No. | Last Cal. | Cal. Interval |
|------|---------------------|--------------|--------------|------------|-----------|---------------|
| 1.   | PXA Signal Analyzer | Agilent      | N9030A       | MY51380221 | Apr.07,22 | 1 Year        |
| 2.   | Power meter         | HP           | 436A         | 2016A07891 | Apr.06,22 | 1 Year        |
| 3.   | Power Sensor        | Agilent      | 8482B        | MY41090514 | Apr.06,22 | 1 Year        |
| 4.   | Attenuator          | Agilent      | 8491B        | MY39269201 | Oct.09,22 | 1 Year        |
| 5.   | RF Cable            | HUBER+SUHNER | SUCOFLEX-106 | 505238/6   | Apr.06,22 | 1 Year        |

### 7.2. Limit

For the band 5.15–5.25 GHz.

For mobile and portable client devices in the 5.15–5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi.

For the 5.25–5.35 GHz and 5.47–5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or 11 dBm + 10 log B, where B is the 26 dB emission bandwidth in megahertz.

For the band 5.725–5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W.

### 7.3. Test Procedure

1. Connected the EUT's antenna port to measure device by 20dB attenuator.

- 1) Measure the duty cycle, x, of the transmitter output signal as described in II.B.
- 2) Set span to encompass the EBW (or, alternatively, the entire 99% occupied bandwidth) of the signal.
- 3) Set RBW = 1 MHz.
- 4) Set VBW  $\geq$  3 MHz.
- 5) Number of points in sweep  $\geq 2 \times \text{span} / \text{RBW}$ . (This ensures that bin-to-bin spacing is  $\leq \text{RBW}/2$ , so that narrowband signals are not lost between frequency bins.)
- 6) Sweep time = auto.
- 7) Detector = power averaging (rms), if available. Otherwise, use sample detector mode.
- 8) Do not use sweep triggering. Allow the sweep to “free run.”
- 9) Trace average at least 100 traces in power averaging (rms) mode; however, the number of traces to be averaged shall be increased above 100 as needed to ensure that the average accurately represents the true average over the on and off periods of the transmitter.
- 10) Compute power by integrating the spectrum across the EBW (or, alternatively, the entire 99% occupied bandwidth) of the signal using the instrument's band power measurement function with band limits set equal to the EBW (or occupied bandwidth) band edges. If the instrument does not have a band power function, sum the spectrum levels (in power units) at 1 MHz intervals extending across the EBW (or, alternatively, the entire 99% occupied bandwidth) of the signal.
- 11) Add 10 log (1/x), where x is the duty cycle, to the measured power in order to compute the average power during the actual transmission times

Note: The cable loss and attenuator loss were offset into measure device as an amplitude offset.

## 7.4.Test Results

### U-NII-1 Band:

|                         |                         |                         |
|-------------------------|-------------------------|-------------------------|
| EUT: Room Booking Panel |                         |                         |
| M/N: IAD-18010A         |                         |                         |
| Test date: 2023-01-11   | Pressure: 102.1±1.0 kpa | Humidity: 53.2±3.0%     |
| Tested by: Carl         | Test site: RF site      | Temperature:22.3±0.6 °C |

| Test Mode        | Frequency (MHz) | Power Setting | Output Power (dBm) | Limit (dBm) |
|------------------|-----------------|---------------|--------------------|-------------|
| 11a              | 5180            | Default       | 11.01              | 23.98       |
|                  | 5200            | Default       | 10.70              |             |
|                  | 5240            | Default       | 11.05              |             |
| 11n HT20         | 5180            | Default       | 10.66              | 23.98       |
|                  | 5200            | Default       | 10.50              |             |
|                  | 5240            | Default       | 10.67              |             |
| 11n HT40         | 5190            | Default       | 10.42              | 23.98       |
|                  | 5230            | Default       | 10.40              |             |
| 11ac VHT20       | 5180            | Default       | 10.47              | 23.98       |
|                  | 5200            | Default       | 10.49              |             |
|                  | 5240            | Default       | 10.66              |             |
| 11ac VHT40       | 5190            | Default       | 10.44              | 23.98       |
|                  | 5230            | Default       | 10.42              |             |
| 11ac VHT80       | 5210            | Default       | 9.90               | 23.98       |
| Conclusion: PASS |                 |               |                    |             |

**U-NII-3 Band:**

EUT: Room Booking Panel

M/N: IAD-18010A

Test date: 2023-01-11

Pressure: 102.5±1.0 kpa

Humidity: 53.6±3.0%

Tested by: Carl

Test site: RF site

Temperature: 22.4±0.6 °C

| Test Mode     | Frequency (MHz) | Power Setting | Output Power (dBm) | Limit (dBm) |
|---------------|-----------------|---------------|--------------------|-------------|
| 11a           | 5745            | Default       | 10.59              | 30          |
|               | 5785            | Default       | 10.46              |             |
|               | 5825            | Default       | 10.57              |             |
| 11n<br>HT20   | 5745            | Default       | 10.08              | 30          |
|               | 5785            | Default       | 10.10              |             |
|               | 5825            | Default       | 10.07              |             |
| 11n<br>HT40   | 5755            | Default       | 10.21              | 30          |
|               | 5795            | Default       | 10.15              |             |
| 11ac<br>VHT20 | 5745            | Default       | 10.30              | 30          |
|               | 5785            | Default       | 10.03              |             |
|               | 5825            | Default       | 10.01              |             |
| 11ac<br>VHT40 | 5755            | Default       | 10.20              | 30          |
|               | 5795            | Default       | 10.14              |             |
| 11ac<br>VHT80 | 5775            | Default       | 9.77               | 30          |

Conclusion: PASS