

FCC Radio Test Report

FCC ID: YBN-AIVIL42N0

This report concerns (check one): ☒ Original Grant ☐ Class I Change ☐ Class II Change

Project No. : 1808C227
Equipment : Car Radio with navigation, BT and WLAN
Test Model : AIVIL42N0
Series Model : N/A
Applicant : Bosch Car Multimedia GmbH
Address : Robert-Bosch-Straße 200; 31139 Hildesheim

Date of Receipt : Aug. 29, 2018
Date of Test : Sep. 03, 2018 ~ Sep. 12, 2018
Issued Date : Oct. 12, 2018
Tested by : BTL Inc.

Testing Engineer : Chay Cai
(Chay Cai)

Technical Manager : David Mao
(David Mao)

Authorized Signatory : Steven Lu
(Steven Lu)

B T L I N C .

No.3, Jinshagang 1st Road, Shixia, Dalang Town, Dongguan,
Guangdong, China.

TEL: +86-769-8318-3000 FAX: +86-769-8319-6000



Declaration

BTL represents to the client that testing is done in accordance with standard procedures as applicable and that test instruments used has been calibrated with standards traceable to international standard(s) and/or national standard(s).

BTL's reports apply only to the specific samples tested under conditions. It is manufacture's responsibility to ensure that additional production units of this model are manufactured with the identical electrical and mechanical components. **BTL** shall have no liability for any declarations, inferences or generalizations drawn by the client or others from **BTL** issued reports.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S. Government.

This report is the confidential property of the client. As a mutual protection to the clients, the public and ourselves, the test report shall not be reproduced, except in full, without our written approval.

BTL's laboratory quality assurance procedures are in compliance with the **ISO Guide 17025** requirements, and accredited by the conformity assessment authorities listed in this test report.

BTL is not responsible for the sampling stage, so the results only apply to the sample as received.

The information, data and test plan are provided by manufacturer, so it is manufacturer's responsibility to ensure that the apparatus meets the essential requirements in all the possible configurations as representative of its intended use.

Limitation

For the use of the authority's logo is limited unless the Test Standard(s)/Scope(s)/Item(s) mentioned in this test report is (are) included in the conformity assessment authorities acceptance respective.

Table of Contents

Page

1 . CERTIFICATION	7
2 . SUMMARY OF TEST RESULTS	8
2.1 TEST FACILITY	9
2.2 MEASUREMENT UNCERTAINTY	9
3 . GENERAL INFORMATION	10
3.1 GENERAL DESCRIPTION OF EUT	10
3.2 DESCRIPTION OF TEST MODES	12
3.3 TABLE OF PARAMETERS OF TEXT SOFTWARE SETTING	12
3.4 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	13
3.5 DESCRIPTION OF SUPPORT UNITS	13
4 . EMC EMISSION TEST	14
4.1 RADIATED EMISSION MEASUREMENT	14
4.1.1 RADIATED EMISSION LIMITS	14
4.1.2 TEST PROCEDURE	15
4.1.3 DEVIATION FROM TEST STANDARD	15
4.1.4 TEST SETUP	16
4.1.5 EUT OPERATING CONDITIONS	18
4.1.6 EUT TEST CONDITIONS	18
4.1.7 TEST RESULTS (9KHZ TO 30MHZ)	18
4.1.8 TEST RESULTS (30MHZ TO 1000MHZ)	18
4.1.9 TEST RESULTS (ABOVE 1000MHZ)	18
5 . NUMBER OF HOPPING CHANNEL	19
5.1 APPLIED PROCEDURES	19
5.1.1 TEST PROCEDURE	19
5.1.2 DEVIATION FROM STANDARD	19
5.1.3 TEST SETUP	19
5.1.4 EUT OPERATION CONDITIONS	19
5.1.5 EUT TEST CONDITIONS	19
5.1.6 TEST RESULTS	19
6 . AVERAGE TIME OF OCCUPANCY	20
6.1 APPLIED PROCEDURES / LIMIT	20
6.1.1 TEST PROCEDURE	20
6.1.2 DEVIATION FROM STANDARD	20
6.1.3 TEST SETUP	20
6.1.4 EUT OPERATION CONDITIONS	21
6.1.5 EUT TEST CONDITIONS	21
6.1.6 TEST RESULTS	21

Table of Contents	Page
7 . HOPPING CHANNEL SEPARATION MEASUREMENT	22
7.1 APPLIED PROCEDURES / LIMIT	22
7.1.1 TEST PROCEDURE	22
7.1.2 DEVIATION FROM STANDARD	22
7.1.3 TEST SETUP	22
7.1.4 EUT TEST CONDITIONS	22
7.1.5 TEST RESULTS	22
8 . BANDWIDTH TEST	23
8.1 APPLIED PROCEDURES	23
8.1.1 TEST PROCEDURE	23
8.1.2 DEVIATION FROM STANDARD	23
8.1.3 TEST SETUP	23
8.1.4 EUT OPERATION CONDITIONS	23
8.1.5 EUT TEST CONDITIONS	23
8.1.6 TEST RESULTS	23
9 . PEAK OUTPUT POWER TEST	24
9.1 APPLIED PROCEDURES / LIMIT	24
9.1.1 TEST PROCEDURE	24
9.1.2 DEVIATION FROM STANDARD	24
9.1.3 TEST SETUP	24
9.1.4 EUT OPERATION CONDITIONS	24
9.1.5 EUT TEST CONDITIONS	24
9.1.6 TEST RESULTS	24
10 . ANTENNA CONDUCTED SPURIOUS EMISSION	25
10.1 APPLIED PROCEDURES / LIMIT	25
10.1.1 TEST PROCEDURE	25
10.1.2 DEVIATION FROM STANDARD	25
10.1.3 TEST SETUP	25
10.1.4 EUT OPERATION CONDITIONS	25
10.1.5 EUT TEST CONDITIONS	25
10.1.6 TEST RESULTS	25
11 . MEASUREMENT INSTRUMENTS LIST	26
12 . EUT TEST PHOTO	28
APPENDIX A - RADIATED EMISSION (9KHZ-30MHZ)	33
APPENDIX B - RADIATED EMISSION (30MHZ TO 1000MHZ)	38
APPENDIX C - RADIATED EMISSION (ABOVE 1000MHZ)	45
APPENDIX D - NUMBER OF HOPPING CHANNEL	82

Table of Contents

Page

APPENDIX E - AVERAGE TIME OF OCCUPANCY	83
APPENDIX F - HOPPING CHANNEL SEPARATION MEASUREMENT	84
APPENDIX G - BANDWIDTH	85
APPENDIX H - PEAK OUTPUT POWER	86
APPENDIX I - ANTENNA CONDUCTED SPURIOUS EMISSION	93

REPORT ISSUED HISTORY

Issued No.	Version	Description	Issued Date
BTL-FCCP-4-1808C227	Rev.01	Original Issue.	Sep. 28, 2018
BTL-FCCP-4-1808C227	Rev.02	Changed the test software version	Oct. 12, 2018

1. CERTIFICATION

Equipment : Car Radio with navigation, BT and WLAN
Brand Name : Bosch
Test Model : AIVIL42N0
Series Model : N/A
Applicant : Bosch Car Multimedia GmbH
Manufacturer : #1 Bosch Car Multimedia GmbH
 #2 Bosch Car Multimedia Portugal, S.A.
Address : #1 Robert-Bosch-Straße 200; 31139 Hildesheim
 #2 Rua Max Grundig, 35-Lomar, 4705-820 Braga
Factory : Robert Bosch (Malaysia)
Address : Free Trade Zone 11900, Bayan Lepas, Penang
Date of Test : Sep. 03, 2018 ~ Sep. 12, 2018
Test Sample : Engineering Sample No.: D180907333
Standard(s) : FCC Part15, Subpart C (15.247)/ ANSI C63.10-2013

The above equipment has been tested and found compliance with the requirement of the relative standards by BTL Inc.

The test data, data evaluation, and equipment configuration contained in our test report (Ref No. BTL-FCCP-4-1808C227) were obtained utilizing the test procedures, test instruments, test sites that has been accredited by the Authority of NVLAP according to the ISO-17025 quality assessment standard and technical standard(s).

Test results included in this report is only for the Bluetooth BR/EDR part.

2. SUMMARY OF TEST RESULTS

Test procedures according to the technical standard(s):

Applied Standard(s): FCC Part15, Subpart C (15.247)			
Standard(s) Section	Test Item	Judgment	Remark
15.247(d)	Antenna conducted Spurious Emission	N/A (Note1)	
15.247(a)(1)	Hopping Channel Separation	N/A (Note1)	
15.247(a)(2)	Bandwidth	N/A (Note1)	
15.247(a)(1)	Peak Output Power	PASS	
15.247(d) 15.209	Radiated Spurious Emission	PASS	
15.247(a)(1)(iii)	Number of Hopping Frequency	N/A (Note1)	
15.247(a)(1)(iii)	Dwell Time	N/A (Note1)	
15.205	Restricted Bands	N/A (Note1)	
15.203	Antenna Requirement	N/A (Note1)	

Note:

(1)According to customers's requirement, this test item wasn't performed and the test data wasn't contained in this test report.

2.1 TEST FACILITY

The test facilities used to collect the test data in this report is at the location of No.3, Jinshagang 1st Road, Shixia, Dalang Town, Dongguan, Guangdong, China.

BTL's test firm number for FCC: 854385

BTL's designation number for FCC: CN5020

2.2 MEASUREMENT UNCERTAINTY

The measurement uncertainty figures shall be calculated according the methods described in the ETSI TR 100 028 and shall correspond to an expansion factor (coverage factor) $k=1.96$ or $k=2$ (which provide confidence levels of respectively 90% and 95.45% in the case where the distributions characterizing the actual measurement uncertainties are normal (Gaussian)). Measurement Uncertainty for a Level of Confidence of 95 %, $U=2 \times U_c(y)$.

The BTL measurement uncertainty as below table:

A. Radiated Measurement :

Test Site	Method	Measurement Frequency Range	Ant. H / V	U, (dB)
DG-CB03	CISPR	9KHz~30MHz	V	3.79
		9KHz~30MHz	H	3.57
		30MHz ~ 200MHz	V	3.82
		30MHz ~ 200MHz	H	3.78
		200MHz ~ 1,000MHz	V	4.10
		200MHz ~ 1,000MHz	H	4.06
		1GHz~18GHz	V	3.12
		1GHz~18GHz	H	3.68
		18GHz~40GHz	V	4.15
		18GHz~40GHz	H	4.14

B. Other Measurement:

Test Item	Uncertainty
Conducted Spurious Emission	2.67dB
Hopping Channel Separation	53.46MHz
Peak Output Power	0.95dB
Number of Hopping Frequency	53.46MHz
Temperature	0.08℃
Humidity	1.5%

Note: Unless specifically mentioned, the uncertainty of measurement has not been taken into account to declare the compliance or non-compliance to the specification.

3. GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

Equipment	Car Radio with navigation, BT and WLAN	
Brand Name	Bosch	
Test Model	AIVIL42N0	
Series Model	N/A	
Model Difference	N/A	
Product Description	Operation Frequency	2402 ~ 2480 MHz
	Modulation Technology	GFSK(1Mbps) π /4-DQPSK(2Mbps)
	Bit Rate of Transmitter	8-DPSK(3Mbps)
	Output Power Max.	-3.79 dBm (1Mbps) -4.28 dBm (2Mbps) -3.93 dBm (3Mbps)
Power Source	DC voltage supplied from external power supply.	
Power Rating	DC 13.5V	

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.

2. Channel List:

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
00	2402	27	2429	54	2456
01	2403	28	2430	55	2457
02	2404	29	2431	56	2458
03	2405	30	2432	57	2459
04	2406	31	2433	58	2460
05	2407	32	2434	59	2461
06	2408	33	2435	60	2462
07	2409	34	2436	61	2463
08	2410	35	2437	62	2464
09	2411	36	2438	63	2465
10	2412	37	2439	64	2466
11	2413	38	2440	65	2467
12	2414	39	2441	66	2468
13	2415	40	2442	67	2469
14	2416	41	2443	68	2470
15	2417	42	2444	69	2471
16	2418	43	2445	70	2472
17	2419	44	2446	71	2473
18	2420	45	2447	72	2474
19	2421	46	2448	73	2475
20	2422	47	2449	74	2476
21	2423	48	2450	75	2477
22	2424	49	2451	76	2478
23	2425	50	2452	77	2479
24	2426	51	2453	78	2480
25	2427	52	2454		
26	2428	53	2455		

3 Table for Filed Antenna:

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
1	N/A	N/A	Internal	N/A	-4.5

3.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	TX Mode Note (1)

The EUT system operated these modes were found to be the worst case during the pre-scanning test as following:

For Radiated Emission	
Final Test Mode	Description
Mode 1	TX Mode Note (1)(2)

Note:


- (1) The measurements are performed at the high, middle, low available channels.
- (2) The measurements for Peak Output Power were tested during 1Mbps, 2Mbps and 3Mbps, the worst case are 1Mbps and 3Mbps, only worst case was documented.

3.3 TABLE OF PARAMETERS OF TEXT SOFTWARE SETTING

During testing, channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters of FHSS

Test Software Version	Dut labtool_2.0.0.89_Mar. 09, 2016		
Frequency	2402 MHz	2441 MHz	2480 MHz
Parameters(1Mbps)	0	0	0
Parameters(2Mbps)	0	0	0
Parameters(3Mbps)	0	0	0

3.4 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED



3.5 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	FCC ID	Series No.
A	DC Power Source	TRUE-POWER	GPC30300N	N/A	N/A
B	Test Fixture	N/A	N/A	N/A	N/A
C	Test Fixture	N/A	N/A	N/A	N/A
D	Notebook	Dell	Inspiron 15-7559	N/A	N/A

Item	Shielded Type	Ferrite Core	Length	Note
1	NO	NO	1m	DC Cable
2	NO	NO	10m	RJ45 Cable

4. EMC EMISSION TEST

4.1 RADIATED EMISSION MEASUREMENT

4.1.1 RADIATED EMISSION LIMITS

In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

LIMITS OF RADIATED EMISSION MEASUREMENT(9KHz-1000MHz)

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
960~1000	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

Frequency (MHz)	Band edge at 3m (dBμV/m)		Harmonic at 1.5m (dBμV/m)	
	Peak	Average	Peak	Average
Above 1000	74	54	80 (Note 5)	60(Note 5)

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).
- (4) The test result calculated as following:
 Measurement Value = Reading Level + Correct Factor
 Correct Factor = Antenna Factor + Cable Loss - Amplifier Gain(if use)
 Margin Level = Measurement Value - Limit Value

(5)

$$FS_{\text{limit}} = FS_{\text{max}} - 20\log\left(\frac{d_{\text{limit}}}{d_{\text{measure}}}\right)$$

$$20\log d_{\text{limit}}/d_{\text{measure}}=20\log 3/1.5=6\text{dB}.$$

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RBW / VBW (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average

Spectrum Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9KHz ~90KHz for PK/AVG detector
Start ~ Stop Frequency	90KHz ~110KHz for QP detector
Start ~ Stop Frequency	110KHz ~490KHz for PK/AVG detector
Start ~ Stop Frequency	490KHz ~30MHz for QP detector
Start ~ Stop Frequency	30MHz~1000MHz for QP detector

4.1.2 TEST PROCEDURE


- The measuring distance of 3 m shall be used for measurements. The EUT was placed on the top of a rotating table 0.8 meter above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.(below 1GHz)
- The measuring distance of 3 m or 1.5m shall be used for measurements. The EUT was placed on the top of a rotating table 1.5 meter above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.(above 1GHz)
- The height of the equipment or of the substitution antenna shall be 0.8m or 1.5m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights find the maximum reading (used Bore sight function).
- The receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1GHz.
- The initial step in collecting radiated emission data is a receiver peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- All readings are Peak unless otherwise stated QP in column of Note. Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform. (below 1GHz)
- All readings are Peak Mode value unless otherwise stated AVG in column of Note. If the Peak Mode Measured value compliance with the Peak Limits and lower than AVG Limits, the EUT shall be deemed to meet both Peak & AVG Limits and then only Peak Mode was measured, but AVG Mode didn't perform. (above 1GHz)
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

4.1.3 DEVIATION FROM TEST STANDARD


No deviation

4.1.4 TEST SETUP


(A) Radiated Emission Test Set-Up Frequency Below 1 GHz




(B) Radiated Emission Test Set-Up Frequency Above 1 GHz
Band edge



Harmonic



(C) For Radiated Emissions Below 30MHz



4.1.5 EUT OPERATING CONDITIONS

The EUT was programmed to be in continuously transmitting mode.

4.1.6 EUT TEST CONDITIONS

Temperature: 25°C

Relative Humidity: 55%

Test Voltage: DC 13.5V

4.1.7 TEST RESULTS (9KHZ TO 30MHZ)

Please refer to the Appendix A.

Remark:

- (1) The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.
- (2) Distance extrapolation factor = $40 \log (\text{specific distance} / \text{test distance})$ (dB).
- (3) Limit line = specific limits (dBuV) + distance extrapolation factor.

4.1.8 TEST RESULTS (30MHZ TO 1000MHZ)

Please refer to the Appendix B.

4.1.9 TEST RESULTS (ABOVE 1000MHZ)

Please refer to the Appendix C.

Remark:

- (1) No limit: This is fundamental signal, the judgment is not applicable.
For fundamental signal judgment was referred to Peak output test.

5. NUMBER OF HOPPING CHANNEL

5.1 APPLIED PROCEDURES

FCC Part15 (15.247) , Subpart C			
Section	Test Item	Frequency Range (MHz)	Result
15.247(a)(1)(iii)	Number of Hopping Channel	2400-2483.5	PASS

Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	> Operating Frequency Range
RBW	100 KHz
VBW	100 KHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

5.1.1 TEST PROCEDURE

- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- Spectrum Setting: RBW=100KHz, VBW=100KHz, Sweep time = Auto.

5.1.2 DEVIATION FROM STANDARD

No deviation.

5.1.3 TEST SETUP



5.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 4.1.5 unless otherwise a special operating condition is specified in the follows during the testing.

5.1.5 EUT TEST CONDITIONS

Temperature: 25°C
 Relative Humidity: 55%
 Test Voltage: DC 13.5V

5.1.6 TEST RESULTS

Please refer to the Appendix D.

6. AVERAGE TIME OF OCCUPANCY

6.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(a)(1)(iii)	Average Time of Occupancy	0.4sec	2400-2483.5	PASS

6.1.1 TEST PROCEDURE

- The transmitter output (antenna port) was connected to the spectrum analyzer
- Set RBW of spectrum analyzer to 1MHz and VBW to 1MHz.
- Use a video trigger with the trigger level set to enable triggering only on full pulses.
- Sweep Time is more than once pulse time.
- Set the center frequency on any frequency would be measure and set the frequency span to zero span.
- Measure the maximum time duration of one single pulse.
- Set the EUT for DH5, DH3 and DH1 packet transmitting.
- Measure the maximum time duration of one single pulse.
 - DH5 Packet permit maximum $1600 / 79 / 6 = 3.37$ hops per second in each channel (5 time slots TX, 1 time slot RX). So, the dwell time is the time duration of the pulse times $3.37 \times 31.6 = 106.6$ within 31.6 seconds.
 - DH3 Packet permit maximum $1600 / 79 / 4 = 5.06$ hops per second in each channel (3 time slots TX, 1 time slot RX). So, the dwell time is the time duration of the pulse times $5.06 \times 31.6 = 160$ within 31.6 seconds.
 - DH1 Packet permit maximum $1600 / 79 / 2 = 10.12$ hops per second in each channel (1 time slot TX, 1 time slot RX). So, the dwell time is the time duration of the pulse times $10.12 \times 31.6 = 320$ within 31.6 seconds.

6.1.2 DEVIATION FROM STANDARD

No deviation.

6.1.3 TEST SETUP



6.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 4.1.5 unless otherwise a special operating condition is specified in the follows during the testing.

6.1.5 EUT TEST CONDITIONS

Temperature: 25°C

Relative Humidity: 55%

Test Voltage: DC 13.5V

6.1.6 TEST RESULTS

Please refer to the Appendix E.

7. HOPPING CHANNEL SEPARATION MEASUREMENT

7.1 APPLIED PROCEDURES / LIMIT

Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 KHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	> Measurement Bandwidth or Channel Separation
RBW	30 KHz
VBW	100 KHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto


7.1.1 TEST PROCEDURE

- The EUT must have its hopping function enabled
- Span = wide enough to capture the peaks of two adjacent channels
 Resolution (or IF) Bandwidth (RBW) $\geq$ 1% of the span
 Video (or Average) Bandwidth (VBW) $\geq$ RBW
 Sweep = Auto
 Detector function = Peak
 Trace = Max Hold

7.1.2 DEVIATION FROM STANDARD

No deviation.

7.1.3 TEST SETUP



7.1.4 EUT TEST CONDITIONS

Temperature: 25°C
 Relative Humidity: 55%
 Test Voltage: DC 13.5V

7.1.5 TEST RESULTS

Please refer to the Appendix F.

8. BANDWIDTH TEST

8.1 APPLIED PROCEDURES

FCC Part15 (15.247) , Subpart C		
Section	Test Item	Frequency Range (MHz)
15.247(a)(2)	Bandwidth	2400-2483.5

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	> Measurement Bandwidth or Channel Separation
RBW	30 KHz (20dB Bandwidth) / 30 KHz (Channel Separation)
VBW	100 KHz (20dB Bandwidth) / 100 KHz (Channel Separation)
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

8.1.1 TEST PROCEDURE

- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- Spectrum Setting: RBW= 30KHz, VBW=100KHz, Sweep Time = Auto.

8.1.2 DEVIATION FROM STANDARD

No deviation.

8.1.3 TEST SETUP



8.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 4.1.5 unless otherwise a special operating condition is specified in the follows during the testing.

8.1.5 EUT TEST CONDITIONS

Temperature: 25°C
 Relative Humidity: 55%
 Test Voltage: DC 13.5V

8.1.6 TEST RESULTS

Please refer to the Appendix G.

9. PEAK OUTPUT POWER TEST

9.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(a)(1)	Peak Output Power	0.125Watt or 21dBm	2400-2483.5	PASS

Note: Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

9.1.1 TEST PROCEDURE

- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- Spectrum Setting: RBW= 1MHz/3MHz, VBW= 1MHz/3MHz, Sweep time = Auto.

9.1.2 DEVIATION FROM STANDARD

No deviation.

9.1.3 TEST SETUP



9.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 4.1.5 unless otherwise a special operating condition is specified in the follows during the testing.

9.1.5 EUT TEST CONDITIONS

Temperature: 25°C
 Relative Humidity: 55%
 Test Voltage: DC 13.5V

9.1.6 TEST RESULTS

Please refer to the Appendix H.

10. ANTENNA CONDUCTED SPURIOUS EMISSION

10.1 APPLIED PROCEDURES / LIMIT

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak Output Power limits. If the transmitter complies with the Output Power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

10.1.1 TEST PROCEDURE

- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- Spectrum Setting: RBW= 100KHz, VBW=100KHz, Sweep time = Auto.

10.1.2 DEVIATION FROM STANDARD

No deviation.

10.1.3 TEST SETUP



10.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 4.1.5 unless otherwise a special operating condition is specified in the follows during the testing.

10.1.5 EUT TEST CONDITIONS

Temperature: 25°C
Relative Humidity: 55%
Test Voltage: DC 13.5V

10.1.6 TEST RESULTS

Please refer to the Appendix I.

11. MEASUREMENT INSTRUMENTS LIST

Radiated Emission Measurement - 9kHz TO 30 MHz					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Loop Antenna	EM	EM-6876-1	230	Feb. 07, 2019
2	Cable	N/A	RG 213/U	C-102	Jun. 01, 2019
3	EMI Test Receiver	R&S	ESCI	100382	Mar. 11, 2019
4	Measurement Software	Farad	EZ-EMC Ver.NB-03A1-01	N/A	N/A

Radiated Emission Measurement – 30 MHz TO 1000 MHz					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Antenna	Schwarbeck	VULB9160	9160-3232	Mar. 11, 2019
2	Amplifier	HP	8447D	2944A09673	Aug. 11, 2019
3	Receiver	Agilent	N9038A	MY52130039	Aug. 11, 2019
4	Cable	emci	LMR-400(30MHz-1 GHz)(8m+5m)	N/A	May 25, 2019
5	Controller	CT	SC100	N/A	N/A
6	Controller	MF	MF-7802	MF780208416	N/A
7	Measurement Software	Farad	EZ-EMC Ver.NB-03A1-01	N/A	N/A

Radiated Emission Measurement - Above 1 GHz					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Double Ridged Guide Antenna	ETS	3115	75789	Mar. 11, 2019
2	Broad-Band Horn Antenna	Schwarzbeck	BBHA 9170	9170319	Jun. 30, 2019
3	Amplifier	Agilent	8449B	3008A02274	Mar. 11, 2019
4	Microwave Preamplifier With Adaptor	EMC INSTRUMENT	EMC2654045	980039 & HA01	Mar. 11, 2019
5	Receiver	Agilent	N9038A	MY52130039	Aug. 11, 2019
6	Controller	CT	SC100	N/A	N/A
7	Controller	MF	MF-7802	MF780208416	N/A
8	Cable	mitron	B10-01-01-12M	18072744	Jul. 30, 2019
9	Measurement Software	Farad	EZ-EMC Ver.NB-03A1-01	N/A	N/A


Peak Output Power					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP40	100185	Aug. 11, 2019

Remark: "N/A" denotes no model name, serial no. or calibration specified.
All calibration period of equipment list is one year.

12. EUT TEST PHOTO

Radiated Measurement Photos

9KHz to 30MHz





Radiated Measurement Photos

30MHz to 1000MHz




Radiated Measurement Photos

1GHz to 18GHz



Radiated Measurement Photos

18GHz to 26.5GHz




Band Edge Measurement Photos



APPENDIX A - RADIATED EMISSION (9KHZ-30MHZ)

Test Mode: TX Mode

Ant 0°




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	*	0.0156	37.20	20.64	57.84	123.74	-65.90	AVG	
2		0.0293	28.50	19.86	48.36	118.27	-69.91	AVG	
3		0.0571	22.40	19.39	41.79	112.47	-70.68	AVG	

Test Mode:

TX Mode

Ant 0°




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1		0.2185	29.70	17.11	46.81	100.82	-54.01	AVG	
2		0.6238	31.80	16.92	48.72	71.70	-22.98	QP	
3	*	2.2486	37.70	16.96	54.66	69.54	-14.88	QP	

Test Mode:

TX Mode


Ant 90°



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	*	0.0256	38.60	19.93	58.53	119.44	-60.91	AVG	
2		0.0390	28.70	19.70	48.40	115.78	-67.38	AVG	
3		0.0570	26.20	19.39	45.59	112.49	-66.90	AVG	

Test Mode: TX Mode

Ant 90°




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1		0.2378	26.90	17.08	43.98	100.08	-56.10	AVG	
2	*	2.2132	37.10	16.98	54.08	69.54	-15.46	QP	
3		3.6225	28.40	16.04	44.44	69.54	-25.10	QP	

APPENDIX B - RADIATED EMISSION (30MHZ TO 1000MHZ)

Test Mode: TX 2402 MHz _CH00_1Mbps

Vertical




No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	31.4550	36.69	-15.02	21.67	40.00	-18.33	Peak	
2	147.3700	38.24	-11.65	26.59	43.50	-16.91	Peak	
3	445.6450	34.41	-7.58	26.83	46.00	-19.17	Peak	
4	544.5850	36.12	-5.80	30.32	46.00	-15.68	Peak	
5	799.6950	30.02	-1.06	28.96	46.00	-17.04	Peak	
6 *	952.9550	29.25	1.34	30.59	46.00	-15.41	Peak	

Test Mode: TX 2402 MHz _CH00_1Mbps

Horizontal


80 dBuV/m



No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	148.3400	31.44	-11.59	19.85	43.50	-23.65	Peak	
2	247.2800	34.46	-14.39	20.07	46.00	-25.93	Peak	
3	346.7049	33.37	-11.03	22.34	46.00	-23.66	Peak	
4	445.6450	33.80	-7.58	26.22	46.00	-19.78	Peak	
5	809.8800	30.44	-1.19	29.25	46.00	-16.75	Peak	
6 *	948.5900	29.68	1.35	31.03	46.00	-14.97	Peak	

Test Mode: TX 2441 MHz _CH39_1Mbps

Vertical




No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	31.4550	36.69	-15.02	21.67	40.00	-18.33	Peak	
2	147.3700	38.24	-11.65	26.59	43.50	-16.91	Peak	
3	445.6450	34.41	-7.58	26.83	46.00	-19.17	Peak	
4	544.5850	36.12	-5.80	30.32	46.00	-15.68	Peak	
5	799.6950	30.02	-1.06	28.96	46.00	-17.04	Peak	
6 *	940.3450	29.67	1.02	30.69	46.00	-15.31	Peak	

Test Mode: TX 2441 MHz _CH39_1Mbps

Horizontal

80 dBuV/m




No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	163.3750	29.52	-10.80	18.72	43.50	-24.78	Peak	
2	221.5750	34.58	-14.86	19.72	46.00	-26.28	Peak	
3	346.7049	33.03	-11.03	22.00	46.00	-24.00	Peak	
4	445.6450	31.69	-7.58	24.11	46.00	-21.89	Peak	
5	665.3500	31.73	-4.43	27.30	46.00	-18.70	Peak	
6 *	941.8000	30.40	1.08	31.48	46.00	-14.52	Peak	

Test Mode:

TX 2480 MHz _CH78_1Mbps


Vertical



No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	35.8200	35.72	-14.97	20.75	40.00	-19.25	Peak	
2	148.3400	33.49	-11.59	21.90	43.50	-21.60	Peak	
3	445.6450	34.08	-7.58	26.50	46.00	-19.50	Peak	
4 *	544.5850	36.46	-5.80	30.66	46.00	-15.34	Peak	
5	820.0650	30.04	-1.35	28.69	46.00	-17.31	Peak	
6	970.4150	28.68	0.92	29.60	54.00	-24.40	Peak	

Test Mode: TX 2480 MHz _CH78_1Mbps

Horizontal




No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	148.3400	29.86	-11.59	18.27	43.50	-25.23	Peak	
2	221.5750	35.79	-14.86	20.93	46.00	-25.07	Peak	
3	445.6450	32.61	-7.58	25.03	46.00	-20.97	Peak	
4	742.4650	31.52	-3.85	27.67	46.00	-18.33	Peak	
5	841.4050	32.19	-1.69	30.50	46.00	-15.50	Peak	
6 *	945.6800	30.06	1.24	31.30	46.00	-14.70	Peak	

APPENDIX C - RADIATED EMISSION (ABOVE 1000MHZ)

Test Mode: TX 2402 MHz _CH00_1Mbps

Vertical

130 dBuV/m




No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	2390.0000	38.38	7.39	45.77	74.00	-28.23	Peak	
2	2390.0000	30.07	7.39	37.46	54.00	-16.54	AVG	
3	2401.8250	74.10	7.38	81.48	74.00	7.48	Peak	No Limit
4 *	2402.0000	73.78	7.38	81.16	54.00	27.16	AVG	No Limit

Test Mode:	TX 2402 MHz _CH00_1Mbps
------------	-------------------------

Vertical

130 dBuV/m




No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1 *	4804.0030	35.17	3.45	38.62	60.00	-21.38	AVG	
2	4804.2400	41.70	3.45	45.15	80.00	-34.85	Peak	
3	17898.0000	36.38	17.46	53.84	80.00	-26.16	Peak	

Test Mode:	TX 2402 MHz _CH00_1Mbps
------------	-------------------------

Vertical

130 dBuV/m




No.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin	Detector	Comment
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB		
1 *	25463.0000	40.08	17.30	57.38	80.00	-22.62	Peak	

Test Mode: TX 2402 MHz _CH00_1Mbps

Horizontal

130 dBuV/m




No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	2390.0000	39.38	7.39	46.77	74.00	-27.23	Peak	
2	2390.0000	29.91	7.39	37.30	54.00	-16.70	AVG	
3 *	2402.0000	75.21	7.38	82.59	54.00	28.59	AVG	No Limit
4	2402.1750	75.49	7.38	82.87	74.00	8.87	Peak	No Limit

Test Mode:	TX 2402 MHz _CH00_1Mbps
------------	-------------------------

Horizontal

130 dBuV/m




No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	4803.6880	42.00	3.45	45.45	80.00	-34.55	Peak	
2 *	4804.0040	34.85	3.45	38.30	60.00	-21.70	AVG	
3	17855.5000	36.03	17.33	53.36	80.00	-26.64	Peak	

Test Mode:	TX 2402 MHz _CH00_1Mbps
------------	-------------------------

Horizontal

130 dBuV/m




No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1 *	25590.5000	40.59	17.22	57.81	80.00	-22.19	Peak	

Test Mode: TX 2441 MHz _CH39_1Mbps

Vertical

130 dBuV/m




No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1 *	2441.0000	72.76	7.35	80.11	54.00	26.11	AVG	No Limit
2	2441.1750	73.13	7.35	80.48	74.00	6.48	Peak	No Limit

Test Mode: TX 2441 MHz _CH39_1Mbps

Vertical

130 dBuV/m




No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1 *	4882.0099	32.87	3.63	36.50	60.00	-23.50	AVG	
2	4882.4129	40.70	3.63	44.33	80.00	-35.67	Peak	
3	17949.0000	35.56	17.62	53.18	80.00	-26.82	Peak	

Test Mode:	TX 2441 MHz _CH39_1Mbps
------------	-------------------------

Vertical


130 dBuV/m



No.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin	Detector	Comment
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB		
1 *	25577.7500	39.82	17.24	57.06	80.00	-22.94	Peak	

Test Mode:	TX 2441 MHz _CH39_1Mbps
------------	-------------------------


Horizontal



No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	2440.8500	72.35	7.35	79.70	74.00	5.70	Peak	No Limit
2 *	2441.0000	71.94	7.35	79.29	54.00	25.29	AVG	No Limit

Test Mode:	TX 2441 MHz _CH39_1Mbps
------------	-------------------------

Horizontal




No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1 *	4881.9910	33.55	3.63	37.18	60.00	-22.82	AVG	
2	4882.0390	41.07	3.63	44.70	80.00	-35.30	Peak	
3	17830.0000	35.77	17.25	53.02	80.00	-26.98	Peak	

Test Mode:	TX 2441 MHz _CH39_1Mbps
------------	-------------------------

Horizontal

130 dBuV/m




No.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin	Detector	Comment
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB		
1 *	25543.7500	39.86	17.28	57.14	80.00	-22.86	Peak	

Test Mode: TX 2480 MHz _CH78_1Mbps

Vertical

130 dBuV/m




No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	2479.8000	75.50	7.32	82.82	74.00	8.82	Peak	No Limit
2 *	2480.0250	75.23	7.32	82.55	54.00	28.55	AVG	No Limit
3	2483.5000	39.51	7.32	46.83	74.00	-27.17	Peak	
4	2483.5000	29.45	7.32	36.77	54.00	-17.23	AVG	

Test Mode: TX 2480 MHz _CH78_1Mbps

Vertical

130 dBuV/m




No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	4959.5700	41.86	3.81	45.67	80.00	-34.33	Peak	
2 *	4959.9480	33.28	3.82	37.10	60.00	-22.90	AVG	
3	17991.5000	35.49	17.74	53.23	80.00	-26.77	Peak	

Test Mode:	TX 2480 MHz _CH78_1Mbps
------------	-------------------------

Vertical

130 dBuV/m




No.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin	Detector	Comment
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB		
1 *	26478.7500	39.72	17.97	57.69	80.00	-22.31	Peak	

Test Mode: TX 2480 MHz _CH78_1Mbps

Horizontal

130 dBuV/m




No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	2479.8250	73.74	7.32	81.06	74.00	7.06	Peak	No Limit
2 *	2480.0000	73.36	7.32	80.68	54.00	26.68	AVG	No Limit
3	2483.5000	38.70	7.32	46.02	74.00	-27.98	Peak	
4	2483.5000	29.38	7.32	36.70	54.00	-17.30	AVG	

Test Mode: TX 2480 MHz _CH78_1Mbps

Horizontal

130 dBuV/m




No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	4959.8580	40.94	3.82	44.76	80.00	-35.24	Peak	
2 *	4959.9770	34.06	3.82	37.88	60.00	-22.12	AVG	
3	17983.0000	35.76	17.72	53.48	80.00	-26.52	Peak	

Test Mode:	TX 2480 MHz _CH78_1Mbps
------------	-------------------------

Horizontal

130 dBuV/m




No.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin	Detector	Comment
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB		
1 *	25552.2500	40.53	17.27	57.80	80.00	-22.20	Peak	

Test Mode: TX 2402 MHz _CH00_3Mbps

Vertical

130 dBuV/m




No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	2390.0000	38.97	7.39	46.36	74.00	-27.64	Peak	
2	2390.0000	30.17	7.39	37.56	54.00	-16.44	AVG	
3	2402.0000	72.96	7.38	80.34	74.00	6.34	Peak	No Limit
4 *	2402.0000	69.55	7.38	76.93	54.00	22.93	AVG	No Limit

Test Mode:	TX 2402 MHz _CH00_3Mbps
------------	-------------------------

Vertical

130 dBuV/m




No.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin	Detector	Comment
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB		
1 *	17966.0000	35.51	17.67	53.18	80.00	-26.82	Peak	

Test Mode:	TX 2402 MHz _CH00_3Mbps
------------	-------------------------

Vertical


130 dBuV/m



No.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1 *	25535.2500	40.11	17.28	57.39	80.00	-22.61	Peak	

Test Mode:	TX 2402 MHz _CH00_3Mbps
------------	-------------------------

Horizontal




No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	2390.0000	39.27	7.39	46.66	74.00	-27.34	Peak	
2	2390.0000	30.17	7.39	37.56	54.00	-16.44	AVG	
3	2402.0250	74.39	7.38	81.77	74.00	7.77	Peak	No Limit
4 *	2402.0250	71.00	7.38	78.38	54.00	24.38	AVG	No Limit

Test Mode:	TX 2402 MHz _CH00_3Mbps
------------	-------------------------

Horizontal

130 dBuV/m




No.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin	Detector	Comment
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB		
1 *	17991.5000	35.18	17.74	52.92	80.00	-27.08	Peak	

Test Mode:	TX 2402 MHz _CH00_3Mbps
------------	-------------------------

Horizontal

130 dBuV/m




No.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1 *	25382.2500	39.87	17.26	57.13	80.00	-22.87	Peak	

Test Mode: TX 2441 MHz _CH39_3Mbps

Vertical

130 dBuV/m




No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	2440.9750	71.52	7.35	78.87	74.00	4.87	Peak	No Limit
2 *	2441.0000	68.00	7.35	75.35	54.00	21.35	AVG	No Limit

Test Mode:	TX 2441 MHz _CH39_3Mbps
------------	-------------------------

Vertical

130 dBuV/m




No.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1 *	17940.5000	35.88	17.59	53.47	80.00	-26.53	Peak	

Test Mode:	TX 2441 MHz _CH39_3Mbps
------------	-------------------------

Vertical

130 dBuV/m




No.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin	Detector	Comment
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB		
1 *	25569.2500	39.94	17.25	57.19	80.00	-22.81	Peak	

Test Mode:	TX 2441 MHz _CH39_3Mbps
------------	-------------------------

Horizontal

130 dBuV/m




No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	2440.9750	74.90	7.35	82.25	74.00	8.25	Peak	No Limit
2 *	2441.0000	71.47	7.35	78.82	54.00	24.82	AVG	No Limit

Test Mode:	TX 2441 MHz _CH39_3Mbps
------------	-------------------------

Horizontal

130 dBuV/m




No.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin	Detector	Comment
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB		
1 *	17813.0000	35.90	17.20	53.10	80.00	-26.90	Peak	

Test Mode:	TX 2441 MHz _CH39_3Mbps
------------	-------------------------

Horizontal

130 dBuV/m




No.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1 *	25526.7500	39.62	17.29	56.91	80.00	-23.09	Peak	

Test Mode: TX 2480 MHz _CH78_3Mbps

Vertical

130 dBuV/m




No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	2480.0000	73.72	7.32	81.04	74.00	7.04	Peak	No Limit
2 *	2480.0000	70.36	7.32	77.68	54.00	23.68	AVG	No Limit
3	2483.5000	38.84	7.32	46.16	74.00	-27.84	Peak	
4	2483.5000	29.62	7.32	36.94	54.00	-17.06	AVG	

Test Mode:	TX 2480 MHz _CH78_3Mbps
------------	-------------------------

Vertical

130 dBuV/m




No.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin	Detector	Comment
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB		
1 *	18000.0000	35.19	17.77	52.96	80.00	-27.04	Peak	

Test Mode:	TX 2480 MHz _CH78_3Mbps
------------	-------------------------

Vertical

130 dBuV/m




No.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin	Detector	Comment
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB		
1 *	25526.7500	39.87	17.29	57.16	80.00	-22.84	Peak	

Test Mode: TX 2480 MHz _CH78_3Mbps

Horizontal

130 dBuV/m




No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	2480.0250	74.65	7.32	81.97	74.00	7.97	Peak	No Limit
2 *	2480.0250	71.24	7.32	78.56	54.00	24.56	AVG	No Limit
3	2483.5000	37.49	7.32	44.81	74.00	-29.19	Peak	
4	2483.5000	29.58	7.32	36.90	54.00	-17.10	AVG	

Test Mode:	TX 2480 MHz _CH78_3Mbps
------------	-------------------------

Horizontal

130 dBuV/m




No.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin	Detector	Comment
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB		
1 *	17966.0000	35.96	17.67	53.63	80.00	-26.37	Peak	

Test Mode:	TX 2480 MHz _CH78_3Mbps
------------	-------------------------

Horizontal

130 dBuV/m



No.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin	Detector	Comment
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB		
1 *	25016.7500	40.26	17.04	57.30	80.00	-22.70	Peak	

APPENDIX D - NUMBER OF HOPPING CHANNEL

Test Mode: N/A

Note: According to customers's requirement, this test item wasn't performed.

APPENDIX E - AVERAGE TIME OF OCCUPANCY

Test Mode: N/A

Note: According to customers's requirement, this test item wasn't performed.

APPENDIX F - HOPPING CHANNEL SEPARATION MEASUREMENT

Test Mode: N/A

Note: According to customers's requirement, this test item wasn't performed.

APPENDIX G - BANDWIDTH

Test Mode: N/A


Note: According to customers's requirement, this test item wasn't performed.

APPENDIX H - PEAK OUTPUT POWER

Test Mode : TX Mode _1Mbps


Frequency (MHz)	Output Power (dBm)	Output Power (W)	Max. Limit (dBm)	Max. Limit (W)	Test Result
2402	-3.79	0.0004	21.00	0.125	Pass
2441	-3.83	0.0004	21.00	0.125	Pass
2480	-3.87	0.0004	21.00	0.125	Pass

CH00




13:22:10 05.09.2018

CH39




CH78



Test Mode : TX Mode _2Mbps


Frequency (MHz)	Output Power (dBm)	Output Power (W)	Max. Limit (dBm)	Max. Limit (W)	Test Result
2402	-4.71	0.0003	21.00	0.125	Pass
2441	-4.31	0.0004	21.00	0.125	Pass
2480	-4.28	0.0004	21.00	0.125	Pass

CH00




13:25:32 05.09.2018

CH39



13:26:34 05.09.2018

CH78




13:27:55 05.09.2018

Test Mode : TX Mode _3Mbps


Frequency (MHz)	Output Power (dBm)	Output Power (W)	Max. Limit (dBm)	Max. Limit (W)	Test Result
2402	-4.26	0.0004	21.00	0.125	Pass
2441	-3.98	0.0004	21.00	0.125	Pass
2480	-3.93	0.0004	21.00	0.125	Pass

CH00




13:28:53 05.09.2018

CH39



CH78



APPENDIX I - ANTENNA CONDUCTED SPURIOUS EMISSION

Test Mode: N/A

Note: According to customers's requirement, this test item wasn't performed.

-----END OF TEST REPORT-----