

SAR TEST REPORT

Application No.: SZCR2509004292AT

Applicant: DT Research, Inc.

Address of Applicant: 3RD FL NO 36 WUQUAN 7TH RD WUGU DISTRICT, NEW TAIPEI, Taiwan

Manufacturer: DT Research, Inc.

Address of Manufacturer: 2000 Concourse Drive, San Jose, CA 95131, USA

EUT Description: Rugged Laptop

Model No.: LT360xxxxx (x=0-9, A-Z, - or null, or ., or /) ♣

♣ Please refer to section 2 of this report which indicates which model was actually tested and which were electrically identical.

Trade Mark:



FCC ID: YE3600-BE200NG

Standards: FCC 47CFR §2.1093

Date of Receipt: 2025-11-05

Date of Test: 2025-11-06 to 2025-11-20

Date of Issue: 2025-12-04

Test Result :	PASS *
----------------------	---------------

* In the configuration tested, the EUT detailed in this report complied with the standards specified above.

Keny Xu

Keny Xu
EMC Laboratory Manager



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch EMC Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZSAR-TRF-01 Rev. A/2

Report No.: SZCR250900429206

Page: 2 of 80

Revision Record

Version	Description	Date	Remark
01		2025-12-04	Original

Authorized for issue
by:

Edison Li

Edison Li/Project Engineer

Eric Fu

Eric Fu / Reviewer



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Member of the SGS Group (SGS SA)

TEST SUMMARY

Frequency Band	Maximum Reported SAR(W/kg)
	Body
WI-FI (2.4GHz)	1.28
WI-FI (5GHz)	1.14
WI-FI 6E	1.51
BT	0.69
SAR Limited(W/kg)	1.6
Maximum Simultaneous Transmission SAR (W/kg)	
Scenario	Body
Sum SAR	1.59
SPLSR	/
SPLSR Limited	0.04

Frequency Band	Reported PD (W/m ²)
WIFI 6E	1.16
PD Limit	10.00

Remark for report SZCR250900429206:

Model No.: LT360xxxxx (x=0-9, A-Z, - or null, or ., or /)

Only the model LT360PA was tested. According to the declaration from the applicant, the electrical circuit design, layout, components used, internal wiring and functions were identical for the above models, with only difference on model No., appearance and color.



Contents

1	General Information	6
1.1	General Description of EUT	6
1.2	Test Specification	8
1.3	RF exposure limits	9
1.4	Test Location	10
1.5	Test Engineer	10
1.6	Test Facility	10
2	Laboratory Environment	11
3	SAR Measurements System Configuraion	12
3.1	The SAR Measurement System	12
3.2	Isotropic E-field Probe EX3DV4	14
3.3	Data Acquisition Electronics (DAE)	15
3.4	SAM Twin Phantom	15
3.5	ELI Phantom	16
3.6	Device Holder for Transmitters	17
3.7	Measurement Procedure	18
3.7.1	Scanning procedure	18
3.7.2	Data storage	20
3.7.3	Data Evaluation by SEMCAD	20
4	PD Measurements System Configuraion	22
4.1	Power density measurement system	22
4.2	EUMmWaVe probe	23
4.3	Data Acquisition Electronics (DAE)	24
4.4	Measurement Procedure	24
5	SAR measurement variability and uncertainty	25
5.1	SAR measurement variability	25
5.2	SAR measurement uncertainty	25
6	PD measurement uncertainty	26
7	Description of Test Position	28
7.1	The Body Test Position	28
7.1.1	Laptop computer used next to or against the body	28
8	SAR System Verificaion Procedure	29
8.1	Tissue Simulate Liquid	29
8.1.1	Recipes for Tissue Simulate Liquid	29
8.1.2	Measurement for Tissue Simulate Liquid	30
8.2	SAR System Check	31
8.2.1	Justification for Extended SAR Dipole Calibrations	32



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZSAR-TRF-01 Rev. A/2

Report No.: SZCR250900429206

Page: 5 of 80

8.2.2	Summary System Check Result(s)	33
8.2.3	Detailed System Check Results	33
9	PD System Verification Procedure	34
9.1	PD Test System Verification	34
9.2	PD System Verification Results	36
9.3	Detailed System Check Results	36
10	Test Configuration	37
10.1	Operation Configurations	37
10.1.1	WIFI Test Configuration	37
10.1.2	BT Test Configuration	45
11	Test Result	46
11.1	DUT Antenna Locations (Back View)	46
11.2	Measurement of RF Conducted Power	47
11.2.1	Conducted Power of WIFI 2.4G	47
11.2.2	Conducted Power of WIFI 5G	49
11.2.3	Conducted Power of WIFI 6E	61
11.2.4	Conducted Power of BT	68
11.3	Measurement of SAR Data	69
11.3.1	SAR Result of WIFI 2.4G	70
11.3.2	SAR Result of WIFI 5G	71
11.3.3	SAR Result of WiFi 6E	73
11.3.4	SAR Result of BT	76
11.4	Measurement of PD Data	77
11.4.1	PD Result of WiFi 6E	77
11.5	Multiple Transmitter Evaluation	78
11.5.1	Simultaneous SAR test evaluation	78
11.5.2	Simultaneous Transmission SAR Summation Scenario	78
12	Equipment list	79
13	Calibration certificate	80
14	Photographs	80
Appendix A: Detailed System Check Results		80
Appendix B: Detailed Test Results		80
Appendix C: Calibration certificate		80
Appendix D: Photographs		80



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
 中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

1 General Information

1.1 General Description of EUT

Product Name:	Rugged Laptop		
Model No.:	DT360PA		
Trade Mark:			
Product Phase:	production unit		
Device Type:	portable device		
Exposure Category:	uncontrolled environment / general population		
SN:	036AW25380302		
Hardware Version:	R1.1		
Software Version:	Windows 11		
Antenna Type:	PIFA Antenna		
Antenna Gain:	Band	Antenna 1	Antenna 2
	WIFI 2.4G	7.3dBi	4.4dBi
	WIFI 5G	4.7dBi	3.1dBi
	WIFI 6G	6.2dBi	3.8dBi
	BT/BLE	7.3dBi	
	(Provided by Manufacturer)		
Device Operating Configurations:			
Modulation Mode:	WIFI:DSSS,OFDM,OFDMA; BT:GFSK, π/4DQPSK,8DPSK		
Frequency Bands:	Band	Tx(MHz)	
	WIFI 2.4G	2412~2472	
	WIFI 5G	5150~5250	
		5470~5725	
		5725~5850	
	WIFI 6E	5925~6425	
		6425~6525	
		6525~6875	
		6875~7125	
	BT	2402~2480	
RF Cable:	☒ Provided by applicant ☐ Provided by the laboratory		

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZSAR-TRF-01 Rev. A/2

Report No.: SZCR250900429206

Page: 7 of 80

Battery Information1:	Model:	ACC-006-29(3ICP6/36/115)
	Normal Voltage:	11.4V
	Rated capacity:	3800mAh
	Manufacturer:	Guangdong Pow-Tech New Power Co., Ltd.
Battery Information2:	Model:	ACC-006-29(3ICP6/36/115)
	Normal Voltage:	11.4V
	Rated capacity:	3800mAh
	Manufacturer:	Guangdong Pow-Tech New Power Co., Ltd.
Note: Since the above data and/or information is provided by the client relevant results or conclusions of this report are only made for these data and/or information, SGS is not responsible for the authenticity, integrity and results of the data and information and/or the validity of the conclusion.		



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
 中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

1.2 Test Specification

Identity	Document Title
FCC 47CFR §2.1093	Radiofrequency Radiation Exposure Evaluation: Portable Devices
ANSI/IEEE C95.1-1992	IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz – 300 GHz.
IEEE 1528-2013	Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques
IEC/IEEE 62209-1528:2020	Measurement procedure for the assessment of specific absorption rate of human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices –Part 1528: Human models, instrumentation, and procedures(Frequency range of 4 MHz to 10 GHz)
IEC/IEEE 63195-1:2022	Assessment of power density of human exposure to radio frequency fields from wireless devices in close proximity to the head and body (frequency range of 6 GHz to 300 GHz) – Part 1: Measurement procedure
KDB 248227 D01	SAR Guidance for IEEE 802 11 Wi-Fi SAR v02r02
KDB 447498 D04	Interim General RF Exposure Guidance v01
KDB 865664 D01	SAR Measurement 100 MHz to 6 GHz v01r04
KDB 865664 D02	RF Exposure Reporting v01r02
KDB 690783 D01	SAR Listings on Grants v01r03
KDB 616217 D04	SAR EVALUATION CONSIDERATIONS FOR LAPTOP, NOTEBOOK, NETBOOK AND TABLET COMPUTERS



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

1.3 RF exposure limits

Human Exposure	Uncontrolled Environment General Population	Controlled Environment Occupational
Spatial Peak SAR* (Brain*Trunk)	1.60 mW/g	8.00 mW/g
Spatial Average SAR** (Whole Body)	0.08 mW/g	0.40 mW/g
Spatial Peak SAR*** (Hands/Feet/Ankle/Wrist)	4.00 mW/g	20.00 mW/g

Notes:

* The Spatial Peak value of the SAR averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time

** The Spatial Average value of the SAR averaged over the whole body.

*** The Spatial Peak value of the SAR averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.

Uncontrolled Environments are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure.

Controlled Environments are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation.)

According to ANSI/IEEE C95.1-1992, the criteria listed in Table 1 shall be used to evaluate the environmental impact of human exposure to radio frequency (RF) radiation as specified in §1.1310.

Peak Spatially Averaged Power Density was evaluated over a circular area of 4cm² per interim FCC Guidance for near-field power density evaluations per October 2018 TCB Workshop notes.

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3-3.0	614	1.63	*(100)	6
3.0-30	1842/f	4.89/f	*(900/f ²)	6
30-300	61.4	0.163	1.0	6
300-1500			f/300	6
1500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500			f/1500	30
1500-100,000			1.0	30

Note: 1.0 mW/cm² is equal to 10 W/m²



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

1.4 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China. 518057.

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594

No tests were sub-contracted.

1.5 Test Engineer

Test Engineer: Vito Wang, Roman Pan

1.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **A2LA (Certificate No. 3816.01)**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

- **VCCI (Member No. 1937)**

The 3m Fully-anechoic chamber for above 1GHz, 10m Semi-anechoic chamber for below 1GHz, Shielded Room for Mains Port Conducted Interference Measurement and Telecommunication Port Conducted Interference Measurement of SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen EMC laboratory have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-20026, R-14188, C-12383 and T-11153 respectively.

- **FCC –Designation Number: CN1336**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized as an accredited testing laboratory.

Designation Number: CN1336. Test Firm Registration Number: 787754.

- **Innovation, Science and Economic Development Canada**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized by ISED as an accredited testing laboratory.

CAB identifier: CN0006.

IC#: 4620C.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch EMC Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

2 Laboratory Environment

Temperature	Min. = 18°C, Max. = 25 °C
Relative humidity	Min. = 30%, Max. = 70%
Ground system resistance	< 0.5 Ω
Ambient noise is checked and found very low and in compliance with requirement of standards. Reflection of surrounding objects is minimized and in compliance with requirement of standards.	



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch (SZSAR-TRF-01) Rev. A/2 Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

3 SAR Measurements System Configuraion

3.1 The SAR Measurement System

This SAR Measurement System uses a Computer-controlled 3-D stepper motor system (SPEAG DASY professional system). A E-field probe is used to determine the internal electric fields. The SAR can be obtained from the equation $SAR = \sigma (|E|^2) / \rho$ where σ and ρ are the conductivity and mass density of the tissue-Simulate.


The DASY system for performing compliance tests consists of the following items:

A standard high precision 6-axis robot (Stabile RX family) with controller, teach pendant and software. An arm extension for accommodation the data acquisition electronics (DAE).

A dosimetric probe, i.e., an isotropic E-field probe optimized and calibrated for usage in tissue simulating liquid. The probe is equipped with an optical surface detector system.

A data acquisition electronics (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.

The Electro-optical converter (EOC) performs the conversion between optical and electrical of the signals for the digital communication to DAE and for the analog signal from the optical surface detection. The EOC is connected to the measurement server.



F-1. SAR Measurement System Configuration

- The function of the measurement server is to perform the time critical tasks such as signal filtering,

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZSAR-TRF-01 Rev. A/2

Report No.: SZCR250900429206

Page: 13 of 80

control of the robot operation and fast movement interrupts.

- A probe alignment unit which improves the (absolute) accuracy of the probe positioning.
- A computer operating Windows system.
- DASY software.
- Remote control with teach pendant and additional circuitry for robot safety such as warning lamps, etc.
- The SAM twin phantom enabling testing left-hand, right-hand and Body Worn usage.
- The device holder for handheld mobile phones.
- Tissue simulating liquid mixed according to the given recipes.
- Validation dipole kits allowing to validating the proper functioning of the system.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com


SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Technical Services Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

3.2 Isotropic E-field Probe EX3DV4

	Symmetrical design with triangular core Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., DGBE)
Calibration	ISO/IEC 17025 calibration service available.
Frequency	10 MHz to > 6 GHz Linearity: ± 0.2 dB (30 MHz to 6 GHz)
Directivity	± 0.3 dB in TSL (rotation around probe axis) ± 0.5 dB in TSL (rotation normal to probe axis)
Dynamic Range	10 μ W/g to > 100 mW/g Linearity: ± 0.2 dB (noise: typically < 1 μ W/g)
Dimensions	Overall length: 337 mm (Tip: 20 mm) Tip diameter: 2.5 mm (Body: 12 mm) Typical distance from probe tip to dipole centers: 1 mm
Application	High precision dosimetric measurements in any exposure scenario (e.g., very strong gradient fields); the only probe that enables compliance testing for frequencies up to 6 GHz with precision of better 30%.
Compatibility	DASY52 SAR and higher, EASY4/MRI

3.3 Data Acquisition Electronics (DAE)

Model	DAE	
Construction	Signal amplifier, multiplexer, A/D converter and control logic. Serial optical link for communication with DASY embedded system (fully remote controlled). Two step probe touch detector for mechanical surface detection and emergency robot stop.	
Measurement Range	-100 to +300 mV (16 bit resolution and two range settings: 4mV, 400mV)	
Input Offset Voltage	< 5µV (with auto zero)	
Input Bias Current	< 50 f A	
Dimensions	60 x 60 x 68 mm	


3.4 SAM Twin Phantom

Material	Vinylester, glass fiber reinforced (VE-GF)	
Liquid Compatibility	Compatible with all SPEAG tissue simulating liquids (incl. DGBE type)	
Shell Thickness	2 ± 0.2 mm (6 ± 0.2 mm at ear point)	
Dimensions (incl. Wooden Support)	Length: 1000 mm Width: 500 mm Height: adjustable feet	
Filling Volume	pprox.. 25 liters	
Wooden Support	SPEAG standard phantom table	

The shell corresponds to the specifications of the Specific Anthropomorphic Mannequin (SAM) phantom. It enables the dosimetric evaluation of left and right hand phone usage as well as body mounted usage at the flat phantom region. A cover prevents evaporation of the liquid. Reference markings on the phantom allow the complete setup of all predefined phantom positions and measurement grids by teaching three points with the robot.

Twin SAM V5.0 has the same shell geometry and is manufactured from the same material as Twin SAM V4.0, but has reinforced top structure.

3.5 ELI Phantom

Material	Vinylester, glass fiber reinforced (VE-GF)	
Liquid Compatibility	Compatible with all SPEAG tissue simulating liquids (incl. DGBE type)	
Shell Thickness	2.0 ± 0.2 mm(bottom plate)	
Dimensions	Major axis: 600 mm Minor axis: 400 mm	
Filling Volume	pprox.. 30 liters	
Wooden Support	SPEAG standard phantom table	

Phantom for compliance testing of handheld and body-mounted wireless devices in the frequency range of 4 MHz to 10 GHz. ELI has been optimized regarding its performance and can be integrated into our standard phantom tables. A cover prevents evaporation of the liquid. Reference markings on the phantom allow installation of the complete setup, including all predefined phantom positions and measurement grids, by teaching three points. The phantom is compatible with all SPEAG dosimetric probes and dipoles. ELI V5.0 has the same shell geometry and is manufactured from the same material as ELI4 but has reinforced top structure.

3.6 Device Holder for Transmitters



F-2. Device Holder for Transmitters

- The DASY device holder is designed to cope with different positions given in the standard. It has two scales for the device rotation (with respect to the body axis) and the device inclination (with respect to the line between the ear reference points). The rotation centres for both scales are the ear reference point (ERP). Thus the device needs no repositioning when changing the angles.
- The DASY device holder has been made out of low-loss POM material having the following dielectric parameters: relative permittivity $\epsilon=3$ and loss tangent $\delta=0.02$. The amount of dielectric material has been reduced in the closest vicinity of the device, since measurements have suggested that the influence of the clamp on the test results could thus be lowered.

3.7 Measurement Procedure

3.7.1 Scanning procedure

Step 1: Power reference measurement

The "reference" and "drift" measurements are located at the beginning and end of the batch process. They measure the field drift at one single point in the liquid over the complete procedure.

Step 2: Area scan

The SAR distribution at the exposed side of the head was measured at a distance of 4mm from the inner surface of the shell. The area covered the entire dimension of the head and the horizontal grid spacing was 15mm*15mm or 12mm*12mm or 10mm*10mm. Based on the area scan data, the area of the maximum absorption was determined by spline interpolation.

Step 3: Zoom scan

Around this point, a volume of 32mm*32mm*30mm ($f \leq 2\text{GHz}$), 30mm*30mm*30mm (f for 2-3GHz) and 24mm*24mm*22mm (f for 5-6GHz) was assessed by measuring 5x5x7 points ($f \leq 2\text{GHz}$), 7x7x7 points (f for 2-3GHz) and 7x7x12 points (f for 5-6GHz). On this basis of this data set, the spatial peak SAR value was evaluated with the following procedure:

The data at the surface was extrapolated, since the centre of the dipoles is 2.0mm away from the tip of the probe and the distance between the surface and the lowest measuring point is 1.2mm. (This can be variable. Refer to the probe specification). The extrapolation was based on a least square algorithm. A polynomial of the fourth order was calculated through the points in z-axes. This polynomial was then used to evaluate the points between the surface and the probe tip. The maximum interpolated value was searched with a straight-forward algorithm. Around this maximum the SAR values averaged over the spatial volumes (1g or 10g) were computed using the 3D-Spline interpolation algorithm. The volume was integrated with the trapezoidal algorithm. One thousand points were interpolated to calculate the average. All neighbouring volumes were evaluated until no neighboring volume with a higher average value was found.

If the zoom scan measured as specified in the preceding paragraphs complies with both i) and ii), or if the psSAR is below 0,1 W/kg, no additional measurements are needed.

i) The smallest horizontal distance from the local SAR peaks to all points 3 dB below the SAR peak shall be larger than the horizontal grid steps in both x- and y-directions (Δx , Δy). This shall be checked for the measured zoom scan plane conformal to the phantom at the distance zM1. The minimum distance shall be recorded in the SAR test report.

ii) The ratio of the SAR at the second measured point (M2) to the SAR at the closest measured point (M1) at the x-y location of the measured maximum SAR value shall be at least 30 %. This ratio (in %) shall be recorded in the SAR test report.

		$\leq 3 \text{ GHz}$	$> 3 \text{ GHz}$
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface		$5 \pm 1 \text{ mm}$	$\frac{1}{2} \cdot \delta \cdot \ln(2) \pm 0.5 \text{ mm}$
Maximum probe angle from probe axis to phantom surface normal at the measurement location		$30^\circ \pm 1^\circ$	$20^\circ \pm 1^\circ$
Maximum area scan spatial resolution: $\Delta x_{\text{Area}}, \Delta y_{\text{Area}}$		$\leq 2 \text{ GHz}: \leq 15 \text{ mm}$ $2 - 3 \text{ GHz}: \leq 12 \text{ mm}$	$3 - 4 \text{ GHz}: \leq 12 \text{ mm}$ $4 - 6 \text{ GHz}: \leq 10 \text{ mm}$
		When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be $\leq$ the corresponding x or y dimension of the test device with at least one measurement point on the test device.	
Maximum zoom scan spatial resolution: $\Delta x_{\text{Zoom}}, \Delta y_{\text{Zoom}}$		$\leq 2 \text{ GHz}: \leq 8 \text{ mm}$ $2 - 3 \text{ GHz}: \leq 5 \text{ mm}^*$	$3 - 4 \text{ GHz}: \leq 5 \text{ mm}^*$ $4 - 6 \text{ GHz}: \leq 4 \text{ mm}^*$
Maximum zoom scan spatial resolution, normal to phantom surface	uniform grid: $\Delta z_{\text{Zoom}}(n)$	$\leq 5 \text{ mm}$	$3 - 4 \text{ GHz}: \leq 4 \text{ mm}$ $4 - 5 \text{ GHz}: \leq 3 \text{ mm}$ $5 - 6 \text{ GHz}: \leq 2 \text{ mm}$
	graded grid $\Delta z_{\text{Zoom}}(1)$: between 1 st two points closest to phantom surface	$\leq 4 \text{ mm}$	$3 - 4 \text{ GHz}: \leq 3 \text{ mm}$ $4 - 5 \text{ GHz}: \leq 2.5 \text{ mm}$ $5 - 6 \text{ GHz}: \leq 2 \text{ mm}$
	$\Delta z_{\text{Zoom}}(n>1)$: between subsequent points	$\leq 1.5 \cdot \Delta z_{\text{Zoom}}(n-1)$	
Minimum zoom scan volume	x, y, z	$\geq 30 \text{ mm}$	$3 - 4 \text{ GHz}: \geq 28 \text{ mm}$ $4 - 5 \text{ GHz}: \geq 25 \text{ mm}$ $5 - 6 \text{ GHz}: \geq 22 \text{ mm}$

Step 4: Power reference measurement (drift)

The Power Drift Measurement job measures the field at the same location as the most recent power reference measurement job within the same procedure, and with the same settings. The indicated drift is mainly the variation of the DUT's output power and should vary max $\pm 5 \%$.

3.7.2 Data storage

The DASY software stores the acquired data from the data acquisition electronics as raw data (in microvolt readings from the probe sensors), together with all necessary software parameters for the data evaluation (probe calibration data, liquid parameters and device frequency and modulation data) in measurement files with the extension "DAE". The software evaluates the desired unit and format for output each time the data is visualized or exported. This allows verification of the complete software setup even after the measurement and allows correction of incorrect parameter settings. For example, if a measurement has been performed with a wrong crest factor parameter in the device setup, the parameter can be corrected afterwards and the data can be re-evaluated. The measured data can be visualized or exported in different units or formats, depending on the selected probe type ([V/m], [A/m], [°C], [m W/g], [m W/cm²], [dBrel], etc.). Some of these units are not available in certain situations or show meaningless results, e.g., a SAR output in a lossless media will always be zero. Raw data can also be exported to perform the evaluation with other software packages.

3.7.3 Data Evaluation by SEMCAD

The SEMCAD software automatically executes the following procedures to calculate the field units from the microvolt readings at the probe connector. The parameters used in the evaluation are stored in the configuration modules of the software:

Probe parameters:	- Sensitivity	Normi, ai0, ai1, ai2
- Conversion factor	ConvFi	
- Diode compression point	Dcpi	
Device parameters:	- Frequency	f
- Crest factor	cf	
Media parameters:	- Conductivity	ε
- Density	ρ	

These parameters must be set correctly in the software. They can be found in the component documents, or they can be imported into the software from the configuration files issued for the DASY components. In the direct measuring mode of the multimeter option, the parameters of the actual system setup are used. In the scan visualization and export modes, the parameters stored in the corresponding document files are used.

The first step of the evaluation is a linearization of the filtered input signal to account for the compression characteristics of the detector diode. The compensation depends on the input signal, the diode type and the DC-transmission factor from the diode to the evaluation electronics.

If the exciting field is pulsed, the crest factor of the signal must be known to correctly compensate for peak power. The formula for each channel can be given as:

$$V_i = U_i + U_i^2 \cdot cf / dcp_i$$

With V_i = compensated signal of channel I (I = x, y, z)

U_i = input signal of channel I (I = x, y, z)

cf = crest factor of exciting field (DASY parameter)

dcp I = diode compression point (DASY parameter)

From the compensated input signals the primary field data for each channel can be evaluated:
E-field probes:



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZSAR-TRF-01 Rev. A/2

Report No.: SZCR250900429206

Page: 21 of 80

$$E_i = (V_i / \text{Norm}_i \cdot \text{ConvF})^{1/2}$$

H-field probes:

$$H_i = (V_i)^{1/2} \cdot (a_{i0} + a_{i1}f + a_{i2}f^2) / f$$

With V_i = compensated signal of channel i ($i = x, y, z$)

Norm_i = sensor sensitivity of channel i ($i = x, y, z$)

[mV/(V/m)²] for E-field Probes

ConvF = sensitivity enhancement in solution

a_{ij} = sensor sensitivity factors for H-field probes

f = carrier frequency [GHz]

E_i = electric field strength of channel i in V/m

H_i = magnetic field strength of channel i in A/m

The RSS value of the field components gives the total field strength (Hermitian magnitude):

$$E_{\text{tot}} = (E_x^2 + E_y^2 + E_z^2)^{1/2}$$

The primary field data are used to calculate the derived field units.

$$\text{SAR} = (E_{\text{tot}}^2 \cdot \sigma) / (\epsilon \cdot 1000)$$

with SAR = local specific absorption rate in mW/g

E_{tot} = total field strength in V/m

σ = conductivity in [mho/m] or [Siemens/m]

ϵ = equivalent tissue density in g/cm³

Note that the density is normally set to 1 (or 1.06), to account for actual brain density rather than the density of the simulation liquid. The power flow density is calculated assuming the excitation field to be a free space field.

$$P_{\text{pwe}} = E_{\text{tot}}^2 / 3770 \text{ or } P_{\text{pwe}} = H_{\text{tot}}^2 \cdot 37.7$$

with P_{pwe} = equivalent power density of a plane wave in mW/cm²

E_{tot} = total electric field strength in V/m

H_{tot} = total magnetic field strength in A/m



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.


Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

4 PD Measurements System Configuraion



4.1 Power density measurement system

Power density measurements for mmWave frequencies were performed using SPEAG DASY6 or Higher with mmWave module. The system included a high precision robotics system (Staubli), robot controller, desktop computer, near-field probe, probe alignment sensor, and the mmWave phantom cover.




4.2 EUmmWaVe probe

Frequency	750 MHz – 110 GHz
Probe Overall Length	320 mm
Probe Body Diameter	8.0 mm
Tip Length	23.0 mm
Tip Diameter	8.0 mm
Probe's two dipoles length	0.9 mm – Diode loaded
Dynamic Range	< 20 V/m - 10000 V/m with PRE-10 (min < 50 V/m - 3000 V/m)
Position Precision	< 0.2 mm
Distance between diode sensors and probe's tip	1.5 mm
Minimum Mechanical separation between probe tip and a Surface	0.5 mm
Applications	E-field measurements of 5G devices and other mm-wave transmitters operating above 10GHz in < 2 mm distance from device (free-space) Power density, H-field and far-field analysis using total field reconstruction.
Compatibility	cDASY6 + 5G-Module SW1.0 and higher



The EUmmWaVe probe is based on the pseudo-vector probe design, which not only measures the field magnitude but also derives its polarization ellipse. The design entails two small 0.8mm dipole sensors mechanically protected by high-density foam, printed on both sides of a 0.9mm wide and 0.12mm thick glass substrate. The body of the probe is specifically constructed to minimize distortion by the scattered fields. The probe consists of two sensors with different angles (1 and 2) arranged in the same plane in the probe axis. Three or more measurements of the two sensors are taken for different probe rotational angles to derive the amplitude and polarization information. The probe design allows measurements at distances as small as 2mm from the sensors to the surface of the device under test (DUT). The typical sensor to probe tip distance is 1.5 mm. The exact distance is calibrated.

4.3 Data Acquisition Electronics (DAE)

Model	DAE	
Construction	Signal amplifier, multiplexer, A/D converter and control logic. Serial optical link for communication with DASY embedded system (fully remote controlled). Two step probe touch detector for mechanical surface detection and emergency robot stop.	
Measurement Range	-100 to +300 mV (16 bit resolution and two range settings: 4mV, 400mV)	
Input Offset Voltage	< 5μV (with auto zero)	
Input Bias Current	< 50 f A	
Dimensions	60 x 60 x 68 mm	

4.4 Measurement Procedure

Fine-resolution scans on 2 different planes are performed to reconstruct the E- and H-fields as well as the power density; the z-distance between the 2 planes is set to $\lambda/4$. The (x, y) grid step is also set $\lambda/4$, the grid extent is set to sufficiently large to identify the field pattern and the peak.

5 SAR measurement variability and uncertainty

5.1 SAR measurement variability

Per KDB 865664 D01 SAR measurement 100 MHz to 6 GHz v01r04, SAR measurement variability must be assessed for each frequency band, which is determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. The additional measurements are repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device should be returned to ambient conditions (normal room temperature) with the battery fully charged before it is re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

- 1) Repeated measurement is not required when the original highest measured SAR is < 0.80 W/kg; steps 2) through 4) do not apply.
- 2) When the original highest measured SAR is ≥ 0.80 W/kg, repeat that measurement once.
- 3) Perform a second repeated measurement only if the ratio of largest to smallest SAR for the original and first repeated measurements is > 1.20 or when the original or repeated measurement is ≥ 1.45 W/kg ($\sim 10\%$ from the 1-g SAR limit).
- 4) Perform a third repeated measurement only if the original, first or second repeated measurement is ≥ 1.5 W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 .

The same procedures should be adapted for measurements according to extremity and occupational exposure limits by applying a factor of 2.5 for extremity exposure and a factor of 5 for occupational exposure to the corresponding SAR thresholds.

5.2 SAR measurement uncertainty

Per KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz, when the highest measured 1-g SAR within a frequency band is < 1.5 W/kg, the extensive SAR measurement uncertainty analysis described in IEEE Std 1528-2013 is not required in SAR reports submitted for equipment approval. The equivalent ratio (1.5/1.6) is applied to extremity and occupational exposure conditions.



6 PD measurement uncertainty

Declaration of Conformity:

The test results with all measurement uncertainty excluded is presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

The component of uncertainty may generally be categorized according to the methods used to evaluate them. The evaluation of uncertainty by the statistical analysis of a series of observations is termed a Type A evaluation of uncertainty. The evaluation of uncertainty by means other than the statistical analysis of a series of observation is termed a Type B evaluation of uncertainty. Each component of uncertainty, however evaluated, is represented by an estimated standard deviation, termed standard uncertainty, which is determined by the positive square root of the estimated variance.

A Type A evaluation of standard uncertainty may be based on any valid statistical method for treating data. This includes calculating the standard deviation of the mean of a series of independent observations; using the method of least squares to fit a curve to the data in order to estimate the parameter of the curve and their standard deviations; or carrying out an analysis of variance in order to identify and quantify random effects in certain kinds of measurement.

A type B evaluation of standard uncertainty is typically based on scientific judgment using all of the relevant information available. These may include previous measurement data, experience and knowledge of the behavior and properties of relevant materials and instruments, manufacture's specification, data provided in calibration reports and uncertainties assigned to reference data taken from handbooks. Broadly speaking, the uncertainty is either obtained from an outdoor source or obtained from an assumed distribution, such as the normal distribution, rectangular or triangular distributions indicated in table below.

Uncertainty Distributions	Normal	Rectangular	Triangular	U-Shape
Multiplying Factor ^(a)	1/k ^(b)	1/√3	1/√6	1/√2

Standard Uncertainty for Assumed Distribution

(a) standard uncertainty is determined as the product of the multiplying factor and the estimated range of variations in the measured quantity

(b) κ is the coverage factor

The combined standard uncertainty of the measurement result represents the estimated standard deviation of the result. It is obtained by combining the individual standard uncertainties of both Type A and Type B evaluation using the usual "root-sum-squares" (RSS) methods of combining standard deviations by taking the positive square root of the estimated variances.

Expanded uncertainty is a measure of uncertainty that defines an interval about the measurement result within which the measured value is confidently believed to lie. It is obtained by multiplying the combined standard uncertainty by a coverage factor. Typically, the coverage factor ranges from 2 to 3. Using a coverage factor allows the true value of a measured quantity to be specified with a defined probability within the specified uncertainty range. For purpose of this document, a coverage factor two is used, which corresponds to confidence interval of about 95 %. The DASY uncertainty Budget is shown in the following tables.

Expanded uncertainty is a measure of uncertainty that defines an interval about the measurement result within which the measured value is confidently believed to lie. It is obtained by multiplying the combined standard uncertainty by a coverage factor. The judgment of conformity in the report is based on the measurement results excluding the measurement uncertainty.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZSAR-TRF-01 Rev. A/2

Report No.: SZCR250900429206

Page: 27 of 80

a	b	c	d	e	f=b*e/d	g
Error Description	Uncertainty Value (±dB)	Probability	Div.	Ci	Standard Uncertainty (±dB)	Vi (Veff)
Probe Calibration	0.49	N	1	1	0.49	∞
Probe correction	0.00	R	1.732	1	0.00	∞
Frequency response (BW ≤1 GHz)	0.20	R	1.732	1	0.12	∞
Sensor cross coupling	0.00	R	1.732	1	0.00	∞
Isotropy	0.50	R	1.732	1	0.29	∞
Linearity	0.20	R	1.732	1	0.12	∞
Probe scattering	0.00	R	1.732	1	0.00	∞
Probe positioning offset	0.30	R	1.732	1	0.17	∞
Probe positioning repeatability	0.04	R	1.732	1	0.02	∞
Sensor mechanical offset	0.00	R	1.732	1	0.00	∞
Probe spatial resolution	0.00	R	1.732	1	0.00	∞
Field impedance dependance	0.00	R	1.732	1	0.00	∞
Amplitude and phase drift	0.00	R	1.732	1	0.00	∞
Amplitude and phase noise	0.04	R	1.732	1	0.02	∞
Measurement area truncation	0.00	R	1.732	1	0.00	∞
Data acquisition	0.03	N	1	1	0.03	∞
Sampling	0.00	R	1.732	1	0.00	∞
Field reconstruction	2.00	R	1.732	1	1.15	∞
Forward transformation	0.00	R	1.732	1	0.00	∞
Power density scaling	0.00	R	1.732	1	0.00	∞
Spatial averaging	0.10	R	1.732	1	0.06	∞
System detection limit	0.04	R	1.732	1	0.02	∞
Probe coupling with DUT	0.00	R	1.732	1	0.00	∞
Modulation response	0.40	R	1.732	1	0.23	∞
Integration time	0.00	R	1.732	1	0.00	∞
Response time	0.00	R	1.732	1	0.00	∞
Device holder influence	0.10	R	1.732	1	0.06	∞
DUT alignment	0.00	R	1.732	1	0.00	∞
RF ambient conditions	0.04	R	1.732	1	0.02	∞
Ambient reflections	0.04	R	1.732	1	0.02	∞
Immunity / secondary reception	0.00	R	1.732	1	0.00	∞
Drift of the DUT		R	1.732	1	0.00	∞
Combined Std. Uncertainty					1.33	
Expanded STD Uncertainty (95%), K=2					2.67	



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com


No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
 中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

7 Description of Test Position

7.1 The Body Test Position

7.1.1 Laptop computer used next to or against the body

A typical example of a device used next to the body is a wireless enabled laptop containing a peripheral plug-in radio transmitter that can be supported on the user's body. The DUT shall be positioned with its base (bottom surface) and applicable edges against the flat phantom. The orientations and other use positions can be host device specific. Therefore, these should be determined according to the transmitter and antenna locations on the host device. A testing distance of 5mm or less is used for SAR testing of this type of device.



a) Portable computer

8 SAR System Verificaion Procedure

8.1 Tissue Simulate Liquid

8.1.1 Recipes for Tissue Simulate Liquid

The bellowing tables give the recipes for tissue simulating liquids to be used in different frequency bands:

Ingredients (% by weight)	Frequency (MHz)				
	450	700-1000	1700-2000	2300-2500	2500-2700
Water	38.56	40.30	55.24	55.00	54.92
Salt (NaCl)	3.95	1.38	0.31	0.2	0.23
Sucrose	56.32	57.90	0	0	0
HEC	0.98	0.24	0	0	0
Bactericide	0.19	0.18	0	0	0
Tween	0	0	44.45	44.80	44.85
Salt: 99+% Pure Sodium Chloride Water: De-ionized, 16 MΩ+ resistivity Tween: Polyoxyethylene (20) sorbitan monolaurate Sucrose: 98+% Pure Sucrose HEC: Hydroxyethyl Cellulose					
Head Tissue Simulate Liquid (HBBL600-10000V6) is composed of the following ingredients: (Manufactured by SPEAG) Water: 50-65% Mineral oil: 10-30% Emulsifiers: 8-25% Sodium salt: 0-1.5%					

Table 1 : Recipe of Tissue Simulate Liquid

8.1.2 Measurement for Tissue Simulate Liquid

The Conductivity (σ) and Permittivity (ϵ_r) are listed in Table 2. For the SAR measurement given in this report.


The temperature variation of the Tissue Simulate Liquids was $22 \pm 2^\circ\text{C}$.

Tissue Type	Measured Frequency (MHz)	Measured Tissue		Target Tissue ($\pm 5\%$)		Deviation (Within $\pm 5\%$)		Liquid Temp. ($^\circ\text{C}$)	Test Date
		ϵ_r	$\sigma(\text{S/m})$	ϵ_r	$\sigma(\text{S/m})$	ϵ_r	$\sigma(\text{S/m})$		
2450 Head	2450	38.400	1.790	39.20	1.80	-2.04%	-0.56%	21.7	2025/11/12
5250 Head	5250	36.800	4.690	35.90	4.71	2.51%	-0.42%	22.3	2025/11/6
5600 Head	5600	35.800	5.080	35.50	5.07	0.85%	0.20%	21.9	2025/11/7
5750 Head	5750	35.500	5.250	35.40	5.22	0.28%	0.57%	21.5	2025/11/9
6500 Head	6500	34.000	6.220	34.50	6.07	-1.45%	2.47%	22.1	2025/11/20

Table 2 : Measurement result of Tissue electric parameters

8.2 SAR System Check

The microwave circuit arrangement for system Check is sketched as below. The daily system accuracy verification occurs within the flat section of the SAM phantom. A SAR measurement was performed to see if the measured SAR was within $\pm 10\%$ from the target SAR values. The tests were conducted on the same days as the measurement of the EUT. The obtained results from the system accuracy verification are displayed in the following table (A power level of 250mW (below 3GHz) or 100mW (3GHz or higher) was input to the dipole antenna). During the tests, the ambient temperature of the laboratory was in the range $22\pm 2^\circ\text{C}$, the relative humidity was in the range 60% and the liquid depth above the ear reference points was above $15\pm 0.5\text{ cm}$ in all the cases. It is seen that the system is operating within its specification, as the results are within acceptable tolerance of the reference values.



F-12.The microwave circuit arrangement used for SAR system Check

8.2.1 Justification for Extended SAR Dipole Calibrations

1) Instead of the typical annual calibration recommended by measurement standards, longer calibration intervals of up to three years may be considered when it is demonstrated that the SAR target, impedance and return loss of a dipole have remain stable according to the following requirements. Each measured dipole is expected to evaluate with the following criteria at least on annual interval in Appendix C.

- a) There is no physical damage on the dipole;
- b) System check with specific dipole is within 10% of calibrated value;
- c) Return-loss is within 20% of calibrated measurement;
- d) Impedance is within 5Ω from the previous measurement.

2) Network analyzer probe calibration against air, distilled water and a shorting block performed before measuring liquid parameters.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Inspection & Testing Services Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

8.2.2 Summary System Check Result(s)

Validation Kit	Measured SAR 250mW	Measured SAR 250mW	Measured SAR (normalized to 1W)	Measured SAR (normalized to 1W)	Target SAR (normalized to 1W)	Target SAR (normalized to 1W)	Deviation (Within ±10%)		Liquid Temp. (°C)	Test Date
	1g (W/kg)	10g (W/kg)	1g (W/kg)	10g (W/kg)	1-g(W/kg)	10-g(W/kg)	1-g(W/kg)	10-g(W/kg)		
D2450V2_Head	13.00	6.36	52.00	25.44	51.90	24.50	0.19%	3.84%	21.7	2025/11/12
Validation Kit	Measured SAR 100mW	Measured SAR 100mW	Measured SAR (normalized to 1W)	Measured SAR (normalized to 1W)	Target SAR (normalized to 1W)	Target SAR (normalized to 1W)	Deviation (Within ±10%)		Liquid Temp. (°C)	Test Date
	1g (W/kg)	10g (W/kg)	1g (W/kg)	10g (W/kg)	1-g(W/kg)	10-g(W/kg)	1-g(W/kg)	10-g(W/kg)		
D5GHzV2_5.25G_Head	8.04	2.34	80.40	23.40	79.00	21.80	1.77%	7.34%	22.3	2025/11/6
D5GHzV2_5.6G_Head	7.49	2.17	74.90	21.70	81.60	22.50	-8.21%	-3.56%	21.9	2025/11/7
D5GHzV2_5.75G_Head	7.74	2.22	77.40	22.20	78.30	21.30	-1.15%	4.23%	21.5	2025/11/9
D6500V2_Head	26.50	5.91	265.00	59.10	291.00	53.90	-8.93%	9.65%	22.1	2025/11/20

Table 3 : SAR System Check Result

8.2.3 Detailed System Check Results

Please see the Appendix A

9 PD System Verification Procedure


9.1 PD Test System Verification

The system was verified to be within ± 0.66 dB of the power density targets on the calibration certificate according to the test system specification in the user's manual and calibration facility recommendation. The 0.66 dB deviation threshold represents the expanded uncertainty for system performance checks using SPEAG's mmWave verification sources. The same spatial resolution and measurement region used in the source calibration was applied during the system check.

The measured power density distribution of verification source was also confirmed through visual inspection to have no noticeable differences, both spatially (shape) and numerically (level) from the distribution provided by the manufacturer, per November 2017 TCBC Workshop Notes.

Settings for measurement of verification sources

Frequency [GHz]	Grid step	Grid extent X/Y [mm]	Measurement points
10	0.25 ($\frac{\lambda}{4}$)	120/120	16 × 16
30	0.25 ($\frac{\lambda}{4}$)	60/60	24 × 24
60	0.25 ($\frac{\lambda}{4}$)	32.5/32.5	26 × 26
90	0.25 ($\frac{\lambda}{4}$)	30/30	36 × 36




SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZSAR-TRF-01 Rev. A/2

Report No.: SZCR250900429206

Page: 35 of 80



System Verification Setup Photo



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch (SZSAR-TRF-01) Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

9.2 PD System Verification Results

PD System Validation Result(s)				
Frequent	Measured PD W/m ²	Target PD W/m ²	Circular Deviation (Within ±0.66dB)	Test Date
	4cm ²	4cm ²	4cm ²	
10G HZ Source	179.00	174	0.12	2025/11/24

9.3 Detailed System Check Results

Please see the Appendix A



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
 中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

10 Test Configuration

10.1 Operation Configurations


10.1.1 WIFI Test Configuration

A Wi-Fi device must be configured to transmit continuously at the required data rate, channel bandwidth and signal modulation, using the highest transmission duty factor supported by the test mode tools for SAR measurement.

10.1.1.1 Duty cycle


1) Wi-Fi 2.4GHz 802.11b:

Duty cycle= 99.41%




2) Wi-Fi 5GHz 802.11ac VHT160:

Duty cycle= 98.78%



3) Wi-Fi 5GHz 802.11ax HE160:

Duty cycle= 98.83%




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com


4) Wi-Fi 5GHz 802.11ac VHT80:

Duty cycle= 98.78%



5) Wi-Fi 6E 802.11be EHT320:

Duty cycle= 98.78%



10.1.1.2 Initial Test Position SAR Test Reduction Procedure

DSSS and OFDM configurations are considered separately according to the required SAR procedures. SAR is measured in the initial test position using the 802.11 transmission mode configuration required by the DSSS procedure or initial test configuration and subsequent test configuration(s) according to the OFDM procedures. The initial test position procedure is described in the following:

- 1) . When the reported SAR of the initial test position is ≤ 0.4 W/kg, further SAR measurement is not required for the other (remaining) test positions in that exposure configuration and 802.11 transmission mode combinations within the frequency band or aggregated band. SAR is also not required for that exposure configuration in the subsequent test configuration(s).
- 2) . When the reported SAR of the initial test position is > 0.4 W/kg, SAR is repeated for the 802.11 transmission mode configuration tested in the initial test position using subsequent highest extrapolated or estimated 1-g SAR conditions determined by area scans or next closest/smallest test separation distance and maximum RF coupling test positions based on manufacturer justification, on the highest maximum output power channel, until the reported SAR is ≤ 0.8 W/kg or all required test positions (left, right, touch, tilt or subsequent surfaces and edges) are tested.
- 3) . For all positions/configurations tested using the initial test position and subsequent test positions, when the reported SAR is > 0.8 W/kg, SAR is measured for these test positions/configurations on the subsequent next highest measured output power channel(s) until the reported SAR is ≤ 1.2 W/kg or all required channels are tested. a) Additional power measurements may be required for this step, which should be limited to those necessary for identifying the subsequent highest output power channels.

10.1.1.3 Subsequent Test Configuration Procedures

SAR measurement requirements for the remaining 802.11 transmission mode configurations that have not been tested in the initial test configuration are determined separately for each standalone and aggregated frequency band, in each exposure condition, according to the maximum output power specified for production units. The initial test position procedure is applied to next to the ear, UMPC mini-tablet and hotspot mode configurations. When the same maximum output power is specified for multiple transmission modes, additional power measurements may be required to determine if SAR measurements are required for subsequent highest output power channels in a subsequent test configuration. The subsequent test configuration and SAR measurement procedures are described in the following.

- 1) . When SAR test exclusion provisions of KDB Publication 447498 are applicable and SAR measurement is not required for the initial test configuration, SAR is also not required for the next highest maximum output power transmission mode subsequent test configuration(s) in that frequency band or aggregated band and exposure configuration.
- 2) . When the highest reported SAR for the initial test configuration (when applicable, include subsequent highest output channels), according to the initial test position or fixed exposure position requirements, is adjusted by the ratio of the subsequent test configuration to initial test configuration specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg, SAR is not required for that subsequent test configuration.
- 3) . The number of channels in the initial test configuration and subsequent test configuration can be different due to differences in channel bandwidth. When SAR measurement is required for a subsequent test configuration and the channel bandwidth is smaller than that in the initial test configuration, all channels in the subsequent test configuration that overlap with the larger bandwidth channel tested in the initial test configuration should be used to determine the highest maximum output power channel. This step requires additional power measurement to identify the highest maximum output power channel in the subsequent test configuration to determine SAR test reduction.
 - a) SAR should first be measured for the channel with highest measured output power in the subsequent test configuration.
 - b) SAR for subsequent highest measured maximum output power channels in the subsequent test configuration is required only when the reported SAR of the preceding higher maximum output power channel(s) in the subsequent test configuration is > 1.2 W/kg or until all required channels are tested. i) For channels with the same measured maximum output power, SAR should be measured using the channel closest to the center frequency of the larger channel bandwidth channel in the initial test configuration.
- 4) . SAR measurements for the remaining highest specified maximum output power OFDM transmission mode configurations that have not been tested in the initial test configuration (highest maximum output) or subsequent test configuration(s) (subsequent next highest maximum output power) is determined by recursively applying the subsequent test configuration procedures in this section to the remaining configurations according to the following:
 - a) replace "subsequent test configuration" with "next subsequent test configuration" (i.e., subsequent next highest specified maximum output power configuration)
 - b) replace "initial test configuration" with "all tested higher output power configurations"

10.1.1.4 2.4 GHz WiFi SAR Procedures

Separate SAR procedures are applied to DSSS and OFDM configurations in the 2.4 GHz band to simplify DSSS test requirements. For 802.11b DSSS SAR measurements, DSSS SAR procedure applies to fixed exposure test position and initial test position procedure applies to multiple exposure test positions. When SAR measurement is required for an OFDM configuration, the initial test configuration, subsequent test configuration and initial test position procedures are applied. The SAR test exclusion requirements for 802.11g/n OFDM configurations are described in following.

• 802.11b DSSS SAR Test Requirements

SAR is measured for 2.4 GHz 802.11b DSSS using either a fixed test position or, when applicable, the initial test position procedure. SAR test reduction is determined according to the following:

- 1) . When the reported SAR of the highest measured maximum output power channel for the exposure configuration is ≤ 0.8 W/kg, no further SAR testing is required for 802.11b DSSS in that exposure configuration.
- 2) . When the reported SAR is > 0.8 W/kg, SAR is required for that exposure configuration using the next highest measured output power channel. When any reported SAR is > 1.2 W/kg, SAR is required for the third channel; i.e., all channels require testing.

• 2.4 GHz 802.11g/n OFDM SAR Test Exclusion Requirements

When SAR measurement is required for 2.4 GHz 802.11g/n OFDM configurations, the measurement and test reduction procedures for OFDM are applied (section 5.3, including sub-sections). SAR is not required for the following 2.4 GHz OFDM conditions.

- 1) . When KDB Publication 447498 SAR test exclusion applies to the OFDM configuration.
- 2) . When the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg.

• SAR Test Requirements for OFDM configurations

When SAR measurement is required for 802.11 g/n OFDM configurations, each standalone and frequency aggregated band is considered separately for SAR test reduction. In applying the initial test configuration and subsequent test configuration procedures, the 802.11 transmission configuration with the highest specified maximum output power and the channel within a test configuration with the highest measured maximum output power should be clearly distinguished to apply the procedures.

10.1.1.5 5 GHz WiFi SAR Procedures

• U-NII-1 and U-NII-2A Bands

For devices that operate in only one of the U-NII-1 and U-NII-2A bands, the normally required SAR procedures for OFDM configurations are applied. For devices that operate in both U-NII bands using the same transmitter and antenna(s), SAR test reduction is determined according to the following:

- 1) When the same maximum output power is specified for both bands, begin SAR measurement in U-NII-2A band by applying the OFDM SAR requirements. If the highest reported SAR for a test configuration is ≤ 1.2 W/kg, SAR is not required for U-NII-1 band for that configuration (802.11 mode and exposure condition); otherwise, both bands are tested independently for SAR.
- 2) When different maximum output power is specified for the bands, begin SAR measurement in the band with higher specified maximum output power. The highest reported SAR for the tested configuration is adjusted by the ratio of lower to higher specified maximum output power for the two bands. When the adjusted SAR is ≤ 1.2 W/kg, SAR is not required for the band with lower maximum output power in that test configuration; otherwise, both bands are tested independently for SAR.
- 3) The two U-NII bands may be aggregated to support a 160 MHz channel on channel number 50. Without additional testing, the maximum output power for this is limited to the lower of the maximum output power certified for the two bands. When SAR measurement is required for at least one of the bands and the highest reported SAR adjusted by the ratio of specified maximum output power of aggregated to standalone band is > 1.2 W/kg, SAR is required for the 160 MHz channel. This procedure does not apply to an aggregated band with maximum output higher than the standalone band(s); the aggregated band must be tested independently for SAR. SAR is not required when the 160 MHz channel is operating at a reduced maximum power and also qualifies for SAR test exclusion.

• U-NII-2C and U-NII-3 Bands

The frequency range covered by these bands is 380 MHz (5.47 – 5.85 GHz), which requires a minimum of at least two SAR probe calibration frequency points to support SAR measurements. when Terminal Doppler Weather Radar (TDWR) restriction applies, all channels that operate at 5.60 – 5.65 GHz must be included to apply the SAR test reduction and measurement procedures.

When the same transmitter and antenna(s) are used for U-NII-2C band and U-NII-3 band or 5.8 GHz band of §15.247, the bands may be aggregated to enable additional channels with 20, 40 or 80 MHz bandwidth to span across the band gap, as illustrated in Appendix B. The maximum output power for the additional band gap channels is limited to the lower of those certified for the bands. Unless band gap channels are permanently disabled, they must be considered for SAR testing. The frequency range covered by these bands is 380 MHz (5.47 – 5.85 GHz), which requires a minimum of at least two SAR probe calibration frequency points to support SAR measurements. To maintain SAR measurement accuracy and to facilitate test reduction, the channels in U-NII-2C band above 5.65 GHz may be grouped with the 5.8 GHz channels in U-NII-3 or §15.247 band to enable two SAR probe calibration frequency points to cover the bands, including the band gap channels. When band gap channels are supported and the bands are not aggregated for SAR testing, band gap channels must be considered independently in each band according to the normally required OFDM SAR measurement and probe calibration frequency points requirements.



OFDM Transmission Mode SAR Test Configuration and Channel Selection Requirements

The initial test configuration for 5 GHz OFDM transmission modes is determined by the 802.11 configuration with the highest maximum output power specified for production units, including tune-up tolerance, in each standalone and aggregated frequency band. SAR for the initial test configuration is measured using the highest maximum output power channel determined by the default power measurement procedures. When multiple configurations in a frequency band have the same specified maximum output power, the initial test configuration is determined according to the following steps applied sequentially.

- 1) The largest channel bandwidth configuration is selected among the multiple configurations with the same specified maximum output power.
- 2) If multiple configurations have the same specified maximum output power and largest channel bandwidth, the lowest order modulation among the largest channel bandwidth configurations is selected.
- 3) If multiple configurations have the same specified maximum output power, largest channel bandwidth and lowest order modulation, the lowest data rate configuration among these configurations is selected.
- 4) When multiple transmission modes (802.11a/g/n/ac) have the same specified maximum output power, largest channel bandwidth, lowest order modulation and lowest data rate, the lowest order 802.11 mode is selected; i.e., 802.11a is chosen over 802.11n then 802.11ac or 802.11g is chosen over 802.11n. After an initial test configuration is determined, if multiple test channels have the same measured maximum output power, the channel chosen for SAR measurement is determined according to the following. These channel selection procedures apply to both the initial test configuration and subsequent test configuration(s), with respect to the default power measurement procedures or additional power measurements required for further SAR test reduction. The same procedures also apply to subsequent highest output power channel(s) selection.
 - a) The channel closest to mid-band frequency is selected for SAR measurement.
 - b) For channels with equal separation from mid-band frequency; for example, high and low channels or two mid-band channels, the higher frequency (number) channel is selected for SAR measurement.

• SAR Test Requirements for OFDM configurations


When SAR measurement is required for 802.11 a/n/ac OFDM configurations, each standalone and frequency aggregated band is considered separately for SAR test reduction. When the same transmitter and antenna(s) are used for U-NII-1 and U-NII-2A bands, additional SAR test reduction applies. When band gap channels between U-NII-2C band and 5.8 GHz U-NII-3 or §15.247 band are supported, the highest maximum output power transmission mode configuration and maximum output power channel across the bands must be used to determine SAR test reduction, according to the initial test configuration and subsequent test configuration requirements. In applying the initial test configuration and subsequent test configuration procedures, the 802.11 transmission configuration with the highest specified maximum output power and the channel within a test configuration with the highest measured maximum output power should be clearly distinguished to apply the procedures.



10.1.2 BT Test Configuration

For the Bluetooth SAR tests, a communication link is set up with the test mode software for BT mode test. Bluetooth USES frequency hopping technology to divide the transmitted data into packets and transmit the packets respectively through 79 designated Bluetooth channels, frequency hops at 1600 hops/second per the Bluetooth standard, the EUT is operated at the RF continuous emission mode.

BT DH5 Duty Cycle= 76.75%



11 Test Result

11.1 DUT Antenna Locations (Back View)

The DUT Antenna Locations can be referred to Appendix D



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch (SZSAR-TRF-01) Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

11.2 Measurement of RF Conducted Power

11.2.1 Conducted Power of WIFI 2.4G

WIFI 2.4G Ant1					
Mode	Channel	Frequency(MHz)	Data Rate(Mbps)	Average Power (dBm)	Tune up
802.11b	1	2412	1	14.90	15.50
	6	2437		14.86	15.50
	13	2472		15.12	15.50
802.11g	1	2412	6	14.95	15.50
	6	2437		14.89	15.50
	13	2472		15.18	15.50
802.11n 20MHz	1	2412	6.5	14.80	15.50
	6	2437		14.75	15.50
	13	2472		15.02	15.50
802.11n 40MHz	3	2422	13.5	14.90	15.50
	6	2437		14.97	15.50
	11	2462		15.10	15.50
802.11ax 20MHz	1	2412	MCS0	14.67	15.50
	6	2437		14.60	15.50
	13	2472		14.89	15.50
802.11ax 40MHz	3	2422	MCS0	14.79	15.50
	6	2437		14.91	15.50
	11	2462		14.99	15.50
802.11be 20MHz	1	2412	MCS0	14.65	15.50
	6	2437		14.60	15.50
	13	2472		14.88	15.50
802.11be 40MHz	3	2422	MCS0	14.80	15.50
	6	2437		14.90	15.50
	11	2462		14.99	15.50

WIFI 2.4G Ant2					
Mode	Channel	Frequency(MHz)	Data Rate(Mbps)	Average Power (dBm)	Tune up
802.11b	1	2412	1	14.96	15.50
	6	2437		14.99	15.50
	13	2472		15.06	15.50
802.11g	1	2412	6	15.03	15.50
	6	2437		15.05	15.50
	13	2472		15.14	15.50
802.11n	1	2412	6.5	14.88	15.50



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZSAR-TRF-01 Rev. A/2

Report No.: SZCR250900429206

Page: 48 of 80

20MHz	6	2437		14.91	15.50
	13	2472		14.99	15.50
802.11n 40MHz	3	2422	13.5	15.04	15.50
	6	2437		15.10	15.50
	11	2462		15.13	15.50
802.11ax 20MHz	1	2412	MCS0	14.74	15.50
	6	2437		14.75	15.50
	13	2472		14.86	15.50
802.11ax 40MHz	3	2422	MCS0	14.91	15.50
	6	2437		15.03	15.50
	11	2462		15.04	15.50
802.11be 20MHz	1	2412	MCS0	14.74	15.50
	6	2437		14.77	15.50
	13	2472		14.84	15.50
802.11be 40MHz	3	2422	MCS0	14.93	15.50
	6	2437		15.03	15.50
	11	2462		15.07	15.50

WIFI 2.4G MIMO					
Mode	Channel	Frequency(MHz)	Data Rate(Mbps)	Average Power (dBm)	Tune up
802.11n 20MHz	1	2412	6.5	17.85	18.50
	6	2437		17.84	18.50
	13	2462		18.02	18.50
802.11n 40MHz	3	2422	13.5	17.98	18.50
	6	2437		18.05	18.50
	9	2452		18.13	18.50
802.11ax 20MHz	1	2412	MCS0	17.72	18.50
	6	2437		17.69	18.50
	13	2462		17.89	18.50
802.11ax 40MHz	3	2422	MCS0	17.86	18.50
	6	2437		17.98	18.50
	9	2452		18.03	18.50
802.11be 20MHz	1	2412	MCS0	17.71	18.50
	6	2437		17.70	18.50
	13	2462		17.87	18.50
802.11be 40MHz	3	2422	MCS0	17.88	18.50
	6	2437		17.98	18.50
	9	2452		18.04	18.50



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

11.2.2 Conducted Power of WIFI 5G

WIFI 5G Ant1					
5GHz		Channel	Frequency(MHz)	Average Power (dBm)	Tune up
5GHz U-NII-1	802.11a	36	5180	13.37	14.00
		40	5200	13.22	14.00
		48	5240	13.23	14.00
	802.11n 20MHz	36	5180	13.40	14.00
		40	5200	13.20	14.00
		48	5240	13.20	14.00
	802.11n 40MHz	38	5190	13.31	14.00
		46	5230	13.23	14.00
	802.11ac 20MHz	36	5180	13.36	14.00
		40	5200	13.18	14.00
		48	5240	13.21	14.00
	802.11ac 40MHz	38	5190	13.33	14.00
		46	5230	13.23	14.00
	802.11ac 80MHz	42	5210	13.37	14.00
	802.11ax 20MHz	36	5180	13.08	14.00
		40	5200	12.91	14.00
		48	5240	12.93	14.00
	802.11ax 40MHz	38	5190	13.12	14.00
		46	5230	13.07	14.00
	802.11ax 80MHz	42	5210	13.21	14.00
	802.11be 20MHz	36	5180	13.02	14.00
		40	5200	12.87	14.00
		48	5240	12.88	14.00
	802.11be 40MHz	38	5190	13.05	14.00
		46	5230	12.95	14.00
	802.11be 80MHz	42	5210	13.18	14.00

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZSAR-TRF-01 Rev. A/2

Report No.: SZCR250900429206

Page: 50 of 80

5GHz		Channel	Frequency(MHz)	Average Power (dBm)	Tune up
5GHz U-NII-2A	802.11a	52	5260	13.24	14.00
		60	5300	13.33	14.00
		64	5320	13.28	14.00
	802.11n 20MHz	52	5260	13.15	14.00
		60	5300	13.24	14.00
		64	5320	13.23	14.00
	802.11n 40MHz	54	5270	13.21	14.00
		62	5310	13.28	14.00
	802.11ac 20MHz	52	5260	13.15	14.00
		60	5300	13.20	14.00
		64	5320	13.20	14.00
	802.11ac 40MHz	54	5270	13.25	14.00
		62	5310	13.29	14.00
	802.11ac 80MHz	58	5290	13.42	14.00
	802.11ac 160MHz	50	5250	13.12	14.00
	802.11ax 20MHz	52	5260	12.93	14.00
		60	5300	12.96	14.00
		64	5320	12.96	14.00
	802.11ax 40MHz	54	5270	12.98	14.00
		62	5310	13.04	14.00
	802.11ax 80MHz	58	5290	13.08	14.00
	802.11ax 160MHz	50	5250	12.98	14.00
	802.11be 20MHz	52	5260	12.85	14.00
		60	5300	12.87	14.00
		64	5320	12.84	14.00
	802.11be 40MHz	54	5270	12.95	14.00
		62	5310	12.95	14.00
	802.11be 80MHz	58	5290	13.09	14.00
	802.11be 160MHz	50	5250	13.02	14.00



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZSAR-TRF-01 Rev. A/2

Report No.: SZCR250900429206

Page: 51 of 80

5GHz		Channel	Frequency(MHz)	Average Power (dBm)	Tune up
5GHz UNII-2C	802.11a	100	5500	13.34	14.00
		116	5580	13.81	14.00
		140	5700	13.72	14.00
		144	5720	13.68	14.00
	802.11n 20MHz	100	5500	13.21	14.00
		116	5580	13.71	14.00
		140	5700	13.60	14.00
		144	5720	13.53	14.00
	802.11n 40MHz	102	5510	13.27	14.00
		110	5550	13.63	14.00
		134	5670	13.39	14.00
		142	5710	13.26	14.00
	802.11ac 20MHz	100	5500	13.18	14.00
		116	5580	13.68	14.00
		140	5700	13.59	14.00
		144	5720	13.53	14.00
	802.11ac 40MHz	102	5510	13.25	14.00
		110	5550	13.64	14.00
		134	5670	13.41	14.00
		142	5710	13.44	14.00
	802.11ac 80MHz	106	5530	13.59	14.00
		122	5610	13.79	14.00
	802.11ax 20MHz	100	5500	12.94	14.00
		116	5580	13.48	14.00
		140	5700	13.43	14.00
		144	5720	13.41	14.00
	802.11ax 40MHz	102	5510	12.94	14.00
		110	5550	13.30	14.00
		134	5670	13.14	14.00
		142	5710	13.15	14.00
	802.11ax 80MHz	106	5530	13.26	14.00
		122	5610	13.52	14.00
	802.11ax 160MHz	114	5570	13.29	14.00
	802.11be 20MHz	100	5500	12.78	14.00
		116	5580	13.35	14.00
		140	5700	13.18	14.00
		144	5720	13.12	14.00
	802.11be	102	5510	12.91	14.00



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
 中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZSAR-TRF-01 Rev. A/2

Report No.: SZCR250900429206

Page: 52 of 80

	40MHz	110	5550	13.30	14.00
		134	5670	13.10	14.00
		142	5710	13.11	14.00
	802.11be 80MHz	106	5530	13.25	14.00
		122	5610	13.50	14.00
	802.11be 160MHz	114	5570	13.36	14.00

5GHz		Channel	Frequency(MHz)	Average Power (dBm)	Tune up
5GHz UNII-3	802.11a	149	5745	9.14	10.00
		157	5785	9.08	10.00
		165	5825	8.73	10.00
	802.11n 20MHz	149	5745	9.02	10.00
		157	5785	8.91	10.00
		165	5825	8.59	10.00
	802.11n 40MHz	151	5755	9.03	10.00
		159	5795	8.80	10.00
	802.11ac 20MHz	149	5745	9.01	10.00
		157	5785	8.91	10.00
		165	5825	8.58	10.00
	802.11ac 40MHz	151	5755	9.05	10.00
		159	5795	8.77	10.00
	802.11ac 80MHz	155	5775	9.00	10.00
	802.11ax 20MHz	149	5745	8.84	10.00
		157	5785	8.79	10.00
		165	5825	8.44	10.00
	802.11ax 40MHz	151	5755	8.65	10.00
		159	5795	8.28	10.00
	802.11ax 80MHz	155	5775	8.57	10.00
	802.11be 20MHz	149	5745	8.50	10.00
		157	5785	8.39	10.00
		165	5825	8.05	10.00
	802.11be 40MHz	151	5755	8.63	10.00
		159	5795	8.28	10.00
	802.11be 80MHz	155	5775	8.61	10.00



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZSAR-TRF-01 Rev. A/2

Report No.: SZCR250900429206

Page: 53 of 80

WIFI 5G Ant2					
5GHz		Channel	Frequency(MHz)	Average Power (dBm)	Tune up
5GHz U-NII-1	802.11a	36	5180	13.21	14.00
		40	5200	12.93	14.00
		48	5240	13.07	14.00
	802.11n 20MHz	36	5180	13.25	14.00
		40	5200	12.88	14.00
		48	5240	13.03	14.00
	802.11n 40MHz	38	5190	12.94	14.00
		46	5230	12.96	14.00
	802.11ac 20MHz	36	5180	13.18	14.00
		40	5200	12.88	14.00
		48	5240	13.04	14.00
	802.11ac 40MHz	38	5190	12.96	14.00
		46	5230	12.98	14.00
	802.11ac 80MHz	42	5210	13.11	14.00
	802.11ax 20MHz	36	5180	12.89	14.00
		40	5200	12.57	14.00
		48	5240	12.75	14.00
	802.11ax 40MHz	38	5190	12.74	14.00
		46	5230	12.88	14.00
	802.11ax 80MHz	42	5210	12.97	14.00
	802.11be 20MHz	36	5180	12.92	14.00
		40	5200	12.60	14.00
		48	5240	12.81	14.00
	802.11be 40MHz	38	5190	12.71	14.00
		46	5230	12.75	14.00
	802.11be 80MHz	42	5210	12.90	14.00



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZSAR-TRF-01 Rev. A/2

Report No.: SZCR250900429206

Page: 54 of 80

5GHz		Channel	Frequency(MHz)	Average Power (dBm)	Tune up
5GHz U-NII-2A	802.11a	52	5260	13.16	14.00
		60	5300	13.51	14.00
		64	5320	13.64	14.00
	802.11n 20MHz	52	5260	13.11	14.00
		60	5300	13.38	14.00
		64	5320	13.49	14.00
	802.11n 40MHz	54	5270	13.16	14.00
		62	5310	13.46	14.00
	802.11ac 20MHz	52	5260	13.10	14.00
		60	5300	13.35	14.00
		64	5320	13.50	14.00
	802.11ac 40MHz	54	5270	13.16	14.00
		62	5310	13.47	14.00
	802.11ac 80MHz	58	5290	13.50	14.00
	802.11ac 160MHz	50	5250	13.01	14.00
	802.11ax 20MHz	52	5260	12.85	14.00
		60	5300	13.13	14.00
		64	5320	13.31	14.00
	802.11ax 40MHz	54	5270	13.05	14.00
		62	5310	13.39	14.00
	802.11ax 80MHz	58	5290	13.31	14.00
	802.11ax 160MHz	50	5250	12.95	14.00
	802.11be 20MHz	52	5260	12.86	14.00
		60	5300	13.16	14.00
		64	5320	13.30	14.00
	802.11be 40MHz	54	5270	12.99	14.00
		62	5310	13.28	14.00
	802.11be 80MHz	58	5290	13.31	14.00
	802.11be 160MHz	50	5250	12.98	14.00



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZSAR-TRF-01 Rev. A/2

Report No.: SZCR250900429206

Page: 55 of 80

5GHz		Channel	Frequency(MHz)	Average Power (dBm)	Tune up
5GHz UNII-2C	802.11a	100	5500	13.82	14.00
		116	5580	13.89	14.00
		140	5700	13.88	14.00
		144	5720	13.87	14.00
	802.11n 20MHz	100	5500	13.68	14.00
		116	5580	13.74	14.00
		140	5700	13.74	14.00
		144	5720	13.75	14.00
	802.11n 40MHz	102	5510	13.79	14.00
		110	5550	13.91	14.00
		134	5670	13.46	14.00
		142	5710	13.49	14.00
	802.11ac 20MHz	100	5500	13.69	14.00
		116	5580	13.76	14.00
		140	5700	13.75	14.00
		144	5720	13.71	14.00
	802.11ac 40MHz	102	5510	13.77	14.00
		110	5550	13.92	14.00
		134	5670	13.49	14.00
		142	5710	13.53	14.00
	802.11ac 80MHz	106	5530	13.91	14.00
		122	5610	13.67	14.00
	802.11ax 20MHz	100	5500	13.46	14.00
		116	5580	13.56	14.00
		140	5700	13.58	14.00
		144	5720	13.52	14.00
	802.11ax 40MHz	102	5510	13.63	14.00
		110	5550	13.76	14.00
		134	5670	13.43	14.00
		142	5710	13.61	14.00
	802.11ax 80MHz	106	5530	13.77	14.00
		122	5610	13.57	14.00
	802.11ax 160MHz	114	5570	13.59	14.00
	802.11be 20MHz	100	5500	13.43	14.00
		116	5580	13.56	14.00
		140	5700	13.55	14.00
		144	5720	13.51	14.00
	802.11be	102	5510	13.57	14.00



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
 中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZSAR-TRF-01 Rev. A/2

Report No.: SZCR250900429206

Page: 56 of 80

	40MHz	110	5550	13.70	14.00
		134	5670	13.32	14.00
		142	5710	13.45	14.00
	802.11be 80MHz	106	5530	13.73	14.00
		122	5610	13.58	14.00
	802.11be 160MHz	114	5570	13.59	14.00

5GHz		Channel	Frequency(MHz)	Average Power (dBm)	Tune up
5GHz UNII-3	802.11a	149	5745	8.68	10.00
		157	5785	8.80	10.00
		165	5825	8.59	10.00
	802.11n 20MHz	149	5745	8.56	10.00
		157	5785	8.63	10.00
		165	5825	8.47	10.00
	802.11n 40MHz	151	5755	8.64	10.00
		159	5795	8.68	10.00
	802.11ac 20MHz	149	5745	8.57	10.00
		157	5785	8.65	10.00
		165	5825	8.49	10.00
	802.11ac 40MHz	151	5755	8.63	10.00
		159	5795	8.70	10.00
	802.11ac 80MHz	155	5775	8.65	10.00
	802.11ax 20MHz	149	5745	8.40	10.00
		157	5785	8.49	10.00
		165	5825	8.30	10.00
	802.11ax 40MHz	151	5755	8.53	10.00
		159	5795	8.51	10.00
	802.11ax 80MHz	155	5775	8.55	10.00
	802.11be 20MHz	149	5745	8.35	10.00
		157	5785	8.43	10.00
		165	5825	8.28	10.00
	802.11be 40MHz	151	5755	8.49	10.00
		159	5795	8.50	10.00
	802.11be 80MHz	155	5775	8.55	10.00



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZSAR-TRF-01 Rev. A/2

Report No.: SZCR250900429206

Page: 57 of 80

WIFI 5G MIMO					
5GHz		Channel	Frequency(MHz)	Average Power (dBm)	Tune up
5GHz U-NII-1	802.11n 20MHz	36	5180	16.34	17.00
		40	5200	16.05	17.00
		48	5240	16.13	17.00
	802.11n 40MHz	38	5190	16.14	17.00
		46	5230	16.11	17.00
	802.11ac 20MHz	36	5180	16.28	17.00
		40	5200	16.04	17.00
		48	5240	16.14	17.00
	802.11ac 40MHz	38	5190	16.16	17.00
		46	5230	16.12	17.00
	802.11ac 80MHz	42	5210	16.25	17.00
	802.11ax 20MHz	36	5180	16.00	17.00
		40	5200	15.75	17.00
		48	5240	15.85	17.00
	802.11ax 40MHz	38	5190	15.94	17.00
		46	5230	15.99	17.00
	802.11ax 80MHz	42	5210	16.10	17.00
	802.11be 20MHz	36	5180	15.98	17.00
		40	5200	15.75	17.00
		48	5240	15.86	17.00
	802.11be 40MHz	38	5190	15.89	17.00
		46	5230	15.86	17.00
	802.11be 80MHz	42	5210	16.05	17.00



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZSAR-TRF-01 Rev. A/2

Report No.: SZCR250900429206

Page: 58 of 80

5GHz		Channel	Frequency(MHz)	Average Power (dBm)	Tune up
5GHz U-NII-2A	802.11n HT20	52	5260	16.14	17.00
		60	5300	16.32	17.00
		64	5320	16.37	17.00
	802.11n HT40	54	5270	16.20	17.00
		62	5310	16.38	17.00
	802.11ac VHT20	52	5260	16.14	17.00
		60	5300	16.29	17.00
		64	5320	16.36	17.00
	802.11ac VHT40	54	5270	16.22	17.00
		62	5310	16.39	17.00
	802.11ac VHT80	58	5290	16.47	17.00
	802.11ac VHT160	50	5250	16.08	17.00
	802.11ax HE20	52	5260	15.90	17.00
		60	5300	16.06	17.00
		64	5320	16.15	17.00
	802.11ax HE40	54	5270	16.03	17.00
		62	5310	16.23	17.00
	802.11ax HE80	58	5290	16.21	17.00
	802.11ax HE160	50	5250	15.98	17.00
	802.11be EHT20	52	5260	15.87	17.00
		60	5300	16.03	17.00
		64	5320	16.09	17.00
	802.11be EHT40	54	5270	15.98	17.00
		62	5310	16.13	17.00
	802.11be EHT80	58	5290	16.21	17.00
	802.11be EHT160	50	5250	16.01	17.00



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZSAR-TRF-01 Rev. A/2

Report No.: SZCR250900429206

Page: 59 of 80

5GHz		Channel	Frequency(MHz)	Average Power (dBm)	Tune up
5GHz UNII-2C	802.11n HT20	100	5500	16.46	17.00
		140	5700	16.68	17.00
		144	5720	16.65	17.00
	802.11n HT40	102	5510	16.55	17.00
		110	5550	16.78	17.00
		134	5670	16.44	17.00
		142	5710	16.39	17.00
	802.11ac VHT20	100	5500	16.45	17.00
		140	5700	16.68	17.00
		144	5720	16.63	17.00
	802.11ac VHT40	102	5510	16.53	17.00
		110	5550	16.79	17.00
		134	5670	16.46	17.00
		142	5710	16.50	17.00
	802.11ac VHT80	106	5530	16.76	17.00
		122	5610	16.74	17.00
	802.11ax HE20	100	5500	16.22	17.00
		140	5700	16.52	17.00
		144	5720	16.48	17.00
	802.11ax HE40	102	5510	16.31	17.00
		110	5550	16.55	17.00
		134	5670	16.30	17.00
		142	5710	16.40	17.00
	802.11ax HE80	106	5530	16.53	17.00
		122	5610	16.56	17.00
	802.11ax HE160	114	5570	16.45	17.00
	802.11be EHT20	100	5500	16.13	17.00
		140	5700	16.38	17.00
		144	5720	16.33	17.00
	802.11be EHT40	102	5510	16.26	17.00
		110	5550	16.51	17.00
		134	5670	16.22	17.00
		142	5710	16.29	17.00
	802.11be EHT80	106	5530	16.51	17.00
		122	5610	16.55	17.00
	802.11be EHT160	114	5570	16.49	17.00



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZSAR-TRF-01 Rev. A/2

Report No.: SZCR250900429206

Page: 60 of 80

5GHz		Channel	Frequency(MHz)	Average Power (dBm)	Tune up
5GHz UNII-3	802.11n 20MHz	149	5745	11.81	13.00
		157	5785	11.78	13.00
		165	5825	11.54	13.00
	802.11n 40MHz	151	5755	11.85	13.00
		159	5795	11.75	13.00
	802.11ac 20MHz	149	5745	11.81	13.00
		157	5785	11.79	13.00
		165	5825	11.55	13.00
	802.11ac 40MHz	151	5755	11.86	13.00
		159	5795	11.75	13.00
	802.11ac 80MHz	155	5775	11.84	13.00
	802.11ax 20MHz	149	5745	11.64	13.00
		157	5785	11.65	13.00
		165	5825	11.38	13.00
	802.11ax 40MHz	151	5755	11.60	13.00
		159	5795	11.41	13.00
	802.11ax 80MHz	155	5775	11.57	13.00
	802.11be 20MHz	149	5745	11.44	13.00
		157	5785	11.42	13.00
		165	5825	11.18	13.00
	802.11be 40MHz	151	5755	11.57	13.00
		159	5795	11.40	13.00
	802.11be 80MHz	155	5775	11.59	13.00



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

11.2.3 Conducted Power of WIFI 6E

WIFI 6E Ant1						
Band	Mode	Channel	Frequency (MHz)	Data Rate	Average Power (dBm)	Tune up
U - NII - 5 6.2GHz	802.11ax 20MHz	1	5955	MCS0	13.36	14.5
		45	6175		13.31	14.5
		93	6415		13.27	14.5
	802.11ax 40MHz	3	5965	MCS0	13.40	14.5
		43	6165		13.35	14.5
		91	6405		13.37	14.5
	802.11ax 80MHz	7	5985	MCS0	13.58	14.5
		39	6145		13.51	14.5
		87	6385		13.62	14.5
	802.11ax 160MHz	15	6025	MCS0	13.60	14.5
		47	6185		13.93	14.5
		79	6345		14.06	14.5
	802.11be 20MHz	1	5955	MCS0	13.78	14.5
		45	6175		13.69	14.5
		93	6415		13.57	14.5
	802.11be 40MHz	3	5965	MCS0	13.65	14.5
		43	6165		13.36	14.5
		91	6405		13.75	14.5
	802.11be 80MHz	7	5985	MCS0	13.48	14.5
		39	6145		13.41	14.5
		87	6385		13.47	14.5
	802.11be 160MHz	15	6025	MCS0	13.39	14.5
		47	6185		13.58	14.5
		79	6345		13.70	14.5
	802.11be 320MHz	31	6105	MCS0	13.61	14.5
		63	6265		13.49	14.5
U - NII - 6 6.5GHz	802.11ax 20MHz	97	6435	MCS0	13.30	14.5
		105	6475		13.36	14.5
		113	6515		13.20	14.5
	802.11ax 40MHz	99	6445	MCS0	13.15	14.5
		107	6485		13.38	14.5
	802.11ax 80MHz	103	6465	MCS0	13.47	14.5
		119	6545		13.73	14.5
	802.11ax 160MHz	111	6505	MCS0	14.13	14.5
	802.11be 20MHz	97	6435	MCS0	13.69	14.5
		105	6475		13.48	14.5
		113	6515		13.35	14.5
	802.11be	99	6445	MCS0	13.80	14.5



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZSAR-TRF-01 Rev. A/2

Report No.: SZCR250900429206

Page: 62 of 80

	40MHz	107	6485		13.86	14.5
	802.11be 80MHz	103	6465	MCS0	13.46	14.5
		119	6545		13.40	14.5
	802.11be 160MHz	111	6505	MCS0	13.39	14.5
	802.11be 320MHz	95	6425	MCS0	13.22	14.5

U - NII - 7 6.7GHz	802.11ax 20MHz	117	6535	MCS0	13.08	14.5
		149	6695		13.37	14.5
		181	6855		13.30	14.5
	802.11ax 40MHz	115	6525	MCS0	13.59	14.5
		147	6685		13.52	14.5
		179	6845		13.38	14.5
	802.11ax 80MHz	135	6625	MCS0	13.39	14.5
		151	6705		13.65	14.5
		167	6785		13.60	14.5
	802.11ax 160MHz	143	6665	MCS0	13.73	14.5
		175	6825		14.02	14.5
	802.11be 20MHz	117	6535	MCS0	14.10	14.5
		149	6695		13.80	14.5
		181	6855		13.48	14.5
	802.11be 40MHz	115	6525	MCS0	13.39	14.5
		147	6685		13.55	14.5
		179	6845		13.73	14.5
	802.11be 80MHz	135	6625	MCS0	13.47	14.5
		151	6705		13.40	14.5
		167	6785		13.66	14.5
	802.11be 160MHz	143	6665	MCS0	13.51	14.5
		175	6825		13.56	14.5
	802.11be 320MHz	127	6585	MCS0	13.43	14.5
		159	6745		13.29	14.5
U - NII - 8 7.0GHz	802.11ax 20MHz	185	6875	MCS0	13.36	14.5
		209	6995		13.35	14.5
		233	7115		13.28	14.5
	802.11ax 40MHz	187	6885	MCS0	13.20	14.5
		227	7085		13.36	14.5
	802.11ax 80MHz	183	6865	MCS0	13.92	14.5
		199	6945		13.76	14.5
		215	7025		13.91	14.5
	802.11ax 160MHz	207	6985	MCS0	14.38	14.5
	802.11be	185	6875	MCS0	13.88	14.5



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Inspection & Testing Services Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZSAR-TRF-01 Rev. A/2

Report No.: SZCR250900429206

Page: 63 of 80

	20MHz	209	6995		13.60	14.5
		233	7115		13.69	14.5
	802.11be 40MHz	187	6885	MCS0	13.48	14.5
		227	7085		13.99	14.5
	802.11be 80MHz	183	6865	MCS0	13.60	14.5
		199	6945		13.49	14.5
		215	7025		13.69	14.5
	802.11be 160MHz	207	6985	MCS0	13.63	14.5
	802.11be 320MHz	191	6905	MCS0	13.42	14.5

WIFI 6E Ant2						
Band	Mode	Channel	Frequency (MHz)	Data Rate	Average Power (dBm)	Tune up
U - NII - 5 6.2GHz	802.11ax 20MHz	1	5955	MCS0	13.07	14.5
		45	6175		13.11	14.5
		93	6415		13.02	14.5
	802.11ax 40MHz	3	5965	MCS0	13.00	14.5
		43	6165		13.12	14.5
		91	6405		13.13	14.5
	802.11ax 80MHz	7	5985	MCS0	13.15	14.5
		39	6145		13.13	14.5
		87	6385		13.21	14.5
	802.11ax 160MHz	15	6025	MCS0	13.15	14.5
		47	6185		13.22	14.5
		79	6345		13.36	14.5
	802.11be 20MHz	1	5955	MCS0	13.00	14.5
		45	6175		13.12	14.5
		93	6415		13.44	14.5
	802.11be 40MHz	3	5965	MCS0	13.27	14.5
		43	6165		13.32	14.5
		91	6405		13.05	14.5
	802.11be 80MHz	7	5985	MCS0	13.13	14.5
		39	6145		13.07	14.5
		87	6385		13.22	14.5
	802.11be 160MHz	15	6025	MCS0	13.15	14.5
		47	6185		13.29	14.5
		79	6345		12.94	14.5
	802.11be 320MHz	31	6105	MCS0	12.93	14.5
		63	6265		13.05	14.5
U - NII - 6 6.5GHz	802.11ax 20MHz	97	6435	MCS0	13.13	14.5
		105	6475		13.05	14.5



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Inspection & Testing Services Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZSAR-TRF-01 Rev. A/2

Report No.: SZCR250900429206

Page: 64 of 80

		113	6515		13.03	14.5
	802.11ax 40MHz	99	6445	MCS0	13.09	14.5
		107	6485		13.22	14.5
	802.11ax 80MHz	103	6465	MCS0	13.21	14.5
		119	6545		13.07	14.5
	802.11ax 160MHz	111	6505	MCS0	13.65	14.5
	802.11be 20MHz	97	6435	MCS0	13.22	14.5
		105	6475		13.13	14.5
		113	6515		13.05	14.5
	802.11be 40MHz	99	6445	MCS0	13.11	14.5
		107	6485		13.07	14.5
	802.11be 80MHz	103	6465	MCS0	13.31	14.5
		119	6545		13.43	14.5
	802.11be 160MHz	111	6505	MCS0	13.24	14.5
	802.11be 320MHz	95	6425	MCS0	12.98	14.5

U - NII - 7 6.7GHz	802.11ax 20MHz	117	6535	MCS0	12.93	14.5
		149	6695		13.29	14.5
		181	6855		13.02	14.5
	802.11ax 40MHz	115	6525	MCS0	13.14	14.5
		147	6685		13.23	14.5
		179	6845		13.02	14.5
	802.11ax 80MHz	135	6625	MCS0	13.12	14.5
		151	6705		13.09	14.5
		167	6785		13.08	14.5
	802.11ax 160MHz	143	6665	MCS0	13.27	14.5
		175	6825		13.53	14.5
	802.11be 20MHz	117	6535	MCS0	13.47	14.5
		149	6695		13.22	14.5
		181	6855		13.06	14.5
	802.11be 40MHz	115	6525	MCS0	13.33	14.5
		147	6685		13.05	14.5
		179	6845		13.04	14.5
	802.11be 80MHz	135	6625	MCS0	13.31	14.5
		151	6705		13.26	14.5
		167	6785		13.42	14.5
	802.11be 160MHz	143	6665	MCS0	13.37	14.5
		175	6825		13.24	14.5
	802.11be 320MHz	127	6585	MCS0	13.04	14.5
		159	6745		12.92	14.5



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Technical Services Co., Ltd. Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZSAR-TRF-01 Rev. A/2

Report No.: SZCR250900429206

Page: 65 of 80

U - NII - 8 7.0GHz	802.11ax 20MHz	185	6875	MCS0	13.00	14.5
		209	6995		12.94	14.5
		233	7115		12.90	14.5
	802.11ax 40MHz	187	6885	MCS0	13.15	14.5
		227	7085		13.21	14.5
	802.11ax 80MHz	183	6865	MCS0	13.07	14.5
		199	6945		13.22	14.5
		215	7025		13.29	14.5
	802.11ax 160MHz	207	6985	MCS0	13.84	14.5
	802.11be 20MHz	185	6875	MCS0	13.20	14.5
		209	6995		13.17	14.5
		233	7115		13.16	14.5
	802.11be 40MHz	187	6885	MCS0	13.23	14.5
		227	7085		13.04	14.5
	802.11be 80MHz	183	6865	MCS0	13.11	14.5
		199	6945		13.23	14.5
		215	7025		13.13	14.5
	802.11be 160MHz	207	6985	MCS0	13.19	14.5
	802.11be 320MHz	191	6905	MCS0	13.06	14.5

WIFI 6E MIMO						
Band	Mode	Channel	Frequency (MHz)	Data Rate	Average Power (dBm)	Tune up
U - NII - 5 6.2GHz	802.11ax 20MHz	1	5955	MCS0	16.23	17.50
		45	6175		16.22	17.50
		93	6415		16.16	17.50
	802.11ax 40MHz	3	5965	MCS0	16.21	17.50
		43	6165		16.25	17.50
		91	6405		16.26	17.50
	802.11ax 80MHz	7	5985	MCS0	16.38	17.50
		39	6145		16.33	17.50
		87	6385		16.43	17.50
	802.11ax 160MHz	15	6025	MCS0	16.39	17.50
		47	6185		16.60	17.50
		79	6345		16.73	17.50
	802.11be 20MHz	1	5955	MCS0	16.42	17.50
		45	6175		16.42	17.50
		93	6415		16.52	17.50
	802.11be 40MHz	3	5965	MCS0	16.47	17.50
		43	6165		16.35	17.50



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Inspection & Testing Services Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZSAR-TRF-01 Rev. A/2

Report No.: SZCR250900429206

Page: 66 of 80

U - NII - 6 6.5GHz	802.11be 80MHz	91	6405	MCS0	16.42	17.50
		7	5985		16.32	17.50
		39	6145		16.25	17.50
		87	6385		16.36	17.50
	802.11be 160MHz	15	6025	MCS0	16.28	17.50
		47	6185		16.45	17.50
		79	6345		16.35	17.50
	802.11be 320MHz	31	6105	MCS0	16.29	17.50
		63	6265		16.29	17.50
	802.11ax 20MHz	97	6435	MCS0	16.23	17.50
		105	6475		16.22	17.50
		113	6515		16.13	17.50
U - NII - 7 6.7GHz	802.11ax 40MHz	99	6445	MCS0	16.13	17.50
		107	6485		16.31	17.50
	802.11ax 80MHz	103	6465	MCS0	16.35	17.50
		119	6545		16.42	17.50
	802.11ax 160MHz	111	6505	MCS0	16.91	17.50
	802.11be 20MHz	97	6435	MCS0	16.47	17.50
		105	6475		16.32	17.50
		113	6515		16.21	17.50
	802.11be 40MHz	99	6445	MCS0	16.48	17.50
		107	6485		16.49	17.50
	802.11be 80MHz	103	6465	MCS0	16.40	17.50
		119	6545		16.43	17.50
	802.11be 160MHz	111	6505	MCS0	16.33	17.50
	802.11be 320MHz	95	6425	MCS0	16.11	17.50

U - NII - 7 6.7GHz	802.11ax 20MHz	117	6535	MCS0	16.02	17.50
		149	6695		16.34	17.50
		181	6855		16.17	17.50
	802.11ax 40MHz	115	6525	MCS0	16.38	17.50
		147	6685		16.39	17.50
		179	6845		16.21	17.50
	802.11ax 80MHz	135	6625	MCS0	16.27	17.50
		151	6705		16.39	17.50
		167	6785		16.36	17.50
	802.11ax 160MHz	143	6665	MCS0	16.52	17.50
		175	6825		16.79	17.50
	802.11be 20MHz	117	6535	MCS0	16.81	17.50
		149	6695		16.53	17.50



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Inspection & Testing Services Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZSAR-TRF-01 Rev. A/2

Report No.: SZCR250900429206

Page: 67 of 80

	802.11be 40MHz	181	6855	MCS0	16.29	17.50
		115	6525		16.37	17.50
		147	6685		16.32	17.50
		179	6845		16.41	17.50
	802.11be 80MHz	135	6625	MCS0	16.40	17.50
		151	6705		16.34	17.50
		167	6785		16.55	17.50
	802.11be 160MHz	143	6665	MCS0	16.45	17.50
		175	6825		16.41	17.50
	802.11be 320MHz	127	6585	MCS0	16.25	17.50
		159	6745		16.12	17.50
U - NII - 8 7.0GHz	802.11ax 20MHz	185	6875	MCS0	16.19	17.50
		209	6995		16.16	17.50
		233	7115		16.10	17.50
	802.11ax 40MHz	187	6885	MCS0	16.19	17.50
		227	7085		16.30	17.50
	802.11ax 80MHz	183	6865	MCS0	16.53	17.50
		199	6945		16.51	17.50
		215	7025		16.62	17.50
	802.11ax 160MHz	207	6985	MCS0	17.13	17.50
	802.11be 20MHz	185	6875	MCS0	16.56	17.50
		209	6995		16.40	17.50
		233	7115		16.44	17.50
	802.11be 40MHz	187	6885	MCS0	16.37	17.50
		227	7085		16.55	17.50
	802.11be 80MHz	183	6865	MCS0	16.37	17.50
		199	6945		16.37	17.50
		215	7025		16.43	17.50
	802.11be 160MHz	207	6985	MCS0	16.43	17.50
	802.11be 320MHz	191	6905	MCS0	16.25	17.50



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

11.2.4 Conducted Power of BT

BT		Average Conducted Power(dBm)			Tune up
Band	Channel	0	39	78	
BT	GFSK	14.32	14.66	15.01	15.00
	$\pi/4$ DQPSK	14.00	14.33	14.67	15.00
	8DPSK	14.38	14.70	15.02	15.00
Band	Channel	0	19	39	Tune up
BLE 1M	GFSK	6.02	6.22	6.49	7.00
BLE 2M	GFSK	6.06	6.28	6.54	7.00



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.ssgsgroup.com.cn
 中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

11.3 Measurement of SAR Data

Note:

- 1) The maximum Scaled SAR value is marked in bold. Graph results refer to Appendix B.
- 2) Testing of other required channels within the operating mode of a frequency band is not required when the reported 1-g or 10-g SAR for the mid-band or highest output power channel is:
 - $\leq 0.8\text{W/kg}$ for 1-g or 2.0W/kg for 10-g respectively, when the transmission band is $\leq 100\text{MHz}$.
 - $\leq 0.6\text{ W/kg}$ or 1.5 W/kg , for 1-g or 10-g respectively, when the transmission band is between 100 MHz and 200 MHz.
 - $\leq 0.4\text{ W/kg}$ or 1.0 W/kg , for 1-g or 10-g respectively, when the transmission band is $\geq 200\text{ MHz}$.
- 3) The device does not support DTM function.
- 4) For WiFi 5G,U-NII-2A and U-NII-2C band does not support hotspot function.
- 5) For WiFi SAR test, the djusted SAR is $\leq 1.2\text{ W/kg}$ for other 802.11 modes, SAR test for the other 802.11 modes are not required. For Product specific 10gSAR, the adjusted SAR is $\leq 3.0\text{ W/kg}$ for other 802.11 modes, SAR test for the other 802.11 modes are also not required.



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZSAR-TRF-01 Rev. A/2

Report No.: SZCR250900429206

Page: 70 of 80

11.3.1 SAR Result of WIFI 2.4G

Ant1 Test Record chain1												
Test position	Test mode	Test ch./Freq.	Duty Cycle	Duty Cycle Scaled factor	SAR (W/kg) 1-g	SAR (W/kg) 10-g	Power drift (dB)	Conducted Power(dBm)	Tune up Limit(dBm)	Scaled factor	Scaled SAR 1-g (W/kg)	Liquid Temp.(°C)
Body data (Separate 0mm)												
Front side	802.11b	13/2472	99.41%	1.006	0.823	0.382	-0.09	15.12	15.50	1.091	0.903	21.5
Back side	802.11b	13/2472	99.41%	1.006	0.755	0.372	0.03	15.12	15.50	1.091	0.829	21.5
Left side	802.11b	13/2472	99.41%	1.006	0.069	0.026	0.16	15.12	15.50	1.091	0.076	21.5
Right side	802.11b	13/2472	99.41%	1.006	0.074	0.033	0.18	15.12	15.50	1.091	0.081	21.5
Top side	802.11b	13/2472	99.41%	1.006	0.041	0.015	0.12	15.12	15.50	1.091	0.045	21.5
Bottom side	802.11b	13/2472	99.41%	1.006	0.042	0.012	0.07	15.12	15.50	1.091	0.046	21.5
Front side	802.11b	1/2412	99.41%	1.006	0.674	0.298	-0.06	14.90	15.50	1.148	0.778	21.5
Front side	802.11b	6/2437	99.41%	1.006	0.578	0.272	-0.02	14.86	15.50	1.159	0.674	21.5
Ant2 Test Record chain2												
Test position	Test mode	Test ch./Freq.	Duty Cycle	Duty Cycle Scaled factor	SAR (W/kg) 1-g	SAR (W/kg) 10-g	Power drift (dB)	Conducted Power(dBm)	Tune up Limit(dBm)	Scaled factor	Scaled SAR 1-g (W/kg)	Liquid Temp.(°C)
Body data (Separate 0mm)												
Front side	802.11b	13/2472	99.41%	1.006	0.503	0.236	-0.03	15.06	15.50	1.107	0.560	21.5
Back side	802.11b	13/2472	99.41%	1.006	0.456	0.221	-0.09	15.06	15.50	1.107	0.508	21.5
Left side	802.11b	13/2472	99.41%	1.006	0.021	0.010	0.14	15.06	15.50	1.107	0.023	21.5
Right side	802.11b	13/2472	99.41%	1.006	0.293	0.141	0.19	15.06	15.50	1.107	0.326	21.5
Top side	802.11b	13/2472	99.41%	1.006	0.103	0.054	-0.01	15.06	15.50	1.107	0.115	21.5
Bottom side	802.11b	13/2472	99.41%	1.006	0.045	0.026	0.08	15.06	15.50	1.107	0.050	21.5
Front side	802.11b	1/2412	99.41%	1.006	0.411	0.172	0.02	14.96	15.50	1.132	0.468	21.5
Front side	802.11b	6/2437	99.41%	1.006	0.419	0.190	0.15	14.99	15.50	1.125	0.474	21.5
MIMO Test Record												
Test position	Test mode	Test ch./Freq.	Duty Cycle	Duty Cycle Scaled factor	SAR (W/kg) 1-g	SAR (W/kg) 10-g	Power drift (dB)	Conducted Power(dBm)	Tune up Limit(dBm)	Scaled factor	Scaled SAR 1-g (W/kg)	Liquid Temp.(°C)
Body data (Separate 0mm)												
Front side	802.11b	13/2472	99.41%	1.006	1.140	0.534	0.09	18.02	18.50	1.117	1.281	21.5
Back side	802.11b	13/2472	99.41%	1.006	1.020	0.522	-0.11	18.02	18.50	1.117	1.146	21.5
Left side	802.11b	13/2472	99.41%	1.006	0.196	0.082	-0.17	18.02	18.50	1.117	0.220	21.5
Right side	802.11b	13/2472	99.41%	1.006	0.331	0.152	0.14	18.02	18.50	1.117	0.372	21.5
Top side	802.11b	13/2472	99.41%	1.006	0.703	0.332	-0.06	18.02	18.50	1.117	0.790	21.5
Bottom side	802.11b	13/2472	99.41%	1.006	0.376	0.131	-0.09	18.02	18.50	1.117	0.423	21.5
Front side	802.11b	1/2412	99.41%	1.006	1.050	0.522	0.03	17.85	18.50	1.161	1.226	21.5
Front side	802.11b	6/2437	99.41%	1.006	1.010	0.515	-0.07	17.84	18.50	1.164	1.183	21.5



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained herein reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
 中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

11.3.2 SAR Result of WIFI 5G

Ant1 Test Record chain1												
Test position	Test mode	Test ch./Freq.	Duty Cycle	Duty Cycle Scaled factor	SAR (W/kg) 1-g	SAR (W/kg) 10-g	Power drift (dB)	Conducted Power(dBm)	Tune up Limit(dBm)	Scaled factor	Scaled SAR 1-g (W/kg)	Liquid Temp.(°C)
Body Test data of U-NII-2A (Separate 0mm)												
Front side	802.11ac VHT160	50/5250	98.78%	1.012	0.626	0.200	-0.05	13.12	14.00	1.225	0.776	21.5
Back side	802.11ac VHT160	50/5250	98.78%	1.012	0.104	0.036	0.18	13.12	14.00	1.225	0.129	21.5
Left side	802.11ac VHT160	50/5250	98.78%	1.012	0.035	0.009	0.09	13.12	14.00	1.225	0.043	21.5
Right side	802.11ac VHT160	50/5250	98.78%	1.012	0.022	0.007	-0.04	13.12	14.00	1.225	0.027	21.5
Top side	802.11ac VHT160	50/5250	98.78%	1.012	0.017	0.004	0.17	13.12	14.00	1.225	0.021	21.5
Bottom side	802.11ac VHT160	50/5250	98.78%	1.012	0.055	0.013	-0.18	13.12	14.00	1.225	0.068	21.5
Body Test data of U-NII-2C (Separate 0mm)												
Front side	802.11ax HE160	114/5570	98.83%	1.012	0.705	0.223	-0.11	13.29	14.00	1.178	0.840	21.5
Back side	802.11ax HE160	114/5570	98.83%	1.012	0.255	0.095	0.07	13.29	14.00	1.178	0.304	21.5
Left side	802.11ax HE160	114/5570	98.83%	1.012	0.060	0.014	0.05	13.29	14.00	1.178	0.072	21.5
Right side	802.11ax HE160	114/5570	98.83%	1.012	0.034	0.011	-0.01	13.29	14.00	1.178	0.041	21.5
Top side	802.11ax HE160	114/5570	98.83%	1.012	0.020	0.004	0.07	13.29	14.00	1.178	0.024	21.5
Bottom side	802.11ax HE160	114/5570	98.83%	1.012	0.067	0.018	0.01	13.29	14.00	1.178	0.080	21.5
Body Test data of U-NII-3 (Separate 0mm)												
Front side	802.11ac VHT80	155/5775	98.78%	1.012	0.624	0.182	-0.12	9.00	10.00	1.259	0.795	21.5
Back side	802.11ac VHT80	155/5775	98.78%	1.012	0.442	0.094	-0.17	9.00	10.00	1.259	0.563	21.5
Left side	802.11ac VHT80	155/5775	98.78%	1.012	0.188	0.045	-0.17	9.00	10.00	1.259	0.240	21.5
Right side	802.11ac VHT80	155/5775	98.78%	1.012	0.133	0.055	-0.17	9.00	10.00	1.259	0.169	21.5
Top side	802.11ac VHT80	155/5775	98.78%	1.012	0.061	0.015	0.08	9.00	10.00	1.259	0.078	21.5
Bottom side	802.11ac VHT80	155/5775	98.78%	1.012	0.206	0.048	0.05	9.00	10.00	1.259	0.262	21.5
Ant2 Test Record chain2												
Test position	Test mode	Test ch./Freq.	Duty Cycle	Duty Cycle Scaled factor	SAR (W/kg) 1-g	SAR (W/kg) 10-g	Power drift (dB)	Conducted Power(dBm)	Tune up Limit(dBm)	Scaled factor	Scaled SAR 1-g (W/kg)	Liquid Temp.(°C)
Body Test data of U-NII-2A (Separate 0mm)												
Front side	802.11ac VHT160	50/5250	98.78%	1.012	0.588	0.193	-0.13	13.01	14.00	1.256	0.747	21.5
Back side	802.11ac VHT160	50/5250	98.78%	1.012	0.442	0.131	0.08	13.01	14.00	1.256	0.562	21.5
Left side	802.11ac VHT160	50/5250	98.78%	1.012	0.069	0.018	-0.09	13.01	14.00	1.256	0.088	21.5
Right side	802.11ac VHT160	50/5250	98.78%	1.012	0.628	0.200	0.18	13.01	14.00	1.256	0.798	21.5
Top side	802.11ac VHT160	50/5250	98.78%	1.012	0.050	0.017	-0.04	13.01	14.00	1.256	0.064	21.5
Bottom side	802.11ac VHT160	50/5250	98.78%	1.012	0.093	0.027	-0.03	13.01	14.00	1.256	0.118	21.5
Body Test data of U-NII-2C (Separate 0mm)												
Front side	802.11ax HE160	114/5570	98.83%	1.012	0.408	0.153	0.12	13.59	14.00	1.099	0.454	21.5
Back side	802.11ax HE160	114/5570	98.83%	1.012	0.439	0.144	-0.07	13.59	14.00	1.099	0.488	21.5
Left side	802.11ax HE160	114/5570	98.83%	1.012	0.039	0.011	0.01	13.59	14.00	1.099	0.043	21.5
Right side	802.11ax HE160	114/5570	98.83%	1.012	0.629	0.198	-0.17	13.59	14.00	1.099	0.700	21.5



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained herein reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
 中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZSAR-TRF-01 Rev. A/2

Report No.: SZCR250900429206

Page: 72 of 80

Top side	802.11ax HE160	114/5570	98.83%	1.012	0.101	0.024	0.17	13.59	14.00	1.099	0.112	21.5
Bottom side	802.11ax HE160	114/5570	98.83%	1.012	0.020	0.011	-0.08	13.59	14.00	1.099	0.022	21.5
Body Test data of U-NII-3 (Separate 0mm)												
Front side	802.11ac VHT80	155/5775	98.78%	1.012	0.312	0.109	0.16	8.65	10.00	1.365	0.431	21.5
Back side	802.11ac VHT80	155/5775	98.78%	1.012	0.385	0.121	0.15	8.65	10.00	1.365	0.532	21.5
Left side	802.11ac VHT80	155/5775	98.78%	1.012	0.196	0.094	-0.03	8.65	10.00	1.365	0.271	21.5
Right side	802.11ac VHT80	155/5775	98.78%	1.012	0.330	0.106	-0.03	8.65	10.00	1.365	0.456	21.5
Top side	802.11ac VHT80	155/5775	98.78%	1.012	0.124	0.073	0.08	8.65	10.00	1.365	0.171	21.5
Bottom side	802.11ac VHT80	155/5775	98.78%	1.012	0.194	0.094	-0.17	8.65	10.00	1.365	0.268	21.5
MIMO Test Record												
Test position	Test mode	Test ch./Freq.	Duty Cycle	Duty Cycle Scaled factor	SAR (W/kg) 1-g	SAR (W/kg) 10-g	Power drift (dB)	Conducted Power(dBm)	Tune up Limit(dBm)	Scaled factor	Scaled SAR 1-g (W/kg)	Liquid Temp.(°C)
Body Test data of U-NII-2A (Separate 0mm)												
Front side	802.11ac VHT160	50/5250	98.78%	1.012	0.737	0.229	-0.06	16.08	17.00	1.237	0.923	21.5
Back side	802.11ac VHT160	50/5250	98.78%	1.012	0.365	0.133	-0.11	16.08	17.00	1.237	0.457	21.5
Left side	802.11ac VHT160	50/5250	98.78%	1.012	0.076	0.052	-0.08	16.08	17.00	1.237	0.095	21.5
Right side	802.11ac VHT160	50/5250	98.78%	1.012	0.608	0.191	-0.12	16.08	17.00	1.237	0.761	21.5
Top side	802.11ac VHT160	50/5250	98.78%	1.012	0.039	0.024	0.12	16.08	17.00	1.237	0.049	21.5
Bottom side	802.11ac VHT160	50/5250	98.78%	1.012	0.053	0.024	0.03	16.08	17.00	1.237	0.066	21.5
Body Test data of U-NII-2C (Separate 0mm)												
Front side	802.11ax HE160	114/5570	98.83%	1.012	0.995	0.272	0.02	16.45	17.00	1.134	1.142	21.5
Back side	802.11ax HE160	114/5570	98.83%	1.012	0.524	0.184	0.03	16.45	17.00	1.134	0.601	21.5
Left side	802.11ax HE160	114/5570	98.83%	1.012	0.075	0.053	-0.05	16.45	17.00	1.134	0.086	21.5
Right side	802.11ax HE160	114/5570	98.83%	1.012	0.613	0.213	0.08	16.45	17.00	1.134	0.703	21.5
Top side	802.11ax HE160	114/5570	98.83%	1.012	0.036	0.020	0.11	16.45	17.00	1.134	0.041	21.5
Bottom side	802.11ax HE160	114/5570	98.83%	1.012	0.052	0.026	0.01	16.45	17.00	1.134	0.060	21.5
Body Test data of U-NII-3 (Separate 0mm)												
Front side	802.11ac VHT80	155/5775	98.78%	1.012	0.550	0.122	0.13	11.84	13.00	1.306	0.727	21.5
Back side	802.11ac VHT80	155/5775	98.78%	1.012	0.300	0.103	0.01	11.84	13.00	1.306	0.397	21.5
Left side	802.11ac VHT80	155/5775	98.78%	1.012	0.242	0.142	-0.15	11.84	13.00	1.306	0.320	21.5
Right side	802.11ac VHT80	155/5775	98.78%	1.012	0.255	0.085	0.17	11.84	13.00	1.306	0.337	21.5
Top side	802.11ac VHT80	155/5775	98.78%	1.012	0.118	0.055	0.12	11.84	13.00	1.306	0.156	21.5
Bottom side	802.11ac VHT80	155/5775	98.78%	1.012	0.200	0.076	0.05	11.84	13.00	1.306	0.264	21.5



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZSAR-TRF-01 Rev. A/2

Report No.: SZCR250900429206

Page: 73 of 80

11.3.3 SAR Result of WiFi 6E

Ant 1 Test Record chain1												
Test position	Test mode	Test ch./Freq.	Duty Cycle	Duty Cycle Scaled factor	SAR (W/kg) 1-g	SAR (W/kg) 10-g	Power drift (dB)	Conducted Power(dBm)	Tune up Limit(dBm)	Scaled factor	Scaled SAR 1-g (W/kg)	Liquid Temp.(°C)
Body Test data of U-NII-5 (Separate 0mm)												
Front side	802.11be EHT320	31/6105	98.78%	1.012	0.497	0.147	-0.16	13.61	14.50	1.227	0.617	21.5
Back side	802.11be EHT320	31/6105	98.78%	1.012	0.245	0.066	-0.19	13.61	14.50	1.227	0.304	21.5
Left side	802.11be EHT320	31/6105	98.78%	1.012	0.043	0.009	-0.05	13.61	14.50	1.227	0.053	21.5
Right side	802.11be EHT320	31/6105	98.78%	1.012	0.040	0.011	0.06	13.61	14.50	1.227	0.050	21.5
Top side	802.11be EHT320	31/6105	98.78%	1.012	0.034	0.010	-0.06	13.61	14.50	1.227	0.042	21.5
Bottom side	802.11be EHT320	31/6105	98.78%	1.012	0.020	0.002	0.02	13.61	14.50	1.227	0.025	21.5
Body Test data of U-NII-6 (Separate 0mm)												
Front side	802.11be EHT320	95/6425	98.78%	1.012	0.252	0.090	-0.08	13.22	14.50	1.343	0.342	21.5
Back side	802.11be EHT320	95/6425	98.78%	1.012	0.251	0.069	-0.11	13.22	14.50	1.343	0.341	21.5
Left side	802.11be EHT320	95/6425	98.78%	1.012	0.055	0.036	-0.18	13.22	14.50	1.343	0.075	21.5
Right side	802.11be EHT320	95/6425	98.78%	1.012	0.063	0.015	-0.14	13.22	14.50	1.343	0.086	21.5
Top side	802.11be EHT320	95/6425	98.78%	1.012	0.047	0.012	-0.03	13.22	14.50	1.343	0.064	21.5
Bottom side	802.11be EHT320	95/6425	98.78%	1.012	0.089	0.246	0.16	13.22	14.50	1.343	0.121	21.5
Body Test data of U-NII-7 (Separate 0mm)												
Front side	802.11be EHT320	127/6585	98.78%	1.012	0.310	0.108	0.09	13.43	14.50	1.279	0.401	21.5
Back side	802.11be EHT320	127/6585	98.78%	1.012	0.182	0.055	0.10	13.43	14.50	1.279	0.236	21.5
Left side	802.11be EHT320	127/6585	98.78%	1.012	0.045	0.028	-0.04	13.43	14.50	1.279	0.058	21.5
Right side	802.11be EHT320	127/6585	98.78%	1.012	0.049	0.029	-0.10	13.43	14.50	1.279	0.063	21.5
Top side	802.11be EHT320	127/6585	98.78%	1.012	0.037	0.015	-0.15	13.43	14.50	1.279	0.048	21.5
Bottom side	802.11be EHT320	127/6585	98.78%	1.012	0.100	0.023	0.06	13.43	14.50	1.279	0.129	21.5
Body Test data of U-NII-8 (Separate 0mm)												
Front side	802.11be EHT320	191/6905	98.78%	1.012	0.573	0.216	-0.03	13.42	14.50	1.282	0.743	21.5
Back side	802.11be EHT320	191/6905	98.78%	1.012	0.145	0.042	-0.17	13.42	14.50	1.282	0.188	21.5
Left side	802.11be EHT320	191/6905	98.78%	1.012	0.060	0.013	0.11	13.42	14.50	1.282	0.078	21.5
Right side	802.11be EHT320	191/6905	98.78%	1.012	0.049	0.018	0.04	13.42	14.50	1.282	0.064	21.5
Top side	802.11be EHT320	191/6905	98.78%	1.012	0.034	0.014	-0.15	13.42	14.50	1.282	0.044	21.5
Bottom side	802.11be EHT320	191/6905	98.78%	1.012	0.072	0.018	0.07	13.42	14.50	1.282	0.093	21.5
Ant2 Test Record chain2												
Test position	Test mode	Test ch./Freq.	Duty Cycle	Duty Cycle Scaled factor	SAR (W/kg) 1-g	SAR (W/kg) 10-g	Power drift (dB)	Conducted Power(dBm)	Tune up Limit(dBm)	Scaled factor	Scaled SAR 1-g (W/kg)	Liquid Temp.(°C)
Body Test data of U-NII-5 (Separate 0mm)												
Front side	802.11be EHT320	63/6265	98.78%	1.012	0.414	0.130	0.11	13.05	14.50	1.396	0.585	21.5
Back side	802.11be EHT320	63/6265	98.78%	1.012	0.323	0.105	0.00	13.05	14.50	1.396	0.456	21.5
Left side	802.11be EHT320	63/6265	98.78%	1.012	0.042	0.018	-0.15	13.05	14.50	1.396	0.059	21.5
Right side	802.11be EHT320	63/6265	98.78%	1.012	0.362	0.109	-0.06	13.05	14.50	1.396	0.511	21.5
Top side	802.11be EHT320	63/6265	98.78%	1.012	0.036	0.016	-0.07	13.05	14.50	1.396	0.051	21.5
Bottom side	802.11be EHT320	63/6265	98.78%	1.012	0.013	0.002	-0.05	13.05	14.50	1.396	0.018	21.5



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
 中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZSAR-TRF-01 Rev. A/2

Report No.: SZCR250900429206

Page: 74 of 80

Body Test data of U-NII-6 (Separate 0mm)												
Front side	802.11be EHT320	95/6425	98.78%	1.012	0.307	0.051	0.07	12.98	14.50	1.419	0.441	21.5
Back side	802.11be EHT320	95/6425	98.78%	1.012	0.118	0.044	0.06	12.98	14.50	1.419	0.169	21.5
Left side	802.11be EHT320	95/6425	98.78%	1.012	0.027	0.014	-0.02	12.98	14.50	1.419	0.039	21.5
Right side	802.11be EHT320	95/6425	98.78%	1.012	0.230	0.077	0.16	12.98	14.50	1.419	0.330	21.5
Top side	802.11be EHT320	95/6425	98.78%	1.012	0.027	0.014	-0.16	12.98	14.50	1.419	0.039	21.5
Bottom side	802.11be EHT320	95/6425	98.78%	1.012	0.011	0.004	-0.12	12.98	14.50	1.419	0.016	21.5
Body Test data of U-NII-7 (Separate 0mm)												
Front side	802.11be EHT320	127/6585	98.78%	1.012	0.545	0.172	-0.12	13.04	14.50	1.400	0.772	21.5
Back side	802.11be EHT320	127/6585	98.78%	1.012	0.272	0.088	-0.18	13.04	14.50	1.400	0.385	21.5
Left side	802.11be EHT320	127/6585	98.78%	1.012	0.055	0.024	-0.03	13.04	14.50	1.400	0.078	21.5
Right side	802.11be EHT320	127/6585	98.78%	1.012	0.498	0.151	-0.03	13.04	14.50	1.400	0.706	21.5
Top side	802.11be EHT320	127/6585	98.78%	1.012	0.071	0.028	0.09	13.04	14.50	1.400	0.101	21.5
Bottom side	802.11be EHT320	127/6585	98.78%	1.012	0.015	0.009	0.07	13.04	14.50	1.400	0.021	21.5
MIMO Test Record												
Test position	Test mode	Test ch./Freq.	Duty Cycle	Duty Cycle Scaled factor	SAR (W/kg) 1-g	SAR (W/kg) 10-g	Power drift (dB)	Conducted Power(dBm)	Tune up Limit(dBm)	Scaled factor	Scaled SAR 1-g (W/kg)	Liquid Temp.(°C)
Body Test data of U-NII-5 (Separate 0mm)												
Front side	802.11be EHT320	63/6265	98.78%	1.012	0.461	0.081	0.02	16.29	17.50	1.323	0.617	21.5
Back side	802.11be EHT320	63/6265	98.78%	1.012	0.194	0.066	0.09	16.29	17.50	1.323	0.260	21.5
Left side	802.11be EHT320	63/6265	98.78%	1.012	0.043	0.026	-0.18	16.29	17.50	1.323	0.058	21.5
Right side	802.11be EHT320	63/6265	98.78%	1.012	0.385	0.108	0.10	16.29	17.50	1.323	0.515	21.5
Top side	802.11be EHT320	63/6265	98.78%	1.012	0.036	0.014	-0.19	16.29	17.50	1.323	0.048	21.5
Bottom side	802.11be EHT320	63/6265	98.78%	1.012	0.041	0.023	-0.19	16.29	17.50	1.323	0.055	21.5
Body Test data of U-NII-6 (Separate 0mm)												
Front side	802.11be EHT320	95/6425	98.78%	1.012	0.319	0.065	0.08	16.11	17.50	1.377	0.445	21.5
Back side	802.11be EHT320	95/6425	98.78%	1.012	0.134	0.048	-0.01	16.11	17.50	1.377	0.187	21.5
Left side	802.11be EHT320	95/6425	98.78%	1.012	0.036	0.020	-0.09	16.11	17.50	1.377	0.050	21.5
Right side	802.11be EHT320	95/6425	98.78%	1.012	0.301	0.084	0.15	16.11	17.50	1.377	0.419	21.5
Top side	802.11be EHT320	95/6425	98.78%	1.012	0.022	0.014	0.12	16.11	17.50	1.377	0.031	21.5
Bottom side	802.11be EHT320	95/6425	98.78%	1.012	0.026	0.022	0.03	16.11	17.50	1.377	0.036	21.5
Body Test data of U-NII-7 (Separate 0mm)												
Front side	802.11be EHT320	127/6585	98.78%	1.012	0.586	0.198	0.10	16.25	17.50	1.334	0.791	21.5
Back side	802.11be EHT320	127/6585	98.78%	1.012	0.137	0.043	0.10	16.25	17.50	1.334	0.185	21.5
Left side	802.11be EHT320	127/6585	98.78%	1.012	0.056	0.037	0.09	16.25	17.50	1.334	0.076	21.5
Right side	802.11be EHT320	127/6585	98.78%	1.012	0.195	0.063	0.16	16.25	17.50	1.334	0.263	21.5



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch (Shenzhen) Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained herein reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZSAR-TRF-01 Rev. A/2

Report No.: SZCR250900429206

Page: 75 of 80

Top side	802.11be EHT320	127/6585	98.78%	1.012	0.040	0.025	0.00	16.25	17.50	1.334	0.054	21.5
Bottom side	802.11be EHT320	127/6585	98.78%	1.012	0.046	0.032	-0.08	16.25	17.50	1.334	0.062	21.5
Body Test data of U-NII-8 (Separate 0mm)												
Front side	802.11be EHT320	191/6905	98.78%	1.012	1.120	0.331	0.04	16.25	17.50	1.332	1.510	21.5
Back side	802.11be EHT320	191/6905	98.78%	1.012	0.245	0.076	0.10	16.25	17.50	1.332	0.330	21.5
Left side	802.11be EHT320	191/6905	98.78%	1.012	0.089	0.064	0.00	16.25	17.50	1.332	0.120	21.5
Right side	802.11be EHT320	191/6905	98.78%	1.012	0.197	0.060	0.06	16.25	17.50	1.332	0.266	21.5
Top side	802.11be EHT320	191/6905	98.78%	1.012	0.066	0.037	-0.01	16.25	17.50	1.332	0.089	21.5
Bottom side	802.11be EHT320	191/6905	98.78%	1.012	0.071	0.042	-0.15	16.25	17.50	1.332	0.096	21.5



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 83071443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Inspection & Testing Services Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZSAR-TRF-01 Rev. A/2

Report No.: SZCR250900429206

Page: 76 of 80

11.3.4 SAR Result of BT

Ant1 Test Record												
Test position	Test mode	Test ch./Freq.	Duty Cycle	Duty Cycle Scaled factor	SAR (W/kg) 1-g	SAR (W/kg) 10-g	Power drift (dB)	Conducted Power(dBm)	Tune up Limit(dBm)	Scaled factor	Scaled SAR 1-g (W/kg)	Liquid Temp.(°C)
Body Test data (Separate 0mm)												
Front side	DH5	78/2480	76.75%	1.303	0.375	0.180	-0.11	15.01	15.00	0.998	0.488	21.5
Back side	DH5	78/2480	76.75%	1.303	0.335	0.167	0.16	15.01	15.00	0.998	0.436	21.5
Left side	DH5	78/2480	76.75%	1.303	0.086	0.048	0.15	15.01	15.00	0.998	0.112	21.5
Right side	DH5	78/2480	76.75%	1.303	0.039	0.021	-0.04	15.01	15.00	0.998	0.051	21.5
Top side	DH5	78/2480	76.75%	1.303	0.026	0.004	-0.01	15.01	15.00	0.998	0.034	21.5
Bottom side	DH5	78/2480	76.75%	1.303	0.040	0.018	-0.11	15.01	15.00	0.998	0.052	21.5
Front side	DH5	0/2402	76.75%	1.303	0.441	0.229	-0.10	14.32	15.00	1.169	0.672	21.5
Front side	DH5	39/2441	76.75%	1.303	0.490	0.251	-0.08	14.66	15.00	1.081	0.690	21.5



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.ssgsgroup.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

11.4 Measurement of PD Data

11.4.1 PD Result of WiFi 6E

Test position	Test mode	Test ch./Freq.	Distance (mm)	Grid Step (λ)	Duty Cycle	Duty Cycle Scaled factor	iPDn	iPD ratio	Measured PD 4cm ² (W/m ²)	Power drift (dB)	Conducted Power(dBm)	Tune up Limit(dBm)	Scaling Factor for measurement uncertainty	Tune up Scaled factor	Scaled PD 4cm ² (W/m ²)
Power Density Test DATA															
Front side	802.11be EHT320	191/6905	2	0.0625	98.78%	1.012	13.30	0.86	0.56	0.00	16.25	17.50	1.5493	1.334	1.161
Front side	802.11be EHT320	191/6905	8.7	0.0625	98.78%	1.012	10.91		0.15	0.04	16.25	17.50	1.5493	1.334	0.320
Back side	802.11be EHT320	191/6905	2	0.0625	98.78%	1.012	/	/	0.25	0.01	16.25	17.50	1.5493	1.334	0.523
Left side	802.11be EHT320	191/6905	2	0.0625	98.78%	1.012	/	/	0.09	-0.12	16.25	17.50	1.5493	1.334	0.188
Right side	802.11be EHT320	191/6905	2	0.0625	98.78%	1.012	/	/	0.18	-0.16	16.25	17.50	1.5493	1.334	0.376
Top side	802.11be EHT320	191/6905	2	0.0625	98.78%	1.012	/	/	0.14	0.08	16.25	17.50	1.5493	1.334	0.293
Bottom side	802.11be EHT320	191/6905	2	0.0625	98.78%	1.012	/	/	0.13	0.05	16.25	17.50	1.5493	1.334	0.272
Front side	802.11be EHT160	207/6985	2	0.0625	98.78%	1.012	/	/	0.42	0.01	16.43	17.50	1.5493	1.279	0.842
Front side	802.11be EHT320	63/6265	2	0.0625	98.78%	1.012	/	/	0.39	0.07	16.29	17.50	1.5493	1.321	0.808
Front side	802.11be EHT320	95/6425	2	0.0625	98.78%	1.012	/	/	0.44	-0.04	16.11	17.50	1.5493	1.377	0.950
Front side	802.11be EHT320	127/6585	2	0.0625	98.78%	1.012	/	/	0.47	0.03	16.25	17.50	1.5493	1.334	0.983

11.5 Multiple Transmitter Evaluation

11.5.1 Simultaneous SAR test evaluation

No.	Simultaneous Tx Combination	Body
1	WLAN 2.4GHz Main(Ant2) + BT Aux(Ant1)	Yes
2	WLAN 2.4GHz Main(Ant2) + WLAN 2.4GHz Aux(Ant1)	Yes
3	WLAN 5GHz Main(Ant2) + BT Aux(Ant1)	Yes
4	WLAN 5GHz Main(Ant2) + WLAN 5GHZ Aux(Ant1)	Yes
5	WLAN 6GHz Main(Ant2) + BT Aux(Ant1)	Yes
6	WLAN 6GHz Main(Ant2) + WLAN 6GHz Aux(Ant1)	Yes

11.5.2 Simultaneous Transmission SAR Summation Scenario

Sum_0mm:

Test position		SARmax (W/kg)							Summed SAR					
		WiFi 2.4G Ant1	WiFi 2.4G Ant2	WiFi 5G Ant1	WiFi 5G Ant2	WiFi 6E Ant1	WiFi 6E Ant2	BT						
		1	2	3	4	5	6	7	2+7	1+2	4+7	3+4	6+7	5+6
WIFI	Front side	0.903	0.560	0.840	0.747	0.743	0.772	0.690	1.250	1.463	1.437	1.587	1.462	1.515
	Back side	0.829	0.508	0.563	0.562	0.341	0.456	0.436	0.944	1.337	0.998	1.125	0.892	0.797
	Left side	0.076	0.023	0.240	0.271	0.743	0.114	0.112	0.135	0.099	0.383	0.511	0.226	0.857
	Right side	0.081	0.326	0.169	0.798	0.341	0.706	0.051	0.377	0.407	0.849	0.967	0.757	1.047
	Top side	0.045	0.115	0.078	0.171	0.341	0.101	0.034	0.149	0.160	0.205	0.249	0.135	0.442
	Bottom side	0.046	0.050	0.262	0.268	0.129	0.093	0.052	0.102	0.096	0.320	0.530	0.145	0.222

12 Equipment list

Test Platform		SPEAG DASY Professional				
Software Reference		cDASY8 V16.4.0.5005				
Hardware Reference						
Equipment		Manufacturer	Model	Inventory No.	Calibration Date	Due date of calibration
☒	Test Phantom	SPEAG	ELI	SZ-WSR-A-028	NCR	NCR
☒	DAE	SPEAG	DAE4ip	SZ-WSR-M-074	2025/08/15	2026/08/14
☒	E-Field Probe	SPEAG	EX3DV4	SZ-WSR-M-075	2025/10/14	2026/10/13
☒	Validation Kits	SPEAG	D2450V2	SZ-WSR-M-039	2025/10/15	2028/10/14
☒	Validation Kits	SPEAG	D5GHzV2	SZ-WSR-M-046	2025/10/14	2028/10/13
☒	Validation Kits	SPEAG	D6.5GHzV2	SZ-WSR-M-080	2023/09/11	2026/09/10
☒	Dielectric parameter probes	SPEAG	DAKS-3.5	SZ-WSR-M-053	2025/06/15	2026/06/14
☒	Vector Network Analyzer and Vector Reflectometer	SPEAG	DAKS_VNA R140	SZ-WSR-M-054	2025/6/15	2026/6/14
☒	Radio Communication Analyzer	Anritsu	MT8820C	SZ-WSR-M-005	2025/01/08	2026/01/07
☒	RF Bi-Directional Coupler	Agilent	86205-60001	SZ-WSR-A-004	NCR	NCR
☒	Signal Generator	Agilent	N5171B	SZ-WSR-M-006	2025/01/07	2026/01/06
☒	Preamplifier	Mini-Circuits	ZHL-42W	SZ-WSR-A-001	NCR	NCR
☒	Preamplifier	Compliance Directions Systems Inc.	AMP28-3W	SZ-WSR-A-002	NCR	NCR
☒	Power Meter	Agilent	E4416A	SZ-WSR-M-007	2025/01/07	2026/01/06
☒	Power Sensor	Agilent	8481H	SZ-WSR-M-008	2025/01/07	2026/01/06
☒	Power Sensor	R&S	NRP-Z92	SZ-WSR-M-009	2025/01/08	2026/01/07
☒	Attenuator	SHX	TS2-3dB	SZ-WSR-A-012	NCR	NCR
☒	Speed reading thermometer	Zhengzhou Boyang Instrument	TP3001	SZ-WSR-M-014	2025/05/19	2026/05/18
☒	Humidity and Temperature Indicator	CHIGAO	HTC-1	SZ-WSR-M-013	2025/5/19	2026/5/18

Note: All the equipment are within the valid period when the tests are performed.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

13 Calibration certificate

Please see the Appendix C

14 Photographs

Please see the Appendix D

Appendix A: Detailed System Check Results

Appendix B: Detailed Test Results

Appendix C: Calibration certificate

Appendix D: Photographs

--- End of report ---