

Appendix 5

RF Exposure Information

FCC ID: YFA370401008

IC: 12260A-370401008

Model number: 370401008

Maximum transmitter power:

Frequency (MHz)	Maximum peak output power (dBuV/m)	Output power (mW)
2410	100.24	3.1705
2440	100.56	3.4129
2470	98.89	2.3234

For FCC

According to KDB 447498 D01:

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances* ≤50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$

- for 1-g SAR and ≤7.5 for 10-g extremity SAR, where
- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2

Result:

$$(3.1705/5) \cdot \sqrt{2.410} = 0.984 < 3.0$$

$$(3.4129/5) \cdot \sqrt{2.440} = 1.066 < 3.0$$

$$(2.3234/5) \cdot \sqrt{2.470} = 0.730 < 3.0$$

Conclusion:

No SAR is required.

For ISED

According to table 1 in RSS-102 Issue 5, below exemption limit at separation distance of ≤ 5mm is applied:

Frequency (MHz)	Exemption limits (mW, by linear interpolation)
2410	4.218
2440	4.055
2470	3.962

Conclusion:

The maximum peak output power of the transmitter is less than the SAR evaluation exemption threshold and hence it complies with the RSS-102 RF exposure requirement without SAR evaluation.