

Appendix 5

RF Exposure Information

Maximum transmitter power:

Frequency (MHz)	Maximum peak output power (dBm)	Output power (mW)
2407	1.79	1.510
2442	0.92	1.236
2478	1.18	1.312

For FCC

According to KDB 447498 D01:

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances* ≤50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤7.5 for 10-g extremity SAR, where

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

Result:

$$(1.510/5) \cdot \sqrt{2.407} = 0.468 < 3.0$$

$$(1.236/5) \cdot \sqrt{2.442} = 0.386 < 3.0$$

$$(1.312/5) \cdot \sqrt{2.478} = 0.413 < 3.0$$

Conclusion:

No SAR is required.

For IC

According to table 1 in RSS-102 Issue 5, below exemption limit is applied

Frequency: 2450MHz

At separation distance of ≤ 5mm

Exemption limits: 4mW

Results:

max. power of channel = 1.79 dBm = 1.510 mW < 4mW

Conclusion:

The maximum peak output power of the transmitter is less than the SAR evaluation exemption threshold and hence it complies with the RSS-102 RF exposure requirement