

# **Appendix 5**

## **RF Exposure Information**

FCC ID: YFA370410529  
IC ID: 12260A-370410529

**Maximum transmitter power:**

| Frequency<br>(MHz) | Maximum peak output power<br>(dBm) | Output power<br>(mW) |
|--------------------|------------------------------------|----------------------|
| 2420               | 1.87                               | 1.539                |
| 2445               | 4.07                               | 2.553                |
| 2465               | 1.57                               | 1.436                |

Note: The maximum peak field strength was taken from table of “Subclause 15.249(a)/RSS-210 B.10(a) – Field Strength of Fundamental and Harmonics”.

**For FCC**

According to KDB 447498 D01:

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances* ≤50 mm are determined by:

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$$

for 1-g SAR and ≤7.5 for 10-g extremity SAR, where

- f(GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

**Result:**

$$(1.539/5) \cdot \sqrt{2420} = 0.479 < 3.0$$

$$(2.553/5) \cdot \sqrt{2445} = 0.798 < 3.0$$

$$(1.436/5) \cdot \sqrt{2465} = 0.451 < 3.0$$

**Conclusion:**

No SAR is required.

**For ISED**

According to table 1 in RSS-102 Issue 5, below exemption limit is applied

Frequency: 2450MHz

At separation distance of ≤ 5mm

Exemption limits: 4mW

**Results:**

max. power of channel = 2.553mW < 4mW

**Conclusion:**

The maximum peak output power of the transmitter is less than the SAR evaluation exemption threshold and hence it complies with the RSS-102 RF exposure requirement