

Appendix 5

RF Exposure Information

FCC ID: YFA370410531
IC ID: 12260A-370410531

Maximum transmitter power:

Frequency (MHz)	Maximum peak output power (dBm)	Maximum peak output power (mW)	Maximum peak field strength (dBuV/m)
2471	-2.13	0.612	93.1
2475	-2.33	0.584	92.9
2479	-1.73	0.671	93.5

Note: The maximum peak field strength was taken from table of "Subclause 15.249(a)/RSS-210 B.10(a) – Field Strength of Fundamental and Harmonics".

For FCC

According to KDB 447498 D01:

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances* ≤50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤7.5 for 10-g extremity SAR, where

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

Result:

$$(2.760/5) \cdot \sqrt{2.410} = 0.856 < 3.0$$

$$(2.779/5) \cdot \sqrt{2.442} = 0.868 < 3.0$$

$$(2.792/5) \cdot \sqrt{2.473} = 0.878 < 3.0$$

Conclusion:

No SAR is required.

For ISED

According to table 1 in RSS-102 Issue 5, below exemption limit is applied

Frequency: 2450MHz

At separation distance of ≤5mm

Exemption limits: 4mW

Results:

max. power of channel = 0.025mW < 4mW

Conclusion:

The maximum peak output power of the transmitter is less than the SAR evaluation exemption threshold and hence it complies with the RSS-102 RF exposure requirement