

Prüfbericht - Nr.: 14037510 001
Test Report No.:

Seite 1 von 13
Page 1 of 13

Auftraggeber: Stadlbauer Marketing + Vertrieb GmbH
Client: Rennbahn Allee1
5412 Puch, Salzburg
Austria

Gegenstand der Prüfung: Short Range Device - Radio Control Toy Transceiver (2.4GHz)
Test Item:

Bezeichnung: 401010 **Serien-Nr.:** Engineering sample
Identification: 370401010 *Serial No.:*

Wareneingangs-Nr.: A000116170-002, **Eingangsdatum:** 08.10.2014
Receipt No.: A000116170-003 *Date of Receipt:*

Zustand des Prüfgegenstandes bei Anlieferung: Test sample(s) is/are not damaged and
Condition of test item at delivery: suitable for testing.

Prüfört: Hong Kong Productivity Council
Testing Location: HKPC Building, 78 Tat Chee Avenue, Kowloon, Hong Kong


Prüfgrundlage: FCC Part 15 Subpart C
Test Specification: ANSI C63.4-2009

Prüfergebnis: Das vorstehend beschriebene Gerät wurde geprüft und entspricht oben
Test Results: genannter Prüfgrundlage.
The above mentioned product was tested and **passed**.

Prüflaboratorium: TÜV Rheinland Hong Kong Ltd.
Testing Laboratory: 8 - 10/F., Goldin Financial Global Square, 7 Wang Tai Road, Kowloon Bay, Kowloon, Hong Kong

geprüft/ tested by:

kontrolliert/ reviewed by:

17.02.2015	Hugo Wan		17.02.2015	Sharon Li	
<i>Datum</i>	<i>Name/Stellung</i>	<i>Unterschrift</i>	<i>Datum</i>	<i>Name/Stellung</i>	<i>Unterschrift</i>
<i>Date</i>	<i>Name/Position</i>	<i>Signature</i>	<i>Date</i>	<i>Name/Position</i>	<i>Signature</i>

Sonstiges: FCC ID YFA401010
Other Aspects

Abkürzungen:	P(ass) = entspricht Prüfgrundlage	Abbreviations:	P(ass) = passed
F(ail) = entspricht nicht Prüfgrundlage		F(ail) = failed	
N/A = nicht anwendbar		N/A = not applicable	
N/T = nicht getestet		N/T = not tested	

Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens.
This test report relates to the a. m. test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any safety mark on this or similar products.

Table of Content

	Page
Cover Page	1
Table of Content	2
Product information.....	3
Manufacturers declarations	3
Product function and intended use.....	3
Submitted documents.....	3
Independent Operation Modes	4
Related Submittal(s) Grants.....	4
Test Set-up and Operation Mode.....	5
Principle of Configuration Selection	5
Test Operation and Test Software.....	5
Special Accessories and Auxiliary Equipment.....	5
Countermeasures to achieve EMC Compliance.....	5
Test Methodology	6
Radiated Emission	6
Field Strength Calculation.....	6
List of Test and Measurement Instruments.....	7
Results FCC Part 15 – Subpart C	8
Subclause 15.203 – Antenna Information	Pass..... 8
Subclause 15.204 – Antenna Information	Pass..... 8
Subclause 15.207 – Disturbance Voltage on AC Mains.....	N/A..... 8
Subclause 15.205 – Restricted Bands Next to The Band Edge	Pass..... 8
Subclause 15.215 (c) – 20 dB Bandwidth.....	Pass..... 9
Subclause 15.249 (a) – Radiated Emission (Fundamental and Harmonics).....	Pass..... 10
Subclause 15.249 (d) – Spurious Radiated Emissions.....	Pass..... 12
Safety Human Exposure – Radio Frequency Exposure Compliance.....	Pass..... 13
Appendix 1 – Test Results.....	8 pages
Appendix 2 – Test Setup Photos.....	2 pages
Appendix 3 – Photo documentation.....	7 pages
Appendix 4 – Product documentation.....	46 pages
Appendix 5 – Radio Frequency Exposure.....	2 pages

Product information

Manufacturers declarations

	Transceiver
Operating frequency range	2405 - 2475 MHz
Type of modulation	GFSK, Frequency Hopping Spread Spectrum
Number of channels	71
Frequency Channel Separation	1MHz
Type of antenna	Wired antenna
Power level	fix
Connection to public utility power line	No
Nominal voltage	V _{nom} : 6.0 V DC (4 x AA size batteries)

Product function and intended use

The equipment under test (EUT) is a radio control toy transmitter operating at 2.4GHz. The EUT is powered by batteries only.

Submitted documents

Circuit Diagram
Block Diagram
Bill of material
User manual
Label Artwork

Independent Operation Modes

The basic operation modes are:

- Radio control to the receiver toy.

For further information refer to User Manual

Related Submittal(s) Grants

This is a single application for certification of the transmitter.

Test Set-up and Operation Mode

Principle of Configuration Selection

Emission: The EUT was configured to measure its highest possible radiation level. The test modes were adapted accordingly in reference to the instructions for use.

Test Operation and Test Software

Test mode transmitter was provided by client with following arrangement:

- 1) Fixed channel transmission was set by the specific operation of the EUT.
- 2) The following channels were tested
 - Lo: 2405MHz
 - Mid: 2445MHz
 - Hi: 2475MHz

Special Accessories and Auxiliary Equipment

The product has been tested together with the following additional accessories:

- none

Countermeasures to achieve EMC Compliance

- none

Test Methodology

Radiated Emission

The radiated emission measurements were performed according to the procedures in ANSI C63.4-2009.

The equipment under test (EUT) was placed at the middle of the 80 cm height turntable, and the turntable is 3 meters far from the measuring antenna. During the testing, the EUT was operated standalone and arranged for maximum emissions. The EUT was tested in three orthogonal planes.

The investigation is performed with the EUT rotated 360 °, the antenna height scanned between 1m and 4m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations. Repeat the measurement steps until the maximum emissions were obtained.

All radiated tests were performed at an antenna to EUT with 3 meters distance, unless stated otherwise in particular parts of this test report.

Field Strength Calculation

The field strength at 3 m was established by adding the meter reading of the spectrum analyzer to the factors associated with antenna correction factor, cable loss, preamplifiers and filter attenuation.

The equation is expressed as follow:

$$FS = R + AF + CF + FA - PA$$

Where FS = Field Strength in dBuV/m at 3 meters.
R = Reading of Spectrum Analyzer in dBuV.
AF = Antenna Factor in dB.
CF = Cable Attenuation Factor in dB.
FA = Filter Attenuation Factor in dB.
PA = Preamplifier Factor in dB.

FA and PA are only be used for the measuring frequency above 1 GHz.

List of Test and Measurement Instruments

Global United Technology Services Co., Ltd. (FCC Registration number: 600491)

Radiated Emission

Equipment	Manufacturer	Type	S/N	Cal. Date	Cal. Due Date
3m Semi- Anechoic Chamber	ZhongYu Electron	9.0(L)*6.0(W)* 6.0(H)	--	06 Apr 2013	05 Apr 2015
Control Room	ZhongYu Electron	6.2(L)*2.5(W)* 2.4(H)	--	N/A	N/A
ESU EMI Test Receiver	R&S	ESU26	--	27 Jun 2014	27 Jun 2015
Loop Antenna	Zhinan	ZN30900A	--	27 Jun 2014	27 Jun 2015
Bi-log Hybrid Antenna	SCHWARZBECK	VULB9163	--	09 Mar 2014	08 Mar 2015
Double-ridged horn antenna	SCHWARZBECK	9120D	--	09 Mar 2014	08 Mar 2015
Horn Antenna	ETS-LINDGREN	3160-09	--	09 Mar 2014	08 Mar 2015
RF Amplifier	HP	8347A	--	27 Jun 2014	27 Jun 2015
RF Amplifier	HP	8349B	--	27 Jun 2014	27 Jun 2015
EMI Test Software	AUDIX	E3	--	N/A	N/A
Coaxial cable	GTS	N/A	--	27 Jun 2014	27 Jun 2015
Coaxial Cable	GTS	N/A	--	27 Jun 2014	27 Jun 2015
Thermo meter	N/A	N/A	--	27 Jun 2014	27 Jun 2015
Spectrum Analyzer	Rohde & Schwarz	FSP30	100007	13 Jan 2015	13 Jan 2016

Results FCC Part 15 – Subpart C

Subclause 15.203 – Antenna Information		Pass
Requirement:	No antenna other than that furnished by the responsible party shall be used with the device	
Results:	Permanent attached antenna	
Verdict:	Pass	

Subclause 15.204 – Antenna Information		Pass
Requirement:	Provide information for every antenna proposed for the use with the EUT	
Results:	a) Antenna type: Wired b) Manufacturer and model no: N/A c) Gain with reference to an isotropic radiator: 2 dBi	
Verdict:	Pass	

Subclause 15.207 – Disturbance Voltage on AC Mains		N/A
Results:	The EUT does not have AC mains input/output port and hence this test is not applicable.	

Subclause 15.205 – Restricted Bands Next to The Band Edge		Pass
Test Specification : ANSI C63.4 – 2009 Mode of operation : Tx mode Port of testing : Enclosure Detector : Peak RBW/VBW : 1 MHz / 3 MHz Supply voltage : 6.0VDC, 4x1.5V AA size new battery Temperature : 23°C Humidity : 50%		
Requirement	: Radiated emissions which fall in the restricted bands, as defined in 15.205 (a), must also comply with the radiated emission limits specified in 15.209(a).	
Results	: The emissions found in the restricted bands were below the limit. For details, please refer to Appendix 1.	

Subclause 15.215 (c) – 20 dB Bandwidth		Pass		
Requirement:	The intentional radiators must be designed to ensure that the 20dB bandwidth of the emission, is contained within the frequency band designated in the rule section under which the equipment is operated.			
Test Specification : ANSI C63.4 – 2009 Mode of operation : Tx mode Port of testing : Temporary antenna port RBW/VBW : 100 kHz / 300 kHz Supply voltage : 6.0VDC, 4x1.5V AA size new battery Temperature : 23°C Humidity : 50%				
Results : For test protocols refer to Appendix 1, page 2-3.				
Frequency (MHz)	20 dB left (MHz)	Limit (MHz)	20 dB right (MHz)	Limit (MHz)
2405	2404.430	> 2400	2406.470	< 2483.5
2445	2443.020	> 2400	2445.630	< 2483.5
2475	2473.700	> 2400	2475.630	< 2483.5

Subclause 15.249 (a) – Radiated Emission (Fundamental and Harmonics)		Pass
Test Specification : ANSI C63.4 – 2009 Mode of operation : Tx mode Port of testing : Enclosure RBW/VBW : 120 kHz / 300 kHz for f < 1 GHz 1 MHz / 3 MHz for f > 1 GHz Supply voltage : 6.0VDC, 4x1.5V AA size new battery Temperature : 23°C Humidity : 50%		
Requirement : The field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following limit.		
Results		
Fundamental Frequency 2405MHz		Vertical Polarization
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m
2405.046	84.46	114.0 / P
2405.046	64.47	94.0 / A
Fundamental Frequency 2405MHz		Horizontal Polarization
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m
2405.046	89.16	114.0 / P
2405.046	68.26	94.0 / A
Harmonics 2405MHz		Vertical Polarization
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m
4809.940	58.93	74.0 / P
4809.940	42.92	54.0 / A
7215.260	56.03	74.0 / P
7215.260	42.23	54.0 / A
Harmonics 2405MHz		Horizontal Polarization
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m
4809.940	59.23	74.0 / P
4809.940	43.15	54.0 / A
7215.260	54.99	74.0 / P
7215.260	41.39	54.0 / A
Fundamental Frequency 2445MHz		Vertical Polarization
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m
2445.166	84.56	114.0 / P
2445.166	63.61	94.0 / A

Fundamental Frequency 2445MHz		Horizontal Polarization	
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m	
2445.166	90.81	114.0 / P	
2445.166	67.15	94.0 / A	
Harmonics 2445MHz		Vertical Polarization	
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m	
4890.110	60.79	74.0 / P	
4890.110	43.52	54.0 / A	
7335.170	56.12	74.0 / P	
7335.170	42.26	54.0 / A	
Harmonics 2445MHz		Horizontal Polarization	
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m	
4890.110	61.22	74.0 / P	
4890.110	44.91	54.0 / A	
7335.170	53.83	74.0 / P	
7335.170	42.32	54.0 / A	
Fundamental Frequency 2475MHz		Vertical Polarization	
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m	
2474.924	86.18	114.0 / P	
2474.924	65.40	94.0 / A	
Fundamental Frequency 2475MHz		Horizontal Polarization	
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m	
2474.924	86.72	114.0 / P	
2474.924	64.42	94.0 / A	
Harmonics 2475MHz		Vertical Polarization	
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m	
4950.100	59.09	74.0 / P	
4950.100	41.19	54.0 / A	
7425.310	57.92	74.0 / P	
7425.310	40.74	54.0 / A	
Harmonics 2475MHz		Horizontal Polarization	
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m	
4950.100	55.75	74.0 / P	
4950.100	39.55	54.0 / A	
7425.310	57.14	74.0 / P	
7425.310	41.69	54.0 / A	

Subclause 15.249 (d) – Spurious Radiated Emissions		Pass
Test Specification : ANSI C63.4 - 2009 Mode of operation : Tx mode Port of testing : Enclosure Detector : Peak RBW/VBW : 120 kHz / 300 kHz for $f < 1$ GHz 1 MHz / 3 MHz for $f > 1$ GHz Supply voltage : 6.0VDC, 4x1.5V AA size new battery Temperature : 23°C Humidity : 50%		
Requirement : Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50dB below the level of the fundamental or to the general radiated emission limits in Section 15.209, whichever is the lesser attenuation.		
Results : All three transmit frequency modes comply with the field strength within the restricted bands. There is no spurious found between 12MHz to 30MHz, of which 12MHz is the lowest oscillating frequency in EUT.		
Tx frequency 2405MHz Vertical Polarization		
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m
No peak found	--	--
Tx frequency 2405MHz Horizontal Polarization		
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m
No peak found	--	--
Tx frequency 2445MHz Vertical Polarization		
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m
No peak found	--	--
Tx frequency 2445MHz Horizontal Polarization		
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m
No peak found	--	--
Tx frequency 2475MHz Vertical Polarization		
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m
No peak found	--	--
Tx frequency 2475MHz Horizontal Polarization		
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m
No peak found	--	--

Safety Human Exposure – Radio Frequency Exposure Compliance	Pass
Please refer to Appendix 5 for details.	