

Produkte
Products

Prüfbericht - Nr.: 14037780 001

Test Report No.:

Seite 1 von 10

Page 1 of 10

Auftraggeber: Stadlbauer Marketing + Vertrieb G.m.b.H
Client: Rennbahn Allee 1
5412 Puch / Salzburg
Austria

Gegenstand der Prüfung: Short Range Device - Radio Control Toy Transmitter (2.4GHz)
Test Item:

Bezeichnung: 401011 **Serien-Nr.:** Engineering sample
Identification: *Serial No.:*

Wareneingangs-Nr.: A000137893-001 **Eingangsdatum:** 01.12.2014
Receipt No.: *Date of Receipt:*

Zustand des Prüfgegenstandes bei Anlieferung: Test sample is not damaged and suitable for testing.
Condition of test item at delivery:

Prüfört: TÜV Rheinland Hong Kong Ltd.
Testing Location: 8/F, First Group Centre, 14 Wang Tai Road, Kowloon Bay, Kowloon, Hong Kong
Global United Technology Services Co., Ltd.
2nd Floor, Block No.2, Laodong Industrial Zone, Xixiang Road, Baoan District, Shenzhen, China

Prüfgrundlage: FCC Part 15 Subpart C
Test Specification: ANSI C63.4-2003

Prüfergebnis: Das vorstehend beschriebene Gerät wurde geprüft und entspricht oben
Test Results: genannter Prüfgrundlage.
The above mentioned product was tested and **passed**.

Prüflaboratorium: TÜV Rheinland Hong Kong Ltd.
Testing Laboratory: 8 - 10/F., Goldin Financial Global Square, 7 Wang Tai Road, Kowloon Bay, Kowloon, Hong Kong

geprüft/ tested by:

kontrolliert/ reviewed by:

05.01.2015 Joey Leung
Datum Name/Stellung
Date Name/Position


Unterschrift
Signature

05.01.2015 Sharon Li
Datum Name/Stellung
Date Name/Position


Unterschrift
Signature

Sonstiges: FCCID: YFA90011
Other Aspects

Abkürzungen: P(ass) = entspricht Prüfgrundlage
F(ail) = entspricht nicht Prüfgrundlage
N/A = nicht anwendbar
N/T = nicht getestet

Abbreviations: P(ass) = passed
F(ail) = failed
N/A = not applicable
N/T = not tested

Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens.
This test report relates to the a. m. test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any safety mark on this or similar products.

Table of Content

	Page
Cover Page	1
Table of Content	2
Product information.....	3
Manufacturers declarations	3
Product function and intended use	3
Submitted documents.....	3
Special accessories and auxiliary equipment	3
Independent Operation Modes	4
Related Submittal(s) Grants	4
List of Test and Measurement Instruments.....	5
Results FCC Part 15 – Subpart C	6
Subclause 15.207 – Disturbance Voltage on AC Mains.....	N/A..... 6
Subclause 15.205 – Band edge compliance of radiated emissions	Pass..... 6
Subclause 15.215 (c) – 20 dB Bandwidth.....	Pass..... 7
Subclause 15.249 (a) – Radiated Emission (Fundamental and Harmonics).....	Pass..... 7
Subclause 15.249 (d) – Spurious Radiated Emissions.....	Pass..... 9
Appendix 1 – Test Results.....	7 pages
Appendix 2 – Test Setup Photos.....	3 pages
Appendix 3 – Photo documentation.....	7 pages
Appendix 4 – Product documentation.....	15 pages
Appendix 5 – RF Exposure Information.....	2 pages

Product information

Manufacturers declarations

	Transmitter
Operating frequency range	2410 - 2470 MHz
Type of modulation	GFSK
Number of channels	61
Type of antenna	Wire Antenna
Power level	fix
Connection to public utility power line	No
Nominal voltage	V _{nom} : 9.0 V

Product function and intended use

The equipment under test (EUT) is a radio control toy transmitter operating at 2.4GHz. It is powered by batteries only.

FCCID: YFA90011

Models	Product description
503003	Radio Controlled Toy Quadcopter

Submitted documents

Circuit Diagram
Block Diagram
Bill of material
User manual
Rating Label

Special accessories and auxiliary equipment

The product has been tested together with the following additional accessory:

Nil

Independent Operation Modes

The basic operation modes are:

- Transmitting control signal for the RC toy quadcopter.

For further information refer to User Manual

Related Submittal(s) Grants

This is a single application for certification of the transmitter.

List of Test and Measurement Instruments

Global United Technology Services Co., Ltd. (Registration number: 600491)

Equipment	Manufacturer	Type	S/N	Cal. Due date
3m Semi- Anechoic Chamber	ZhongYu Electron	9.0(L)*6.0(W)* 6.0(H)	---	05 Apr 2015
Control Room	ZhongYu Electron	6.2(L)*2.5(W)* 2.4(H)	---	N/A
ESU EMI Test Receiver	R&S	ESU26	---	27 Jun 2015
Loop Antenna	Zhinan	ZN30900A	---	27 Jun 2015
Bi-log Hybrid Antenna	SCHWARZBECK	VULB9163	---	08 Mar 2015
Double-ridged horn antenna	SCHWARZBECK	9120D	---	08 Mar 2015
RF Amplifier	HP	8347A	---	27 Jun 2015
RF Amplifier	HP	8349B	---	27 Jun 2015
EMI Test Software	AUDIX	E3	---	N/A
Coaxial cable	GTS	N/A	---	27 Jun 2015
Coaxial Cable	GTS	N/A	---	27 Jun 2015
Thermo meter	N/A	N/A	---	27 Jun 2015
FSP 30 Spectrum Analyzer	Rohde & Schwarz	FSP3	100561	16 Apr 2016

Results FCC Part 15 – Subpart C

Subclause 15.207 – Disturbance Voltage on AC Mains	N/A
There is no AC power input or output ports on the EUT.	

Subclause 15.205 – Band edge compliance of radiated emissions		Pass
Test Specification : ANSI C63.4 – 2003 Mode of operation : Tx mode Port of testing : Enclosure Detector : Peak RBW/VBW : 100 kHz / 300 kHz for f < 1 GHz 1 MHz / 3 MHz for f > 1 GHz Supply voltage : 9.0VDC, 6 x 1.5V AA size new battery Temperature : 23°C Humidity : 50%		
Requirement:	Radiated emissions which fall in the restricted bands, as defined in 15.205 (a), must also comply with the radiated emission limits specified in 15.209(a).	
Results:	For test protocols refer to Appendix 1, page 4-7.	
Tx frequency 2410MHz Vertical Polarization		
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m
No peak found	---	74.0 / P
No peak found	---	54.0 / A
Tx frequency 2410MHz Horizontal Polarization		
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m
No peak found	---	74.0 / P
No peak found	---	54.0 / A
Tx frequency 2470MHz Vertical Polarization		
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m
2487.971	46.25	74.0 / P
2487.971	28.03	54.0 / A
Tx frequency 2470MHz Horizontal Polarization		
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m
2488.038	62.91	74.0 / P
2488.038	34.67	54.0 / A

Subclause 15.215 (c) – 20 dB Bandwidth				Pass
Test Specification : ANSI C63.4 – 2003 Mode of operation : Tx mode Port of testing : Enclosure RBW/VBW : 100 kHz / 300 kHz Supply voltage : 9.0VDC, 6 x 1.5V AA size new battery Temperature : 23°C Humidity : 50%				
Requirement: The intentional radiators must be designed to ensure that the 20dB bandwidth of the emission, is contained within the frequency band designated in the rule section under which the equipment is operated.				
Results: For test protocols refer to Appendix 1, page 2-3.				
Frequency (MHz)	20 dB left (MHz)	Limit (MHz)	20 dB right (MHz)	Limit (MHz)
2410	2407.496	> 2400	2410.956	< 2483.5
2440	2437.400	> 2400	2440.984	< 2483.5
2470	2466.360	> 2400	2471.552	< 2483.5

Subclause 15.249 (a) – Radiated Emission (Fundamental and Harmonics)				Pass
Test Specification : ANSI C63.4 – 2003 Mode of operation : Tx mode Port of testing : Enclosure RBW/VBW : 100 kHz / 300 kHz for f < 1 GHz 1 MHz / 3 MHz for f > 1 GHz Supply voltage : 9.0VDC, 6 x 1.5V AA size new battery Temperature : 23°C Humidity : 50%				
Requirement: The field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following limit.				
Results: PASS				
Fundamental Frequency 2410MHz		Vertical Polarization		
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m		
2409.950	67.17	114.0 / P		
2409.950	36.87	94.0 / A		
Fundamental Frequency 2410MHz		Horizontal Polarization		
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m		
2409.950	74.92	114.0 / P		
2409.950	43.37	94.0 / A		

Harmonics 2410MHz			Vertical Polarization		
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m	Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m
4819.830	45.74	74.0 / P	4819.830	31.15	54.0 / A
Harmonics 2410MHz			Horizontal Polarization		
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m	Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m
4819.830	57.97	74.0 / P	4819.830	35.39	54.0 / A
Fundamental Frequency 2440MHz			Vertical Polarization		
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m	Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m
2440.020	68.91	114.0 / P	2440.020	40.28	94.0 / A
Fundamental Frequency 2440MHz			Horizontal Polarization		
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m	Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m
2440.020	78.38	114.0 / P	2440.020	47.14	94.0 / A
Harmonics 2440MHz			Vertical Polarization		
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m	Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m
4880.000	42.27	74.0 / P	4880.000	27.88	54.0 / A
Harmonics 2440MHz			Horizontal Polarization		
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m	Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m
4880.000	51.74	74.0 / P	4880.000	30.59	54.0 / A
Fundamental Frequency 2470MHz			Vertical Polarization		
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m	Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m
2470.010	69.48	114.0 / P	2470.010	41.81	94.0 / A
Fundamental Frequency 2470MHz			Horizontal Polarization		
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m	Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m
2470.010	78.65	114.0 / P	2470.010	47.64	94.0 / A
Harmonics 2470MHz			Vertical Polarization		
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m	Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m
4940.400	42.57	74.0 / P	4940.400	28.50	54.0 / A

Harmonics 2470MHz		Horizontal Polarization
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m
4940.400	57.58	74.0 / P
4940.400	35.57	54.0 / A

Subclause 15.249 (d) – Spurious Radiated Emissions		Pass
Test Specification : ANSI C63.4 - 2003 Mode of operation : Tx mode Port of testing : Enclosure Detector : Peak RBW/VBW : 100 kHz / 300 kHz for f < 1 GHz 1 MHz / 3 MHz for f > 1 GHz Supply voltage : 9.0VDC, 6 x 1.5V AA size new battery Temperature : 23°C Humidity : 50%		
Requirement:		Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50dB below the level of the fundamental or to the general radiated emission limits in Section 15.209, whichever is the lesser attenuation.
Results:		All three transmit frequency modes comply with the field strength within the restricted bands. There is no spurious found below 30MHz.
Tx frequency 2410MHz		Vertical Polarization
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m
No peak found	---	74.0 / P
No peak found	---	54.0 / A
Tx frequency 2410MHz		Horizontal Polarization
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m
No peak found	---	74.0 / P
No peak found	---	54.0 / A
Tx frequency 2440MHz		Vertical Polarization
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m
No peak found	---	74.0 / P
No peak found	---	54.0 / A
Tx frequency 2440MHz		Horizontal Polarization
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m
No peak found	---	74.0 / P
No peak found	---	54.0 / A

Tx frequency 2470MHz		Vertical Polarization	
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m	
No peak found	---	74.0 / P	
No peak found	---	54.0 / A	
Tx frequency 2470MHz		Horizontal Polarization	
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m	
No peak found	---	74.0 / P	
No peak found	---	54.0 / A	