

TEST REPORT

Application No.: SZCR2510004481AT
Applicant: ACCO Brands USA LLC
Address of Applicant: 4 Corporate Drive, Lake Zurich, 60047, Illinois, United States
Manufacturer: ACCO Brands USA LLC
Address of Manufacturer: 4 Corporate Drive, Lake Zurich, 60047, Illinois, United States
Factory:
 1. Dashine Electronics Co., Ltd
 2. VIET NAM HAI PHONG HOA DAT ELECTRONIC SCIENCE LIMITED COMPANY
 3. Huizhou Dashine Electronics Co Ltd
Address of Factory:
 1. No.53, Guangtian Road, Yanchuan community, Yanluo street, Bao'an District, ShenZhen, China
 2. Kaixia A Village, Guang Zhong Township, Anao County, Hai Phong City, Vietnam
 3. No.19, Weishi Liu Road, Longxi Street, Boluo County, Huizhou City, Guangdong, China
Equipment Under Test (EUT):
EUT Name: PowerA Advantage Wireless Controller for Xbox Series X|S
Model No.: XBGPAWL
Trade Mark: PowerA
FCC ID: YFK-XBGPAWLDA
Standard(s) : 47 CFR Part 15, Subpart C 15.247
Date of Receipt: 2025-10-17
Date of Test: 2025-11-20 to 2025-12-17
Date of Issue: 2026-01-06

Test Result:	Pass*
---------------------	--------------

* In the configuration tested, the EUT complied with the standards specified above.

Keny Xu

Keny Xu
EMC Laboratory Manager



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/2

Report No.: SZCR251000448102

Page: 2 of 71

Revision Record				
Version	Chapter	Date	Modifier	Remark
01		2026-01-06		Original

Authorized for issue by:				
		Tree Zhan		
		Tree Zhan/Project Engineer		
		Eric Fu		
		Eric Fu/Reviewer		



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Testing & Calibration Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

2 Test Summary

Radio Spectrum Technical Requirement				
Item	Standard	Method	Requirement	Result
Antenna Requirement	47 CFR Part 15, Subpart C 15.247	N/A	47 CFR Part 15, Subpart C 15.203 & 15.247(b)(4)	Pass

Radio Spectrum Matter Part				
Item	Standard	Method	Requirement	Result
Conducted Emissions at AC Power Line (150kHz-30MHz)	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2020) Section 6.2	47 CFR Part 15, Subpart C 15.207	Pass
Radiated Emissions which fall in the restricted bands		ANSI C63.10 (2020) Section 6.10.5	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass
Radiated Spurious Emissions Below 1GHz		ANSI C63.10 (2020) Section 6.4,6.5	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass
Radiated Spurious Emissions Above 1GHz		ANSI C63.10 (2020) Section 6.6	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass
Conducted Peak Output Power		ANSI C63.10 (2020) Section 11.9.1	47 CFR Part 15, Subpart C 15.247(b)(3)	Pass
Minimum 6dB Bandwidth		ANSI C63.10 (2020) Section 11.8.1	47 CFR Part 15, Subpart C 15.247a(2)	Pass
Power Spectrum Density		ANSI C63.10 (2020) Section 11.10.2	47 CFR Part 15, Subpart C 15.247(e)	Pass
Conducted Band Edges Measurement		ANSI C63.10 (2020) Section 6.10.4	47 CFR Part 15, Subpart C 15.247(d)	Pass
Conducted Spurious Emissions		ANSI C63.10 (2020) Section 11.11	47 CFR Part 15, Subpart C 15.247(d)	Pass



3 Contents

	Page
1 Cover Page	1
2 Test Summary	3
3 Contents	4
4 General Information	6
4.1 Details of E.U.T.	6
4.2 Description of Support Units	6
4.3 Measurement Uncertainty	6
4.4 Test Location	7
4.5 Test Facility	7
4.6 Deviation from Standards	7
4.7 Abnormalities from Standard Conditions	7
5 Equipment List	8
6 Radio Spectrum Technical Requirement	10
6.1 Antenna Requirement	10
6.1.1 Test Requirement:	10
6.1.2 Conclusion	10
6.2 Other requirements Frequency Hopping Spread Spectrum System Hopping Sequence	11
6.2.1 Test Requirement:	11
6.2.2 Conclusion	11
7 Radio Spectrum Matter Test Results	13
7.1 Conducted Emissions at AC Power Line (150kHz-30MHz)	13
7.1.1 E.U.T. Operation	13
7.1.2 Test Mode Description	13
7.1.3 Test Setup Diagram	14
7.1.4 Measurement Procedure and Data	14
7.2 Radiated Emissions which fall in the restricted bands	17
7.2.1 E.U.T. Operation	17
7.2.2 Test Mode Description	17
7.2.3 Test Setup Diagram	18
7.2.4 Measurement Procedure and Data	19
7.3 Radiated Spurious Emissions Below 1GHz	22
7.3.1 E.U.T. Operation	22
7.3.2 Test Mode Description	22
7.3.3 Test Setup Diagram	23
7.3.4 Measurement Procedure and Data	23
7.4 Radiated Spurious Emissions Above 1GHz	31
7.4.1 E.U.T. Operation	31
7.4.2 Test Mode Description	31
7.4.3 Test Setup Diagram	31



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/2

Report No.: SZCR251000448102

Page: 5 of 71

7.4.4	Measurement Procedure and Data.....	32
7.5	Conducted Peak Output Power.....	39
7.5.1	E.U.T. Operation	39
7.5.2	Test Mode Description	39
7.5.3	Test Setup Diagram	40
7.5.4	Measurement Procedure and Data.....	40
7.6	Minimum 6dB Bandwidth	41
7.6.1	E.U.T. Operation	41
7.6.2	Test Mode Description	41
7.6.3	Test Setup Diagram	41
7.6.4	Measurement Procedure and Data.....	41
7.7	Power Spectrum Density.....	42
7.7.1	E.U.T. Operation	42
7.7.2	Test Mode Description	42
7.7.3	Test Setup Diagram	42
7.7.4	Measurement Procedure and Data.....	42
7.8	Conducted Band Edges Measurement	43
7.8.1	E.U.T. Operation	43
7.8.2	Test Mode Description	43
7.8.3	Test Setup Diagram	44
7.8.4	Measurement Procedure and Data.....	44
7.9	Conducted Spurious Emissions	45
7.9.1	E.U.T. Operation	45
7.9.2	Test Mode Description	45
7.9.3	Test Setup Diagram	46
7.9.4	Measurement Procedure and Data.....	46
8	Test Setup Photo	47
9	EUT Constructional Details (EUT Photos)	47
10	Appendix.....	48



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Testing Center (CCTC) Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

4 General Information

4.1 Details of E.U.T.

Power supply:	Lithium-ion rechargeable battery (DC 3.7V 800mAh) which can be charged from USB-C port.
Cable(s):	USB cable 305cm unshielded
Operation Frequency:	2402MHz to 2480MHz
Modulation Type:	GFSK
Number of Channels:	40
Channel Spacing:	2MHz
Antenna Type:	PCB Antenna
Antenna Gain:	0.38 dBi

Remark: The information in this section is provided by the applicant or manufacturer, SGS is not liable to the accuracy, suitability, reliability or/and integrity of the information.

4.2 Description of Support Units

Description	Manufacturer	Model No.	Serial No.
Adapter	Apple	A1357	REF. No.SEA05A03C
The EUT has been tested as an independent unit.			

4.3 Measurement Uncertainty

Test Item	Measurement Uncertainty
Conducted Emissions at AC Power Line (150kHz-30MHz)	$\pm 3.2\text{dB}$
Radiated Emissions which fall in the restricted bands	$\pm 6.0\text{dB}$ (Below 1GHz); $\pm 4.6\text{dB}$ (Above 1GHz)
Radiated Spurious Emissions Below 1GHz	$\pm 6.0\text{dB}$ for 3m; $\pm 5.0\text{dB}$ for 10m
Radiated Spurious Emissions Above 1GHz	$\pm 4.6\text{dB}$ (1-18GHz); $\pm 4.8\text{dB}$ (18-40GHz)
Conducted Peak Output Power	$\pm 0.4\text{dB}$
Minimum 6dB Bandwidth	$\pm 0.3\%$
Power Spectrum Density	$\pm 0.4\text{dB}$
Conducted Band Edges Measurement	$\pm 2.7\text{dB}$
Conducted Spurious Emissions	$\pm 2.7\text{dB}$

Remark:

The U_{lab} (lab Uncertainty) is less than $U_{\text{CISPR/ETSI}}$ (CISPR/ETSI Uncertainty), so the test results
 – compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
 – non-compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/2

Report No.: SZCR251000448102

Page: 7 of 71

4.4 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China. 518057.

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594

No tests were sub-contracted.

4.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

• A2LA (Certificate No. 3816.01)

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

• VCCI (Member No. 1937)

The 3m Fully-anechoic chamber for above 1GHz, 10m Semi-anechoic chamber for below 1GHz, Shielded Room for Mains Port Conducted Interference Measurement and Telecommunication Port Conducted Interference Measurement of SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen EMC laboratory have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-20026, R-14188, C-12383 and T-11153 respectively.

• FCC –Designation Number: CN1336

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized as an accredited testing laboratory.

Designation Number: CN1336. Test Firm Registration Number: 787754.

• Innovation, Science and Economic Development Canada

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized by ISED as an accredited testing laboratory.

CAB identifier: CN0006.

IC#: 4620C.

4.6 Deviation from Standards

None

4.7 Abnormalities from Standard Conditions

None



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch EMC Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

5 Equipment List

Conducted Emissions at AC Power Line (150kHz-30MHz)					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
Shielding Room	ZhongYu Electron	GB-88	SEM001-06	2025-05-07	2028-05-06
EMI Test Receiver	Rohde&Schwarz	ESR	SZ-WRG-M-047	2025-01-08	2026-01-07
Measurement Software	AUDIX	e3 V8.2014-6-27a	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM024-01	2025-07-05	2026-07-04
LISN	Rohde&Schwarz	ENV216	SEM007-01	2025-07-25	2026-07-24
LISN	ETS-LINDGREN	3816/2	SEM007-02	2025-03-03	2026-03-02

Radiated Emissions which fall in the restricted bands					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
3m Fully-Anechoic Chamber	AUDIX	N/A	SEM001-02	2025-05-07	2028-05-06
Signal Analyzer	Rohde & Schwarz	FSV40	SEM008-04	2025-03-04	2026-03-03
Horn Antenna	Rohde&Schwarz	HF907	SEM003-07	2025-07-22	2026-07-21
Microwave system amplifier	Agilent	83017A	SEM005-25	2025-09-10	2026-09-09
Measurement Software	AUDIX	e3 V8.2014-6-27	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM026-01	2025-07-05	2026-07-04
Broad-Band Horn Antenna	Schwarzbeck	BBHA 9170	SEM003-15	2025-07-22	2027-07-21
Pre-Amplifier	Compliance Directions Systems Inc.	PAP-2640-50	SEM005-08	2025-03-21	2026-03-20

Radiated Spurious Emissions Below 1GHz					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
10m Semi-Anechoic Chamber	SAEMC	FSAC1018	SEM001-03	2025-03-21	2026-03-20
MXE EMI receiver	KEYSIGHT	N9038A	SEM004-16	2025-07-25	2026-07-24
Trilog-Broadband Antenna	Schwarzbeck	VULB9168	SEM003-18	2025-08-29	2027-08-28
Pre-amplifier	Sonoma Instrument Co	310N	SEM005-04	2025-03-04	2026-03-03
Loop Antenna	ETS-Lindgren	6502	SEM003-08	2025-11-17	2027-11-16
Measurement Software	AUDIX	e3 V8.2014-6-27	N/A	N/A	N/A



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/2

Report No.: SZCR251000448102

Page: 9 of 71

Coaxial Cable	SGS	N/A	SEM029-01	2025-07-05	2026-07-04
---------------	-----	-----	-----------	------------	------------

Radiated Spurious Emissions Above 1GHz

Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
3m Fully-Anechoic Chamber	AUDIX	N/A	SEM001-02	2025-05-07	2028-05-06
Signal Analyzer	Rohde & Schwarz	FSV40	SEM008-04	2025-03-04	2026-03-03
Horn Antenna	Rohde&Schwarz	HF907	SEM003-07	2025-07-22	2026-07-21
Microwave system amplifier	Agilent	83017A	SEM005-25	2025-09-10	2026-09-09
Measurement Software	AUDIX	e3 V8.2014-6-27	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM026-01	2025-07-05	2026-07-04
Broad-Band Horn Antenna	Schwarzbeck	BBHA 9170	SEM003-15	2025-07-22	2027-07-21
Pre-Amplifier	Compliance Directions Systems Inc.	PAP-2640-50	SEM005-08	2025-03-21	2026-03-20

RF Conducted Test

Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
Power Sensor	TST PASS	TSPS2023R	SEM009-26	2025-03-04	2026-03-03
Power Sensor	KEYSIGHT	U2021XA	SEM009-16	2025-03-04	2026-03-03
DC Power Supply	Chroma	62012P-80-60	SEM011-11	2025-07-24	2026-07-23
MXA Signal Analyzer	KEYSIGHT	N9020A	SEM004-19	2025-03-04	2026-03-03
Measurement Software	TST PASS	TST PASS V2.0	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM031-01	2025-07-05	2026-07-04
Attenuator	Huber+Suhner	6620_SMA-50-1	SEM021-09	2025-03-03	2026-03-02

General used equipment

Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
Humidity/ Temperature Indicator	deli	8838	SEM002-32	2025-07-23	2026-07-22
Humidity/ Temperature Indicator	deli	8838	SEM002-33	2025-07-23	2026-07-22
Barometer	Changchun Meteorological Industry Factory	DYM3	SEM002-01	2025-03-03	2026-03-02



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Inspection & Testing Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

6 Radio Spectrum Technical Requirement

6.1 Antenna Requirement

6.1.1 Test Requirement:

47 CFR Part 15, Subpart C 15.203 & 15.247(b)(4)

6.1.2 Conclusion

15.203 requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

EUT Antenna:

The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is 0.38dBi.

Antenna location: Refer to internal photos



6.2 Other requirements Frequency Hopping Spread Spectrum System Hopping Sequence

6.2.1 Test Requirement:

47 CFR Part 15, Subpart C 15.247(a)(1),(g),(h)

6.2.2 Conclusion

Standard Requirement:

The system shall hop to channel frequencies that are selected at the system hopping rate from a Pseudorandom ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

Frequency hopping spread spectrum systems are not required to employ all available hopping channels during each transmission. However, the system, consisting of both the transmitter and the receiver, must be designed to comply with all of the regulations in this section should the transmitter be presented with a continuous data (or information) stream. In addition, a system employing short transmission bursts must comply with the definition of a frequency hopping system and must distribute its transmissions over the minimum number of hopping channels specified in this section.

The incorporation of intelligence within a frequency hopping spread spectrum system that permits the system to recognize other users within the spectrum band so that it individually and independently chooses and adapts its hopsets to avoid hopping on occupied channels is permitted. The coordination of frequency hopping systems in any other manner for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters is not permitted.

Compliance for section 15.247(a)(1):

According to Technical Specification, the pseudorandom sequence may be generated in a nine-stage shift register whose 5th and 9th stage outputs are added in a modulo-two addition stage. And the result is fed back to the input of the first stage. The sequence begins with the first ONE of 9 consecutive ONES; i.e. the shift register is initialized with nine ones.

> Number of shift register stages: 9

> Length of pseudo-random sequence: $2^9 - 1 = 511$ bits

> Longest sequence of zeros: 8 (non-inverted signal)

Linear Feedback Shift Register for Generation of the PRBS sequence

An example of Pseudorandom Frequency Hopping Sequence as follow:

Each frequency used equally on the average by each transmitter.

According to Technical Specification, the receivers are designed to have input and IF bandwidths that match the hopping channel bandwidths of any transmitters and shift frequencies in synchronization with the transmitted signals.

Compliance for section 15.247(g):

According to Technical Specification, the system transmits the packet with the pseudorandom hopping frequency with a continuous data and the short burst transmission from the Bluetooth system is also transmitted under the frequency hopping system with the pseudorandom hopping frequency system.



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/2

Report No.: SZCR251000448102

Page: 12 of 71

Compliance for section 15.247(h):

According to Technical specification, the system incorporates with an adaptive system to detect other user within the spectrum band so that it individually and independently to avoid hopping on the occupied channels.

The system is designed not have the ability to coordinated with other FHSS System in an effort to avoid the simultaneous occupancy of individual hopping frequencies by multiple transmitter.



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Testing & Calibration Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

7 Radio Spectrum Matter Test Results

7.1 Conducted Emissions at AC Power Line (150kHz-30MHz)

Test Requirement 47 CFR Part 15, Subpart C 15.207
 Test Method: ANSI C63.10 (2020) Section 6.2
 Test Engineer: Mason Wu

Limit:

Frequency of emission(MHz)	Conducted limit(dBμV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50
*Decreases with the logarithm of the frequency.		
Detector: Peak for pre-scan (9kHz resolution bandwidth) 0.15M to 30MHz		

7.1.1 E.U.T. Operation

Operating Environment:


Temperature: 25.3 °C Humidity: 40.5 % RH Atmospheric Pressure: 1020 mbar

7.1.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	06	TX mode(1Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Pre-scan	07	TX mode(2Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.



7.1.3 Test Setup Diagram



7.1.4 Measurement Procedure and Data

- 1) The mains terminal disturbance voltage test was conducted in a shielded room.
- 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a 50ohm/50μH + 5ohm linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.
- 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane.
- 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.
- 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.

Remark : Level=Read Level+ Cable Loss+ LISN Factor




SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/2

Report No.: SZCR251000448102

Page: 15 of 71

Test Mode: 06; Line: Live line



Site : Shielding Room
Condition: Line
Job No. : 04481AT/04483AT
Test mode: 06

	Freq	Cable Loss	LISN Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB	dBuV	dBuV	dBuV	dB	
1 *	0.1508	0.06	10.19	24.93	35.18	65.96	-30.78	QP
2 *	0.1508	0.06	10.19	12.49	22.74	55.96	-33.22	Average
3	0.3003	0.08	9.85	11.48	21.41	60.24	-38.83	QP
4	0.3003	0.08	9.85	2.24	12.17	50.24	-38.07	Average
5	0.9282	0.11	9.59	0.96	10.66	56.00	-45.34	QP
6	0.9282	0.11	9.59	-6.12	3.58	46.00	-42.42	Average
7	1.9284	0.12	9.58	-2.25	7.45	56.00	-48.55	QP
8	1.9284	0.12	9.58	-8.96	0.74	46.00	-45.26	Average
9	4.1137	0.14	9.66	-0.52	9.28	56.00	-46.72	QP
10	4.1137	0.14	9.66	-6.71	3.09	46.00	-42.91	Average
11	7.5258	0.15	9.68	11.61	21.44	60.00	-38.56	QP
12	7.5258	0.15	9.68	3.95	13.78	50.00	-36.22	Average



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Testing Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com


SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/2

Report No.: SZCR251000448102

Page: 16 of 71

Test Mode: 06; Line: Neutral Line



Site : Shielding Room
Condition: Neutral
Job No. : 04481AT/04483AT
Test mode: 06

	Freq	Cable Loss	LISN Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB	dBuV	dBuV	dBuV	dB	
1 *	0.1548	0.06	10.14	25.22	35.42	65.74	-30.32	QP
2 *	0.1548	0.06	10.14	12.42	22.62	55.74	-33.12	Average
3	0.5731	0.10	9.69	10.82	20.61	56.00	-35.39	QP
4	0.5731	0.10	9.69	1.79	11.58	46.00	-34.42	Average
5	0.9233	0.11	9.56	1.11	10.78	56.00	-45.22	QP
6	0.9233	0.11	9.56	-5.54	4.13	46.00	-41.87	Average
7	1.9386	0.12	9.55	-2.59	7.08	56.00	-48.92	QP
8	1.9386	0.12	9.55	-8.79	0.88	46.00	-45.12	Average
9	4.5736	0.14	9.56	-0.64	9.06	56.00	-46.94	QP
10	4.5736	0.14	9.56	-5.99	3.71	46.00	-42.29	Average
11	7.5258	0.15	9.64	11.66	21.45	60.00	-38.55	QP
12	7.5258	0.15	9.64	3.87	13.66	50.00	-36.34	Average



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Testing Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

7.2 Radiated Emissions which fall in the restricted bands

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209
 Test Method: ANSI C63.10 (2020) Section 6.10.5
 Measurement Distance: 3m
 Test Engineer: Logic Wang

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

7.2.1 E.U.T. Operation

Operating Environment:


Temperature: 23.5 °C Humidity: 56.3 % RH Atmospheric Pressure: 1020 mbar

7.2.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	06	TX mode(1Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	07	TX mode(2Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.



7.2.3 Test Setup Diagram



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

7.2.4 Measurement Procedure and Data

- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.

Remark 1: Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor


Remark 2: For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.

Remark 3: The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 3MHz for Peak detection (PK) and Average detection (AV) at frequency above 1GHz.

Remark 4: For fundamental and harmonic signal measurement, the resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is $\geq 1/T$ (Duty cycle $< 98\%$) or 10Hz (Duty cycle $\geq 98\%$) for Average detection (AV) at frequency above 1GHz.




BLE_1M_TX_CH_00_Horizontal



Site : chamber
Condition: 3m HORIZONTAL
Job No : 04481AT\04483AT
Mode : 2402 Band edge
BLE 1M

	Freq	Cable Loss	Factor	Ant Factor	Preamplifier	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB		dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2377.941	16.12	29.10	32.79	37.28	49.71	74.00	-24.29	peak	
2	2390.000	16.13	29.10	32.78	33.05	45.50	74.00	-28.50	peak	
3 p	2402.000	16.15	29.09	32.77	90.61	103.08	74.00	29.08	peak	


BLE_1M_TX_CH_00_Vertical



Site : chamber
Condition: 3m VERTICAL
Job No : 04481AT\04483AT
Mode : 2402 Band edge
BLE 1M

	Freq	Cable Loss	Factor	Ant Factor	Preamplifier	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB		dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2361.971	16.09	29.10	32.79	35.45	47.85	74.00	-26.15	peak	
2	2390.000	16.13	29.10	32.78	34.46	46.91	74.00	-27.09	peak	
3 p	2402.000	16.15	29.09	32.77	87.69	100.16	74.00	26.16	peak	


BLE_1M_TX_CH_39_Horizontal



Site : chamber
Condition: 3m HORIZONTAL
Job No : 04481AT\04483AT
Mode : 2480 Band edge
BLE 1M

	Freq	Cable Loss	Factor	Ant Factor	Preamplifier	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB		dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 p	2480.000	16.27	28.90	32.73	91.55	103.99	74.00	29.99	Peak	
2	2483.500	16.28	28.90	32.73	40.80	53.25	74.00	-20.75	Peak	
3 q	2484.495	16.28	28.90	32.73	30.19	42.64	54.00	-11.36	Average	
4	2484.495	16.28	28.90	32.73	42.00	54.45	74.00	-19.55	Peak	

BLE_1M_TX_CH_39_Vertical




Site : chamber
Condition: 3m VERTICAL
Job No : 04481AT\04483AT
Mode : 2480 Band edge
BLE 1M

	Freq	Cable Loss	Factor	Ant Factor	Preamplifier	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB		dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 p	2480.000	16.27	28.90	32.73	89.56	102.00	74.00	28.00	Peak	
2 q	2483.500	16.28	28.90	32.73	24.28	36.73	54.00	-17.27	Average	
3	2483.500	16.28	28.90	32.73	41.74	54.19	74.00	-19.81	Peak	
4	2483.896	16.28	28.90	32.73	40.93	53.38	74.00	-20.62	Peak	




BLE_2M_TX_CH_00_Horizontal



Site : chamber
Condition: 3m HORIZONTAL
Job No : 04481AT/04483AT
Mode : 2402 Band edge
BLE 2M

	Freq	Cable Loss	Factor	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB		dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2370.495	16.10	29.10	32.79	37.23	49.64	74.00	-24.36	Peak	
2	2390.000	16.13	29.10	32.78	35.42	47.87	74.00	-26.13	Peak	
3 p	2402.000	16.15	29.09	32.77	90.73	103.20	74.00	29.20	Peak	


BLE_2M_TX_CH_00_Vertical



Site : chamber
Condition: 3m VERTICAL
Job No : 04481AT/04483AT
Mode : 2402 Band edge
BLE 2M

	Freq	Cable Loss	Factor	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB		dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2383.995	16.13	29.10	32.78	37.04	49.49	74.00	-24.51	Peak	
2	2390.000	16.13	29.10	32.78	33.31	45.76	74.00	-28.24	Peak	
3 p	2402.000	16.15	29.09	32.77	88.76	101.23	74.00	27.23	Peak	


BLE_2M_TX_CH_39_Horizontal



Site : chamber
Condition: 3m HORIZONTAL
Job No : 04481AT/04483AT
Mode : 2480 Band edge
BLE 2M

	Freq	Cable Loss	Factor	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB		dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 p	2480.000	16.27	28.90	32.73	91.29	103.73	74.00	29.73	Peak	
2 q	2483.500	16.28	28.90	32.73	35.93	48.38	54.00	-5.62	Average	
3	2483.500	16.28	28.90	32.73	44.45	56.90	74.00	-17.10	Peak	
4	2483.821	16.28	28.90	32.73	33.25	45.70	54.00	-8.30	Average	
5	2483.821	16.28	28.90	32.73	42.21	54.66	74.00	-19.34	Peak	

BLE_2M_TX_CH_39_Vertical



Site : chamber
Condition: 3m VERTICAL
Job No : 04481AT/04483AT
Mode : 2480 Band edge
BLE 2M

	Freq	Cable Loss	Factor	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB		dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 p	2480.000	16.27	28.90	32.73	89.19	101.63	74.00	27.63	Peak	
2 q	2483.500	16.28	28.90	32.73	28.95	41.40	54.00	-12.60	Average	
3	2483.500	16.28	28.90	32.73	41.97	54.42	74.00	-19.58	Peak	
4	2483.821	16.28	28.90	32.73	40.83	53.28	74.00	-20.72	Peak	



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/2

Report No.: SZCR251000448102

Page: 22 of 71

7.3 Radiated Spurious Emissions Below 1GHz

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209
 Test Method: ANSI C63.10 (2020) Section 6.4,6.5
 Measurement Distance: 3 or 10m
 Test Engineer: Ted Wu

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
960-1000	500	3

7.3.1 E.U.T. Operation

Operating Environment:

Temperature: 22.6 °C Humidity: 49.3 % RH Atmospheric Pressure: 1020 mbar

7.3.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Pre-scan	06	TX mode(1Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	07	TX mode(2Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.




SGS-CSTC Standards Technical Services Co., Ltd.
 Shenzhen Branch Inspection & Testing Services Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.ssgroup.com.cn
 中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

7.3.3 Test Setup Diagram



7.3.4 Measurement Procedure and Data

- For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 10 meters for frequency above 30MHz, and 3 meter for frequency below 30MHz away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using quasi-peak method as specified and then reported in a data sheet.
- Test the EUT in the lowest channel, the middle channel, the Highest channel.
- The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- Repeat above procedures until all frequencies measured was complete.

Remark:

- Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor
- Scan from 9kHz to 30MHz, the disturbance below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.




SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/2

Report No.: SZCR251000448102

Page: 24 of 71

Test Mode: 07; Polarity: Coaxial



Condition: 3m

Job No. : 04481AT/04483AT

Test Mode: 07

: coaxial

Remark: margin more than 20dB.




SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Testing & Calibration Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Test Mode: 07; Polarity: Coplanar



Condition: 3m

Job No. : 04481AT/04483AT


Test Mode: 07

: coplanar

Remark: margin more than 20dB.



Test Mode: 07; Polarity: Coaxial



Condition: 3m

Job No. : 04481AT/04483AT


Test Mode: 07

: coaxial

Remark: margin more than 20dB.



Test Mode: 07; Polarity: Coplanar



Condition: 3m

Job No. : 04481AT/04483AT

Test Mode: 07

: coplanar

Remark: margin more than 20dB.




SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/2

Report No.: SZCR251000448102

Page: 28 of 71

Test Mode: 07; Polarity: Horizontal



Condition: 10m HORIZONTAL
Job No. : 04481AT/04483AT
Test Mode: 07

	Freq	Read Level	Ant Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	47.994	29.31	17.95	0.24	32.40	15.10	29.50	-14.40	QP
2	148.441	36.28	17.71	0.64	32.50	22.13	33.00	-10.87	QP
3	223.733	33.58	14.42	0.73	32.50	16.23	35.60	-19.37	QP
4	351.708	30.51	18.54	1.34	32.44	17.95	35.60	-17.65	QP
5 pp	771.449	30.21	26.44	2.48	32.48	26.65	35.60	-8.95	QP
6	952.094	27.42	27.96	2.76	31.73	26.41	35.60	-9.19	QP




SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Testing Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Test Mode: 07; Polarity: Vertical



Condition: 10m VERTICAL

Job No. : 04481AT/04483AT

Test Mode: 07

		Read	Ant	Cable	Preamp		Limit	Over	
	Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	pp	36.895	37.97	16.68	0.12	32.40	22.37	29.50	-7.13 QP
2		101.289	37.83	13.36	0.75	32.50	19.44	33.00	-13.56 QP
3		136.460	37.07	16.80	0.66	32.50	22.03	33.00	-10.97 QP
4		351.708	33.93	18.54	1.34	32.44	21.37	35.60	-14.23 QP
5		779.607	30.19	26.46	2.51	32.46	26.70	35.60	-8.90 QP
6		996.500	27.42	28.23	2.85	31.52	26.98	44.40	-17.42 QP



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/2

Report No.: SZCR251000448102

Page: 30 of 71

The test was performed at a 10m test site. According to below formulate and the test data at 10m test distance,

$$L_3 / L_{10} = D_{10} / D_3$$

Note:

L₃: Level @ 3m distance. Unit: uV/m;

L₁₀: Level @ 10m distance. Unit: uV/m;

D₃: 3m distance. Unit: m

D₁₀: 10m distance. Unit: m

The level at 3m test distance is below:

Frequency (MHz)	Level @ 10m (dBuV/m)	Level @ 10m (uV/m)	Level @ 3m (uV/m)	Level @ 3m (dBuV/m)	Limit @ 3m (dBuV/m)	Margin (dB)	Ant. Polarization
47.994	15.10	5.69	18.96	25.56	40	-14.44	H
148.441	22.13	12.78	42.60	32.59	43.5	-10.91	H
223.733	16.23	6.48	21.60	26.69	46	-19.31	H
351.708	17.95	7.90	26.33	28.41	46	-17.59	H
771.449	26.65	21.50	71.68	37.11	46	-8.89	H
952.094	26.41	20.92	69.72	36.87	46	-9.13	H
36.895	22.37	13.14	43.79	32.83	40	-7.17	V
101.289	19.44	9.38	31.25	29.90	43.5	-13.60	V
136.460	22.03	12.63	42.11	32.49	43.5	-11.01	V
351.708	21.37	11.71	39.03	31.83	46	-14.17	V
779.607	26.70	21.63	72.09	37.16	46	-8.84	V
996.500	26.98	22.34	74.45	37.44	54	-16.56	V



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch (SZEMC) Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

7.4 Radiated Spurious Emissions Above 1GHz

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209
 Test Method: ANSI C63.10 (2020) Section 6.6
 Measurement Distance: 1m or 3m
 Test Engineer: Logic Wang

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
Above 1000	500	3

7.4.1 E.U.T. Operation


Operating Environment:

Temperature: 23.5 °C Humidity: 56.3 % RH Atmospheric Pressure: 1020 mbar

7.4.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	06	TX mode(1Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	07	TX mode(2Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.

7.4.3 Test Setup Diagram



7.4.4 Measurement Procedure and Data


- a. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters for frequency above 1GHz, and 1 meter for frequency above 18GHz away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak or average method as specified and then reported in a data sheet.
- g. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- i. Repeat above procedures until all frequencies measured was complete.

Remark:

1. Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor
2. Scan from 18GHz to 10th harmonic of the fundamental frequency or 40 GHz, whichever is lower, the disturbance above 18GHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.
3. As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 3MHz for Peak detection (PK) and Average detection (AV) at frequency above 1GHz.
- 5:For fundamental and harmonic signal measurement, the resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is $\geq 1/T$ (Duty cycle $\leq 98\%$) or 10Hz (Duty cycle $\geq 98\%$) for Average detection (AV) at frequency above 1GHz.




BLE_1M_TX_CH_00_Horizontal



Site : chamber
Condition: 3m HORIZONTAL
Job No : 04481AT/04483AT
Mode : 2402 TX RSE
BLE 1M

Freq	Cable	Ant	Preamp	Read	Level	Limit	Over	Remark
MHz	Loss	Factor	Factor	Level	dBuV	dBuV/m	Line	
	dB	dB/m	dB				dB	
1 4392.376	7.11	34.74	54.26	54.41	42.00	74.00	-32.00	Peak
2 6053.894	8.92	35.01	53.11	53.43	44.25	74.00	-29.75	Peak
3 7280.309	8.50	35.70	53.18	57.75	48.77	74.00	-25.23	Peak
4 11533.480	11.46	37.77	53.11	41.71	37.83	54.00	-16.17	Average
5 11533.480	11.46	37.77	53.11	53.24	49.36	74.00	-24.64	Peak
6 13957.530	10.97	39.62	52.91	52.15	49.83	74.00	-24.17	Peak
7 13957.530	10.97	39.62	52.91	39.33	37.01	54.00	-16.99	Average
8 q16842.290	10.99	43.03	52.73	38.19	39.48	54.00	-14.52	Average
9 p16842.290	10.99	43.03	52.73	51.16	52.45	74.00	-21.55	Peak


BLE_1M_TX_CH_00_Vertical



Site : chamber
Condition: 3m VERTICAL
Job No : 04481AT/04483AT
Mode : 2402 TX RSE
BLE 1M

Freq	Cable	Ant	Preamp	Read	Level	Limit	Over	Remark
MHz	Loss	Factor	Factor	Level	dBuV	dBuV/m	Line	
	dB	dB/m	dB				dB	
1 3196.094	6.01	32.87	54.85	58.62	42.65	74.00	-31.35	Peak
2 7280.309	8.50	35.70	53.18	58.97	49.99	74.00	-24.01	Peak
3 11701.380	11.52	37.90	53.14	51.83	48.11	74.00	-25.89	Peak
4 11701.380	11.52	37.90	53.14	48.02	36.30	54.00	-17.70	Average
5 15003.420	10.40	40.70	52.60	38.97	37.47	54.00	-16.53	Average
6 15003.420	10.40	40.70	52.60	51.82	50.32	74.00	-23.68	Peak
7 q16842.290	10.99	43.03	52.73	38.24	39.53	54.00	-14.47	Average
8 p16842.290	10.99	43.03	52.73	51.18	52.47	74.00	-21.53	Peak


BLE_1M_TX_CH_19_Horizontal



Site : chamber
Condition: 3m HORIZONTAL
Job No : 04481AT/04483AT
Mode : 2440 TX RSE
BLE 1M

Freq	Cable	Ant	Preamp	Read	Level	Limit	Over	Remark
MHz	Loss	Factor	Factor	Level	dBuV	dBuV/m	Line	
	dB	dB/m	dB				dB	
1 3168.500	6.00	32.65	54.87	56.22	40.00	74.00	-34.00	Peak
2 4831.962	7.43	34.43	54.22	54.68	42.32	74.00	-31.68	Peak
3 7326.267	8.46	35.70	53.17	60.71	51.70	74.00	-22.30	Peak
4 11709.210	11.15	37.52	53.02	52.77	48.42	74.00	-25.58	Peak
5 11709.210	11.15	37.52	53.02	40.01	35.66	54.00	-18.34	Average
6 15622.990	10.88	41.12	52.10	38.07	37.97	54.00	-16.03	Average
7 15622.990	10.88	41.12	52.10	50.46	50.36	74.00	-23.64	Peak
8 q17793.090	11.38	43.89	52.50	37.72	40.49	54.00	-13.51	Average
9 p17793.090	11.38	43.89	52.50	50.06	52.83	74.00	-21.17	Peak

BLE_1M_TX_CH_19_Vertical




Site : chamber
Condition: 3m VERTICAL
Job No : 04481AT/04483AT
Mode : 2440 TX RSE
BLE 1M

Freq	Cable	Ant	Preamp	Read	Level	Limit	Over	Remark
MHz	Loss	Factor	Factor	Level	dBuV	dBuV/m	Line	
	dB	dB/m	dB				dB	
1 3376.523	6.12	32.26	54.71	56.64	40.31	74.00	-33.69	Peak
2 6053.894	8.92	35.01	53.11	53.64	44.46	74.00	-29.54	Peak
3 7326.267	8.46	35.70	53.17	60.31	51.30	74.00	-22.70	Peak
4 11709.210	11.55	37.90	53.16	39.25	35.54	54.00	-18.46	Average
5 11709.210	11.55	37.90	53.16	51.81	48.10	74.00	-25.90	Peak
6 15443.410	10.83	41.04	52.24	50.47	50.10	74.00	-23.90	Peak
7 15443.410	10.83	41.04	52.24	38.95	38.58	54.00	-15.42	Average
8 q17639.470	11.28	43.68	52.58	37.15	39.53	54.00	-14.47	Average
9 p17639.470	11.28	43.68	52.58	49.82	52.20	74.00	-21.80	Peak




BLE_1M_TX_CH_39_Horizontal



Site : chamber
Condition: 3m HORIZONTAL
Job No : 04481AT/04483AT
Mode : 2480 TX RSE
BLE 1M

Freq	Cable	Ant	Preamp	Read	Level	Limit	Over	
MHz	Loss	Factor	Factor	Level	dBuV/m	Line	Limit	Remark
	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 4367.058	7.10	34.54	54.26	54.63	42.01	74.00	-31.99	Peak
2 6303.890	8.90	34.99	53.13	53.67	44.43	74.00	-29.57	Peak
3 7432.914	8.43	35.93	53.16	58.46	49.66	74.00	-24.34	Peak
4 11769.210	11.55	37.90	53.16	39.67	35.96	54.00	-18.04	Average
5 11769.210	11.55	37.90	53.16	52.67	48.96	74.00	-25.04	Peak
6 15354.390	10.74	41.00	52.31	50.90	50.33	74.00	-23.67	Peak
7 15354.390	10.74	41.00	52.31	37.97	37.40	54.00	-16.60	Average
8 q17588.560	11.25	43.58	52.60	37.70	39.93	54.00	-14.07	Average
9 p17588.560	11.25	43.58	52.60	50.58	52.81	74.00	-21.19	Peak


BLE_1M_TX_CH_39_Vertical



Site : chamber
Condition: 3m VERTICAL
Job No : 04481AT/04483AT
Mode : 2480 TX RSE
BLE 1M

Freq	Cable	Ant	Preamp	Read	Level	Limit	Over	
MHz	Loss	Factor	Factor	Level	dBuV	dBuV/m	dBuV/m	dB
	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 3186.869	6.01	32.79	54.85	59.21	43.16	74.00	-30.84	Peak
2 6213.441	8.91	34.75	53.12	53.91	44.45	74.00	-29.55	Peak
3 7432.914	8.43	35.93	53.16	55.88	47.08	74.00	-26.92	Peak
4 12044.520	11.63	37.76	53.20	40.98	37.17	54.00	-16.83	Average
5 12044.520	11.63	37.76	53.20	52.66	48.85	74.00	-25.15	Peak
6 15354.390	10.74	41.00	52.31	51.21	50.64	74.00	-23.36	Peak
7 15354.390	10.74	41.00	52.31	38.67	38.10	54.00	-15.90	Average
8 p17741.740	11.35	43.84	52.53	49.61	52.27	74.00	-21.73	Peak
9 q17741.740	11.35	43.84	52.53	36.86	39.52	54.00	-14.48	Average


BLE_2M_TX_CH_00_Horizontal



Site : chamber
Condition: 3m HORIZONTAL
Job No : 04481AT/04483AT
Mode : 2402 TX RSE
BLE 2M

Freq	Cable	Ant	Preamp	Read	Level	Limit	Over	
MHz	Loss	Factor	Factor	Level	dBuV	dBuV/m	dBuV/m	dB
	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 3366.778	6.11	32.20	54.72	56.13	39.72	74.00	-34.28	Peak
2 4888.151	7.48	34.65	54.21	54.33	42.25	74.00	-31.75	Peak
3 7200.309	8.50	35.70	53.18	57.64	48.66	74.00	-25.34	Peak
4 12009.760	11.63	37.79	53.20	39.51	35.73	54.00	-18.27	Average
5 12009.760	11.63	37.79	53.20	52.41	48.63	74.00	-25.37	Peak
6 14575.970	10.43	40.48	52.72	39.74	37.93	54.00	-16.07	Average
7 14575.970	10.43	40.48	52.72	51.53	49.72	74.00	-24.28	Peak
8 q17844.590	11.41	43.90	52.48	38.17	41.00	54.00	-13.00	Average
9 p17844.590	11.41	43.90	52.48	50.02	52.85	74.00	-21.15	Peak

BLE_2M_TX_CH_00_Vertical




Site : chamber
Condition: 3m VERTICAL
Job No : 04481AT/04483AT
Mode : 2402 TX RSE
BLE 2M

Freq	Cable	Ant	Preamp	Read	Level	Limit	Over	
MHz	Loss	Factor	Factor	Level	dBuV	dBuV/m	dBuV/m	dB
	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 3186.869	6.01	32.79	54.85	59.04	42.99	74.00	-31.01	Peak
2 4790.245	7.40	34.22	54.22	56.16	43.56	74.00	-30.44	Peak
3 7200.309	8.50	35.70	53.18	58.75	49.77	74.00	-24.23	Peak
4 13957.530	10.97	39.62	52.91	51.57	49.25	74.00	-24.75	Peak
5 13957.530	10.97	39.62	52.91	38.64	36.32	54.00	-17.68	Average
6 15265.880	10.66	41.00	52.38	39.04	38.32	54.00	-15.68	Average
7 15265.880	10.66	41.00	52.38	51.30	50.58	74.00	-23.42	Peak
8 q17793.090	11.38	43.89	52.50	37.41	40.18	54.00	-13.82	Average
9 p17793.090	11.38	43.89	52.50	50.27	53.04	74.00	-20.96	Peak




BLE_2M_TX_CH_19_Horizontal



Site : chamber
Condition: 3m HORIZONTAL
Job No : 04481AT/04483AT
Mode : 2440 TX RSE

Freq	Cable		Ant		Preamp		Read		Limit		Over	Remark
	Loss	Factor	Factor	Level	Level	Level	Level	Line	Line	Limit		
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dBuV/m	dB	dB	dB		
1 3725.195	6.52	32.95	54.47	56.55	41.55	74.00	-32.45	Peak				
2 5949.811	8.86	34.70	53.15	53.55	43.96	74.00	-30.04	Peak				
3 7326.267	8.46	35.70	53.17	58.38	49.37	74.00	-24.63	Peak				
4 13520.740	10.89	38.82	53.04	40.07	36.74	54.00	-17.26	Average				
5 13520.740	10.89	38.82	53.04	52.47	49.14	74.00	-24.86	Peak				
6 16842.290	10.99	43.03	52.73	38.47	39.76	54.00	-14.24	Average				
7 16842.290	10.99	43.03	52.73	50.82	52.11	74.00	-21.89	Peak				
8 q17639.470	11.28	43.68	52.58	38.66	41.04	54.00	-12.96	Average				
9 p17639.470	11.28	43.68	52.58	50.61	52.99	74.00	-21.01	Peak				


BLE_2M_TX_CH_19_Vertical



Site : chamber
Condition: 3m VERTICAL
Job No : 04481AT/04483AT
Mode : 2440 TX RSE

Freq	Cable		Ant		Preamp		Read		Limit		Over	Remark
	Loss	Factor	Factor	Level	Level	Level	Level	Line	Line	Limit		
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dBuV/m	dB	dB	dB		
1 4354.454	7.09	34.44	54.26	55.04	42.31	74.00	-31.69	Peak				
2 7326.267	8.46	35.70	53.17	57.72	48.71	74.00	-25.29	Peak				
3 9669.164	10.72	37.50	53.33	53.09	47.98	74.00	-26.02	Peak				
4 13957.530	10.97	39.62	52.91	52.21	49.89	74.00	-24.11	Peak				
5 13957.530	10.97	39.62	52.91	40.44	38.12	54.00	-15.88	Average				
6 16793.680	10.99	42.89	52.68	39.18	40.38	54.00	-13.62	Average				
7 16793.680	10.99	42.89	52.68	51.62	52.82	74.00	-21.18	Peak				
8 q17639.470	11.28	43.68	52.58	38.70	41.08	54.00	-12.92	Average				
9 p17639.470	11.28	43.68	52.58	50.51	52.89	74.00	-21.11	Peak				


BLE_2M_TX_CH_39_Horizontal



Site : chamber
Condition: 3m HORIZONTAL
Job No : 04481AT/04483AT
Mode : 2480 TX RSE

Freq	Cable		Ant		Preamp		Read		Limit		Over	Remark
	Loss	Factor	Factor	Level	Level	Level	Level	Line	Line	Limit		
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dBuV/m	dB	dB	dB		
1 4354.454	7.09	34.44	54.26	55.12	42.39	74.00	-31.61	Peak				
2 6071.417	8.92	35.04	53.11	53.16	44.01	74.00	-29.99	Peak				
3 7432.914	8.43	35.93	53.16	58.67	49.87	74.00	-24.13	Peak				
4 10980.470	11.04	37.48	53.00	41.11	36.63	54.00	-17.37	Average				
5 10980.470	11.04	37.48	53.00	52.80	48.32	74.00	-25.68	Peak				
6 13957.530	10.97	39.62	52.91	51.12	48.80	74.00	-25.20	Peak				
7 13957.530	10.97	39.62	52.91	38.45	36.13	54.00	-17.87	Average				
8 q17793.090	10.99	42.89	52.68	39.54	40.74	54.00	-13.26	Average				
9 p17793.090	10.99	42.89	52.68	51.08	52.28	74.00	-21.72	Peak				

BLE_2M_TX_CH_39_Vertical



Site : chamber
Condition: 3m VERTICAL
Job No : 04481AT/04483AT
Mode : 2480 TX RSE


Freq	Cable		Ant		Preamp		Read		Limit		Over	Remark
	Loss	Factor	Factor	Level	Level	Level	Level	Line	Line	Limit		
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dBuV/m	dB	dB	dB		
1 3196.094	6.01	32.87	54.85	58.95	42.98	74.00	-31.02	Peak				
2 4790.245	7.40	34.22	54.22	55.82	43.22	74.00	-30.78	Peak				
3 7432.914	8.43	35.93	53.16	58.75	49.95	74.00	-24.05	Peak				
4 11533.480	11.46	37.77	53.11	51.85	47.97	74.00	-26.03	Peak				
5 14575.970	10.43	40.48	52.72	38.85	37.04	54.00	-16.96	Average				
6 14575.970	10.43	40.48	52.72	51.60	49.79	74.00	-24.21	Peak				
7 q17793.090	11.38	43.89	52.50	36.91	39.68	54.00	-14.32	Average				
8 p17793.090	11.38	43.89	52.50	49.81	52.58	74.00	-21.42	Peak				



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com


BLE_1M_TX_CH_00_Horizontal



Site : chamber
Condition: 3m HORIZONTAL
Job No : 04481AT\04483AT
Mode : 2402 TX RSE
BLE1M

Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark	Aux Factor
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1 p23978.580	6.78	38.99	50.39	50.77	36.61	74.00	-37.39	Peak	-9.54


BLE_1M_TX_CH_00_Vertical



Site : chamber
Condition: 3m VERTICAL
Job No : 04481AT\04483AT
Mode : 2402 TX RSE
BLE1M

Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark	Aux Factor
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1 p24649.340	6.83	39.16	51.72	51.31	36.04	74.00	-37.96	Peak	-9.54


BLE_1M_TX_CH_19_Horizontal



Site : chamber
Condition: 3m HORIZONTAL
Job No : 04481AT\04483AT
Mode : 2440 TX RSE
BLE1M

Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark	Aux Factor
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1 p23829.260	6.77	38.93	50.37	50.72	36.51	74.00	-37.49	Peak	-9.54

BLE_1M_TX_CH_19_Vertical




Site : chamber
Condition: 3m VERTICAL
Job No : 04481AT\04483AT
Mode : 2440 TX RSE
BLE1M

Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark	Aux Factor
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1 p23813.610	6.77	38.93	50.36	50.68	36.48	74.00	-37.52	Peak	-9.54




BLE_1M_TX_CH_39_Horizontal



Site : chamber
Condition: 3m HORIZONTAL
Job No : 04481AT\04483AT
Mode : 2480 TX RSE
BLE1M

Freq	Cable	Ant	Preamp	Read	Level	Limit	Over	Aux
MHz	Loss	Factor	Factor	Level	dBuV/m	dBuV/m	Limit	Factor
	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	dB
1 p24399.600	6.81	39.06	51.36	52.75	37.72	74.00	-36.28 Peak	-9.54


BLE_1M_TX_CH_39_Vertical



Site : chamber
Condition: 3m VERTICAL
Job No : 04481AT\04483AT
Mode : 2480 TX RSE
BLE1M

Freq	Cable	Ant	Preamp	Read	Level	Limit	Over	Aux
MHz	Loss	Factor	Factor	Level	dBuV	dBuV/m	dBuV/m	Factor
	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	dB
1 p24303.600	6.80	39.02	51.13	51.01	36.16	74.00	-37.84 Peak	-9.54


BLE_2M_TX_CH_00_Horizontal



Site : chamber
Condition: 3m HORIZONTAL
Job No : 04481AT\04483AT
Mode : 2402 TX RSE
BLE2M

Freq	Cable	Ant	Preamp	Read	Level	Limit	Over	Aux
MHz	Loss	Factor	Factor	Level	dBuV	dBuV/m	dBuV/m	Factor
	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	dB
1 p23931.240	6.78	38.97	50.39	49.73	35.55	74.00	-38.45 Peak	-9.54

BLE_2M_TX_CH_00_Vertical




Site : chamber
Condition: 3m VERTICAL
Job No : 04481AT\04483AT
Mode : 2402 TX RSE
BLE2M

Freq	Cable	Ant	Preamp	Read	Level	Limit	Over	Aux
MHz	Loss	Factor	Factor	Level	dBuV	dBuV/m	dBuV/m	Factor
	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	dB
1 p23931.240	6.78	38.97	50.39	50.76	36.58	74.00	-37.42 Peak	-9.54




BLE_2M_TX_CH_19_Horizontal



Site : chamber
Condition: 3m HORIZONTAL
Job No : 04481AT\04483AT
Mode : 2440 TX RSE
BLE2M

Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark	Aux Factor
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1 p23860.590	6.77	38.94	50.37	50.76	36.56	74.00	-37.44	Peak	-9.54


BLE_2M_TX_CH_19_Vertical



Site : chamber
Condition: 3m VERTICAL
Job No : 04481AT\04483AT
Mode : 2440 TX RSE
BLE2M

Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark	Aux Factor
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1 p23891.970	6.78	38.96	50.38	51.50	37.32	74.00	-36.68	Peak	-9.54


BLE_2M_TX_CH_39_Horizontal



Site : chamber
Condition: 3m HORIZONTAL
Job No : 04481AT\04483AT
Mode : 2480 TX RSE
BLE2M

Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark	Aux Factor
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1 p23978.460	6.78	38.99	50.40	50.54	36.37	74.00	-37.63	Peak	-9.54

BLE_2M_TX_CH_39_Vertical



Site : chamber
Condition: 3m VERTICAL
Job No : 04481AT\04483AT
Mode : 2480 TX RSE
BLE2M

Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark	Aux Factor
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1 p23885.790	6.77	38.92	50.36	50.41	36.20	74.00	-37.80	Peak	-9.54



7.5 Conducted Peak Output Power

Test Requirement 47 CFR Part 15, Subpart C 15.247(b)(3)
 Test Method: ANSI C63.10 (2020) Section 11.9.1
 Test Engineer: Byron Liang

Limit:

Frequency range(MHz)	Output power of the intentional radiator(watt)
902-928	1 for ≥ 50 hopping channels
	0.25 for $25 \leq$ hopping channels < 50
	1 for digital modulation
2400-2483.5	1 for ≥ 75 non-overlapping hopping channels
	0.125 for all other frequency hopping systems
	1 for digital modulation
5725-5850	1 for frequency hopping systems and digital modulation

7.5.1 E.U.T. Operation

Operating Environment:


Temperature: 23.2 °C Humidity: 46.7 % RH Atmospheric Pressure: 1020 mbar

7.5.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	06	TX mode(1Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	07	TX mode(2Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.



7.5.3 Test Setup Diagram



7.5.4 Measurement Procedure and Data

Note: Since the verify power the same operating range bandwidth and smaller power can be covered by the higher power.

Please Refer to Appendix for Details



7.6 Minimum 6dB Bandwidth

Test Requirement 47 CFR Part 15, Subpart C 15.247a(2)
 Test Method: ANSI C63.10 (2020) Section 11.8.1
 Test Engineer: Byron Liang

Limit:
 ≥500 kHz


7.6.1 E.U.T. Operation

Operating Environment:
 Temperature: 23.2 °C Humidity: 46.7 % RH Atmospheric Pressure: 1020 mbar

7.6.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	06	TX mode(1Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	07	TX mode(2Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.

7.6.3 Test Setup Diagram



7.6.4 Measurement Procedure and Data

Please Refer to Appendix for Details

7.7 Power Spectrum Density

Test Requirement 47 CFR Part 15, Subpart C 15.247(e)
 Test Method: ANSI C63.10 (2020) Section 11.10.2
 Test Engineer: Byron Liang

Limit:

≤8dBm in any 3 kHz band during any time interval of continuous transmission

7.7.1 E.U.T. Operation


Operating Environment:

Temperature: 23.2 °C Humidity: 46.7 % RH Atmospheric Pressure: 1020 mbar

7.7.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	06	TX mode(1Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	07	TX mode(2Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.

7.7.3 Test Setup Diagram



7.7.4 Measurement Procedure and Data

Please Refer to Appendix for Details

7.8 Conducted Band Edges Measurement

Test Requirement 47 CFR Part 15, Subpart C 15.247(d)
 Test Method: ANSI C63.10 (2020) Section 6.10.4
 Test Engineer: Byron Liang

Limit:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

7.8.1 E.U.T. Operation

Operating Environment:


Temperature: 23.2 °C Humidity: 46.7 % RH Atmospheric Pressure: 1020 mbar

7.8.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	06	TX mode(1Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	07	TX mode(2Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.



7.8.3 Test Setup Diagram



7.8.4 Measurement Procedure and Data

Please Refer to Appendix for Details

7.9 Conducted Spurious Emissions

Test Requirement: 47 CFR Part 15, Subpart C 15.247(d)
 Test Method: ANSI C63.10 (2020) Section 11.11
 Test Engineer: Byron Liang

Limit:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

7.9.1 E.U.T. Operation

Operating Environment:


Temperature: 23.2 °C Humidity: 46.7 % RH Atmospheric Pressure: 1020 mbar

7.9.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	06	TX mode(1Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	07	TX mode(2Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.



7.9.3 Test Setup Diagram



7.9.4 Measurement Procedure and Data

Please Refer to Appendix for Details



8 Test Setup Photo

Refer to Appendix - Test Setup Photo for SZCR2510004481AT

9 EUT Constructional Details (EUT Photos)

Refer to External and Internal Photos for SZCR2510004481AT



10 Appendix

1. Duty Cycle

1.1 Test Result


1.1.1 Ant1

Ant1							
Mode	TX Type	Frequency (MHz)	T _{on} (ms)	Period (ms)	Duty Cycle (%)	Duty Cycle Correction Factor (dB)	Max. DC Variation (%)
1M	SISO	2402	2.144	2.500	85.76	0.67	0.00
		2440	2.143	2.499	85.75	0.67	0.00
		2480	2.143	2.500	85.72	0.67	0.03
2M	SISO	2402	1.090	1.250	87.20	0.59	0.03
		2440	1.090	1.250	87.20	0.59	0.03
		2480	1.090	1.250	87.20	0.59	0.03



1.2 Test Graph

1.2.1 Ant1




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com


SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch (Shenzhen) Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

1M_HCH_2480MHz_Ant1_NTNV



2M_LCH_2402MHz_Ant1_NTNV




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com


SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Testing & Calibration Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

2M_MCH_2440MHz_Ant1_NTNV



2M_HCH_2480MHz_Ant1_NTNV



2. Bandwidth

2.1 Test Result

2.1.1 OBW


Mode	TX Type	Frequency (MHz)	ANT	99% Occupied Bandwidth (MHz)		Verdict
				Result	Limit	
1M	SISO	2402	1	1.056	/	Pass
		2440	1	1.057	/	Pass
		2480	1	1.056	/	Pass
2M	SISO	2402	1	2.057	/	Pass
		2440	1	2.055	/	Pass
		2480	1	2.053	/	Pass

2.1.2 6dB BW

Mode	TX Type	Frequency (MHz)	ANT	6dB Bandwidth (MHz)		Verdict
				Result	Limit	
1M	SISO	2402	1	0.726	≥ 0.5	Pass
		2440	1	0.721	≥ 0.5	Pass
		2480	1	0.729	≥ 0.5	Pass
2M	SISO	2402	1	1.241	≥ 0.5	Pass
		2440	1	1.241	≥ 0.5	Pass
		2480	1	1.237	≥ 0.5	Pass

2.2 Test Graph

2.2.1 OBW




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com


SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch (Shenzhen) Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com


1M_HCH_2480MHz_Ant1_NTNV




2M_LCH_2402MHz_Ant1_NTNV




2M_MCH_2440MHz_Ant1_NTNV




2M_HCH_2480MHz_Ant1_NTNV




2.2.2 6dB BW




1M_HCH_2480MHz_Ant1_NTNV




2M_LCH_2402MHz_Ant1_NTNV



2M_MCH_2440MHz_Ant1_NTNV



2M_HCH_2480MHz_Ant1_NTNV



3. Maximum Conducted Output Power

3.1 Test Result

3.1.1 Power

Mode	TX Type	Frequency (MHz)	Maximum Peak Conducted Output Power (dBm)		Verdict
			ANT1	Limit	
1M	SISO	2402	5.97	<=30	Pass
		2440	5.81	<=30	Pass
		2480	6.17	<=30	Pass
2M	SISO	2402	5.94	<=30	Pass
		2440	5.76	<=30	Pass
		2480	6.14	<=30	Pass

Note1: Antenna Gain: Ant1: 0.38dBi;

4. Maximum Power Spectral Density

4.1 Test Result


4.1.1 PSD

Mode	TX Type	Frequency (MHz)	Maximum PSD (dBm)		Verdict
			ANT1	Limit	
1M	SISO	2402	4.92	<=8	Pass
		2440	4.79	<=8	Pass
		2480	5.16	<=8	Pass
2M	SISO	2402	4.34	<=8	Pass
		2440	4.26	<=8	Pass
		2480	4.63	<=8	Pass


Note1: Antenna Gain: Ant1: 0.38dBi;

4.2 Test Graph


4.2.1 PSD




1M_HCH_2480MHz_Ant1_NTNV




2M_LCH_2402MHz_Ant1_NTNV



2M_MCH_2440MHz_Ant1_NTNV



2M_HCH_2480MHz_Ant1_NTNV



5. Unwanted Emissions In Non-restricted Frequency Bands

5.1 Test Result

5.1.1 Ref

Mode	TX Type	Frequency (MHz)	ANT	Level of Reference (dBm)
1M	SISO	2402	1	4.92
		2440	1	4.77
		2480	1	5.16
2M	SISO	2402	1	4.33
		2440	1	4.29
		2480	1	4.64

Note1: Refer to FCC Part 15.247 (d) and ANSI C63.10-2020, the channel contains the maximum PSD level was used to establish the reference level.


5.1.2 CSE

Mode	TX Type	Frequency (MHz)	ANT	Level of Reference (dBm)	Limit (dBm)	Verdict
1M	SISO	2402	1	5.16	-14.84	Pass
		2440	1	5.16	-14.84	Pass
		2480	1	5.16	-14.84	Pass
2M	SISO	2402	1	4.64	-15.36	Pass
		2440	1	4.64	-15.36	Pass
		2480	1	4.64	-15.36	Pass


Note1: Refer to FCC Part 15.247 (d) and ANSI C63.10-2020, the channel contains the maximum PSD level was used to establish the reference level.

5.2 Test Graph


5.2.1 Ref




1M_HCH_2480MHz_Ant1_NTNV




2M_LCH_2402MHz_Ant1_NTNV




2M_MCH_2440MHz_Ant1_NTNV



2M_HCH_2480MHz_Ant1_NTNV




5.2.2 CSE




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com


1M_MCH_2440MHz_Ant1_NTNV




1M_HCH_2480MHz_Ant1_NTNV




1M_HCH_2480MHz_Ant1_NTNV




2M_LCH_2402MHz_Ant1_NTNV




2M_LCH_2402MHz_Ant1_NTNV




2M_MCH_2440MHz_Ant1_NTNV



2M_HCH_2480MHz_Ant1_NTNV



2M_HCH_2480MHz_Ant1_NTNV



- End of the Report -

