

TEST REPORT

Reference No..... : WTX26X06185900W003
FCC ID : YHLBLU96GC
Applicant : BLU Products, Inc.
Address : 8600 NW 36th Street, Suite #300 | Miami, FL 33166, USA
Manufacturer : The same as Applicant
Address : The same as Applicant
Product Name : Smart Phone
Model No..... : G96
Standards : FCC Part 15.407
Date of Receipt sample : 2026-06-26
Date of Test..... : 2026-07-01 to 2026-07-23
Date of Issue : 2026-07-27
Test Report Form No. : WTX_Part 15_407W
Test Result..... : Pass

Remarks:

The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of approver.


Prepared By:

Waltek Testing Group (Shenzhen) Co., Ltd.

Address: 1/F., Room 101, Building 1, Hongwei Industrial Park, Liuxian 2nd Road,
Block 70 Bao'an District, Shenzhen, Guangdong, China

Tel.: +86-755-33663308 Fax.: +86-755-33663309 Email: sem@waltek.com.cn

Tested by:



Dashan Chen/Project Engineer

Approved by:



Jason Su/Manager

TABLE OF CONTENTS

1. GENERAL INFORMATION	5
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	5
1.2 TEST STANDARDS.....	6
1.3 TEST METHODOLOGY	6
1.4 TABLE FOR PARAMETERS OF TEST SOFTWARE SETTING.....	6
1.5 EUT OPERATING DURING TEST.....	8
1.6 TEST FACILITY	8
1.7 EUT SETUP AND TEST MODE	9
1.8 MEASUREMENT UNCERTAINTY	10
1.9 TEST EQUIPMENT LIST AND DETAILS	11
2. SUMMARY OF TEST RESULTS.....	15
3. ANTENNA REQUIREMENT.....	16
3.1 STANDARD APPLICABLE	16
3.2 EVALUATION INFORMATION	16
4. AUTOMATICALLY DISCONTINUE TRANSMISSION	17
4.1 STANDARD APPLICABLE	17
4.2 SUMMARY OF TEST RESULTS.....	17
5. POWER SPECTRAL DENSITY	18
5.1 STANDARD APPLICABLE	18
5.2 TEST PROCEDURE	18
5.3 SUMMARY OF TEST RESULTS/PLOTS.....	19
6. EMISSION BANDWIDTH AND OCCUPIED BANDWIDTH	20
6.1 STANDARD APPLICABLE	20
6.2 TEST PROCEDURE	20
6.3 SUMMARY OF TEST RESULTS/PLOTS.....	22
7. MAXIMUM CONDUCTED OUTPUT POWER	23
7.1 STANDARD APPLICABLE	23
7.2 TEST PROCEDURE	23
7.3 SUMMARY OF TEST RESULTS/PLOTS.....	24
8. RADIATED SPURIOUS EMISSIONS	25
8.1 STANDARD APPLICABLE	25
8.2 TEST PROCEDURE	25
8.3 TEST RECEIVER SETUP	27
8.4 CORRECTED AMPLITUDE & MARGIN CALCULATION.....	27
8.5 SUMMARY OF TEST RESULTS/PLOTS.....	27
9. FREQUENCY STABILITY	87
9.1 STANDARD APPLICABLE	87
9.2 TEST PROCEDURE	87
9.3 SUMMARY OF TEST RESULTS/PLOTS.....	87
10. CONDUCTED EMISSIONS	88
10.1 TEST PROCEDURE.....	88
10.2 BASIC TEST SETUP BLOCK DIAGRAM.....	88
10.3 TEST RECEIVER SETUP	88
10.4 SUMMARY OF TEST RESULTS/PLOTS	88
APPENDIX SUMMARY	91
APPENDIX A1: EMISSION BANDWIDTH	92
APPENDIX A2: OCCUPIED CHANNEL BANDWIDTH	114
APPENDIX A3: MIN EMISSION BANDWIDTH.....	136
APPENDIX B: DUTY CYCLE	142
APPENDIX C: MAXIMUM CONDUCTED OUTPUT POWER	164
APPENDIX D: MAXIMUM POWER SPECTRAL DENSITY	188

Reference No.: WTX26X06185900W003

APPENDIX E: BAND EDGE MEASUREMENTS210

APPENDIX F: CONDUCTED SPURIOUS EMISSION.....225

APPENDIX G: FREQUENCY STABILITY268

APPENDIX PHOTOGRAPHS.....293

Report version

Version No.	Date of issue	Description
Rev.00	2026-07-27	Original
/	/	/

1. GENERAL INFORMATION

1.1 Product Description for Equipment Under Test (EUT)

General Description of EUT	
Product Name:	Smart Phone
Trade Name:	BLU
Model No.:	G96
Adding Model(s):	/
Rated Voltage:	Battery:DC3.87V Type-C:DC5V
Battery Capacity:	C1016656700P Rated: 6830mAh 26.44Wh, Typical: 7000mAh 27.09Wh
Power Adapter:	US-BJ-1825Q Input:AC100-240V 50/60Hz 0.5A Output:DC5V3A/9V2A/12V1.5A
<i>Note: The sample information is provided by the customer.</i>	

Technical Characteristics of EUT	
Support Standards:	802.11a, 802.11n(HT20), 802.11n-HT40, 802.11ac-VHT20, 802.11ac-VHT40,802.11ac-VHT80
Frequency Range:	5180-5240MHz, 5260-5320MHz 5500-5700MHz, 5745-5825MHz
Max. RF Output Power:	Normal: 17.12dBm (Conducted) Receiver ON: 13.27dBm (Conducted)
Type of Modulation:	QPSK, 16QAM, 64QAM, 256QAM
Type of Antenna:	PIFA Antenna
Antenna Gain:	-0.96dBi
<i>Note: 1: The Antenna Gain is provided by the customer and can affect the validity of results.</i>	
<i>2: The data provided by the customer and can affect the validity of results.</i>	

1.2 Test Standards

The tests were performed according to following standards:

FCC Rules Part 15.407: General technical requirements.

ANSI C63.10-2020: American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

KDB789033 D02 v02r01: Guidelines for Compliance Testing of Unlicensed National Information Infrastructure (U-Nii) Devices Part 15, Subparte.

Maintenance of compliance is the responsibility of the manufacturer. Any modification of the product, which result in lowering the emission, should be checked to ensure compliance has been maintained.

1.3 Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2020, KDB789033 D02 v02r01. The equipment under test (EUT) was configured to measure its highest possible emission level. The test modes were adapted accordingly in reference to the Operating Instructions.

1.4 Table for parameters of Test Software setting

Enter *****3646633***** into the calculator to enter the engineer mode, you can start to test. During testing, Channel and Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

Normal mode:

Mode	Test Frequency (MHz)												
	NCB: 20MHz												
	5180	5200	5240	5260	5300	5320	5500	5580	5700	5720	5745	5785	5825
802.11a 6Mbps	17	17	17	17	17	17	17	17	17	17	17	17	17
802.11n-HT20 MCS0	17	17	17	17	17	17	17	17	17	17	17	17	17
802.11ac-VHT20 MCS0	16	16	16	16	16	16	16	16	16	16	16	16	16
Mode	NCB: 40MHz												
	5190	5230	5270	5310	5510	5550	5670	5710	5755	5795			
802.11n-HT40 MCS0	16	16	16	16	16	16	16	16	16	16	16	16	
802.11ac-VHT40 MCS0	16	16	16	16	16	16	16	16	16	16	16	16	
Mode	NCB: 80MHz												

	5210	5290	5530	5610	5690	5775
802.11ac-VHT80 MCS0	16	16	16	16	16	16

Receiver on:

Mode	Test Frequency (MHz)												
	NCB: 20MHz												
	5180	5200	5240	5260	5300	5320	5500	5580	5700	5720	5745	5785	5825
802.11a 6Mbps	14	14	14	14	14	14	14	14	14	14	14	14	14
802.11n-HT20 MCS0	14	14	14	14	14	14	14	14	14	14	14	14	14
802.11ac-VHT20 MCS0	13	13	13	13	13	13	13	13	13	13	13	13	13
Mode	NCB: 40MHz												
	5190	5230	5270	5310	5510	5550	5670	5710	5755	5795			
802.11n-HT40 MCS0	13	13	13	13	13	13	13	13	13	13	13	13	
802.11ac-VHT40 MCS0	13	13	13	13	13	13	13	13	13	13	13	13	
Mode	NCB: 80MHz												
	5210		5290		5530		5610		5690		5775		
802.11ac-VHT80 MCS0	13		13		13		13		13		13		

1.5 EUT Operating during test

EUT was programmed to be in continuously transmitting mode. During the test, EUT operation to normal function and programs under Android were executed.

1.6 Test Facility

Address of the test laboratory

Laboratory: Waltek Testing Group (Shenzhen) Co., Ltd.

Address: 1/F., Room 101, Building 1, Hongwei Industrial Park, Liuxian 2nd Road, Block 70 Bao'an District, Shenzhen, Guangdong, China

FCC – Registration No.: 125990

Waltek Testing Group (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files. The Designation Number is CN5010, and Test Firm Registration Number is 125990.

Industry Canada (IC) Registration No.: 11464A

The 3m Semi-anechoic chamber of Waltek Testing Group (Shenzhen) Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 11464A and the CAB identifier is CN0057.

1.7 EUT Setup and Test Mode

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. All testing shall be performed under maximum output power condition, with a duty cycle equal to 100%, and to measure its highest possible emissions level, more detailed description as follows:

Test Mode List		
Test Mode	Description	Remark
TM1	802.11a	5180MHz,5200MHz,5240MHz,5260MHz,5280MHz,5320MHz,5500MHz,5580MHz,5700MHz,5745MHz, 5785MHz,5825MHz
TM2	802.11n-HT20	5180MHz,5200MHz,5240MHz,5260MHz,5280MHz,5320MHz,5500MHz,5580MHz,5700MHz,5745MHz, 5785MHz,5825MHz
TM3	802.11ac-HT20	5180MHz,5200MHz,5240MHz,5260MHz,5280MHz,5320MHz,5500MHz,5580MHz,5700MHz,5745MHz, 5785MHz,5825MHz
TM4	802.11n-HT40	5190MHz,5230MHz,5270MHz,5310MHz,5510MHz,5550MHz,5670MHz,5755MHz,5795MHz
TM5	802.11ac-HT40	5190MHz,5230MHz,5270MHz,5310MHz,5510MHz,5550MHz,5670MHz,5755MHz,5795MHz
TM6	802.11ac-VH80	5210MHz,5290MHz,5530MHz,5610MHz,5775MHz

Test Conditions	
Temperature:	22~25 °C
Relative Humidity:	50~55 %.
ATM Pressure:	1019 mbar

EUT Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
Type-C Cable	1.0	Unshielded	Without Ferrite
Earphone Cable	1.1	Unshielded	Without Ferrite

Special Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
/	/	/	/

Auxiliary Equipment List and Details			
Description	Manufacturer	Model	Serial Number
Notebook	Lenovo	TianYi 100-14IBD	PF0F4ABV

1.8 Measurement Uncertainty

Measurement uncertainty		
Parameter	Conditions	Uncertainty
RF Output Power	Conducted	$\pm 0.57\text{dB}$
Occupied Bandwidth	Conducted	$\pm 0.015\text{MHz}$
Power Spectral Density	Conducted	$\pm 1.8\text{dB}$
Conducted Spurious Emission	Conducted	$\pm 2.17\text{dB}$
Conducted Emission 1#	Conducted	@9kHz to 150kHz: $\pm 3.74\text{dB}$
		@150kHz to 30MHz: $\pm 3.34\text{dB}$
Conducted Emission 2#	Conducted	@9kHz to 150kHz: $\pm 3.74\text{dB}$
		@150kHz to 30MHz: $\pm 3.34\text{dB}$
Transmitter Spurious Emissions chamber A	Radiated	@9kHz to 30MHz: $\pm 3.0\text{dB}$
		@30MHz to 1GHz: $\pm 5.70\text{dB}$
		@1GHz to 6GHz: $\pm 5.88\text{dB}$
		@6GHz to 18GHz: $\pm 5.96\text{dB}$
		@18GHz to 40GHz: $\pm 6.12\text{dB}$
Transmitter Spurious Emissions chamber B	Radiated	@30MHz to 1GHz: $\pm 5.36\text{dB}$
Transmitter Spurious Emissions chamber C	Radiated	@9kHz to 30MHz: $\pm 3.0\text{dB}$
		@30MHz to 1GHz: $\pm 5.28\text{dB}$
		@1GHz to 6GHz: $\pm 5.56\text{dB}$
		@6GHz to 18GHz: $\pm 5.72\text{dB}$
		@18GHz to 40GHz: $\pm 6.12\text{dB}$

1.9 Test Equipment List and Details

Internal No.	Description	Manufacturer	Model	Serial No.	Cal Date	Due. Date
WTXE1041A 1002	Communication Tester	Rohde & Schwarz	CMW500	1201.0002 k50-14865 0-FB	2026-03-25	2027-03-24
WTXE1005A 1005	MXA Signal Analyzer	Agilent	N9020A	US471401 02	2026-03-25	2027-03-24
WTXE1084A 1001	MXA Signal Analyzer	KEYSIGHT	N9020A	MY543205 48	2026-02-06	2027-02-05
WTXE1005A 1006	Spectrum Analyzer	Rohde & Schwarz	FSP40	1164.4391 K38Ser. 100368	2026-04-29	2027-04-28
WTXW1105A 1010	MXA signal Analyzer	KEYSIGHT	N9020A	MY512856 78	2026-02-06	2027-02-05
WTXE1105A 1008	RF Control Unit	Tonscend	JS0806-2	/	2026-02-06	2027-02-05
WTXW1105A 1136	RF ATTENUATOR	FEIYANG	N-JK	/	2026-02-06	2027-02-05
WTXE1003A 1-005	Coaxial Cable	/	0M4RFC	/	2026-02-23	2027-02-22
☐ Chamber A: Below 1GHz						
WTXE1005A 1003	Spectrum Analyzer	Rohde & Schwarz	FSP30	836079/03 5	2026-02-05	2027-02-04
WTXE1001A 1001	EMI Test Receiver	Rohde & Schwarz	ESPI	101611	2026-02-05	2027-02-04
WTXE1007A 1002	Amplifier	HP	8447F	2805A034 75	2026-02-05	2027-02-04
WTXE1010A 1007	Loop Antenna	Schwarz beck	FMZB 1516	9773	2026-02-05	2027-02-04
WTXE1010A 1006	Broadband Antenna	Schwarz beck	VULB9163	9163-333	2026-03-11	2029-03-10
WTXE1104A 1032-1	Coaxial Cable	/	RC_6G-N-M	/	2026-02-23	2027-02-22
WTXE1104A 1032-2	Coaxial Cable	/	RC_6G-N-M	/	2026-02-23	2027-02-22
WTXE1104A 1032-3	Coaxial Cable	/	RC_6G-N-M	/	2026-02-23	2027-02-22
☐ Chamber A: Above 1GHz						
WTXE1005A 1003	Spectrum Analyzer	Rohde & Schwarz	FSP30	836079/03 5	2026-02-05	2027-02-04
WTXE1001A	EMI Test	Rohde &	ESPI	101611	2026-02-05	2027-02-04

1001	Receiver	Schwarz				
WTXE1065A 1001	Amplifier	C&D	PAP-1.0G18	14918	2026-02-05	2027-02-04
WTXE1010A 1005	Horn Antenna	ETS	3117	00086197	2026-02-05	2027-02-04
WTXE1010A 1010	DRG Horn Antenna	A.H. SYSTEMS	SAS-574	571	2026-02-10	2027-02-09
WTXE1003A 1001	Pre-amplifier	Schwarzbeck	BBV 9721	9721-031	2026-02-05	2027-02-04
WTXE1104A 1033-1	Coaxial Cable	/	C16-07-07	/	2026-02-23	2027-02-22
WTXE1104A 1033-2	Coaxial Cable	/	C16-07-07	/	2026-02-23	2027-02-22
WTXE1104A 1033-3	Coaxial Cable	/	C16-07-07	/	2026-02-23	2027-02-22
☐ Chamber B:Below 1GHz						
WTXE1010A 1006	Trilog Broadband Antenna	Schwarz beck	VULB9163(B)	9163-635	2024-03-17	2027-03-16
WTXE1038A 1001	Amplifier	Agilent	8447D	2944A104 57	2026-02-05	2027-02-04
WTXE1001A 1002	EMI Test Receiver	Rohde & Schwarz	ESPI	101391	2026-02-05	2027-02-04
WTXE1104A 1031-1	Coaxial Cable	/	1.5MRFC-LWB3	/	2026-02-23	2027-02-22
WTXE1104A 1031-2	Coaxial Cable	/	RG 316	/	2026-02-23	2027-02-22
WTXE1104A 1031-3	Coaxial Cable	/	RG 316	/	2026-02-23	2027-02-22
☒ Chamber C:Below 1GHz						
WTXE1093A 1001	EMI Test Receiver	Rohde & Schwarz	ESIB 26	100401	2026-02-05	2027-02-04
WTXE1010A 1013-1	Trilog Broadband Antenna	Schwarz beck	VULB 9168	1194	2024-04-18	2027-04-17
WTXE1010A 1007	Loop Antenna	Schwarz beck	FMZB 1516	9773	2026-02-05	2027-02-04
WTXE1007A 1003	Amplifier	HP	8447F	2944A038 69	2026-02-05	2027-02-04
WTXE1104A 1034-1	Coaxial Cable	/	RC_6G-N-M	/	2026-02-23	2027-02-22
WTXE1104A	Coaxial Cable	/	RC_6G-N-M	/	2026-02-23	2027-02-22

1034-2						
WTXE1104A 1034-3	Coaxial Cable	/	RC_6G-N-M	/	2026-02-23	2027-02-22
☒ Chamber C: Above 1GHz						
WTXE1093A 1001	EMI Test Receiver	Rohde & Schwarz	ESIB 26	100401	2026-02-05	2027-02-04
WTXE1103A 1005	Horn Antenna	POAM	RTF-118A	1820	2025-06-13	2027-06-12
WTXE1103A 1006	Amplifier	Tonscend	TAP01018050	AP22E806 235	2026-02-05	2027-02-04
WTXE1010A 1010	DRG Horn Antenna	A.H. SYSTEMS	SAS-574	571	2026-02-10	2027-02-09
WTXE1003A 1001	Pre-amplifier	Schwarzbeck	BBV 9721	9721-031	2026-02-05	2027-02-04
WTXE1104A 1035-1	Coaxial Cable	/	RC-18G-N-M	/	2026-02-23	2027-02-22
WTXE1104A 1035-2	Coaxial Cable	/	RC-18G-N-M	/	2026-02-23	2027-02-22
WTXE1104A 1035-3	Coaxial Cable	/	RC-18G-N-M	/	2026-02-23	2027-02-22
☐ Conducted Room 1#						
WTXE1104A 1029	EMI Test Receiver	Rohde & Schwarz	ESCI	100525	2025-11-25	2026-11-24
WTXE1002A 1001	Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100911	2026-02-05	2027-02-04
WTXE1003A 1001	AC LISN	Schwarz beck	NSLK8126	8126-279	2026-02-05	2027-02-04
WTXE1104A 1036	Coaxial Cable	/	RG 316	/	2026-02-23	2027-02-22
WTXE1104A 1038	Coaxial Cable	/	6MRFC-DP	/	2026-02-23	2027-02-22
☒ Conducted Room 2#						
WTXE1001A 1004	EMI Test Receiver	Rohde & Schwarz	ESPI	101259	2026-02-05	2027-02-04
WTXE1003A 1003	LISN	Rohde & Schwarz	ENV 216	100097	2026-02-05	2027-02-04
WTXE1104A 1037	Coaxial Cable	/	RG 316	/	2026-02-23	2027-02-22

Software List			
Description	Manufacturer	Model	Version
EMI Test Software/EZ-EMC (Radiated Emission A)	Farad	RA-03A1	1.1.4.2
EMI Test Software/EZ-EMC (Radiated Emission B)	Farad	RA-03A1	1.1.4.2
EMI Test Software/EZ-EMC (Radiated Emission C)	Farad	RA-03A1-2	1.1.4.2
EMI Test Software/EZ-EMC (Conducted Emission Room 1#)	Farad	3A1*CE-RE	1.1.4.3
EMI Test Software/EZ-EMC (Conducted Emission Room 2#)	Farad	3A1*CE-RE	1.1.4.3
RF Test System	Tonscend	JS1120-3	V3.6.21

*Remark: indicates software version used in the compliance certification testing.

2. SUMMARY OF TEST RESULTS

FCC Rules	Description of Test Item	Result
§15.203; §15.405	Antenna Requirement	Compliant
15.407 (c)	Automatically Discontinue Transmission	Compliant
§15.207; §15.407(b)(6)	Conducted Emission	Compliant
§15.407(a)(1),(2)	Power Spectral Density	Compliant
§15.407(e)	Emission Bandwidth and Occupied Bandwidth	Compliant
§15.407(a)(1),(2)	Maximum Conducted Output Power	Compliant
§15.407(b)(1),(2),(3),(4)	Undesirable emission	Compliant
§15.205; §15.209; §15.407(b)(1),(2),(3)	Radiated Emission	Compliant
§15.407(g)	Frequency Stability	Compliant
§15.407(h)	Dynamic Frequency Selection (DFS)	Compliant

N/A: Not applicable.

3. Antenna Requirement

3.1 Standard Applicable

According to FCC Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

3.2 Evaluation Information

This product has a PIFA antenna, fulfill the requirement of this section.

4. Automatically Discontinue Transmission

4.1 Standard Applicable

According to FCC Part 15.407(c), the device shall automatically discontinue transmission in case of either absence of information to transmit or operational failure. These provisions are not intended to preclude the transmission of control or signaling information or the use of repetitive codes used by certain digital technologies to complete frame or burst intervals. Applicants shall include in their application for equipment authorization to describe how this requirement is met.

4.2 Summary of Test Results

While the EUT is not transmitting any information, the EUT can automatically discontinue transmission and become standby mode for power saving. The EUT can detect the controlling signal of ACK message transmitting from remote device and verify whether it shall resend or discontinue transmission.

5. Power Spectral Density

5.1 Standard Applicable

Section 15.407(a) Power limits:

(1) For the band 5.15-5.25GHz.

(iv) For mobile and portable client devices in the 5.15-5.25GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250mW provided the maximum antenna gain does not exceed 6dBi. In addition, the maximum power spectral density shall not exceed 11dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

(2) For the 5.25-5.35GHz and 5.47-5.725GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250mW or $11 \text{ dBm} + 10 \log B$, where B is the 26dB emission bandwidth in megahertz. In addition, the maximum power spectral density shall not exceed 11dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

(3) For the band 5.725-5.85GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30dBm in any 500kHz band. If transmitting antennas of directional gain greater than 6dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

5.2 Test Procedure

According to 789033 D02 v02r01 General UNII Test Procedures New Rules v02, the following is the measurement procedure.

For devices operating in the bands 5.15-5.25GHz, 5.25-5.35GHz, and 5.47-5.725GHz, the above procedures make use of 1 MHz RBW to satisfy directly the 1 MHz reference bandwidth specified in § 15.407(a)(5). For devices operating in the band 5.725-5.85GHz, the rules specify a measurement bandwidth of 500kHz. Many spectrum analyzers do not have 500kHz RBW, thus a narrower RBW may need to be used. The rules permit the use of a RBWs less than 1 MHz, or 500kHz, "provided that the measured power is integrated over the full

reference bandwidth” to show the total power over the specified measurement bandwidth (i.e., 1MHz, or 500kHz). If measurements are performed using a reduced resolution bandwidth ($< 1\text{MHz}$, or $< 500\text{kHz}$) and integrated over 1 MHz, or 500kHz bandwidth, the following adjustments to the procedures apply:

- a) Set $\text{RBW} \geq 1/T$, where T is defined in section II.B.I.a).
- b) Set $\text{VBW} \geq 3 \text{ RBW}$.
- c) If measurement bandwidth of Maximum PSD is specified in 500kHz, add $10\log(500\text{kHz}/\text{RBW})$ to the measured result, whereas $\text{RBW} (< 500\text{kHz})$ is the reduced resolution bandwidth of the spectrum analyzer set during measurement.
- d) If measurement bandwidth of Maximum PSD is specified in 1 MHz, add $10\log(1\text{MHz}/\text{RBW})$ to the measured result, whereas $\text{RBW} (< 1\text{MHz})$ is the reduced resolution bandwidth of spectrum analyzer set during measurement.
- e) Care must be taken to ensure that the measurements are performed during a period of continuous transmission or are corrected upward for duty cycle.

Note: As a practical matter, it is recommended to use reduced RBW of 100kHz for the sections 5.c) and 5.d) above, since $\text{RBW}=100\text{kHz}$ is available on nearly all spectrum analyzers.

5.3 Summary of Test Results/Plots

Please refer to Appendix D

6. Emission Bandwidth and Occupied Bandwidth

6.1 Standard Applicable

According to 15.407(a) and (e):

(1) For the band 5.15-5.25GHz.

(iv) For mobile and portable client devices in the 5.15-5.25GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250mW provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 11dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

(2) For the 5.25-5.35GHz and 5.47-5.725GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250mW or $11\text{dBm} + 10 \log B$, where B is the 26dB emission bandwidth in megahertz. In addition, the maximum power spectral density shall not exceed 11dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

(3) For the band 5.725-5.85GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30dBm in any 500kHz band. If transmitting antennas of directional gain greater than 6dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

(e) Within the 5.725-5.85GHz band, the minimum 6dB bandwidth of U-NII devices shall be at least 500kHz.

6.2 Test Procedure

According to 789033 D02 v02r0r section C&D, the following is the measurement procedure.

1. Emission Bandwidth (EBW)

- a) Set RBW = approximately 1% of the emission bandwidth.
- b) Set the VBW > RBW.

- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Measure the maximum width of the emission that is 26dB down from the maximum of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.

2. Minimum Emission Bandwidth for the band 5.725-5.85GHz Section 15.407(e) specifies the minimum 6 dB emission bandwidth of at least 500KHz for the band 5.715-5.85 GHz. The following procedure shall be used for measuring this bandwidth:

- a) Set RBW = 100kHz.
- b) Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6dB relative to the maximum level measured in the fundamental emission.

Note: The automatic bandwidth measurement capability of a spectrum analyzer or EMI receiver may be employed if it implements the functionality described above.

D. 99 Percent Occupied Bandwidth

The 99-percent occupied bandwidth is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers are each equal to 0.5 % of the total mean power of the given emission. Measurement of the 99-percent occupied bandwidth is required only as a condition for using the optional band-edge measurement techniques described in section II.G.3.d). Measurements of 99-percent occupied bandwidth may also optionally be used in lieu of the EBW to 789033 D02 v02r01 General UNII Test Procedures New Rules v01 define the minimum frequency range over which the spectrum is integrated when measuring maximum conducted output power as described in section II.E. However, the EBW must be measured to determine bandwidth dependent limits on maximum conducted output power in accordance with 15.407(a).

The following procedure shall be used for measuring (99 %) power bandwidth:

- 1. Set center frequency to the nominal EUT channel center frequency.
- 2. Set span = 1.5 times to 5.0 times the OBW.
- 3. Set RBW = 1 % to 5 % of the OBW
- 4. Set VBW $\geq 3 \times$ RBW
- 5. Video averaging is not permitted. Where practical, a sample detection and single sweep mode shall be used. Otherwise, peak detection and max hold mode (until the trace stabilizes) shall be used.
- 6. Use the 99 % power bandwidth function of the instrument (if available).
- 7. If the instrument does not have a 99 % power bandwidth function, the trace data points are recovered and directly summed in power units. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5 % of the total is reached; that frequency is recorded as the lower frequency.

Reference No.: WTX26X06185900W003

The process is repeated until 99.5 % of the total is reached; that frequency is recorded as the upper frequency. The 99% occupied bandwidth is the difference between these two frequencies.

6.3 Summary of Test Results/Plots

Please refer to Appendix A

7. Maximum Conducted Output Power

7.1 Standard Applicable

Section 15.407(a) Power limits:

(1) For the band 5.15-5.25GHz.

(iv) For mobile and portable client devices in the 5.15-5.25GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250mW provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 11dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

(2) For the 5.25-5.35GHz and 5.47-5.725GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250mW or 11dBm + 10 log B, where B is the 26dB emission bandwidth in megahertz. In addition, the maximum power spectral density shall not exceed 11dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

(3) For the band 5.725-5.85GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30dBm in any 500kHz band. If transmitting antennas of directional gain greater than 6dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

7.2 Test Procedure

According to KDB789033 D02 v02r01 section E, the following is the measurement procedure.

- (i) Set span to encompass the entire emission bandwidth (EBW) (or, alternatively, the entire 99% occupied bandwidth) of the signal.
- (ii) Set RBW = 1MHz.
- (iii) Set VBW $\geq$ 3MHz.
- (iv) Number of points in sweep $\geq$ 2 Span / RBW. (This ensures that bin-to-bin spacing is $\leq$ RBW/2, so that

narrowband signals are not lost between frequency bins.)

(v) Sweep time = auto.

(vi) Detector = RMS (i.e., power averaging), if available. Otherwise, use sample detector mode.

(vii) If transmit duty cycle < 98 percent, use a video trigger with the trigger level set to enable triggering only on full power pulses. Transmitter must operate at maximum power control level for the entire duration of every sweep. If the EUT transmits continuously (i.e., with no off intervals) or at duty cycle $\geq$ 98 percent, and if each transmission is entirely at the maximum power control level, then the trigger shall be set to "free run".

(viii) Trace average at least 100 traces in power averaging (i.e., RMS) mode.

(ix) Compute power by integrating the spectrum across the EBW (or, alternatively, the entire 99% occupied bandwidth) of the signal using the instrument's band power measurement function with band limits set equal to the EBW (or occupied bandwidth) band edges. If the instrument does not have a band power function, sum the spectrum levels (in power units) at 1MHz intervals extending across the EBW (or, alternatively, the entire 99% occupied bandwidth) of the spectrum.

7.3 Summary of Test Results/Plots

Please refer to Appendix C

8. Radiated Spurious Emissions

8.1 Standard Applicable

According to §15.407(b), undesirable emission limits. Except as shown in paragraph (b)(7) of this section, the maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:

- (1) For transmitters operating in the 5.15-5.25GHz band: All emissions outside of the 5.15-5.35GHz band shall not exceed an e.i.r.p. of -27dBm/MHz.
- (2) For transmitters operating in the 5.25-5.35GHz band: All emissions outside of the 5.15-5.35GHz band shall not exceed an e.i.r.p. of -27dBm/MHz.
- (3) For transmitters operating in the 5.47-5.725GHz band: All emissions outside of the 5.47-5.725GHz band shall not exceed an e.i.r.p. of -27dBm/MHz.
- (4) For transmitters operating in the 5.725-5.85GHz band:
 - (i) All emissions shall be limited to a level of -27dBm/MHz at 75MHz or more above or below the band edge increasing linearly to 10dBm/MHz at 25MHz above or below the band edge, and from 25MHz above or below the band edge increasing linearly to a level of 15.6dBm/MHz at 5MHz above or below the band edge, and from 5MHz above or below the band edge increasing linearly to a level of 27dBm/MHz at the band edge.

According to §15.407(b)(6), Unwanted emissions below 1GHz must comply with the general field strength limits set forth in §15.209. Further, any U-NII devices using an AC power line are required to comply also with the conducted limits set forth in §15.207.

According to §15.407(b)(7), The provisions of §15.205 apply to intentional radiators operating under this section.

789033 D02 v02r01 General UNII Test Procedures New Rules v01

If radiated measurements are performed, field strength is then converted to EIRP as follows:

$$\text{EIRP} = ((E \cdot d)^2) / 30$$

where:


- E is the field strength in V/m;
- d is the measurement distance in meters;
- EIRP is the equivalent isotropically radiated power in watts.

8.2 Test Procedure


The setup of EUT is according with per ANSI C63.10-2020 measurement procedure. The specification used was with the FCC Part 15.205 15.407(b)(6) and FCC Part 15.209 Limit..

The external I/O cables were draped along the test table and formed a bundle 30 to 40cm long in the middle. The spacing between the peripherals was 10cm.


The test setup for emission measurement below 30MHz.



The test setup for emission measurement from 30MHz to 1GHz.



The test setup for emission measurement above 1GHz.



8.3 Test Receiver Setup

During the radiated emission test for above 1GHz, the test receiver was set with the following configurations:

For peak detector:

RBW = 1000kHz, VBW = 3000kHz, Sweep Time = Auto

For average detector:

RBW = 1000kHz, VBW = 10Hz, Sweep Time = Auto

8.4 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated adding the Antenna Factor and the Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} + \text{Ant. Factor} + \text{Cable Loss} - \text{Ampl. Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -6dB μ V means the emission is 6dB μ V below the maximum limit for Class B. The equation for margin calculation is as follows:


$$\text{Margin} = \text{Corr. Ampl.} - \text{FCC Part 15 Limit}$$

8.5 Summary of Test Results/Plots

Note: this EUT was tested in 3 orthogonal positions and the worst case position data was reported.

➤ Spurious Emission From 9kHz-30MHz


802.11a(Worst case)			
Test Channel	5180MHz(Worst case)	Polarity:	Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	0.0098	62.94	-7.18	55.76	127.76	-72.00	-	-	peak
2	0.0354	49.82	-7.46	42.36	116.61	-74.25	-	-	peak
3	0.0916	46.12	-7.80	38.32	108.36	-70.04	-	-	peak
4	0.4812	59.25	-8.16	51.09	93.96	-42.87	-	-	peak
5	0.6238	64.82	-8.03	56.79	71.71	-14.92	-	-	peak
6	11.4983	45.68	-7.87	37.81	69.50	-31.69	-	-	peak

- Spurious Emission From 30MHz to 1GHz
- 5150-5250MHz

802.11a(Worst case)			
Test Channel	5180MHz(Worst case)	Polarity:	Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	37.5647	29.96	-9.15	20.81	40.00	-19.19	-	-	peak
2	54.5166	27.90	-8.47	19.43	40.00	-20.57	-	-	peak
3	158.6397	29.39	-8.30	21.09	43.50	-22.41	-	-	peak
4	280.2935	29.69	-8.79	20.90	46.00	-25.10	-	-	peak
5	433.3397	32.06	-5.36	26.70	46.00	-19.30	-	-	peak
6	776.4848	29.91	1.45	31.36	46.00	-14.64	-	-	peak


802.11a(Worst case)

Test Channel

5180MHz(Worst case)

Polarity:

Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	40.0172	27.82	-8.84	18.98	40.00	-21.02	-	-	peak
2	66.3714	28.99	-9.70	19.29	40.00	-20.71	-	-	peak
3	147.8746	29.33	-8.58	20.75	43.50	-22.75	-	-	peak
4	324.8644	29.12	-7.62	21.50	46.00	-24.50	-	-	peak
5	573.9882	29.75	-1.77	27.98	46.00	-18.02	-	-	peak
6	809.9238	30.28	1.72	32.00	46.00	-14.00	-	-	peak

➤ 5250-5350MHz


802.11a(Worst case)

Test Channel	5260MHz(Worst case)	Polarity:	Horizontal
--------------	---------------------	-----------	------------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	35.5112	29.06	-9.46	19.60	40.00	-20.40	-	-	peak
2	54.1349	28.57	-8.44	20.13	40.00	-19.87	-	-	peak
3	148.9173	28.92	-8.57	20.35	43.50	-23.15	-	-	peak
4	300.6988	29.53	-8.28	21.25	46.00	-24.75	-	-	peak
5	433.3397	32.95	-5.36	27.59	46.00	-18.41	-	-	peak
6	669.9523	32.06	0.00	32.06	46.00	-13.94	-	-	peak


802.11a(Worst case)			
Test Channel	5260MHz(worst case)	Polarity:	Vertical



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	41.4483	29.82	-8.73	21.09	40.00	-18.91	-	-	peak
2	74.2696	32.06	-11.20	20.86	40.00	-19.14	-	-	peak
3	137.8398	28.86	-9.05	19.81	43.50	-23.69	-	-	peak
4	282.2701	28.70	-8.70	20.00	46.00	-26.00	-	-	peak
5	484.9068	29.70	-3.97	25.73	46.00	-20.27	-	-	peak
6	833.0126	37.33	1.69	39.02	46.00	-6.98	-	-	peak


➤ 5470-5725MHz

802.11a(worst case)			
Test Channel	5500MHz(worst case)	Polarity:	Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	46.3806	28.06	-8.30	19.76	40.00	-20.24	-	-	peak
2	69.2297	27.61	-10.28	17.33	40.00	-22.67	-	-	peak
3	157.5289	30.21	-8.28	21.93	43.50	-21.57	-	-	peak
4	455.1887	29.22	-4.56	24.66	46.00	-21.34	-	-	peak
5	660.6024	30.19	-0.05	30.14	46.00	-15.86	-	-	peak
6	899.9576	31.25	2.66	33.91	46.00	-12.09	-	-	peak


802.11a(worst case)			
Test Channel	5500MHz(worst case)	Polarity:	Vertical



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	34.2851	27.80	-9.58	18.22	40.00	-21.78	-	-	peak
2	74.2696	32.12	-11.20	20.92	40.00	-19.08	-	-	peak
3	144.7898	28.20	-8.74	19.46	43.50	-24.04	-	-	peak
4	318.0875	29.01	-7.79	21.22	46.00	-24.78	-	-	peak
5	520.2078	30.37	-3.03	27.34	46.00	-18.66	-	-	peak
6	833.0126	36.32	1.69	38.01	46.00	-7.99	-	-	peak

➤ 5725-5850MHz


802.11a(worst case)			
Test Channel	5745MHz(worst case)	Polarity:	Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	47.7028	28.08	-8.30	19.78	40.00	-20.22	-	-	peak
2	111.6398	27.81	-11.10	16.71	43.50	-26.79	-	-	peak
3	156.4258	29.72	-8.28	21.44	43.50	-22.06	-	-	peak
4	282.2701	28.48	-8.70	19.78	46.00	-26.22	-	-	peak
5	498.7302	29.84	-3.57	26.27	46.00	-19.73	-	-	peak
6	665.2609	31.80	-0.02	31.78	46.00	-14.22	-	-	peak

802.11a(worst case)

Test Channel	5745MHz(worst case)	Polarity:	Vertical
--------------	---------------------	-----------	----------




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	41.1580	28.65	-8.75	19.90	40.00	-20.10	-	-	peak
2	74.2696	31.13	-11.20	19.93	40.00	-20.07	-	-	peak
3	165.4716	28.91	-8.48	20.43	43.50	-23.07	-	-	peak
4	412.5394	29.11	-5.97	23.14	46.00	-22.86	-	-	peak
5	646.8217	31.25	-0.24	31.01	46.00	-14.99	-	-	peak
6	919.1315	31.31	3.03	34.34	46.00	-11.66	-	-	peak

Remark: '-' Means the test Degree and Height are not recorded by the test software and only show the worst case in the test report.


➤ Spurious Emission above 1GHz

802.11a- Restricted Bandedge			
Test Channel	5180MHz	Polarity:	Vertical(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	4500.000	55.60	-13.10	42.50	74.00	-31.50	-	-	peak
2	5150.000	73.82	-11.59	62.23	74.00	-11.77	-	-	peak

802.11a- Restricted Bandedge			
Test Channel	5180MHz	Polarity:	Vertical(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	4500.000	43.26	-13.10	30.16	54.00	-23.84	-	-	AVG
2	5150.000	50.39	-11.59	38.80	54.00	-15.20	-	-	AVG

802.11n-HT20- Restricted Bandedge			
Test Channel	5180MHz	Polarity:	Vertical(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	4500.000	56.20	-13.10	43.10	74.00	-30.90	-	-	peak
2	5150.000	73.60	-11.59	62.01	74.00	-11.99	-	-	peak

802.11n-HT20- Restricted Bandedge			
Test Channel	5180MHz	Polarity:	Vertical(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	4500.000	43.23	-13.10	30.13	54.00	-23.87	-	-	AVG
2	5150.000	47.89	-11.59	36.30	54.00	-17.70	-	-	AVG

802.11ac-VHT20- Restricted Bandedge			
Test Channel	5180MHz	Polarity:	Vertical(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	4500.000	56.94	-13.10	43.84	74.00	-30.16	-	-	peak
2	5150.000	68.60	-11.59	57.01	74.00	-16.99	-	-	peak

802.11ac-VHT20- Restricted Bandedge			
Test Channel	5180MHz	Polarity:	Vertical(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	4500.000	43.70	-13.10	30.60	54.00	-23.40	-	-	AVG
2	5150.000	45.70	-11.59	34.11	54.00	-19.89	-	-	AVG

802.11n-HT40- Restricted Bandedge			
Test Channel	5190MHz	Polarity:	Vertical(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	4500.000	56.22	-13.10	43.12	74.00	-30.88	-	-	peak
2	5150.000	66.86	-11.59	55.27	74.00	-18.73	-	-	peak

802.11n-HT40- Restricted Bandedge			
Test Channel	5190MHz	Polarity:	Vertical(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	4500.000	43.54	-13.10	30.44	54.00	-23.56	-	-	AVG
2	5150.000	45.07	-11.59	33.48	54.00	-20.52	-	-	AVG

802.11ac-VHT40- Restricted Bandedge			
Test Channel	5190MHz	Polarity:	Vertical(worst case)




No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	()	(cm)	
1	4500.000	55.86	-13.10	42.76	74.00	-31.24	-	-	peak
2	5150.000	65.99	-11.59	54.40	74.00	-19.60	-	-	peak

802.11ac-VHT40- Restricted Bandedge			
Test Channel	5190MHz	Polarity:	Vertical(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	4500.000	43.69	-13.10	30.59	54.00	-23.41	-	-	AVG
2	5150.000	45.76	-11.59	34.17	54.00	-19.83	-	-	AVG

802.11ac-HT80- Restricted Bandedge			
Test Channel	band 5.15-5.25GHz	Polarity:	Vertical(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	4500.000	55.63	-13.10	42.53	74.00	-31.47	-	-	peak
2	5150.000	66.17	-11.59	54.58	74.00	-19.42	-	-	peak

802.11ac-HT80- Restricted Bandedge			
Test Channel	band 5.15-5.25GHz	Polarity:	Vertical(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	4500.000	43.46	-13.10	30.36	54.00	-23.64	-	-	AVG
2	5150.000	45.02	-11.59	33.43	54.00	-20.57	-	-	AVG

802.11a- Restricted Bandedge			
Test Channel	5320MHz	Polarity:	Vertical(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	5351.543	69.35	-9.76	59.59	74.00	-14.41	-	-	peak

802.11a- Restricted Bandedge			
Test Channel	5320MHz	Polarity:	Vertical(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	5350.000	45.46	-9.75	35.71	54.00	-18.29	-	-	AVG

802.11n-HT20- Restricted Bandedge			
Test Channel	5320MHz	Polarity:	Vertical(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	5350.220	69.75	-9.75	60.00	74.00	-14.00	-	-	peak

802.11n-HT20- Restricted Bandedge			
Test Channel	5320MHz	Polarity:	Vertical(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	5350.000	47.59	-9.75	37.84	54.00	-16.16	-	-	AVG

802.11ac-VHT20- Restricted Bandedge			
Test Channel	5320MHz	Polarity:	Vertical(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	5351.323	73.92	-9.76	64.16	74.00	-9.84	-	-	peak

802.11ac-VHT20- Restricted Bandedge			
Test Channel	5320MHz	Polarity:	Vertical(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	5350.220	47.26	-9.75	37.51	54.00	-16.49	-	-	AVG

802.11n-HT40- Restricted Bandedge			
Test Channel	5310MHz	Polarity:	Vertical(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	5352.645	75.32	-9.76	65.56	74.00	-8.44	-	-	peak

802.11n-HT40- Restricted Bandedge			
Test Channel	5310MHz	Polarity:	Vertical(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	5350.220	53.10	-9.75	43.35	54.00	-10.65	-	-	AVG

802.11ac-VHT40- Restricted Bandedge			
Test Channel	5310MHz	Polarity:	Vertical(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	5355.731	75.86	-9.76	66.10	74.00	-7.90	-	-	peak

802.11ac-VHT40- Restricted Bandedge			
Test Channel	5310MHz	Polarity:	Vertical(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	5350.661	53.33	-9.75	43.58	54.00	-10.42	-	-	AVG

802.11ac-HT80- Restricted Bandedge			
Test Channel	5290MHz	Polarity:	Vertical(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	5350.882	69.36	-9.76	59.60	74.00	-14.40	-	-	peak

802.11ac-HT80- Restricted Bandedge			
Test Channel	5290MHz	Polarity:	Vertical(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	5350.000	49.46	-9.75	39.71	54.00	-14.29	-	-	AVG

802.11a- Restricted Bandedge			
Test Channel	5500MHz	Polarity:	Vertical(worst case)




No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	()	(cm)	
1	5453.166	70.68	-9.53	61.15	74.00	-12.85	-	-	peak

802.11a- Restricted Bandedge			
Test Channel	5500MHz	Polarity:	Vertical(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	5460.000	46.96	-9.54	37.42	54.00	-16.58	-	-	AVG

802.11n-HT20- Restricted Bandedge			
Test Channel	5500MHz	Polarity:	Vertical(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	5453.828	70.66	-9.54	61.12	74.00	-12.88	-	-	peak

802.11n-HT20- Restricted Bandedge			
Test Channel	5500MHz	Polarity:	Vertical(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	5460.000	47.41	-9.54	37.87	54.00	-16.13	-	-	AVG

802.11ac-VHT20- Restricted Bandedge			
Test Channel	5500MHz	Polarity:	Vertical(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	5452.505	68.46	-9.54	58.92	74.00	-15.08	-	-	peak

802.11ac-VHT20- Restricted Bandedge			
Test Channel	5500MHz	Polarity:	Vertical(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	5459.779	47.21	-9.54	37.67	54.00	-16.33	-	-	AVG

802.11n-HT40- Restricted Bandedge			
Test Channel	5510MHz	Polarity:	Vertical(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	5460.000	66.14	-9.54	56.60	74.00	-17.40	-	-	peak

802.11n-HT40- Restricted Bandedge			
Test Channel	5510MHz	Polarity:	Vertical(worst case)




No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	()	(cm)	
1	5458.236	48.67	-9.54	39.13	54.00	-14.87	-	-	AVG

802.11ac-VHT40- Restricted Bandedge			
Test Channel	5510MHz	Polarity:	Vertical(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	5459.780	69.14	-9.54	59.60	74.00	-14.40	-	-	peak

802.11ac-VHT40- Restricted Bandedge			
Test Channel	5510MHz	Polarity:	Vertical(worst case)




No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	()	(cm)	
1	5458.016	48.68	-9.54	39.14	54.00	-14.86	-	-	AVG

802.11ac-HT80- Restricted Bandedge			
Test Channel	5530MHz	Polarity:	Vertical(worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	5452.725	69.18	-9.53	59.65	74.00	-14.35	-	-	peak

802.11ac-HT80- Restricted Bandedge			
Test Channel	5530MHz	Polarity:	Vertical(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	5457.575	49.91	-9.54	40.37	54.00	-13.63	-	-	AVG

Note: The Restricted Bandedge was tested in Horizontal /Vertical and the worst case position data was reported.

Remark: ‘-’Means’ the test Degree and Height is not recorded by the test software and only show the worst case in the test report.


- For the frequency band 5.15-5.25GHz (802.11a) (Worst case)
- Harmonics And Spurious Emissions

Test Channel	5180MHz(Worst case)	Polarity:	Horizontal
--------------	---------------------	-----------	------------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	10360.000	49.59	-3.44	46.15	74.00	-27.85	-	-	peak

Test Channel	5180MHz(Worst case)	Polarity:	Vertical
--------------	---------------------	-----------	----------




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	10360.000	50.90	-3.44	47.46	74.00	-26.54	-	-	peak

Reference No.: WTX26X06185900W003


- For the frequency band 5.250-5.350GHz (802.11a) (Worst case)
- Harmonics And Spurious Emissions

Test Channel	5260MHz(Worst case)	Polarity:	Horizontal
--------------	---------------------	-----------	------------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	10520.000	50.16	-3.15	47.01	74.00	-26.99	-	-	peak

Test Channel	5260MHz(worst case)	Polarity:	Vertical
--------------	---------------------	-----------	----------




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	10520.000	49.89	-3.15	46.74	74.00	-27.26	-	-	peak

Reference No.: WTX26X06185900W003


- For the frequency band 5.470-5.725GHz (802.11a) (Worst case)
- Harmonics And Spurious Emissions

Test Channel	5500MHz(worst case)	Polarity:	Horizontal
--------------	---------------------	-----------	------------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	11000.000	50.02	-3.05	46.97	74.00	-27.03	-	-	peak

Test Channel	5500MHz(worst case)	Polarity:	Vertical
--------------	---------------------	-----------	----------




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	11000.000	49.68	-3.05	46.63	74.00	-27.37	-	-	peak

Reference No.: WTX26X06185900W003


- For the frequency band 5.725-5.850GHz (802.11a) (Worst case)
- Harmonics And Spurious Emissions

Test Channel	5745MHz(worst case)	Polarity:	Horizontal
--------------	---------------------	-----------	------------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	11490.000	50.37	-1.65	48.72	74.00	-25.28	-	-	peak

Test Channel	5745MHz(worst case)	Polarity:	Vertical
--------------	---------------------	-----------	----------



No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	()	(cm)	
1	11490.000	50.58	-1.65	48.93	74.00	-25.07	-	-	peak

Remark: '-'Means' the test Degree and Height are not recorded by the test software and only show the worst case in the test report.

➤ Out of Band edge for 5.15-5.25GHz(802.11a)

Test CH.	Test Segment	Result	Limit
	MHz	dBm/MHz	dBm/MHz
Lowest	Below 5150	-43.61	-27
Highest	Above 5350	-42.75	-27
Note: the data just list the worst cases			

➤ Out of Band edge 5150-5250MHz(802.11n HT20)

Test CH.	Test Segment	Result	Limit
	MHz	dBm/MHz	dBm/MHz
Lowest	Below 5150	-40.67	-27
Highest	Above 5350	-41.54	-27
Note: the data just list the worst cases			

➤ Out of Band edge 5150-5250MHz(802.11ac VHT20)

Test CH.	Test Segment	Result	Limit
	MHz	dBm/MHz	dBm/MHz
Lowest	Below 5150	-40.65	-27
Highest	Above 5350	-41.32	-27
Note: the data just list the worst cases			

➤ Out of Band edge for 5150-5250MHz(802.11n HT40)

Test CH.	Test Segment	Result	Limit
	MHz	dBm/MHz	dBm/MHz
Lowest	Below 5150	-39.29	-27
Highest	Above 5350	-38.45	-27
Note: the data just list the worst cases			

➤ Out of Band edge for 5150-5250MHz (802.11ac VHT40)

Test CH.	Test Segment	Result	Limit
	MHz	dBm/MHz	dBm/MHz
Lowest	Below 5150	-39.85	-27
Highest	Above 5350	-38.10	-27
Note: the data just list the worst cases			

➤ Out of Band edge for 5150-5250MHz(802.11ac VHT80)

Test CH.	Test Segment	Result	Limit
	MHz	dBm/MHz	dBm/MHz
Lowest	Below 5150	-37.24	-27
Highest	Above 5350	-36.51	-27
Note: the data just list the worst cases			

➤ Out of Band edge for 5250-5350MHz(802.11a)

Test CH.	Test Segment	Result	Limit
	MHz	dBm/MHz	dBm/MHz
Lowest	Below 5150	-42.12	-27
Highest	Above 5350	-41.75	-27
Note: the data just list the worst cases			

➤ Out of Band edge 5150-5250MHz(802.11n HT20)

Test CH.	Test Segment	Result	Limit
	MHz	dBm/MHz	dBm/MHz
Lowest	Below 5150	-40.67	-27
Highest	Above 5350	-41.54	-27
Note: the data just list the worst cases			

➤ Out of Band edge for 5250-5350MHz(802.11ac HT20)

Test CH.	Test Segment	Result	Limit
	MHz	dBm/MHz	dBm/MHz
Lowest	Below 5150	-41.12	-27
Highest	Above 5350	-42.59	-27
Note: the data just list the worst cases			

➤ Out of Band edge for 5250-5350MHz(802.11n HT40)

Test CH.	Test Segment	Result	Limit
	MHz	dBm/MHz	dBm/MHz
Lowest	Below 5150	-37.12	-27
Highest	Above 5350	-38.67	-27
Note: the data just list the worst cases			

➤ Out of Band edge for 5250-5350MHz(802.11ac VHT40)

Test CH.	Test Segment	Result	Limit
	MHz	dBm/MHz	dBm/MHz
Lowest	Below 5150	-37.65	-27
Highest	Above 5350	-38.98	-27
Note: the data just list the worst cases			

➤ Out of Band edge for 5250-5350MHz (802.11ac VHT80)

Test CH.	Test Segment	Result	Limit
	MHz	dBm/MHz	dBm/MHz
Lowest	Below 5150	-38.68	-27
Highest	Above 5350	-36.59	-27
Note: the data just list the worst cases			

➤ Out of Band edge for 5470-5725MHz(802.11a)

Test CH.	Test Segment	Result	Limit
	MHz	dBm/MHz	dBm/MHz
Lowest	Below 5470	-42.60	-27
Highest	Above 5725	-39.59	-27
Note: the data just list the worst cases			

➤ Out of Band edge for 5470-5725MHz(802.11n HT20)

Test CH.	Test Segment	Result	Limit
	MHz	dBm/MHz	dBm/MHz
Lowest	Below 5470	-38.57	-27
Highest	Above 5725	-39.20	-27
Note: the data just list the worst cases			

➤ Out of Band edge for 5470-5725MHz(802.11ac VHT20)

Test CH.	Test Segment	Result	Limit
	MHz	dBm/MHz	dBm/MHz
Lowest	Below 5470	-38.39	-27
Highest	Above 5725	-39.25	-27
Note: the data just list the worst cases			

➤ Out of Band edge for 5470-5725MHz(802.11n HT40)

Test CH.	Test Segment	Result	Limit
	MHz	dBm/MHz	dBm/MHz
Lowest	Below 5470	-35.59	-27
Highest	Above 5725	-37.36	-27
Note: the data just list the worst cases			

➤ Out of Band edge for 5470-5725MHz (802.11ac VHT40)

Test CH.	Test Segment	Result	Limit
	MHz	dBm/MHz	dBm/MHz
Lowest	Below 5470	-36.65	-27
Highest	Above 5725	-37.13	-27
Note: the data just list the worst cases			

➤ Out of Band edge for 5470-5725MHz (802.11ac VHT80)

Test CH.	Test Segment	Result	Limit
	MHz	dBm/MHz	dBm/MHz
Lowest	Below 5470	-39.24	-27
Highest	Above 5725	-37.85	-27
Note: the data just list the worst cases			

➤ Out of Band edge for 5725-5850MHz(802.11a)

Test CH.	Test Segment	Result	Limit
	MHz	dBm/MHz	dBm/MHz
Lowest	Below 5650	-46.16	-27
	5650 to 5700	-33.57	-27 to -17
	5700 to 5720	-27.38	-17 to 15.6
	5720 to 5725	-17.46	15.6 to 27
Highest	5850 to 5855	-14.39	27 to 15.6
	5855 to 5875	-21.21	15.6 to -17
	5875 to 5925	-33.85	-17 to -27
	Above 5925	-38.19	-27
Note: the data just list the worst cases			

➤ Out of Band edge for 5725-5850MHz(802.11n HT20)

Test CH.	Test Segment	Result	Limit
	MHz	dBm/MHz	dBm/MHz
Lowest	Below 5650	-46.71	-27
	5650 to 5700	-33.19	-27 to -17
	5700 to 5720	-27.25	-17 to 15.6
	5720 to 5725	-17.36	15.6 to 27
Highest	5850 to 5855	-14.48	27 to 15.6
	5855 to 5875	-21.17	15.6 to -17
	5875 to 5925	-33.59	-17 to -27
	Above 5925	-38.24	-27
Note: the data just list the worst cases			

➤ Out of Band edge for 5725-5850MHz(802.11ac VHT20)

Test CH.	Test Segment	Result	Limit
	MHz	dBm/MHz	dBm/MHz
Lowest	Below 5650	-46.85	-27
	5650 to 5700	-33.70	-27 to -17
	5700 to 5720	-27.39	-17 to 15.6
	5720 to 5725	-17.24	15.6 to 27
Highest	5850 to 5855	-14.35	27 to 15.6
	5855 to 5875	-21.60	15.6 to -17
	5875 to 5925	-33.12	-17 to -27
	Above 5925	-38.77	-27
Note: the data just list the worst cases			

➤ Out of Band edge for 5725-5850MHz(802.11n HT40)

Test CH.	Test Segment	Result	Limit
	MHz	dBm/MHz	dBm/MHz
Lowest	Below 5715	-41.28	-27
	5715 to 5725	-35.54	-17
Highest	5850 to 5860	-37.30	-17
	Above 5860	-38.29	-27
Note: the data just list the worst cases			

➤ Out of Band edge for 5725-5850MHz(802.11ac VHT40)

Test CH.	Test Segment	Result	Limit
	MHz	dBm/MHz	dBm/MHz
Lowest	Below 5650	-46.80	-27
	5650 to 5700	-33.12	-27 to -17
	5700 to 5720	-27.65	-17 to 15.6
	5720 to 5725	-17.34	15.6 to 27
Highest	5850 to 5855	-14.28	27 to 15.6
	5855 to 5875	-21.16	15.6 to -17
	5875 to 5925	-33.45	-17 to -27
	Above 5925	-38.70	-27
Note: the data just list the worst cases			

➤ Out of Band edge for 5725-5850MHz(802.11ac VHT80)

Test CH.	Test Segment	Result	Limit
	MHz	dBm/MHz	dBm/MHz
Lowest	Below 5650	-46.16	-27
	5650 to 5700	-33.72	-27 to -17
	5700 to 5720	-27.65	-17 to 15.6
	5720 to 5725	-17.34	15.6 to 27
Highest	5850 to 5855	-14.70	27 to 15.6
	5855 to 5875	-22.12	15.6 to -17
	5875 to 5925	-33.69	-17 to -27
	Above 5925	-38.24	-27
Note: the data just list the worst cases			

Note: Testing is carried out with frequency rang 9kHz to 40Ghz, other than listed in the table above are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

Conducted Spurious Emission Please refer to Appendix F

9. Frequency Stability

9.1 Standard Applicable

According to §15.407(g), manufacturers of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified in the users manual.

9.2 Test Procedure

According to §2.1055, the following test procedure was performed.

The Frequency Stability is measured directly with a Frequency Domain Analyzer. Frequency Deviation in ppm is calculated from the measured peak to peak value.

The Carrier Frequency Stability over Power Supply Voltage and over Temperature is measured with a Frequency Domain Analyzer in histogram mode.

9.3 Summary of Test Results/Plots

Please refer to Appendix G


10. Conducted Emissions

10.1 Test Procedure

The setup of EUT is according with per ANSI C63.10-2020 measurement procedure. The specification used was with the FCC Part 15.207 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40cm long in the middle. The spacing between the peripherals was 10cm.

10.2 Basic Test Setup Block Diagram




10.3 Test Receiver Setup

During the conducted emission test, the test receiver was set with the following configurations:

Start Frequency	150kHz
Stop Frequency	30MHz
Sweep Speed	Auto
IF Bandwidth.....	10kHz
Quasi-Peak Adapter Bandwidth	9kHz
Quasi-Peak Adapter Mode	Normal


10.4 Summary of Test Results/Plots

Test Mode	Communication	AC120V 60Hz	Polarity:	Neutral
-----------	---------------	-------------	-----------	---------



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.1500	33.26	9.43	42.69	65.99	-23.30	QP
2	0.1500	18.92	9.43	28.35	55.99	-27.64	AVG
3	0.2100	18.80	9.63	28.43	53.20	-24.77	AVG
4	0.2260	33.17	9.63	42.80	62.59	-19.79	QP
5	0.2660	32.87	9.63	42.50	61.24	-18.74	QP
6	0.2860	17.30	9.63	26.93	50.64	-23.71	AVG
7	0.6020	15.20	9.69	24.89	46.00	-21.11	AVG
8	0.6740	29.81	9.73	39.54	56.00	-16.46	QP
9*	4.4220	32.80	9.50	42.30	56.00	-13.70	QP
10	4.6979	16.92	9.54	26.46	46.00	-19.54	AVG
11	8.1459	19.50	9.80	29.30	50.00	-20.70	AVG
12	10.1820	34.50	9.80	44.30	60.00	-15.70	QP

Test Mode	Communication	AC120V 60Hz	Polarity:	Line
-----------	---------------	-------------	-----------	------



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.1539	39.00	9.45	48.45	65.78	-17.33	QP
2	0.1539	19.42	9.45	28.87	55.78	-26.91	AVG
3	0.2140	22.41	9.63	32.04	53.04	-21.00	AVG
4	0.2180	36.06	9.63	45.69	62.89	-17.20	QP
5	0.2900	34.69	9.63	44.32	60.52	-16.20	QP
6	0.3460	19.34	9.63	28.97	49.06	-20.09	AVG
7	0.9020	20.06	9.75	29.81	46.00	-16.19	AVG
8	0.9260	34.37	9.75	44.12	56.00	-11.88	QP
9	6.5740	35.59	9.75	45.34	60.00	-14.66	QP
10	7.2180	22.55	9.79	32.34	50.00	-17.66	AVG
11	9.3460	23.18	9.81	32.99	50.00	-17.01	AVG
12*	10.4060	38.34	9.79	48.13	60.00	-11.87	QP

APPENDIX SUMMARY

Project No.	WTX26X06185900W003	Test Engineer	BAldi
Start date	2026/7/13	Finish date	2026/7/20
Temperature	22.6℃	Humiditdy	57%
RF specifications	WiFi-5G		

APPENDIX	Description of Test Item	Result
A	Emission Bandwidth& Occupied channel bandwidth& Min emission bandwidth	Compliant
B	Duty Cycle	Compliant
C	Maximum conducted output power	Compliant
D	Maximum power spectral density	Compliant
E	Band edge measurements	Compliant
F	Conducted Spurious Emission	Compliant
G	Frequency Stability	Compliant

Appendix A1: Emission Bandwidth**Test Result**

TestMode	Antenna	Frequency[MHz]	26db EBW [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
11A	Ant1	5180	22.920	5169.040	5191.960	---	---
11A	Ant1	5200	21.600	5188.720	5210.320	---	---
11A	Ant1	5240	20.600	5229.640	5250.240	---	---
11A	Ant1	5260	21.400	5249.160	5270.560	---	---
11A	Ant1	5280	20.360	5269.600	5289.960	---	---
11A	Ant1	5320	20.320	5310.120	5330.440	---	---
11A	Ant1	5500	23.600	5489.440	5513.040	---	---
11A	Ant1	5580	27.920	5567.040	5594.960	---	---
11A	Ant1	5700	24.360	5687.800	5712.160	---	---
11A	Ant1	5745	22.800	5733.600	5756.400	---	---
11A	Ant1	5785	20.640	5774.360	5795.000	---	---
11A	Ant1	5825	22.000	5814.680	5836.680	---	---
11N20SISO	Ant1	5180	20.040	5170.040	5190.080	---	---
11N20SISO	Ant1	5200	21.080	5189.240	5210.320	---	---
11N20SISO	Ant1	5240	21.360	5228.760	5250.120	---	---
11N20SISO	Ant1	5260	20.080	5249.960	5270.040	---	---
11N20SISO	Ant1	5280	21.000	5269.120	5290.120	---	---
11N20SISO	Ant1	5320	20.600	5309.520	5330.120	---	---
11N20SISO	Ant1	5500	20.200	5489.880	5510.080	---	---
11N20SISO	Ant1	5580	20.520	5569.440	5589.960	---	---
11N20SISO	Ant1	5700	20.640	5689.480	5710.120	---	---
11N20SISO	Ant1	5745	20.520	5734.640	5755.160	---	---
11N20SISO	Ant1	5785	21.640	5773.560	5795.200	---	---
11N20SISO	Ant1	5825	22.440	5812.720	5835.160	---	---
11N40SISO	Ant1	5190	40.640	5169.520	5210.160	---	---
11N40SISO	Ant1	5230	40.320	5209.920	5250.240	---	---
11N40SISO	Ant1	5270	40.320	5249.920	5290.240	---	---
11N40SISO	Ant1	5310	40.800	5289.440	5330.240	---	---
11N40SISO	Ant1	5510	40.720	5489.440	5530.160	---	---
11N40SISO	Ant1	5550	40.640	5529.680	5570.320	---	---
11N40SISO	Ant1	5670	40.000	5650.080	5690.080	---	---
11N40SISO	Ant1	5755	40.800	5734.440	5775.240	---	---
11N40SISO	Ant1	5795	40.400	5774.680	5815.080	---	---
11AC20SISO	Ant1	5180	20.280	5169.880	5190.160	---	---
11AC20SISO	Ant1	5200	20.280	5189.920	5210.200	---	---
11AC20SISO	Ant1	5240	20.200	5229.960	5250.160	---	---
11AC20SISO	Ant1	5260	20.160	5250.000	5270.160	---	---

11AC20SISO	Ant1	5280	20.080	5270.080	5290.160	---	---
11AC20SISO	Ant1	5320	20.080	5310.000	5330.080	---	---
11AC20SISO	Ant1	5500	19.960	5490.040	5510.000	---	---
11AC20SISO	Ant1	5580	20.000	5569.960	5589.960	---	---
11AC20SISO	Ant1	5700	20.040	5690.000	5710.040	---	---
11AC20SISO	Ant1	5745	20.040	5734.920	5754.960	---	---
11AC20SISO	Ant1	5785	20.120	5774.960	5795.080	---	---
11AC20SISO	Ant1	5825	20.240	5815.080	5835.320	---	---
11AC40SISO	Ant1	5190	40.160	5170.080	5210.240	---	---
11AC40SISO	Ant1	5230	40.080	5210.080	5250.160	---	---
11AC40SISO	Ant1	5270	39.760	5250.400	5290.160	---	---
11AC40SISO	Ant1	5310	39.840	5290.080	5329.920	---	---
11AC40SISO	Ant1	5510	40.080	5489.920	5530.000	---	---
11AC40SISO	Ant1	5550	40.320	5529.840	5570.160	---	---
11AC40SISO	Ant1	5670	40.240	5650.000	5690.240	---	---
11AC40SISO	Ant1	5755	39.600	5735.240	5774.840	---	---
11AC40SISO	Ant1	5795	40.320	5774.840	5815.160	---	---
11AC80SISO	Ant1	5210	80.320	5170.320	5250.640	---	---
11AC80SISO	Ant1	5290	80.480	5250.000	5330.480	---	---
11AC80SISO	Ant1	5530	80.480	5489.840	5570.320	---	---
11AC80SISO	Ant1	5610	81.120	5569.840	5650.960	---	---
11AC80SISO	Ant1	5775	80.800	5734.680	5815.480	---	---

Test Graphs




11A-Ant1-5180




11A-Ant1-5200



11A-Ant1-5240



11A-Ant1-5260



11A-Ant1-5280



11A-Ant1-5320



11A-Ant1-5500



11A-Ant1-5580



11A-Ant1-5700



11A-Ant1-5745




11A-Ant1-5785



11A-Ant1-5825




11N20SISO-Ant1-5180




11N20SISO-Ant1-5200




11N20SISO-Ant1-5240



11N20SISO-Ant1-5260




11N20SISO-Ant1-5280




11N20SISO-Ant1-5320




11N20SISO-Ant1-5500




11N20SISO-Ant1-5580




11N20SISO-Ant1-5700



11N20SISO-Ant1-5745




11N20SISO-Ant1-5785




11N20SISO-Ant1-5825



11N40SISO-Ant1-5190




11N40SISO-Ant1-5230




11N40SISO-Ant1-5270



11N40SISO-Ant1-5310




11N40SISO-Ant1-5510




11N40SISO-Ant1-5550




11N40SISO-Ant1-5670




11N40SISO-Ant1-5755




11N40SISO-Ant1-5795




11AC20SISO-Ant1-5180




11AC20SISO-Ant1-5200




11AC20SISO-Ant1-5240




11AC20SISO-Ant1-5260




11AC20SISO-Ant1-5280




11AC20SISO-Ant1-5320



11AC20SISO-Ant1-5500




11AC20SISO-Ant1-5580




11AC20SISO-Ant1-5700




11AC20SISO-Ant1-5745



11AC20SISO-Ant1-5785



11AC20SISO-Ant1-5825



11AC40SISO-Ant1-5190



11AC40SISO-Ant1-5230



11AC40SISO-Ant1-5270