


RF TEST REPORT



Report No.: 16071343-FCC-R2-V1

Supersede Report No.: N/A

Applicant	BLU Products, Inc.	
Product Name	smartphone	
Model No.	ADVANCE 4.0 L3	
Serial No.	N/A	
Test Standard	FCC Part 15.247: 2015, ANSI C63.10: 2013	
Test Date	Dec 3 to Dec 30, 2016	
Issue Date	Jan 9 , 2017	
Test Result	☒ Pass ☐ Fail	
Equipment complied with the specification	☒	
Equipment did not comply with the specification	☐	
		
Loren Luo Test Engineer	David Huang Checked By	
This test report may be reproduced in full only Test result presented in this test report is applicable to the tested sample only		

Issued by:

SIEMIC (SHENZHEN-CHINA) LABORATORIES

Zone A, Floor 1, Building 2 Wan Ye Long Technology Park

South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108

Phone: +86 0755 2601 4629801 Email: China@siemic.com.cn

Laboratories Introduction

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.



In addition to testing and certification, SIEMIC provides initial design reviews and compliance management throughout a project. Our extensive experience with China, Asia Pacific, North America, European, and International compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the global markets.

Accreditations for Conformity Assessment

Country/Region	Scope
USA	EMC, RF/Wireless, SAR, Telecom
Canada	EMC, RF/Wireless, SAR, Telecom
Taiwan	EMC, RF, Telecom, SAR, Safety
Hong Kong	RF/Wireless, SAR, Telecom
Australia	EMC, RF, Telecom, SAR, Safety
Korea	EMI, EMS, RF, SAR, Telecom, Safety
Japan	EMI, RF/Wireless, SAR, Telecom
Singapore	EMC, RF, SAR, Telecom
Europe	EMC, RF, SAR, Telecom, Safety

Test Report	16071343-FCC-R2-V1-V1
Page	3 of 59

This page has been left blank intentionally.

CONTENTS

1. REPORT REVISION HISTORY	5
2. CUSTOMER INFORMATION	5
3. TEST SITE INFORMATION	5
4. EQUIPMENT UNDER TEST (EUT) INFORMATION	6
5. TEST SUMMARY	8
6. MEASUREMENTS, EXAMINATION AND DERIVED RESULTS	9
6.1 ANTENNA REQUIREMENT	9
6.2 CHANNEL SEPARATION	10
6.3 20DB BANDWIDTH.....	14
6.4 PEAK OUTPUT POWER.....	18
6.5 NUMBER OF HOPPING CHANNEL.....	22
6.6 TIME OF OCCUPANCY (DWEIL TIME).....	24
6.7 BAND EDGE & RESTRICTED BAND	28
6.8 AC POWER LINE CONDUCTED EMISSIONS.....	36
6.9 RADIATED SPURIOUS EMISSIONS & RESTRICTED BAND	42
ANNEX A. TEST INSTRUMENT	48
ANNEX B. EUT AND TEST SETUP PHOTOGRAPHS	49
ANNEX C. TEST SETUP AND SUPPORTING EQUIPMENT	54
ANNEX D. USER MANUAL / BLOCK DIAGRAM / SCHEMATICS / PARTLIST	58
ANNEX E. DECLARATION OF SIMILARITY.....	59

1. Report Revision History

Report No.	Report Version	Description	Issue Date
16071343-FCC-R2	NONE	Original	Dec 30 , 2016
16071343-FCC-R2-V1	V1	Corrected output power of Bluetooth	Jan 9 , 2017

2. Customer information

Applicant Name	BLU Products, Inc.
Applicant Add	10814 NW 33rd St # 100 Doral, FL 33172
Manufacturer	BLU Products, Inc.
Manufacturer Add	10814 NW 33rd St # 100 Doral, FL 33172

3. Test site information

Lab performing tests	SIEMIC (Shenzhen-China) LABORATORIES
Lab Address	Zone A, Floor 1, Building 2 Wan Ye Long Technology Park South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108
FCC Test Site No.	718246
IC Test Site No.	4842E-1
Test Software	Radiated Emission Program-To Shenzhen v2.0

4. Equipment under Test (EUT) Information

Description of EUT: smartphone

Main Model: ADVANCE 4.0 L3

Serial Model: N/A

Date EUT received: Dec 2, 2016

Test Date(s): Dec 3 to Dec 30, 2016

Equipment Category : DSS

Antenna Gain:

- GSM850: -0.5dBi
- PCS1900:0.5dBi
- UMTS-FDD Band V: -0.5dBi
- UMTS-FDD Band IV: 0.5dBi
- UMTS-FDD Band II: 0.5dBi
- WIFI: 1.6dBi
- Bluetooth:1.6dBi
- GPS: 0.5dBi

Antenna Type: PIFA antenna

Type of Modulation:

- GSM / GPRS: GMSK
- EGPRS: GMSK,8PSK
- UMTS-FDD: QPSK
- 802.11b/g/n: DSSS, OFDM
- Bluetooth: GFSK, π /4DQPSK, 8DPSK
- GPS:BPSK

RF Operating Frequency (ies):

- GSM850 TX: 824.2 ~ 848.8 MHz; RX: 869.2 ~ 893.8 MHz
- PCS1900 TX: 1850.2 ~ 1909.8 MHz; RX: 1930.2 ~ 1989.8 MHz
- UMTS-FDD Band V TX: 826.4 ~ 846.6 MHz; RX: 871.4 ~ 891.6 MHz
- UMTS-FDD Band IV TX:1712.4 ~ 1752.6 MHz;
RX : 2112.4 ~ 2152.6 MHz
- UMTS-FDD Band II TX:1852.4 ~ 1907.6 MHz;
RX: 1932.4 ~ 1987.6 MHz

Test Report	16071343-FCC-R2-V1-V1
Page	7 of 59

WIFI: 802.11b/g/n(20M): 2412-2462 MHz

Bluetooth& BLE: 2402-2480 MHz

GPS: 1575.42 MHz

Max. Output Power: 5.908dBm

GSM 850: 124CH

PCS1900: 299CH

UMTS-FDD Band V: 102CH

UMTS-FDD Band IV: 202CH

UMTS-FDD Band II: 277CH

WIFI :802.11b/g/n(20M): 11CH

Bluetooth: 79CH

GPS:1CH

Port: USB Port, Earphone Port

Adapter:

Model: US-BM-0700

Input: AC100-240V, 50/60Hz,0.12A

Output: DC 5.0V-0.7A

Input Power: Battery:

Model: C535143130T

Voltage: 3.7V

Battery Capacity: 1300mAh , 4.81Wh

Charging limit voltage: 4.35V

Trade Name : BLU

GPRS/EGPRS Multi-slot class 8/10/12

FCC ID: YHLBLUAD4L3

5. Test Summary

The product was tested in accordance with the following specifications.

All testing has been performed according to below product classification:

FCC Rules	Description of Test	Result
§15.203	Antenna Requirement	Compliance
§15.247(a)(1)	Channel Separation	Compliance
§15.247(a)(1)	20 dB Bandwidth	Compliance
§15.247(b)(1)	Peak Output Power	Compliance
§15.247(a)(1)(iii)	Number of Hopping Channel	Compliance
§15.247(a)(1)(iii)	Time of Occupancy (Dwell Time)	Compliance
§15.247(d)	Band Edge& Restricted Band	Compliance
§15.207(a)	AC Line Conducted Emissions	Compliance
§15.205, §15.209, §15.247(d)	Radiated Emissions& Restricted Band	Compliance

Measurement Uncertainty

Emissions		
Test Item	Description	Uncertainty
Band Edge and Radiated Spurious Emissions	Confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2 (for EUTs < 0.5m X 0.5m X 0.5m)	+5.6dB/-4.5dB
-	-	-

6. Measurements, Examination And Derived Results

6.1 Antenna Requirement

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.

Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Antenna Connector Construction

The EUT has 2 antennas:

A permanently attached Metallic antenna for Bluetooth/BLE/WIFI/GPS, the gain is 1.6dBi for Bluetooth/BLE/WIFI/GPS.

A permanently attached PIFA antenna for GSM/PCS/UMTS, the gain is -0.5dBi for GSM850, 0.5dBi for PCS1900,-0.5dBi for UMTS-FDD Band V, 0.5dBi for UMTS-FDD Band II, 0.5dBi for UMTS-FDD Band IV.


The antenna meets up with the ANTENNA REQUIREMENT.

Result: Compliance.

6.2 Channel Separation

Temperature	23 °C
Relative Humidity	53%
Atmospheric Pressure	1010mbar
Test date :	Dec 12, 2016
Tested By :	Loren Luo

Requirement(s):

Spec	Item	Requirement	Applicable
§ 15.247(a)(1)	a)	Channel Separation < 20dB BW and 20dB BW < 25KHz ; Channel Separation Limit=25KHz Chanel Separation < 20dB BW and 20dB BW > 25kHz ; Channel Separation Limit=2/3 20dB BW	
Test Setup	 Spectrum Analyzer EUT		
Test Procedure	The test follows FCC Public Notice DA 00-705 Measurement Guidelines. Use the following spectrum analyzer settings: - The EUT must have its hopping function enabled - Span = wide enough to capture the peaks of two adjacent channels - Resolution (or IF) Bandwidth (RBW) ≥ 1% of the span - Video (or Average) Bandwidth (VBW) ≥ RBW - Sweep = auto - Detector function = peak - Trace = max hold - Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels. The limit is specified in one of the subparagraphs of this Section. Submit this plot.		

Remark	
Result	☒ Pass ☐ Fail

Test Data ☒ Yes ☐ N/A


Test Plot ☒ Yes (See below) ☐ N/A


Channel Separation measurement result

Type/ Modulation	CH	CH Frequency (MHz)	CH Separation (MHz)	Limit (MHz)	Result
CH Separation GFSK	Low Channel	2402	1.005	0.668	Pass
	Adjacency Channel	2403			
	Mid Channel	2440	1.005	0.695	Pass
	Adjacency Channel	2441			
	High Channel	2480	1.005	0.692	Pass
	Adjacency Channel	2479			
CH Separation $\pi/4$ DQPSK	Low Channel	2402	1.005	0.847	Pass
	Adjacency Channel	2403			
	Mid Channel	2440	1.005	0.865	Pass
	Adjacency Channel	2441			
	High Channel	2480	1.005	0.865	Pass
	Adjacency Channel	2479			
CH Separation 8DPSK	Low Channel	2402	1.005	0.860	Pass
	Adjacency Channel	2403			
	Mid Channel	2440	1.005	0.863	Pass
	Adjacency Channel	2441			
	High Channel	2480	1.005	0.865	Pass
	Adjacency Channel	2479			


Test Plots

Channel Separation measurement result






8DPSK - Low Channel



8DPSK - Middle Channel




8DPSK - High Channel

6.3 20dB Bandwidth

Temperature	23 °C
Relative Humidity	53%
Atmospheric Pressure	1010mbar
Test date :	Dec 12, 2016
Tested By :	Loren Luo

Requirement(s):

Spec	Item	Requirement	Applicable
§15.247(a) (1)	a)	Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.	☒
Test Setup	 Spectrum Analyzer EUT		
Test Procedure	The test follows FCC Public Notice DA 00-705 Measurement Guidelines. Use the following spectrum analyzer settings: - Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hopping channel - RBW ≥ 1% of the 20 dB bandwidth - VBW ≥ RBW - Sweep = auto - Detector function = peak - Trace = max hold. - The EUT should be transmitting at its maximum data rate. Allow the trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. Use the marker-delta function to measure 20 dB down one side of the emission. Reset the marker-delta function, and move the marker to the other side of the emission, until it is (as close as possible to) even with the reference		

Test Report	16071343-FCC-R2-V1-V1
Page	15 of 59

	marker level. The marker-delta reading at this point is the 20 dB bandwidth of the emission. If this value varies with different modes of operation (e.g., data rate, modulation format, etc.), repeat this test for each variation. The limit is specified in one of the subparagraphs of this Section. Submit this plot(s).
Remark	
Result	☒ Pass ☐ Fail

Test Data ☒ Yes ☐ N/A


Test Plot ☒ Yes (See below) ☐ N/A


Measurement result

Modulation	CH	CH Frequency (MHz)	20dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)
GFSK	Low	2402	1.002	0.9056
	Mid	2441	1.042	0.9036
	High	2480	1.038	0.9054
$\pi/4$ DQPSK	Low	2402	1.270	1.1366
	Mid	2441	1.298	1.1694
	High	2480	1.297	1.1672
8-DPSK	Low	2402	1.290	1.1781
	Mid	2441	1.294	1.1725
	High	2480	1.297	1.1695


Test Plots

20dB Bandwidth measurement result






8DPSK - Low Channel



8DPSK - Middle Channel




8DPSK - High Channel

6.4 Peak Output Power

Temperature	23 °C
Relative Humidity	53%
Atmospheric Pressure	1010mbar
Test date :	Dec 12, 2016
Tested By :	Loren Luo

Requirement(s):

Spec	Item	Requirement	Applicable
§15.247(b) (3)	a)	FHSS in 2400-2483.5MHz with ≥ 75 channels: ≤ 1 Watt	☒
	b)	FHSS in 5725-5850MHz: ≤ 1 Watt	☐
	c)	For all other FHSS in the 2400-2483.5MHz band: ≤ 0.125 Watt.	☒
	d)	FHSS in 902-928MHz with ≥ 50 channels: ≤ 1 Watt	☐
	e)	FHSS in 902-928MHz with ≥ 25 & <50 channels: ≤ 0.25 Watt	☐
	f)	DTS in 902-928MHz, 2400-2483.5MHz: ≤ 1 Watt	☐

Test Setup	 Spectrum Analyzer EUT
------------	--

Test Procedure	The test follows FCC Public Notice DA 00-705 Measurement Guidelines. Use the following spectrum analyzer settings: - Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel - RBW > the 20 dB bandwidth of the emission being measured - VBW $\geq$ RBW - Sweep = auto - Detector function = peak - Trace = max hold - Allow the trace to stabilize.
----------------	--

Test Report	16071343-FCC-R2-V1-V1
Page	19 of 59

	Use the marker-to-peak function to set the marker to the peak of the emission. The indicated level is the peak output power (see the note above regarding external attenuation and cable loss). The limit is specified in one of the subparagraphs of this Section. Submit this plot. A peak responding power meter may be used instead of a spectrum analyzer.
Remark	
Result	☒ Pass ☐ Fail

Test Data ☒ Yes ☐ N/A


Test Plot ☒ Yes (See below) ☐ N/A


Peak Output Power measurement result

Type	Modulation	CH	Frequency (MHz)	Conducted Power (dBm)	Limit (mW)	Result
Output power	GFSK	Low	2402	4.952	125	Pass
		Mid	2441	4.580	125	Pass
		High	2480	4.721	125	Pass
	$\pi/4$ DQPSK	Low	2402	5.721	125	Pass
		Mid	2441	5.882	125	Pass
		High	2480	5.451	125	Pass
	8-DPSK	Low	2402	5.772	125	Pass
		Mid	2441	5.908	125	Pass
		High	2480	5.557	125	Pass


Test Plots

Output Power measurement result






8DPSK Output power - Low CH 2402



8DPSK Output power - Mid CH 2441




8DPSK Output power - High CH 2480

6.5 Number of Hopping Channel

Temperature	23 °C
Relative Humidity	53%
Atmospheric Pressure	1010mbar
Test date :	Dec 12, 2016
Tested By :	Loren Luo

Requirement(s):

Spec	Item	Requirement	Applicable
§15.247(a) (1)(iii)	a)	FHSS in 2400-2483.5MHz ≥ 15 channels	☒
Test Setup	 Spectrum Analyzer EUT		
Test Procedure	The test follows FCC Public Notice DA 00-705 Measurement Guidelines. <u>Use the following spectrum analyzer settings:</u> The EUT must have its hopping function enabled. - Span = the frequency band of operation - RBW ≥ 1% of the span - VBW ≥ RBW - Sweep = auto - Detector function = peak - Trace = max hold - Allow trace to fully stabilize. - It may prove necessary to break the span up to sections, in order to clearly show all of the hopping frequencies. The limit is specified in one of the subparagraphs of this Section. Submit this plot(s).		
Remark			
Result	☒ Pass ☐ Fail		

Test Data ☒ Yes ☐ N/A


Test Plot ☒ Yes (See below) ☐ N/A

Number of Hopping Channel measurement result

Type	Modulation	Frequency Range	Number of Hopping Channel	Limit
Number of Hopping Channel	GFSK	2400-2483.5	78	15
	$\pi/4$ DQPSK	2400-2483.5	78	15
	8-DPSK	2400-2483.5	78	15

Test Plots


Number of Hopping Channels measurement result



6.6 Time of Occupancy (Dwell Time)

Temperature	23 °C
Relative Humidity	53%
Atmospheric Pressure	1010mbar
Test date :	Dec 12, 2016
Tested By :	Loren Luo

Requirement(s):

Spec	Item	Requirement	Applicable
§15.247(a) (1)(iii)	a)	Dwell Time < 0.4s	☒
Test Setup	 Spectrum Analyzer EUT		
Test Procedure	The test follows FCC Public Notice DA 00-705 Measurement Guidelines. <u>Use the following spectrum analyzer</u> - Span = zero span, centered on a hopping channel - RBW = 1 MHz - VBW ≥ RBW - Sweep = as necessary to capture the entire dwell time per hopping channel - Detector function = peak - Trace = max hold - use the marker-delta function to determine the dwell time		
Remark			
Result	☒ Pass ☐ Fail		


Test Data ☒ Yes ☐ N/A


Test Plot ☒ Yes (See below) ☐ N/A

Type	Modulation	CH	Pulse Width (ms)	Dwell Time (ms)	Limit (ms)	Result
Dwell Time	GFSK	Low	2.925	312.000	400	Pass
		Mid	2.925	312.000	400	Pass
		High	2.925	312.000	400	Pass
	$\pi/4$ DQPSK	Low	2.925	312.000	400	Pass
		Mid	2.925	312.000	400	Pass
		High	2.925	312.000	400	Pass
	8-DPSK	Low	2.950	314.667	400	Pass
		Mid	2.950	314.667	400	Pass
		High	2.925	312.000	400	Pass
Note: Dwell time=Pulse Time (ms) $\times$ (1600 $\div$ 6 $\div$ 79) $\times$ 31.6						


Test Plots

Dwell Time measurement result






8DPSK - Low CH 2402



8DPSK - Mid CH 2441




8DPSK - High CH 2480

6.7 Band Edge & Restricted Band

Temperature	24 °C
Relative Humidity	51%
Atmospheric Pressure	1027mbar
Test date :	Dec 27, 2016
Tested By :	Loren Luo

Requirement(s):

Spec	Item	Requirement	Applicable
§15.247(a) (1)(iii)	a)	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.	☒
Test Setup			
Test Procedure	The test follows FCC Public Notice DA 00-705 Measurement Guidelines. Radiated Method Only 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator. 2. Position the EUT without connection to measurement instrument. Put it on the Rotated table and turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range,		

Test Report	16071343-FCC-R2-V1-V1
Page	29 of 59


	and make sure the instrument is operated in its linear range. - 3. First, set both RBW and VBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100kHz bandwidth from band edge, check the emission of EUT, if pass then set Spectrum Analyzer as below: a. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasiy Peak detection at frequency below 1GHz. b. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz with Peak detection for Peak measurement at frequency above 1GHz. c. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz with Peak detection for Average Measurement as below at frequency above 1GHz. - 4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency. - 5. Repeat above procedures until all measured frequencies were complete.
Remark	
Result	☒ Pass ☐ Fail

Test Data ☐ Yes ☒ N/A

Test Plot ☒ Yes (See below) ☐ N/A


Test Plots

GFSK Mode:




GFSK-Hopping Left Side-PK

Note: F1 is frequency 2400MHz



GFSK-Hopping Right Side-PK



Note: F1 is frequency 2483.5MHz



GFSK-Hopping Left Side-AV


Note: (no need if PK value less than the AV limit)

GFSK-Hopping Right Side-AV




GFSK-Left Side-PK

Note: F1 is frequency 2400MHz



GFSK-Right Side-PK



Note: F1 is frequency 2483.5MHz



GFSK-Left Side-AV


GFSK-Right Side-AV

$\pi/4$ DQPSK Mode:




$\pi/4$ DQPSK-Hopping Left Side-PK

Note: F1 is frequency 2400MHz




$\pi/4$ DQPSK-Hopping Right Side-PK

Note: F1 is frequency 2483.5MHz




$\pi/4$ DQPSK-Hopping Left-AV

$\pi/4$ DQPSK-Hopping Right-AV



Date: 27.DEC.2016 12:55:29




Date: 27.DEC.2016 14:01:50

$\pi/4$ DQPSK-Left Side-PK


Note: F1 is frequency 2400MHz

$\pi/4$ DQPSK-Right Side-PK

Note: F1 is frequency 2483.5MHz



Date: 27.DEC.2016 12:56:07




Date: 27.DEC.2016 14:03:17

$\pi/4$ DQPSK-Left Side-AV


$\pi/4$ DQPSK-Right Side-AV

8-DPSK Mode:




8DPSK-Hopping Left Side-PK

Note: F1 is frequency 2400MHz




8DPSK-Hopping Right Side-PK


Note: F1 is frequency 2483.5MHz




8DPSK-Hopping Left-AV



8DPSK-Hopping Right-AV




Date: 27.DEC.2016 13:00:59




Date: 27.DEC.2016 13:58:40

8DPSK-Left Side-PK

Note: F1 is frequency 2400MHz



Date: 27.DEC.2016 13:07:39



Date: 27.DEC.2016 13:57:07

8DPSK-Left Side-AV


8DPSK-Right Side-AV

6.8 AC Power Line Conducted Emissions

Temperature	25 °C
Relative Humidity	53%
Atmospheric Pressure	1020mbar
Test date :	Dec 20, 2016
Tested By :	Loren Luo

Requirement(s):

Spec	Item	Requirement	Applicable		
47CFR§15.207, RSS210 (A8.1)	a)	For Low-power radio-frequency devices that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 [mu]H/50 ohms line impedance stabilization network (LISN). The lower limit applies at the boundary between the frequencies ranges.	☒		
		Frequency ranges (MHz)		Limit (dBµV)	
				QP	Average
		0.15 ~ 0.5		66 – 56	56 – 46
		0.5 ~ 5		56	46
5 ~ 30	60	50			

Test Setup	 Note: 1. Support units were connected to second LISN. 2. Both of LISNs (AMN) are 80cm from EUT and at least 80cm from other units and other metal planes support units.
------------	---

Procedure	- The EUT and supporting equipment were set up in accordance with the requirements of the standard on top of a 1.5m x 1m x 0.8m high, non-metallic table. - The power supply for the EUT was fed through a 50W/50mH EUT LISN, connected to filtered mains. - The RF OUT of the EUT LISN was connected to the EMI test receiver via a low-loss
-----------	---


Test Report	16071343-FCC-R2-V1-V1
Page	37 of 59

	coaxial cable. 4. All other supporting equipment were powered separately from another main supply. 5. The EUT was switched on and allowed to warm up to its normal operating condition. 6. A scan was made on the NEUTRAL line (for AC mains) or Earth line (for DC power) over the required frequency range using an EMI test receiver. 7. High peaks, relative to the limit line, The EMI test receiver was then tuned to the selected frequencies and the necessary measurements made with a receiver bandwidth setting of 10 kHz. 8. Step 7 was then repeated for the LIVE line (for AC mains) or DC line (for DC power).
Remark	
Result	☒ Pass ☐ Fail

Test Data ☒ Yes ☐ N/A

Test Plot ☒ Yes (See below) ☐ N/A

Test Mode: Bluetooth Mode




Test Data

Phase Line Plot at 120Vac, 60Hz

No.	P/L	Frequency	Reading	Detector	Corrected	Result	Limit	Margin
		(MHz)	(dBuV)		(dB}	(dBuV)	(dBuV)	(dB)
1	L1	1.4487	21.04	QP	10.04	31.08	56.00	-24.92
2	L1	1.4487	11.43	AVG	10.04	21.47	46.00	-24.53
3	L1	1.9986	22.69	QP	10.04	32.73	56.00	-23.27
4	L1	1.9986	12.58	AVG	10.04	22.62	46.00	-23.38
5	L1	4.3767	25.90	QP	10.07	35.97	56.00	-20.03
6	L1	4.3767	16.30	AVG	10.07	26.37	46.00	-19.63
7	L1	5.3907	25.90	QP	10.09	35.99	60.00	-24.01
8	L1	5.3907	16.89	AVG	10.09	26.98	50.00	-23.02
9	L1	8.7447	21.11	QP	10.13	31.24	60.00	-28.76
10	L1	8.7447	10.87	AVG	10.13	21.00	50.00	-29.00
11	L1	14.1462	25.91	QP	10.21	36.12	60.00	-23.88
12	L1	14.1462	15.30	AVG	10.21	25.51	50.00	-24.49

Test Mode: Bluetooth Mode




Test Data

Phase Neutral Plot at 120Vac, 60Hz

No.	P/L	Frequency	Reading	Detector	Corrected	Result	Limit	Margin
		(MHz)	(dBuV)		(dB)	(dBuV)	(dBuV)	(dB)
1	N	0.5244	24.48	QP	10.02	34.50	56.00	-21.50
2	N	0.5244	14.68	AVG	10.02	24.70	46.00	-21.30
3	N	0.7389	19.04	QP	10.02	29.06	56.00	-26.94
4	N	0.7389	11.51	AVG	10.02	21.53	46.00	-24.47
5	N	1.7373	24.08	QP	10.04	34.12	56.00	-21.88
6	N	1.7373	12.41	AVG	10.04	22.45	46.00	-23.55
7	N	4.9539	32.21	QP	10.07	42.28	56.00	-13.72
8	N	4.9539	19.97	AVG	10.07	30.04	46.00	-15.96
9	N	6.4008	25.78	QP	10.09	35.87	60.00	-24.13
10	N	6.4008	16.37	AVG	10.09	26.46	50.00	-23.54
11	N	14.2515	26.89	QP	10.19	37.08	60.00	-22.92
12	N	14.2515	16.12	AVG	10.19	26.31	50.00	-23.69

Test Mode: Bluetooth Mode




Test Data

Phase Line Plot at 240Vac, 60Hz

No.	P/L	Frequency	Reading	Detector	Corrected	Result	Limit	Margin
		(MHz)	(dBuV)		(dB)	(dBuV)	(dBuV)	(dB)
1	L1	0.7896	20.49	QP	10.03	30.52	56.00	-25.48
2	L1	0.7896	10.88	AVG	10.03	20.91	46.00	-25.09
3	L1	1.3434	20.86	QP	10.03	30.89	56.00	-25.11
4	L1	1.3434	11.41	AVG	10.03	21.44	46.00	-24.56
5	L1	1.8933	22.95	QP	10.04	32.99	56.00	-23.01
6	L1	1.8933	12.99	AVG	10.04	23.03	46.00	-22.97
7	L1	4.9617	27.47	QP	10.08	37.55	56.00	-18.45
8	L1	4.9617	18.10	AVG	10.08	28.18	46.00	-17.82
9	L1	6.1044	21.56	QP	10.10	31.66	60.00	-28.34
10	L1	6.1044	12.12	AVG	10.10	22.22	50.00	-27.78
11	L1	13.7367	25.28	QP	10.21	35.49	60.00	-24.51
12	L1	13.7367	15.14	AVG	10.21	25.35	50.00	-24.65

Test Mode: Bluetooth Mode



Test Data

Phase Neutral Plot at 240Vac, 60Hz

No.	P/L	Frequency	Reading	Detector	Corrected	Result	Limit	Margin
		(MHz)	(dBuV)		(dB}	(dBuV)	(dBuV)	(dB)
1	N	0.5166	24.04	QP	10.02	34.06	56.00	-21.94
2	N	0.5166	14.76	AVG	10.02	24.78	46.00	-21.22
3	N	1.8465	24.33	QP	10.04	34.37	56.00	-21.63
4	N	1.8465	13.90	AVG	10.04	23.94	46.00	-22.06
5	N	2.7825	26.84	QP	10.05	36.89	56.00	-19.11
6	N	2.7825	14.15	AVG	10.05	24.20	46.00	-21.80
7	N	4.8759	32.47	QP	10.07	42.54	56.00	-13.46
8	N	4.8759	20.01	AVG	10.07	30.08	46.00	-15.92
9	N	13.6353	27.07	QP	10.18	37.25	60.00	-22.75
10	N	13.6353	16.23	AVG	10.18	26.41	50.00	-23.59
11	N	15.8154	24.95	QP	10.21	35.16	60.00	-24.84
12	N	15.8154	13.17	AVG	10.21	23.38	50.00	-26.62

6.9 Radiated Spurious Emissions & Restricted Band

Temperature	24 °C
Relative Humidity	56%
Atmospheric Pressure	1023mbar
Test date :	Dec 23, 2016
Tested By :	Loren Luo

Requirement(s):

Spec	Item	Requirement	Applicable											
47CFR§15.205, §15.209, §15.247(d)	a)	Except higher limit as specified elsewhere in other section, the emissions from the low-power radio-frequency devices shall not exceed the field strength levels specified in the following table and the level of any unwanted emissions shall not exceed the level of the fundamental emission. The tighter limit applies at the band edges	☒											
		<table><tr><th>Frequency range (MHz)</th><th>Field Strength (µV/m)</th></tr><tr><td>30 – 88</td><td>100</td></tr><tr><td>88 – 216</td><td>150</td></tr><tr><td>216 960</td><td>200</td></tr><tr><td>Above 960</td><td>500</td></tr></table>		Frequency range (MHz)	Field Strength (µV/m)	30 – 88	100	88 – 216	150	216 960	200	Above 960	500	
		Frequency range (MHz)		Field Strength (µV/m)										
		30 – 88		100										
		88 – 216		150										
		216 960		200										
Above 960	500													

Test Setup	
------------	--

Procedure	- The EUT was switched on and allowed to warm up to its normal operating condition. - The test was carried out at the selected frequency points obtained from the EUT characterization. Maximization of the emissions, was carried out by rotating the EUT, changing the antenna polarization, and adjusting the antenna height in the following manner:
-----------	---

Test Report	16071343-FCC-R2-V1-V1
Page	43 of 59


	a. Vertical or horizontal polarization (whichever gave the higher emission level over a full rotation of the EUT) was chosen. b. The EUT was then rotated to the direction that gave the maximum emission. c. Finally, the antenna height was adjusted to the height that gave the maximum emission. 3. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasiy Peak detection at frequency below 1GHz. 4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz with Peak detection for Peak measurement at frequency above 1GHz. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz with Peak detection for Average Measurement as below at frequency above 1GHz. 5. Steps 2 and 3 were repeated for the next frequency point, until all selected frequency points were measured.
Remark	
Result	☒ Pass ☐ Fail

Test Data ☒ Yes ☐ N/A

Test Plot ☒ Yes (See below) ☐ N/A

Test Mode: Bluetooth Mode

Below 1GHz



Test Data

Horizontal Polarity Plot @3m

No.	P/L	Frequency	Reading	Detector	Corrected	Result	Limit	Margin	Height	Degree
		(MHz)	(dBuV/m)		(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	(cm)	(°)
1	H	30.0000	37.72	QP	-0.26	37.46	40.00	-2.54	203	221
2	H	34.6385	42.36	QP	-3.67	38.69	40.00	-1.31	123	138
3	H	42.8998	46.73	QP	-9.53	37.20	40.00	-2.80	195	30
4	H	47.8260	49.70	QP	-12.20	37.50	40.00	-2.50	189	265
5	H	53.8818	50.29	QP	-13.64	36.65	40.00	-3.35	224	13
6	H	59.8588	48.22	QP	-14.34	33.88	40.00	-6.12	214	52

Below 1GHz



Test Data

Vertical Polarity Plot @3m

No.	P/L	Frequency	Reading	Detector	Corrected	Result	Limit	Margin	Height	Degree
		(MHz)	(dBuV/m)		(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	(cm)	(°)
1	V	51.1209	50.55	QP	-13.30	37.25	40.00	-2.75	171	42
2	V	90.8554	44.19	peak	-13.15	31.04	43.50	-12.46	183	4
3	V	181.9202	40.06	peak	-9.76	30.30	43.50	-13.20	169	272
4	V	291.0360	31.96	peak	-7.31	24.65	46.00	-21.35	234	175
5	V	30.2111	36.06	QP	-0.41	35.65	40.00	-4.35	177	311
6	V	839.1818	35.56	peak	3.68	39.24	46.00	-6.76	250	238

Above 1GHz

Test Mode:	Transmitting Mode
------------	-------------------

Low Channel: GFSK Mode (Worst Case) (2402 MHz)

Frequency (MHz)	S.A. Reading (dBμV)	Detector (PK/AV)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Cord. Amp. (dBμV/m)	Limit (dBμV/m)	Margin (dB)
4804	39.06	AV	V	33.67	6.86	32.66	46.93	54	-7.07
4804	38.83	AV	H	33.67	6.86	32.66	46.7	54	-7.3
4804	48.11	PK	V	33.67	6.86	32.66	55.98	74	-18.02
4804	47.94	PK	H	33.67	6.86	32.66	55.81	74	-18.19
17796	25.37	AV	V	45.03	11.21	32.38	49.23	54	-4.77
17796	25.18	AV	H	45.03	11.21	32.38	49.04	54	-4.96
17796	41.65	PK	V	45.03	11.21	32.38	65.51	74	-8.49
17796	41.44	PK	H	45.03	11.21	32.38	65.3	74	-8.7

Middle Channel: π /4 DQPSK Mode (Worst Case) (2441 MHz)

Frequency (MHz)	S.A. Reading (dBμV)	Detector (PK/AV)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Cord. Amp. (dBμV/m)	Limit (dBμV/m)	Margin (dB)
4882	38.97	AV	V	33.71	6.95	32.74	46.89	54	-7.11
4882	38.76	AV	H	33.71	6.95	32.74	46.68	54	-7.32
4882	48.13	PK	V	33.71	6.95	32.74	56.05	74	-17.95
4882	47.9	PK	H	33.71	6.95	32.74	55.82	74	-18.18
17811	25.42	AV	V	45.15	11.18	32.41	49.34	54	-4.66
17811	25.21	AV	H	45.15	11.18	32.41	49.13	54	-4.87
17811	41.73	PK	V	45.15	11.18	32.41	65.65	74	-8.35
17811	41.52	PK	H	45.15	11.18	32.41	65.44	74	-8.56

High Channel: $\pi/4$ DQPSK Mode (Worst Case) (2480 MHz)

Frequency (MHz)	S.A. Reading (dB μ V)	Detector (PK/AV)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Cord. Amp. (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
4960	38.91	AV	V	33.9	6.76	32.74	46.83	54	-7.17
4960	38.69	AV	H	33.9	6.76	32.74	46.61	54	-7.39
4960	48.04	PK	V	33.9	6.76	32.74	55.96	74	-18.04
4960	47.87	PK	H	33.9	6.76	32.74	55.79	74	-18.21
17802	25.39	AV	V	45.22	11.35	32.38	49.58	54	-4.42
17802	25.16	AV	H	45.22	11.35	32.38	49.35	54	-4.65
17802	41.57	PK	V	45.22	11.35	32.38	65.76	74	-8.24
17802	41.35	PK	H	45.22	11.35	32.38	65.54	74	-8.46

Note:

1, The testing has been conformed to $10 \times 2480 \text{ MHz} = 24,800 \text{ MHz}$

2, All other emissions more than 30 dB below the limit


3, X-Axis, Y-Axis and Z-Axis were investigated. The results above show only the worst case.


Annex A. TEST INSTRUMENT

Instrument	Model	Serial #	Cal Date	Cal Due	In use
AC Line Conducted					
EMI test receiver	ESCS30	8471241027	09/16/2016	09/15/2017	☒
Line Impedance	LI-125A	191106	09/24/2016	09/23/2017	☒
Line Impedance	LI-125A	191107	09/24/2016	09/23/2017	☒
LISN	ISN T800	34373	09/24/2016	09/23/2017	☒
Double Ridge Horn Antenna (1 ~18GHz)	AH-118	71283	09/23/2016	09/22/2017	☒
Transient Limiter	LIT-153	531118	08/31/2016	08/30/2017	☒
RF conducted test					
Agilent ESA-E SERIES	E4407B	MY45108319	09/16/2016	09/15/2017	☒
Power Splitter	1#	1#	08/31/2016	08/30/2017	☒
DC Power Supply	E3640A	MY40004013	09/16/2016	09/15/2017	☒
Radiated Emissions					
EMI test receiver	ESL6	100262	09/16/2016	09/15/2017	☒
Positioning Controller	UC3000	MF780208282	11/18/2016	11/17/2017	☒
OPT 010 AMPLIFIER (0.1-1300MHz)	8447E	2727A02430	08/31/2016	08/30/2017	☒
Microwave Preamplifier (1 ~ 26.5GHz)	8449B	3008A02402	03/24/2016	03/23/2017	☒
Bilog Antenna (30MHz~6GHz)	JB6	A110712	09/20/2016	09/19/2017	☒
Double Ridge Horn Antenna (1 ~18GHz)	AH-118	71283	09/23/2016	09/22/2017	☒
Universal Radio Communication Tester	CMU200	121393	09/24/2016	09/23/2017	☒


Annex B. EUT And Test Setup Photographs

Annex B.i. Photograph: EUT External Photo







EUT - Top View



EUT - Bottom View



EUT - Left View



EUT - Right View


Annex B.ii. Photograph: EUT Internal Photo




Cover Off - Top View 1




Cover Off - Top View 2




Battery - Front View




Battery - Rear View




Mainboard with Shielding - Front View



Mainboard without Shielding - Front View



Mainboard – Rear View



LCD – Front View



LCD – Rear View



GSM/PCS/UMTS-FDD Antenna View



WIFI/BT/BLE/GPS - Antenna View


Annex B.iii. Photograph: Test Setup Photo




Conducted Emissions Test Setup Front View



Conducted Emissions Test Setup Side View



Radiated Spurious Emissions Test Setup Below 1GHz




Radiated Spurious Emissions Test Setup Above
1GHz


Annex C. TEST SETUP AND SUPPORTING EQUIPMENT

Annex C.ii. TEST SET UP BLOCK


Block Configuration Diagram for AC Line Conducted Emissions



Block Configuration Diagram for Radiated Emissions (Below 1GHz) .



Block Configuration Diagram for Radiated Emissions (Above 1GHz) .



Annex C. ii. SUPPORTING EQUIPMENT DESCRIPTION

The following is a description of supporting equipment and details of cables used with the EUT.

Supporting Equipment:

Manufacturer	Equipment Description	Model	Serial No
BLU Products, Inc.	Adapter	UB-BM-0700	D0523

Supporting Cable:

Cable type	Shield Type	Ferrite Core	Length	Serial No
USB Cable	Un-shielding	No	0.8m	D0523

Test Report	16071343-FCC-R2-V1-V1
Page	58 of 59

Annex D. User Manual / Block Diagram / Schematics / Partlist

Please see the attachment

Test Report	16071343-FCC-R2-V1-V1
Page	59 of 59

Annex E. DECLARATION OF SIMILARITY

N/A