FCC SAR Test Report

Product	:	Smart Phone
Trade mark	:	BLU
Model/Type reference	:	ADVANCE L5
Report Number	:	200916005SAR-1
Date of Issue	:	October 9, 2020
FCC ID	:	YHLBLUADL5
Test Standards	:	FCC 47 CFR Part 2 §2.1093
		ANSI/IEEE C95.1-1992
		IEEE Std 1528-2013
Test result	:	PASS

Prepared for:

BLU Products, Inc.
10814 NW 33rd St # 100 Doral, FL 33172 ,USA

Prepared by:

Shenzhen UnionTrust Quality and Technology Co., Ltd.
16/F, Block A, Building 6, Baoneng Science and Technology Park, Qingxiang Road No.1, Longhua New District, Shenzhen, China
TEL: +86-755-2823 0888
FAX: +86-755-2823 0886

Prepared by: Kaye Bao, Supervisor

Reviewed by: Kevin Liang, Assistant Manager

Approved by: Billy Li, Technical Director

Date: October 9, 2020

UnionTrust Laboratories UnionTrust * Certified *

Version

Version No.	Date	Description
V1.0	October 9, 2020	Original

Contents

Page

1 GENERAL INFORMATION 5
1.1 STATEMENT OF COMPLIANCE 5
1.2 EUT DESCRIPTION 6
1.2.1 General Description 6
1.2.2 Wireless Technologies 7
1.2.3 List of Accessory 8
1.3 MAXIMUM CONDUCTED POWER 9
1.4 OTHER INFORMATION 10
1.5 TESTING LOCATION 10
1.6 TEST FACILITY 10
1.7 GUIDANCE STANDARD 11
2 SPECIFIC ABSORPTION RATE (SAR) 12
2.1 INTRODUCTION 12
2.2 SAR DEFINITION 12
2.3 SAR LIMITS 12
3 SAR MEASUREMENT SYSTEM 13
3.1 SPEAG DASY SYSTEM 13
3.1.1 Robot 13
3.1.2 Probe 14
3.1.3 Data Acquisition Electronics (DAE) 14
3.1.4 Phantom 15
3.1.5 Device Holder 16
3.1.6 System Validation Dipoles 16
3.2 SAR SCAN PROCEDURE 17
3.2.1 SAR Reference Measurement (drift) 17
3.2.2 Area Scan 17
3.2.3 Zoom Scan 17
3.2.4 SAR Drift Measurement 18
3.3 TEST EQUIPMENT 19
3.4 MEASUREMENT UNCERTAINTY 20
3.5 TISSUE DIELECTRIC PARAMETER MEASUREMENT & SYSTEM VERIFICATION 21
3.5.1 Tissue Simulating Liquids 21
3.5.2 System Check Description 23
3.5.3 Tissue Verification 24
3.5.4 System Verification 24
4 SAR MEASUREMENT EVALUATION 25
4.1 EUT CONFIGURATION AND SETTING 25
4.1.1 GSM Configuration and Testing 25
4.1.2 WCDMA Configuration and Testing 25
4.1.3 LTE Configuration and Testing 26
4.1.4 WLAN Configuration and Testing 28
4.2 EUT TESTING POSITION 29
4.2.1 Head Exposure Conditions 29
4.2.2 Body-worn Accessory Exposure Conditions 31
4.2.3 Hotspot Mode Exposure Conditions 32
4.3 MEASURED CONDUCTED POWER RESULT 33
4.3.1 Conducted Power of GSM Band 33
4.3.2 Conducted Power of WCDMA Band 34
4.3.3 Conducted Power of LTE Band 34
4.3.4 Conducted Power of WLAN 40

4.3.5 Conducted Power of BT 40
4.4 SAR TEST EXCLUSION EVALUATIONS 40
4.4.1 Standalone SAR Test Exclusion Considerations 40
4.4.2 Estimated SAR Calculation 42
4.5 SAR TESTING RESULTS 43
4.5.1 SAR Test Reduction Considerations 43
4.5.2 SAR Results for Head Exposure Condition 45
4.5.3 SAR Results for Body-worn Exposure Condition (Separation Distance is 10mm) 47
4.5.4 SAR Results for Hotspot Exposure Condition (Separation Distance is 1.0 cm) 48
4.6 SIMULTANEOUS MULTI-BAND TRANSMISSION EVALUATION 50
4.6.1 Simultaneous Transmission SAR Test Exclusion Considerations 50
4.6.2 Simultaneous Transmission Possibilities 51
4.6.3 Max. Standalone SAR 52
4.6.4 Sum of SAR 53

Appendix A. SAR Plots of System Verification
Appendix B. SAR Plots of SAR Measurement
Appendix C. Calibration Certificate for Probe and Dipole
Appendix D. Photographs of EUT and Setup

1 General Information

1.1 Statement of Compliance

The maximum results of Specific Absorption Rate (SAR) found during testing for the EUT are as follows:

Mode	Highest Reported Head SAR_{1g} (W/kg)	Highest Reported Body-worn SAR_{1g} (1.0 cm Gap) (W/kg)	Highest Reported Hotspot SAR_{1g} (1.0 cm Gap) (W/kg)
GSM850	0.60	0.22	0.22
GSM1900	0.24	0.15	0.15
WCDMA II	0.26	1.31	1.31
WCDMA V	0.27	0.54	0.54
LTE 2	0.30	**1.35**	**1.35**
LTE 4	0.39	1.27	1.27
LTE 5	0.36	0.54	0.54
LTE 7	0.06	0.67	0.55
2.4G WLAN	**0.94**	0.24	0.39
Bluetooth	N/A	N/A	N/A
Highest Simultaneous Transmission SAR	**1.54**	**1.59**	**1.59**

1.2 EUT Description

1.2.1 General Description

Product Name	Smart Phone
Trade mark	BLU
Model No.(EUT)	ADVANCE L5
FCC ID	YHLBLUADL5
IMEI Code	357518075493155 357518075493189
Tx Frequency Bands (Unit: MHz)	GSM850: 824.2 ~ 848.8 GSM1900: 1850.2 ~ 1909.8 WCDMA Band II: 1852.4 ~ 1907.6 WCDMA Band V: 826.4 ~ 846.6 LTE Band 2: 1850.7 ~ 1909.3 (1.4M), 1851.5 ~ 1908.5 (3M), 1852.5 ~ 1907.5 (5M), 1855 ~ 1905 (10M), 1857.5 ~ 1902.5 (15M), 1860 ~ 1900 (20M) LTE Band 4: 1710.7 ~ 1754.3 (1.4M), 1711.5 ~ 1753.5 (3M), 1712.5 ~ 1752.5 (5M), 1715 ~ 1750 (10M), 1717.5 ~ 1747.5 (15M), 1720 ~ 1745 (20M) LTE Band 5: 824.7 ~ 848.3 (1.4M), 825.5 ~ 847.5 (3M), 826.5 ~ 846.5 (5M), 829 ~ 844 (10M) LTE Band 7: 2502.5 ~ 2567.5 (5M), 2505 ~ 2565 (10M), 2507.5 ~ 2562.5 (15M), 2510 ~ 2560 (20M) WLAN: 2412 ~ 2462 Bluetooth: 2402 ~ 2480
Device Class	B
Antenna Type	Fixed Internal Antenna
EUT Stage	Identical Prototype

1.2.2 Wireless Technologies

GSM	Voice GPRS (Multi-Slot Class: 12-4UP) EDGE (Multi-Slot Class: 12-4UP)
WCDMA	RMC HSDPA HSUPA
LTE	QPSK 16QAM VoLTE
2.4G WLAN	802.11b 802.11g 802.11n (HT20)
Bluetooth	BR+EDR LE
Wireless Router (Hotspot)	2.4G WLAN: Support
VOIP	Support Note: Since this device supports VOIP capability through 3rd party apps software, we have evaluated data mode for head and body-worn SAR.

1.2.3 List of Accessory

Battery	
Model No.:	C348246140L
Battery Type:	Lithium-ion Polymer Rechargeable Battery
Rated Voltage:	3.7 Vdc
Limited Charge Voltage:	4.2 Vdc
Rated Capacity:	1400 mAh
Manufacturer:	Shenzhen Truepower New Energy Co.,Ltd.

1.3 Maximum Conducted Power

The maximum conducted average power (Unit: dBm) including tune-up tolerance is shown as below.

Mode	GSM850	GSM1900
GSM (GMSK, 1Tx-slot)	32.87	30.90
GPRS (GMSK, 1Tx-slot)	32.85	30.88
GPRS (GMSK, 2Tx-slot)	30.70	28.70
GPRS (GMSK, 3Tx-slot)	28.82	27.13
GPRS (GMSK, 4Tx-slot)	26.66	25.05
EDGE (8PSK, 1Tx-slot)	26.30	24.75
EDGE (8PSK, 2Tx-slot)	24.80	24.33
EDGE (8PSK, 3Tx-slot)	22.26	20.47
EDGE (8PSK, 4Tx-slot)	19.61	20.22

Mode	WCDMA Band II	WCDMA Band V
RMC 12.2K	23.88	22.39
HSDPA	22.94	22.07
HSUPA	23.17	22.00

Band	Mode	Maximum Conducted Power (Unit: dBm)
LTE 2	QPSK / 16QAM	24.40
LTE 4	QPSK / 16QAM	22.96
LTE 5	QPSK / 16QAM	22.48
LTE 7	QPSK / 16QAM	24.29

Mode	2.4G WLAN
802.11b	17.13
802.11g	16.34
802.11n HT20	14.53

Mode		2.4G Bluetooth
BR + EDR	GFSK	3.72
	π/4-DQPSK	3.00
	8-DPSK	3.01
LE	GFSK	-2.49

1.4 Other Information

Sample Received Date:	September 17, 2020
Sample tested Date:	September 18, 2020 to October 8, 2020

1.5 Testing Location

Shenzhen UnionTrust Quality and Technology Co., Ltd.
Address: Address: 16/F, Block A, Building 6, Baoneng Science and Technology Park, Qingxiang Road No.1, Longhua New District, Shenzhen, China
Telephone: +86-755-28230888 Fax: +86-755-28230886
Mail: info@uttlab.com Website: Http://www.uttlab.com

1.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

CNAS-Lab Code: L9069
The measuring equipment utilized to perform the tests documented in this report has been calibrated once a year or in accordance with the manufacturer's recommendations, and is traceable under the ISO/IEC/EN 17025 to international or national standards. Equipment has been calibrated by accredited calibration laboratories.

FCC Accredited Lab.
Designation Number: CN1194
Test Firm Registration Number: 259480

A2LA-Lab Certificate No.: 4312.01
Shenzhen UnionTrust Quality and Technology Co., Ltd. has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

ISED Wireless Device Testing Laboratories
CAB identifier: CN0032

1.7 Guidance Standard

The tests documented in this report were performed in accordance with FCC 47 CFR Part 2 §2.1093, IEEE Std 1528-2013, ANSI/IEEE C95.1-1992, the following FCC Published RF exposure KDB procedures:

KDB 865664 D01 v01r04

KDB 865664 D02 v01r02

KDB 248227 D01 v02r02

KDB 447498 D01 v06

KDB 648474 D04 v01r03

KDB 941225 D01 v03r01

KDB 941225 D05 v02r05

KDB 941225 D06 v02r01

2 Specific Absorption Rate (SAR)

2.1 Introduction

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling, by appropriate techniques, to produce specific absorption rates (SARs) as averaged over the whole-body, any 1 g or any 10 g of tissue (defined as a tissue volume in the shape of a cube). All SAR values are to be averaged over any six-minute period. When portable device was used within 20 cm of the user's body, SAR evaluation of the device will be required. The SAR limit in chapter 2.3.

2.2 SAR Definition

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density (ρ). The equation description is as below:

$$\mathbf{SAR} = \frac{\mathbf{d}}{\mathbf{dt}}\left(\frac{\mathbf{dW}}{\mathbf{dm}}\right) = \frac{\mathbf{d}}{\mathbf{dt}}\left(\frac{\mathbf{dW}}{\boldsymbol{\rho}\mathbf{dv}}\right)$$

SAR is expressed in units of Watts per kilogram (W/kg)

SAR measurement can be related to the electrical field in the tissue by

$$\mathbf{SAR} = \frac{\boldsymbol{\sigma}|\mathbf{E}|^2}{\boldsymbol{\rho}}$$

Where: σ is the conductivity of the tissue, ρ is the mass density of the tissue and E is the RMS electrical field strength.

2.3 SAR Limits

(A) Limits for Occupational/Controlled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.4	8.0	20.0

(B) Limits for General Population/Uncontrolled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.08	1.6	4.0

Note:

1. Whole-Body SAR is averaged over the entire body, partial-body SAR is averaged over any 1 gram of tissue defined as a tissue volume in the shape of a cube. SAR for hands, wrists, feet and ankles is averaged over any 10 grams of tissue defined as a tissue volume in the shape of a cube.
2. At frequencies above 6.0 GHz, SAR limits are not applicable and MPE limits for power density should be applied at 5 cm or more from the transmitting device.
3. The SAR limit is specified in FCC 47 CFR Part 2 §2.1093, ANSI/IEEE C95.1-1992.

3 SAR Measurement System

3.1 SPEAG DASY System

DASY system consists of high precision robot, probe alignment sensor, phantom, robot controller, controlled measurement server and near-field probe. The robot includes six axes that can move to the precision position of the DASY5 software defined. The DASY software can define the area that is detected by the probe. The robot is connected to controlled box. Controlled measurement server is connected to the controlled robot box. The DAE includes amplifier, signal multiplexing, AD converter, offset measurement and surface detection. It is connected to the Electro-optical coupler (ECO). The ECO performs the conversion form the optical into digital electric signal of the DAE and transfers data to the PC.



DASY Measurement System

3.1.1 Robot

The DASY system uses the high precision robots from Stäubli SA (France). For the 6-axis controller system, the robot controller version (DASY4: CS7MB) from Stäubli is used. The Stäubli robot series have many features that are important for our application:

- High precision (repeatability ±0.02 mm)
- High reliability (industrial design)
- Jerk-free straight movements
- Low ELF interference (the closed metallic construction shields against motor control fields

3.1.2 Probe

The SAR measurement is conducted with the dosimetric probe. The probe is specially designed and calibrated for use in liquid with high permittivity. The dosimetric probe has special calibration in liquid at different frequency.

Model	EX3DV4	
Construction	Symmetrical design with triangular core. Built-in shielding against static charges. PEEK enclosure material (resistant to organic solvents, e.g., DGBE).	
Frequency	10 MHz to 6 GHz Linearity: ± 0.2 dB	
Directivity	± 0.3 dB in HSL (rotation around probe axis) ± 0.5 dB in tissue material (rotation normal to probe axis)	
Dynamic Range	10 µW/g to 100 mW/g Linearity: ± 0.2 dB (noise: typically < 1 µW/g)	
Dimensions	Overall length: 337 mm (Tip: 20 mm) Tip diameter: 2.5 mm (Body: 12 mm) Typical distance from probe tip to dipole centers: 1 mm	

Model	ES3DV3	
Construction	Symmetrical design with triangular core. Interleaved sensors. Built-in shielding against static charges. PEEK enclosure material (resistant to organic solvents, e.g., DGBE).	
Frequency	10 MHz to 4 GHz Linearity: ± 0.2 dB	
Directivity	± 0.2 dB in HSL (rotation around probe axis) ± 0.3 dB in tissue material (rotation normal to probe axis)	
Dynamic Range	5 µW/g to 100 mW/g Linearity: ± 0.2 dB	
Dimensions	Overall length: 337 mm (Tip: 20 mm) Tip diameter: 3.9 mm (Body: 12 mm) Distance from probe tip to dipole centers: 2.0 mm	

3.1.3 Data Acquisition Electronics (DAE)

Model	DAE3, DAE4	
Construction	Signal amplifier, multiplexer, A/D converter and control logic. Serial optical link for communication with DASY embedded system (fully remote controlled). Two step probe touch detector for mechanical surface detection and emergency robot stop.	
Measurement Range	-100 to +300 mV (16 bit resolution and two range settings: 4mV, 400mV)	
Input Offset Voltage	< 5µV (with auto zero)	
Input Bias Current	< 50 fA	
Dimensions	60 x 60 x 68 mm	

3.1.4 Phantom

Model	Twin SAM	
Construction	The shell corresponds to the specifications of the Specific Anthropomorphic Mannequin (SAM) phantom defined in IEEE 1528 and IEC 62209-1. It enables the dosimetric evaluation of left and right hand phone usage as well as body mounted usage at the flat phantom region. A cover prevents evaporation of the liquid. Reference markings on the phantom allow the complete setup of all predefined phantom positions and measurement grids by teaching three points with the robot.	
Material	Vinylester, glass fiber reinforced (VE-GF)	
Shell Thickness	2 ± 0.2 mm (6 ± 0.2 mm at ear point)	
Dimensions	Length: 1000 mm Width: 500 mm Height: adjustable feet	
Filling Volume	approx. 25 liters	

Model	ELI	
Construction	Phantom for compliance testing of handheld and body-mounted wireless devices in the frequency range of 30 MHz to 6 GHz. ELI is fully compatible with the IEC 62209-2 standard and all known tissue simulating liquids. ELI has been optimized regarding its performance and can be integrated into our standard phantom tables. A cover prevents evaporation of the liquid. Reference markings on the phantom allow installation of the complete setup, including all predefined phantom positions and measurement grids, by teaching three points. The phantom is compatible with all SPEAG dosimetric probes and dipoles.	
Material	Vinylester, glass fiber reinforced (VE-GF)	
Shell Thickness	2.0 ± 0.2 mm (bottom plate)	
Dimensions	Major axis: 600 mm Minor axis: 400 mm	
Filling Volume	approx. 30 liters	

3.1.5 Device Holder

Model	Mounting Device	
Construction	In combination with the Twin SAM Phantom or ELI4, the Mounting Device enables the rotation of the mounted transmitter device in spherical coordinates. Rotation point is the ear opening point. Transmitter devices can be easily and accurately positioned according to IEC, IEEE, FCC or other specifications. The device holder can be locked for positioning at different phantom sections (left head, right head, flat).	
Material	POM	

Model	Laptop Extensions Kit	
Construction	Simple but effective and easy-to-use extension for Mounting Device that facilitates the testing of larger devices according to IEC 62209-2 (e.g., laptops, cameras, etc.). It is lightweight and fits easily on the upper part of the Mounting Device in place of the phone positioner.	
Material	POM, Acrylic glass, Foam	

3.1.6 System Validation Dipoles

Model	D-Serial	
Construction	Symmetrical dipole with l/4 balun. Enables measurement of feed point impedance with NWA. Matched for use near flat phantoms filled with tissue simulating solutions.	
Frequency	750 MHz to 5800 MHz	
Return Loss	> 20 dB	
Power Capability	> 100 W (f < 1GHz), > 40 W (f > 1GHz)	

3.2 SAR Scan Procedure

3.2.1 SAR Reference Measurement (drift)

Prior to the SAR test, local SAR shall be measured at a stationary reference point where the SAR exceeds the lower detection limit of the measurement system.

3.2.2 Area Scan

Measurement procedures for evaluating the SAR of wireless device start with a coarse measurement grid to determine the approximate location of the local peak SAR values. This is known as the area-scan procedure. All antennas and radiating structures that may contribute to the measured SAR or influence the SAR distribution must be included in the area scan. The area scan measurement resolution must enable the extrapolation algorithms of the SAR system to correctly identify the peak SAR location(s) for subsequent zoom scan measurements to correctly determine the 1-g SAR. Area scans are performed at a constant distance from the phantom surface, determined by the measurement frequencies. When a measured peak is closer than ½ the zoom scan volume dimension (x, y) from the edge of the area scan region, unless the entire peak and gram-averaging volume are both captured within the zoom scan volume, the area scan must be repeated by shifting and expanding the area scan region to ensure all peaks are away from the area scan boundary. The area scan resolutions specified in the table below must be applied to the SAR measurements.

	≤ 3 GHz	> 3 GHz
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface	5 mm ± 1 mm	½·δ·ln(2) mm ± 0.5 mm
Maximum probe angle from probe axis to phantom surface normal at the measurement location	30° ± 1°	20° ± 1°
Maximum area scan spatial resolution: $\Delta x_{Area}, \Delta y_{Area}$	≤ 2 GHz: ≤ 15 mm 2 – 3 GHz: ≤ 12 mm	3 – 4 GHz: ≤ 12 mm 4 – 6 GHz: ≤ 10 mm When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be ≤ the corresponding x or y dimension of the test device with at least one measurement point on the test device.

3.2.3 Zoom Scan

To evaluate the peak spatial-average SAR values with respect to 1 g or 10 g cubes, fine resolution volume scans, called zoom scans, are performed at the peak SAR locations identified during the area scan. If the cube volume within the zoom scan chosen to calculate the peak spatial-average SAR touches any boundary of the zoom-scan volume, the zoom scan shall be repeated with the center of the zoom-scan volume shifted to the new maximum SAR location. For any secondary peaks found in the area scan that are within 2 dB of the maximum peak and are not within this zoom scan, the zoom scan shall be performed for such peaks, unless the peak spatial-average SAR at the location of the maximum peak is more than 2 dB below the applicable SAR limit (i.e., 1 W/kg for a 1.6 W/kg 1 g limit, or 1.26 W/kg for a 2 W/kg 10 g limit). The zoom scan resolutions specified in the table below must be applied to the SAR measurements.

			≤ 3 GHz	> 3 GHz
Maximum zoom scan spatial resolution: Δx_{Zoom}, Δy_{Zoom}			≤ 2 GHz: ≤ 8 mm 2 – 3 GHz: ≤ 5 mm*	3 – 4 GHz: ≤ 5 mm* 4 – 6 GHz: ≤ 4 mm*
Maximum zoom Scan spatial resolution, normal to phantom surface	uniform grid: $\Delta Z_{Zoom}(n)$		≤ 5 mm	3 – 4 GHz: ≤ 4 mm 4 – 5 GHz: ≤ 3 mm 5 – 6 GHz: ≤ 2 mm
	graded grid	$\Delta Z_{Zoom}(1)$: between 1ST two points closest to phantom surface	≤ 4 mm	3 – 4 GHz: ≤ 3 mm 4 – 5 GHz: ≤ 2.5 mm 5 – 6 GHz: ≤ 2 mm
		$\Delta Z_{Zoom}(n>1)$: between subsequent points	≤ 1.5·$\Delta Z_{Zoom}(n-1)$ mm	
Minimum zoom scan volume	x, y, z		≥ 30 mm	3 – 4 GHz: ≥ 28 mm 4 – 5 GHz: ≥ 25 mm 5 – 6 GHz: ≥ 22 mm

Note: δ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see IEEE Std 1528-2013 for details.

* When zoom scan is required and the reported SAR from the area scan based 1-g SAR estimation procedures of KDB Publication 447498 is ≤ 1.4 W/kg, ≤ 8 mm, ≤ 7 mm and ≤ 5 mm zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.

3.2.4 SAR Drift Measurement

The local SAR (or conducted power) shall be measured at exactly the same location as in 3.2.1 section. The absolute value of the measurement drift (the difference between the SAR measured in 3.2.1 and 3.2.4 section) shall be recorded. The SAR drift shall be kept within ± 5%.

3.3 Test Equipment

Equipment	Manufacturer	Model	SN	Cal. Date	Cal. Interval
System Validation Dipole	SPEAG	D835V2	4d005	May 18, 2018	3 Year
System Validation Dipole	SPEAG	D1750V2	1086	May 18, 2018	3 Year
System Validation Dipole	SPEAG	D1900V2	509	May 18, 2018	3 Year
System Validation Dipole	SPEAG	D2450V2	883	September 20, 2019	3 Year
System Validation Dipole	SPEAG	D2600V2	1082	September 20, 2019	3 Year
Dosimetric E-Field Probe	SPEAG	ES3DV3	3090	May 9, 2020	1 Year
Data Acquisition Electronics	SPEAG	DAE4	662	May 6, 2020	1 Year
Twins Phantom	SPEAG	SAM	TP-1378	N/A	N/A
Twins Phantom	SPEAG	SAM	TP-1376	N/A	N/A
Radio Communication Analyzer	Anritsu	MT8820C	6200918396	November 24, 2019	1 Year
Wideband Radio Communication Tester	R&S	CMW500	119583	July 31, 2019	1 Year
ENA Series Network Analyzer	Agilent	8753ES	MY40000519	November 24, 2019	1 Year
Dielectric Assessment Kit	SPEAG	DAK-3.5	1056	N/A	N/A
USB/GPIB Interface	Agilent	82357B	N10149	N/A	N/A
Signal Generator	R&S	SMF 100A	100691	May. 14, 2020	1 Year
POWER METER	R&S	NRP	101293	November 24, 2019	1 Year
Temperature and humidity meter	Lisheng	HTC-1	/	Nov. 25, 2019	1 Year
Coupler	REBES	TC-05180-10S	161221001	N/A	N/A
Amplifier	Mini-Circuit	ZHL42	QA1252001	N/A	N/A
DC Source	Agilent	66319B	MY43000795	N/A	N/A

3.4 Measurement Uncertainty

Per KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz, when the highest measured 1-g SAR within a frequency band is < 1.5 W/kg, the extensive SAR measurement uncertainty analysis described in IEEE Std 1528-2013 is not required in SAR reports submitted for equipment approval.

3.5 Tissue Dielectric Parameter Measurement & System Verification

3.5.1 Tissue Simulating Liquids

The temperature of the tissue-equivalent medium used during measurement must also be within 18 °C to 25 °C and within ± 2 °C of the temperature when the tissue parameters are characterized. The dielectric parameters must be measured before the tissue-equivalent medium is used in a series of SAR measurements. The parameters should be re-measured after each 3 - 4 days of use; or earlier if the dielectric parameters can become out of tolerance.

The depth of tissue-equivalent liquid in a phantom must be ≥ 15.0 cm with ≤ ± 0.5 cm variation for SAR measurements ≤ 3 GHz and ≥ 10.0 cm with ≤ ± 0.5 cm variation for measurements > 3 GHz. The nominal dielectric values of the tissue simulating liquids in the phantom and the tolerance of 5% are listed in Table-3.1.

Photo of Liquid Height

Table-3.1 Tissue Dielectric Parameters for Head and Body

Target Frequency (MHz)	Head		Body	
	εr	σ (S/m)	εr	σ (S/m)
750	*41.9*	*0.89*	*55.5*	*0.96*
835	41.5	0.90	55.2	0.97
900	41.5	0.97	55.0	1.05
1450	*40.5*	*1.20*	*54.0*	*1.30*
1640	*40.3*	*1.29*	*53.8*	*1.40*
1750	*40.1*	*1.37*	*53.4*	*1.49*
1800	40.0	1.40	53.3	1.52
1900	40.0	1.40	53.3	1.52
2000	40.0	1.40	53.3	1.52
2300	*39.5*	*1.67*	*52.9*	*1.81*
2450	39.2	1.80	52.7	1.95
2600	*39.0*	*1.96*	*52.5*	*2.16*
3500	*37.9*	*2.91*	*51.3*	*3.31*
5200	*36.0*	*4.66*	*49.0*	*5.30*
5300	*35.9*	*4.76*	*48.9*	*5.42*
5500	*35.6*	*4.96*	*48.6*	*5.65*
5600	*35.5*	*5.07*	*48.5*	*5.77*
5800	35.3	5.27	48.2	6.00

(εr = relative permittivity, σ = conductivity and ρ = 1000 kg/m3)

The following table gives the recipes for tissue simulating liquids.

Table-3.2 Recipes of Tissue Simulating Liquid

Tissue Type	Bactericide	DGBE	HEC	NaCl	Sucrose	Triton X-100	Water	Diethylene Glycol Mono-hexylether
H750	0.2	-	0.2	1.4	57.0	-	41.1	-
H835	0.1	-	1.0	1.4	57.0	-	40.5	-
H900	0.1	-	1.0	1.5	56.5	-	40.9	-
H1450	-	45.5	-	0.7	-	-	53.8	-
H1640	-	45.8	-	0.5	-	-	53.7	-
H1750	-	44.5	-	0.3	-	-	55.2	-
H1800	-	44.9	-	0.2	-	-	54.9	-
H1900	-	44.9	-	0.2	-	-	54.9	-
H2000	-	50	-	–	-	-	50	-
H2300	-	44.9	-	0.1	-	-	55.0	-
H2450	-	45.0	-	0.1	-	-	54.9	-
H2600	-	45.1	-	0.1	-	-	54.8	-
H3500	-	8.0	-	0.2	-	20.0	71.8	-
H5G	-	-	-	-	-	17.2	65.52	17.3
B750	0.2	-	0.2	0.8	48.8	-	50.0	-
B835	0.2	-	0.2	0.9	48.5	-	50.2	-
B900	0.2	-	0.2	0.9	48.2	-	50.5	-
B1450	-	34.0	-	0.3	-	-	65.7	-
B1640	-	32.5	-	0.3	-	-	67.2	-
B1750	-	29.4	-	0.4	-	-	70.2	-
B1800	-	29.5	-	0.4	-	-	70.1	-
B1900	-	29.5	-	0.3	-	-	70.2	-
B2000	-	30.0	-	0.2	-	-	69.8	-
B2300	-	31.0	-	0.1	-	-	68.9	-
B2450	-	31.4	-	0.1	-	-	68.5	-
B2600	-	31.8	-	0.1	-	-	68.1	-
B3500	-	28.8	-	0.1	-	-	71.1	-
B5G	-	-	-	-	-	10.7	78.6	10.7

3.5.2 System Check Description

The system check procedure provides a simple, fast, and reliable test method that can be performed daily or before every SAR measurement. The objective here is to ascertain that the measurement system has acceptable accuracy and repeatability. This test requires a flat phantom and a radiating source. The system verification setup is shown as below.



System Verification Setup

3.5.3 Tissue Verification

The measuring results for tissue simulating liquid are shown as below.

Test Date	Tissue Type	Frequency (MHz)	Liquid Temp. (℃)	Measured Conductivity (σ)	Measured Permittivity (ε_r)	Target Conductivity (σ)	Target Permittivity (ε_r)	Conductivity Deviation (%)	Permittivity Deviation (%)
Sep. 18, 2020	Head	835	22.3	0.878	40.600	0.90	41.50	-2.44	-2.17
Sep. 23, 2020	Head	1750	22.2	1.380	39.300	1.37	40.10	0.73	-2.00
Sep. 28, 2020	Head	1900	22.0	1.440	41.000	1.40	40.00	2.86	2.50
Oct. 04, 2020	Head	2450	22.2	1.800	40.400	1.80	39.20	0.00	3.06
Oct. 08, 2020	Head	2600	22.5	2.010	38.300	1.96	39.00	2.55	-1.79

Note:

The dielectric properties of the tissue simulating liquid must be measured within 24 hours before the SAR testing and within ± 5% of the target values. The variation of the liquid temperature must be within ± 2 °C during the test.

3.5.4 System Verification

The measuring result for system verification is tabulated as below.

Test Date	Tissue Type	Frequency (MHz)	1W Target SAR-1g (W/kg)	Measured SAR-1g (W/kg)	Normalized to 1W SAR-1g (W/kg)	Deviation (%)	Dipole S/N	Probe S/N	DAE S/N
Sep. 18, 2020	Head	835	9.45	2.51	10.04	6.24	4d005	3090	662
Sep. 23, 2020	Head	1750	36.90	8.80	35.20	-4.61	1086	3090	662
Sep. 28, 2020	Head	1900	39.60	9.70	38.80	-2.02	509	3090	662
Oct. 04, 2020	Head	2450	52.60	12.60	50.40	-4.18	883	3090	662
Oct. 08, 2020	Head	2600	55.90	14.04	56.16	0.47	1082	3090	662

Note:

Comparing to the reference SAR value, the validation data should be within its specification of 10%. The result indicates the system check can meet the variation criterion and the plots can be referred to Appendix A of this report.

4 SAR Measurement Evaluation

4.1 EUT Configuration and Setting

Connections between EUT and System Simulator

For WWAN SAR testing, the EUT was linked and controlled by base station emulator. Communication between the EUT and the emulator was established by air link. The distance between the EUT and the communicating antenna of the emulator is larger than 50 cm and the output power radiated from the emulator antenna is at least 30 dB smaller than the output power of EUT. The EUT was set from the emulator to radiate maximum output power during SAR testing.

4.1.1 GSM Configuration and Testing

GSM (GMSK: CS1) voice mode transmits with 1 time slot. GPRS (GMSK: CS1) and EDGE (GMSK: MCS1, 8PSK: MCS9) may transmit up to 4 time slots in the 8 time-slot frame according to the multislot class implemented in a device.

4.1.2 WCDMA Configuration and Testing

WCDMA Handsets Head SAR

SAR for next to the ear head exposure is measured using a 12.2 kbps RMC with TPC bits configured to all “1’s”. The 3G SAR test reduction procedure is applied to AMR configurations with 12.2 kbps RMC as the primary mode.

WCDMA Handsets Body-worn SAR

SAR for body-worn configurations is measured using a 12.2 kbps RMC with TPC bits configured to all “1’s”. The 3G SAR test reduction procedure is applied to other spreading codes and multiple $DPDCH_n$ configurations supported by the handset with 12.2 kbps RMC as the primary mode.

Handsets with Release 5 HSDPA

The 3G SAR test reduction procedure is applied to HSDPA body-worn configurations with 12.2 kbps RMC as the primary mode. Otherwise, SAR is measured for HSDPA using the HSDPA body SAR procedures in the “Release 5 HSDPA Data Devices”, for the highest reported SAR body-worn exposure configuration in 12.2 kbps RMC. Handsets with both HSDPA and HSUPA are tested according to Release 6 HSPA test procedures.

Handsets with Release 6 HSUPA

The 3G SAR test reduction procedure is applied to HSPA (HSUPA/HSDPA with RMC) body-worn configurations with 12.2 kbps RMC as the primary mode. Otherwise, SAR is measured for HSPA using the HSPA body SAR procedures in the “Release 6 HSPA Data Devices”, for the highest reported body-worn exposure SAR configuration in 12.2 kbps RMC. When VOIP is applicable for next to the ear head exposure in HSPA, the 3G SAR test reduction procedure is applied to HSPA with 12.2 kbps RMC as the primary mode; otherwise, the same HSPA configuration used for body-worn measurements is tested for next to the ear head exposure.

Release 5 HSDPA Data Devices

The 3G SAR test reduction procedure is applied to body SAR with 12.2 kbps RMC as the primary mode. Otherwise, body SAR for HSDPA is measured using an FRC with H-Set 1 in Sub-test 1 and a 12.2 kbps RMC configured in Test Loop Mode 1, for the highest reported SAR configuration in 12.2 kbps RMC without HSDPA. HSDPA is configured according to the applicable UE category of a test device. The number of HS-DSCH /

HS-PDSCHs, HARQ processes, minimum inter-TTI interval, transport block sizes and RV coding sequence are defined by the H-set. To maintain a consistent test configuration and stable transmission conditions, QPSK is used in the H-set for SAR testing. HS-DPCCH should be configured with a CQI feedback cycle of 4 ms and a CQI repetition factor of 2 to maintain a constant rate of active CQI slots. DPCCH and DPDCH gain factors (β_c, β_d), and HS-DPCCH power offset parameters (Δ_{ACK}, Δ_{NACK}, Δ_{CQI}) are set according to values indicated in below. The CQI value is determined by the UE category, transport block size, number of HS-PDSCHs and modulation used in the H-set.

Sub-test	β_c	β_d	β_d (SF)	β_c / β_d	β_{hs} (1)	CM (dB)(2)	MPR
1	2 / 15	15 / 15	64	2 / 15	4 / 15	0.0	0
2	12 / 15 (3)	15 / 15 (3)	64	12 / 15 (3)	24 / 15	1.0	0
3	15 / 15	8 / 15	64	15 / 8	30 / 15	1.5	0.5
4	15 / 15	4 / 15	64	15 / 4	30 / 15	1.5	0.5

Note 1: Δ_{ACK}, Δ_{NACK} and Δ_{CQI} = 8 ⇔ $A_{hs} = \beta_{hs} / \beta_c = 30 / 15 \Leftrightarrow \beta_{hs} = 30 / 15 * \beta_c$.
Note 2: CM = 1 for $\beta_c / \beta_d = 12 / 15$, $\beta_{hs} / \beta_c = 24 / 15$.
Note 3: For subtest 2 the β_c / β_d ratio of 12 / 15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signaled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 11 / 15$ and $\beta_d = 15 / 15$.

Release 6 HSUPA Data Devices

The 3G SAR test reduction procedure is applied to body SAR with 12.2 kbps RMC as the primary mode. Otherwise, body SAR for HSPA is measured with E-DCH Sub-test 5, using H-Set 1 and QPSK for FRC and a 12.2 kbps RMC configured in Test Loop Mode 1 and power control algorithm 2, according to the highest reported body SAR configuration in 12.2 kbps RMC without HSPA. When VOIP applies to head exposure, the 3G SAR test reduction procedure is applied with 12.2 kbps RMC as the primary mode. Otherwise, the same HSPA configuration used for body SAR measurements are applied to head exposure testing. Due to inner loop power control requirements in HSPA, a communication test set is required for output power and SAR tests. The 12.2 kbps RMC, FRC H-set 1 and E-DCH configurations for HSPA are configured according to the β values indicated in below.

Sub-test	β_c	β_d	β_d (SF)	β_c / β_d	β_{hs} (1)	β_{ec}	β_{ed}	β_{ed} (SF)	β_{ed} (codes)	CM (2) (dB)	MPR (dB)	AG (4) Index	E-TFCI
1	11 / 15 (3)	15 / 15 (3)	64	11 / 15 (3)	22 / 15	209 / 225	1039 / 225	4	1	1.0	0.0	20	75
2	6 / 15	15 / 15	64	6 / 15	12 / 15	12 / 15	94 / 75	4	1	3.0	2.0	12	67
3	15 / 15	9 / 15	64	15 / 9	30 / 15	30 / 15	β_{ed1}: 47/15 β_{ed2}: 47/15	4	2	2.0	1.0	15	92
4	2 / 15	15 / 15	64	2 / 15	4 / 15	2 / 15	56 / 75	4	1	3.0	2.0	17	71
5	15 / 15 (4)	15 / 15 (4)	64	15 / 15 (4)	30 / 15	24 / 15	134 / 15	4	1	1.0	0.0	21	81

Note 1: Δ_{ACK}, Δ_{NACK} and Δ_{CQI} = 8 ⇔ $A_{hs} = \beta_{hs} / \beta_c = 30 / 15 \Leftrightarrow \beta_{hs} = 30 / 15 * \beta_c$.
Note 2: CM = 1 for $\beta_c / \beta_d = 12 / 15$, $\beta_{hs} / \beta_c = 24 / 15$. For all other combinations of DPDCH, DPCCH, HS-DPCCH, E-DPDCH and E-DPCCH the MPR is based on the relative CM difference.
Note 3: For subtest 1 the β_c / β_d ratio of 11 / 15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signaled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 10 / 15$ and $\beta_d = 15 / 15$.
Note 4: For subtest 5 the β_c / β_d ratio of 15 / 15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signaled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 14 / 15$ and $\beta_d = 15 / 15$.
Note 5: Testing UE using E-DPDCH Physical Layer category 1 Sub-test 3 is not required according to TS 25.306 Table 5.1g.
Note 6: β_{ed} cannot be set directly; it is set by Absolute Grant Value.

4.1.3 LTE Configuration and Testing

UE power class is category 3. The LTE maximum power reduction (MPR) in accordance with 3GPP TS 36.101 is active all times during LTE operation. The allowed MPR for the maximum output power please refer to the tune

up procedure.

In addition, the device is compliant with additional maximum power reduction (A-MPR) requirements defined in 3GPP TS 36.101 section 6.2.4 that was disabled for all FCC compliance testing.

A properly configured base station simulator is used for the SAR and power measurements, so spectrum plots for each RB allocation and offset configuration are not included in the SAR report to demonstrate that the tested RB allocations have been correctly established at the maximum output power conditions.

TDD-LTE Setup Configurations

According to KDB 941225 D05, SAR testing for TDD-LTE device must be tested using a fixed periodic duty factor according to the highest transmission duty factor implemented for the device and supported by the defined 3GPP TDD-LTE configurations. The TDD-LTE of this device supports frame structure type 2 defined in 3GPP TS 36.211 section 4.2, and the frame structure configuration can be referred to below.



3GPP TS 36.211 Figure 4.2-1: Frame Structure Type 2

Special Subframe Configuration	Normal Cyclic Prefix in Downlink			Extended Cyclic Prefix in Downlink		
	DwPTS	UpPTS		DwPTS	UpPTS	
		Normal Cyclic Prefix in Uplink	Extended Cyclic Prefix in Uplink		Normal Cyclic Prefix in Uplink	Extended Cyclic Prefix in Uplink
0	6592 • Ts	2192 • Ts	2560 • Ts	7680 • Ts	2192 • Ts	2560 • Ts
1	19760 • Ts			20480 • Ts		
2	21952 • Ts			23040 • Ts		
3	24144 • Ts			25600 • Ts		
4	26336 • Ts			7680 • Ts	4384 • Ts	5120 • Ts
5	6592 • Ts	4384 • Ts	5120 • Ts	20480 • Ts		
6	19760 • Ts			23040 • Ts		
7	21952 • Ts			12800 • Ts		
8	24144 • Ts			-	-	-
9	13168 • Ts			-	-	-

3GPP TS 36.211 Table 4.2-1: Configuration of Special Subframe

Uplink-Downlink Configuration	Downlink-to-Uplink Switch-Point Periodicity	Subframe Number										Duty-Cycle
		0	1	2	3	4	5	6	7	8	9	
0	5 ms	D	S	U	U	U	D	S	U	U	U	63.33%
1	5 ms	D	S	U	U	D	D	S	U	U	D	43.33%
2	5 ms	D	S	U	D	D	D	S	U	D	D	23.33%
3	10 ms	D	S	U	U	U	D	D	D	D	D	31.67%
4	10 ms	D	S	U	U	D	D	D	D	D	D	21.67%
5	10 ms	D	S	U	D	D	D	D	D	D	D	11.67%

6	5 ms	D	S	U	U	U	D	S	U	U	D	53.33%

Uplink-Downlink Configurations and duty cycle

Considering the highest transmission duty cycle, TDD-LTE was tested using Uplink-Downlink Configuration 0 with 6 uplink subframe and 2 special subframe. The special subframe was set to special subframe configuration 7 using extended cyclic prefix uplink. Therefore, SAR testing for TDD-LTE was performed at the maximum output power with highest transmission duty cycle of 63.33%.

4.1.4 WLAN Configuration and Testing

In general, various vendor specific external test software and chipset based internal test modes are typically used for SAR measurement. These chipset based test mode utilities are generally hardware and manufacturer dependent, and often include substantial flexibility to reconfigure or reprogram a device. A Wi-Fi device must be configured to transmit continuously at the required data rate, channel bandwidth and signal modulation, using the highest transmission duty factor supported by the test mode tools for SAR measurement. The test frequencies established using test mode must correspond to the actual channel frequencies. When 802.11 frame gaps are accounted for in the transmission, a maximum transmission duty factor of 92 - 96% is typically achievable in most test mode configurations. A minimum transmission duty factor of 85% is required to avoid certain hardware and device implementation issues related to wide range SAR scaling. In addition, a periodic transmission duty factor is required for current generation SAR systems to measure SAR correctly. The reported SAR must be scaled to 100% transmission duty factor to determine compliance at the maximum tune-up tolerance limit.

According to KDB 248227 D01, this device has installed WLAN engineering testing software which can provide continuous transmitting RF signal. During WLAN SAR testing, this device was operated to transmit continuously at the maximum transmission duty with specified transmission mode, operating frequency, lowest data rate, and maximum output power.

Initial Test Configuration

An initial test configuration is determined for OFDM transmission modes in 2.4 GHz and 5 GHz bands according to the channel bandwidth, modulation and data rate combination(s) with the highest maximum output power specified for production units in each standalone and aggregated frequency band. When the same maximum power is specified for multiple transmission modes in a frequency band, the largest channel bandwidth, lowest order modulation, lowest data rate and lowest order 802.11a/g/n/ac mode is used for SAR measurement, on the highest measured output power channel in the initial test configuration, for each frequency band.

Subsequent Test Configuration

SAR measurement requirements for the remaining 802.11 transmission mode configurations that have not been tested in the initial test configuration are determined separately for each standalone and aggregated frequency band, in each exposure condition, according to the maximum output power specified for production units. Additional power measurements may be required to determine if SAR measurements are required for subsequent highest output power channels in a subsequent test configuration. When the highest reported SAR for the initial test configuration according to the initial test position or fixed exposure position requirements, is adjusted by the ratio of the subsequent test configuration to initial test configuration specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg, SAR is not required for that subsequent test configuration.

SAR Test Configuration and Channel Selection

When multiple channel bandwidth configurations in a frequency band have the same specified maximum output power, the initial test configuration is using largest channel bandwidth, lowest order modulation, lowest data rate, and lowest order 802.11 mode (i.e., 802.11a is chosen over 802.11n then 802.11ac or 802.11g is chosen over 802.11n). After an initial test configuration is determined, if multiple test channels have the same measured maximum output power, the channel chosen for SAR measurement is determined according to the following.

1) The channel closest to mid-band frequency is selected for SAR measurement.

2) For channels with equal separation from mid-band frequency; for example, high and low channels or two mid-band channels, the higher frequency (number) channel is selected for SAR measurement.

4.2 EUT Testing Position

4.2.1 Head Exposure Conditions

RF Exposure Conditions	Test Position	Separation Distance	SAR test exclusion
Head	Right Cheek Right Tilted Left Cheek Left Tilted	0 cm	N/A

Note:

1. Head exposure for voice mode of handset is limited to next to the ear exposure conditions.
2. Devices that are designed to transmit next to the ear must be tested using the SAM phantom.
3. Other head exposure conditions, for example, in-front-of the face, should be tested using a flat phantom according to the required published RF exposure KDB procedures.
4. When data mode operates in next to the ear configurations, either data alone or in conjunction with voice transmissions, SAR evaluation is required for such use conditions.
5. When device supports VoIP, SAR evaluation for head Exposure Conditions using the most appropriate wireless data mode configurations is required.



Fig-4.1 Cheek Position



Fig-4.2 Tilted Position

Define two imaginary lines on the handset

a) The vertical centerline passes through two points on the front side of the handset - the midpoint of the width w_t of the handset at the level of the acoustic output, and the midpoint of the width w_b of the bottom of the handset.

b) The horizontal line is perpendicular to the vertical centerline and passes through the center of the acoustic output. The horizontal line is also tangential to the face of the handset at point A.

c) The two lines intersect at point A. Note that for many handsets, point A coincides with the center of the acoustic output; however, the acoustic output may be located elsewhere on the horizontal line. Also note that the vertical centerline is not necessarily parallel to the front face of the handset, especially for clamshell handsets, handsets with flip covers, and other irregularly shaped handsets.



Fig-4.3 Handset Vertical and Horizontal Reference Lines

4.2.2 Body-worn Accessory Exposure Conditions

RF Exposure Conditions	Test Position	Separation Distance	SAR test exclusion
Body-worn	Front Face	0 ~ 2.5 cm	N/A
	Rear Face		

Note:

1. Body-worn accessories that do not contain metallic or conductive components may be tested according to worst-case exposure configurations, typically according to the smallest test separation distance required for the group of body-worn accessories with similar operating and exposure characteristics. All body-worn accessories containing metallic components are tested in conjunction with the host device.
2. Body-worn accessory SAR compliance is based on a single minimum test separation distance for all wireless and operating modes applicable to each body-worn accessory used by the host, and according to the relevant voice and/or data mode transmissions and operations. If a body-worn accessory supports voice only operations in its normal and expected use conditions, testing of data mode for body-worn compliance is not required.
3. A conservative minimum test separation distance for supporting off-the-shelf body-worn accessories that may be acquired by users of consumer handsets should be used to test for body-worn accessory SAR compliance. This distance is determined by the handset manufacturer according to the typical body-worn accessories users may acquire at the time of equipment certification, but not more than 2.5 cm, to enable users to purchase aftermarket body-worn accessories with the required minimum separation.
4. Devices that are designed to operate on the body of users using lanyards and straps or without requiring additional body-worn accessories must be tested for SAR compliance using a conservative minimum test separation distance ≤ 5 mm to support compliance.
5. When device supports VoIP, SAR evaluation for body-worn accessory Exposure Conditions using the most appropriate wireless data mode configurations is required.
6. Body-worn accessory exposure is typically related to voice mode operations when handsets are carried in body-worn accessories.
7. When the reported SAR for a body-worn accessory, measured without a headset connected to the handset, is > 1.2 W/kg, the highest reported SAR configuration for that wireless mode and frequency band should be repeated for the body-worn accessory with a headset attached to the handset.



Fig-4.4 Body Worn Position

4.2.3 Hotspot Mode Exposure Conditions

RF Exposure Conditions	Test Position	Separation Distance	SAR test exclusion
Hotspot	Front Face	1 cm	Note 2/3
	Rear Face		
	Left Side		
	Right Side		
	Top Side		
	Bottom Side		

Note:

1. The SAR test separation distance for hotspot mode is determined according to device form factor. When the overall length and width of a device is > 9 cm x 5 cm (~3.5” x 2”), a test separation distance of 10 mm is required for hotspot mode SAR measurements. A test separation distance of 5 mm or less is required for smaller devices. The SAR test separation distance for hotspot mode is determined according to device form factor.
2. Hotspot mode SAR is measured for all edges and surfaces of the device with a transmitting antenna located within 25 mm from that surface or edge.
3. Based on the antenna location shown on appendix D of this report, the SAR testing required for hotspot mode is listed on section 4.5.1.



Fig-4.5 Test Positions for Hotspot Mode

4.3 Measured Conducted Power Result

4.3.1 Conducted Power of GSM Band

The measuring conducted average power (Unit: dBm) is shown as below.

Band	GSM850			GSM1900		
Channel	**128**	**190**	**251**	**512**	**661**	**810**
Frequency (MHz)	**824.2**	**836.6**	**848.8**	**1850.2**	**1880.0**	**1909.8**
Maximum Burst-Averaged Output Power						
GSM (GMSK, 1Tx-slot)	32.84	**32.87**	32.83	30.87	**30.90**	30.68
GPRS (GMSK, 1Tx-slot)	32.83	32.85	32.82	30.85	30.88	30.66
GPRS (GMSK, 2Tx-slot)	30.68	30.70	30.64	28.70	28.64	28.58
GPRS (GMSK, 3Tx-slot)	28.80	28.82	28.77	27.09	27.13	26.91
GPRS (GMSK, 4Tx-slot)	26.47	26.51	26.66	25.05	25.00	25.01
EDGE (8PSK, 1Tx-slot)	26.26	26.30	26.16	24.75	27.15	26.25
EDGE (8PSK, 2Tx-slot)	24.60	24.80	24.68	21.70	24.33	23.52
EDGE (8PSK, 3Tx-slot)	22.26	22.12	22.01	17.21	20.47	19.25
EDGE (8PSK, 4Tx-slot)	19.61	19.60	19.54	16.03	20.22	18.91
Maximum Frame-Averaged Output Power						
GSM (GMSK, 1Tx-slot)	23.84	23.87	23.83	21.87	21.90	21.68
GPRS (GMSK, 1Tx-slot)	23.83	23.85	23.82	21.85	21.88	21.66
GPRS (GMSK, 2Tx-slot)	24.68	24.70	24.64	22.70	22.64	22.58
GPRS (GMSK, 3Tx-slot)	24.54	24.56	24.51	22.83	22.87	22.65
GPRS (GMSK, 4Tx-slot)	23.47	23.51	23.66	22.05	22.00	22.01
EDGE (8PSK, 1Tx-slot)	17.26	17.30	17.16	15.75	18.15	17.25
EDGE (8PSK, 2Tx-slot)	18.60	18.80	18.68	15.70	18.33	17.52
EDGE (8PSK, 3Tx-slot)	18.00	17.86	17.75	12.95	16.21	14.99
EDGE (8PSK, 4Tx-slot)	16.61	16.60	16.54	13.03	17.22	15.91

Note:

1. SAR testing was performed on the maximum frame-averaged power mode.
2. The frame-averaged power is linearly proportion to the slot number configured and it is linearly scaled the maximum burst-averaged power based on time slots. The calculated method is shown as below:
   Frame-averaged power = 10 x log (Burst-averaged power mW x Slot used / 8)

4.3.2 Conducted Power of WCDMA Band

Band	WCDMA Band II			WCDMA Band V		
Channel	9262	9400	9538	4132	4182	4233
Frequency (MHz)	1852.4	1880.0	1907.6	826.4	836.4	846.6
RMC 12.2K	23.64	**23.88**	23.85	22.35	**22.39**	22.38
HSDPA Subtest-1	22.94	22.50	22.43	21.81	21.34	21.88
HSDPA Subtest-2	21.19	20.41	20.38	21.93	21.54	21.97
HSDPA Subtest-3	20.10	20.06	20.04	21.92	21.56	22.07
HSDPA Subtest-4	20.33	19.62	19.42	21.99	21.63	22.04
HSUPA Subtest-1	20.28	19.94	19.74	20.18	19.80	20.36
HSUPA Subtest-2	20.83	20.35	20.39	20.47	20.14	20.25
HSUPA Subtest-3	20.61	20.41	20.35	20.19	20.05	20.34
HSUPA Subtest-4	21.20	20.66	20.62	20.22	19.82	20.17
HSUPA Subtest-5	23.12	23.14	23.17	21.96	21.53	22.00

4.3.3 Conducted Power of LTE Band

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)	64QAM			3GPP MPR (dB)
			Low CH 18607	Mid CH 18900	High CH 19193		Low CH 18607	Mid CH 18900	High CH 19193		Low CH 18607	Mid CH 18900	High CH 19193	
			1850.7 MHz	1880.0 MHz	1909.3 MHz		1850.7 MHz	1880.0 MHz	1909.3 MHz		1850.7 MHz	1880.0 MHz	1909.3 MHz	
2 / 1.4M	1	0	23.97	24.23	24.14	0	23.15	23.45	23.38	1	/	/	/	2
	1	2	24.03	24.39	24.35	0	23.37	23.29	23.81	1	/	/	/	2
	1	5	24.02	24.12	24.18	0	23.61	23.19	23.54	1	/	/	/	2
	3	0	24.38	24.77	24.57	0	23.70	23.89	23.79	1	/	/	/	2
	3	1	24.52	24.81	24.85	0	23.69	23.82	24.03	1	/	/	/	2
	3	3	24.68	24.83	24.77	0	23.63	23.78	24.07	1	/	/	/	2
	6	0	23.61	23.73	23.69	1	22.72	22.78	23.02	2	/	/	/	3

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)	64QAM			3GPP MPR (dB)
			Low CH 18615	Mid CH 18900	High CH 19185		Low CH 18615	Mid CH 18900	High CH 19185		Low CH 18615	Mid CH 18900	High CH 19185	
			1851.5 MHz	1880.0 MHz	1908.5 MHz		1851.5 MHz	1880.0 MHz	1908.5 MHz		1851.5 MHz	1880.0 MHz	1908.5 MHz	
2 / 3M	1	0	23.86	24.12	24.06	0	23.24	23.48	23.39	1	/	/	/	2
	1	7	24.01	24.34	24.25	0	23.41	23.38	23.65	1	/	/	/	2
	1	14	24.09	24.09	24.35	0	23.52	23.24	23.62	1	/	/	/	2
	8	0	23.45	23.78	23.62	1	22.67	22.89	22.84	2	/	/	/	3
	8	3	23.50	23.63	23.78	1	22.55	22.71	23.00	2	/	/	/	3
	8	7	23.57	23.94	23.75	1	22.66	22.90	23.03	2	/	/	/	3
	15	0	23.55	23.71	23.63	1	22.60	22.79	22.95	2	/	/	/	3

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)	64QAM			3GPP MPR (dB)
			Low CH 18625	Mid CH 18900	High CH 19175		Low CH 18625	Mid CH 18900	High CH 19175		Low CH 18625	Mid CH 18900	High CH 19175	
			1852.5 MHz	1880.0 MHz	1907.5 MHz		1852.5 MHz	1880.0 MHz	1907.5 MHz		1852.5 MHz	1880.0 MHz	1907.5 MHz	
2 / 5M	1	0	23.88	24.13	24.15	0	23.15	23.49	23.36	1	/	/	/	2
	1	12	24.01	24.34	24.32	0	23.26	23.22	23.69	1	/	/	/	2
	1	24	24.02	24.17	24.31	0	23.62	23.28	23.58	1	/	/	/	2
	12	0	23.51	23.70	23.75	1	22.65	22.74	22.85	2	/	/	/	3
	12	6	23.57	23.66	23.89	1	22.59	22.74	22.91	2	/	/	/	3
	12	13	23.51	23.79	23.88	1	22.70	22.81	22.96	2	/	/	/	3
	25	0	23.49	23.72	23.76	1	22.66	22.81	23.02	2	/	/	/	3

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)	64QAM			3GPP MPR (dB)
			Low CH 18650	Mid CH 18900	High CH 19150		Low CH 18650	Mid CH 18900	High CH 19150		Low CH 18650	Mid CH 18900	High CH 19150	
			1855.0	1880.0	1905.0		1855.0	1880.0	1905.0		1855.0	1880.0	1905.0	

			MHz	MHz	MHz		MHz	MHz	MHz		MHz	MHz	MHz	
2 / 10M	1	0	24.02	24.13	24.16	0	23.18	23.36	23.36	1	/	/	/	2
	1	24	23.86	24.38	24.24	0	23.41	23.33	23.79	1	/	/	/	2
	1	49	24.05	24.25	24.21	0	23.49	23.24	23.64	1	/	/	/	2
	25	0	23.41	23.88	23.63	1	22.61	22.83	22.73	2	/	/	/	3
	25	12	23.44	23.65	23.72	1	22.54	22.76	23.04	2	/	/	/	3
	25	25	23.69	23.85	23.80	1	22.68	22.79	22.96	2	/	/	/	3
	50	0	23.49	23.77	23.72	1	22.57	22.71	22.99	2	/	/	/	3

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)	64QAM			3GPP MPR (dB)
			Low CH 18675 1857.5 MHz	Mid CH 18900 1880.0 MHz	High CH 19125 1902.5 MHz		Low CH 18675 1857.5 MHz	Mid CH 18900 1880.0 MHz	High CH 19125 1902.5 MHz		Low CH 18675 1857.5 MHz	Mid CH 18900 1880.0 MHz	High CH 19125 1902.5 MHz	
2 / 15M	1	0	23.95	24.09	24.17	0	23.18	23.36	23.39	1	/	/	/	2
	1	37	23.99	24.37	24.34	0	23.32	23.39	23.75	1	/	/	/	2
	1	74	24.04	24.20	24.29	0	23.50	23.20	23.59	1	/	/	/	2
	36	0	23.36	23.76	23.74	1	22.68	22.88	22.89	2	/	/	/	3
	36	19	23.53	23.77	23.87	1	22.67	22.89	23.07	2	/	/	/	3
	36	39	23.61	23.80	23.87	1	22.75	22.84	22.92	2	/	/	/	3
	75	0	23.59	23.76	23.78	1	22.63	22.78	22.94	2	/	/	/	3

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)	64QAM			3GPP MPR (dB)
			Low CH 18700 1860.0 MHz	Mid CH 18900 1880.0 MHz	High CH 19100 1900.0 MHz		Low CH 18700 1860.0 MHz	Mid CH 18900 1880.0 MHz	High CH 19100 1900.0 MHz		Low CH 18700 1860.0 MHz	Mid CH 18900 1880.0 MHz	High CH 19100 1900.0 MHz	
2 / 20M	1	0	24.04	24.24	24.22	0	23.32	23.53	23.55	1	/	/	/	2
	1	50	24.03	24.40	24.38	0	23.43	23.42	23.82	1	/	/	/	2
	1	99	24.13	24.26	24.37	0	23.66	23.33	23.65	1	/	/	/	2
	50	0	23.55	23.89	23.75	1	22.75	22.89	22.92	2	/	/	/	3
	50	25	23.64	23.81	23.90	1	22.71	22.89	23.09	2	/	/	/	3
	50	50	23.70	23.95	23.93	1	22.78	22.92	23.07	2	/	/	/	3
	100	0	23.63	23.88	23.83	1	22.75	22.86	23.04	2	/	/	/	3

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)	64QAM			3GPP MPR (dB)
			Low CH 19957 1710.7 MHz	Mid CH 20175 1732.5 MHz	High CH 20393 1754.3 MHz		Low CH 19957 1710.7 MHz	Mid CH 20175 1732.5 MHz	High CH 20393 1754.3 MHz		Low CH 19957 1710.7 MHz	Mid CH 20175 1732.5 MHz	High CH 20393 1754.3 MHz	
4 / 1.4M	1	0	22.55	22.63	22.78	0	21.52	21.54	21.97	1	/	/	/	2
	1	2	22.72	22.70	22.70	0	21.41	21.60	21.80	1	/	/	/	2
	1	5	22.70	22.90	22.74	0	21.42	21.68	21.88	1	/	/	/	2
	3	0	22.89	22.80	22.82	0	22.35	22.40	22.59	1	/	/	/	2
	3	1	22.68	22.73	22.80	0	22.29	22.54	22.71	1	/	/	/	2
	3	3	22.88	22.88	21.87	0	22.45	22.54	22.77	1	/	/	/	2
	6	0	21.78	21.77	21.75	1	21.43	21.42	21.50	2	/	/	/	3

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)	64QAM			3GPP MPR (dB)
			Low CH 19965 1711.5 MHz	Mid CH 20175 1732.5 MHz	High CH 20385 1753.5 MHz		Low CH 19965 1711.5 MHz	Mid CH 20175 1732.5 MHz	High CH 20385 1753.5 MHz		Low CH 19965 1711.5 MHz	Mid CH 20175 1732.5 MHz	High CH 20385 1753.5 MHz	
4 / 3M	1	0	22.68	22.66	22.73	0	21.46	21.43	21.87	1	/	/	/	2
	1	7	22.60	22.79	22.77	0	21.54	21.61	21.87	1	/	/	/	2
	1	14	22.79	22.85	22.89	0	21.52	21.76	21.87	1	/	/	/	2
	8	0	21.74	21.85	21.76	1	21.37	21.36	21.56	2	/	/	/	3
	8	3	21.74	21.81	21.74	1	21.43	21.58	21.70	2	/	/	/	3
	8	7	21.86	21.75	21.02	1	21.54	21.56	21.75	2	/	/	/	3
	15	0	21.79	21.80	21.75	1	21.31	21.40	21.57	2	/	/	/	3

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)	64QAM			3GPP MPR (dB)
			Low CH 19975 1712.5 MHz	Mid CH 20175 1732.5 MHz	High CH 20375 1752.5 MHz		Low CH 19975 1712.5 MHz	Mid CH 20175 1732.5 MHz	High CH 20375 1752.5 MHz		Low CH 19975 1712.5 MHz	Mid CH 20175 1732.5 MHz	High CH 20375 1752.5 MHz	
4 / 5M	1	0	22.63	22.66	22.87	0	21.48	21.42	21.90	1	/	/	/	2
	1	12	22.77	22.77	22.83	0	21.50	21.56	21.80	1	/	/	/	2
	1	24	22.79	22.93	22.78	0	21.50	21.62	21.81	1	/	/	/	2
	12	0	21.84	21.78	21.80	1	21.31	21.49	21.68	2	/	/	/	3
	12	6	21.76	21.81	21.76	1	21.36	21.62	21.60	2	/	/	/	3
	12	13	21.85	21.85	21.02	1	21.60	21.64	21.73	2	/	/	/	3
	25	0	21.66	21.77	21.74	1	21.40	21.44	21.59	2	/	/	/	3

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)	64QAM			3GPP MPR (dB)
			Low CH 20000 1715.0 MHz	Mid CH 20175 1732.5 MHz	High CH 20350 1750.0 MHz		Low CH 20000 1715.0 MHz	Mid CH 20175 1732.5 MHz	High CH 20350 1750.0 MHz		Low CH 20000 1715.0 MHz	Mid CH 20175 1732.5 MHz	High CH 20350 1750.0 MHz	
4 / 10M	1	0	22.60	22.67	22.73	0	21.39	21.47	21.92	1	/	/	/	2
	1	24	22.75	22.77	22.83	0	21.50	21.51	21.82	1	/	/	/	2
	1	49	22.81	22.93	22.85	0	21.35	21.68	21.80	1	/	/	/	2
	25	0	21.72	21.83	21.77	1	21.30	21.42	21.59	2	/	/	/	3
	25	12	21.72	21.92	21.79	1	21.31	21.56	21.56	2	/	/	/	3
	25	25	21.82	21.77	21.06	1	21.56	21.64	21.71	2	/	/	/	3
	50	0	21.81	21.79	21.69	1	21.34	21.48	21.53	2	/	/	/	3

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)	64QAM			3GPP MPR (dB)
			Low CH 20025 1717.5 MHz	Mid CH 20175 1732.5 MHz	High CH 20325 1747.5 MHz		Low CH 20025 1717.5 MHz	Mid CH 20175 1732.5 MHz	High CH 20325 1747.5 MHz		Low CH 20025 1717.5 MHz	Mid CH 20175 1732.5 MHz	High CH 20325 1747.5 MHz	
4 / 15M	1	0	22.68	22.57	22.75	0	21.44	21.41	21.90	1	/	/	/	2
	1	37	22.61	22.75	22.76	0	21.40	21.65	21.81	1	/	/	/	2
	1	74	22.69	22.85	22.77	0	21.37	21.61	21.79	1	/	/	/	2
	36	0	21.73	21.80	21.89	1	21.27	21.48	21.57	2	/	/	/	3
	36	19	21.72	21.84	21.85	1	21.43	21.47	21.68	2	/	/	/	3
	36	39	21.79	21.82	21.03	1	21.54	21.57	21.67	2	/	/	/	3
	75	0	21.67	21.81	21.80	1	21.33	21.43	21.53	2	/	/	/	3

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)	64QAM			3GPP MPR (dB)
			Low CH 20050 1720.0 MHz	Mid CH 20175 1732.5 MHz	High CH 20300 1745.0 MHz		Low CH 20050 1720.0 MHz	Mid CH 20175 1732.5 MHz	High CH 20300 1745.0 MHz		Low CH 20050 1720.0 MHz	Mid CH 20175 1732.5 MHz	High CH 20300 1745.0 MHz	
4 / 20M	1	0	22.75	22.77	22.87	0	21.58	21.60	21.98	1	/	/	/	2
	1	50	22.77	22.81	22.90	0	21.55	21.68	21.95	1	/	/	/	2
	1	99	22.86	22.96	22.93	0	21.55	21.77	21.90	1	/	/	/	2
	50	0	21.90	21.96	21.95	1	21.44	21.56	21.75	2	/	/	/	3
	50	25	21.77	21.93	21.93	1	21.48	21.67	21.74	2	/	/	/	3
	50	50	21.90	21.92	21.07	1	21.63	21.66	21.83	2	/	/	/	3
	100	0	21.86	21.89	21.88	1	21.50	21.54	21.68	2	/	/	/	3

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)	64QAM			3GPP MPR (dB)
			Low CH 20407 824.7 MHz	Mid CH 20525 836.5 MHz	High CH 20643 848.3 MHz		Low CH 20407 824.7 MHz	Mid CH 20525 836.5 MHz	High CH 20643 848.3 MHz		Low CH 20407 824.7 MHz	Mid CH 20525 836.5 MHz	High CH 20643 848.3 MHz	
5 / 1.4M	1	0	22.30	22.37	22.24	0	22.10	21.94	21.95	1	/	/	/	2
	1	2	22.39	22.31	22.30	0	21.82	21.84	21.78	1	/	/	/	2
	1	5	22.28	22.33	22.36	0	21.96	21.87	21.95	1	/	/	/	2
	3	0	22.92	22.94	22.94	0	22.04	21.94	21.72	1	/	/	/	2
	3	1	23.00	22.88	22.65	0	21.83	21.89	22.00	1	/	/	/	2
	3	3	23.03	22.93	23.03	0	21.98	21.86	21.90	1	/	/	/	2
	6	0	21.86	21.81	21.85	1	20.82	20.99	20.96	2	/	/	/	3

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)	64QAM			3GPP MPR (dB)
			Low CH 20415 825.5 MHz	Mid CH 20525 836.5 MHz	High CH 20635 847.5 MHz		Low CH 20415 825.5 MHz	Mid CH 20525 836.5 MHz	High CH 20635 847.5 MHz		Low CH 20415 825.5 MHz	Mid CH 20525 836.5 MHz	High CH 20635 847.5 MHz	
5 / 3M	1	0	22.37	22.39	22.33	0	21.94	21.82	21.91	1	/	/	/	2
	1	7	22.26	22.33	22.20	0	21.92	22.01	21.96	1	/	/	/	2
	1	14	22.37	22.27	22.34	0	21.99	21.88	21.98	1	/	/	/	2
	8	0	22.00	21.80	21.92	1	20.92	20.91	20.81	2	/	/	/	3
	8	3	21.97	21.77	21.75	1	20.76	20.88	20.95	2	/	/	/	3
	8	7	21.95	21.94	21.87	1	20.95	20.91	20.92	2	/	/	/	3
	15	0	21.81	21.82	21.79	1	20.89	21.02	21.08	2	/	/	/	3

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)	64QAM			3GPP MPR (dB)
			Low CH 20425 826.5 MHz	Mid CH 20525 836.5 MHz	High CH 20625 846.5 MHz		Low CH 20425 826.5 MHz	Mid CH 20525 836.5 MHz	High CH 20625 846.5 MHz		Low CH 20425 826.5 MHz	Mid CH 20525 836.5 MHz	High CH 20625 846.5 MHz	
5 / 5M	1	0	22.27	22.27	22.41	0	22.04	21.88	21.88	1	/	/	/	2
	1	12	22.33	22.39	22.30	0	21.93	21.87	21.95	1	/	/	/	2
	1	24	22.35	22.32	22.42	0	21.97	21.91	22.06	1	/	/	/	2
	12	0	22.06	21.89	21.85	1	21.00	20.92	20.78	2	/	/	/	3
	12	6	21.90	21.91	21.69	1	20.86	20.82	21.06	2	/	/	/	3
	12	13	22.01	22.02	21.89	1	21.01	20.81	20.97	2	/	/	/	3
	25	0	21.71	21.83	21.90	1	20.72	21.03	21.09	2	/	/	/	3

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)	64QAM			3GPP MPR (dB)
			Low CH 20450 829.0 MHz	Mid CH 20525 836.5 MHz	High CH 20600 844.0 MHz		Low CH 20450 829.0 MHz	Mid CH 20525 836.5 MHz	High CH 20600 844.0 MHz		Low CH 20450 829.0 MHz	Mid CH 20525 836.5 MHz	High CH 20600 844.0 MHz	
5 / 10M	1	0	22.45	22.42	22.41	0	22.11	22.02	22.07	1	/	/	/	2
	1	24	22.41	22.48	22.40	0	21.98	22.04	21.97	1	/	/	/	2
	1	49	22.39	22.37	22.47	0	22.00	21.97	22.13	1	/	/	/	2
	25	0	22.09	21.94	22.02	1	21.10	21.00	20.87	2	/	/	/	3
	25	12	22.06	21.95	21.85	1	20.91	21.01	21.15	2	/	/	/	3
	25	25	22.07	22.10	22.03	1	21.05	20.92	21.05	2	/	/	/	3
	50	0	21.91	21.95	21.92	1	20.91	21.10	21.12	2	/	/	/	3

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)	64QAM			3GPP MPR (dB)
			Low CH 20775 2502.5 MHz	Mid CH 21100 2535.0 MHz	High CH 21425 2567.5 MHz		Low CH 20775 2502.5 MHz	Mid CH 21100 2535.0 MHz	High CH 21425 2567.5 MHz		Low CH 20775 2502.5 MHz	Mid CH 21100 2535.0 MHz	High CH 21425 2567.5 MHz	
7 / 5M	1	0	23.85	24.03	24.14	0	23.20	23.41	23.29	1	/	/	/	2
	1	12	23.85	24.00	24.02	0	23.32	23.31	23.61	1	/	/	/	2
	1	24	24.13	24.21	24.06	0	23.43	23.52	23.57	1	/	/	/	2
	12	0	23.36	23.61	23.72	1	23.11	23.42	23.31	2	/	/	/	3
	12	6	23.50	23.80	23.83	1	23.18	23.48	23.60	2	/	/	/	3
	12	13	23.55	23.72	23.80	1	23.38	23.28	23.56	2	/	/	/	3
	25	0	23.57	23.78	23.68	1	23.18	23.25	23.45	2	/	/	/	3

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)	64QAM			3GPP MPR (dB)
			Low CH 20800 2505.0 MHz	Mid CH 21100 2535.0 MHz	High CH 21400 2565.0 MHz		Low CH 20800 2505.0 MHz	Mid CH 21100 2535.0 MHz	High CH 21400 2565.0 MHz		Low CH 20800 2505.0 MHz	Mid CH 21100 2535.0 MHz	High CH 21400 2565.0 MHz	
7 / 10M	1	0	23.87	23.93	24.20	0	23.24	23.31	23.34	1	/	/	/	2
	1	24	23.96	23.99	24.06	0	23.21	23.31	23.49	1	/	/	/	2
	1	49	24.12	24.28	24.19	0	23.40	23.53	23.41	1	/	/	/	2
	25	0	23.44	23.63	23.66	1	23.09	23.33	23.41	2	/	/	/	3
	25	12	23.51	23.71	23.76	1	23.28	23.44	23.44	2	/	/	/	3
	25	25	23.54	23.71	23.84	1	23.37	23.36	23.56	2	/	/	/	3
	50	0	23.61	23.64	23.81	1	23.12	23.38	23.39	2	/	/	/	3

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)	64QAM			3GPP MPR (dB)
			Low CH 20825 2507.5 MHz	Mid CH 21100 2535.0 MHz	High CH 21375 2562.5 MHz		Low CH 20825 2507.5 MHz	Mid CH 21100 2535.0 MHz	High CH 21375 2562.5 MHz		Low CH 20825 2507.5 MHz	Mid CH 21100 2535.0 MHz	High CH 21375 2562.5 MHz	
7 / 15M	1	0	23.81	23.97	24.18	0	23.35	23.35	23.33	1	/	/	/	2
	1	37	23.85	24.10	24.13	0	23.31	23.47	23.66	1	/	/	/	2
	1	74	24.17	24.15	24.16	0	23.36	23.57	23.46	1	/	/	/	2
	36	0	23.43	23.55	23.78	1	23.08	23.42	23.46	2	/	/	/	3
	36	19	23.63	23.74	23.76	1	23.32	23.44	23.55	2	/	/	/	3
	36	39	23.69	23.73	23.87	1	23.40	23.30	23.38	2	/	/	/	3
	75	0	23.51	23.66	23.65	1	23.11	23.25	23.42	2	/	/	/	3

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)	64QAM			3GPP MPR (dB)
			Low CH 20850 2510.0 MHz	Mid CH 21100 2535.0 MHz	High CH 21350 2560.0 MHz		Low CH 20850 2510.0 MHz	Mid CH 21100 2535.0 MHz	High CH 21350 2560.0 MHz		Low CH 20850 2510.0 MHz	Mid CH 21100 2535.0 MHz	High CH 21350 2560.0 MHz	
7 / 20M	1	0	24.00	24.09	24.21	0	23.36	23.45	23.44	1	/	/	/	2
	1	50	24.03	24.11	24.22	0	23.35	23.48	23.67	1	/	/	/	2
	1	99	24.17	24.29	24.25	0	23.47	23.63	23.59	1	/	/	/	2
	50	0	23.54	23.63	23.80	1	23.24	23.46	23.50	2	/	/	/	3
	50	25	23.64	23.80	23.88	1	23.32	23.50	23.63	2	/	/	/	3
	50	50	23.72	23.90	23.87	1	23.43	23.46	23.57	2	/	/	/	3
	100	0	23.62	23.84	23.83	1	23.19	23.40	23.50	2	/	/	/	3

4.3.4 Conducted Power of WLAN

Mode		Channel	Frequency (MHz)	Average Power (dBm)
2.4G	802.11b	1	2412	17.13
		6	2437	16.32
		11	2462	16.46
	802.11g	1	2412	13.21
		6	2437	16.34
		11	2462	14.94
	802.11n (HT20)	1	2412	14.53
		6	2437	11.96
		11	2462	13.71

4.3.5 Conducted Power of BT

Mode		Channel	Frequency (MHz)	Average Power (dBm)
BR + EDR	GFSK	0	2402	3.59
		39	2441	3.38
		78	2480	3.72
	π/4-DQPSK	0	2402	2.85
		39	2441	2.62
		78	2480	3.00
	8-DPSK	0	2402	2.90
		39	2441	2.66
		78	2480	3.01

Mode		Channel	Frequency (MHz)	Average Power (dBm)
LE	LE	0	2402	-2.49
		19	2440	-4.46
		39	2480	-4.08

4.4 SAR Test Exclusion Evaluations

4.4.1 Standalone SAR Test Exclusion Considerations

According to KDB 447498 D01, the SAR test exclusion condition is based on source-based time-averaged maximum conducted output power, adjusted for tune-up tolerance, and the minimum test separation distance required for the exposure conditions. The 1-g and 10-g *SAR test exclusion thresholds* are determined by the following:

a) For 100 MHz to 6 GHz and *test separation distances* ≤ 50 mm:

$$\frac{Max.Tune\ up\ Power_{(mW)}}{Min.Test\ Separation\ Distance_{(mm)}} \times \sqrt{f_{(GHz)}} \leq 3.0 \text{ for SAR-1g, } \leq 7.5 \text{ for SAR-10g}$$

When the minimum *test separation distance* is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

b) For 100 MHz to 1500 MHz and *test separation distances* > 50 mm:

{[Threshold for 50 mm in step a)] + [(test separation distance – 50 mm) · ($f_{(MHz)}$/150)]} mW

c) For > 1500 MHz and ≤ 6 GHz and *test separation distances* > 50 mm:

{[Threshold for 50 mm in step a)] + [(test separation distance – 50 mm) ·10]} mW

When the calculated result in step a) is <= 3.0 for SAR-1g exposure condition, or <= 7.5 for SAR-10g exposure condition, the SAR testing exclusion is applied.

When the device output power is less than the calculated result (power threshold, mW) shown in in step b) and c), the SAR testing exclusion is applied.

Mode / Band	Frequency (GHz)	Max. Tune-up Power (dBm)	Test Position	Max. Tune-up (mW)	√f(GHz)	value	Limit	SAR Test (Yes/No)
BT (DSS)	2.48	4.5	Head	2.82	1.575	0.9	3.0	No
BT (DSS)	2.48	4.5	Body-worn	2.82	1.575	0.4	3.0	No

4.4.2 Estimated SAR Calculation

According to KDB 447498 D01, when an antenna qualifies for the standalone SAR test exclusion and also transmits simultaneously with other antennas, the standalone SAR value must be estimated according to the following to determine the simultaneous transmission SAR test exclusion criteria:

a) For *test separation distances* ≤ 50 mm:

$$Estimated\ SAR = \frac{Max.Tune\ up\ Power_{(mW)}}{Min.Test\ Separation\ Distance_{(mm)}} \times \frac{\sqrt{f(\mathrm{GHz})}}{x}$$

Where x = 7.5 for 1-g SAR and x = 18.75 for 10-g SAR.

b) For *test separation distances* > 50 mm, 0.4 W/kg for 1-g SAR and 1.0 W/kg for 10-g SAR.

Mode / Band	Frequency (GHz)	Max. Tune-up Power (dBm)	Test Position	Separation Distance (mm)	Estimated SAR (W/kg)
BT (DSS)	2.48	4.5	Head	5	0.12
BT (DSS)	2.48	4.5	Body-worn	10	0.06

4.5 SAR Testing Results

4.5.1 SAR Test Reduction Considerations

KDB 447498 D01 General RF Exposure Guidance

Testing of other required channels within the operating mode of a frequency band is not required when the *reported* SAR for the mid-band or highest output power channel is:

a) ≤ 0.8 W/kg or 2.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≤ 100 MHz
b) ≤ 0.6 W/kg or 1.5 W/kg, for 1-g or 10-g respectively, when the transmission band is between 100 MHz and 200 MHz
c) ≤ 0.4 W/kg or 1.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≥ 200 MHz

KDB 941225 D01 3G SAR Procedures

a) GSM SAR Test Reduction

SAR test reduction for GPRS and EDGE modes is determined by the source-based time-averaged output power specified for production units, including tune-up tolerance. The data mode with highest specified time-averaged output power should be tested for SAR compliance in the applicable exposure conditions. For modes with the same specified maximum output power and tolerance, the higher number time-slot configuration should be tested. The GMSK EDGE configurations are grouped with GPRS and considered with respect to time-averaged maximum output power to determine compliance. The 3G SAR test reduction procedure is applied to 8-PSK EDGE with GMSK GPRS/EDGE as the primary mode.

b) 3G SAR Test Reduction Procedure

The mode tested for SAR is referred to as the primary mode. The equivalent modes considered for SAR test reduction are denoted as secondary modes. Both primary and secondary modes must be in the same frequency band. When the maximum output power and tune-up tolerance specified for production units in a secondary mode is ≤ 1/4 dB higher than the primary mode or when the highest reported SAR of the primary mode is scaled by the ratio of specified maximum output power and tune-up tolerance of secondary to primary mode and the adjusted SAR is ≤ 1.2 W/kg, SAR measurement is not required for the secondary mode.

KDB 941225 D05 SAR for LTE Devices

a) QPSK with 1 RB and 50% RB allocation

Start with the largest channel bandwidth and measure SAR, using the RB offset and required test channel combination with the highest maximum output power among RB offsets at the upper edge, middle and lower edge of each required test channel. When the reported SAR is ≤ 0.8 W/kg, testing of the remaining RB offset configurations and required test channels is not required; otherwise, SAR is required for the remaining required test channels and only for the RB offset configuration with the highest output power for that channel. When the reported SAR of a required test channel is > 1.45 W/kg, SAR is required for all three RB offset configurations for that required test channel.

b) QPSK with 100% RB allocation

SAR is not required when the highest maximum output power for 100% RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation are ≤ 0.8 W/kg. Otherwise, SAR is measured for the highest output power channel; and if the reported SAR is > 1.45 W/kg, the remaining required test channels must also be tested.

c) Higher order modulations

SAR is required only when the highest maximum output power for the configuration in the higher order

modulation is > 1/2 dB higher than the same configuration in QPSK or when the reported SAR for the QPSK configuration is > 1.45 W/kg.

d) Other channel bandwidth
SAR is required when the highest maximum output power of the smaller channel bandwidth is > 1/2 dB higher than the equivalent channel configurations in the largest channel bandwidth configuration or the reported SAR of a configuration for the largest channel bandwidth is > 1.45 W/kg.

KDB 941225 D06 Hot Spot SAR

Hotspot mode SAR is measured for all edges and surfaces of the device with a transmitting antenna located within 25 mm from that surface or edge.

Antenna	Front Face	Rear Face	Left Side	Right Side	Top Side	Bottom Side
WWAN Ant	Yes	Yes	Yes	Yes	N/A	Yes
WLAN / BT	Yes	Yes	N/A	Yes	Yes	N/A

KDB 248227 D01 Wi-Fi SAR

a) For handsets operating next to ear, hotspot mode or mini-tablet configurations, the initial test position procedures were applied. The test position with the highest extrapolated peak SAR will be used as the initial test position. When the reported SAR of initial test position is <= 0.4 W/kg, SAR testing for remaining test positions is not required. Otherwise, SAR is evaluated at the subsequent highest peak SAR positions until the reported SAR result is <= 0.8 W/kg or all test positions are measured.

b) For WLAN 2.4 GHz, the highest measured maximum output power channel for DSSS was selected for SAR measurement. When the reported SAR is <= 0.8 W/kg, no further SAR testing is required. Otherwise, SAR is evaluated at the next highest measured output power channel. When any reported SAR is > 1.2 W/kg, SAR is required for the third channel. For OFDM modes (802.11g/n), SAR is not required when the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and it is <= 1.2 W/kg.

c) For WLAN 5 GHz, the initial test configuration was selected according to the transmission mode with the highest maximum output power. When the reported SAR of initial test configuration is > 0.8 W/kg, SAR is required for the subsequent highest measured output power channel until the reported SAR result is <= 1.2 W/kg or all required channels are measured. For other transmission modes, SAR is not required when the highest reported SAR for initial test configuration is adjusted by the ratio of subsequent test configuration to initial test configuration specified maximum output power and it is <= 1.2 W/kg.

d) For WLAN MIMO mode, the power-based standalone SAR test exclusion or the sum of SAR provision in KDB 447498 to determine simultaneous transmission SAR test exclusion should be applied. Otherwise, SAR for MIMO mode will be measured with all applicable antennas transmitting simultaneously at the specified maximum output power of MIMO operation.

4.5.2 SAR Results for Head Exposure Condition

Band	Mode	Test Position	Ch.	RB	offset	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Measured SAR-1g (W/kg)	Scaling Factor	Scaled SAR-1g (W/kg)
GSM850	GSM	Right Cheek	190	-	-	33.5	32.87	0.520	1.16	**0.601**
GSM850	GSM	Right Tilted	190	-	-	33.5	32.87	0.516	1.16	0.597
GSM850	GSM	Left Cheek	190	-	-	33.5	32.87	0.413	1.16	0.477
GSM850	GSM	Left Tilted	190	-	-	33.5	32.87	0.367	1.16	0.424
GSM1900	GSM	Right Cheek	661	-	-	32.0	30.90	0.074	1.29	0.095
GSM1900	GSM	Right Tilted	661	-	-	32.0	30.90	0.068	1.29	0.088
GSM1900	GSM	Left Cheek	661	-	-	32.0	30.90	0.183	1.29	**0.236**
GSM1900	GSM	Left Tilted	661	-	-	32.0	30.90	0.040	1.29	0.052
WCDMA II	RMC12.2K	Right Cheek	9400	-	-	24.5	23.88	0.137	1.15	0.158
WCDMA II	RMC12.2K	Right Tilted	9400	-	-	24.5	23.88	0.120	1.15	0.138
WCDMA II	RMC12.2K	Left Cheek	9400	-	-	24.5	23.88	0.225	1.15	**0.260**
WCDMA II	RMC12.2K	Left Tilted	9400	-	-	24.5	23.88	0.101	1.15	0.116
WCDMA V	RMC12.2K	Right Cheek	4132	-	-	23.5	22.39	0.210	1.29	**0.271**
WCDMA V	RMC12.2K	Right Tilted	4132	-	-	23.5	22.39	0.169	1.29	0.218
WCDMA V	RMC12.2K	Left Cheek	4132	-	-	23.5	22.39	0.200	1.29	0.258
WCDMA V	RMC12.2K	Left Tilted	4132	-	-	23.5	22.39	0.151	1.29	0.195
LTE 2	QPSK20M	Right Cheek	18900	1	50	25.70	24.40	0.126	1.35	0.170
LTE 2	QPSK20M	Right Tilted	18900	1	50	25.70	24.40	0.072	1.35	0.097
LTE 2	QPSK20M	Left Cheek	18900	1	50	25.70	24.40	0.219	1.35	**0.295**
LTE 2	QPSK20M	Left Tilted	18900	1	50	25.70	24.40	0.076	1.35	0.103
LTE 2	QPSK20M	Right Cheek	18900	50	50	24.70	23.95	0.106	1.19	0.126
LTE 2	QPSK20M	Right Tilted	18900	50	50	24.70	23.95	0.066	1.19	0.078
LTE 2	QPSK20M	Left Cheek	18900	50	50	24.70	23.95	0.201	1.19	0.239
LTE 2	QPSK20M	Left Tilted	18900	50	50	24.70	23.95	0.068	1.19	0.081
LTE 4	QPSK20M	Right Cheek	20300	1	99	23.50	22.96	0.183	1.13	0.207
LTE 4	QPSK20M	Right Tilted	20300	1	99	23.50	22.96	0.075	1.13	0.085
LTE 4	QPSK20M	Left Cheek	20300	1	99	23.50	22.96	0.346	1.13	**0.392**
LTE 4	QPSK20M	Left Tilted	20300	1	99	23.50	22.96	0.123	1.13	0.139
LTE 4	QPSK20M	Right Cheek	20300	50	0	22.50	21.96	0.160	1.13	0.181
LTE 4	QPSK20M	Right Tilted	20300	50	0	22.50	21.96	0.070	1.13	0.079
LTE 4	QPSK20M	Left Cheek	20300	50	0	22.50	21.96	0.274	1.13	0.310
LTE 4	QPSK20M	Left Tilted	20300	50	0	22.50	21.96	0.083	1.13	0.094
LTE 5	QPSK10M	Right Cheek	20525	1	24	23.50	22.48	0.284	1.26	**0.359**
LTE 5	QPSK10M	Right Tilted	20525	1	24	23.50	22.48	0.241	1.26	0.305
LTE 5	QPSK10M	Left Cheek	20525	1	24	23.50	22.48	0.175	1.26	0.221
LTE 5	QPSK10M	Left Tilted	20525	1	24	23.50	22.48	0.125	1.26	0.158
LTE 5	QPSK10M	Right Cheek	20525	25	25	22.50	22.10	0.243	1.10	0.266
LTE 5	QPSK10M	Right Tilted	20525	25	25	22.50	22.10	0.189	1.10	0.207
LTE 5	QPSK10M	Left Cheek	20525	25	25	22.50	22.10	0.141	1.10	0.155
LTE 5	QPSK10M	Left Tilted	20525	25	25	22.50	22.10	0.126	1.10	0.138
LTE 7	QPSK20M	Right Cheek	21100	1	99	25.70	24.29	0.043	1.38	**0.059**
LTE 7	QPSK20M	Right Tilted	21100	1	99	25.70	24.29	0.021	1.38	0.029

LTE 7	QPSK20M	Left Cheek	21100	1	99	25.70	24.29	0.031	1.38	0.043
LTE 7	QPSK20M	Left Tilted	21100	1	99	25.70	24.29	0.011	1.38	0.015
LTE 7	QPSK20M	Right Cheek	21100	50	50	24.70	23.90	0.025	1.20	0.030
LTE 7	QPSK20M	Right Tilted	21100	50	50	24.70	23.90	0.013	1.20	0.016
LTE 7	QPSK20M	Left Cheek	21100	50	50	24.70	23.90	0.017	1.20	0.021
LTE 7	QPSK20M	Left Tilted	21100	50	50	24.70	23.90	0.005	1.20	0.006
802.11b	-	Right Cheek	6	-	-	18.00	17.19	0.730	1.21	0.880
802.11b	-	Right Cheek	1	-	-	18.00	17.58	0.711	1.10	0.783
802.11b	-	Right Cheek	11	-	-	18.00	17.02	0.751	1.25	**0.941**
802.11b	-	Right Cheek Repeated	11	-	-	18.00	17.02	0.741	1.25	0.929
802.11b	-	Right Tilted	6	-	-	18.00	17.19	0.629	1.21	0.758
802.11b	-	Left Cheek	6	-	-	18.00	17.19	0.548	1.21	0.660
802.11b	-	Left Tilted	6	-	-	18.00	17.19	0.325	1.21	0.392

4.5.3 SAR Results for Body-worn Exposure Condition (Separation Distance is 10mm)

Band	Mode	Test Position	Separation Distance (mm)	Ch.	RB	offset	Headset	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Measured SAR-1g (W/kg)	Scaling Factor	Scaled SAR-1g (W/kg)
GSM850	GPRS 2TS	Front Face	10	190	-	-	-	31.50	30.70	0.137	1.20	0.165
GSM850	GPRS 2TS	Rear Face	10	190	-	-	-	31.50	30.70	0.184	1.20	**0.221**
GSM1900	GPRS 3TS	Front Face	10	661	-	-	-	28.00	27.13	0.110	1.22	0.134
GSM1900	GPRS 3TS	Rear Face	10	661	-	-	-	28.00	27.13	0.123	1.22	**0.150**
WCDMA II	RMC12.2K	Front Face	10	9400	-	-	-	24.50	23.88	0.740	1.15	0.854
WCDMA II	RMC12.2K	Rear Face	10	9400	-	-	-	24.50	23.88	1.140	1.15	**1.315**
WCDMA II	RMC12.2K	Rear Face	10	9262	-	-	-	24.50	23.64	1.070	1.22	1.304
WCDMA II	RMC12.2K	Rear Face	10	9538	-	-	-	24.50	23.85	1.103	1.16	1.281
WCDMA II	RMC12.2K	Rear Face Repeated	10	9400	-	-	-	24.50	23.88	1.110	1.15	1.280
WCDMA II	RMC12.2K	Rear Face	10	9400	-	-	Headset	24.50	23.88	1.030	1.15	1.188
WCDMA V	RMC12.2K	Front Face	10	4132	-	-	-	23.50	22.39	0.391	1.29	0.505
WCDMA V	RMC12.2K	Rear Face	10	4132	-	-	-	23.50	22.39	0.416	1.29	**0.537**
LTE 2	QPSK20M	Front Face	10	18900	1	50	-	25.70	24.40	0.769	1.35	1.037
LTE 2	QPSK20M	Front Face	10	18700	1	50	-	25.70	24.03	0.658	1.47	0.967
LTE 2	QPSK20M	Front Face	10	19100	1	50	-	25.70	24.38	0.667	1.36	0.904
LTE 2	QPSK20M	Rear Face	10	18900	1	50	-	25.70	24.40	1.000	1.35	**1.349**
LTE 2	QPSK20M	Rear Face Repeated	10	18900	1	50	-	25.70	24.40	0.988	1.35	1.333
LTE 2	QPSK20M	Rear Face	10	18700	1	50	-	25.70	24.03	0.900	1.47	1.322
LTE 2	QPSK20M	Rear Face	10	19100	1	50	-	25.70	24.38	0.987	1.36	1.338
LTE 2	QPSK20M	Front Face	10	18900	50	50	-	24.70	23.95	0.654	1.19	0.777
LTE 2	QPSK20M	Rear Face	10	18900	50	50	-	24.70	23.95	1.130	1.19	1.343
LTE 2	QPSK20M	Rear Face	10	18700	50	50	-	24.70	23.70	1.059	1.26	1.333
LTE 2	QPSK20M	Rear Face	10	19100	50	50	-	24.70	23.93	1.111	1.19	1.327
LTE 2	QPSK20M	Front Face	10	18900	100	0	-	24.70	23.88	0.656	1.21	0.792
LTE 2	QPSK20M	Rear Face	10	18900	100	0	-	24.70	23.88	1.096	1.21	1.324
LTE 2	QPSK20M	Rear Face	10	18900	1	50	Headset	25.70	24.40	0.88	1.35	1.187
LTE 4	QPSK20M	Front Face	10	20175	1	99	-	23.50	22.96	0.721	1.13	0.816
LTE 4	QPSK20M	Front Face	10	20050	1	99	-	23.50	22.86	0.965	1.16	1.118
LTE 4	QPSK20M	Front Face	10	20300	1	99	-	23.50	22.93	0.598	1.14	0.682
LTE 4	QPSK20M	Rear Face	10	20175	1	99	-	23.50	22.96	0.971	1.13	1.100
LTE 4	QPSK20M	Rear Face	10	20050	1	99	-	23.50	22.86	1.100	1.16	**1.275**
LTE 4	QPSK20M	Rear Face Repeated	10	20050	1	99	-	23.50	22.86	1.089	1.16	1.262
LTE 4	QPSK20M	Rear Face	10	20300	1	99	-	23.50	22.93	0.780	1.14	0.889
LTE 4	QPSK20M	Front Face	10	20175	50	0	-	22.50	21.96	0.497	1.13	0.563
LTE 4	QPSK20M	Rear Face	10	20175	50	0	-	22.50	21.96	0.704	1.13	0.797
LTE 4	QPSK20M	Front Face	10	20175	100	0	-	22.50	21.89	0.788	1.15	0.907
LTE 4	QPSK20M	Rear Face	10	20175	100	0	-	22.50	21.89	1.048	1.15	1.206
LTE 4	QPSK20M	Rear Face	10	20050	1	99	Headset	23.50	22.86	1.000	1.16	1.159
LTE 5	QPSK10M	Front Face	10	20525	1	24	-	23.50	22.48	0.289	1.26	0.366
LTE 5	QPSK10M	Rear Face	10	20525	1	24	-	23.50	22.48	0.424	1.26	**0.536**
LTE 5	QPSK10M	Front Face	10	20525	25	25	-	22.50	22.10	0.279	1.10	0.306
LTE 5	QPSK10M	Rear Face	10	20525	25	25	-	22.50	22.10	0.382	1.10	0.419

LTE 7	QPSK20M	Front Face	10	21100	1	99	-	25.70	24.29	0.181	1.38	0.250
LTE 7	QPSK20M	Rear Face	10	21100	1	99	-	25.70	24.29	0.398	1.38	**0.551**
LTE 7	QPSK20M	Front Face	10	21100	50	50	-	24.70	23.90	0.141	1.20	0.170
LTE 7	QPSK20M	Rear Face	10	21100	50	50	-	24.70	23.90	0.283	1.20	0.340
802.11b	-	Front Face	10	6	-	-	-	18.00	17.19	0.202	1.21	**0.243**
802.11b	-	Rear Face	10	6	-	-	-	18.00	17.19	0.199	1.21	0.240

4.5.4 SAR Results for Hotspot Exposure Condition (Separation Distance is 1.0 cm)

Band	Mode	Test Position	Separation Distance (mm)	Ch.	RB	offset	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Measured SAR-1g (W/kg)	Scaling Factor	Scaled SAR-1g (W/kg)
GSM850	GPRS 2TS	Front Face	10	190	-	-	31.50	30.70	0.137	1.20	0.165
GSM850	GPRS 2TS	Rear Face	10	190	-	-	31.50	30.70	0.184	1.20	**0.221**
GSM850	GPRS 2TS	Right Side	10	190	-	-	31.50	30.70	0.113	1.20	0.136
GSM850	GPRS 2TS	Left Side	10	190	-	-	31.50	30.70	0.106	1.20	0.127
GSM850	GPRS 2TS	Bottom Side	10	190	-	-	31.50	30.70	0.021	1.20	0.025
GSM1900	GPRS 3TS	Front Face	10	661	-	-	28.00	27.13	0.110	1.22	0.134
GSM1900	GPRS 3TS	Rear Face	10	661	-	-	28.00	27.13	0.123	1.22	**0.150**
GSM1900	GPRS 3TS	Right Side	10	661	-	-	28.00	27.13	0.016	1.22	0.020
GSM1900	GPRS 3TS	Left Side	10	661	-	-	28.00	27.13	0.034	1.22	0.042
GSM1900	GPRS 3TS	Bottom Side	10	661	-	-	28.00	27.13	0.113	1.22	0.138
WCDMA II	RMC12.2K	Front Face	10	9400	-	-	24.50	23.88	0.740	1.15	0.854
WCDMA II	RMC12.2K	Rear Face	10	9400	-	-	24.50	23.88	1.140	1.15	**1.315**
WCDMA II	RMC12.2K	Rear Face	10	9262	-	-	24.50	23.64	1.070	1.22	1.304
WCDMA II	RMC12.2K	Rear Face	10	9538	-	-	24.50	23.85	1.103	1.16	1.281
WCDMA II	RMC12.2K	Right Side	10	9400	-	-	24.50	23.88	0.126	1.15	0.145
WCDMA II	RMC12.2K	Left Side	10	9400	-	-	24.50	23.88	0.232	1.15	0.268
WCDMA II	RMC12.2K	Bottom Side	10	9400	-	-	24.50	23.88	1.105	1.15	1.275
WCDMA II	RMC12.2K	Bottom Side	10	9262	-	-	24.50	23.64	1.068	1.22	1.302
WCDMA II	RMC12.2K	Bottom Side	10	9538	-	-	24.50	23.85	1.088	1.16	1.264
WCDMA V	RMC12.2K	Front Face	10	4132	-	-	23.50	22.39	0.391	1.29	0.505
WCDMA V	RMC12.2K	Rear Face	10	4132	-	-	23.50	22.39	0.416	1.29	**0.537**
WCDMA V	RMC12.2K	Right Side	10	4132	-	-	23.50	22.39	0.351	1.29	0.453
WCDMA V	RMC12.2K	Left Side	10	4132	-	-	23.50	22.39	0.305	1.29	0.394
WCDMA V	RMC12.2K	Bottom Side	10	4132	-	-	23.50	22.39	0.064	1.29	0.083
LTE 2	QPSK20M	Front Face	10	18900	1	50	25.70	24.40	0.769	1.35	1.037
LTE 2	QPSK20M	Front Face	10	18700	1	50	25.70	24.03	0.658	1.47	0.967
LTE 2	QPSK20M	Front Face	10	19100	1	50	25.70	24.38	0.667	1.36	0.904
LTE 2	QPSK20M	Rear Face	10	18900	1	50	25.70	24.40	1.000	1.35	**1.349**
LTE 2	QPSK20M	Rear Face	10	18900	1	50	25.70	24.40	0.988	1.35	1.333
LTE 2	QPSK20M	Rear Face	10	18700	1	50	25.70	24.03	0.900	1.47	1.322
LTE 2	QPSK20M	Rear Face	10	19100	1	50	25.70	24.38	0.987	1.36	1.338
LTE 2	QPSK20M	Right Side	10	18900	1	50	25.70	24.40	0.132	1.35	0.178
LTE 2	QPSK20M	Left Side	10	18900	1	50	25.70	24.40	0.269	1.35	0.363
LTE 2	QPSK20M	Bottom Side	10	18900	1	50	25.70	24.40	0.990	1.35	1.335
LTE 2	QPSK20M	Bottom Side	10	18700	1	50	25.70	24.03	0.818	1.47	1.202
LTE 2	QPSK20M	Bottom Side	10	19100	1	50	25.70	24.38	0.852	1.36	1.155

LTE 2	QPSK20M	Front Face	10	18900	50	50	24.70	23.95	0.654	1.19	0.777
LTE 2	QPSK20M	Rear Face	10	18900	50	50	24.70	23.95	1.130	1.19	1.343
LTE 2	QPSK20M	Rear Face	10	18700	50	50	24.70	23.70	1.059	1.26	1.333
LTE 2	QPSK20M	Rear Face	10	19100	50	50	24.70	23.93	1.111	1.19	1.327
LTE 2	QPSK20M	Right Side	10	18900	50	50	24.70	23.95	0.106	1.19	0.126
LTE 2	QPSK20M	Left Side	10	18900	50	50	24.70	23.95	0.205	1.19	0.244
LTE 2	QPSK20M	Bottom Side	10	18900	50	50	24.70	23.95	0.915	1.19	1.087
LTE 2	QPSK20M	Bottom Side	10	18700	50	50	24.70	23.70	0.912	1.26	1.148
LTE 2	QPSK20M	Bottom Side	10	19100	50	50	24.70	23.93	0.817	1.19	0.975
LTE 2	QPSK20M	Front Face	10	18900	100	0	24.70	23.88	0.656	1.21	0.792
LTE 2	QPSK20M	Rear Face	10	18900	100	0	24.70	23.88	1.096	1.21	1.324
LTE 2	QPSK20M	Bottom Side	10	18900	100	0	24.70	23.88	0.977	1.21	1.180
LTE 4	QPSK20M	Front Face	10	20175	1	99	23.50	22.96	0.721	1.13	0.816
LTE 4	QPSK20M	Front Face	10	20050	1	99	23.50	22.86	0.965	1.16	1.118
LTE 4	QPSK20M	Front Face	10	20300	1	99	23.50	22.93	0.598	1.14	0.682
LTE 4	QPSK20M	Rear Face	10	20175	1	99	23.50	22.96	0.971	1.13	1.100
LTE 4	QPSK20M	Rear Face	10	20050	1	99	23.50	22.86	1.100	1.16	**1.275**
LTE 4	QPSK20M	Rear Face	10	20050	1	99	23.50	22.86	1.089	1.16	1.262
LTE 4	QPSK20M	Rear Face	10	20300	1	99	23.50	22.93	0.780	1.14	0.889
LTE 4	QPSK20M	Right Side	10	20175	1	99	23.50	22.96	0.125	1.13	0.142
LTE 4	QPSK20M	Left Side	10	20175	1	99	23.50	22.96	0.332	1.13	0.376
LTE 4	QPSK20M	Bottom Side	10	20175	1	99	23.50	22.96	0.786	1.13	0.890
LTE 4	QPSK20M	Bottom Side	10	20050	1	99	23.50	22.86	0.748	1.16	0.867
LTE 4	QPSK20M	Bottom Side	10	20300	1	99	23.50	22.93	0.801	1.14	0.913
LTE 4	QPSK20M	Front Face	10	20175	50	0	22.50	21.96	0.497	1.13	0.563
LTE 4	QPSK20M	Rear Face	10	20175	50	0	22.50	21.96	0.704	1.13	0.797
LTE 4	QPSK20M	Right Side	10	20175	50	0	22.50	21.96	0.119	1.13	0.135
LTE 4	QPSK20M	Left Side	10	20175	50	0	22.50	21.96	0.247	1.13	0.280
LTE 4	QPSK20M	Bottom Side	10	20175	50	0	22.50	21.96	0.621	1.13	0.703
LTE 4	QPSK20M	Front Face	10	20175	100	0	22.50	21.89	0.788	1.13	0.907
LTE 4	QPSK20M	Rear Face	10	20175	100	0	22.50	21.89	1.048	1.13	1.206
LTE 4	QPSK20M	Bottom Side	10	20175	100	0	22.50	21.89	0.646	1.13	0.743
LTE 5	QPSK10M	Front Face	10	20525	1	24	23.50	22.48	0.289	1.26	0.366
LTE 5	QPSK10M	Rear Face	10	20525	1	24	23.50	22.48	0.424	1.26	**0.536**
LTE 5	QPSK10M	Right Side	10	20525	1	24	23.50	22.48	0.245	1.26	0.310
LTE 5	QPSK10M	Left Side	10	20525	1	24	23.50	22.48	0.292	1.26	0.369
LTE 5	QPSK10M	Bottom Side	10	20525	1	24	23.50	22.48	0.065	1.26	0.082
LTE 5	QPSK10M	Front Face	10	20525	25	25	22.50	22.10	0.279	1.10	0.306
LTE 5	QPSK10M	Rear Face	10	20525	25	25	22.50	22.10	0.382	1.10	0.419
LTE 5	QPSK10M	Right Side	10	20525	25	25	22.50	22.10	0.280	1.10	0.307
LTE 5	QPSK10M	Left Side	10	20525	25	25	22.50	22.10	0.235	1.10	0.258
LTE 5	QPSK10M	Bottom Side	10	20525	25	25	22.50	22.10	0.061	1.10	0.067
LTE 7	QPSK20M	Front Face	10	21100	1	99	25.70	24.29	0.181	1.38	0.250
LTE 7	QPSK20M	Rear Face	10	21100	1	99	25.70	24.29	0.398	1.38	0.551
LTE 7	QPSK20M	Right Side	10	21100	1	99	25.70	24.29	0.074	1.38	0.102
LTE 7	QPSK20M	Left Side	10	21100	1	99	25.70	24.29	0.054	1.38	0.075
LTE 7	QPSK20M	Bottom Side	10	21100	1	99	25.70	24.29	0.389	1.38	0.538
LTE 7	QPSK20M	Bottom Side	10	21100	1	99	25.70	24.29	0.483	1.38	**0.668**
LTE 7	QPSK20M	Front Face	10	21100	50	50	24.70	23.90	0.141	1.20	0.170
LTE 7	QPSK20M	Rear Face	10	21100	50	50	24.70	23.90	0.283	1.20	0.340
LTE 7	QPSK20M	Right Side	10	21100	50	50	24.70	23.90	0.046	1.20	0.055
LTE 7	QPSK20M	Left Side	10	21100	50	50	24.70	23.90	0.034	1.20	0.041

LTE 7	QPSK20M	Bottom Side	10	21100	50	50	24.70	23.90	0.330	1.20	0.397
LTE 7	QPSK20M	Bottom Side	10	21100	50	50	24.70	23.90	0.427	1.20	0.513
802.11b	-	Front Face	10	6	-	-	18.00	17.19	0.202	1.21	0.243
802.11b	-	Rear Face	10	6	-	-	18.00	17.19	0.199	1.21	0.240
802.11b	-	Right Side	10	6	-	-	18.00	17.19	0.046	1.21	0.055
802.11b	-	Left Side	10	6	-	-	18.00	17.19	0.238	1.21	0.287
802.11b	-	Top Side	10	6	-	-	18.00	17.19	0.293	1.21	0.353
802.11b	-	Top Side	10	6	-	-	18.00	17.19	0.324	1.21	**0.390**

4.6 Simultaneous Multi-band Transmission Evaluation

4.6.1 Simultaneous Transmission SAR Test Exclusion Considerations

a) Sum of SAR

Simultaneous transmission SAR test exclusion is determined for each operating configuration and exposure condition according to the reported standalone SAR of each applicable simultaneous transmitting antenna. When the sum of SAR_{1g} of all simultaneously transmitting antennas in an operating mode and exposure condition combination is within the SAR limit (SAR_{1g} 1.6 W/kg), the simultaneous transmission SAR is not required. When the sum of SAR_{1g} is greater than the SAR limit (SAR_{1g} 1.6 W/kg), SAR test exclusion is determined by the SPLSR.

b) SAR to Peak Location Separation Ratio

The simultaneous transmitting antennas in each operating mode and exposure condition combination are considered one pair at a time to determine the SPLSR.

$$SPLSR = (SAR_1 + SAR_2)^{1.5}/R_i$$

The ratio is rounded to two decimal digits, and must be ≤ 0.04 for all antenna pairs in the configuration to qualify for 1-g SAR test exclusion. When 10-g SAR applies, the ratio must be ≤ 0.10.

SAR_1 and SAR_2 are the highest reported or estimated SAR values for each antenna in the pair, and R_i is the separation distance in mm between the peak SAR locations for the antenna pair

$$peak\ location\ separation\ distance = \sqrt{(x_1 - x_2)^2 + (y_1 - y_2)^2 + (z_1 - z_2)^2}$$

Where $(x_1,\ y_1,\ z_1)$ and $(x_2,\ y_2,\ z_2)$ are the coordinates of the extrapolated peak SAR locations in the area or zoom scans.

When standalone test exclusion applies, SAR is estimated; the peak location is assumed to be at the feed-point or geometric center of the antenna. Due to curvatures on the SAM phantom, when SAR is estimated for one of the antennas in an antenna pair, the measured peak SAR location will be translated onto the test device to determine the peak location separation for the antenna pair.

When SAR is estimated for both antennas, the peak location separation should be determined by the closest physical separation of the antennas, according to the feed-point or geometric center of the antennas.

c) Volume Scan

When the SPLSR is <= 0.04 for 1-g SAR and <= 0.10 for 10-g SAR, the simultaneous transmission SAR is not required. Otherwise, the enlarged zoom scan and volume scan post-processing procedures will be performed.

4.6.2 Simultaneous Transmission Possibilities

The simultaneous transmission possibilities for this device are listed as below.

Simultaneous Transmission Configurations	Head (Voice / VoIP)	Body-worn (Voice / VoIP)	Hotspot (Data)
GSM (Voice / Data) + WLAN	Yes	Yes	Yes
WCDMA (Voice / Data) + WLAN	Yes	Yes	Yes
LTE (Data) + WLAN	Yes	Yes	Yes
GSM (Voice / Data) + BT	Yes	Yes	No
WCDMA (Voice / Data) + BT	Yes	Yes	No
LTE (Data) + BT	Yes	Yes	No

Note:

1. The WLAN and Bluetooth cannot transmit simultaneously, so there is no co-location test requirement for WLAN and Bluetooth.
2. Both GSM/WCDMA and LTE can transmit through WWAN antenna. However, only one technology (GSM/WCDMA or LTE) can transmit from an antenna at a time.

4.6.3 Max. Standalone SAR

Position		GSM		WCDMA		LTE				WLAN	BT
		850	1900	II	V	2	4	5	7	2.4G	2.4G
Head	Right Cheek	0.601	0.095	0.158	0.271	0.170	0.207	0.359	0.059	0.941	0.120
	Right Tilted	0.597	0.088	0.138	0.218	0.097	0.085	0.305	0.029	0.758	0.120
	Left Cheek	0.477	0.236	0.260	0.258	0.295	0.392	0.221	0.043	0.660	0.120
	Left Tilted	0.424	0.052	0.116	0.195	0.103	0.139	0.158	0.015	0.392	0.120
Body-worn	Front Face	0.165	0.134	0.854	0.505	1.037	1.118	0.366	0.250	0.243	0.060
	Rear Face	0.221	0.150	1.315	0.537	1.349	1.275	0.536	0.551	0.240	0.060
Hotspot	Front Face	0.165	0.134	0.854	0.505	1.037	1.118	0.366	0.250	0.243	N/A
	Rear Face	0.221	0.150	1.315	0.537	1.349	1.275	0.536	0.551	0.240	N/A
	Right Side	0.136	0.020	0.145	0.453	0.178	0.142	0.536	0.102	0.055	N/A
	Left Side	0.127	0.042	0.268	0.394	0.363	0.376	0.310	0.075	0.287	N/A
	Top Side	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	0.390	N/A
	Bottom Side	0.025	0.138	1.302	0.083	1.335	0.913	0.082	0.668	0.000	N/A

4.6.4 Sum of SAR

WWAN + WLAN (DTS)

Position		Highest Simultaneous Transmission SAR	GSM		WCDMA		LTE			
			850	1900	II	V	2	4	5	7
Head	Right Cheek	1.542	**1.542**	1.036	1.099	1.212	1.111	1.148	1.300	1.000
	Right Tilted		1.355	0.846	0.896	0.976	0.855	0.843	1.063	0.787
	Left Cheek		1.138	0.896	0.920	0.919	0.956	1.052	0.882	0.703
	Left Tilted		0.816	0.443	0.508	0.587	0.494	0.531	0.550	0.407
Body-worn	Front Face	1.589	0.408	0.378	1.097	0.748	1.281	1.362	0.609	0.494
	Rear Face		0.461	0.390	1.555	0.777	**1.589**	1.514	0.776	0.790
Hotspot	Front Face	1.589	0.408	0.378	1.097	0.748	1.281	1.362	0.609	0.494
	Rear Face		0.461	0.390	1.555	0.777	**1.589**	1.514	0.776	0.790
	Left Side		0.191	0.075	0.201	0.509	0.233	0.197	0.592	0.158
	Right Side		0.414	0.328	0.554	0.681	0.650	0.663	0.597	0.362
	Top Side		0.390	0.390	0.390	0.390	0.390	0.390	0.390	0.390
	Bottom Side		0.025	0.138	1.302	0.083	1.335	0.913	0.082	0.668

WWAN + BT(DSS)

Position		Highest Simultaneous Transmission SAR	GSM		WCDMA		LTE			
			850	1900	II	V	2	4	5	7
Head	Right Cheek	0.721	0.721	0.215	0.278	0.391	0.290	0.327	0.479	0.179
	Right Tilted		0.717	0.208	0.258	0.338	0.217	0.205	0.425	0.149
	Left Cheek		0.597	0.356	0.380	0.378	0.415	0.512	0.341	0.163
	Left Tilted		0.544	0.172	0.236	0.315	0.223	0.259	0.278	0.135
Body-worn	Front Face	1.409	0.225	0.194	0.914	0.565	1.097	1.178	0.426	0.310
	Rear Face		0.281	0.210	1.375	0.597	1.409	1.335	0.596	0.611
Hotspot	Front Face	1.349	0.165	0.134	0.854	0.505	1.037	1.118	0.366	0.250
	Rear Face		0.221	0.150	1.315	0.537	1.349	1.275	0.536	0.551
	Left Side		0.136	0.020	0.145	0.453	0.178	0.142	0.536	0.102
	Right Side		0.127	0.042	0.268	0.394	0.363	0.376	0.310	0.075
	Top Side		0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
	Bottom Side		0.025	0.138	1.302	0.083	1.335	0.913	0.082	0.668

*** End of Report ***

The test report is effective only with both signature and specialized stamp. The result(s) shown in this report refer only to the sample(s) tested. Without written approval of UnionTrust, this report can't be reproduced except in full.

Appendix A. SAR Plots of System Verification

The plots for system verification with largest deviation for each SAR system combination are shown as follows.

Appendix B. SAR Plots of SAR Measurement

The SAR plots for highest measured SAR in each exposure configuration, wireless mode and frequency band combination, and measured SAR > 1.5 W/kg are shown as follows.

Appendix C. Calibration Certificate for Probe and Dipole

The calibration certificates are shown as follows.

Appendix D. Photographs of EUT and Setup