




FCC PART 27  
FCC PART 22H, PART 24E  
TEST REPORT

For

**BLU Products, Inc.**

10814 NW 33rd St # 100 Doral, FL 33172, United States

**FCC ID: YHLBLUADVANCE5**

|                                                                                                                                                                                                                                                                                                                             |                                     |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------|
| <b>Report Type:</b><br>Original Report                                                                                                                                                                                                                                                                                      | <b>Product Type:</b><br>Smart Phone |
| <b>Report Number:</b> RSZ190531001-00A                                                                                                                                                                                                                                                                                      |                                     |
| <b>Report Date:</b> 2019-06-20                                                                                                                                                                                                                                                                                              |                                     |
| Candy Li                                                                                                                                                                                                                                |                                     |
| <b>Reviewed By:</b> RF Engineer                                                                                                                                                                                                                                                                                             |                                     |
| <b>Prepared By:</b> Bay Area Compliance Laboratories Corp. (Shenzhen)<br>6/F., West Wing, Third Phase of Wanli Industrial<br>Building, Shihua Road, Futian Free Trade Zone,<br>Shenzhen, Guangdong, China<br>Tel: +86-755-33320018<br>Fax: +86-755-33320008<br><a href="http://www.baclcorp.com.cn">www.baclcorp.com.cn</a> |                                     |

**Note:** This report must not be used by the customer to claim product certification, approval, or endorsement by A2LA\* or any agency of the Federal Government. \* This report may contain data that are not covered by the A2LA accreditation and are marked with an asterisk “\*”.

The information marked # is provided by the applicant, the laboratory is not responsible for its authenticity.

## **TABLE OF CONTENTS**

|                                                                                                                     |           |
|---------------------------------------------------------------------------------------------------------------------|-----------|
| <b>GENERAL INFORMATION.....</b>                                                                                     | <b>3</b>  |
| PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) .....                                                            | 3         |
| OBJECTIVE .....                                                                                                     | 3         |
| RELATED SUBMITTAL(S)/GRANT(S).....                                                                                  | 3         |
| TEST METHODOLOGY .....                                                                                              | 4         |
| MEASUREMENT UNCERTAINTY .....                                                                                       | 4         |
| TEST FACILITY .....                                                                                                 | 4         |
| <b>SYSTEM TEST CONFIGURATION .....</b>                                                                              | <b>5</b>  |
| DESCRIPTION OF TEST CONFIGURATION .....                                                                             | 5         |
| EQUIPMENT MODIFICATIONS .....                                                                                       | 5         |
| SUPPORT EQUIPMENT LIST AND DETAILS .....                                                                            | 5         |
| BLOCK DIAGRAM OF TEST SETUP .....                                                                                   | 5         |
| <b>SUMMARY OF TEST RESULTS .....</b>                                                                                | <b>6</b>  |
| <b>TEST EQUIPMENT LIST .....</b>                                                                                    | <b>7</b>  |
| <b>FCC §1.1307(B) &amp; §2.1093 - RF EXPOSURE INFORMATION.....</b>                                                  | <b>9</b>  |
| APPLICABLE STANDARD .....                                                                                           | 9         |
| TEST RESULT .....                                                                                                   | 9         |
| <b>FCC §2.1047 - MODULATION CHARACTERISTIC .....</b>                                                                | <b>10</b> |
| <b>FCC § 2.1046, § 22.913 (A) &amp; § 24.232 (C); §27.50 (D) (H) - RF OUTPUT POWER .....</b>                        | <b>11</b> |
| APPLICABLE STANDARD .....                                                                                           | 11        |
| TEST PROCEDURE .....                                                                                                | 11        |
| TEST DATA .....                                                                                                     | 11        |
| <b>FCC §2.1049, §22.917, §22.905 &amp; §24.238 &amp; §27.53 - OCCUPIED BANDWIDTH .....</b>                          | <b>17</b> |
| APPLICABLE STANDARD .....                                                                                           | 17        |
| TEST PROCEDURE .....                                                                                                | 17        |
| TEST DATA .....                                                                                                     | 17        |
| <b>FCC §2.1051, §22.917(A) &amp; §24.238(A); §27.53 (H) (M) - SPURIOUS EMISSIONS AT ANTENNA<br/>TERMINALS .....</b> | <b>25</b> |
| APPLICABLE STANDARD .....                                                                                           | 25        |
| TEST PROCEDURE .....                                                                                                | 25        |
| TEST DATA .....                                                                                                     | 25        |
| <b>FCC § 2.1053; § 22.917 (A);§ 24.238 (A); §27.53 (H)(M) SPURIOUS RADIATED EMISSIONS.....</b>                      | <b>33</b> |
| APPLICABLE STANDARD .....                                                                                           | 33        |
| TEST PROCEDURE .....                                                                                                | 33        |
| TEST DATA .....                                                                                                     | 33        |
| <b>FCC § 22.917 (A);§ 24.238 (A); §27.53 (H)(M) - BAND EDGES .....</b>                                              | <b>36</b> |
| APPLICABLE STANDARD .....                                                                                           | 36        |
| TEST PROCEDURE .....                                                                                                | 36        |
| TEST DATA .....                                                                                                     | 36        |
| <b>FCC § 2.1055; § 22.355; § 24.235; §27.54 - FREQUENCY STABILITY .....</b>                                         | <b>48</b> |
| APPLICABLE STANDARD .....                                                                                           | 48        |
| TEST PROCEDURE .....                                                                                                | 48        |
| TEST DATA .....                                                                                                     | 49        |

## GENERAL INFORMATION

### Product Description for Equipment under Test (EUT)

|                                     |                                                                                                                            |
|-------------------------------------|----------------------------------------------------------------------------------------------------------------------------|
| Product                             | Mobile Phone                                                                                                               |
| Model                               | ADVANCE L5                                                                                                                 |
| Frequency Range                     | Cellular: 824-849 MHz<br>PCS: 1850-1910 MHz<br>WCDMA B2: 1850-1910 MHz<br>WCDMA B4: 1710-1755 MHz<br>WCDMA B5: 824-849 MHz |
| Transmit Power<br>(Conducted Power) | Cellular: 32.67dBm<br>PCS: 29.95dBm<br>WCDMA B2: 22.54dBm<br>WCDMA B4: 22.87dBm<br>WCDMA B5: 22.52dBm                      |
| Modulation<br>Technique             | 2G: GMSK<br>3G: BPSK, QPSK, 16QAM                                                                                          |
| Antenna Specification               | PIFA Antennas                                                                                                              |
| Voltage Range                       | DC 3.7V battery or DC 5.0V by adapter                                                                                      |
| Date of Test                        | 2019-06-02 to 2019-06-19                                                                                                   |
| Sample serial number                | 190531001                                                                                                                  |
| Received date                       | 2019-05-31                                                                                                                 |
| Sample/EUT Status                   | Good condition                                                                                                             |
| Adapter information                 | Model: US-WW-0501<br>Input: AC 100-240V, 50/60Hz, 0.15A<br>Output: DC 5V, 500mA                                            |

### Objective

This test report is prepared on behalf of *BLU Products, Inc.* in accordance with Part 2-Subpart J, Part 22-Subpart H and Part 24-Subpart E and Subpart 27 of the Federal Communication Commissions rules.

The objective is to determine the compliance of the EUT with FCC rules for output power, modulation characteristic, occupied bandwidth, and spurious emission at antenna terminal, spurious radiated emission, frequency stability and band edge.

### Related Submittal(s)/Grant(s)

FCC Part 15.247 DSS, Part 15.247 DTS and Part 15B JBP submissions with  
FCC ID: YHLBLUADVANCEL5.

## Test Methodology

All tests and measurements indicated in this document were performed in accordance with the Code of Federal Regulations Title 47 Part 2-Subpart J as well as the following parts:

Part 22 Subpart H - Public Mobile Services  
Part 24 Subpart E - Personal Communication Services  
Part 27 – Miscellaneous wireless communications services

Applicable Standards: TIA/EIA 603-D.

All emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

## Measurement Uncertainty

| Parameter                    |            | Uncertainty |
|------------------------------|------------|-------------|
| Occupied Channel Bandwidth   |            | ±5%         |
| RF output power, conducted   |            | ±0.73dB     |
| Unwanted Emission, conducted |            | ±1.6dB      |
| Emissions,<br>Radiated       | Below 1GHz | ±4.75dB     |
|                              | Above 1GHz | ±4.88dB     |
| Temperature                  |            | ±1°C        |
| Humidity                     |            | ±6%         |
| Supply voltages              |            | ±0.4%       |

*Note: Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.*

## Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 6/F., West Wing, Third Phase of Wanli Industrial Building, Shihua Road, Futian Free Trade Zone, Shenzhen, Guangdong, China.

The test site has been approved by the FCC under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No.: 342867, the FCC Designation No.: CN1221.

The test site has been registered with ISED Canada under ISED Canada Registration Number 3062B.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The EUT was configured for testing according to TIA/EIA-603-D.  
The final qualification test was performed with the EUT operating at normal mode.


Equipment Modifications

No modification was made to the EUT.

Support Equipment List and Details

| Manufacturer    | Description                          | Model  | Serial Number |
|-----------------|--------------------------------------|--------|---------------|
| Rohde & Schwarz | Universal Radio Communication Tester | CMU200 | 110605        |

Block Diagram of Test Setup



**SUMMARY OF TEST RESULTS**

| FCC Rules                                              | Description of Test                    | Result         |
|--------------------------------------------------------|----------------------------------------|----------------|
| § 1.1307 , §2.1093                                     | RF Exposure (SAR)                      | Compliance*    |
| §2.1046; § 22.913 (a);<br>§ 24.232 (c); §27.50 (d) (h) | RF Output Power                        | Compliance     |
| § 2.1047                                               | Modulation Characteristics             | Not Applicable |
| § 2.1049; § 22.905;<br>§ 22.917; § 24.238; §27.53      | Occupied Bandwidth                     | Compliance     |
| § 2.1051; § 22.917 (a);<br>§ 24.238 (a); §27.53 (h)(m) | Spurious Emissions at Antenna Terminal | Compliance     |
| § 2.1053; § 22.917 (a);<br>§ 24.238 (a); §27.53 (h)(m) | Field Strength of Spurious Radiation   | Compliance     |
| § 22.917 (a);<br>§ 24.238 (a); §27.53 (h)(m)           | Band Edge                              | Compliance     |
| § 2.1055; § 22.355;<br>§ 24.235; §27.54;               | Frequency stability                    | Compliance     |

Note: \* Please refer to SAR report released by BACL, report number: RSZ190531001-20A.

**TEST EQUIPMENT LIST**

| Manufacturer                  | Description        | Model                          | Serial Number          | Calibration Date | Calibration Due Date |
|-------------------------------|--------------------|--------------------------------|------------------------|------------------|----------------------|
| <b>Radiated Emission Test</b> |                    |                                |                        |                  |                      |
| Sunol Sciences                | Horn Antenna       | DRH-118                        | A052604                | 2017-12-22       | 2020-12-21           |
| Rohde & Schwarz               | Signal Analyzer    | FSEM                           | 845987/005             | 2018-06-23       | 2019-06-23           |
| Sunol Sciences                | Broadband Antenna  | JB1                            | A040904-1              | 2017-12-22       | 2020-12-21           |
| COM-POWER                     | Pre-amplifier      | PA-122                         | 181919                 | 2018-11-12       | 2019-11-12           |
| Sonoma Instrument             | Amplifier          | 310N                           | 186238                 | 2018-11-12       | 2019-11-12           |
| Agilent                       | Signal Generator   | N5183A                         | MY51040755             | 2018-12-03       | 2019-12-03           |
| Rohde & Schwarz               | EMI Test Receiver  | ESR                            | 1316.3003K03-101746-zn | 2018-07-11       | 2019-07-11           |
| COM-POWER                     | Dipole Antenna     | AD-100                         | 41000                  | NCR              | NCR                  |
| A.H. System                   | Horn Antenna       | SAS-200/571                    | 135                    | 2018-09-01       | 2021-08-31           |
| UTiFLEX MICRO-C0AX            | RF Cable           | UFA147A-2362-100100            | MFR64639 231029-003    | 2018-11-12       | 2019-11-12           |
| Ducommun Technologies         | RF Cable           | 104PEA                         | 218124002              | 2018-11-12       | 2019-11-12           |
| Ducommun technologies         | RF Cable           | RG-214                         | 1                      | 2018-11-19       | 2019-11-19           |
| Ducommun technologies         | RF Cable           | RG-214                         | 2                      | 2018-11-12       | 2019-11-12           |
| Ducommun Technologies         | Horn Antenna       | ARH-4223-02                    | 1007726-04             | 2017-12-29       | 2020-12-28           |
| Ducommun technologies         | Horn Antenna       | ARH-4223-02                    | 1007726-03             | 2017-12-29       | 2020-12-28           |
| Heatsink Required             | Amplifier          | QLW-18405536-J0                | 15964001002            | 2018-11-12       | 2019-11-12           |
| Wainwright Germany            | Band Reject Filter | WRCG1850/1910-1835/1925-40/8SS | 22                     | 2019-03-02       | 2020-03-01           |
| Wainwright Germany            | Band Reject Filter | WRCG823/850-813/860-40/8SS     | 7                      | 2019-03-02       | 2020-03-01           |

| Manufacturer             | Description                          | Model     | Serial Number | Calibration Date | Calibration Due Date |
|--------------------------|--------------------------------------|-----------|---------------|------------------|----------------------|
| <b>RF Conducted Test</b> |                                      |           |               |                  |                      |
| Rohde & Schwarz          | Spectrum Analyzer                    | FSU26     | 200120        | 2019-03-02       | 2020-03-01           |
| Fluke                    | Digital Multimeter                   | 287       | 19000011      | 2019-04-12       | 2020-04-12           |
| ESPEC                    | Temperature & Humidity Chamber       | EL-10KA   | 9107726       | 2019-01-05       | 2020-01-05           |
| Long Wei                 | DC Power Supply                      | TPR-6420D | 398363        | NCR              | NCR                  |
| Rohde & Schwarz          | Universal Radio Communication Tester | CMU200    | 106891        | 2019-01-15       | 2020-01-15           |
| Ducommun Technologies    | RF Cable                             | RG-214    | 3             | Each Time        |                      |
| WEINSCHEL                | 10dB Attenuator                      | 5324      | AU 3842       | Each Time        |                      |
| WEINSCHEL                | 3dB Attenuator                       | 6231      | 666           | Each Time        |                      |
| Unknown                  | Power Splitter                       | 1620      | 129           | Each Time        |                      |

\* Statement of Traceability: Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

---

## **FCC §1.1307(b) & §2.1093 - RF EXPOSURE INFORMATION**

---

### **Applicable Standard**

FCC§1.1310 and §2.1093.

### **Test Result**

Compliance, please refer to the SAR report: RSZ190531001-20A.

## **FCC §2.1047 - MODULATION CHARACTERISTIC**

---

According to FCC § 2.1047(d), Part 22H & 24E & 27 there is no specific requirement for digital modulation, therefore modulation characteristic is not presented.

## FCC § 2.1046, § 22.913 (a) & § 24.232 (c); §27.50 (d) (h) - RF OUTPUT POWER

### Applicable Standard

According to FCC §2.1046 and §22.913 (a), the ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 watts.

According to FCC §2.1046 and §24.232 (C), mobile and portable stations are limited to 2 watts EIRP and the equipment must employ a means for limiting power to the minimum necessary for successful communications.


The peak-to-average power ratio (PAPR) of the transmitter output power must not exceed 13 dB.

According to §27.50(d), the maximum EIRP must not exceed 1Watts (30dBm) for 1710-1755MHz.

### Test Procedure

*Conducted method:*

The RF output of the transmitter was connected to the CMU200 through sufficient attenuation.



*Radiated method:*

TIA 603-D section 2.2.17

### Test Data

#### Environmental Conditions

|                    |           |
|--------------------|-----------|
| Temperature:       | 25 °C     |
| Relative Humidity: | 50 %      |
| ATM Pressure:      | 101.0 kPa |

*The testing was performed by George Zhong on 2019-06-09.*

**Conducted Power****Cellular Band (Part 22H)**

| Mode | Channel | Frequency (MHz) | Average Output Power (dBm) | Limit (dBm) |
|------|---------|-----------------|----------------------------|-------------|
| GSM  | 128     | 824.2           | 31.97                      | 38.45       |
|      | 190     | 836.6           | 31.84                      | 38.45       |
|      | 251     | 848.8           | 31.81                      | 38.45       |

| Mode | Channel | Frequency (MHz) | Average Output Power (dBm) |         |         |         | Limit (dBm) |
|------|---------|-----------------|----------------------------|---------|---------|---------|-------------|
|      |         |                 | 1 slot                     | 2 slots | 3 slots | 4 slots |             |
| GPRS | 128     | 824.2           | 31.64                      | 30.11   | 28.43   | 25.78   | 38.45       |
|      | 190     | 836.6           | 31.63                      | 30.02   | 28.47   | 26.33   | 38.45       |
|      | 251     | 848.8           | 32.67                      | 30.04   | 28.73   | 26.95   | 38.45       |

| Mode           | Test Condition | Test Mode | 3GPP Sub Test | Average Output Power (dBm) |                  |                |
|----------------|----------------|-----------|---------------|----------------------------|------------------|----------------|
|                |                |           |               | Low Frequency              | Middle Frequency | High Frequency |
| WCDMA (Band V) | Normal         | RMC12.2k  |               | 22.52                      | 22.46            | 22.49          |
|                |                | HSDPA     | 1             | 21.28                      | 21.17            | 21.05          |
|                |                |           | 2             | 21.39                      | 21.10            | 21.20          |
|                |                |           | 3             | 21.25                      | 21.16            | 21.12          |
|                |                |           | 4             | 21.27                      | 21.19            | 21.23          |
|                |                | HSUPA     | 1             | 21.42                      | 21.75            | 21.16          |
|                |                |           | 2             | 21.40                      | 21.28            | 21.12          |
|                |                |           | 3             | 21.31                      | 21.32            | 21.10          |
|                |                |           | 4             | 21.28                      | 21.34            | 21.05          |
|                |                |           | 5             | 21.35                      | 21.30            | 21.11          |

**PCS Band (Part 24E)**

| Mode | Channel | Frequency (MHz) | Average Output Power (dBm) | Limit (dBm) |
|------|---------|-----------------|----------------------------|-------------|
| GSM  | 512     | 1850.2          | 28.49                      | 33          |
|      | 661     | 1880.0          | 28.61                      | 33          |
|      | 810     | 1909.8          | 28.63                      | 33          |

| Mode | Channel | Frequency (MHz) | Average Output Power (dBm) |         |         |         | Limit (dBm) |
|------|---------|-----------------|----------------------------|---------|---------|---------|-------------|
|      |         |                 | 1 slot                     | 2 slots | 3 slots | 4 slots |             |
| GPRS | 512     | 1850.2          | 29.76                      | 27.18   | 26.58   | 24.44   | 33          |
|      | 661     | 1880.0          | 29.82                      | 27.46   | 26.51   | 24.53   | 33          |
|      | 810     | 1909.8          | 29.95                      | 27.81   | 26.68   | 24.74   | 33          |

| Mode            | Test Condition | Test Mode | 3GPP Sub Test | Average Output Power (dBm) |                  |                |
|-----------------|----------------|-----------|---------------|----------------------------|------------------|----------------|
|                 |                |           |               | Low Frequency              | Middle Frequency | High Frequency |
| WCDMA (Band II) | Normal         | RMC12.2k  |               | 22.47                      | 22.43            | 22.54          |
|                 |                | HSDPA     | 1             | 21.54                      | 21.72            | 21.48          |
|                 |                |           | 2             | 21.53                      | 21.75            | 21.41          |
|                 |                |           | 3             | 21.36                      | 21.83            | 21.45          |
|                 |                |           | 4             | 21.63                      | 21.85            | 21.52          |
|                 |                | HSUPA     | 1             | 21.17                      | 21.10            | 21.18          |
|                 |                |           | 2             | 21.21                      | 21.36            | 21.19          |
|                 |                |           | 3             | 21.24                      | 21.41            | 21.22          |
|                 |                |           | 4             | 21.34                      | 21.44            | 21.30          |
|                 |                |           | 5             | 21.37                      | 21.50            | 21.34          |

**AWS Band (Part 27)**

| Mode            | Test Condition | Test Mode | 3GPP Sub Test | Average Output Power (dBm) |                  |                |
|-----------------|----------------|-----------|---------------|----------------------------|------------------|----------------|
|                 |                |           |               | Low Frequency              | Middle Frequency | High Frequency |
| WCDMA (Band IV) | Normal         | RMC12.2k  |               | 22.37                      | 22.87            | 22.49          |
|                 |                | HSDPA     | 1             | 21.32                      | 21.02            | 21.28          |
|                 |                |           | 2             | 21.37                      | 21.07            | 21.11          |
|                 |                |           | 3             | 21.43                      | 21.10            | 21.14          |
|                 |                |           | 4             | 21.27                      | 21.64            | 21.20          |
|                 |                | HSUPA     | 1             | 21.86                      | 21.50            | 21.03          |
|                 |                |           | 2             | 21.46                      | 21.20            | 21.06          |
|                 |                |           | 3             | 21.53                      | 21.23            | 21.11          |
|                 |                |           | 4             | 21.59                      | 21.30            | 21.14          |
|                 |                |           | 5             | 21.65                      | 21.37            | 21.16          |

**Peak-to-average ratio (PAR)****Cellular Band**

| Mode | Channel | PAR (dB) | Limit (dB) |
|------|---------|----------|------------|
| GSM  | Low     | 1.21     | 13         |
|      | Middle  | 1.04     | 13         |
|      | High    | 1.14     | 13         |

| Mode          | Channel | PAR (dB) | Limit (dB) |
|---------------|---------|----------|------------|
| RMC (BPSK)    | Low     | 2.81     | 13         |
|               | Middle  | 2.86     | 13         |
|               | High    | 2.73     | 13         |
| HSDPA (16QAM) | Low     | 3.01     | 13         |
|               | Middle  | 3.04     | 13         |
|               | High    | 3.04     | 13         |
| HSUPA (BPSK)  | Low     | 2.94     | 13         |
|               | Middle  | 2.89     | 13         |
|               | High    | 2.98     | 13         |

**PCS Band**

| Mode | Channel | PAR (dB) | Limit (dB) |
|------|---------|----------|------------|
| GSM  | Low     | 1.32     | 13         |
|      | Middle  | 1.28     | 13         |
|      | High    | 1.22     | 13         |

| Mode          | Channel | PAR (dB) | Limit (dB) |
|---------------|---------|----------|------------|
| RMC (BPSK)    | Low     | 2.43     | 13         |
|               | Middle  | 2.47     | 13         |
|               | High    | 2.46     | 13         |
| HSDPA (16QAM) | Low     | 2.76     | 13         |
|               | Middle  | 2.68     | 13         |
|               | High    | 2.82     | 13         |
| HSUPA (BPSK)  | Low     | 2.76     | 13         |
|               | Middle  | 2.91     | 13         |
|               | High    | 2.86     | 13         |

**AWS Band**

| Mode          | Channel | PAR (dB) | Limit (dB) |
|---------------|---------|----------|------------|
| RMC (BPSK)    | Low     | 3.14     | 13         |
|               | Middle  | 3.02     | 13         |
|               | High    | 3.10     | 13         |
| HSDPA (16QAM) | Low     | 3.03     | 13         |
|               | Middle  | 3.10     | 13         |
|               | High    | 3.13     | 13         |
| HSUPA (BPSK)  | Low     | 3.01     | 13         |
|               | Middle  | 3.05     | 13         |
|               | High    | 3.11     | 13         |

**Radiated Power  
GSM Mode:**

| Frequency<br>(MHz)                               | Receiver<br>Reading<br>(dBμV) | Turntable<br>Angle<br>Degree | Rx Antenna    |                | Substituted    |                       |                              | Absolute<br>Level<br>(dBm) | Limit<br>(dBm) | Margin<br>(dB) |
|--------------------------------------------------|-------------------------------|------------------------------|---------------|----------------|----------------|-----------------------|------------------------------|----------------------------|----------------|----------------|
|                                                  |                               |                              | Height<br>(m) | Polar<br>(H/V) | Level<br>(dBm) | Cable<br>loss<br>(dB) | Antenna<br>Gain<br>(dBd/dBi) |                            |                |                |
| ERP for Cellular Band (Part 22H), Middle Channel |                               |                              |               |                |                |                       |                              |                            |                |                |
| 836.6                                            | 87.71                         | 124                          | 1.9           | H              | 28.3           | 1.35                  | 0                            | 26.95                      | 38.45          | 11.50          |
| 836.6                                            | 86.68                         | 139                          | 1.4           | V              | 26.7           | 1.35                  | 0                            | 25.35                      | 38.45          | 13.10          |
| EIRP for PCS Band (Part 24E), Middle Channel     |                               |                              |               |                |                |                       |                              |                            |                |                |
| 1880.0                                           | 91.72                         | 291                          | 1.1           | H              | 22.0           | 1.30                  | 9.40                         | 30.10                      | 33             | 2.90           |
| 1880.0                                           | 89.89                         | 158                          | 1.7           | V              | 20.0           | 1.30                  | 9.40                         | 28.10                      | 33             | 4.90           |

**WCDMA Mode:**

| Frequency<br>(MHz)                                | Receiver<br>Reading<br>(dBμV) | Turntable<br>Angle<br>Degree | Rx Antenna    |                | Substituted    |                       |                              | Absolute<br>Level<br>(dBm) | Limit<br>(dBm) | Margin<br>(dB) |
|---------------------------------------------------|-------------------------------|------------------------------|---------------|----------------|----------------|-----------------------|------------------------------|----------------------------|----------------|----------------|
|                                                   |                               |                              | Height<br>(m) | Polar<br>(H/V) | Level<br>(dBm) | Cable<br>loss<br>(dB) | Antenna<br>Gain<br>(dBd/dBi) |                            |                |                |
| ERP for WCDMA Band V (Part 22H), Middle Channel   |                               |                              |               |                |                |                       |                              |                            |                |                |
| 836.6                                             | 78.87                         | 133                          | 1.5           | H              | 19.5           | 1.35                  | 0                            | 18.15                      | 38.45          | 20.30          |
| 836.6                                             | 77.69                         | 285                          | 1.6           | V              | 17.7           | 1.35                  | 0                            | 16.35                      | 38.45          | 22.10          |
| EIRP for WCDMA Band II (Part 24E), Middle Channel |                               |                              |               |                |                |                       |                              |                            |                |                |
| 1880.0                                            | 85.05                         | 315                          | 1.6           | H              | 15.4           | 1.30                  | 9.40                         | 23.50                      | 33             | 9.50           |
| 1880.0                                            | 83.12                         | 350                          | 1.4           | V              | 13.2           | 1.30                  | 9.40                         | 21.30                      | 33             | 11.70          |
| EIRP for WCDMA Band IV (Part 27), Middle Channel  |                               |                              |               |                |                |                       |                              |                            |                |                |
| 1732.6                                            | 87.95                         | 200                          | 1.2           | H              | 14.6           | 1.30                  | 8.90                         | 22.20                      | 30             | 7.80           |
| 1732.6                                            | 86.40                         | 258                          | 1.8           | V              | 13.7           | 1.30                  | 8.90                         | 21.30                      | 30             | 8.70           |

**Note:**

All above data were tested with no amplifier.

Absolute Level = Substituted Level - Cable loss + Antenna Gain

Margin = Limit - Absolute Level

dBd is for the ERP, dBi is for EIRP.

## FCC §2.1049, §22.917, §22.905 & §24.238 & §27.53 - OCCUPIED BANDWIDTH


### Applicable Standard

FCC 47 §2.1049, §22.917, §22.905, §24.238 and §27.53.

### Test Procedure

The RF output of the transmitter was connected to the simulator and the spectrum analyzer through sufficient attenuation.

The resolution bandwidth of the spectrum analyzer was set at 1% to 5% of the anticipated emission bandwidth and the 26 dB & 99% bandwidth was recorded.



### Test Data

#### Environmental Conditions

|                    |           |
|--------------------|-----------|
| Temperature:       | 25 °C     |
| Relative Humidity: | 50 %      |
| ATM Pressure:      | 101.0 kPa |

*The testing was performed by George Zhong on 2019-06-09.*

*EUT operation mode: Transmitting*

Test Result: Compliance. Please refer to the following tables and plots.

### Cellular Band (Part 22H)

| Mode      | Frequency (MHz) | 99% Occupied Bandwidth (kHz) | 26 dB Emission Bandwidth (kHz) |
|-----------|-----------------|------------------------------|--------------------------------|
| GSM(GMSK) | 836.6           | 244.00                       | 312.82                         |

| Mode          | Frequency (MHz) | 99% Occupied Bandwidth (MHz) | 26 dB Emission Bandwidth (MHz) |
|---------------|-----------------|------------------------------|--------------------------------|
| RMC (BPSK)    | 836.6           | 4.16                         | 4.71                           |
| HSUPA (BPSK)  | 836.6           | 4.16                         | 4.69                           |
| HSDPA (16QAM) | 836.6           | 4.16                         | 4.66                           |

### PCS Band (Part 24E)

| Mode      | Frequency (MHz) | 99% Occupied Bandwidth (kHz) | 26 dB Emission Bandwidth (kHz) |
|-----------|-----------------|------------------------------|--------------------------------|
| GSM(GMSK) | 1880.0          | 246.00                       | 319.23                         |


| Mode          | Frequency (MHz) | 99% Occupied Bandwidth (MHz) | 26 dB Emission Bandwidth (MHz) |
|---------------|-----------------|------------------------------|--------------------------------|
| RMC (BPSK)    | 1880.0          | 4.16                         | 4.71                           |
| HSUPA (BPSK)  | 1880.0          | 4.16                         | 4.66                           |
| HSDPA (16QAM) | 1880.0          | 4.14                         | 4.66                           |

### AWS Band (Part 27)

| Mode          | Frequency (MHz) | 99% Occupied Bandwidth (MHz) | 26 dB Emission Bandwidth (MHz) |
|---------------|-----------------|------------------------------|--------------------------------|
| RMC (BPSK)    | 1732.6          | 4.16                         | 4.71                           |
| HSUPA (BPSK)  | 1732.6          | 4.14                         | 4.67                           |
| HSDPA (16QAM) | 1732.6          | 4.16                         | 4.67                           |


## Cellular Band (Part 22H)

## 26 dB Emissions &amp; 99% Occupied Bandwidth for GSM (GMSK) Mode




Date: 9.JUN.2019 13:58:31

## 26 dB Emissions &amp; 99% Occupied Bandwidth for RMC (BPSK) Mode




Date: 9.JUN.2019 16:25:17

### 26 dB Emissions & 99% Occupied Bandwidth for HSUPA (BPSK) Mode



Date: 9.JUN.2019 16:48:25


### 26 dB Emissions & 99% Occupied Bandwidth for HSDPA (16QAM) Mode



Date: 9.JUN.2019 16:51:56


## PCS Band (Part 24E)

## 26 dB Emissions &amp; 99% Occupied Bandwidth for GSM (GMSK) Mode




Date: 9.JUN.2019 14:16:25

## 26 dB Emissions &amp; 99% Occupied Bandwidth for RMC (BPSK) Mode




Date: 9.JUN.2019 15:24:27

## 26 dB Emissions & 99% Occupied Bandwidth for HSUPA (BPSK) Mode



Date: 9.JUN.2019 15:15:12


## 26 dB Emissions & 99% Occupied Bandwidth for HSDPA (16QAM) Mode



Date: 9.JUN.2019 15:14:07


## AWS Band (Part 27)

## 26 dB Emissions &amp; 99% Occupied Bandwidth for RMC (BPSK) Mode




Date: 9.JUN.2019 15:54:32

## 26 dB Emissions &amp; 99% Occupied Bandwidth for HSUPA (BPSK) Mode



Date: 9.JUN.2019 17:11:42

## 26 dB Emissions & 99% Occupied Bandwidth for HSDPA (16QAM) Mode



Date: 9.JUN.2019 17:09:14

## FCC §2.1051, §22.917(a) & §24.238(a); §27.53 (h) (m) - SPURIOUS EMISSIONS AT ANTENNA TERMINALS


### Applicable Standard

FCC §2.1051, §22.917(a) and §24.238(a) and §27.53(h) (m).

The spectrum was to be investigated to the tenth harmonics of the highest fundamental frequency as specified in § 2.1051.

### Test Procedure

The RF output of the transceiver was connected to a spectrum analyzer and simulator through appropriate attenuation. The resolution bandwidth of the spectrum analyzer was set at 1MHz. Sufficient scans were taken to show any out of band emissions up to 10<sup>th</sup> harmonic.



### Test Data

#### Environmental Conditions

|                    |           |
|--------------------|-----------|
| Temperature:       | 25 °C     |
| Relative Humidity: | 55 %      |
| ATM Pressure:      | 101.0 kPa |

*The testing was performed by George Zhong on 2019-06-09.*


*Test result: Compliance.*

*EUT operation mode: transmitting*

*Please refer to the following plots.*

## Cellular Band (Part 22H)


## 30 MHz – 1 GHz (GSM Mode)



Fundamental test


Date: 9.JUN.2019 14:02:36

## 1 GHz – 10 GHz (GSM Mode)



Date: 9.JUN.2019 14:01:21


### 30 MHz – 1 GHz (WCDMA Mode)



Fundamental test

Date: 9.JUN.2019 16:35:02


### 1 GHz – 10 GHz (WCDMA Mode)



Date: 9.JUN.2019 16:36:07


PCS Band (Part 24E)

30 MHz – 1 GHz (GSM Mode)



Date: 9.JUN.2019 14:06:06


1 GHz – 2 GHz (GSM Mode)



Fundamental test


Date: 9.JUN.2019 14:07:36

### 2 GHz – 20 GHz (GSM Mode)




Date: 9.JUN.2019 14:08:23

### 30 MHz – 1 GHz (WCDMA Mode)



Date: 9.JUN.2019 15:27:35


### 1 GHz – 2 GHz (WCDMA Mode)



Fundamental test

Date: 9.JUN.2019 15:28:44


### 2 GHz – 20 GHz (WCDMA Mode)



Date: 9.JUN.2019 15:29:06


# AWS Band (Part 27)

## 30 MHz – 1 GHz (WCDMA Mode)




Date: 9.JUN.2019 15:45:10

## 1 GHz – 2 GHz (WCDMA Mode)



Date: 9.JUN.2019 15:44:08

## 2 GHz – 20 GHz (WCDMA Mode)



Date: 9.JUN.2019 15:44:42

**FCC § 2.1053; § 22.917 (a); § 24.238 (a); § 27.53 (h)(m) SPURIOUS RADIATED EMISSIONS**

---

**Applicable Standard**

FCC § 2.1053, § 22.917(a) and § 24.238(a) and § 27.53(h)(m)

**Test Procedure**

The transmitter was placed on a wooden turntable, and it was transmitting into a non-radiating load which was also placed on the turntable.

The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the receiving antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis.

The frequency range up to tenth harmonic of the fundamental frequency was investigated.

**Test Data****Environmental Conditions**

|                           |           |
|---------------------------|-----------|
| <b>Temperature:</b>       | 25 °C     |
| <b>Relative Humidity:</b> | 50 %      |
| <b>ATM Pressure:</b>      | 101.0 kPa |

*The testing was performed by George Zhong on 2019-06-09.*

*EUT operation mode: Transmitting*

Pre-scan with Low, Middle and High channel, the worst case as below:

30 MHz ~ 10 GHz:

**Cellular Band (Part 22H)**

| Frequency<br>(MHz)         | Receiver<br>Reading<br>(dBμV) | Turntable<br>Angle<br>Degree | Rx Antenna    |                | Substituted    |                       |                              | Absolute<br>Level<br>(dBm) | FCC Part 22H   |                |
|----------------------------|-------------------------------|------------------------------|---------------|----------------|----------------|-----------------------|------------------------------|----------------------------|----------------|----------------|
|                            |                               |                              | Height<br>(m) | Polar<br>(H/V) | Level<br>(dBm) | Cable<br>Loss<br>(dB) | Antenna<br>Gain<br>(dBd/dBi) |                            | Limit<br>(dBm) | Margin<br>(dB) |
| GSM Mode, middle channel   |                               |                              |               |                |                |                       |                              |                            |                |                |
| 948.65                     | 37.89                         | 67                           | 1.5           | H              | -62.7          | 1.37                  | 0                            | -64.07                     | -13            | 51.07          |
| 948.65                     | 36.63                         | 242                          | 2.2           | V              | -62.7          | 1.37                  | 0                            | -64.07                     | -13            | 51.07          |
| 1673.20                    | 57.32                         | 248                          | 1.0           | H              | -49.0          | 1.30                  | 8.90                         | -41.40                     | -13            | 28.40          |
| 1673.20                    | 59.52                         | 287                          | 1.7           | V              | -46.2          | 1.30                  | 8.90                         | -38.60                     | -13            | 25.60          |
| 2509.80                    | 48.52                         | 325                          | 1.1           | H              | -54.8          | 2.60                  | 10.20                        | -47.20                     | -13            | 34.20          |
| 2509.80                    | 57.15                         | 55                           | 2.1           | V              | -45.6          | 2.60                  | 10.20                        | -38.00                     | -13            | 25.00          |
| 3346.40                    | 44.25                         | 249                          | 1.3           | H              | -56.6          | 1.50                  | 11.70                        | -46.40                     | -13            | 33.40          |
| 3346.40                    | 44.43                         | 43                           | 1.1           | V              | -56.5          | 1.50                  | 11.70                        | -46.30                     | -13            | 33.30          |
| WCDMA Mode, Middle channel |                               |                              |               |                |                |                       |                              |                            |                |                |
| 948.54                     | 37.65                         | 210                          | 1.4           | H              | -63.0          | 1.37                  | 0                            | -64.37                     | -13            | 51.37          |
| 948.54                     | 36.30                         | 280                          | 1.8           | V              | -63.0          | 1.37                  | 0                            | -64.37                     | -13            | 51.37          |
| 1673.20                    | 48.77                         | 169                          | 1.2           | H              | -57.6          | 1.30                  | 8.90                         | -50.00                     | -13            | 37.00          |
| 1673.20                    | 46.99                         | 23                           | 2.1           | V              | -58.7          | 1.30                  | 8.90                         | -51.10                     | -13            | 38.10          |
| 2509.80                    | 47.45                         | 105                          | 1.1           | H              | -55.9          | 2.60                  | 10.20                        | -48.30                     | -13            | 35.30          |
| 2509.80                    | 48.40                         | 193                          | 2.4           | V              | -54.3          | 2.60                  | 10.20                        | -46.70                     | -13            | 33.70          |
| 3346.40                    | 43.51                         | 76                           | 1.4           | H              | -57.4          | 1.50                  | 11.70                        | -47.20                     | -13            | 34.20          |
| 3346.40                    | 44.12                         | 42                           | 1.6           | V              | -56.8          | 1.50                  | 11.70                        | -46.60                     | -13            | 33.60          |

30 MHz ~ 20 GHz:

## PCS Band (Part 24E)

| Frequency<br>(MHz)                 | Receiver<br>Reading<br>(dBμV) | Turntable<br>Angle<br>Degree | Rx Antenna    |                | Substituted    |                       |                              | Absolute<br>Level<br>(dBm) | FCC Part 24E   |                |
|------------------------------------|-------------------------------|------------------------------|---------------|----------------|----------------|-----------------------|------------------------------|----------------------------|----------------|----------------|
|                                    |                               |                              | Height<br>(m) | Polar<br>(H/V) | Level<br>(dBm) | Cable<br>Loss<br>(dB) | Antenna<br>Gain<br>(dBd/dBi) |                            | Limit<br>(dBm) | Margin<br>(dB) |
| GSM Mode, middle channel           |                               |                              |               |                |                |                       |                              |                            |                |                |
| 948.71                             | 37.62                         | 296                          | 1.4           | H              | -63.0          | 1.37                  | 0                            | -64.37                     | -13            | 51.37          |
| 948.71                             | 36.79                         | 308                          | 1.2           | V              | -62.5          | 1.37                  | 0                            | -63.87                     | -13            | 50.87          |
| 3760.00                            | 45.51                         | 201                          | 2.5           | H              | -56.5          | 1.50                  | 11.80                        | -46.20                     | -13            | 33.20          |
| 3760.00                            | 45.54                         | 46                           | 1.9           | V              | -56.0          | 1.50                  | 11.80                        | -45.70                     | -13            | 32.70          |
| 5640.00                            | 48.46                         | 104                          | 2.2           | H              | -51.2          | 1.70                  | 12.40                        | -40.50                     | -13            | 27.50          |
| 5640.00                            | 47.59                         | 207                          | 2.4           | V              | -51.8          | 1.70                  | 12.40                        | -41.10                     | -13            | 28.10          |
| 9400.00                            | 45.94                         | 299                          | 1.7           | H              | -50.9          | 2.20                  | 11.50                        | -41.60                     | 13             | 54.60          |
| 9400.00                            | 43.17                         | 212                          | 1.1           | V              | -53.9          | 2.20                  | 11.50                        | -44.60                     | -13            | 31.60          |
| WCDMA Mode Band II, Middle channel |                               |                              |               |                |                |                       |                              |                            |                |                |
| 947.92                             | 38.05                         | 104                          | 1.5           | H              | -62.6          | 1.37                  | 0                            | -63.97                     | -13            | 50.97          |
| 947.92                             | 36.46                         | 289                          | 1.3           | V              | -62.8          | 1.37                  | 0                            | -64.17                     | -13            | 51.17          |
| 3760.00                            | 43.25                         | 171                          | 1.9           | H              | -58.0          | 1.50                  | 11.80                        | -47.70                     | -13            | 34.70          |
| 3760.00                            | 42.60                         | 220                          | 1.6           | V              | -58.2          | 1.50                  | 11.80                        | -47.90                     | -13            | 34.90          |

30 MHz ~ 20 GHz:

## AWS Band (Part 27)

| Frequency<br>(MHz)                 | Receiver<br>Reading<br>(dBμV) | Turntable<br>Angle<br>Degree | Rx Antenna    |                | Substituted    |                       |                              | Absolute<br>Level<br>(dBm) | FCC Part 27    |                |
|------------------------------------|-------------------------------|------------------------------|---------------|----------------|----------------|-----------------------|------------------------------|----------------------------|----------------|----------------|
|                                    |                               |                              | Height<br>(m) | Polar<br>(H/V) | Level<br>(dBm) | Cable<br>Loss<br>(dB) | Antenna<br>Gain<br>(dBd/dBi) |                            | Limit<br>(dBm) | Margin<br>(dB) |
| WCDMA Mode Band IV, Middle channel |                               |                              |               |                |                |                       |                              |                            |                |                |
| 947.36                             | 37.76                         | 124                          | 1.7           | H              | -62.8          | 1.37                  | 0                            | -64.17                     | -13            | 51.17          |
| 947.36                             | 36.17                         | 153                          | 1.8           | V              | -63.1          | 1.37                  | 0                            | -64.47                     | -13            | 51.47          |
| 3465.20                            | 44.67                         | 43                           | 1.6           | H              | -56.1          | 1.50                  | 12.00                        | -45.60                     | -13            | 32.60          |
| 3465.20                            | 43.45                         | 162                          | 2.5           | V              | -58.1          | 1.50                  | 12.00                        | -47.60                     | -13            | 34.60          |

**Note:**

1) Absolute Level = Substituted Level - Cable loss + Antenna Gain

2) Margin = Limit- Absolute Level

3) The unit of antenna gain is dBd for frequency below 1GHz and is dBi for frequency above 1GHz.

**FCC § 22.917 (a);§ 24.238 (a); §27.53 (h)(m) - BAND EDGES****Applicable Standard**

According to § 22.917(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43 + 10 \log(P)$  dB.


According to §24.238(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43 + 10 \log(P)$  dB.

According to FCC §27.53 (h)(m), the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43 + 10 \log(P)$  dB.

**Test Procedure**

The RF output of the transmitter was connected to the input of the spectrum analyzer through sufficient attenuation.

The center of the spectrum analyzer was set to block edge frequency

**Test Data****Environmental Conditions**


|                    |           |
|--------------------|-----------|
| Temperature:       | 25 °C     |
| Relative Humidity: | 55 %      |
| ATM Pressure:      | 101.0 kPa |

*The testing was performed by George Zhong on 2019-06-09.*

*EUT operation mode: Transmitting*


*Test Result: Compliance. Please refer to the following plots.*

### Cellular Band, Left Band Edge for GSM (GMSK) Mode




Date: 9.JUN.2019 13:48:02

### Cellular Band, Right Band Edge for GSM (GMSK) Mode




Date: 9.JUN.2019 13:52:55

### Cellular Band, Left Band Edge for WCDMA (BPSK) Mode




Date: 9.JUN.2019 16:21:09

### Cellular Band, Right Band Edge for WCDMA (BPSK) Mode




Date: 9.JUN.2019 16:22:17

### Cellular Band, Left Band Edge for HSDPA (16QAM) Mode




Date: 9.JUN.2019 16:53:03

### Cellular Band, Right Band Edge for HSDPA (16QAM) Mode




Date: 9.JUN.2019 16:53:48

### Cellular Band, Left Band Edge for HSUPA (BPSK) Mode




Date: 9.JUN.2019 16:45:09

### Cellular Band, Right Band Edge for HSUPA (BPSK) Mode




Date: 9.JUN.2019 16:46:13

### PCS Band, Left Band Edge for GSM (GMSK) Mode




Date: 9.JUN.2019 14:11:35

### PCS Band, Right Band Edge for GSM (GMSK) Mode




Date: 9.JUN.2019 14:12:37

### PCS Band, Left Band Edge for WCDMA (BPSK) Mode




Date: 9.JUN.2019 15:20:32

### PCS Band, Right Band Edge for WCDMA (BPSK) Mode




Date: 9.JUN.2019 15:19:39

### PCS Band, Left Band Edge for HSDPA (16QAM) Mode




Date: 9.JUN.2019 14:57:46

### PCS Band, Right Band Edge for HSDPA (16QAM) Mode




Date: 9.JUN.2019 14:58:42

### PCS Band, Left Band Edge for HSUPA (BPSK) Mode




Date: 9.JUN.2019 15:20:32

### PCS Band, Right Band Edge for HSUPA (BPSK) Mode




Date: 9.JUN.2019 15:19:39

### AWS Band, Left Band Edge for WCDMA (BPSK) Mode




Date: 9.JUN.2019 15:56:08

### AWS Band, Right Band Edge for WCDMA (BPSK) Mode




Date: 9.JUN.2019 15:57:05

### AWS Band, Left Band Edge for HSDPA (16QAM) Mode




Date: 9.JUN.2019 16:08:42

### AWS Band, Right Band Edge for HSDPA (16QAM) Mode




Date: 9.JUN.2019 16:07:53

### AWS Band, Left Band Edge for HSUPA (BPSK) Mode



Date: 9.JUN.2019 16:17:12

### AWS Band, Right Band Edge for HSUPA (BPSK) Mode



Date: 9.JUN.2019 16:16:05

## FCC § 2.1055; § 22.355; § 24.235; §27.54 - FREQUENCY STABILITY

### Applicable Standard

FCC § 2.1055, §22.355, §24.235 and §27.54.

According to FCC §2.1055, the frequency stability shall be sufficient to ensure that the fundamental emissions stay within the authorized bands of operation.

According to §22.355, the carrier frequency of each transmitter in the Public Mobile Services must be maintained within the tolerances given in Table below:

Frequency Tolerance for Transmitters in the Public Mobile Services

| Frequency Range (MHz) | Base, fixed (ppm) | Mobile ≤ 3 watts (ppm) | Mobile > 3 watts (ppm) |
|-----------------------|-------------------|------------------------|------------------------|
| 25 to 50              | 20.0              | 20.0                   | 50.0                   |
| 50 to 450             | 5.0               | 5.0                    | 50.0                   |
| 450 to 512            | 2.5               | 5.0                    | 5.0                    |
| 821 to 896            | 1.5               | 2.5                    | 2.5                    |
| 928 to 929.           | 5.0               | N/A                    | N/A                    |
| 929 to 960.           | 1.5               | N/A                    | N/A                    |
| 2110 to 2220          | 10.0              | N/A                    | N/A                    |


According to §24.235, the frequency stability shall be sufficient to ensure that the fundamental emissions stays within the authorized frequency block.

### Test Procedure

**Frequency Stability vs. Temperature:** The equipment under test was connected to an external DC power supply and the RF output was connected to communication test set via feed-through attenuators. The EUT was placed inside the temperature chamber. The DC leads and RF output cable exited the chamber through an opening made for the purpose.

After the temperature stabilized for approximately 20 minutes, the frequency output was recorded from the communication test set.

**Frequency Stability vs. Voltage:** For hand carried, battery powered equipment; reduce primary supply voltage to the battery operating end point which shall be specified by the manufacturer.



**Test Data****Environmental Conditions**

|                           |           |
|---------------------------|-----------|
| <b>Temperature:</b>       | 25 °C     |
| <b>Relative Humidity:</b> | 50 %      |
| <b>ATM Pressure:</b>      | 101.0 kPa |

The testing was performed by George Zhong on 2019-06-09.

EUT operation mode: Transmitting

Test Result: Compliance. Please refer to the following tables.

**Cellular Band (Part 22H)****GSM Mode**

| Middle Channel, $f_0 = 836.6\text{MHz}$ |                                     |                      |                       |             |
|-----------------------------------------|-------------------------------------|----------------------|-----------------------|-------------|
| Temperature (°C)                        | Voltage Supplied (V <sub>DC</sub> ) | Frequency Error (Hz) | Frequency Error (ppm) | Limit (ppm) |
| -30                                     | 3.7                                 | 2                    | 0.0024                | 2.5         |
| -20                                     |                                     | -1                   | -0.0012               | 2.5         |
| -10                                     |                                     | 1                    | 0.0012                | 2.5         |
| 0                                       |                                     | -2                   | -0.0024               | 2.5         |
| 10                                      |                                     | -3                   | -0.0036               | 2.5         |
| 20                                      |                                     | 2                    | 0.0024                | 2.5         |
| 30                                      |                                     | 1                    | 0.0012                | 2.5         |
| 40                                      |                                     | 2                    | 0.0024                | 2.5         |
| 50                                      |                                     | -2                   | -0.0024               | 2.5         |
| 20                                      | V min.= 3.5                         | 1                    | 0.0012                | 2.5         |
|                                         | V max.= 4.2                         | 2                    | 0.0024                | 2.5         |

**WCDMA Mode**

| Middle Channel, $f_0 = 836.6\text{MHz}$ |                               |                      |                       |             |
|-----------------------------------------|-------------------------------|----------------------|-----------------------|-------------|
| Temperature (°C)                        | Voltage Supplied ( $V_{DC}$ ) | Frequency Error (Hz) | Frequency Error (ppm) | Limit (ppm) |
| -30                                     | 3.7                           | 5                    | 0.0060                | 2.5         |
| -20                                     |                               | 3                    | 0.0036                | 2.5         |
| -10                                     |                               | -1                   | -0.0012               | 2.5         |
| 0                                       |                               | 1                    | 0.0012                | 2.5         |
| 10                                      |                               | 0                    | 0.0000                | 2.5         |
| 20                                      |                               | -1                   | -0.0012               | 2.5         |
| 30                                      |                               | -4                   | -0.0048               | 2.5         |
| 40                                      |                               | 1                    | 0.0012                | 2.5         |
| 50                                      |                               | 5                    | 0.0060                | 2.5         |
| 20                                      | V min.= 3.5                   | 1                    | 0.0012                | 2.5         |
|                                         | V max.= 4.2                   | -6                   | -0.0072               | 2.5         |

**PCS Band (Part 24E)**

| Middle Channel, $f_0 = 1880.0\text{ MHz}$ |                               |                      |                       |        |
|-------------------------------------------|-------------------------------|----------------------|-----------------------|--------|
| Temperature (°C)                          | Voltage Supplied ( $V_{DC}$ ) | Frequency Error (Hz) | Frequency Error (ppm) | Result |
| -30                                       | 3.7                           | 2                    | 0.0011                | pass   |
| -20                                       |                               | 4                    | 0.0021                | pass   |
| -10                                       |                               | 2                    | 0.0011                | pass   |
| 0                                         |                               | -4                   | -0.0021               | pass   |
| 10                                        |                               | -3                   | -0.0016               | pass   |
| 20                                        |                               | -3                   | -0.0016               | pass   |
| 30                                        |                               | 4                    | 0.0021                | pass   |
| 40                                        |                               | 5                    | 0.0027                | pass   |
| 50                                        |                               | 3                    | 0.0016                | pass   |
| 20                                        | V min.= 3.5                   | 2                    | 0.0011                | pass   |
|                                           | V max.= 4.2                   | -3                   | -0.0016               | pass   |

**WCDMA Mode**

| Middle Channel, $f_0=1880.0$ MHz |                                     |                      |                       |        |
|----------------------------------|-------------------------------------|----------------------|-----------------------|--------|
| Temperature (°C)                 | Voltage Supplied (V <sub>DC</sub> ) | Frequency Error (Hz) | Frequency Error (ppm) | Result |
| -30                              | 3.7                                 | 4                    | 0.0021                | pass   |
| -20                              |                                     | 10                   | 0.0053                | pass   |
| -10                              |                                     | 8                    | 0.0043                | pass   |
| 0                                |                                     | 6                    | 0.0032                | pass   |
| 10                               |                                     | 4                    | 0.0021                | pass   |
| 20                               |                                     | -11                  | -0.0059               | pass   |
| 30                               |                                     | 12                   | 0.0064                | pass   |
| 40                               |                                     | 6                    | 0.0032                | pass   |
| 50                               |                                     | -1                   | -0.0005               | pass   |
| 20                               | V min.= 3.5                         | 8                    | 0.0043                | pass   |
|                                  | V max.= 4.2                         | 1                    | 0.0005                | pass   |

**AWS Band (Part 27)**

| Temperature (°C) | Power Supplied (V <sub>DC</sub> ) | F <sub>L</sub> (MHz) | F <sub>H</sub> (MHz) | F <sub>L</sub> Limit (MHz) | F <sub>H</sub> Limit (MHz) |
|------------------|-----------------------------------|----------------------|----------------------|----------------------------|----------------------------|
| -30              | 3.7                               | 1710.0071            | 1754.9974            | 1710                       | 1755                       |
| -20              |                                   | 1710.0032            | 1754.9977            | 1710                       | 1755                       |
| -10              |                                   | 1710.0058            | 1754.9973            | 1710                       | 1755                       |
| 0                |                                   | 1710.0021            | 1754.9954            | 1710                       | 1755                       |
| 10               |                                   | 1710.0021            | 1754.9973            | 1710                       | 1755                       |
| 20               |                                   | 1710.0047            | 1754.9989            | 1710                       | 1755                       |
| 30               |                                   | 1710.0054            | 1754.9966            | 1710                       | 1755                       |
| 40               |                                   | 1710.0031            | 1754.9975            | 1710                       | 1755                       |
| 50               |                                   | 1710.0070            | 1754.9985            | 1710                       | 1755                       |
| 20               | V min.= 3.5                       | 1710.0045            | 1754.9960            | 1710                       | 1755                       |
|                  | V max.= 4.2                       | 1710.0015            | 1754.9981            | 1710                       | 1755                       |

\*\*\*\*\* END OF REPORT \*\*\*\*\*