



EMC TEST REPORT



Report No.: 17070456-FCC-E-V1

Supersede Report No: N/A

Applicant	BLU Products, Inc.	
Product Name	Mobile Phone	
Model No.	BLU C5	
Serial No.	N/A	
Test Standard	FCC Part 15 Subpart B Class B:2016, ANSI C63.4: 2014	
Test Date	July 27 to August 13, 2017	
Issue Date	August 21, 2017	
Test Result	☒ Pass ☐ Fail	
Equipment complied with the specification ☒		
Equipment did not comply with the specification ☐		
		
Evans He Test Engineer	David Huang Checked By	
This test report may be reproduced in full only Test result presented in this test report is applicable to the tested sample only		

Issued by:

SIEMIC (SHENZHEN-CHINA) LABORATORIES

Zone A, Floor 1, Building 2 Wan Ye Long Technology Park

South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108

Phone: +86 0755 2601 4629801 Email: China@siemic.com.cn

Laboratories Introduction

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.



In addition to testing and certification, SIEMIC provides initial design reviews and compliance management throughout a project. Our extensive experience with China, Asia Pacific, North America, European, and International compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the global markets.

Accreditations for Conformity Assessment

Country/Region	Scope
USA	EMC, RF/Wireless, SAR, Telecom
Canada	EMC, RF/Wireless, SAR, Telecom
Taiwan	EMC, RF, Telecom, SAR, Safety
Hong Kong	RF/Wireless, SAR, Telecom
Australia	EMC, RF, Telecom, SAR, Safety
Korea	EMI, EMS, RF, SAR, Telecom, Safety
Japan	EMI, RF/Wireless, SAR, Telecom
Singapore	EMC, RF, SAR, Telecom
Europe	EMC, RF, SAR, Telecom, Safety

Test Report	17070456-FCC-E-V1
Page	3 of 36

This page has been left blank intentionally.

CONTENTS

1. REPORT REVISION HISTORY	5
2. CUSTOMER INFORMATION.....	5
3. TEST SITE INFORMATION	5
4. EQUIPMENT UNDER TEST (EUT) INFORMATION	6
5. TEST SUMMARY	8
6. MEASUREMENTS, EXAMINATION AND DERIVED RESULTS.....	9
6.1 AC POWER LINE CONDUCTED EMISSIONS.....	9
6.2 RADIATED EMISSIONS.....	15
ANNEX A. TEST INSTRUMENT.....	20
ANNEX B. EUT AND TEST SETUP PHOTOGRAPHS.....	21
ANNEX C. TEST SETUP AND SUPPORTING EQUIPMENT	32
ANNEX D. USER MANUAL / BLOCK DIAGRAM / SCHEMATICS / PARTLIST	35
ANNEX E. DECLARATION OF SIMILARITY	36

1. Report Revision History

Report No.	Report Version	Description	Issue Date
17070456-FCC-E	NONE	Original	August 14, 2017
17070456-FCC-E-V1	V1	P7 Changed the GPRS/EGPRS Multi-slot class data	August 21, 2017

2. Customer information

Applicant Name	BLU Products, Inc.
Applicant Add	10814 NW 33rd St # 100 Doral, FL 33172
Manufacturer	BLU Products, Inc.
Manufacturer Add	10814 NW 33rd St # 100 Doral, FL 33172

3. Test site information

Lab performing tests	SIEMIC (Shenzhen-China) LABORATORIES
Lab Address	Zone A, Floor 1, Building 2 Wan Ye Long Technology Park South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108
FCC Test Site No.	718246
IC Test Site No.	4842E-1
Test Software of Radiated Emission	Radiated Emission Program-To Shenzhen v2.0
Test Software of Conducted Emission	EZ-EMC(ver.lcp-03A1)

4. Equipment under Test (EUT) Information

Description of EUT:	Mobile Phone
Main Model:	BLU C5
Serial Model:	N/A
Antenna Gain:	GSM850: -2.0dBi PCS1900: -1.2dBi UMTS-FDD Band V: -2.0dBi UMTS-FDD Band IV: -1.5dBi UMTS-FDD Band II: -2.0dBi WIFI: 0.5dBi Bluetooth/BLE: 0.5dBi GPS: 0.5dBi
Antenna Type:	PIFA antenna
Input Power:	Adapter: Model: US-WW-1001 Input: AC100-240V~50/60Hz, 0.2A Output: DC 5.0V, 1000mA Battery: Model: C775840200L Spec: 3.8V, 2000mAh, 7.60Wh
Equipment Category :	JBP
Type of Modulation:	GSM / GPRS: GMSK EGPRS: GMSK, 8PSK UMTS-FDD: QPSK 802.11b/g/n: DSSS, OFDM Bluetooth: GFSK, π /4DQPSK, 8DPSK BLE: GFSK GPS: BPSK
RF Operating Frequency (ies):	GSM850 TX: 824.2 ~ 848.8 MHz; RX: 869.2 ~ 893.8 MHz PCS1900 TX: 1850.2 ~ 1909.8 MHz; RX: 1930.2 ~ 1989.8 MHz

UMTS-FDD Band V TX: 826.4 ~ 846.6 MHz; RX: 871.4 ~ 891.6 MHz

UMTS-FDD Band IV TX: 1712.4 ~ 1752.6 MHz;

RX : 2112.4 ~ 2152.6 MHz

UMTS-FDD Band II TX: 1852.4 ~ 1907.6 MHz;

RX: 1932.4 ~ 1987.6 MHz

WIFI: 802.11b/g/n(20M): 2412-2462 MHz

WIFI: 802.11n(40M): 2422-2452 MHz

Bluetooth& BLE: 2402-2480 MHz

GPS: 1575.42 MHz

GSM 850: 124CH

PCS1900: 299CH

UMTS-FDD Band V: 102CH

UMTS-FDD Band IV: 202CH

UMTS-FDD Band II: 277CH

WIFI :802.11b/g/n(20M): 11CH

WIFI :802.11n(40M): 7CH

Bluetooth: 79CH

BLE: 40CH

GPS:1CH

Number of Channels:

Port:

USB Port, Earphone Port

Trade Name :

BLU

FCC ID:

YHLBLUC5

GPRS/ EGPRS Multi-slot class

8/10/11/12

Date EUT received:

July 26, 2017

Test Date(s):

July 27 to August 13, 2017

5. Test Summary

The product was tested in accordance with the following specifications.

All testing has been performed according to below product classification:

FCC Rules	Description of Test	Result
§15.107; ANSI C63.4: 2014	AC Power Line Conducted Emissions	Compliance
§15.109; ANSI C63.4: 2014	Radiated Emissions	Compliance

Measurement Uncertainty

Parameter	Uncertainty
AC Power Line Conducted Emissions (150kHz~30MHz)	±3.11dB
Radiated Emission(30MHz~1GHz)	±5.12dB
Radiated Emission(1GHz~6GHz)	±5.34dB


6. Measurements, Examination And Derived Results

6.1 AC Power Line Conducted Emissions

Temperature	25 °C
Relative Humidity	57%
Atmospheric Pressure	1015mbar
Test date :	August 07, 2017
Tested By :	Evans He

Requirement(s):

Spec	Item	Requirement	Applicable														
47CFR§15.107	a)	For Low-power radio-frequency devices that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 [mu] H/50 ohms line impedance stabilization network (LISN). The lower limit applies at the boundary between the frequencies ranges.															
		<table><tr><th rowspan="2">Frequency ranges (MHz)</th><th colspan="2">Limit (dBµV)</th></tr><tr><th>QP</th><th>Average</th></tr><tr><td>0.15 ~ 0.5</td><td>66 – 56</td><td>56 – 46</td></tr><tr><td>0.5 ~ 5</td><td>56</td><td>46</td></tr><tr><td>5 ~ 30</td><td>60</td><td>50</td></tr></table>		Frequency ranges (MHz)	Limit (dBµV)		QP	Average	0.15 ~ 0.5	66 – 56	56 – 46	0.5 ~ 5	56	46	5 ~ 30	60	50
		Frequency ranges (MHz)			Limit (dBµV)												
				QP	Average												
		0.15 ~ 0.5		66 – 56	56 – 46												
		0.5 ~ 5		56	46												
5 ~ 30	60	50															

Test Setup	 Note: 1.Support units were connected to second LISN. 2.Both of LISNs (AMN) are 80cm from EUT and at least 80cm from other units and other metal planes support units.
------------	---


Procedure	- The EUT and supporting equipment were set up in accordance with the requirements of the standard on top of a 1.5m x 1m x 0.8m high, non-metallic table. - The power supply for the EUT was fed through a 50Ω /50mH EUT LISN, connected to filtered mains.
-----------	--

	3. The RF OUT of the EUT LISN was connected to the EMI test receiver via a low-loss coaxial cable. 4. All other supporting equipment were powered separately from another main supply. 5. The EUT was switched on and allowed to warm up to its normal operating condition. 6. A scan was made on the NEUTRAL line (for AC mains) or Earth line (for DC power) over the required frequency range using an EMI test receiver. 7. High peaks, relative to the limit line, The EMI test receiver was then tuned to the selected frequencies and the necessary measurements made with a receiver bandwidth setting of 10 kHz. 8. Step 7 was then repeated for the LIVE line (for AC mains) or DC line (for DC power).
Remark	
Result	☒ Pass ☐ Fail

Test Data ☒ Yes ☐ N/A

Test Plot ☒ Yes (See below) ☐ N/A

Test Mode : USB Mode




Test Data

Phase Line Plot at 120Vac, 60Hz

No.	P/L	Frequency	Reading	Detector	Corrected	Result	Limit	Margin
		(MHz)	(dBuV)		(dB)	(dBuV)	(dBuV)	(dB)
1	L1	0.1773	44.69	QP	10.03	54.72	64.61	-9.89
2	L1	0.1773	30.50	AVG	10.03	40.53	54.61	-14.08
3	L1	0.4620	38.74	QP	10.03	48.77	56.66	-7.89
4	L1	0.4620	23.40	AVG	10.03	33.43	46.66	-13.23
5	L1	0.5322	38.99	QP	10.03	49.02	56.00	-6.98
6	L1	0.5322	16.70	AVG	10.03	26.73	46.00	-19.27
7	L1	0.7662	36.47	QP	10.03	46.50	56.00	-9.50
8	L1	0.7662	23.76	AVG	10.03	33.79	46.00	-12.21
9	L1	1.8231	39.04	QP	10.04	49.08	56.00	-6.92
10	L1	1.8231	18.21	AVG	10.04	28.25	46.00	-17.75
11	L1	16.7904	35.52	QP	10.25	45.77	60.00	-14.23
12	L1	16.7904	22.56	AVG	10.25	32.81	50.00	-17.19

Test Mode: USB Mode




Test Data

Phase Neutral Plot at 120Vac, 60Hz

No.	P/L	Frequency	Reading	Detector	Corrected	Result	Limit	Margin
		(MHz)	(dBuV)		(dB)	(dBuV)	(dBuV)	(dB)
1	L1	0.2709	25.23	QP	10.03	35.26	61.09	-25.83
2	L1	0.2709	17.86	AVG	10.03	27.89	51.09	-23.20
3	L1	0.3489	25.75	QP	10.03	35.78	58.99	-23.21
4	L1	0.3489	18.70	AVG	10.03	28.73	48.99	-20.26
5	L1	0.4542	29.45	QP	10.03	39.48	56.80	-17.32
6	L1	0.4542	4.91	AVG	10.03	14.94	46.80	-31.86
7	L1	0.9807	26.73	QP	10.03	36.76	56.00	-19.24
8	L1	0.9807	6.37	AVG	10.03	16.40	46.00	-29.60
9	L1	1.5696	22.11	QP	10.04	32.15	56.00	-23.85
10	L1	1.5696	-0.39	AVG	10.04	9.65	46.00	-36.35
11	L1	20.5578	13.73	QP	10.31	24.04	60.00	-35.96
12	L1	20.5578	7.24	AVG	10.31	17.55	50.00	-32.45

Test Mode : USB Mode




Test Data

Phase Line Plot at 240Vac, 60Hz

No.	P/L	Frequency	Reading	Detector	Corrected	Result	Limit	Margin
		(MHz)	(dBuV)		(dB}	(dBuV)	(dBuV)	(dB)
1	L1	0.1851	41.60	QP	10.03	51.63	64.25	-12.62
2	L1	0.1851	29.93	AVG	10.03	39.96	54.25	-14.29
3	L1	0.2787	42.24	QP	10.03	52.27	60.85	-8.58
4	L1	0.2787	28.16	AVG	10.03	38.19	50.85	-12.66
5	L1	0.4698	40.38	QP	10.03	50.41	56.52	-6.11
6	L1	0.4698	25.12	AVG	10.03	35.15	46.52	-11.37
7	L1	0.6921	40.96	QP	10.03	50.99	56.00	-5.01
8	L1	0.6921	24.52	AVG	10.03	34.55	46.00	-11.45
9	L1	1.6398	41.45	QP	10.04	51.49	56.00	-4.51
10	L1	1.6398	17.29	AVG	10.04	27.33	46.00	-18.67
11	L1	3.4719	38.73	QP	10.06	48.79	56.00	-7.21
12	L1	3.4719	13.23	AVG	10.06	23.29	46.00	-22.71

Test Mode : USB Mode



Test Data

Phase Neutral Plot at 240Vac, 60Hz


No.	P/L	Frequency	Reading	Detector	Corrected	Result	Limit	Margin
		(MHz)	(dBuV)		(dB}	(dBuV)	(dBuV)	(dB)
1	L1	0.4620	36.40	QP	10.03	46.43	56.66	-10.23
2	L1	0.4620	13.98	AVG	10.03	24.01	46.66	-22.65
3	L1	1.1718	28.10	QP	10.03	38.13	56.00	-17.87
4	L1	1.1718	6.21	AVG	10.03	16.24	46.00	-29.76
5	L1	2.1975	25.24	QP	10.04	35.28	56.00	-20.72
6	L1	2.1975	3.84	AVG	10.04	13.88	46.00	-32.12
7	L1	2.8137	24.90	QP	10.05	34.95	56.00	-21.05
8	L1	2.8137	5.26	AVG	10.05	15.31	46.00	-30.69
9	L1	14.2905	24.70	QP	10.21	34.91	60.00	-25.09
10	L1	14.2905	7.19	AVG	10.21	17.40	50.00	-32.60
11	L1	21.0843	19.66	QP	10.32	29.98	60.00	-30.02
12	L1	21.0843	6.73	AVG	10.32	17.05	50.00	-32.95

6.2 Radiated Emissions

Temperature	25 °C
Relative Humidity	50%
Atmospheric Pressure	1008mbar
Test date :	August 08, 2017
Tested By :	Evans He

Requirement(s):

Spec	Item	Requirement	Applicable	
47CFR§15.109(d)	a)	Except higher limit as specified elsewhere in other section, the emissions from the low-power radio-frequency devices shall not exceed the field strength levels specified in the following table and the level of any unwanted emissions shall not exceed the level of the fundamental emission. The tighter limit applies at the band edges	☒	
		Frequency range (MHz)		Field Strength (µV/m)
		30 – 88		100
		88 – 216		150
		216 - 960		200
		Above 960		500

Test Setup	
------------	--

Procedure	- The EUT was switched on and allowed to warm up to its normal operating condition. - The test was carried out at the selected frequency points obtained from the EUT characterization. Maximization of the emissions, was carried out by rotating the EUT, changing the antenna polarization, and adjusting the antenna height in the following manner: - Vertical or horizontal polarization (whichever gave the higher emission level
-----------	--

	over a full rotation of the EUT) was chosen. b. The EUT was then rotated to the direction that gave the maximum emission. c. Finally, the antenna height was adjusted to the height that gave the maximum emission. 3. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasi Peak detection at frequency below 1GHz. 4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz with Peak detection for Peak measurement at frequency above 1GHz. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth with Peak detection for Average Measurement as below at frequency above 1GHz. ■ 1 kHz (Duty cycle < 98%) □ 10 Hz (Duty cycle > 98%) 5. Steps 2 and 3 were repeated for the next frequency point, until all selected frequency points were measured.
Remark	
Result	☒ Pass ☐ Fail


Test Data ☒ Yes ☐ N/A

Test Plot ☒ Yes (See below) ☐ N/A

Test Mode : USB Mode

Below 1GHz

80.0 dBuV/m




Test Data

Horizontal Polarity Plot @3m

No.	P/L	Frequency (MHz)	Reading (dBuV/m)	Detector	Ant_F (dB/m)	PA_G (dB)	Cab_L (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (°)
1	H	60.7044	32.78	peak	7.34	22.41	0.77	18.48	40.00	-21.52	100	68
2	H	114.1138	29.71	peak	12.87	22.35	1.17	21.40	43.50	-22.10	200	232
3	H	204.9551	43.94	peak	12.03	22.37	1.56	35.16	43.50	-8.34	100	254
4	H	233.3487	43.36	peak	11.63	22.32	1.65	34.32	46.00	-11.68	100	90
5	H	333.6867	40.91	peak	14.31	22.20	1.96	34.98	46.00	-11.02	100	74
6	H	477.1694	38.35	peak	17.24	21.86	2.29	36.02	46.00	-9.98	100	206

Below 1GHz



Test Data

Vertical Polarity Plot @3m

No.	P/L	Frequency	Reading	Detector	Ant_F	PA_G	Cab_L	Result	Limit	Margin	Height	Degree
		(MHz)	(dBuV/m)		(dB/m)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	(cm)	(°)
1	V	60.7044	38.85	peak	7.34	22.41	0.77	24.55	40.00	-15.45	100	311
2	V	96.7749	30.53	peak	9.63	22.32	1.04	18.88	43.50	-24.62	100	168
3	V	185.7882	40.89	peak	11.32	22.29	1.46	31.38	43.50	-12.12	100	137
4	V	274.1939	36.17	peak	12.46	22.29	1.74	28.08	46.00	-17.92	100	328
5	V	475.4991	32.02	peak	17.21	21.86	2.28	29.65	46.00	-16.35	100	164
6	V	714.1734	36.44	peak	20.37	21.33	2.63	38.11	46.00	-7.89	100	350

Above 1GHz

Frequency (MHz)	Read_level (dBμV/m)	Azimuth	Height (cm)	Polarity (H/V)	Level (dBμV/m)	Factors (dB)	Limit (dBμV/m)	Margin (dB)	Detector (PK/AV)
1412.3	67.53	168	100	V	-18.97	48.56	74	-25.44	PK
1987.5	62.5	248	100	V	-15.25	47.25	74	-26.75	PK
2234.6	59.66	137	100	V	-14.35	45.31	74	-28.69	PK
1654.9	67.52	62	100	H	-17.64	49.88	74	-24.12	PK
2035.6	59.54	150	100	H	-14.39	45.15	74	-28.85	PK
2481.2	62.9	227	100	H	-13.7	49.2	74	-24.8	PK

Note1: The highest frequency of the EUT is 2480 MHz, so the testing has been conformed to $5 \times 2480 \text{ MHz} = 12,400 \text{ MHz}$.

Note2: The frequency that above 3GHz is mainly from the environment noise.

Note3: The AV measurement performed, more than 20dB below limit so AV test data was not presented.

Annex A. TEST INSTRUMENT

Instrument	Model	Serial #	Cal Date	Cal Due	In use
AC Line Conducted Emissions					
EMI test receiver	ESCS30	8471241027	09/16/2016	09/15/2017	☒
Line Impedance Stabilization Network	LI-125A	191106	09/24/2016	09/23/2017	☒
Line Impedance Stabilization Network	LI-125A	191107	09/24/2016	09/23/2017	☒
ISN	ISN T800	34373	09/24/2016	09/23/2017	☐
Transient Limiter	LIT-153	531118	08/31/2016	08/30/2017	☒
Radiated Emissions					
EMI test receiver	ESL6	100262	09/16/2016	09/15/2017	☒
OPT 010 AMPLIFIER (0.1-1300MHz)	8447E	2727A02430	08/31/2016	08/30/2017	☒
Microwave Preamplifier (1 ~ 26.5GHz)	8449B	3008A02402	03/23/2017	03/22/2018	☒
Bilog Antenna (30MHz~6GHz)	JB6	A110712	09/20/2016	09/19/2017	☒
Double Ridge Horn Antenna	AH-118	71259	09/23/2016	09/22/2017	☒

Annex B. EUT And Test Setup Photographs

Annex B.i. Photograph: EUT External Photo

Whole Package View



Adapter - Label View



EUT - Front View



EUT - Rear View



EUT - Top View



EUT - Bottom View



EUT - Left View



EUT - Right View



Annex B.ii. Photograph: EUT Internal Photo

Cover Off - Top View 1




Cover Off - Top View 2



Battery - Front View



Battery - Rear View




A photograph of a green printed circuit board (PCB) of a mobile phone, showing various components like the SIM card slot, camera lens, and connectors. A ruler is placed vertically on the left side for scale. The PCB is populated with numerous components, including a SIM card slot at the top, a camera lens in the center, and various connectors and chips. A white label with the text "Z401103030000" and "AG0110" is visible. The board is set against a blue textured background.

Mainboard without Shielding – Front View



Mainboard without Shielding – Rear View



LCD – Front View



LCD – Rear View



GSM/PCS/UMTS-FDD - Antenna View




WIFI/BT/BLE/GPS - Antenna View




Annex B.iii. Photograph: Test Setup Photo




Conducted Emissions Test Setup – Front View



Conducted Emissions Test Setup – Side View



Radiated Emissions Test Setup Below 1GHz




Radiated Emissions Test Setup Above 1GHz


Annex C. TEST SETUP AND SUPPORTING EQUIPMENT

Annex C.ii. TEST SET UP BLOCK

Block Configuration Diagram for Conducted Emissions



Block Configuration Diagram for Radiated Emissions



Annex C. ii. SUPPORTING EQUIPMENT DESCRIPTION

The following is a description of supporting equipment and details of cables used with the EUT.

Supporting Equipment:

Manufacturer	Equipment Description	Model	Serial No
Lenovo	Laptop	E40	LR-1EHRX
GOLDWEB	Router	R102	1202032094
Lenovo	AC Adapter	42T4416	21D9JU
HP	Printer	VCVRA-1003	CN36M19JWX
DELL	Mouse	E100	912NMTUT41481
BULL	Socket	GN-403	GN201203
SAMSUNG	headset	HS330	N/A

Supporting Cable:

Cable type	Shield Type	Ferrite Core	Length	Serial No
USB Cable	Un-shielding	No	2m	JX120051274
USB Cable	Un-shielding	No	2m	CBA3000AH0C1
RJ45 Cable	Un-shielding	No	2m	KX156327541
Router Power cable	Un-shielding	No	2m	13274630Z
Printer Power cable	Un-shielding	No	2m	127581031
Power Cable	Un-shielding	No	0.8m	GT211032
Earphone Cables	Un-shielding	No	0.5m	N/A

Test Report	17070456-FCC-E-V1
Page	35 of 36

Annex D. User Manual / Block Diagram / Schematics / Partlist

Please see the attachment

Annex E. DECLARATION OF SIMILARITY

N/A