


# FCC Test Report

APPLICANT : CT Asia  
EQUIPMENT : Mobile Phone  
BRAND NAME : BLU  
MODEL NAME : Dash Jr TV  
FCC ID : YHLBLUDASHJRTV  
STANDARD : FCC 47 CFR FCC Part 15 Subpart B  
CLASSIFICATION : Certification


The product was received on Jun. 16, 2014 and testing was completed on Jul. 07, 2014. We, SPORTON INTERNATIONAL (SHENZHEN) INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures given in ANSI C63.4-2003 and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL (SHENZHEN) INC., the test report shall not be reproduced except in full.



---

Reviewed by: Louis Wu / Manager



---

Approved by: Jones Tsai / Manager



## **SPORTON INTERNATIONAL (SHENZHEN) INC.**

**No. 3 Building, the third floor of south, Shahe River west, Fengzeyuan warehouse, Nanshan District, Shenzhen, Guangdong, P.R.C.**



## TABLE OF CONTENTS

|                                                              |    |
|--------------------------------------------------------------|----|
| REVISION HISTORY .....                                       | 3  |
| SUMMARY OF TEST RESULT .....                                 | 4  |
| 1. GENERAL DESCRIPTION .....                                 | 5  |
| 1.1. Applicant.....                                          | 5  |
| 1.2. Manufacturer .....                                      | 5  |
| 1.3. Product Feature of Equipment Under Test .....           | 5  |
| 1.4. Product Specification subjective to this standard.....  | 6  |
| 1.5. Modification of EUT .....                               | 6  |
| 1.6. Test Location.....                                      | 7  |
| 1.7. Applicable Standards .....                              | 7  |
| 2. TEST CONFIGURATION OF EQUIPMENT UNDER TEST .....          | 8  |
| 2.1. Test Mode .....                                         | 8  |
| 2.2. Connection Diagram of Test System .....                 | 10 |
| 2.3. Support Unit used in test configuration and system..... | 11 |
| 2.4. EUT Operation Test Setup .....                          | 12 |
| 3. TEST RESULT .....                                         | 13 |
| 3.1. Test of AC Conducted Emission Measurement .....         | 13 |
| 3.2. Test of Radiated Emission Measurement .....             | 19 |
| 4. LIST OF MEASURING EQUIPMENT .....                         | 23 |
| 5. UNCERTAINTY OF EVALUATION .....                           | 24 |
| APPENDIX A. SETUP PHOTOGRAPHS                                |    |



## REVISION HISTORY

| REPORT NO. | VERSION | DESCRIPTION             | ISSUED DATE   |
|------------|---------|-------------------------|---------------|
| FC461607   | Rev. 01 | Initial issue of report | Aug. 05, 2014 |
|            |         |                         |               |
|            |         |                         |               |
|            |         |                         |               |
|            |         |                         |               |
|            |         |                         |               |
|            |         |                         |               |
|            |         |                         |               |
|            |         |                         |               |
|            |         |                         |               |
|            |         |                         |               |
|            |         |                         |               |
|            |         |                         |               |
|            |         |                         |               |
|            |         |                         |               |



## SUMMARY OF TEST RESULT

| Report Section | FCC Rule | Description           | Limit           | Result | Remark                                   |
|----------------|----------|-----------------------|-----------------|--------|------------------------------------------|
| 3.1            | 15.107   | AC Conducted Emission | < 15.107 limits | PASS   | Under limit<br>8.17 dB at<br>0.540 MHz   |
| 3.2            | 15.109   | Radiated Emission     | < 15.109 limits | PASS   | Under limit<br>4.79 dB at<br>199.560 MHz |

## 1. General Description

### 1.1. Applicant

**CT Asia**

Unit 01, 15/F, Seaview Centre, 139-141 Hoi bun road, Kwun Tong, Kowloon, Hongkong

### 1.2. Manufacturer

**Zechin Communications Co.,Ltd.**

Unit804, 8th Floor Desay Tech Building Gaoxin Road South, Nanshan District Shenzhen, China

### 1.3. Product Feature of Equipment Under Test

| Product Feature                 |                                                                                       |
|---------------------------------|---------------------------------------------------------------------------------------|
| Equipment                       | Mobile Phone                                                                          |
| Brand Name                      | BLU                                                                                   |
| Model Name                      | Dash Jr TV                                                                            |
| FCC ID                          | YHLBLUDASHJRTV                                                                        |
| EUT supports Radios application | GSM/GPRS<br>WLAN 2.4GHz 802.11b/g/n HT20/40<br>Bluetooth v3.0 + EDR/Bluetooth v4.0 LE |
| HW Version                      | S1016-MB-V1.0                                                                         |
| SW Version                      | BLU_D140T_V14_GENERIC                                                                 |
| EUT Stage                       | Pre-Production                                                                        |

**Remark:** The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

#### 1.4. Product Specification subjective to this standard

| Product Specification subjective to this standard |                                                                                                                                                                                                  |
|---------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Tx Frequency</b>                               | GSM850 : 824.2 MHz ~ 848.8 MHz<br>GSM1900 : 1850.2 MHz ~ 1909.8MHz<br>802.11b/g/n: 2412 MHz ~ 2462 MHz<br>Bluetooth: 2402 MHz ~ 2480 MHz                                                         |
| <b>Rx Frequency</b>                               | GSM850 : 869.2 MHz ~ 893.8 MHz<br>GSM1900 : 1930.2 MHz ~ 1989.8 MHz<br>802.11b/g/n: 2412 MHz ~ 2462 MHz<br>Bluetooth: 2402 MHz ~ 2480 MHz                                                        |
| <b>Antenna Type</b>                               | WWAN : PIFA Antenna<br>WLAN : PIFA Antenna<br>Bluetooth : PIFA Antenna                                                                                                                           |
| <b>Type of Modulation</b>                         | GSM: GMSK<br>GPRS: GMSK<br>802.11b : DSSS (DBPSK / DQPSK / CCK)<br>802.11g/n : OFDM (BPSK / QPSK / 16QAM / 64QAM )<br>Bluetooth LE : GFSK<br>Bluetooth v3.0 + EDR : GFSK, $\pi/4$ -DQPSK, 8-DPSK |

#### 1.5. Modification of EUT

No modifications are made to the EUT during all test items.

## 1.6. Test Location

|                    |                                                                                                                                                            |           |                      |
|--------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------|----------------------|
| Test Site          | SPORTON INTERNATIONAL (SHENZHEN) INC.                                                                                                                      |           |                      |
| Test Site Location | No. 3 Building, the third floor of south, Shahe River west, Fengzeyuan warehouse, Nanshan District, Shenzhen, Guangdong, P.R.C.<br>TEL: +86-755- 3320-2398 |           |                      |
| Test Site No.      | Sporton Site No.                                                                                                                                           |           | FCC Registration No. |
|                    | CO01-SZ                                                                                                                                                    | 03CH01-SZ | 831040               |

## 1.7. Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC 47 CFR FCC Part 15 Subpart B
- ANSI C63.4-2003

### Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.

## 2. Test Configuration of Equipment Under Test

### 2.1. Test Mode

The EUT has been associated with peripherals pursuant to ANSI C63.4-2003 and configuration operated in a manner tended to maximize its emission characteristics in a typical application.

Frequency range investigated: conduction (150 kHz to 30 MHz), radiation (30MHz to the 5th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower).

The following tables are showing the test modes as the worst cases and recorded in this report.

| Item | EUT Configuration                                                  | Test Condition |           |           |
|------|--------------------------------------------------------------------|----------------|-----------|-----------|
|      |                                                                    | EMI AC         | EMI RE<1G | EMI RE≥1G |
| 1.   | Charging Mode (EUT with adapter)                                   | ☒              | ☒         | Note 1    |
| 2.   | Data application transferred mode<br>(EUT connected with notebook) | ☒              | ☒         | ☒         |

#### Abbreviations:

- EMI AC: AC conducted emissions
- EMI RE ≥ 1G: EUT radiated emissions ≥ 1GHz
- EMI RE < 1G: EUT radiated emissions < 1GHz


**Note 1:** Testing for this mode is not required or not the worst case.

**Remark:** For signal above 1GHz, the worst case was test item 2.

| Test Items                                                                                                                                                                                                                                                                                                                                                                      | EUT Configure Mode | Function Type                                                                                                                                                                                                                                                                                                                                                       |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| AC Conducted Emission                                                                                                                                                                                                                                                                                                                                                           | 1/2                | Mode 1: GSM850 Idle + Bluetooth Idle + WLAN Idle + Earphone + USB Cable (Charging from Adapter) + Camera + SIM1<Fig.1><br>Mode 2: GSM1900 Idle + Bluetooth Idle + WLAN Idle + Earphone + USB Cable (Charging from Adapter) + MPEG4 + SIM1<Fig.1><br>Mode 3: GSM850 Idle + Bluetooth Idle + WLAN Idle + Earphone + USB Cable (Data Link with Notebook) + SIM1<Fig.2> |
| Radiated Emissions < 1GHz                                                                                                                                                                                                                                                                                                                                                       | 1/2                | Mode 1: GSM850 Idle + Bluetooth Idle + WLAN Idle + Earphone + USB Cable (Charging from Adapter) + Camera + SIM1<Fig.1><br>Mode 2: GSM1900 Idle + Bluetooth Idle + WLAN Idle + Earphone + USB Cable (Charging from Adapter) + MPEG4 + SIM1<Fig.1><br>Mode 3: GSM850 Idle + Bluetooth Idle + WLAN Idle + Earphone + USB Cable (Data Link with Notebook) + SIM1<Fig.2> |
| Radiated Emissions ≥ 1GHz                                                                                                                                                                                                                                                                                                                                                       | 2                  | Mode 1: GSM850 Idle + Bluetooth Idle + WLAN Idle + Earphone + USB Cable (Data Link with Notebook) + SIM1<Fig.2>                                                                                                                                                                                                                                                     |
| <b>Remark:</b> <ol style="list-style-type: none"> <li>The worst case of AC is mode 2, and the USB Link mode of AC is mode 3, the test data of these modes are reported.</li> <li>The worst case of RE &lt; 1G is mode 3; only the test data of this mode was reported.</li> <li>Link with Notebook means data application transferred mode between EUT and Notebook.</li> </ol> |                    |                                                                                                                                                                                                                                                                                                                                                                     |


## 2.2. Connection Diagram of Test System

### <EUT with Adapter Mode>



<Fig.1>

### <EUT with USB Cable (Link with Notebook) Mode>



<Fig.2>

## 2.3. Support Unit used in test configuration and system

| Item | Equipment          | Trade Name | Model Name | FCC ID      | Data Cable      | Power Cord                                                |
|------|--------------------|------------|------------|-------------|-----------------|-----------------------------------------------------------|
| 1.   | System Simulator   | R&S        | CMW 500    | N/A         | N/A             | Unshielded, 1.8 m                                         |
| 2.   | Bluetooth Earphone | Nokia      | BH-108     | PYAHS-107W  | N/A             | N/A                                                       |
| 3.   | WLAN AP            | D-link     | DIR-615    | N/A         | N/A             | Unshielded, 1.8m                                          |
| 4.   | WLAN AP            | D-link     | DIR-628    | KA2DIR628A2 | N/A             | Unshielded, 1.8m                                          |
| 5.   | Base Station       | Agilent    | 8960       | N/A         | N/A             | Unshielded, 1.8 m                                         |
| 6.   | Notebook           | Lenovo     | G480       | FCC DoC     | N/A             | AC I/P:<br>Unshielded, 1.2m<br>DC O/P:<br>Shielded, 1.8 m |
| 7.   | Notebook           | Lenovo     | E540       | FCC DoC     | N/A             | AC I/P:<br>Unshielded, 1.2m<br>DC O/P:<br>Shielded, 1.8 m |
| 8.   | LCD Monitor        | DELL       | IN1940MWb  | FCC DoC     | Shielded, 1.6 m | Unshielded, 1.8 m                                         |
| 9.   | SD Card            | SanDisk    | 4G class 4 | FCC DoC     | N/A             | N/A                                                       |
| 10.  | iPod               | Apple      | MC525 ZP/A | FCC DoC     | Shielded, 1.0 m | N/A                                                       |
| 11.  | iPod nano 8GB      | Apple      | MC690 ZP/A | FCC DoC     | Shielded, 1.2 m | N/A                                                       |

## **2.4. EUT Operation Test Setup**

The EUT was in GSM idle mode during the testing. The EUT was synchronized to the BCCH, and was in continuous receiving mode by setting system simulator's paging reorganization.

At the same time, the EUT was attached to the Bluetooth earphone or WLAN AP, and the following programs installed in the EUT were programmed during the test.

1. Data application is transferred between notebook and EUT via USB cable.
2. Execute "Video player" to play MPEG4 files.
3. Turn on camera to capture images.

### 3. Test Result

#### 3.1. Test of AC Conducted Emission Measurement

##### 3.1.1 Limits of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

| Frequency of emission<br>(MHz) | Conducted limit (dBuV) |           |
|--------------------------------|------------------------|-----------|
|                                | Quasi-peak             | Average   |
| 0.15-0.5                       | 66 to 56*              | 56 to 46* |
| 0.5-5                          | 56                     | 46        |
| 5-30                           | 60                     | 50        |

\*Decreases with the logarithm of the frequency.


##### 3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

##### 3.1.3 Test Procedure

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode.

### 3.1.4 Test Setup






## 3.1.5 Test Result of AC Conducted Emission

|                 |                                                                                                         |                     |        |
|-----------------|---------------------------------------------------------------------------------------------------------|---------------------|--------|
| Test Mode :     | Mode 2                                                                                                  | Temperature :       | 21~22℃ |
| Test Engineer : | Jack Tian                                                                                               | Relative Humidity : | 41~42% |
| Test Voltage :  | 120Vac / 60Hz                                                                                           | Phase :             | Line   |
| Function Type : | GSM1900 Idle + Bluetooth Idle + WLAN Idle + Earphone + USB Cable (Charging from Adapter) + MPEG4 + SIM1 |                     |        |

Data: 3




Site : C001-SZ  
Condition: FCC 15B\_QP LISN\_L\_20140304 LINE  
Project : (FC)461607  
Mode : Mode 2

|     | Freq  | Level | Over Limit | Limit Line | Read Level | LISN Factor | Cable Loss | Remark  |
|-----|-------|-------|------------|------------|------------|-------------|------------|---------|
|     | MHz   | dBuV  | dB         | dBuV       | dBuV       | dB          | dB         |         |
| 1   | 0.19  | 28.62 | -25.36     | 53.98      | 18.10      | 0.22        | 10.30      | Average |
| 2   | 0.19  | 37.82 | -26.16     | 63.98      | 27.30      | 0.22        | 10.30      | QP      |
| 3   | 0.43  | 35.15 | -12.14     | 47.29      | 24.70      | 0.29        | 10.16      | Average |
| 4   | 0.43  | 40.45 | -16.84     | 57.29      | 30.00      | 0.29        | 10.16      | QP      |
| 5 * | 0.54  | 37.83 | -8.17      | 46.00      | 27.41      | 0.27        | 10.15      | Average |
| 6   | 0.54  | 45.03 | -10.97     | 56.00      | 34.61      | 0.27        | 10.15      | QP      |
| 7   | 0.58  | 35.80 | -10.20     | 46.00      | 25.40      | 0.25        | 10.15      | Average |
| 8   | 0.58  | 43.40 | -12.60     | 56.00      | 33.00      | 0.25        | 10.15      | QP      |
| 9   | 1.28  | 24.31 | -21.69     | 46.00      | 13.90      | 0.25        | 10.16      | Average |
| 10  | 1.28  | 35.81 | -20.19     | 56.00      | 25.40      | 0.25        | 10.16      | QP      |
| 11  | 28.75 | 26.05 | -23.95     | 50.00      | 11.20      | 4.24        | 10.61      | Average |
| 12  | 28.75 | 34.95 | -25.05     | 60.00      | 20.10      | 4.24        | 10.61      | QP      |



|                 |                                                                                                         |                     |         |
|-----------------|---------------------------------------------------------------------------------------------------------|---------------------|---------|
| Test Mode :     | Mode 2                                                                                                  | Temperature :       | 21~22℃  |
| Test Engineer : | Jack Tian                                                                                               | Relative Humidity : | 41~42%  |
| Test Voltage :  | 120Vac / 60Hz                                                                                           | Phase :             | Neutral |
| Function Type : | GSM1900 Idle + Bluetooth Idle + WLAN Idle + Earphone + USB Cable (Charging from Adapter) + MPEG4 + SIM1 |                     |         |




Site : CO01-SZ  
Condition: FCC 15B\_QP LISN\_N\_20140304 NEUTRAL  
Project : (FC)461607  
Mode : Mode 2

|     | Freq  | Level | Over   | Limit | Read  | LISN   | Cable |         |
|-----|-------|-------|--------|-------|-------|--------|-------|---------|
|     | MHz   | dBuV  | Limit  | Line  | Level | Factor | Loss  | Remark  |
|     | MHz   | dBuV  | dB     | dBuV  | dBuV  | dB     | dB    |         |
| 1   | 0.20  | 28.72 | -25.08 | 53.80 | 18.10 | 0.32   | 10.30 | Average |
| 2   | 0.20  | 40.62 | -23.18 | 63.80 | 30.00 | 0.32   | 10.30 | QP      |
| 3   | 0.25  | 24.19 | -27.59 | 51.78 | 13.61 | 0.34   | 10.24 | Average |
| 4   | 0.25  | 35.99 | -25.79 | 61.78 | 25.41 | 0.34   | 10.24 | QP      |
| 5   | 0.44  | 26.96 | -20.11 | 47.07 | 16.40 | 0.40   | 10.16 | Average |
| 6   | 0.44  | 36.86 | -20.21 | 57.07 | 26.30 | 0.40   | 10.16 | QP      |
| 7   | 0.55  | 26.52 | -19.48 | 46.00 | 16.00 | 0.37   | 10.15 | Average |
| 8 * | 0.55  | 41.92 | -14.08 | 56.00 | 31.40 | 0.37   | 10.15 | QP      |
| 9   | 0.68  | 24.21 | -21.79 | 46.00 | 13.80 | 0.26   | 10.15 | Average |
| 10  | 0.68  | 36.21 | -19.79 | 56.00 | 25.80 | 0.26   | 10.15 | QP      |
| 11  | 26.70 | 27.44 | -22.56 | 50.00 | 13.60 | 3.26   | 10.58 | Average |
| 12  | 26.70 | 39.64 | -20.36 | 60.00 | 25.80 | 3.26   | 10.58 | QP      |



|                 |                                                                                                  |                     |        |
|-----------------|--------------------------------------------------------------------------------------------------|---------------------|--------|
| Test Mode :     | Mode 3                                                                                           | Temperature :       | 21~22℃ |
| Test Engineer : | Jack Tian                                                                                        | Relative Humidity : | 41~42% |
| Test Voltage :  | 120Vac / 60Hz                                                                                    | Phase :             | Line   |
| Function Type : | GSM850 Idle + Bluetooth Idle + WLAN Idle + Earphone + USB Cable (Data Link with Notebook) + SIM1 |                     |        |




Site : C001-SZ  
Condition: FCC 15B\_QP LISN\_L 20140304 LINE  
Project : (FC)461607  
Mode : Mode 3

|     | Freq | Level | Over Limit | Limit Line | Read Level | LISN Factor | Cable Loss | Remark  |
|-----|------|-------|------------|------------|------------|-------------|------------|---------|
|     | MHz  | dBuV  | dB         | dBuV       | dBuV       | dB          | dB         |         |
| 1   | 0.17 | 24.65 | -30.43     | 55.08      | 14.10      | 0.22        | 10.33      | Average |
| 2   | 0.17 | 38.85 | -26.23     | 65.08      | 28.30      | 0.22        | 10.33      | QP      |
| 3   | 0.18 | 20.73 | -33.60     | 54.33      | 10.20      | 0.22        | 10.31      | Average |
| 4   | 0.18 | 36.33 | -28.00     | 64.33      | 25.80      | 0.22        | 10.31      | QP      |
| 5   | 0.25 | 18.78 | -33.00     | 51.78      | 8.30       | 0.24        | 10.24      | Average |
| 6   | 0.25 | 31.78 | -30.00     | 61.78      | 21.30      | 0.24        | 10.24      | QP      |
| 7   | 4.65 | 21.64 | -24.36     | 46.00      | 11.00      | 0.40        | 10.24      | Average |
| 8   | 4.65 | 32.84 | -23.16     | 56.00      | 22.20      | 0.40        | 10.24      | QP      |
| 9 * | 6.42 | 32.26 | -17.74     | 50.00      | 21.60      | 0.39        | 10.27      | Average |
| 10  | 6.42 | 40.76 | -19.24     | 60.00      | 30.10      | 0.39        | 10.27      | QP      |
| 11  | 9.50 | 25.62 | -24.38     | 50.00      | 14.70      | 0.61        | 10.31      | Average |
| 12  | 9.50 | 36.82 | -23.18     | 60.00      | 25.90      | 0.61        | 10.31      | QP      |



|                 |                                                                                                  |                     |         |
|-----------------|--------------------------------------------------------------------------------------------------|---------------------|---------|
| Test Mode :     | Mode 3                                                                                           | Temperature :       | 21~22℃  |
| Test Engineer : | Jack Tian                                                                                        | Relative Humidity : | 41~42%  |
| Test Voltage :  | 120Vac / 60Hz                                                                                    | Phase :             | Neutral |
| Function Type : | GSM850 Idle + Bluetooth Idle + WLAN Idle + Earphone + USB Cable (Data Link with Notebook) + SIM1 |                     |         |



Site : CO01-SZ  
Condition: FCC 15B\_QP LISN\_N\_20140304 NEUTRAL  
Project : (FC)461607  
Mode : Mode 3

|     | Freq | Level | Over Limit | Limit Line | Read Level | LISN Factor | Cable Loss | Remark  |
|-----|------|-------|------------|------------|------------|-------------|------------|---------|
|     | MHz  | dBuV  | dB         | dBuV       | dBuV       | dB          | dB         |         |
| 1   | 0.17 | 20.36 | -34.63     | 54.99      | 9.70       | 0.33        | 10.33      | Average |
| 2   | 0.17 | 38.46 | -26.53     | 64.99      | 27.80      | 0.33        | 10.33      | QP      |
| 3   | 0.20 | 21.42 | -32.25     | 53.67      | 10.80      | 0.32        | 10.30      | Average |
| 4   | 0.20 | 34.92 | -28.75     | 63.67      | 24.30      | 0.32        | 10.30      | QP      |
| 5   | 0.25 | 15.79 | -36.07     | 51.86      | 5.20       | 0.34        | 10.25      | Average |
| 6   | 0.25 | 30.99 | -30.87     | 61.86      | 20.40      | 0.34        | 10.25      | QP      |
| 7   | 4.87 | 23.13 | -22.87     | 46.00      | 12.40      | 0.49        | 10.24      | Average |
| 8   | 4.87 | 34.93 | -21.07     | 56.00      | 24.20      | 0.49        | 10.24      | QP      |
| 9 * | 6.49 | 30.62 | -19.38     | 50.00      | 19.90      | 0.45        | 10.27      | Average |
| 10  | 6.49 | 40.32 | -19.68     | 60.00      | 29.60      | 0.45        | 10.27      | QP      |
| 11  | 9.65 | 24.00 | -26.00     | 50.00      | 12.99      | 0.69        | 10.32      | Average |
| 12  | 9.65 | 33.40 | -26.60     | 60.00      | 22.39      | 0.69        | 10.32      | QP      |

## 3.2. Test of Radiated Emission Measurement

### 3.2.1. Limit of Radiated Emission

The emissions from an unintentional radiator shall not exceed the field strength levels specified in the following table:

| Frequency<br>(MHz) | Field Strength<br>(microvolts/meter) | Measurement Distance<br>(meters) |
|--------------------|--------------------------------------|----------------------------------|
| 30 – 88            | 100                                  | 3                                |
| 88 – 216           | 150                                  | 3                                |
| 216 - 960          | 200                                  | 3                                |
| Above 960          | 500                                  | 3                                |

### 3.2.2. Measuring Instruments


The measuring equipment is listed in the section 4 of this test report.

### 3.2.3. Test Procedures


1. The EUT was placed on a turntable with 0.8 meter above ground.
2. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest radiation.
4. The antenna is a Bi-Log antenna and its height is adjusted between one to four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
5. For each suspected emission, the EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.
6. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode.
7. If the emission level of the EUT in peak mode was 3 dB lower than the limit specified, peak values of EUT will be reported. Otherwise, the emission will be repeated by using the quasi-peak method and reported.
8. Emission level (dB $\mu$ V/m) = 20 log Emission level ( $\mu$ V/m)
9. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level

### 3.2.4. Test Setup of Radiated Emission

For radiated emissions from 30MHz to 1GHz




For radiated emissions above 1GHz





## 3.2.5. Test Result of Radiated Emission

|                 |                                                                                                   |                     |            |
|-----------------|---------------------------------------------------------------------------------------------------|---------------------|------------|
| Test Mode :     | Mode 3                                                                                            | Temperature :       | 23~25°C    |
| Test Engineer : | Rock Tang                                                                                         | Relative Humidity : | 48~52%     |
| Test Distance : | 3m                                                                                                | Polarization :      | Horizontal |
| Function Type : | GSM 850 Idle + Bluetooth Idle + WLAN Idle + Earphone + USB Cable (Data Link with Notebook) + SIM1 |                     |            |
| Remark :        | #7 is system simulator signal which can be ignored.                                               |                     |            |




Site : 03CH01-SZ  
Condition : FCC CLASS-B 3m LF\_ANT\_131026 HORIZONTAL  
Project : (FC) 461607  
Mode : Mode 3

|     | Freq     | Level  | Over Limit | Limit Line | ReadAntenna Level | Cable Factor | Preamp Loss | A/Pos | T/Pos | Remark |
|-----|----------|--------|------------|------------|-------------------|--------------|-------------|-------|-------|--------|
|     | MHz      | dBuV/m | dB         | dBuV/m     | dBuV              | dB/m         | dB          | dB    | cm    | deg    |
| 1   | 157.44   | 25.67  | -17.83     | 43.50      | 44.94             | 9.14         | 1.53        | 29.94 | ---   | ---    |
| 2 P | 199.56   | 38.71  | -4.79      | 43.50      | 57.85             | 9.10         | 1.70        | 29.94 | 100   | 203    |
| 3   | 268.14   | 32.37  | -13.63     | 46.00      | 48.24             | 12.15        | 1.91        | 29.93 | ---   | ---    |
| 4   | 328.70   | 29.96  | -16.04     | 46.00      | 43.66             | 14.13        | 2.10        | 29.93 | ---   | ---    |
| 5   | 399.40   | 31.22  | -14.78     | 46.00      | 42.96             | 15.90        | 2.29        | 29.93 | ---   | ---    |
| 6   | 722.10   | 30.83  | -15.17     | 46.00      | 38.46             | 19.30        | 3.00        | 29.93 | ---   | ---    |
| 7   | 880.30   | 26.48  |            |            | 32.56             | 20.58        | 3.28        | 29.94 | ---   | ---    |
| 8   | 2368.00  | 30.59  | -43.41     | 74.00      | 50.16             | 31.81        | 5.59        | 56.97 | ---   | ---    |
| 9   | 4864.00  | 30.55  | -43.45     | 74.00      | 45.69             | 33.90        | 8.41        | 57.45 | ---   | ---    |
| 10  | 6276.00  | 32.65  | -41.35     | 74.00      | 45.81             | 34.00        | 9.57        | 56.73 | ---   | ---    |
| 11  | 7438.00  | 34.79  | -39.21     | 74.00      | 47.83             | 33.97        | 10.03       | 57.04 | ---   | ---    |
| 12  | 9920.00  | 36.00  | -38.00     | 74.00      | 44.69             | 36.90        | 12.54       | 58.13 | ---   | ---    |
| 13  | 12798.00 | 37.39  | -36.61     | 74.00      | 42.75             | 38.44        | 14.30       | 58.10 | 100   | 203    |



|                 |                                                                                                   |                     |          |
|-----------------|---------------------------------------------------------------------------------------------------|---------------------|----------|
| Test Mode :     | Mode 3                                                                                            | Temperature :       | 23~25°C  |
| Test Engineer : | Rock Tang                                                                                         | Relative Humidity : | 48~52%   |
| Test Distance : | 3m                                                                                                | Polarization :      | Vertical |
| Function Type : | GSM 850 Idle + Bluetooth Idle + WLAN Idle + Earphone + USB Cable (Data Link with Notebook) + SIM1 |                     |          |
| Remark :        | #7 is system simulator signal which can be ignored.                                               |                     |          |



Site : 03CH01-SZ  
Condition : FCC CLASS-B 3m LF\_ANT\_131026 VERTICAL  
Project : (FC) 461607  
Mode : Mode 3  
IMEI : 351771053480910

|     | Freq     | Level  | Over Limit | Limit Line | ReadAntenna Level | Factor | Cable Loss | Preamp Factor | A/Pos | T/Pos | Remark |
|-----|----------|--------|------------|------------|-------------------|--------|------------|---------------|-------|-------|--------|
|     | MHz      | dBuV/m | dB         | dBuV/m     | dBuV              | dB/m   | dB         | dB            | cm    | deg   |        |
| 1   | 42.15    | 24.32  | -15.68     | 40.00      | 42.03             | 11.35  | 0.87       | 29.93         | ---   | ---   | Peak   |
| 2   | 166.62   | 22.87  | -20.63     | 43.50      | 42.63             | 8.62   | 1.56       | 29.94         | ---   | ---   | Peak   |
| 3 P | 192.00   | 35.38  | -8.12      | 43.50      | 54.88             | 8.78   | 1.66       | 29.94         | 100   | 205   | Peak   |
| 4   | 328.00   | 28.36  | -17.64     | 46.00      | 42.14             | 14.06  | 2.09       | 29.93         | ---   | ---   | Peak   |
| 5   | 498.10   | 29.06  | -16.94     | 46.00      | 39.42             | 17.04  | 2.52       | 29.92         | ---   | ---   | Peak   |
| 6   | 722.10   | 28.57  | -17.43     | 46.00      | 36.20             | 19.30  | 3.00       | 29.93         | ---   | ---   | Peak   |
| 7   | 880.30   | 31.91  |            |            | 37.99             | 20.58  | 3.28       | 29.94         | ---   | ---   | Peak   |
| 8   | 1952.00  | 32.97  | -41.03     | 74.00      | 55.14             | 29.72  | 5.06       | 56.95         | ---   | ---   | Peak   |
| 9   | 4590.00  | 31.11  | -42.89     | 74.00      | 47.66             | 33.29  | 8.12       | 57.96         | ---   | ---   | Peak   |
| 10  | 6716.00  | 33.29  | -40.71     | 74.00      | 46.73             | 33.88  | 9.86       | 57.18         | ---   | ---   | Peak   |
| 11  | 7708.00  | 33.76  | -40.24     | 74.00      | 45.83             | 34.39  | 10.32      | 56.78         | ---   | ---   | Peak   |
| 12  | 9936.00  | 36.01  | -37.99     | 74.00      | 44.66             | 36.93  | 12.54      | 58.12         | ---   | ---   | Peak   |
| 13  | 12752.00 | 37.37  | -36.63     | 74.00      | 42.85             | 38.35  | 14.28      | 58.11         | 100   | 207   | Peak   |



## 4. List of Measuring Equipment

| Instrument                        | Manufacturer         | Model No. | Serial No.   | Characteristics | Calibration Date | Test Date     | Due Date      | Remark                |
|-----------------------------------|----------------------|-----------|--------------|-----------------|------------------|---------------|---------------|-----------------------|
| ESCIO TEST Receiver               | R&S                  | ESCI      | 100724       | 9kHz~3GHz       | Feb. 21, 2014    | Jul. 07, 2014 | Feb. 20, 2015 | Radiation (03CH01-SZ) |
| Spectrum Analyzer                 | Agilent Technologies | N9038A    | MY52260185   | 20Hz~26.5GHz    | May 26, 2014     | Jul. 07, 2014 | May 25, 2015  | Radiation (03CH01-SZ) |
| Bilog Antenna                     | TESEQ                | CBL 6112D | 23188        | 30MHz~2GHz      | Oct. 26, 2013    | Jul. 07, 2014 | Oct. 25, 2014 | Radiation (03CH01-SZ) |
| Double Ridge Horn Antenna         | ETS Lindgren         | 3117      | 00119436     | 1GHz~18GHz      | Oct. 26, 2013    | Jul. 07, 2014 | Oct. 25, 2014 | Radiation (03CH01-SZ) |
| Amplifier                         | ADVANTEST            | BB525C    | E9007003     | 9kHz~3000MHz    | Feb. 21, 2014    | Jul. 07, 2014 | Feb. 20, 2015 | Radiation (03CH01-SZ) |
| Amplifier                         | Yiai                 | AV3860B   | 04030        | 2GHz~26.5GHz    | May 08, 2014     | Jul. 07, 2014 | May 07, 2015  | Radiation (03CH01-SZ) |
| AC Source(AVR)                    | Chroma               | 61601     | 616010001985 | 100Vac~250Vac   | Mar. 25, 2014    | Jul. 07, 2014 | Mar. 24, 2015 | Radiation (03CH01-SZ) |
| Turn Table                        | EM Electronics       | EM 1000   | N/A          | 0~360 degree    | NCR              | Jul. 07, 2014 | NCR           | Radiation (03CH01-SZ) |
| Antenna Mast                      | EM Electronics       | EM 1000   | N/A          | 1 m~4 m         | NCR              | Jul. 07, 2014 | NCR           | Radiation (03CH01-SZ) |
| ESCIO TEST Receiver               | R&S                  | ESCI      | 100724       | 9kHz~3GHz       | Feb. 21, 2014    | Jun. 24, 2014 | Feb. 20, 2015 | Conduction (CO01-SZ)  |
| AC LISN                           | EMCO                 | 3816/2SH  | 00103912     | 9kHz~30MHz      | Mar. 04, 2014    | Jun. 24, 2014 | Mar. 03, 2015 | Conduction (CO01-SZ)  |
| AC LISN (for auxiliary equipment) | EMCO                 | 3816/2SH  | 00103892     | 9kHz~30MHz      | Mar. 04, 2014    | Jun. 24, 2014 | Mar. 03, 2015 | Conduction (CO01-SZ)  |
| AC Power Source                   | Chroma               | 61602     | 616020000891 | 100Vac~250Vac   | Dec. 17, 2013    | Jun. 24, 2014 | Dec. 16, 2014 | Conduction (CO01-SZ)  |

## 5. Uncertainty of Evaluation

### Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

|                                                                          |     |
|--------------------------------------------------------------------------|-----|
| Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2U_c(y)$ ) | 2.3 |
|--------------------------------------------------------------------------|-----|

### Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

|                                                                          |     |
|--------------------------------------------------------------------------|-----|
| Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2U_c(y)$ ) | 3.9 |
|--------------------------------------------------------------------------|-----|