

FCC RF Test Report

APPLICANT : CT Asia
EQUIPMENT : GSM mobile phone
BRAND NAME : BLU
MODEL NAME : Deco Pro
FCC ID : YHLBLUDECOPRO
STANDARD : FCC Part 15 Subpart C §15.247
CLASSIFICATION : Digital Spread Spectrum (DSS)

The product was received on Dec. 23, 2011 and completely tested on Feb. 16, 2012. We, SPORTON INTERNATIONAL (KUNSHAN) INC., would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.4-2003 and shown the compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL (KUNSHAN) INC., the test report shall not be reproduced except in full.

Reviewed by:



Jones Tsai / Manager



SPORTON INTERNATIONAL (KUNSHAN) INC.
No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P.R.C.

TABLE OF CONTENTS

REVISION HISTORY.....	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION.....	5
1.1 Applicant.....	5
1.2 Manufacturer.....	5
1.3 Feature of Equipment Under Test.....	6
1.4 Testing Site.....	7
1.5 Applied Standards	7
1.6 Ancillary Equipment List	8
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST.....	9
2.1 RF Output Power.....	9
2.2 Test Mode.....	10
2.3 Connection Diagram of Test System.....	11
2.4 RF Utility	11
3 TEST RESULT	12
3.1 Number of Channel Measurement	12
3.2 20dB Bandwidth Measurement	14
3.3 Hopping Channel Separation Measurement	21
3.4 Dwell Time Measurement.....	28
3.5 Peak Output Power Measurement	30
3.6 Band Edges Measurement.....	33
3.7 Spurious Emission Measurement.....	44
3.8 AC Conducted Emission Measurement.....	48
3.9 Radiated Emission Measurement.....	52
3.10 Antenna Requirements.....	61
4 LIST OF MEASURING EQUIPMENT.....	62
5 UNCERTAINTY OF EVALUATION.....	63
APPENDIX A. PHOTOGRAPHS OF EUT	
APPENDIX B. SETUP PHOTOGRAPHS	



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR1D2304A	Rev. 01	Initial issue of report	Feb. 16, 2012

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(1)	Number of Channels	$\geq 15\text{Chs}$	Pass	-
3.2	15.247(a)(1)	20dB Bandwidth	NA	Pass	-
3.3	15.247(a)(1)	Channel Separation	$\geq 2/3$ of 20dB BW	Pass	-
3.4	15.247(a)(1)	Dwell Time of Each Channel	$\leq 0.4\text{sec}$ in 31.6sec period	Pass	-
3.5	15.247(b)(1)	Peak Output Power	$\leq 125\text{ mW}$	Pass	-
3.6	15.247(d)	Frequency Band Edges	$\leq 20\text{dBc}$	Pass	-
3.7	15.247(d)	Spurious Emission	$< 20\text{ dBc}$	Pass	-
3.8	15.207	AC Conducted Emission	15.207(a)	Pass	Under limit 8.97 dB at 2.85 MHz
3.9	15.247(d)	Transmitter Radiated Emission	15.209(a) & 15.247(d)	Pass	Under limit 3.46 dB at 207.12 MHz
3.10	15.203 & 15.247(b)	Antenna Requirement	N/A	Pass	-



1 General Description

1.1 Applicant

CT Asia

RMA2011, 20/F, GOLDEN CENTRAL TOWER, NO.3037# JINTIAN ROAD, FUTIAN DISTRICT

1.2 Manufacturer

zechin communication co., Ltd

Unit804, 8th Floor Desay Tech Building Gaoxin Road South, Nanshan District Shenzhen, China

1.3 Feature of Equipment Under Test

Product Feature & Specification	
Equipment	GSM mobile phone
Brand Name	BLU
Model Name	Deco Pro
FCC ID	YHLBLUDECOPRO
Tx/Rx Frequency Range	2402 MHz ~ 2480 MHz
Number of Channels	79
Carrier Frequency of Each Channel	2402+n*1 MHz; n=0~78
Channel Spacing	1 MHz
Maximum Output Power to Antenna	Bluetooth (1Mbps) : 9.78 dBm (0.00950 W) Bluetooth EDR (2Mbps) : 9.42 dBm (0.00874 W) Bluetooth EDR (3Mbps) : 9.59 dBm (0.00909 W)
Antenna Type	Dipole Antenna with gain -1 dBi
HW Version	E720-MB-V1.0
SW Version	E720_HX_LCH_BT_FM_FL_GS_TV_WF_DC_003_V011
Type of Modulation	Bluetooth (1Mbps) : GFSK Bluetooth EDR (2Mbps) : $\pi/4$ -DQPSK Bluetooth EDR (3Mbps) : 8-DPSK
EUT Stage	Identical Prototype

Remark:

1. For other wireless features of this EUT, test report will be issued separately.
2. This test report recorded only product characteristics and test results of Digital Spread Spectrum (DSS).
3. The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.
4. There are two different types of EUT. They are single SIM card mobile and dual SIM card mobile. The others are the same including circuit design, PCB board, structure and all components. It is special to declare. After pre-scan two types of EUT, we found test result of the sample that dual SIM was the worst, so we choose dual SIM card mobile to perform all test.

1.4 Testing Site

Test Site	SPORTON INTERNATIONAL (KUNSHAN) INC.	
Test Site Location	No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P.R.C. TEL: +86-0512-5790-0158 FAX: +86-0512-5790-0958	
Test Site No.	Sporton Site No.	
	TH01-KS	03CH01-KS

Test Site	SPORTON INTERNATIONAL (SHENZHEN) INC.	
Test Site Location	No. 101, Complex Building C, Guanglong Village, Xili Town, Nanshan District, Shenzhen, Guangdong, P.R.C. TEL: +86-755-8637-9589 FAX: +86-755-8637-9595	
Test Site No.	Sporton Site No. :	
	CO01-SZ	

1.5 Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart C §15.247
- ♦ FCC Public Notice DA 00-705
- ♦ ANSI C63.4-2003

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B (Certification), recorded in a separate test report.

1.6 Ancillary Equipment List

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	Agilent	8960	N/A	N/A	Unshielded, 1.8 m
2.	Bluetooth Base Station	R&S	CBT	FCC DoC	N/A	Unshielded, 1.8 m
3.	DC Power Supply	GW	GPS-3030D	N/A	N/A	Unshielded, 1.8 m
4.	Bluetooth Earphone	Nokia	BH-108	N/A	N/A	N/A
5.	Notebook	IBM	1706	FCC DoC	N/A	AC I/P: Unshielded, 1.8 m DC O/P: Shielded, 1.8 m
6.	Router	D-Link	DIR-615	N/A	N/A	Unshielded, 1.8 m

2 Test Configuration of Equipment Under Test

2.1 RF Output Power

Preliminary tests were performed in different data rate and recorded the RF output power in the following table:

Channel	Frequency	Bluetooth RF Output Power					
		Data Rate / Modulation					
		GFSK		π /4-DQPSK		8-DPSK	
		1Mbps		2Mbps		3Mbps	
Ch00	2402MHz	8.44	dBm	8.11	dBm	8.28	dBm
Ch39	2441MHz	9.35	dBm	9.05	dBm	9.20	dBm
Ch78	2480MHz	9.78	dBm	9.42	dBm	9.59	dBm

Remark:

1. The data rate was set in 1Mbps for all the test items due to the highest RF output power.
2. The EUT is programmed to transmit signals continuously for all testing.

2.2 Test Mode

The EUT has been associated with peripherals pursuant to ANSI C63.4-2003 and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction (150 kHz to 30 MHz), radiation (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower).


Pre-scanned tests were conducted to determine the final configuration from all possible combinations. The following tables are showing the test modes as the worst cases (H plane) and recorded in this report.

The following tables are showing the test modes as the worst cases and recorded in this report.


Test Cases			
Test Item	Data Rate / Modulation		
	Bluetooth 1Mbps GFSK	Bluetooth EDR 2Mbps $\pi/4$ -DQPSK	Bluetooth EDR 3Mbps 8-DPSK
Conducted TCs	Mode 1: CH00_2402 MHz Mode 2: CH39_2441 MHz Mode 3: CH78_2480 MHz	Mode 4: CH00_2402 MHz Mode 5: CH39_2441 MHz Mode 6: CH78_2480 MHz	Mode 7: CH00_2402 MHz Mode 8: CH39_2441 MHz Mode 9: CH78_2480 MHz
Radiated TCs	Mode 1: CH00_2402 MHz Mode 2: CH39_2441 MHz Mode 3: CH78_2480 MHz	N/A	N/A
AC Conducted Emission	Mode 1 :GSM 850 Idle + Bluetooth Link + WLAN Link + Adapter + Earphone + Camera		
Remark: For radiated TCs, the data rate was set in 1Mbps due to the highest RF output power; only the data of these modes was reported.			

2.3 Connection Diagram of Test System

<Bluetooth Tx Mode>



<AC Conducted Emission Mode>



2.4 RF Utility

For Bluetooth function, the RF utility, “*#336633#” was installed in EUT which was programmed in order to make the EUT into the engineering modes to contact with Bluetooth base station for transmitting and receiving signals continuously.

3 Test Result

3.1 Number of Channel Measurement

3.1.1 Limits of Number of Hopping Frequency

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.


3.1.2 Measuring Instruments

See list of measuring instruments of this test report.

3.1.3 Test Procedure


1. The testing follows FCC Public Notice DA 00-705 Measurement Guidelines.
2. The RF output of EUT was connected to the spectrum analyzer by a low loss cable.
3. The modulation types of EUT are irrelevant to number of hopping channels deviation.
4. The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:
Span = the frequency band of operation; $RBW \geq 1\%$ of the span; $VBW \geq RBW$; Sweep = auto;
Detector function = peak; Trace = max hold.
5. The number of hopping frequency used is defined as the device has the numbers of total channel.

3.1.4 Test Setup




3.1.5 Test Result of Number of Hopping Frequency

Test Mode :	Mode 1~3	Temperature :	24~25°C
Test Engineer :	Zhi Lu	Relative Humidity :	48~49%
Number of Hopping Channels (Channel)		Limits (Channel)	Pass/Fail
79		> 15	Pass

Number of Hopping Channel Plot on Channel 00 - 78


Date: 27.DEC.2011 00:10:10



Date: 27.DEC.2011 00:13:46

3.2 20dB Bandwidth Measurement

3.2.1 Limit of 20dB Bandwidth

N/A


3.2.2 Measuring Instruments

See list of measuring instruments of this test report.

3.2.3 Test Procedures

1. The testing follows FCC Public Notice DA 00-705 Measurement Guidelines.
2. The RF output of EUT was connected to the spectrum analyzer by a low loss cable.
3. The EUT should be transmitting at its maximum data rate as the worst cases.
4. Use the following spectrum analyzer settings:
Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hopping channel;
RBW $\geq$ 1% of the 20 dB bandwidth; VBW $\geq$ RBW; Sweep = auto; Detector function = peak;
Trace = max hold.
5. The marker-delta reading at this point is the 20 dB bandwidth of the emission.

3.2.4 Test Setup




3.2.5 Test Result of 20dB Bandwidth

Test Mode :	Mode 1, 2, 3	Temperature :	24~25℃
Test Engineer :	Zhi Lu	Relative Humidity :	48~49%

Channel	Frequency (MHz)	20dB Bandwidth (MHz)
00	2402	0.940
39	2441	0.940
78	2480	0.856


20 dB Bandwidth Plot on Channel 00



Date: 26.DEC.2011 23:45:56




20 dB Bandwidth Plot on Channel 39



Date: 26.DEC.2011 23:46:24


20 dB Bandwidth Plot on Channel 78



Date: 26.DEC.2011 23:46:49




Channel	Frequency (MHz)	20dB Bandwidth (MHz)
00	2402	1.284
39	2441	1.278
78	2480	1.272



Date: 26.DEC.2011 23:47:34




20 dB Bandwidth Plot on Channel 39



Date: 26.DEC.2011 23:48:05


20 dB Bandwidth Plot on Channel 78




Date: 26.DEC.2011 23:48:20

Test Mode :	Mode 7, 8, 9	Temperature :	24~25℃
Test Engineer :	Zhi Lu	Relative Humidity :	48~49%


Channel	Frequency (MHz)	20dB Bandwidth (MHz)
00	2402	1.290
39	2441	1.296
78	2480	1.266

20 dB Bandwidth Plot on Channel 00


Date: 26.DEC.2011 23:49:00

20 dB Bandwidth Plot on Channel 39


Date: 26.DEC.2011 23:49:23

20 dB Bandwidth Plot on Channel 78


Date: 26.DEC.2011 23:49:44

3.3 Hopping Channel Separation Measurement

3.3.1 Limit of Hopping Channel Separation

Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.


3.3.2 Measuring Instruments

See list of measuring instruments of this test report.

3.3.3 Test Procedures

1. Please refer FCC Public Notice DA 00-705 Measurement Guidelines.
2. The RF output of EUT was connected to the spectrum analyzer by a low loss cable.
3. The EUT should be transmitting at its maximum data rate as the worst cases.
4. Use the following spectrum analyzer settings:
Span = wide enough to capture the peaks of two adjacent channels; $RBW \geq 1\%$ of the span;
VBW $\geq$ RBW; Sweep = auto; Detector function = peak; Trace = max hold.
5. Use the marker-delta function to determine the separation between the peaks of the adjacent channels.

3.3.4 Test Setup




3.3.5 Test Result of Hopping Channel Separation


Test Mode :	Mode 1, 2, 3	Temperature :	24~25℃
Test Engineer :	Zhi Lu	Relative Humidity :	48~49%

Channel	Frequency (MHz)	Frequency Separation (MHz)	(2/3 of 20dB BW) Limits (MHz)	Pass/Fail
00	2402	1.002	0.627	Pass
39	2441	1.002	0.627	Pass
78	2480	1.008	0.571	Pass


Channel Separation Plot on Channel 00 - 01



Date: 26.DEC.2011 23:33:04

Channel Separation Plot on Channel 39 - 40


Date: 26.DEC.2011 23:33:45

Channel Separation Plot on Channel 77 - 78



Date: 26.DEC.2011 23:34:25




Test Mode :	Mode 4, 5, 6	Temperature :	24~25°C
Test Engineer :	Zhi Lu	Relative Humidity :	48~49%

Channel	Frequency (MHz)	Frequency Separation (MHz)	(2/3 of 20dB BW) Limits (MHz)	Pass/Fail
00	2402	1.002	0.856	Pass
39	2441	1.002	0.852	Pass
78	2480	1.002	0.848	Pass


Channel Separation Plot on Channel 00 - 01



Date: 26.DEC.2011 23:36:31

Channel Separation Plot on Channel 39 - 40



Date: 26.DEC.2011 23:37:24

Channel Separation Plot on Channel 77 - 78



Date: 26.DEC.2011 23:38:03

Test Mode :	Mode 7, 8, 9	Temperature :	24~25°C
Test Engineer :	Zhi Lu	Relative Humidity :	48~49%


Channel	Frequency (MHz)	Frequency Separation (MHz)	(2/3 of 20dB BW) Limits (MHz)	Pass/Fail
00	2402	1.002	0.860	Pass
39	2441	1.002	0.864	Pass
78	2480	1.002	0.844	Pass

Channel Separation Plot on Channel 00 - 01


Date: 26.DEC.2011 23:40:41

Channel Separation Plot on Channel 39 - 40


Date: 26.DEC.2011 23:41:19

Channel Separation Plot on Channel 77 - 78


Date: 26.DEC.2011 23:41:59

3.4 Dwell Time Measurement

3.4.1 Limit of Dwell Time

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.


3.4.2 Measuring Instruments

See list of measuring instruments of this test report.

3.4.3 Test Procedures

1. The testing follows FCC Public Notice DA 00-705 Measurement Guidelines.
2. The RF output of EUT was connected to the spectrum analyzer by a low loss cable.
3. The EUT should be transmitting at its maximum data rate as the worst cases.
4. The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:
Span = zero span, centered on a hopping channel; RBW = 1 MHz; VBW $\geq$ RBW; Sweep = as necessary to capture the entire dwell time per hopping channel; Detector function = peak; Trace = max hold.
5. Use the marker-delta function to calculate the dwell time.

3.4.4 Test Setup




3.4.5 Test Result of Dwell Time

Test Mode :	Mode 2	Temperature :	24~25℃
Test Engineer :	Zhi Lu	Relative Humidity :	48~49%


Package Mode	Average Hopping Channel	Package Transfer Time (usec)	Dwell Time (sec)	Limits (sec)	Pass/Fail
DH5	3.50	2946.00	0.33	0.4	Pass

Remark:

1. Dwell Time=79(channels) x 0.4(s) x average hopping channel x package transfer time
2. 79 channels come from the Hopping Channel number.
3. Average Hopping Channel = hops/sweep time
4. t: Package Transfer Time(us)

DH5 Dwell Time (One Pulse) Plot on Channel 39


Date: 26.DEC.2011 23:28:58

DH5 Dwell Time (Count Pulses) Plot on Channel 39


Date: 26.DEC.2011 23:42:45

3.5 Peak Output Power Measurement

3.5.1 Limit of Peak Output Power

Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW (20.97dBm).


3.5.2 Measuring Instruments

See list of measuring instruments of this test report.

3.5.3 Test Procedures

1. The testing follows FCC Public Notice DA 00-705 Measurement Guidelines.
2. The RF output of EUT was connected to the spectrum analyzer by a low loss cable.

3.5.4 Test Setup




3.5.5 Test Result of Peak Output Power

Test Mode :	Mode 1, 2, 3	Temperature :	24~25℃	
Test Engineer :	Zhi Lu	Relative Humidity :	48~49%	


Channel	Frequency (MHz)	RF Power (dBm)		
		GFSK	Max. Limits (dBm)	Pass/Fail
		1 Mbps		
00	2402	8.44	20.97	Pass
39	2441	9.35	20.97	Pass
78	2480	9.78	20.97	Pass

Peak Output Power Plot on Channel 00




Date: 26.DEC.2011 23:20:19

Peak Output Power Plot on Channel 39



Date: 26.DEC.2011 23:21:36

Peak Output Power Plot on Channel 78



Date: 26.DEC.2011 23:22:57

3.6 Band Edges Measurement

3.6.1 Limit of Band Edges

In any 100 kHz bandwidth outside the intentional radiation frequency band, the radio frequency power shall be at least 20 dB below the highest level of the radiated power. In addition, radiated emissions which fall in the restricted bands must also comply with the radiated emission limits.

3.6.2 Measuring Instruments


See list of measuring instruments of this test report.

3.6.3 Test Procedures


1. The testing follows the guidelines in ANSI C63.4-2003 and FCC Public Notice DA 00-705 Measurement Guidelines.
2. RF antenna conducted test: Set RBW = 300kHz, Video bandwidth (VBW) $\geq$ RBW. Band edge emissions must be at least 20 dB down from the highest emission level within the authorized band as measured with a 300k Hz RBW. Note: If the device complies with the use of power option 2 the attenuation under this paragraph shall be 30 dB instead of 20 dB.
3. Radiated emission test: Applies to band edge emissions that fall in the restricted bands listed in FCC Section 15.205. The maximum permitted average field strength is listed in FCC Section 15.209. A pre-amp is necessary for this measurement. For measurements above 1 GHz, set RBW = 1MHz, VBW = 1MHz, Sweep: Auto for Peak; set RBW = 1MHz, VBW = 10 Hz, Sweep: Auto for Average. If the emission is pulsed, modify the unit for continuous operation; use the settings shown above, then correct the reading by subtracting the peak-average correction factor, derived from the appropriate duty cycle calculation. See FCC Section 15.35(b) and (c).
4. In case the emission is fail due to the used RBW / VBW is too wide, marker-delta method of FCC Public Notice DA 00-705 will be followed.

3.6.4 Test Setup

<Radiated Band Edges>



<Conducted Band Edges>



3.6.5 Test Result of Radiated Band Edges

Test Mode :	Mode 1	Temperature :	23~24°C
Test Channel :	00	Relative Humidity :	50~51%
		Test Engineer :	Cloud Peng

ANTENNA POLARITY : HORIZONTAL										
Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2390	48.75	-25.25	74	46.47	32.86	3.47	34.05	100	0	Peak
2390	36.18	-17.82	54	33.9	32.86	3.47	34.05	100	0	Average

ANTENNA POLARITY : VERTICAL										
Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2390	48.9	-25.1	74	46.62	32.86	3.47	34.05	100	0	Peak
2390	36.38	-17.62	54	34.1	32.86	3.47	34.05	100	0	Average

Test Mode :	Mode 3	Temperature :	23~24°C
Test Channel :	78	Relative Humidity :	50~51%
		Test Engineer :	Cloud Peng

ANTENNA POLARITY : HORIZONTAL										
Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2483.5	34.96	-19.04	54	32.47	33.01	3.68	34.2	100	360	Average
2483.5	44.9	-29.1	74	42.41	33.01	3.68	34.2	100	360	Peak

Summary results of marker-delta method:

Test mode	Maximum field strength of the fundamental emission (dBμV/m)	Delta Result (dB)	Average Result (dBμV/m)	Average Limit (dBμV/m)	Margin (dB)	Result
Single Carrier Mode	63.99	31.23	32.76	54	-21.24	Pass
Hopping Mode	63.99	29.03	34.96	54	-19.04	Pass

Note : Average result = Maximum field strength – Delta result


ANTENNA POLARITY : VERTICAL										
Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2483.5	35.94	-18.06	54	33.45	33.01	3.68	34.2	200	120	Average
2483.5	44.59	-29.41	74	42.1	33.01	3.68	34.2	200	120	Peak

Summary results of marker-delta method:

Test mode	Maximum field strength of the fundamental emission (dBμV/m)	Delta Result (dB)	Average Result (dBμV/m)	Average Limit (dBμV/m)	Margin (dB)	Result
Single Carrier Mode	65.64	29.7	35.94	54	-18.06	Pass
Hopping Mode	65.64	30.48	35.16	54	-18.84	Pass

Note : Average result = Maximum field strength – Delta result.

Test Mode :	Mode 3	Temperature :	23~24°C
Test Channel :	78	Relative Humidity :	50~51%
Test Engineer :	Cloud Peng	Polarization :	Horizontal




Site : 03CH01-KS
 Condition: FCC PART 15C 3m HF ANT-100803 HORIZONTAL
 Project : (FR) 1D2304
 Mode : mode 3
 Plane : H

	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	Ant	Table	
	MHz	dBuV/m	dB	dBuV/m	Level	Loss	Factor	Pos	Pos	Remark
					dBuV	dB	dB	cm	deg	
1 X	2480.00	74.76	0.76	74.00	72.27	33.01	3.68	34.20	100	229 Peak
2 X	2480.00	63.99	9.99	54.00	61.50	33.01	3.68	34.20	100	229 Average

* Maximum field strength of the fundamental emission

Test Mode :	Mode 3	Temperature :	23~24°C
Test Channel :	78	Relative Humidity :	50~51%
Test Engineer :	Cloud Peng	Polarization :	Horizontal




Site : 03CH01-KS
 Condition: FCC PART 15C 3m HF ANT-100803 HORIZONTAL
 Project : (FR) 1D2304
 Mode : mode 3
 Plane : H

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level Factor	Cable Loss	Preamp Factor	Ant Pos	Table Pos	Remark	
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1 X	2479.82	74.26	0.26	74.00	71.77	33.01	3.68	34.20	----	----	Peak
2	2483.50	43.03	-30.97	74.00	40.54	33.01	3.68	34.20	----	----	Peak

* Marker-Delta Method (RBW/VBW=100KHz): 31.23 dB , single carrier Mode

Test Mode :	Mode 3	Temperature :	23~24°C
Test Channel :	78	Relative Humidity :	50~51%
Test Engineer :	Cloud Peng	Polarization :	Horizontal




Site : 03CH01-KS
 Condition: FCC PART 15C 3m HF ANT-100803 HORIZONTAL
 Project : (FR) 1D2304
 Mode : mode 3
 Plane : H

	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	Ant	Table	
	MHz	dBuV/m	Limit	Line	Level	Loss	Factor	Pos	Pos	Remark
			dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg
1	2478.18	73.93	-0.07	74.00	71.44	33.01	3.68	34.20	---	Peak
2	2483.50	44.90	-29.10	74.00	42.41	33.01	3.68	34.20	---	Peak

* Marker-Delta Method (RBW/VBW=100KHz): 29.03 dB , Hopping Mode


Test Mode :	Mode 3	Temperature :	23~24°C
Test Channel :	78	Relative Humidity :	50~51%
Test Engineer :	Cloud Peng	Polarization :	Vertical




Site : 03CH01-KS
 Condition: FCC PART 15C 3m HF ANT-100803 VERTICAL
 Project : (FR) 1D2304
 Mode : mode 3
 Plane : H

	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	Ant	Table	
	MHz	dBuV/m	Limit	Line	Level	Loss	Factor	Pos	Pos	Remark
			dB	dBuV/m	dBuV	dB	dB	cm	deg	
1 X	2480.00	74.31	0.31	74.00	71.82	33.01	3.68	34.20	100	99 Peak
2 X	2480.00	65.64	11.64	54.00	63.15	33.01	3.68	34.20	100	99 Average

* Maximum field strength of the fundamental emission



Test Mode :	Mode 3	Temperature :	23~24°C
Test Channel :	78	Relative Humidity :	50~51%
Test Engineer :	Cloud Peng	Polarization :	Vertical



Site : 03CH01-KS
 Condition: FCC PART 15C 3m HF ANT-100803 VERTICAL
 Project : (FR) 1D2304
 Mode : mode 3
 Plane : H


	Freq	Level	Over Limit	Limit Line	ReadAntenna Level Factor	Cable Loss	Preamp Factor	Ant Pos	Table Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	cm	deg	
1	2479.84	73.86	-0.14	74.00	71.37	33.01	3.68	34.20	---	Peak
2	2483.50	43.38	-30.62	74.00	40.89	33.01	3.68	34.20	---	Peak

* Marker-Delta Method (RBW/VBW=100KHz): 30.48 dB , Hopping Mode

3.6.6 Test Result of Conducted Band Edges


Test Mode :	Mode 1 and 3	Temperature :	24~25°C
Test Channel :	00 and 78	Relative Humidity :	48~49%
		Test Engineer :	Zhi Lu

Low Band Edge Plot on Channel 00



Date: 26.DEC.2011 23:50:39

High Band Edge Plot on Channel 78



Date: 26.DEC.2011 23:51:41

3.7 Spurious Emission Measurement

3.7.1 Limit of Spurious Emission Measurement

All harmonics/spurious must be at least 20 dB down from the highest emission level within the authorized band.


3.7.2 Measuring Instruments

See list of measuring instruments of this test report.

3.7.3 Test Procedure

1. The transmitter output was connected to the spectrum analyzer via a low lose cable.
2. Set RBW = 100 kHz, Video bandwidth (VBW) $\geq$ RBW, scan up through 10th harmonic. All harmonics / spurs must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100 kHz RBW.


3.7.4 Test Setup



3.7.5 Test Result


Test Mode :	Mode 1	Temperature :	24~25℃
Test Channel :	00	Relative Humidity :	48~49%
		Test Engineer :	Zhi Lu

Conducted Spurious Emission Plot between 30MHz ~ 3 GHz




Date: 27.DEC.2011 00:02:00

Conducted Spurious Emission Plot between 3 GHz ~ 25 GHz




Date: 27.DEC.2011 00:02:13

Test Mode :	Mode 2	Temperature :	24~25°C
Test Channel :	39	Relative Humidity :	48~49%
		Test Engineer :	Zhi Lu

Conducted Spurious Emission Plot between 30MHz ~ 3 GHz



Date: 27.DEC.2011 00:03:05

Conducted Spurious Emission Plot between 3 GHz ~ 25 GHz



Date: 27.DEC.2011 00:03:17



Test Mode :	Mode 3	Temperature :	24~25℃
Test Channel :	78	Relative Humidity :	48~49%
		Test Engineer :	Zhi Lu

Conducted Spurious Emission Plot between 30MHz ~ 3 GHz

Date: 27.DEC.2011 00:04:09

Conducted Spurious Emission Plot between 3 GHz ~ 25 GHz

Date: 27.DEC.2011 00:04:22

3.8 AC Conducted Emission Measurement

3.8.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.8.2 Measuring Instruments

See list of measuring instruments of this test report.

3.8.3 Test Procedures


1. Please follow the guidelines in ANSI C63.4-2003.
2. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
3. Connect EUT to the power mains through a line impedance stabilization network (LISN).
4. All the support units are connecting to the other LISN.
5. The LISN provides 50 ohm coupling impedance for the measuring instrument.
6. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
7. Both sides of AC line were checked for maximum conducted interference.
8. The frequency range from 150 kHz to 30 MHz was searched.
9. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode.

3.8.4 Test Setup



3.8.5 Test Result of AC Conducted Emission


Test Mode :	Mode 1	Temperature :	22~23℃
Test Engineer :	King Liu	Relative Humidity :	44~46%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	GSM 850 Idle + Bluetooth Link + WLAN Link + Adapter + Earphone + Camera		
Remark :	All emissions not reported here are more than 10 dB below the prescribed limit.		



Site : CO01-SZ
 Condition : FCC 15C_QP LISN_L_2000601 LINE
 Project : (FR)1D2304
 Mode : Mode1

	Freq	Level	Over	Limit	Read	LISN	Cable	Remark
	MHz	dBuV	Limit	Line	Level	Factor	Loss	
			dB	dBuV	dBuV	dB	dB	
1	0.42	31.50	-16.01	47.51	21.40	0.02	10.08	Average
2	0.42	39.50	-18.01	57.51	29.40	0.02	10.08	QP
3	1.22	28.25	-17.75	46.00	18.10	0.03	10.12	Average
4	1.22	37.35	-18.65	56.00	27.20	0.03	10.12	QP
5	1.50	29.66	-16.34	46.00	19.50	0.03	10.13	Average
6	1.50	39.76	-16.24	56.00	29.60	0.03	10.13	QP
7	1.93	31.58	-14.42	46.00	21.40	0.03	10.15	Average
8	1.93	41.08	-14.92	56.00	30.90	0.03	10.15	QP
9	2.42	32.81	-13.19	46.00	22.60	0.04	10.17	Average
10	2.42	42.01	-13.99	56.00	31.80	0.04	10.17	QP
11	3.24	32.74	-13.26	46.00	22.50	0.05	10.19	Average
12	3.24	42.14	-13.86	56.00	31.90	0.05	10.19	QP

Test Mode :	Mode 1	Temperature :	22~23°C
Test Engineer :	King Liu	Relative Humidity :	44~46%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	GSM 850 Idle + Bluetooth Link + WLAN Link + Adapter + Earphone + Camera		
Remark :	All emissions not reported here are more than 10 dB below the prescribed limit.		



Site : CO01-SZ
 Condition : FCC 15C_QP LISN_N_2000601 NEUTRAL
 Project : (FR)1D2304
 Mode : Mode1

	Freq	Level	Over	Limit	Read	LISN	Cable	Remark
	MHz	dBuV	Limit	Line	Level	Factor	Loss	
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.36	36.49	-12.20	48.69	26.40	0.02	10.07	Average
2	0.36	45.59	-13.10	58.69	35.50	0.02	10.07	QP
3	0.98	32.03	-13.97	46.00	21.90	0.02	10.11	Average
4	0.98	41.93	-14.07	56.00	31.80	0.02	10.11	QP
5	1.17	32.44	-13.56	46.00	22.30	0.02	10.12	Average
6	1.17	41.84	-14.16	56.00	31.70	0.02	10.12	QP
7	2.00	35.78	-10.22	46.00	25.60	0.03	10.15	Average
8	2.00	45.28	-10.72	56.00	35.10	0.03	10.15	QP
9	2.85	37.03	-8.97	46.00	26.81	0.04	10.18	Average
10	2.85	46.73	-9.27	56.00	36.51	0.04	10.18	QP
11	3.76	35.05	-10.95	46.00	24.80	0.06	10.19	Average
12	3.76	45.05	-10.95	56.00	34.80	0.06	10.19	QP

3.9 Radiated Emission Measurement

3.9.1 Limit of Radiated Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. In addition, radiated emissions which fall in the restricted bands must also comply with the FCC section 15.209 limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.9.2 Measuring Instruments


See list of measuring instruments of this test report.

3.9.3 Test Procedures


- The testing follows the guidelines in FCC Public Notice DA 00-705 Measurement Guidelines.
- Use the following spectrum analyzer settings:
 - Span = wide enough to fully capture the emission being measured; RBW = 1 MHz for $f \geq 1$ GHz, 100 kHz for $f < 1$ GHz; VBW $\geq$ RBW; Sweep = auto; Detector function = peak; Trace = max hold.
 - Above 18 GHz shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade from 3m to 1m.
Distance extrapolation factor = $20 \log (\text{specific distance [3m]} / \text{test distance [1m]})$ (dB)
- Follow the guidelines in ANSI C63.4-2003 with respect to maximizing the emission by rotating the EUT, measuring the emission for three EUT orthogonal planes, and adjusting the measurement antenna height and polarization. A pre-amp and a high pass filter are used for this test in order to get the good signal level.
- Measured average value for the peak value is greater than 54 dBuV/m

3.9.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



3.9.5 Test Results of Radiated Emissions (9 kHz ~ 30 MHz)

Test Engineer :	Cloud Peng	Temperature :	23~24℃	
		Relative Humidity :	50~51%	

Frequency (MHz)	Level (dBuV)	Over Limit (dB)	Limit Line (dBuV)	Remark
-	-	-	-	See Note

Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor = $40 \log (\text{specific distance} / \text{test distance})$ (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.

3.9.6 Test Result of Radiated Emission (30 MHz ~ 10th Harmonic)

Test Mode :	Mode 1	Temperature :	23~24°C
Test Channel :	00	Relative Humidity :	50~51%
Test Engineer :	Cloud Peng	Polarization :	Horizontal
Remark :	2402 MHz is Fundamental Signals which can be ignored.		

Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
30	20.69	-19.31	40	32.51	18	0.26	30.08	-	-	Peak
102.36	27.24	-16.26	43.5	45.91	10.87	0.42	29.96	-	-	Peak
207.12	38.94	-4.56	43.5	59	9.34	0.6	30	100	360	QP
309.8	26.65	-19.35	46	42.65	13.22	0.73	29.95	-	-	Peak
778.8	22.03	-23.97	46	30.51	19.87	1.22	29.57	-	-	Peak
946.8	27.07	-26.93	54	34.56	20.72	1.33	29.54	-	-	Peak
2390	48.75	-25.25	74	46.47	32.86	3.47	34.05	100	0	Peak
2390	36.18	-17.82	54	33.9	32.86	3.47	34.05	100	0	Average
2402	80.24	-	-	77.96	32.86	3.47	34.05	109	113	Peak
2402	70.15	-	-	67.87	32.86	3.47	34.05	109	113	Average
2483.5	48.08	-25.92	74	45.59	33.01	3.68	34.2	100	0	Peak
2483.5	37.05	-16.95	54	34.56	33.01	3.68	34.2	100	0	Average

Test Mode :	Mode 1	Temperature :	23~24°C
Test Channel :	00	Relative Humidity :	50~51%
Test Engineer :	Cloud Peng	Polarization :	Vertical
Remark :	2402 MHz is Fundamental Signals which can be ignored.		

Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
34.86	30.84	-9.16	40	45.6	15.1	0.23	30.09	-	-	Peak
102.36	23.6	-19.9	43.5	42.27	10.87	0.42	29.96	-	-	Peak
207.12	37.79	-5.71	43.5	57.85	9.34	0.6	30	100	0	Peak
309.8	32.92	-13.08	46	48.92	13.22	0.73	29.95	-	-	Peak
517	28.96	-17.04	46	40.13	17.58	0.97	29.72	-	-	Peak
946.8	26.84	-27.16	54	34.33	20.72	1.33	29.54	-	-	Peak
2390	48.9	-25.1	74	46.62	32.86	3.47	34.05	100	0	Peak
2390	36.38	-17.62	54	34.1	32.86	3.47	34.05	100	0	Average
2402	81.67	-	-	79.39	32.86	3.47	34.05	100	271	Peak
2402	71.86	-	-	69.58	32.86	3.47	34.05	100	271	Average
2483.5	48.1	-25.9	74	45.61	33.01	3.68	34.2	100	0	Peak
2483.5	37.09	-16.91	54	34.6	33.01	3.68	34.2	100	0	Average

Test Mode :	Mode 2	Temperature :	23~24°C
Test Channel :	39	Relative Humidity :	50~51%
Test Engineer :	Cloud Peng	Polarization :	Horizontal
Remark :	2441 MHz is Fundamental Signals which can be ignored.		

Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
31.08	19.75	-20.25	40	32.29	17.29	0.25	30.08	-	-	Peak
102.36	24.69	-18.81	43.5	43.36	10.87	0.42	29.96	-	-	Peak
206.85	39.42	-4.08	43.5	59.52	9.3	0.6	30	100	0	Peak
309.8	27.47	-18.53	46	43.47	13.22	0.73	29.95	-	-	Peak
402.9	23.14	-22.86	46	36.12	16.01	0.84	29.83	-	-	Peak
946.8	26.78	-27.22	54	34.27	20.72	1.33	29.54	-	-	Peak
2390	49.06	-24.94	74	46.78	32.86	3.47	34.05	100	0	Peak
2390	37.38	-16.62	54	35.1	32.86	3.47	34.05	100	0	Average
2441	79.71	-	-	77.31	32.95	3.6	34.15	142	360	Peak
2441	70.36	-	-	67.96	32.95	3.6	34.15	142	360	Average
2483.5	49.54	-24.46	74	47.05	33.01	3.68	34.2	100	0	Peak
2483.5	36.99	-17.01	54	34.5	33.01	3.68	34.2	100	0	Average

Test Mode :	Mode 2	Temperature :	23~24°C
Test Channel :	39	Relative Humidity :	50~51%
Test Engineer :	Cloud Peng	Polarization :	Vertical
Remark :	2441 MHz is Fundamental Signals which can be ignored.		

Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
34.59	31.08	-8.92	40	45.84	15.1	0.23	30.09	-	-	Peak
103.44	24.53	-18.97	43.5	43.06	11.01	0.42	29.96	-	-	Peak
207.12	35.09	-8.41	43.5	55.15	9.34	0.6	30	100	0	Peak
309.8	26.96	-19.04	46	42.96	13.22	0.73	29.95	-	-	Peak
517	27.68	-18.32	46	38.85	17.58	0.97	29.72	-	-	Peak
946.8	27.46	-26.54	54	34.95	20.72	1.33	29.54	-	-	Peak
2390	48.67	-25.33	74	46.39	32.86	3.47	34.05	100	0	Peak
2390	36.49	-17.51	54	34.21	32.86	3.47	34.05	100	0	Average
2441	79.96	-	-	77.56	32.95	3.6	34.15	100	265	Peak
2441	70.6	-	-	68.2	32.95	3.6	34.15	100	265	Average
2483.5	48.7	-25.3	74	46.21	33.01	3.68	34.2	100	0	Peak
2483.5	37.72	-16.28	54	35.23	33.01	3.68	34.2	100	0	Average

Test Mode :	Mode 3	Temperature :	23~24°C
Test Channel :	78	Relative Humidity :	50~51%
Test Engineer :	Cloud Peng	Polarization :	Horizontal
Remark :	2480 MHz is Fundamental Signals which can be ignored.		

Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
102.36	26.75	-16.75	43.5	45.42	10.87	0.42	29.96	-	-	Peak
207.12	40.04	-3.46	43.5	60.1	9.34	0.6	30	100	42	QP
299.46	24.33	-21.67	46	40.56	13	0.72	29.95	-	-	Peak
309.8	33.6	-12.4	46	49.6	13.22	0.73	29.95	-	-	Peak
517	24.95	-21.05	46	36.12	17.58	0.97	29.72	-	-	Peak
946.8	27.89	-26.11	54	35.38	20.72	1.33	29.54	-	-	Peak
2390	48.81	-25.19	74	46.53	32.86	3.47	34.05	100	0	Peak
2390	35.78	-18.22	54	33.5	32.86	3.47	34.05	100	0	Average
2480	74.76	-	-	72.27	33.01	3.68	34.2	100	229	Peak
2480	63.99	-	-	61.5	33.01	3.68	34.2	100	229	Average
2483.5	34.96	-19.04	54	32.47	33.01	3.68	34.2	100	360	Average
2483.5	44.9	-29.1	74	42.41	33.01	3.68	34.2	100	360	Peak

Test Mode :	Mode 3	Temperature :	23~24°C
Test Channel :	78	Relative Humidity :	50~51%
Test Engineer :	Cloud Peng	Polarization :	Vertical
Remark :	2480 MHz is Fundamental Signals which can be ignored.		

Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
34.59	30.31	-9.69	40	45.07	15.1	0.23	30.09	-	-	Peak
103.98	25.26	-18.24	43.5	43.79	11.01	0.42	29.96	-	-	Peak
207.12	34.78	-8.72	43.5	54.84	9.34	0.6	30	100	0	Peak
309.8	31.8	-14.2	46	47.8	13.22	0.73	29.95	-	-	Peak
517	29.54	-16.46	46	40.71	17.58	0.97	29.72	-	-	Peak
946.8	27.77	-26.23	54	35.26	20.72	1.33	29.54	-	-	Peak
2390	48.98	-25.02	74	46.7	32.86	3.47	34.05	100	0	Peak
2390	36.88	-17.12	54	34.6	32.86	3.47	34.05	100	0	Average
2480	65.64	-	-	63.15	33.01	3.68	34.2	100	99	Average
2480	74.31	-	-	71.82	33.01	3.68	34.2	100	99	Peak
2483.5	35.94	-18.06	54	33.45	33.01	3.68	34.2	200	120	Average
2483.5	44.59	-29.41	74	42.1	33.01	3.68	34.2	200	120	Peak

3.10 Antenna Requirements

3.10.1 Standard Applicable

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the FCC rule.

3.10.2 Antenna Connected Construction

The antennas type used in this product is Dipole Antenna without connector and it is considered to meet antenna requirement.

3.10.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.

4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSP40	100319	9kHz~40GHz	Dec. 30, 2011	Jan. 05, 2012	Dec. 29, 2012	Conducted (TH01-KS)
Bluetooth Base Station	R&S	CBT	100783	N/A	Aug. 18, 2011	Jan. 05, 2012	Aug. 17, 2012	Conducted (TH01-KS)
DC Power Supply	TOPWARD	GPS-3030D	E1884515	N/A	Aug. 23, 2011	Jan. 05, 2012	Aug. 22, 2012	Conducted (TH01-KS)
Thermal Chamber	Ten Billion	TTC-B3S	TBN-960502	N/A	Dec. 30, 2011	Jan. 05, 2012	Dec. 29, 2012	Conducted (TH01-KS)
EMI TEST Receiver	R&S	ECSI	100724	9K-3GHz	Mar. 08, 2011	Jan. 05, 2012	Mar. 07, 2012	Conduction (CO01-SZ)
AC LISN	ETS-LINDGRE N	3816/2SH	00103912	0.1MHz~108MHz	Feb. 28, 2011	Jan. 05, 2012	Feb. 27, 2012	Conduction (CO01-SZ)
AC LISN	ETS-LINDGRE N	3816/2SH	00103892	0.1MHz~108MHz	Feb. 28, 2011	Jan. 05, 2012	Feb. 27, 2012	Conduction (CO01-SZ)
AVR	Throma	61602	616020000891N/A	/	Oct. 12, 2011	Jan. 05, 2012	Oct. 11, 2012	Conduction (CO01-SZ)
AC Filter	ETS-LINDGRE N	LRE-2030/PE N 256260	00093783	/	N/A	Jan. 05, 2012	N/A	Conduction (CO01-SZ)
AC Filter	ETS-LINDGRE N	LRE-2030/PE N 256260	00097973	/	N/A	Jan. 05, 2012	N/A	Conduction (CO01-SZ)
System Simulator	Aglient	E5515C	MY50264168	GSM/WCDMA /CDMA2000	Mar. 14, 2011	Jan. 05, 2012	Mar. 13, 2012	Conduction (CO01-SZ)
EMI Test Receiver	R&S	ESCI	100534	9kHz~3GHz	Nov. 09, 2011	Feb. 16, 2012	Nov. 08, 2012	Radiation (03CH01-KS)
Spectrum Analyzer	R&S	FSP40	100319	9kHz~40GHz	Dec. 30, 2011	Feb. 16, 2012	Dec. 29, 2012	Radiation (03CH01-KS)
Bilog Antenna	SCHAFFNER	CBL6112D	23182	25MHz~2GHz	Dec. 08, 2011	Feb. 16, 2012	Dec. 07, 2012	Radiation (03CH01-KS)
Loop Antenna	R&S	HFH2-Z2	860004/00	9 kHz~30 MHz	Jul. 28, 2011	Feb. 16, 2012	Jul. 27, 2012	Radiation (03CH01-KS)
Double Ridge Horn Antenna	EMCO	3117	00075959	1GHz~18GHz	Jan. 06, 2012	Feb. 16, 2012	Jan. 05, 2013	Radiation (03CH01-KS)
Amplifier	Wireless	FPA-6592G	060004	30MHz~2GHz	Dec. 30, 2011	Feb. 16, 2012	Dec. 29, 2012	Radiation (03CH01-KS)
Amplifier	Agilent	8449B	3008A02370	1GHz~26.5GHz	Dec. 30, 2011	Feb. 16, 2012	Dec. 29, 2012	Radiation (03CH01-KS)
Active Horn Antenna	com-power	AHA-118	701023	1GHz~18GHz	Nov. 07, 2011	Feb. 16, 2012	Nov. 06, 2012	Radiation (03CH01-KS)
SHF-EHF Horn	Schwarzbeck	BBHA 9170	BBHA170249	15GHz~40GHz	Oct. 11, 2011	Feb. 16, 2012	Oct.10, 2012	Radiation (03CH01-KS)
Bluetooth Base Station	R&S	CBT	100783	N/A	Aug. 18, 2011	Feb. 16, 2012	Aug. 17, 2012	-

5 Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Contribution	Uncertainty of X_i		$u(X_i)$
	dB	Probability Distribution	
Receiver Reading	0.10	Normal (k=2)	0.05
Cable Loss	0.10	Normal (k=2)	0.05
AMN Insertion Loss	2.50	Rectangular	0.63
Receiver Specification	1.50	Rectangular	0.43
Site Imperfection	1.39	Rectangular	0.80
Mismatch	+0.34 / -0.35	U-Shape	0.24
Combined Standard Uncertainty $U_c(y)$	1.13		
Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	2.26		

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Contribution	Uncertainty of X_i		$u(X_i)$
	dB	Probability Distribution	
Receiver Reading	0.41	Normal (k=2)	0.21
Antenna Factor Calibration	0.83	Normal (k=2)	0.42
Cable Loss Calibration	0.25	Normal (k=2)	0.13
Pre-Amplifier Gain Calibration	0.27	Normal (k=2)	0.14
RCV/SPA Specification	2.50	Rectangular	0.72
Antenna Factor Interpolation for Frequency	1.00	Rectangular	0.29
Site Imperfection	1.43	Rectangular	0.83
Mismatch	+0.39 / -0.41	U-Shape	0.28
Combined Standard Uncertainty $U_c(y)$	1.27		
Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	2.54		

Uncertainty of Radiated Emission Measurement (1 GHz ~ 40 GHz)

Contribution	Uncertainty of X_i		$u(X_i)$	C_i	$C_i * u(X_i)$
	dB	Probability Distribution			
Receiver Reading	± 0.10	Normal (k=2)	0.10	1	0.10
Antenna Factor Calibration	± 1.70	Normal (k=2)	0.85	1	0.85
Cable Loss Calibration	± 0.50	Normal (k=2)	0.25	1	0.25
Receiver Correction	± 2.00	Rectangular	1.15	1	1.15
Antenna Factor Directional	± 1.50	Rectangular	0.87	1	0.87
Site Imperfection	± 2.80	Triangular	1.14	1	1.14
Mismatch Receiver VSWR $\Gamma_1 = 0.197$ Antenna VSWR $\Gamma_2 = 0.194$ Uncertainty = $20\log(1-\Gamma_1*\Gamma_2)$	+0.34 / -0.35	U-Shape	0.244	1	0.244
Combined Standard Uncertainty $U_c(y)$	2.36				
Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	4.72				



Appendix A. Photographs of EUT

Please refer to Sporton report number EP1D2304 as below.