EMC TEST REPORT

Report No.: 18070333-FCC-E

Supersede Report No: N/A

Applicant	BLU Products,Inc
Product Name	Feature Phone
Model No.	FLASH
Serial No.	N/A
Test Standard	FCC Part 15 Subpart B Class B:2017, ANSI C63.4: 2014
Test Date	April 10 to April 24, 2018
Issue Date	April 25, 2018
Test Result	☑ Pass ☐ Fail
Equipment complied with the specification	☑
Equipment did not comply with the specification	☐

Evans He Test Engineer	David Huang Checked By	

This test report may be reproduced in full only

Test result presented in this test report is applicable to the tested sample only

Issued by:

SIEMIC (SHENZHEN-CHINA) LABORATORIES

Zone A, Floor 1, Building 2 Wan Ye Long Technology Park

South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108

Phone: +86 0755 2601 4629801 Email: China@siemic.com.cn

Laboratories Introduction

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.

In addition to testing and certification, SIEMIC provides initial design reviews and compliance management throughout a project. Our extensive experience with China, Asia Pacific, North America, European, and International compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the global markets.

Accreditations for Conformity Assessment

Country/Region	Scope
USA	EMC, RF/Wireless, SAR, Telecom
Canada	EMC, RF/Wireless, SAR, Telecom
Taiwan	EMC, RF, Telecom, SAR, Safety
Hong Kong	RF/Wireless, SAR, Telecom
Australia	EMC, RF, Telecom, SAR, Safety
Korea	EMI, EMS, RF, SAR, Telecom, Safety
Japan	EMI, RF/Wireless, SAR, Telecom
Singapore	EMC, RF, SAR, Telecom
Europe	EMC, RF, SAR, Telecom, Safety

This page has been left blank intentionally.

CONTENTS

1. REPORT REVISION HISTORY 5

2. CUSTOMER INFORMATION 5

3. TEST SITE INFORMATION 5

4. EQUIPMENT UNDER TEST (EUT) INFORMATION 6

5. TEST SUMMARY 8

6. MEASUREMENTS, EXAMINATION AND DERIVED RESULTS 9

6.1 AC POWER LINE CONDUCTED EMISSIONS 9

6.2 RADIATED EMISSIONS 15

ANNEX A. TEST INSTRUMENT 20

ANNEX B. EUT AND TEST SETUP PHOTOGRAPHS 21

ANNEX C. TEST SETUP AND SUPPORTING EQUIPMENT 32

ANNEX D. USER MANUAL / BLOCK DIAGRAM / SCHEMATICS / PARTLIST 35

ANNEX E. DECLARATION OF SIMILARITY 36

1. Report Revision History

Report No.	Report Version	Description	Issue Date
18070333-FCC-E	NONE	Original	April 25, 2018

2. Customer information

Applicant Name	BLU Products,Inc
Applicant Add	10814 NW 33rd St # 100 Doral, FL 33172 , USA
Manufacturer	BLU Products,Inc
Manufacturer Add	10814 NW 33rd St # 100 Doral, FL 33172,USA

3. Test site information

Lab performing tests	SIEMIC (Shenzhen-China) LABORATORIES
Lab Address	Zone A, Floor 1, Building 2 Wan Ye Long Technology Park South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108
FCC Test Site No.	535293
IC Test Site No.	4842E-1
Test Software of Radiated Emission	Radiated Emission Program-To Shenzhen v2.0
Test Software of Conducted Emission	EZ-EMC(ver.lcp-03A1)

4. Equipment under Test (EUT) Information

Description of EUT:	Feature Phone
Main Model:	FLASH
Serial Model:	N/A
Antenna Gain:	GSM850: -0.5dBi PCS1900: -0.8dBi Bluetooth: -0.4dBi
Antenna Type:	GSM: PIFA antenna BT: Monopole antenna
Input Power:	Adapter: Model: US-NB-0550 Input: AC100-240V~50/60Hz,0.15A Output: DC 5.0V, 550mA Battery: Model: C41664160170L Spec: 3.7V, 1700mAh, 6.29Wh
Equipment Category：	JBP
Type of Modulation:	GSM / GPRS: GMSK EGPRS: GMSK Bluetooth: GFSK, π /4DQPSK, 8DPSK
RF Operating Frequency (ies):	GSM850 TX: 824.2 ~ 848.8 MHz; RX: 869.2 ~ 893.8 MHz PCS1900 TX: 1850.2 ~ 1909.8 MHz; RX: 1930.2 ~ 1989.8 MHz Bluetooth: 2402-2480 MHz
Number of Channels:	GSM 850: 124CH PCS1900: 299CH Bluetooth: 79CH
Port:	USB Port, Earphone Port

Trade Name :	BLU
FCC ID:	YHLBLUFLASH18
GPRS Multi-slot class	8/10/11/12
Date EUT received:	April 09, 2018
Test Date(s):	April 10 to April 24, 2018

5. Test Summary

The product was tested in accordance with the following specifications.

All testing has been performed according to below product classification:

FCC Rules	Description of Test	Result
§15.107; ANSI C63.4: 2014	AC Power Line Conducted Emissions	Compliance
§15.109; ANSI C63.4: 2014	Radiated Emissions	Compliance

Measurement Uncertainty

Parameter	Uncertainty
AC Power Line Conducted Emissions (150kHz~30MHz)	±3.11dB
Radiated Emission(30MHz~1GHz)	±5.12dB
Radiated Emission(1GHz~6GHz)	±5.34dB

6. Measurements, Examination And Derived Results

6.1 AC Power Line Conducted Emissions

Temperature	27 °C
Relative Humidity	58%
Atmospheric Pressure	1010mbar
Test date :	April 10, 2018
Tested By :	Evans He

Requirement(s):

<table>
<tr><th>Spec</th><th>Item</th><th>Requirement</th><th>Applicable</th></tr>
<tr><td>47CFR§15.107</td><td>a)</td><td>For Low-power radio-frequency devices that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 [mu] H/50 ohms line impedance stabilization network (LISN). The lower limit applies at the boundary between the frequencies ranges.
<table>
<tr><th rowspan="2">Frequency ranges (MHz)</th><th colspan="2">Limit (dBμV)</th></tr>
<tr><th>QP</th><th>Average</th></tr>
<tr><td>0.15 ~ 0.5</td><td>66 – 56</td><td>56 – 46</td></tr>
<tr><td>0.5 ~ 5</td><td>56</td><td>46</td></tr>
<tr><td>5 ~ 30</td><td>60</td><td>50</td></tr>
</table></td><td>☑</td></tr>
<tr><td>Test Setup</td><td colspan="3"> 

Note: 1.Support units were connected to second LISN.
2.Both of LISNs (AMN) are 80cm from EUT and at least 80cm from other units and other metal planes support units.</td></tr>
<tr><td>Procedure</td><td colspan="3">1. The EUT and supporting equipment were set up in accordance with the requirements of the standard on top of a 1.5m x 1m x 0.8m high, non-metallic table.
2. The power supply for the EUT was fed through a 50Ω /50mH EUT LISN, connected to filtered mains.</td></tr>
</table>

	3. The RF OUT of the EUT LISN was connected to the EMI test receiver via a low-loss coaxial cable. 4. All other supporting equipment were powered separately from another main supply. 5. The EUT was switched on and allowed to warm up to its normal operating condition. 6. A scan was made on the NEUTRAL line (for AC mains) or Earth line (for DC power) over the required frequency range using an EMI test receiver. 7. High peaks, relative to the limit line, The EMI test receiver was then tuned to the selected frequencies and the necessary measurements made with a receiver bandwidth setting of 10 kHz. 8. Step 7 was then repeated for the LIVE line (for AC mains) or DC line (for DC power).
Remark	
Result	☑ Pass ☐ Fail

Test Data ☑ Yes ☐ N/A

Test Plot ☑ Yes (See below) ☐ N/A

Test Mode :	USB Mode



Test Data

Phase Line Plot at 120Vac, 60Hz

No.	P/L	Frequency	Reading	Detector	Corrected	Result	Limit	Margin
		(MHz)	(dBuV)		(dB}	(dBuV)	(dBuV)	(dB)
1	L1	0.1578	29.89	QP	10.03	39.92	65.58	-25.66
2	L1	0.1578	17.07	AVG	10.03	27.10	55.58	-28.48
3	L1	0.4191	36.78	QP	10.03	46.81	57.47	-10.66
4	L1	0.4191	28.64	AVG	10.03	38.67	47.47	-8.80
5	L1	0.6687	23.32	QP	10.03	33.35	56.00	-22.65
6	L1	0.6687	16.99	AVG	10.03	27.02	46.00	-18.98
7	L1	1.9011	25.55	QP	10.04	35.59	56.00	-20.41
8	L1	1.9011	11.79	AVG	10.04	21.83	46.00	-24.17
9	L1	4.9383	23.77	QP	10.08	33.85	56.00	-22.15
10	L1	4.9383	11.56	AVG	10.08	21.64	46.00	-24.36
11	L1	23.6973	14.28	QP	10.37	24.65	60.00	-35.35
12	L1	23.6973	8.03	AVG	10.37	18.40	50.00	-31.60

Test Mode:	USB Mode



Test Data

Phase Neutral Plot at 120Vac, 60Hz

No.	P/L	Frequency	Reading	Detector	Corrected	Result	Limit	Margin
		(MHz)	(dBuV)		(dB}	(dBuV)	(dBuV)	(dB)
1	N	0.1582	34.01	QP	10.02	44.03	65.56	-21.53
2	N	0.1582	17.82	AVG	10.02	27.84	55.56	-27.72
3	N	0.4425	23.73	QP	10.02	33.75	57.01	-23.26
4	N	0.4425	14.41	AVG	10.02	24.43	47.01	-22.58
5	N	0.8091	19.22	QP	10.03	29.25	56.00	-26.75
6	N	0.8091	8.26	AVG	10.03	18.29	46.00	-27.71
7	N	1.9752	17.88	QP	10.04	27.92	56.00	-28.08
8	N	1.9752	8.51	AVG	10.04	18.55	46.00	-27.45
9	N	3.3315	21.16	QP	10.05	31.21	56.00	-24.79
10	N	3.3315	9.79	AVG	10.05	19.84	46.00	-26.16
11	N	24.0015	18.79	QP	10.32	29.11	60.00	-30.89
12	N	24.0015	9.92	AVG	10.32	20.24	50.00	-29.76

Test Mode :	USB Mode



Test Data

Phase Line Plot at 240Vac, 60Hz

No.	P/L	Frequency	Reading	Detector	Corrected	Result	Limit	Margin
		(MHz)	(dBuV)		(dB}	(dBuV)	(dBuV)	(dB)
1	L1	0.4269	36.35	QP	10.03	46.38	57.31	-10.93
2	L1	0.4269	22.86	AVG	10.03	32.89	47.31	-14.42
3	L1	0.9417	25.78	QP	10.03	35.81	56.00	-20.19
4	L1	0.9417	18.81	AVG	10.03	28.84	46.00	-17.16
5	L1	1.2771	26.16	QP	10.03	36.19	56.00	-19.81
6	L1	1.2771	19.38	AVG	10.03	29.41	46.00	-16.59
7	L1	3.2145	25.47	QP	10.06	35.53	56.00	-20.47
8	L1	3.2145	19.37	AVG	10.06	29.43	46.00	-16.57
9	L1	5.3946	23.25	QP	10.09	33.34	60.00	-26.66
10	L1	5.3946	14.85	AVG	10.09	24.94	50.00	-25.06
11	L1	24.0678	12.94	QP	10.38	23.32	60.00	-36.68
12	L1	24.0678	7.34	AVG	10.38	17.72	50.00	-32.28

Test Mode :	USB Mode



Test Data

Phase Neutral Plot at 240Vac, 60Hz

No.	P/L	Frequency	Reading	Detector	Corrected	Result	Limit	Margin
		(MHz)	(dBuV)		(dB}	(dBuV)	(dBuV)	(dB)
1	N	0.4308	38.64	QP	10.02	48.66	57.24	-8.58
2	N	0.4308	29.62	AVG	10.02	39.64	47.24	-7.60
3	N	0.8403	28.52	QP	10.03	38.55	56.00	-17.45
4	N	0.8403	18.40	AVG	10.03	28.43	46.00	-17.57
5	N	1.2537	30.07	QP	10.03	40.10	56.00	-15.90
6	N	1.2537	20.88	AVG	10.03	30.91	46.00	-15.09
7	N	2.0441	28.57	QP	10.04	38.61	56.00	-17.39
8	N	2.0441	19.73	AVG	10.04	29.77	46.00	-16.23
9	N	5.0904	26.36	QP	10.07	36.43	60.00	-23.57
10	N	5.0904	16.86	AVG	10.07	26.93	50.00	-23.07
11	N	23.8806	16.76	QP	10.32	27.08	60.00	-32.92
12	N	23.8806	7.84	AVG	10.32	18.16	50.00	-31.84

6.2 Radiated Emissions

Temperature	25 °C
Relative Humidity	53%
Atmospheric Pressure	1021mbar
Test date :	April 12, 2018
Tested By :	Evans He

Requirement(s):

Spec	Item	Requirement	Applicable
47CFR§15.109(d)	a)	Except higher limit as specified elsewhere in other section, the emissions from the low-power radio-frequency devices shall not exceed the field strength levels specified in the following table and the level of any unwanted emissions shall not exceed the level of the fundamental emission. The tighter limit applies at the band edges Frequency range (MHz) / Field Strength (μV/m) 30 – 88 / 100 88 – 216 / 150 216 - 960 / 200 Above 960 / 500	☑
Test Setup			
Procedure	1. The EUT was switched on and allowed to warm up to its normal operating condition. 2. The test was carried out at the selected frequency points obtained from the EUT characterization. Maximization of the emissions, was carried out by rotating the EUT, changing the antenna polarization, and adjusting the antenna height in the following manner: a. Vertical or horizontal polarization (whichever gave the higher emission level		

	over a full rotation of the EUT) was chosen. b. The EUT was then rotated to the direction that gave the maximum emission. c. Finally, the antenna height was adjusted to the height that gave the maximum emission. 3. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasiy Peak detection at frequency below 1GHz. 4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz with Peak detection for Peak measurement at frequency above 1GHz. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth with Peak detection for Average Measurement as below at frequency above 1GHz. ■ 1 kHz (Duty cycle < 98%) □ 10 Hz (Duty cycle > 98%) 5. Steps 2 and 3 were repeated for the next frequency point, until all selected frequency points were measured.
Remark	
Result	☑ Pass ☐ Fail

Test Data ☑ Yes ☐ N/A

Test Plot ☑ Yes (See below) ☐ N/A

Test Mode :	USB Mode

Below 1GHz



Test Data

Horizontal Polarity Plot @3m

No.	P/L	Frequency	Reading	Detector	Ant_F	PA_G	Cab_L	Result	Limit	Margin	Height	Degree
		(MHz)	(dBuV/m)		(dB/m)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	(cm)	( )
1	H	468.8762	42.68	QP	17.08	21.87	2.24	40.13	46.00	-5.87	100	265
2	H	234.1684	47.93	peak	11.62	22.32	1.65	38.88	46.00	-7.12	100	227
3	H	143.8295	42.77	peak	12.60	22.38	1.30	34.29	43.50	-9.21	100	26
4	H	99.5281	35.29	peak	10.29	22.32	1.11	24.37	43.50	-19.13	100	283
5	H	324.4561	39.81	peak	14.11	22.22	1.91	33.61	46.00	-12.39	100	44
6	H	71.8320	35.60	peak	7.76	22.39	0.97	21.94	40.00	-18.06	100	0

Below 1GHz



Test Data

Vertical Polarity Plot @3m

No.	P/L	Frequency	Reading	Detector	Ant_F	PA_G	Cab_L	Result	Limit	Margin	Height	Degree
		(MHz)	(dBuV/m)		(dB/m)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	(cm)	( )
1	V	234.1684	44.06	peak	11.62	22.32	1.65	35.01	46.00	-10.99	100	43
2	V	468.8762	36.81	peak	17.08	21.87	2.24	34.26	46.00	-11.74	100	157
3	V	131.7577	36.18	peak	13.14	22.39	1.21	28.14	43.50	-15.36	100	141
4	V	79.8003	35.68	peak	7.60	22.42	1.05	21.91	40.00	-18.09	200	131
5	V	51.3005	36.90	peak	8.26	22.38	0.79	23.57	40.00	-16.43	100	268
6	V	33.3279	38.16	QP	18.84	22.26	0.71	35.45	40.00	-4.55	100	48

Above 1GHz

Frequency (MHz)	Read_level (dBμV/m)	Azimuth	Height (cm)	Polarity (H/V)	Level (dBμV/m)	Factors (dB)	Limit (dBμV/m)	Margin (dB)	Detector (PK/AV)
1068.542	68.22	335	100	V	-20.3	47.92	74	-26.08	PK
1375.659	66.46	121	100	V	-19.14	47.32	74	-26.68	PK
2184.107	63.19	80	100	V	-14.49	48.7	74	-25.3	PK
1139.738	64.13	113	100	H	-20.01	44.12	74	-29.88	PK
1764.712	65.49	145	100	H	-16.76	48.73	74	-25.27	PK
3216.286	57.91	278	100	H	-12.83	45.08	74	-28.92	PK

*Note1: The highest frequency of the EUT is 2480 MHz, so the testing has been conformed to 5*2480MHz=12,400MHz.*

Note2: The frequency that above 3GHz is mainly from the environment noise.

Note3: The AV measurement performed, more than 20dB below limit so AV test data was not presented.

Annex A. TEST INSTRUMENT

Instrument	Model	Serial #	Cal Date	Cal Due	In use
AC Line Conducted Emissions					
EMI test receiver	ESCS30	8471241027	09/15/2017	09/14/2018	☑
Line Impedance Stabilization Network	LI-125A	191106	09/23/2017	09/22/2018	☑
Line Impedance Stabilization Network	LI-125A	191107	09/23/2017	09/22/2018	☑
ISN	ISN T800	34373	09/23/2017	09/22/2018	☐
Transient Limiter	LIT-153	531118	08/30/2017	08/29/2018	☑
Radiated Emissions					
EMI test receiver	E SL6	100262	09/15/2017	09/14/2018	☑
OPT 010 AMPLIFIER (0.1-1300MHz)	8447E	2727A02430	08/30/2017	08/29/2018	☑
Microwave Preamplifier (1 ~ 26.5GHz)	8449B	3008A02402	03/22/2018	03/21/2019	☑
Bilog Antenna (30MHz~6GHz)	JB6	A110712	09/19/2017	09/18/2018	☑
Double Ridge Horn Antenna	AH-118	71259	09/22/2017	09/21/2018	☑

Annex B. EUT And Test Setup Photographs

Annex B.i. Photograph: EUT External Photo

Whole Package View

Adapter - Lable View

EUT - Front View

EUT - Rear View

EUT - Top View

EUT - Bottom View

EUT - Left View

EUT - Right View

Annex B.ii. Photograph: EUT Internal Photo

Cover Off - Top View 1

Cover Off - Top View 2

Battery - Front View



Battery - Rear View

Mainboard with Shielding – Front View



Mainboard with Shielding – Rear View



Mainboard without Shielding – Front View



LCD – Front View



LCD – Rear View



GSM/PCS - Antenna View



BT - Antenna View



FM - Antenna View

Annex B.iii. Photograph: Test Setup Photo

Conducted Emissions Test Setup – Front View



Conducted Emissions Test Setup – Side View



Radiated Emissions Test Setup Below 1GHz



Radiated Emissions Test Setup Above 1GHz

Annex C. TEST SETUP AND SUPPORTING EQUIPMENT

Annex C.ii. TEST SET UP BLOCK

Block Configuration Diagram for Conducted Emissions



Block Configuration Diagram for Radiated Emissions



Annex C. iI. SUPPORTING EQUIPMENT DESCRIPTION

The following is a description of supporting equipment and details of cables used with the EUT.

Supporting Equipment:

Manufacturer	Equipment Description	Model	Serial No
Lenovo	Laptop	E40	LR-1EHRX
GOLDWEB	Router	R102	1202032094
Lenovo	AC Adapter	42T4416	21D9JU
HP	Printer	VCVRA-1003	CN36M19JWX
DELL	Mouse	E100	912NMTUT41481
BULL	Socket	GN-403	GN201203
SAMSUNG	headset	HS330	N/A

Supporting Cable:

Cable type	Shield Type	Ferrite Core	Length	Serial No
USB Cable	Un-shielding	No	2m	JX120051274
USB Cable	Un-shielding	No	2m	CBA3000AH0C1
RJ45 Cable	Un-shielding	No	2m	KX156327541
Router Power cable	Un-shielding	No	2m	13274630Z
Printer Power cable	Un-shielding	No	2m	127581031
Power Cable	Un-shielding	No	0.8m	GT211032

Annex D. User Manual / Block Diagram / Schematics / Partlist

Please see the attachment

Annex E. DECLARATION OF SIMILARITY

N/A