FCC TEST REPORT

Product Name:	Smart Phone
Trade Mark:	BLU
Model No.:	G73
Report Number:	2303224514RFC-2
Test Standards:	FCC 47 CFR Part 15 Subpart C
FCC ID:	YHLBLUG73W
Test Result:	PASS
Date of Issue:	May 10, 2023

Prepared for:

BLU Products, Inc.
8600 NW 36th Street, Suite #200 Doral, FL 33166

Prepared by:

Shenzhen UnionTrust Quality and Technology Co., Ltd.
Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China
TEL: +86-755-2823 0888
FAX: +86-755-2823 0886

Prepared by:	Kieron Luo Project Engineer	Reviewed by:	Henry Lu Team Leader
Approved by:	Kevin Liang Assistant Manager	Date:	May 10, 2023

UnionTrust Laboratories *Certified*

Version

Version No.	Date	Description
V1.0	May 10, 2023	Original

CONTENTS

1. GENERAL INFORMATION 5
   1.1 CLIENT INFORMATION 5
   1.2 EUT INFORMATION 5
      1.2.1 GENERAL DESCRIPTION OF EUT 5
      1.2.2 DESCRIPTION OF ACCESSORIES 6
   1.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD 7
   1.4 OTHER INFORMATION 7
   1.5 DESCRIPTION OF SUPPORT UNITS 8
   1.6 TEST LOCATION 8
   1.7 TEST FACILITY 8
   1.8 DEVIATION FROM STANDARDS 8
   1.9 ABNORMALITIES FROM STANDARD CONDITIONS 8
   1.10 OTHER INFORMATION REQUESTED BY THE CUSTOMER 9
   1.11 MEASUREMENT UNCERTAINTY 9
2. TEST SUMMARY 10
3. EQUIPMENT LIST 11
4. TEST CONFIGURATION 12
   4.1 ENVIRONMENTAL CONDITIONS FOR TESTING 12
      4.1.1 NORMAL OR EXTREME TEST CONDITIONS 12
      4.1.2 RECORD OF NORMAL ENVIRONMENT AND TEST SAMPLE 12
   4.2 TEST CHANNELS 12
   4.3 EUT TEST STATUS 12
   4.4 PRE-SCAN 13
      4.4.1 PRE-SCAN UNDER ALL PACKETS AT MIDDLE CHANNEL 13
      4.4.2 WORST-CASE DATA PACKETS 13
      4.4.3 TESTED CHANNEL DETAIL 13
   4.5 TEST SETUP 14
      4.5.1 FOR RADIATED EMISSIONS TEST SETUP 14
      4.5.2 FOR CONDUCTED EMISSIONS TEST SETUP 15
      4.5.3 FOR CONDUCTED RF TEST SETUP 16
   4.6 SYSTEM TEST CONFIGURATION 16
   4.7 DUTY CYCLE 17
5. RADIO TECHNICAL REQUIREMENTS SPECIFICATION 18
   5.1 REFERENCE DOCUMENTS FOR TESTING 18
   5.2 ANTENNA REQUIREMENT 18
   5.3 CONDUCTED PEAK OUTPUT POWER 19
   5.4 20 DB BANDWIDTH 20
   5.5 CARRIER FREQUENCIES SEPARATION 21
   5.6 NUMBER OF HOPPING CHANNEL 22
   5.7 DWELL TIME 23
   5.8 CONDUCTED OUT OF BAND EMISSION 24
   5.9 RADIATED SPURIOUS EMISSIONS 25
   5.10 BAND EDGE MEASUREMENTS (RADIATED) 29
   5.11 CONDUCTED EMISSION 32
APPENDIX A RF TEST DATA 35
   A.1 CONDUCTED PEAK OUTPUT POWER 35
   A.2 99% BANDWIDTH 37
   A.3 20DB BANDWIDTH 39
   A.4 CARRIER FREQUENCIES SEPARATION 41
   A.5 CONDUCTED OUT OF BAND EMISSION 42
   A.6 DWELL TIME 47
   A.7 NUMBER OF HOPPING CHANNEL 51

APPENDIX 1 PHOTOS OF TEST SETUP **53**
APPENDIX 2 PHOTOS OF EUT CONSTRUCTIONAL DETAILS **53**

1. GENERAL INFORMATION

1.1 CLIENT INFORMATION

Applicant:	BLU Products, Inc.
Address of Applicant:	8600 NW 36th Street, Suite #200 Doral, FL 33166
Manufacturer:	BLU Products, Inc.
Address of Manufacturer:	8600 NW 36th Street, Suite #200 Doral, FL 33166

1.2 EUT INFORMATION

1.2.1 General Description of EUT

Product Name:	Smart Phone		
Model No.:	G73		
Trade Mark:	BLU		
DUT Stage:	Identical Prototype		
EUT Supports Function: (Provided by the customer)	GSM Bands:	GSM850/PCS 1900	
	UTRA Bands:	WCDMA Band II/ Band IV/ Band V	
	E-UTRA Bands:	FDD Band 2/ Band 4/ Band 5/ Band 7/ Band 12/ Band 17/ Band 66/ Band 71	
		TDD Band 38	
	2.4 GHz ISM Band:	IEEE 802.11b/g/n	
		Bluetooth 5.0	
	5 GHz U-NII Bands:	5 150 MHz to 5 250 MHz	IEEE 802.11a/n/ac
		5 725 MHz to 5 850 MHz	IEEE 802.11a/n/ac
	RNSS Band:	1559 MHz to 1610 MHz	GPS/ BDS/ Galileo/ GLONASS
	BSR:	VHF Band II	FM
Software Version:	BLU_G0771_V13.0.01.01_GENERIC 20-03-2023 23:37 (Provided by the customer)		
Hardware Version:	SC6002_MB_V2.0.0 (Provided by the customer)		
Sample Received Date:	March 22, 2023		
Sample Tested Date:	March 22, 2023 to April 28, 2023		
Remark: The above EUT's information was provided by customer. Please refer to the specifications or user's manual for more detailed description.			

1.2.2 Description of Accessories

Adapter	
Model No.:	US-HY-2002
Input:	100-240 V~50/60 Hz 0.5 A
Output:	9.0 V ⎓ 2000 mA 18W

Battery	
Model No.:	C806051500P
Battery Type:	Lithium-ion Polymer Battery
Rated Voltage:	3.87 Vdc
Limited Charge Voltage:	4.45 Vdc
Typical Capacity:	5000 mAh
Rated Capacity:	4900 mAh

Cable	
Connector:	USB Cable
Cable Type:	Unshielded without ferrite
Length:	1.0 Meter

1.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD

Frequency Band:	2400 MHz to 2483.5 MHz
Frequency Range:	2402 MHz to 2480 MHz
Bluetooth Version:	Bluetooth BR + EDR
Modulation Technique:	Frequency Hopping Spread Spectrum (FHSS)
Type of Modulation:	GFSK, π/4DQPSK, 8DPSK
Number of Channels:	79
Channel Separation:	1 MHz
Hopping Channel Type:	Adaptive Frequency Hopping Systems
Antenna Type: (Provided by the customer)	FPCB Antenna
Antenna Gain: (Provided by the customer)	1.26 dBi
Maximum Peak Power:	9.742 dBm
Normal Test Voltage:	3.87 Vdc

1.4 OTHER INFORMATION

Operation Frequency Each of Channel
f = 2402 + k MHz, k = 0,…,78
Note: **f** is the operating frequency (MHz); **k** is the operating channel.

Modulation Configure			
Modulation	**Packet**	**Packet Type**	**Packet Size**
GFSK	1-DH1	4	27
	1-DH3	11	183
	1-DH5	15	339
π/4 DQPSK	2-DH1	20	54
	2-DH3	26	367
	2-DH5	30	679
8DPSK	3-DH1	24	83
	3-DH3	27	552
	3-DH5	31	1021

1.5 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested with associated equipment below.

1) Support Equipment

Description	Manufacturer	Model No.	Serial Number	Supplied by
--	--	--	--	--

2) Support Cable

Cable No.	Description	Connector	Length	Supplied by
1	Antenna Cable	SMA	0.1 Meter	Applicant

1.6 TEST LOCATION

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China, China 518109
Telephone: +86 (0) 755 2823 0888
Fax: +86 (0) 755 2823 0886

1.7 TEST FACILITY

The test facility is recognized, certified, or accredited by the following organizations:

CNAS-Lab Code: L9069
The measuring equipment utilized to perform the tests documented in this report has been calibrated once a year or in accordance with the manufacturer's recommendations, and is traceable under the ISO/IEC 17025 to international or national standards. Equipment has been calibrated by accredited calibration laboratories.

A2LA-Lab Certificate No.: 4312.01
Shenzhen UnionTrust Quality and Technology Co., Ltd. has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

ISED Wireless Device Testing Laboratories
CAB identifier: CN0032

FCC Accredited Lab.
Designation Number: CN1194
Test Firm Registration Number: 259480

1.8 DEVIATION FROM STANDARDS

None.

1.9 ABNORMALITIES FROM STANDARD CONDITIONS

None.

1.10 OTHER INFORMATION REQUESTED BY THE CUSTOMER

None.

1.11 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the Product as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

No.	Item	Measurement Uncertainty
1	Conducted emission 9kHz-150kHz	±3.2 dB
2	Conducted emission 150kHz-30MHz	±2.7 dB
3	Radiated emission 9kHz-30MHz	± 4.7 dB
4	Radiated emission 30MHz-1GHz	± 4.9 dB
5	Radiated emission 1GHz-18GHz	± 4.8 dB
6	Radiated emission 18GHz-26GHz	± 5.1 dB
7	Radiated emission 26GHz-40GHz	± 5.1 dB
8	Conducted spurious emissions	± 2.7 dB
9	RF Power, Conducted	± 0.68 dB
10	Occupied Bandwidth	± 1.86 %
11	Radio Frequency	2.4 GHz: ± 6.5 x 10^{-8}
12	Transmission Time	± 0.19 %

2. TEST SUMMARY

FCC 47 CFR Part 15 Subpart C Test Cases			
Test Item	**Test Requirement**	**Test Method**	**Result**
Antenna Requirement	FCC 47 CFR Part 15 Subpart C Section 15.203/15.247 (b)	N/A	PASS
AC Power Line Conducted Emission	FCC 47 CFR Part 15 Subpart C Section 15.207	ANSI C63.10-2013 Section 6.2	PASS
Conducted Peak Output Power	FCC 47 CFR Part 15 Subpart C Section 15.247 (b)(1)	ANSI C63.10-2013 Section 7.8.5	PASS
20 dB Bandwidth	FCC 47 CFR Part 15 Subpart C Section 15.247 (a)(1)	ANSI C63.10-2013 Section 6.9.2	PASS
Carrier Frequencies Separation	FCC 47 CFR Part 15 Subpart C Section 15.247 (a)(1)	ANSI C63.10-2013 Section 7.8.2	PASS
Number of Hopping Channel	FCC 47 CFR Part 15 Subpart C Section 15.247 (b)(1)	ANSI C63.10-2013 Section 7.8.3	PASS
Dwell Time	FCC 47 CFR Part 15 Subpart C Section 15.247 (a)(1)	ANSI C63.10-2013 Section 7.8.4	PASS
Conducted Out of Band Emission	FCC 47 CFR Part 15 Subpart C Section 15.247(d)	ANSI C63.10-2013 Section 6.10.4 & Section 7.8.8	PASS
Radiated Emissions	FCC 47 CFR Part 15 Subpart C Section 15.205/15.209	ANSI C63.10-2013 Section 6.3 & 6.5 & 6.6	PASS
Band Edge Measurement	FCC 47 CFR Part 15 Subpart C Section 15.205/15.209	ANSI C63.10-2013 Section 6.10.5	PASS
Disclaimer and Explanations: The declared of product specification and data (e.g., antenna gain, RF specification, etc) for EUT presented in the report are provided by the customer, and the customer takes all the responsibilities for the accuracy of product specification.			

3. EQUIPMENT LIST

Radiated Emission Test Equipment List						
Used	**Equipment**	**Manufacturer**	**Model No.**	**Serial Number**	**Cal. date**	**Cal. Due date**
☒	3m SAC	ETS-LINDGREN	3M	Euroshiedpn-CT001270-1317	22-Jan-2021	21-Jan-2024
☒	Receiver	R&S	ESIB26	100114	3-Nov-2022	2-Nov-2023
☒	EXA Spectrum Analyzer	KEYSIGHT	N9010A	MY51440197	15-Apr-2022	14-Apr-2023
					14-Apr-2023	13-Apr-2024
☒	Loop Antenna	ETS-LINDGREN	6502	00202525	21-Nov-2022	20-Nov-2023
☒	Broadband Antenna	ETS-LINDGREN	3142E	00201566	13-Dec-2022	12-Dec-2023
☒	6dB Attenuator	Talent	RA6A5-N-18	18103001	13-Dec-2022	12-Dec-2023
☒	Preamplifier	HP	8447F	2805A02960	1-Nov-2022	31-Oct-2023
☒	Horn Antenna (Pre-amplifier)	ETS-LINDGREN	3117-PA	00201541	17-Apr-2022	16-Apr-2024
☒	Pre-amplifier	ETS-LINDGREN	00118385	00201874	1-Nov-2022	31-Oct-2023
☒	Horn Antenna (Pre-amplifier)	ETS-LINDGREN	3116C-PA	00202652	21-Nov-2022	20-Nov-2023
☒	Pre-amplifier	ETS-LINDGREN	00118384	00202652	21-Nov-2022	20-Nov-2023
☒	Band Reject Filter (2400MHz~2500MHz)	Micro-Tronics	BRM50702	G248	2-Nov-2022	1-Nov-2023
☒	Multi device Controller	ETS-LINDGREN	7006-001	00160105	N/A	N/A
☒	Test Software	Audix	e3	Software Version: 9.160323		

Conducted Emission Test Equipment List						
Used	**Equipment**	**Manufacturer**	**Model No.**	**Serial Number**	**Cal. date**	**Cal. Due date**
☒	Receiver	R&S	ESR7	101181	1-Nov-2022	31-Oct-2023
☒	Pulse Limiter	R&S	ESH3-Z2	0357.8810.54	1-Nov-2022	31-Oct-2023
☒	LISN	R&S	ESH2-Z5	860014/024	1-Nov-2022	31-Oct-2023
☐	LISN	ETS-Lindgren	3816/2SH	00201088	1-Nov-2022	31-Oct-2023
☒	Test Software	Audix	e3	Software Version: 9 20151119i		

RF Conducted Test Equipment List						
Used	**Equipment**	**Manufacturer**	**Model No.**	**Serial Number**	**Cal. date**	**Cal. Due date**
☒	EXA Spectrum Analyzer	KEYSIGHT	N9010A	MY51440197	15-Apr-2022	14-Apr-2023
					14-Apr-2023	13-Apr-2024
☐	EXA Spectrum Analyzer	KEYSIGHT	N9020A	MY51286807	1-Nov-2022	31-Oct-2023
☒	USB Wideband Power Sensor	KEYSIGHT	U2021XA	MY55430035	3-Nov-2022	2-Nov-2023

4. TEST CONFIGURATION

4.1 ENVIRONMENTAL CONDITIONS FOR TESTING

4.1.1 Normal or Extreme Test Conditions

Environment Parameter	Selected Values During Tests		
Test Condition	Ambient		
	Temperature (°C)	Voltage(V)	Relative Humidity (%)
NT/NV	+15 to +35	3.87	20 to 75
Remark: 1) NV: Normal Voltage; NT: Normal Temperature			

4.1.2 Record of Normal Environment and Test Sample

Test Item	Temp. (°C)	Relative Humidity (%)	Pressure (kPa)	Sample No.	Tested by
AC Power Line Conducted Emission	23.2	59	100.2	S202303221229-ZJA04/6	Andy Lin
Conducted Peak Output Power	22.8	57	100.2	S202303221229-ZJA01/6	Rain Wang
20 dB Bandwidth					
Carrier Frequencies Separation					
Number of Hopping Channel					
Dwell Time					
Conducted Out of Band Emission					
Radiated Emissions	24.2	66.0	99.0	S202303221229-ZJA04/6	Fire Huo
Band Edge Measurement					

4.2 TEST CHANNELS

Mode	Tx/Rx Frequency	Test RF Channel Lists		
		Lowest(L)	Middle(M)	Highest(H)
GFSK (DH1, DH3, DH5)	2402 MHz to 2480 MHz	Channel 0	Channel 39	Channel 78
		2402 MHz	2441 MHz	2480 MHz
π/4DQPSK (DH1, DH3, DH5)	2402 MHz to 2480 MHz	Channel 0	Channel 39	Channel 78
		2402 MHz	2441 MHz	2480 MHz
8DPSK (DH1, DH3, DH5)	2402 MHz to 2480 MHz	Channel 0	Channel 39	Channel 78
		2402 MHz	2441 MHz	2480 MHz

4.3 EUT TEST STATUS

Type of Modulation	Tx Function	Description
GFSK/π/4DQPSK/ 8DPSK	1Tx	1. Keep the EUT in continuously transmitting with Modulation test single 2. Keep the EUT in continuously transmitting with Modulation test Hopping Frequency.

Power Setting (Provided by the customer)
Power Setting: 9

Test Software (Provided by the customer)
Engineering mode: *#*#74655577#*#*

4.4 PRE-SCAN

4.4.1 Pre-scan under all packets at middle channel

Conducted Average Power (dBm) for packets									
Type of Modulation	**GFSK**			**π/4DQPSK**			**8DPSK**		
Packets	1-DH1	1-DH3	1-DH5	2-DH1	2-DH3	2-DH5	3-DH1	3-DH3	3-DH5
Power (dBm)	1.96	5.02	5.65	-0.14	2.81	3.42	-0.19	2.79	3.43

4.4.2 Worst-case data packets

Type of Modulation	Worst-case data rates
GFSK	1-DH5
π/4DQPSK	2-DH5
8DPSK	3-DH5

4.4.3 Tested channel detail

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data packets and antenna ports (if EUT with antenna diversity architecture). Following channel(s) was (were) selected for the final test as listed below.

Type of Modulation	**GFSK**			**π/4DQPSK**			**8DPSK**		
Data Packets	1-DH 1	1-DH 3	1-DH 5	2-DH 1	2-DH 3	2-DH 5	3-DH 1	3-DH 3	3-DH 5
Available Channel	0 to 78								
Test Item	**Test channel and choose of data packets**								
AC Power Line Conducted Emission	Frequency Hopping Channel 0 to 78								
	Link								
Conducted Peak Output Power	Channel 0 & 39 & 78								
	☐	☐	☒	☐	☐	☒	☐	☐	☒
20 dB Bandwidth	Channel 0 & 39 & 78								
	☐	☐	☒	☐	☐	☒	☐	☐	☒
Carrier Frequencies Separation	Frequency Hopping Channel 0 to 78								
	☐	☐	☒	☐	☐	☒	☐	☐	☒
Number of Hopping Channel	Frequency Hopping Channel 0 to 78								
	☐	☐	☒	☐	☐	☒	☐	☐	☒
Dwell Time	Channel 39								
	☒	☒	☒	☒	☒	☒	☒	☒	☒
Conducted Out of Band Emission	Channel 0 & 39 & 78								
	☐	☐	☒	☐	☐	☒	☐	☐	☒
Radiated Emissions	Channel 0 & 39 & 78								
	☐	☐	☒	☐	☐	☐	☐	☐	☐
Band Edge Measurements (Radiated)	Channel 0 & 78								
	☐	☐	☒	☐	☐	☐	☐	☐	☐

Remark:
1. The mark "☒" means is chosen for testing;
2. The mark "☐" means is not chosen for testing.

4.5 TEST SETUP

4.5.1 For Radiated Emissions test setup

Figure 1. Below 30MHz



Figure 2. 30MHz to 1GHz



Figure 3. Above 1GHz



4.5.2 For Conducted Emissions test setup



4.5.3 For Conducted RF test setup



4.6 SYSTEM TEST CONFIGURATION

For emissions testing, the equipment under test (EUT) setup to transmit continuously to simplify the measurement methodology. Care was taken to ensure proper power supply voltages during testing. During testing, radiated emission were performed with the EUT set to transmit at the channel with highest output power as worst-case scenario. It was powered by a 3.87V battery. Only the worst case data were recorded in this test report.

The signal is maximized through rotation and placement in the three orthogonal axes. The antenna height and polarization are varied during the search for maximum signal level. The antenna height is varied from 1 to 4 meters. Radiated emissions are taken at three meters unless the signal level is too low for measurement at that distance. If necessary, a pre-amplifier is used and/or the test is conducted at a closer distance. Therefore, all final radiated testing was performed with the EUT in orientation.

All readings are extrapolated back to the equivalent three meter reading using inverse scaling with distance. Analyzer resolution is 100 kHz or greater for frequencies below 1000 MHz. The resolution is 1 MHz or greater for frequencies above 1000 MHz. The spurious emissions more than 20 dB below the permissible value are not reported.

Radiated emission measurement were performed from the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.

4.7 DUTY CYCLE

Test Procedure: ANSI C63.10-2013 Clause 11.6.

Test Results

Modulation	Packets	On Time (msec)	Period (msec)	Duty Cycle (linear)	Duty Cycle (%)	Duty Cycle Factor (dB)	1/T Minimum VBW (kHz)
GFSK	1-DH5	2.895	3.750	0.7720	77.20	1.124	0.35

Remark:

1) Duty cycle= On Time/ Period;

2) Duty Cycle factor = 10 * log(1/ Duty cycle);

The test plots as follows

GFSK_ 1-DH5



5. RADIO TECHNICAL REQUIREMENTS SPECIFICATION

5.1 REFERENCE DOCUMENTS FOR TESTING

No.	Identity	Document Title
1	FCC 47 CFR Part 2	Frequency allocations and radio treaty matters; general rules and regulations
2	FCC 47 CFR Part 15	Radio Frequency Devices
3	ANSI C63.10-2013	American National Standard for Testing Unlicesed Wireless Devices
4	KDB 558074 D01 15.247 Meas Guidance v05r02	Guidance for compliance measurements on Digital Transmission Systems, Frequency Hopping Spread Spectrum system, and Hybrid system devices operating under Section 15.247 of the FCC rules

5.2 ANTENNA REQUIREMENT

Standard Requirement
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. **15.247(b) (4) requirement:** The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.
EUT Antenna:
Antenna in the interior of the equipment and no consideration of replacement. The gain of the antenna is 1.26 dBi.

5.3 CONDUCTED PEAK OUTPUT POWER

Test Requirement: FCC 47 CFR Part 15 Subpart C Section15.247 (b)(1)

Test Method: ANSI C63.10-2013 Section 7.8.5

Limit: For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt.
Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

Test Procedure: Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.

a) Use the following spectrum analyzer settings:
   1) Span: Approximately 5 x 20 dB bandwidth, centered on a hopping channel.
   2) RBW > 20 dB bandwidth of the emission being measured.
   3) VBW ≥ RBW.
   4) Sweep: Auto.
   5) Detector function: Peak.
   6) Trace: Max hold.

b) Allow trace to stabilize.
c) Use the marker-to-peak function to set the marker to the peak of the emission.
d) The indicated level is the peak output power, after any corrections for external attenuators and cables.
e) A plot of the test results and setup description shall be included in the test report.

Test Setup: Refer to section 4.5.3 for details.

Instruments Used: Refer to section 3 for details

Test Mode: Link mode

Test Results: **Please refer to Appendix A**

5.4 20 DB BANDWIDTH

Test Requirement: FCC 47 CFR Part 15 Subpart C Section 15.247 (a)(1)

Test Method: ANSI C63.10-2013 Section 6.9.2

Limit: None; for reporting purposes only.

Test Procedure: Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
Use the following spectrum analyzer settings:

a) Span = approximately 2 to 5 times the OBW, centered on a hopping channel.
b) RBW = 1% to 5% of the OBW.
c) VBW ≥ 3 x RBW
d) Sweep = auto;
e) Detector function = peak
f) Trace = max hold
g) All the trace to stabilize, use the marker-to-peak function to set the marker to the peak of the emission, use the marker-delta function to measure and record the 20dB down bandwidth of the emission.

Note: The cable loss and attenuator loss were offset into measure device as an amplitude offset.

Test Setup: Refer to section 4.5.3 for details.

Instruments Used: Refer to section 3 for details

Test Mode: Link mode

Test Results: **Please refer to Appendix A**

5.5 CARRIER FREQUENCIES SEPARATION

Test Requirement: FCC 47 CFR Part 15 Subpart C Section 15.247 (a)(1)

Test Method: ANSI C63.10-2013 Section 7.8.2

Limit: Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.
Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

Test Procedure: Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
Use the following spectrum analyzer settings:

a) Span: Wide enough to capture the peaks of two adjacent channels.
b) RBW: Start with the RBW set to approximately 30% of the channel spacing; adjust as necessary to best identify the center of each individual channel.
c) Video (or average) bandwidth (VBW) ≥ RBW.
d) Sweep: Auto.
e) Detector function: Peak.
f) Trace: Max hold.
g) Allow the trace to stabilize.
h) Use the marker-delta function to determine the separation between the peaks of the adjacent channels.

Note: The cable loss and attenuator loss were offset into measure device as an amplitude offset.

Test Setup: Refer to section 4.5.3 for details.

Instruments Used: Refer to section 3 for details

Test Mode: Link mode

Test Results: **Please refer to Appendix A**

5.6 NUMBER OF HOPPING CHANNEL

Test Requirement: FCC 47 CFR Part 15 Subpart C Section 15.247(b)(1)

Test Method: ANSI C63.10-2013 Section 7.8.3

Limit: Frequency hopping systems in the 2400 – 2483.5 MHz band shall use at least 15 non-overlapping channels.

Test Procedure: Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
Use the following spectrum analyzer settings:

a) Span: The frequency band of operation. Depending on the number of channels the device supports, it may be necessary to divide the frequency range of operation across multiple spans, to allow the individual channels to be clearly seen.
b) RBW < 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller.
c) VBW ≥ RBW.
d) Sweep: Auto.
e) Detector function: Peak.
f) Trace: Max hold.
g) Allow the trace to stabilize.

Note: The cable loss and attenuator loss were offset into measure device as an amplitude offset.

Test Setup: Refer to section 4.5.3 for details.

Instruments Used: Refer to section 3 for details

Test Mode: Link mode

Test Results: **Please refer to Appendix A**

5.7 DWELL TIME

Test Requirement: FCC 47 CFR Part 15 Subpart C Section 15.247(a)(1)

Test Method: ANSI C63.10-2013 Section 7.8.4

Limit: Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

Test Procedure: Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
Use the following spectrum analyzer settings:

a) Span = zero span, centered on a hopping channel
b) RBW shall be ≤ channel spacing and where possible RBW should be set >> 1 / T, where T is the expected dwell time per channel.
c) Sweep = As necessary to capture the entire dwell time per hopping channel; where possible use a video trigger and trigger delay so that the transmitted signal starts a little to the right of the start of the plot. The trigger level might need slight adjustment to prevent triggering when the system hops on an adjacent channel; a second plot might be needed with a longer sweep time to show two successive hops on a channel.
d) Detector function = peak
e) Trace = max hold
f) Use the marker-delta function to determine the dwell time

Note: The cable loss and attenuator loss were offset into measure device as an amplitude offset.

Test Setup: Refer to section 4.5.3 for details.

Instruments Used: Refer to section 3 for details

Test Mode: Link mode

Test Results: **Please refer to Appendix A**

5.8 CONDUCTED OUT OF BAND EMISSION

Test Requirement: FCC 47 CFR Part 15 Subpart C Section 15.247(d)

Test Method: ANSI C63.10-2013 Section 6.10.4 & Section 7.8.8

Limit: In any 100kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator in operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power.

Test Procedure: Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
Use the following spectrum analyzer settings:

Step 1: Measurement Procedure REF

a) Set instrument center frequency to 2400 MHz or 2483.5 MHz.
b) Wide enough to capture the peak level of the emission operating on the channel closest to the band edge, as well as any modulation products that fall outside of the authorized band of operation.
c) Set the RBW = 100 kHz.
d) Set the VBW ≥ 3 x RBW.
e) Detector = peak.
f) Sweep time = auto couple.
g) Sweep points ≥ 2 x Span/RBW
h) Trace mode = max hold.
i) Allow the trace to stabilize.
j) Set the marker on the emission at the band edge, or on the highest modulation product outside of the band, if this level is greater than that at the band edge. Enable the marker-delta function, and then use the marker-to-peak function to move the marker to the peak of the in-band emission.

Step 2: Measurement Procedure OOBE

a) Set RBW = 100 kHz.
b) Set VBW ≥ 300 kHz.
c) Detector = peak.
d) Sweep = auto couple.
e) Trace Mode = max hold.
f) Allow trace to fully stabilize.
g) Use the peak marker function to determine the maximum amplitude level.

Note: The cable loss and attenuator loss were offset into measure device as an amplitude offset.

Test Setup: Refer to section 4.5.3 for details.

Instruments Used: Refer to section 3 for details

Test Mode: Hopping Frequencies Transmitter mode

Test Results: **Please refer to Appendix A**

5.9 RADIATED SPURIOUS EMISSIONS

Test Requirement: FCC 47 CFR Part 15 Subpart C Section 15.205/15.209

Test Method: ANSI C63.10-2013 Section 6.3 & 6.5 & 6.6

Receiver Setup:

Frequency	RBW
0.009 MHz-0.150 MHz	200/300 kHz
0.150 MHz -30 MHz	9/10 kHz
30 MHz-1 GHz	100/120 kHz
Above 1 GHz	1 MHz

Limits:

Spurious Emissions

Frequency	Field strength (microvolt/meter)	Limit (dBμV/m)	Remark	Measurement distance (m)
0.009 MHz-0.490 MHz	2400/F(kHz)	--	--	300
0.490 MHz-1.705 MHz	24000/F(kHz)	--	--	30
1.705 MHz-30 MHz	30	--	--	30
30 MHz-88 MHz	100	40.0	Quasi-peak	3
88 MHz-216 MHz	150	43.5	Quasi-peak	3
216 MHz-960 MHz	200	46.0	Quasi-peak	3
960MHz-1GHz	500	54.0	Quasi-peak	3
Above 1 GHz	500	54.0	Average	3

Remark:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000 MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20 dB under any condition of modulation.

Test Setup: Refer to section 4.5.1 for details.

Test Procedures:

1. From 30 MHz to 1GHz test procedure as below:

1) The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic camber. The table was rotated 360 degrees to determine the position of the highest radiation.
2) The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
3) The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
4) For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rota table table was turned from 0 degrees to 360 degrees to find the maximum reading.
5) The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6) If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

2. Above 1GHz test procedure as below:

1) Different between above is the test site, change from Semi- Anechoic Chamber to fully Anechoic Chamber and change form table 0.8 meter to 1.5 meter (Above 18GHz the distance is 1 meter and table is 1.5 meter).

2) Test the EUT in the lowest channel, middle channel, the Highest channel
3) The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the Y axis positioning which it is worse case.
4) Repeat above procedures until all frequencies measured was complete.

Equipment Used: Refer to section 3 for details.

Test Result: Pass

The worst measurement data as follows:

Radiated Emission Test Data (9 kHz ~ 30 MHz):
The amplitude of spurious emissions attenuated more than 20 dB below the permissible value is not required to be report.

Radiated Emission Test Data (30 MHz ~ 1 GHz):
Worst-Case Configuration

Horizontal



No.	Frequency (MHz)	Reading (dBuV)	Correction factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	31.959	28.2	-5.1	23.1	40.0	-16.9	QP
2	42.63	31.6	-9.2	22.5	40.0	-17.5	QP
3	47.703	35.6	-13.3	22.4	40.0	-17.6	QP
4	104.798	30.4	-15.4	14.9	43.5	-28.6	QP
5	546.437	25.6	-1.1	24.5	46.0	-21.5	QP
6	862.802	24.0	3.8	27.7	46.0	-18.3	QP

Vertical



No.	Frequency (MHz)	Reading (dBuV)	Correction factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	31.735	26.5	-5.1	21.4	40.0	-18.6	QP
2	43.845	30.6	-10.5	20.2	40.0	-19.9	QP
3	48.039	33.2	-13.6	19.5	40.0	-20.5	QP
4	809.924	25.2	3.1	28.4	46.0	-17.7	QP
5	856.76	25.0	3.6	28.5	46.0	-17.5	QP
6	938.714	24.7	5.1	29.9	46.0	-16.2	QP

Radiated Emission Test Data (Above 1GHz):								
Lowest Channel:								
No.	**Frequency (MHz)**	**Reading (dBμV)**	**Correction factor (dB/m)**	**Result (dBμV/m)**	**Limit (dBμV/m)**	**Margin (dB)**	**Detector**	**Antenna Polaxis**
1	4804	40.2	-2.4	37.8	74	-36.2	Peak	Horizontal
2	4804	25.5	-2.4	23.1	54	-30.9	Average	Horizontal
3	7206	40.7	1.6	42.3	74	-31.7	Peak	Horizontal
4	7206	27.5	1.6	29.1	54	-24.9	Average	Horizontal
5	4804	41.2	-2.4	38.7	74	-35.3	Peak	Vertical
6	4804	25.8	-2.4	23.4	54	-30.6	Average	Vertical
7	7206	40.4	1.6	42.0	74	-32.0	Peak	Vertical
8	7206	27.8	1.6	29.4	54	-24.6	Average	Vertical
Middle Channel:								
1	4882	40.0	-2.4	37.7	74	-36.3	Peak	Horizontal
2	4882	25.4	-2.4	23.1	54	-30.9	Average	Horizontal
3	7323	39.9	1.7	41.6	74	-32.4	Peak	Horizontal
4	7323	27.0	1.7	28.7	54	-25.3	Average	Horizontal
5	4882	39.5	-2.4	37.2	74	-36.8	Peak	Vertical
6	4882	27.4	-2.4	25.0	54	-29.0	Average	Vertical
7	7323	40.5	1.7	42.2	74	-31.8	Peak	Vertical
8	7323	28.2	1.7	29.9	54	-24.1	Average	Vertical
Highest Channel:								
1	4960	42.5	-2.3	40.2	74	-33.8	Peak	Horizontal
2	4960	28.2	-2.3	25.9	54	-28.1	Average	Horizontal
3	7440	40.7	1.8	42.5	74	-31.5	Peak	Horizontal
4	7440	28.0	1.8	29.8	54	-24.2	Average	Horizontal
5	4960	41.0	-2.3	38.7	74	-35.3	Peak	Vertical
6	4960	28.7	-2.3	26.4	54	-27.6	Average	Vertical
7	7440	38.6	1.8	40.3	74	-33.7	Peak	Vertical
8	7440	26.6	1.8	28.4	54	-25.6	Average	Vertical

Remark:

1. Correct Factor = Antenna Factor + Cable Loss - Amplifier Gain, the value was added to Original Receiver Reading by the software automatically.
2. Result = Reading + Correct Factor.
3. Margin = Result – Limit

5.10 BAND EDGE MEASUREMENTS (RADIATED)

Test Requirement: FCC 47 CFR Part 15 Subpart C Section 15.205/15.209

Test Method: ANSI C63.10-2013 Section 6.10.5

Limits:

Radiated emissions which fall in the restricted bands, as defined in section 15.205(a), must also comply with the radiated emission limits specified in section 15.209(a).

Frequency	Limit (dBμV/m @3m)	Remark
30 MHz-88 MHz	40.0	Quasi-peak Value
88 MHz-216 MHz	43.5	Quasi-peak Value
216 MHz-960 MHz	46.0	Quasi-peak Value
960 MHz-1 GHz	54.0	Quasi-peak Value
Above 1 GHz	54.0	Average Value
	74.0	Peak Value

Test Setup: Refer to section 4.5.1 for details.

Test Procedures:

Radiated band edge measurements at 2390 MHz and 2483.5 MHz were made with the unit transmitting in the low end of the channel range and the high end closest to the restricted bands respectively. The emissions were made on the 966 Semi-Chamber. Use (resolution bandwidth (RBW) = 1 MHz, video bandwidth (VBW) = 3 MHz for peak levels and RBW = 1 MHz and VBW = 10 Hz or 1/T for average levels).

1. Use radiated spurious emission test procedure described in clause 5.10. The transmitter output (antenna port) was connected to the test receiver.
2. Set the PK and AV limit line.
3. Record the fundamental emission and emissions out of the band-edge.
4. Determine band-edge compliance as required.

Equipment Used: Refer to section 3 for details.

Test Result: Pass

The worst measurement data as follows:

Test Channel:	Lowest Channel	Ant. Polar. :	Horizontal



Frequency (MHz)	Peak level (dBuv/m)	Peak Limit (dBuv/m)	AV level (dBuv/m)	AV Limit (dBuv/m)	Conclusion
2390.0000	42.97	74.00	28.41	54.00	Pass

Test Channel:	Lowest Channel	Ant. Polar. :	Vertical



Frequency (MHz)	Peak level (dBuv/m)	Peak Limit (dBuv/m)	AV level (dBuv/m)	AV Limit (dBuv/m)	Conclusion
2390.0000	43.90	74.00	28.11	54.00	Pass

Test Channel:	Highest Channel	Ant. Polar. :	Horizontal



Frequency (MHz)	Peak level (dBuv/m)	Peak Limit (dBuv/m)	AV level (dBuv/m)	AV Limit (dBuv/m)	Conclusion
2483.5000	50.38	74.00	43.99	54.00	Pass

Test Channel:	Highest Channel	Ant. Polar. :	Vertical



Frequency (MHz)	Peak level (dBuv/m)	Peak Limit (dBuv/m)	AV level (dBuv/m)	AV Limit (dBuv/m)	Conclusion
2483.5000	44.68	74.00	36.46	54.00	Pass

5.11 CONDUCTED EMISSION

Test Requirement: 47 CFR Part 15C Section 15.207

Test Method: ANSI C63.10-2013 Section 6.2

Limits:

Frequency range (MHz)	Limits (dB(μV)	
	Quasi-peak	Average
0,15 to 0,50	66 to 56	56 to 46
0,50 to 5	56	46
5 to 30	60	50

Remark:

1. The lower limit shall apply at the transition frequencies.
2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 to 0.50 MHz.

Test Setup: Refer to section 4.5.2 for details.

Test Procedures:

Test frequency range :150KHz-30MHz

1) The mains terminal disturbance voltage test was conducted in a shielded room.
2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a 50Ω/50μH + 5Ω linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.
3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane,
4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.
5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.

Equipment Used: Refer to section 3 for details.

Test Result: Pass

The worst measurement data as follows:
Quasi Peak and Average:
Mode: BT Link

Live Line



No.	Frequency (MHz)	Reading (dBµV)	Correction factor(dB)	Result (dBµV)	Limit (dBµV)	Margin (dB)	Detector
1	0.182	10.95	10.02	20.97	54.39	-33.42	Average
2	0.182	31.95	10.02	41.97	64.39	-22.42	QP
3	0.486	21.24	10.04	31.28	46.24	-14.96	Average
4	0.486	29.24	10.04	39.28	56.24	-16.96	QP
5	1.070	15.53	10.06	25.59	46.00	-20.41	Average
6	1.070	24.53	10.06	34.59	56.00	-21.41	QP
7	1.614	17.51	10.11	27.62	46.00	-18.38	Average
8	1.614	25.51	10.11	35.62	56.00	-20.38	QP
9	2.270	15.60	10.14	25.74	46.00	-20.26	Average
10	2.270	24.60	10.14	34.74	56.00	-21.26	QP
11	16.083	16.48	10.92	27.40	50.00	-22.60	Average
12	16.083	32.48	10.92	43.40	60.00	-16.60	QP

Neutral Line



No.	Frequency (MHz)	Reading (dBµV)	Correction factor(dB)	Result (dBµV)	Limit (dBµV)	Margin (dB)	Detector
1	0.150	12.67	10.02	22.69	56.00	-33.31	Average
2	0.150	34.67	10.02	44.69	66.00	-21.31	QP
3	0.486	11.32	10.03	21.35	46.24	-24.89	Average
4	0.486	27.32	10.03	37.35	56.24	-18.89	QP
5	0.966	8.84	10.05	18.89	46.00	-27.11	Average
6	0.966	26.84	10.05	36.89	56.00	-19.11	QP
7	1.686	8.62	10.09	18.71	46.00	-27.29	Average
8	1.686	25.62	10.09	35.71	56.00	-20.29	QP
9	3.645	6.99	10.24	17.23	46.00	-28.77	Average
10	3.645	24.99	10.24	35.23	56.00	-20.77	QP
11	15.307	10.12	10.85	20.97	50.00	-29.03	Average
12	15.307	34.12	10.85	44.97	60.00	-15.03	QP

Remark:

1. Correct Factor = LISN Factor + Cable Loss + Pulse Limiter Factor, the value was added to Original Receiver Reading by the software automatically.
2. Result = Reading + Correct Factor.
3. Margin = Result - Limit
4. An initial pre-scan was performed on the Phase and neutral lines with peak detector. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission were detected.
5. All possible modes of operation were investigated, and testing at two nominal voltages of 240V/50Hz and 120V/60Hz, only the worst case emissions reported.

APPENDIX A RF TEST DATA

A.1 CONDUCTED PEAK OUTPUT POWER

Modulation	Packet Type	Channel	Peak Output Power (dBm)	Peak Output Power (mW)	Max. Avg. Power (dBm)	Limit (dBm)	Result
GFSK	DH5	0	9.742	9.423	7.97	20.97	PASS
		39	7.486	5.605	5.65		PASS
		78	7.812	6.042	5.88		PASS
π/4DQPSK	2-DH5	0	8.338	6.820	4.18		PASS
		39	7.643	5.812	3.42		PASS
		78	7.582	5.731	3.34		PASS
8DPSK	3-DH5	0	8.364	6.861	4.19		PASS
		39	7.688	5.872	3.43		PASS
		78	7.587	5.737	3.35		PASS

Test Graphs



Peak Output Power
GFSK_Channel 0



Peak Output Power
GFSK_Channel 39



Peak Output Power
GFSK_Channel 78



Peak Output Power
π/4DQPSK_Channel 0



Peak Output Power
π/4DQPSK_Channel 39



Peak Output Power
π/4DQPSK_Channel 78



Peak Output Power
8DPSK_Channel 0



Peak Output Power
8DPSK_Channel 39



Peak Output Power
8DPSK_Channel 78

Void

A.2 99% BANDWIDTH

Modulation	Channel	99% BW (MHz)
GFSK	0	0.85010
	39	0.85557
	78	0.84619
π/4DQPSK	0	1.1861
	39	1.1842
	78	1.1842
8DPSK	0	1.1942
	39	1.1929
	78	1.2028

Test Graphs

GFSK_DH5_Channel 0



π/4DQPSK_2-DH5_Channel 0



GFSK_DH5_Channel 39



π/4DQPSK_2-DH5_Channel 39

GFSK_DH5_Channel 78



π/4DQPSK_2-DH5_Channel 78



8DPSK_3-DH5_Channel 0



8DPSK_3-DH5_Channel 39



8DPSK_3-DH5_Channel 78

Void

A.3 20DB BANDWIDTH

Modulation	Channel	Center Frequency (MHz)	20 dB Bandwidth (MHz)
GFSK	0	2402 MHz	0.9525
	39	2441 MHz	0.9529
	78	2480 MHz	0.9518
π/4DQPSK	0	2402 MHz	1.284
	39	2441 MHz	1.284
	78	2480 MHz	1.284
8DPSK	0	2402 MHz	1.295
	39	2441 MHz	1.300
	78	2480 MHz	1.296

Test Graphs



GFSK_DH5_Channel 0



GFSK_DH5_Channel 39



GFSK_DH5_Channel 78



π/4DQPSK_2-DH5_Channel 0



π/4DQPSK_2-DH5_Channel 39



π/4DQPSK_2-DH5_Channel 78



8DPSK_3-DH5_Channel 0



8DPSK_3-DH5_Channel 39



8DPSK_3-DH5_Channel 78

Void

A.4 CARRIER FREQUENCIES SEPARATION

Modulation	Packet	Left Center frequency (MHz)	Right Center frequency (MHz)	Hopping Frequency Separation (MHz)	Limit (MHz)	Result
GFSK	DH5	2439.8302	2440.8317	1.0015	0.635	PASS
π/4DQPSK	2-DH5	2440.0246	2441.0264	1.0018	0.856	PASS
8DPSK	3-DH5	2439.9937	2441.0036	1.0099	0.867	PASS

Test Graphs



GFSK



π/4DQPSK



8DPSK

Void

A.5 CONDUCTED OUT OF BAND EMISSION

Non-Hopping

Modulation	Packet	Channel	OOB Emission Frequency (MHz)	OOB Emission Level (dBm)	Limit (dBm)	Over Limit (dB)	Result
GFSK	DH5	0	2400.00	-52.383	-10.53	-41.853	PASS
			2397.61	-51.283	-10.53	-40.753	PASS
			24820.8	-52.698	-10.53	-42.168	PASS
		39	24958.2	-52.267	-12.72	-39.547	PASS
		78	2483.50	-53.621	-12.46	-41	PASS
			24995.6	-50.959	-12.46	-38.499	PASS
π/4DQPSK	2-DH5	0	2400.00	-50.728	-13.9	-37	PASS
			24410.1	-51.877	-13.9	-37.977	PASS
		39	24250.9	-52.452	-14.39	-38.062	PASS
		78	2483.50	-53.326	-14.42	-39	PASS
			24390.7	-51.856	-14.42	-37.436	PASS
8DPSK	3-DH5	0	2400.00	-49.710	-13.69	-36	PASS
			24790.9	-52.370	-13.69	-38.680	PASS
		39	24774.0	-52.605	-14.3	-38.305	PASS
		78	2483.50	-53.638	-14.35	-39	PASS
			24993.8	-52.419	-14.35	-38.069	PASS

Hopping

Modulation	Packet	Channel	OOB Emission Frequency (MHz)	OOB Emission Level (dBm)	Limit (dBm)	Over Limit (dB)	Result
GFSK	DH5	Hopping	2397.03	-51.124	-10.34	-40.784	PASS
			2400.00	-53.037	-10.34	-42.697	PASS
			2483.50	-52.340	-12.41	-39.930	PASS
π/4DQPSK	2-DH5		2400.00	-51.169	-13.56	-37.609	PASS
			2483.50	-53.387	-14.6	-38.787	PASS
8DPSK	3-DH5		2400.00	-50.393	-13.52	-36.873	PASS
			2483.50	-52.992	-14.38	-38.612	PASS

Test Graphs



Out Of Band Emission
GFSK_DH5_Channel 0



Out Of Band Emission
π/4DQPSK_2-DH5_Channel 0



Spurious Emission
GFSK_DH5_Channel 0



Spurious Emission
π/4DQPSK_2-DH5_Channel 0



Out Of Band Emission
GFSK_DH5_Channel 39



Out Of Band Emission
π/4DQPSK_2-DH5_Channel 39



Spurious Emissions
GFSK_DH5_Channel 39



Spurious Emissions
π/4DQPSK_2-DH5_Channel 39



Out Of Band Emission
GFSK_DH5_Channel 78



Out Of Band Emission
π/4DQPSK_2-DH5_Channel 78



Spurious Emission
GFSK_DH5_Channel 78



Spurious Emission
π/4DQPSK_2-DH5_Channel 78



Out Of Band Emission
8DPSK_3-DH5_Channel 0



Spurious Emission
8DPSK_3-DH5_Channel 0