FCC RF Test Report

APPLICANT	:	CT Asia
EQUIPMENT	:	Mobile phone
BRAND NAME	:	BLU
MODEL NAME	:	Life Pure 8
MARKETING NAME	:	Life Pure 8
FCC ID	:	YHLBLULIFEPURE8
STANDARD	:	FCC 47 CFR Part 2, 22(H), 24(E)
CLASSIFICATION	:	PCS Licensed Transmitter Held to Ear (PCE)

The product was received on Aug. 23, 2014 and testing was completed on Sep. 11, 2014. We, SPORTON INTERNATIONAL (KUNSHAN) INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures given in ANSI / TIA / EIA-603-C-2004 and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL (KUNSHAN) INC., the test report shall not be reproduced except in full.

Reviewed by: Joseph Lin / Supervisor

Approved by: Jones Tsai / Manager

Testing Laboratory
2627

SPORTON INTERNATIONAL (KUNSHAN) INC.
No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P.R.C.

TABLE OF CONTENTS

SUMMARY OF TEST RESULT **4**

1 GENERAL DESCRIPTION **5**

1.1 Applicant 5
1.2 Manufacturer 5
1.3 Product Feature of Equipment Under Test 5
1.4 Product Specification subjective to this standard 6
1.5 Modification of EUT 6
1.6 Maximum ERP/EIRP Power, Frequency Tolerance, and Emission Designator 6
1.7 Testing Location 7
1.8 Applicable Standards 7

2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST **8**

2.1 Test Mode 8
2.2 Connection Diagram of Test System 11
2.3 Support Unit used in test configuration 12
2.4 Measurement Results Explanation Example 12

3 TEST RESULT **13**

3.1 Conducted Output Power Measurement 13
3.2 Peak-to-Average Ratio 15
3.3 Effective Radiated Power and Effective Isotropic Radiated Power Measurement 21
3.4 99% Occupied Bandwidth and 26dB Bandwidth Measurement 25
3.5 Band Edge Measurement 39
3.6 Conducted Spurious Emission Measurement 48
3.7 Field Strength of Spurious Radiation Measurement 59
3.8 Frequency Stability Measurement 65

4 LIST OF MEASURING EQUIPMENT **70**

5 UNCERTAINTY OF EVALUATION **72**

APPENDIX A. SETUP PHOTOGRAPHS

REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FG482303	Rev. 01	Initial issue of report	Sep. 25, 2014

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	§2.1046	Conducted Output Power	N/A	PASS	-
3.2	§24.232(d)	Peak-to-Average Ratio	<13 dB	PASS	-
3.3	§22.913(a)(2)	Effective Radiated Power	< 7 Watts	PASS	-
3.4	§2.1049 §22.917(b) §24.238(b)	Occupied Bandwidth	N/A	PASS	-
3.3	§2.1051 §22.917(a) §24.238(a)	Band Edge Measurement	< $43+10\log_{10}$(P[Watts])	PASS	-
3.6	§2.1051 §22.917(a) §24.238(a)	Conducted Spurious Emission	< $43+10\log_{10}$(P[Watts])	PASS	-
3.7	§2.1053 §22.917(a) §24.238(a)	Field Strength of Spurious Radiation	< $43+10\log_{10}$(P[Watts])	PASS	Under limit 23.17 dB at 5637.000 MHz
3.8	§2.1055 §22.355 §24.235	Frequency Stability for Temperature & Voltage	< 2.5 ppm for Part 22.355 Emission must remain In-band for 24.235	PASS	-

1 General Description

1.1 Applicant

CT Asia
Unit 01, 15/F, Seaview Centre, 139-141 Hoi bun road, Kwun Tong, Kowloon, Hongkong

1.2 Manufacturer

Ragentek Technology
D10/D11，No.3188, Xiupu Road, PuDong District, Shanghai

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Mobile phone
Brand Name	BLU
Model Name	Life Pure 8
Marketing Name	Life Pure 8
FCC ID	YHLBLULIFEPURE8
EUT supports Radios application	GSM/GPRS/WCDMA/HSPA WLAN 2.4GHz 802.11b/g/n HT20/ Bluetooth v3.0 + EDR/Bluetooth v4.0 LE
HW Version	V1.2
SW Version	V0.3
EUT Stage	Pre-Production

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Product Specification subjective to this standard

Product Specification subjective to this standard	
Tx Frequency	GSM850: 824.2 MHz ~ 848.8 MHz GSM1900: 1850.2 MHz ~ 1909.8MHz WCDMA Band V: 826.4 MHz ~ 846.6 MHz WCDMA Band II: 1852.4 MHz ~ 1907.6 MHz
Rx Frequency	GSM850: 869.2 MHz ~ 893.8 MHz GSM1900: 1930.2 MHz ~ 1989.8 MHz WCDMA Band V: 871.4 MHz ~ 891.6 MHz WCDMA Band II: 1932.4 MHz ~ 1987.6 MHz
Maximum Output Power to Antenna	GSM850 : 32.20 dBm GSM1900 : 29.08 dBm WCDMA Band V : 22.94 dBm WCDMA Band II : 23.05 dBm
Antenna Type	PIFA Antenna
Type of Modulation	GSM: GMSK GPRS: GMSK WCDMA : QPSK (Uplink) HSDPA : QPSK (Uplink) HSUPA : QPSK (Uplink)

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Maximum ERP/EIRP Power, Frequency Tolerance, and Emission Designator

FCC Rule	System	Type of Modulation	Maximum ERP/EIRP (W)	Frequency Tolerance (ppm)	Emission Designator
Part 22	GSM850 GSM	GMSK	0.5986	0.0347 ppm	249KGXW
Part 22	WCDMA Band V RMC 12.2Kbps	QPSK	0.0761	0.0478 ppm	4M20F9W
Part 24	GSM1900 GSM	GMSK	1.1390	0.0202 ppm	247KGXW
Part 24	WCDMA Band II RMC 12.2Kbps	QPSK	0.2829	0.0287 ppm	4M18F9W

1.7 Testing Location

Test Site	SPORTON INTERNATIONAL (KUNSHAN) INC.		
Test Site Location	No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P.R.C. TEL: +86-0512-5790-0158 FAX: +86-0512-5790-0958		
Test Site No.	**Sporton Site No.**		**FCC Registration No.**
	03CH01-KS	OTA01-KS	149928

Test Site	SPORTON INTERNATIONAL (SHENZHEN) INC.	
Test Site Location	No. 3 Building, the third floor of south, Shahe River west, Fengzeyuan warehouse, Nanshan District, Shenzhen, Guangdong, P.R.C. TEL: +86-755-3320-2398	
Test Site No.	**Sporton Site No.**	**FCC Registration No.**
	TH01-SZ	831040

1.8 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC 47 CFR Part 2, 22(H), 24(E)
- ANSI / TIA / EIA-603-C-2004
- FCC KDB 971168 D01 Power Meas. License Digital Systems v02r01

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

2.1 Test Mode

Antenna port conducted and radiated test items were performed according to KDB 971168 D01 Power Meas. License Digital Systems v02r01 with maximum output power.

Radiated measurements were performed with rotating EUT in different three orthogonal test planes to find the maximum emission.

Frequency range investigated for radiated emission: 30MHz to 10th harmonic.

Test Modes		
Band	**Radiated TCs**	**Conducted TCs**
GSM 850	■ GSM Link	■ GSM Link
GSM 1900	■ GSM Link	■ GSM Link
WCDMA Band V	■ RMC 12.2Kbps Link	■ RMC 12.2Kbps Link
WCDMA Band II	■ RMC 12.2Kbps Link	■ RMC 12.2Kbps Link

Note: The maximum power levels are chosen to test as the worst case configuration as follows:

GSM mode for GMSK modulation,

RMC 12.2Kbps mode for WCDMA band V,

RMC 12.2Kbps mode for WCDMA band II, only these modes were used for all tests.

Conducted Power Measurement Results:

For SIM1 Card

Conducted Power (*Unit: dBm)						
Band	**GSM850**			**GSM1900**		
Channel	**128**	**189**	**251**	**512**	**661**	**810**
Frequency	**824.2**	**836.4**	**848.8**	**1850.2**	**1880.0**	**1909.8**
GSM	32.19	**32.20**	32.16	29.07	**29.08**	29.04
GPRS class 8	32.18	32.19	32.15	29.06	29.07	29.05
GPRS class 10	31.35	31.36	31.32	28.14	28.15	28.12
GPRS class 11	29.58	29.59	29.56	26.32	26.33	26.28
GPRS class 12	28.86	28.87	28.78	25.51	25.52	25.48

Conducted Power (*Unit: dBm)						
Band	**WCDMA Band V**			**WCDMA Band II**		
Channel	**4132**	**4182**	**4233**	**9262**	**9400**	**9538**
Frequency	**826.4**	**836.4**	**846.6**	**1852.4**	**1880.0**	**1907.6**
AMR 12.2Kbps	22.90	22.92	22.65	23.01	23.04	23.00
RMC 12.2Kbps	22.91	**22.94**	22.67	23.03	**23.05**	23.01
HSDPA Subtest-1	21.70	21.72	21.65	22.10	22.12	22.08
HSDPA Subtest-2	21.75	21.79	21.71	22.07	22.09	22.05
HSDPA Subtest-3	21.30	21.32	21.26	21.60	21.64	21.56
HSDPA Subtest-4	21.26	21.28	21.21	21.59	21.61	21.53
HSUPA Subtest-1	19.72	19.73	19.63	20.00	20.01	19.98
HSUPA Subtest-2	19.73	19.74	19.65	20.03	20.05	20.01
HSUPA Subtest-3	20.70	20.71	20.68	20.86	20.88	20.85
HSUPA Subtest-4	19.56	19.59	19.52	19.60	19.61	19.59
HSUPA Subtest-5	20.90	20.92	20.85	20.96	20.98	20.94

For SIM2 Card

Conducted Power (*Unit: dBm)						
Band	**GSM850**			**GSM1900**		
Channel	**128**	**189**	**251**	**512**	**661**	**810**
Frequency	**824.2**	**836.4**	**848.8**	**1850.2**	**1880.0**	**1909.8**
GSM	32.16	**32.18**	32.13	29.02	**29.05**	29.00
GPRS class 8	32.15	32.17	32.11	29.00	29.03	28.99
GPRS class 10	31.30	31.32	31.29	28.07	28.11	28.04
GPRS class 11	29.53	29.56	29.51	26.27	26.29	26.25
GPRS class 12	28.82	28.85	28.75	25.48	25.50	25.45

Conducted Power (*Unit: dBm)						
Band	**WCDMA Band V**			**WCDMA Band II**		
Channel	**4132**	**4182**	**4233**	**9262**	**9400**	**9538**
Frequency	**826.4**	**836.4**	**846.6**	**1852.4**	**1880.0**	**1907.6**
AMR 12.2Kbps	22.88	22.90	22.62	23.00	23.01	22.97
RMC 12.2Kbps	22.89	**22.92**	22.63	23.01	**23.03**	22.98
HSDPA Subtest-1	21.68	21.71	21.62	22.06	22.10	22.06
HSDPA Subtest-2	21.73	21.77	21.70	22.07	22.08	22.03
HSDPA Subtest-3	21.29	21.30	21.23	21.60	21.63	21.55
HSDPA Subtest-4	21.25	21.27	21.20	21.58	21.60	21.52
HSUPA Subtest-1	19.70	19.71	19.60	19.96	20.00	19.97
HSUPA Subtest-2	19.69	19.73	19.58	20.01	20.02	20.00
HSUPA Subtest-3	20.65	20.70	20.63	20.85	20.86	20.83
HSUPA Subtest-4	19.53	19.58	19.50	19.56	19.60	19.58
HSUPA Subtest-5	20.85	20.90	20.81	20.95	20.96	20.92

2.2 Connection Diagram of Test System

<22H Tx Mode>



<24E Tx Mode>



2.3 Support Unit used in test configuration

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU 200	N/A	N/A	Unshielded, 1.8 m
2.	DC Power Supply	GWINSTEK	GPS-3030D	N/A	N/A	Unshielded, 1.8 m

2.4 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between RF conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level will be exactly the RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

The following shows an offset computation example with RF cable loss 7.5 dB and a 10dB attenuator.

Example :

Offset(dB) = RF cable loss(dB) + attenuator factor(dB).

= 7.5 + 10 = 17.5 (dB)

3 Test Result

3.1 Conducted Output Power Measurement

3.1.1 Description of the Conducted Output Power Measurement

A system simulator was used to establish communication with the EUT. Its parameters were set to enforce EUT transmitting at the maximum power. The measured power in the radio frequency on the transmitter output terminals shall be reported.

3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedures

1. The transmitter output port was connected to the system simulator.
2. Set EUT at maximum power through system simulator.
3. Select lowest, middle, and highest channels for each band and different modulation.
4. Measure the maximum burst average power for GSM and maximum average power for other modulation signal.

3.1.4 Test Setup



3.1.5 Test Result of Conducted Output Power

Cellular Band						
Modes	**GSM850 (GSM)**			**WCDMA Band V (RMC 12.2Kbps)**		
Channel	**128 (Low)**	**189 (Mid)**	**251 (High)**	**4132 (Low)**	**4182 (Mid)**	**4233 (High)**
Frequency (MHz)	**824.2**	**836.4**	**848.8**	**826.4**	**836.4**	**846.6**
Conducted Power (dBm)	32.19	32.20	32.16	22.91	22.94	22.67
Conducted Power (Watts)	1.66	1.66	1.64	0.20	0.20	0.18

PCS Band						
Modes	**GSM1900 (GSM)**			**WCDMA Band II (RMC 12.2Kbps)**		
Channel	**512 (Low)**	**661 (Mid)**	**810 (High)**	**9262 (Low)**	**9400 (Mid)**	**9538 (High)**
Frequency (MHz)	**1850.2**	**1880**	**1909.8**	**1852.4**	**1880**	**1907.6**
Conducted Power (dBm)	29.07	29.08	29.04	23.03	23.05	23.01
Conducted Power (Watts)	0.81	0.81	0.80	0.20	0.20	0.20

Note: maximum burst average power for GSM, and maximum average power for WCDMA.

3.2 Peak-to-Average Ratio

3.2.1 Description of the PAR Measurement

The peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.2.3 Test Procedures

1. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
2. For GSM/EGPRS operating modes:
   a. Set EUT in maximum power output.
   b. Set the RBW = 1MHz, VBW = 3MHz, Peak detector on spectrum analyzer for first trace.
   c. Set the RBW = 1MHz, VBW = 3MHz, RMS detector on spectrum analyzer for second trace.
   d. The wanted burst signal is triggered by spectrum analyzer, and measured respectively the peak level and Mean level without burst-off time, after system simulator has synchronized with the spectrum analyzer.
3. For UMTS operating modes:
   a. Set the CCDF (Complementary Cumulative Distribution Function) option on the spectrum analyzer.
   b. The highest RF powers were measured and recorded the maximum PAPR level associated with a probability of 0.1 %.
4. Record the deviation as Peak to Average Ratio.

3.2.4 Test Setup



3.2.5 Test Result of Peak-to-Average Ratio

PCS Band						
Modes	GSM1900 (GSM)			WCDMA Band II (RMC 12.2Kbps)		
Channel	512 (Low)	661 (Mid)	810 (High)	9262 (Low)	9400 (Mid)	9538 (High)
Frequency (MHz)	1850.2	1880	1909.8	1852.4	1880	1907.6
Peak-to-Average Ratio (dB)	0.27	0.27	0.27	3.19	3.22	3.25

3.2.6 Test Result (Plots) of Peak-to-Average Ratio

Band :	GSM 1900	Test Mode :	GSM Link (GMSK)

Peak-to-Average Ratio on Channel 512 (1850.2 MHz)



Date: 11.SEP.2014 21:16:39

Peak-to-Average Ratio on Channel 661 (1880.0 MHz)



Date: 11.SEP.2014 21:16:21

Peak-to-Average Ratio on Channel 810 (1909.8 MHz)



Band :	WCDMA Band II	Test Mode :	RMC 12.2Kbps Link (QPSK)

Peak-to-Average Ratio on Channel 9262 (1852.4 MHz)



Date: 4.SEP.2014 05:26:03

Peak-to-Average Ratio on Channel 9400 (1880.0 MHz)



Date: 4.SEP.2014 05:24:40

Peak-to-Average Ratio on Channel 9538 (1907.6 MHz)



Date: 4.SEP.2014 05:26:40

3.3 Effective Radiated Power and Effective Isotropic Radiated Power Measurement

3.3.1 Description of the ERP/EIRP Measurement

The substitution method, in ANSI / TIA / EIA-603-C-2004, was used for ERP/EIRP measurement, and the spectrum analyzer configuration follows KDB 971168 D01 Power Meas. License Digital Systems v02r01. The ERP of mobile transmitters must not exceed 7 Watts and the EIRP of mobile transmitters are limited to 2 Watts.

3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.3.3 Test Procedures

1. The testing follows FCC KDB 971168 v02r01 Section 5.2.1. (for CDMA/WCDMA), Section 5.2.2.2 (for GSM/GPRS/EDGE) and ANSI / TIA-603-C-2004 Section 2.2.17.
2. The EUT was placed on a turntable 1.5 meters high in a fully anechoic chamber.
3. The EUT was placed 3 meters from the receiving antenna, which was mounted on the antenna tower.
4. GSM operating modes: Set RBW= 1MHz, VBW= 3MHz, RMS detector over burst;
   UMTS operating modes: Set RBW= 100 kHz, VBW= 300 kHz, RMS detector over frame, and use channel power option with bandwidth=5MHz, per KDB 971168 D01.
5. The table was rotated 360 degrees to determine the position of the highest radiated power.
6. The height of the receiving antenna is adjusted to look for the maximum ERP/EIRP.
7. Taking the record of maximum ERP/EIRP.
8. A dipole antenna was substituted in place of the EUT and was driven by a signal generator.
9. The conducted power at the terminal of the dipole antenna is measured.
10. Repeat step 3 to step 5 to get the maximum ERP/EIRP of the substitution antenna.
11. ERP/EIRP = Ps + Et – Es + Gs = Ps + Rt – Rs + Gs
    Ps (dBm)：Input power to substitution antenna.
    Gs (dBi or dBd)：Substitution antenna Gain.
    Et = Rt + AF
    Es = Rs + AF
    AF (dB/m)：Receive antenna factor
    Rt：The highest received signal in spectrum analyzer for EUT.
    Rs：The highest received signal in spectrum analyzer for substitution antenna.

3.3.4 Test Setup



3.3.5 Test Result of ERP

GSM850 (GSM) Radiated Power ERP						
Horizontal Polarization						
Frequency (MHz)	**Rt (dBm)**	**Rs (dBm)**	**Ps (dBm)**	**Gs (dBd)**	**ERP (dBm)**	**ERP (W)**
824.20	-19.70	-48.12	0.00	-1.08	27.34	0.5422
836.40	-19.79	-48.28	0.00	-0.93	27.56	0.5698
848.80	-19.82	-48.35	0.00	-0.76	27.77	0.5986
Vertical Polarization						
Frequency (MHz)	**Rt (dBm)**	**Rs (dBm)**	**Ps (dBm)**	**Gs (dBd)**	**ERP (dBm)**	**ERP (W)**
824.20	-30.75	-47.97	0.00	-1.08	16.14	0.0411
836.40	-30.74	-48.01	0.00	-0.93	16.34	0.0430
848.80	-30.64	-48.05	0.00	-0.76	16.65	0.0463

WCDMA Band V (RMC 12.2Kbps) Radiated Power ERP						
Horizontal Polarization						
Frequency (MHz)	**Rt (dBm)**	**Rs (dBm)**	**Ps (dBm)**	**Gs (dBd)**	**ERP (dBm)**	**ERP (W)**
826.40	-29.08	-48.12	0.00	-1.08	17.96	0.0625
836.40	-28.53	-48.28	0.00	-0.93	18.82	0.0761
846.60	-28.81	-48.35	0.00	-0.76	18.78	0.0756
Vertical Polarization						
Frequency (MHz)	**Rt (dBm)**	**Rs (dBm)**	**Ps (dBm)**	**Gs (dBd)**	**ERP (dBm)**	**ERP (W)**
826.40	-39.93	-47.97	0.00	-1.08	6.96	0.0050
836.40	-39.43	-48.01	0.00	-0.93	7.65	0.0058
846.60	-39.48	-48.05	0.00	-0.76	7.81	0.0060

3.3.6 Test Result of EIRP

GSM1900 (GSM) Radiated Power EIRP						
Horizontal Polarization						
Frequency (MHz)	**Rt (dBm)**	**Rs (dBm)**	**Ps (dBm)**	**Gs (dBi)**	**EIRP (dBm)**	**EIRP (W)**
1850.20	-23.59	-51.88	0.00	1.96	30.25	1.0581
1880.00	-25.36	-52.99	0.00	2.00	29.63	0.9177
1909.80	-27.43	-54.28	0.00	1.98	28.83	0.7635
Vertical Polarization						
Frequency (MHz)	**Rt (dBm)**	**Rs (dBm)**	**Ps (dBm)**	**Gs (dBi)**	**EIRP (dBm)**	**EIRP (W)**
1850.20	-23.52	-52.13	0.00	1.96	30.57	1.1390
1880.00	-25.38	-53.17	0.00	2.00	29.79	0.9526
1909.80	-27.27	-54.13	0.00	1.98	28.84	0.7657

WCDMA Band II (RMC 12.2Kbps) Radiated Power EIRP						
Horizontal Polarization						
Frequency (MHz)	**Rt (dBm)**	**Rs (dBm)**	**Ps (dBm)**	**Gs (dBi)**	**EIRP (dBm)**	**EIRP (W)**
1852.40	-29.63	-51.88	0.00	1.96	24.21	0.2638
1880.00	-31.59	-52.99	0.00	2.00	23.40	0.2189
1907.60	-33.98	-54.28	0.00	1.98	22.28	0.1691
Vertical Polarization						
Frequency (MHz)	**Rt (dBm)**	**Rs (dBm)**	**Ps (dBm)**	**Gs (dBi)**	**EIRP (dBm)**	**EIRP (W)**
1852.40	-29.57	-52.13	0.00	1.96	24.52	0.2829
1880.00	-31.62	-53.17	0.00	2.00	23.55	0.2267
1907.60	-33.75	-54.13	0.00	1.98	22.36	0.1721

3.4 99% Occupied Bandwidth and 26dB Bandwidth Measurement

3.4.1 Description of 99% Occupied Bandwidth and 26dB Bandwidth Measurement

The 99% occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The emission bandwidth is defined as the width of the signal between two points, located at the 2 sides of the carrier frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.

3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.4.3 Test Procedures

1. The testing follows FCC KDB 971168 v02r01 Section 4.2.
2. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
3. The RF output of the EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
4. The 99% occupied bandwidth were measured, set RBW= 1% of span, VBW= 3*RBW, sample detector, trace maximum hold.
5. The 26dB bandwidth were measured, set RBW= 1% of EBW, VBW= 3*RBW, peak detector, trace maximum hold.

3.4.4 Test Setup



3.4.5 Test Result of Occupied Bandwidth and 26dB Bandwidth

Cellular Band			
Modes	**GSM850 (GSM)**		
Channel	**128(Low)**	**189(Mid)**	**251(High)**
Frequency (MHz)	**824.2**	**836.4**	**848.8**
99% OBW (MHz)	247.47	246.02	248.91
26dB BW (MHz)	305.40	305.40	308.20

PCS Band			
Modes	**GSM1900 (GSM)**		
Channel	**512(Low)**	**661(Mid)**	**810(High)**
Frequency (MHz)	**1850.2**	**1880**	**1909.8**
99% OBW (MHz)	247.47	244.57	246.02
26dB BW (MHz)	311.10	311.10	283.60

Cellular Band			
Modes	**WCDMA Band V (RMC 12.2Kbps)**		
Channel	**4132 (Low)**	**4182 (Mid)**	**4233 (High)**
Frequency (MHz)	**826.4**	**836.4**	**846.6**
99% OBW (MHz)	4.18	4.17	4.20
26dB BW (MHz)	4.70	4.67	4.70

PCS Band			
Modes	**WCDMA Band II (RMC 12.2Kbps)**		
Channel	**9262 (Low)**	**9400 (Mid)**	**9538 (High)**
Frequency (MHz)	**1852.4**	**1880**	**1907.6**
99% OBW (MHz)	4.18	4.17	4.17
26dB BW (MHz)	4.67	4.69	4.69

3.4.6 Test Result (Plots) of Occupied Bandwidth and 26dB Bandwidth

Band :	GSM 850	Test Mode :	GSM Link (GMSK)

99% Occupied Bandwidth Plot on Channel 128 (824.2 MHz)



Date: 4.SEP.2014 04:41:56

26dB Bandwidth Plot on Channel 128 (824.2 MHz)



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	824.2116 MHz	25.18 dBm	ndB down	305.4 kHz
T1		1	824.0495 MHz	-1.29 dBm	ndB	26.00 dB
T2		1	824.3548 MHz	-0.29 dBm	Q factor	2699.2

Date: 4.SEP.2014 04:36:00

99% Occupied Bandwidth Plot on Channel 189 (836.4 MHz)



Date: 4.SEP.2014 04:40:42

26dB Bandwidth Plot on Channel 189 (836.4 MHz)



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	836.468 MHz	25.35 dBm	ndB down	305.4 kHz
T1		1	836.2495 MHz	-1.12 dBm	ndB	26.00 dB
T2		1	836.5548 MHz	-0.84 dBm	Q factor	2739.3

Date: 4.SEP.2014 04:37:07

99% Occupied Bandwidth Plot on Channel 251 (848.8 MHz)



Date: 4.SEP.2014 04:39:34

26dB Bandwidth Plot on Channel 251 (848.8 MHz)



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	848.787 MHz	24.90 dBm	ndB down	308.2 kHz
T1		1	848.6466 MHz	-1.67 dBm	ndB	26.00 dB
T2		1	848.9548 MHz	-1.88 dBm	Q factor	2753.6

Date: 4.SEP.2014 04:38:14

Band :	GSM 1900	Test Mode :	GSM Link (GMSK)

99% Occupied Bandwidth Plot on Channel 512 (1850.2 MHz)



Date: 4.SEP.2014 06:07:37

26dB Bandwidth Plot on Channel 512 (1850.2 MHz)



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	1.8501957 GHz	21.56 dBm	ndB down	311.1 kHz
T1		1	1.8500452 GHz	-4.83 dBm	ndB	26.00 dB
T2		1	1.8503563 GHz	-4.57 dBm	Q factor	5946.4

Date: 4.SEP.2014 06:12:53

99% Occupied Bandwidth Plot on Channel 661 (1880.0 MHz)



Date: 4.SEP.2014 06:06:32

26dB Bandwidth Plot on Channel 661 (1880.0 MHz)



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	1.8800217 GHz	21.19 dBm	ndB down	311.1 kHz
T1		1	1.8798452 GHz	-4.20 dBm	ndB	26.00 dB
T2		1	1.8801563 GHz	-5.25 dBm	Q factor	6042.3

Date: 4.SEP.2014 06:14:13

99% Occupied Bandwidth Plot on Channel 810 (1909.8 MHz)



Date: 4.SEP.2014 06:08:32

26dB Bandwidth Plot on Channel 810 (1909.8 MHz)



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	1.909868 GHz	23.96 dBm	ndB down	283.6 kHz
T1		1	1.9096596 GHz	-2.14 dBm	ndB	26.00 dB
T2		1	1.9099433 GHz	-3.85 dBm	Q factor	6733.3

Date: 4.SEP.2014 06:15:56

Band :	WCDMA Band V	Test Mode :	RMC 12.2Kbps Link (QPSK)

99% Occupied Bandwidth Plot on Channel 4132 (826.4 MHz)



Date: 4.SEP.2014 05:11:42

26dB Bandwidth Plot on Channel 4132 (826.4 MHz)



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	825.054 MHz	17.89 dBm	ndB down	4.703 MHz
T1		1	824.041 MHz	-7.73 dBm	ndB	26.00 dB
T2		1	828.744 MHz	-7.82 dBm	Q factor	175.4

Date: 4.SEP.2014 05:16:10

99% Occupied Bandwidth Plot on Channel 4182 (836.4 MHz)



Date: 4.SEP.2014 05:12:36

26dB Bandwidth Plot on Channel 4182 (836.4 MHz)



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	836.993 MHz	18.76 dBm	ndB down	4.674 MHz
T1		1	834.07 MHz	-6.51 dBm	ndB	26.00 dB
T2		1	838.744 MHz	-7.54 dBm	Q factor	179.1

Date: 4.SEP.2014 05:15:21

99% Occupied Bandwidth Plot on Channel 4233 (846.6 MHz)



Date: 4.SEP.2014 05:13:21

26dB Bandwidth Plot on Channel 4233 (846.6 MHz)



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	845.717 MHz	18.15 dBm	ndB down	4.703 MHz
T1		1	844.256 MHz	-7.20 dBm	ndB	26.00 dB
T2		1	848.959 MHz	-8.50 dBm	Q factor	179.8

Date: 4.SEP.2014 05:14:48

Band :	WCDMA Band II	Test Mode :	RMC 12.2Kbps Link (QPSK)

99% Occupied Bandwidth Plot on Channel 9262 (1852.4 MHz)



Date: 4.SEP.2014 05:30:36

26dB Bandwidth Plot on Channel 9262 (1852.4 MHz)



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	1.851546 GHz	18.07 dBm	ndB down	4.674 MHz
T1		1	1.850056 GHz	-7.80 dBm	ndB	26.00 dB
T2		1	1.85473 GHz	-7.10 dBm	Q factor	396.1

Date: 4.SEP.2014 05:34:40

99% Occupied Bandwidth Plot on Channel 9400 (1880.0 MHz)



Date: 4.SEP.2014 05:31:46

26dB Bandwidth Plot on Channel 9400 (1880.0 MHz)



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	1.879132 GHz	17.06 dBm	ndB down	4.689 MHz
T1		1	1.877656 GHz	-9.89 dBm	ndB	26.00 dB
T2		1	1.882344 GHz	-8.69 dBm	Q factor	400.8

Date: 4.SEP.2014 05:33:59

99% Occupied Bandwidth Plot on Channel 9538 (1907.6 MHz)



Date: 4.SEP.2014 05:32:26

26dB Bandwidth Plot on Channel 9538 (1907.6 MHz)



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	1.906746 GHz	16.01 dBm	ndB down	4.689 MHz
T1		1	1.905256 GHz	-11.13 dBm	ndB	26.00 dB
T2		1	1.909944 GHz	-10.05 dBm	Q factor	406.7

Date: 4.SEP.2014 05:33:15

3.5 Band Edge Measurement

3.5.1 Description of Band Edge Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least 43 + 10 log (P) dB.

3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.5.3 Test Procedures

1. The testing follows FCC KDB 971168 v02r01 Section 6.0.
2. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by an RF cable and attenuator. The path loss was compensated to the results for each measurement.
4. The band edges of low and high channels for the highest RF powers were measured.
5. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
6. The limit line is derived from 43 + 10log(P) dB below the transmitter power P(Watts)
   = P(W) - [43 + 10log(P)] (dB)
   = [30 + 10log(P)] (dBm) - [43 + 10log(P)] (dB)
   = -13dBm.

3.5.4 Test Setup



3.5.5 Test Result (Plots) of Conducted Band Edge

Band :	GSM850	**Test Mode :**	GSM Link (GMSK)
Correction Factor :	0.12 dB	**Maximum 26dB Bandwidth :**	0.308MHz
Band Edge :	-17.01dBm	**Measurement Value :**	-17.13dBm

Lower Band Edge Plot on Channel 128 (824.2 MHz)



Date: 4.SEP.2014 04:43:43

1. Correction Factor(dB)= 10log(1% Emission BW/RBW)

2. Band Edge= Measurement Value + Correction Factor(dB)

Band :	GSM850	Test Mode :	GSM Link (GMSK)
Correction Factor :	0.12 dB	Maximum 26dB Bandwidth :	0.308MHz
Band Edge :	-16.57dBm	Measurement Value :	-16.69dBm

Higher Band Edge Plot on Channel 251 (848.8 MHz)



Date: 4.SEP.2014 04:44:50

1. Correction Factor(dB)= 10log(1% Emission BW/RBW)

2. Band Edge= Measurement Value + Correction Factor(dB)

Band :	GSM1900	Test Mode :	GSM Link (GMSK)
Correction Factor :	0.16dB	Maximum 26dB Bandwidth :	0.311MHz
Band Edge :	-18.05dBm	Measurement Value :	-18.21dBm

Lower Band Edge Plot on Channel 512 (1850.2 MHz)



Date: 4.SEP.2014 06:18:35

1. Correction Factor(dB)= 10log(1% Emission BW/RBW)

2. Band Edge= Measurement Value + Correction Factor(dB)

Band :	GSM1900	Test Mode :	GSM Link (GMSK)
Correction Factor :	0.16dB	Maximum 26dB Bandwidth :	0.311MHz
Band Edge :	-19.40dBm	Measurement Value :	-19.56dBm

Higher Band Edge Plot on Channel 810 (1909.8 MHz)



Date: 4.SEP.2014 06:17:09

1. Correction Factor(dB)= 10log(1% Emission BW/RBW)

2. Band Edge= Measurement Value + Correction Factor(dB)

Band :	WCDMA Band V	**Test Mode :**	RMC 12.2Kbps Link (QPSK)
Correction Factor :	-3.28dB	**Maximum 26dB Bandwidth :**	4.700MHz
Band Edge :	-26.84dBm	**Measurement Value :**	-23.56dBm

Lower Band Edge Plot on Channel 4132 (826.4 MHz)



Date: 4.SEP.2014 05:17:32

1. Correction Factor(dB)= 10log(1% Emission BW/RBW)

2. Band Edge= Measurement Value + Correction Factor(dB)

Band :	WCDMA Band V	**Test Mode :**	RMC 12.2Kbps Link (QPSK)
Correction Factor :	-3.28dB	**Maximum 26dB Bandwidth :**	4.700MHz
Band Edge :	-26.09dBm	**Measurement Value :**	-22.81dBm

Higher Band Edge Plot on Channel 4233 (846.6 MHz)



Date: 4.SEP.2014 05:18:11

1. Correction Factor(dB)= 10log(1% Emission BW/RBW)

2. Band Edge= Measurement Value + Correction Factor(dB)

Band :	WCDMA Band II	Test Mode :	RMC 12.2Kbps Link (QPSK)
Correction Factor :	-3.29dB	Maximum 26dB Bandwidth :	4.690MHz
Band Edge :	-28.70dBm	Measurement Value :	-25.41dBm

Lower Band Edge Plot on Channel 9262 (1852.4 MHz)



Date: 4.SEP.2014 05:29:20

1. Correction Factor(dB)= 10log(1% Emission BW/RBW)

2. Band Edge= Measurement Value + Correction Factor(dB)

Band :	WCDMA Band II	**Test Mode :**	RMC 12.2Kbps Link (QPSK)
Correction Factor :	-3.29dB	**Maximum 26dB Bandwidth :**	4.690MHz
Band Edge :	-30.84dBm	**Measurement Value :**	-27.55dBm

Higher Band Edge Plot on Channel 9538 (1907.6 MHz)



Date: 4.SEP.2014 05:28:45

1. Correction Factor(dB)= 10log(1% Emission BW/RBW)

2. Band Edge= Measurement Value + Correction Factor(dB)

3.6 Conducted Spurious Emission Measurement

3.6.1 Description of Conducted Spurious Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least 43 + 10 log (P) dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10th harmonic.

3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.6.3 Test Procedures

1. The testing follows FCC KDB 971168 v02r01 Section 6.0.
2. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by an RF cable and attenuator. The path loss was compensated to the results for each measurement.
4. The middle channel for the highest RF power within the transmitting frequency was measured.
5. The conducted spurious emission for the whole frequency range was taken.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
7. The limit line is derived from 43 + 10log(P) dB below the transmitter power P(Watts)
   = P(W) - [43 + 10log(P)] (dB)
   = [30 + 10log(P)] (dBm) - [43 + 10log(P)] (dB)
   = -13dBm.

3.6.4 Test Setup



3.6.5 Test Result (Plots) of Conducted Spurious Emission

Band :	GSM850	Channel :	CH189
Test Mode :	GSM Link (GMSK)	Frequency :	836.4 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz



Date: 4.SEP.2014 04:47:37

Conducted Spurious Emission Plot between 1GHz ~ 3GHz



Date: 4.SEP.2014 04:50:09

Conducted Spurious Emission Plot between 3GHz ~ 7GHz



Date: 4.SEP.2014 04:51:50

Conducted Spurious Emission Plot between 7GHz ~ 9GHz



Date: 4.SEP.2014 04:53:14

Band :	GSM1900	Channel :	CH661
Test Mode :	GSM Link (GMSK)	Frequency :	1880.0 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz



Date: 4.SEP.2014 05:59:12

Conducted Spurious Emission Plot between 1GHz ~ 3GHz



Date: 4.SEP.2014 05:58:16

Conducted Spurious Emission Plot between 3GHz ~ 7GHz



Date: 4.SEP.2014 05:51:23

Conducted Spurious Emission Plot between 7GHz ~ 13.6GHz



Date: 4.SEP.2014 05:50:24

Conducted Spurious Emission Plot between 13.6GHz ~ 19.1GHz



Date: 4.SEP.2014 05:49:29

Band :	WCDMA Band V	Channel :	CH4182
Test Mode :	RMC 12.2Kbps Link (QPSK)	Frequency :	836.4 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz



Date: 4.SEP.2014 05:04:10

Conducted Spurious Emission Plot between 1GHz ~ 3GHz



Date: 4.SEP.2014 05:01:19

Conducted Spurious Emission Plot between 3GHz ~ 7GHz



Date: 4.SEP.2014 05:00:19

Conducted Spurious Emission Plot between 7GHz ~ 9GHz



Date: 4.SEP.2014 04:58:55

Band :	WCDMA Band II	Channel :	CH9400
Test Mode :	RMC 12.2Kbps Link (QPSK)	Frequency :	1880.0 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz



Date: 4.SEP.2014 05:42:25

Conducted Spurious Emission Plot between 1GHz ~ 3GHz



Date: 4.SEP.2014 05:43:38

Conducted Spurious Emission Plot between 3GHz ~ 7GHz



Date: 4.SEP.2014 05:45:24

Conducted Spurious Emission Plot between 7GHz ~ 13.6GHz



Date: 4.SEP.2014 05:46:20

Conducted Spurious Emission Plot between 13.6GHz ~ 19.1GHz



Date: 4.SEP.2014 05:47:13

3.7 Field Strength of Spurious Radiation Measurement

3.7.1 Description of Field Strength of Spurious Radiated Measurement

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least 43 + 10 log (P) dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

3.7.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.7.3 Test Procedures

1. The testing follows FCC KDB 971168 v02r01 Section 5.8 and ANSI / TIA-603-C-2004 Section 2.2.12.
2. The EUT was placed on a rotatable wooden table 0.8 meters above the ground.
3. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
4. The table was rotated 360 degrees to determine the position of the highest spurious emission.
5. The height of the receiving antenna is varied between one meter and four meters to search for the maximum spurious emission for both horizontal and vertical polarizations.
6. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking record of maximum spurious emission.
7. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
8. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
9. Taking the record of output power at antenna port.
10. Repeat step 7 to step 8 for another polarization.
11. EIRP (dBm) = S.G. Power – Tx Cable Loss + Tx Antenna Gain
12. ERP (dBm) = EIRP - 2.15
13. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
14. The limit line is derived from 43 + 10log(P) dB below the transmitter power P(Watts)

    = P(W) - [43 + 10log(P)] (dB)

    = [30 + 10log(P)] (dBm) - [43 + 10log(P)] (dB)

    = -13dBm.

3.7.4 Test Setup

For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



3.7.5 Test Result of Field Strength of Spurious Radiated

Band :	GSM850	**Temperature :**	22~23°C
Test Mode :	GSM Link (GMSK)	**Relative Humidity :**	42~43%
Test Engineer :	Star Wei	**Polarization :**	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		

Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1672	-63.08	-13	-50.08	-57.06	-63.73	0.57	3.37	H	Pass
2510	-55.04	-13	-42.04	-56.20	-57.27	0.78	5.16	H	Pass
3344	-64.71	-13	-51.71	-64.34	-68.35	0.87	6.66	H	Pass

Band :	GSM850	**Temperature :**	22~23°C
Test Mode :	GSM Link (GMSK)	**Relative Humidity :**	42~43%
Test Engineer :	Star Wei	**Polarization :**	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		

Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1672	-57.28	-13	-44.28	-57.85	-57.93	0.57	3.37	V	Pass
2510	-46.89	-13	-33.89	-54.71	-49.12	0.78	5.16	V	Pass
3344	-64.36	-13	-51.36	-65.42	-68.00	0.87	6.66	V	Pass

Band :	GSM1900	**Temperature :**	22~23°C
Test Mode :	GSM Link (GMSK)	**Relative Humidity :**	42~43%
Test Engineer :	Star Wei	**Polarization :**	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3760	-60.98	-13	-47.98	-64.33	-67.36	0.78	7.16	H	Pass
5640	-57.06	-13	-44.06	-67.12	-65.60	1.04	9.58	H	Pass
7521	-55.62	-13	-42.62	-67.16	-65.73	1.35	11.46	H	Pass

Band :	GSM1900	**Temperature :**	22~23°C
Test Mode :	GSM Link (GMSK)	**Relative Humidity :**	42~43%
Test Engineer :	Star Wei	**Polarization :**	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3759	-55.59	-13	-42.59	-63.99	-61.97	0.78	7.16	V	Pass
5640	-53.85	-13	-40.85	-66.5	-62.39	1.04	9.58	V	Pass
7521	-52.89	-13	-39.89	-66.98	-63.00	1.35	11.46	V	Pass

Band :	WCDMA Band V	**Temperature :**	22~23°C
Test Mode :	RMC 12.2Kbps Link (QPSK)	**Relative Humidity :**	42~43%
Test Engineer :	Star Wei	**Polarization :**	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		

Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1672	-68.38	-13	-55.38	-59.81	-69.03	0.57	3.37	H	Pass
2512	-61.09	-13	-48.09	-59.76	-63.32	0.78	5.16	H	Pass
3344	-66.36	-13	-53.36	-65.99	-70.00	0.87	6.66	H	Pass

Band :	WCDMA Band V	**Temperature :**	22~23°C
Test Mode :	RMC 12.2Kbps Link (QPSK)	**Relative Humidity :**	42~43%
Test Engineer :	Star Wei	**Polarization :**	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		

Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1670	-66.86	-13	-53.86	-63.06	-67.51	0.57	3.37	V	Pass
2508	-52.43	-13	-39.43	-58.49	-54.66	0.78	5.16	V	Pass
3344	-64.75	-13	-51.75	-65.81	-68.39	0.87	6.66	V	Pass

Band :	WCDMA Band II	**Temperature :**	22~23°C
Test Mode :	RMC 12.2Kbps Link (QPSK)	**Relative Humidity :**	42~43%
Test Engineer :	Star Wei	**Polarization :**	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3759	-58.24	-13	-45.24	-61.83	-64.62	0.78	7.16	H	Pass
5637	-41.01	-13	-28.01	-55.44	-49.55	1.04	9.58	H	Pass
7521	-55.15	-13	-42.15	-66.69	-65.26	1.35	11.46	H	Pass

Band :	WCDMA Band II	**Temperature :**	22~23°C
Test Mode :	RMC 12.2Kbps Link (QPSK)	**Relative Humidity :**	42~43%
Test Engineer :	Star Wei	**Polarization :**	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3756	-55.06	-13	-42.06	-63.46	-61.44	0.78	7.16	V	Pass
5637	-36.17	-13	-23.17	-52.78	-44.71	1.04	9.58	V	Pass
7521	-53.16	-13	-40.16	-67.25	-63.27	1.35	11.46	V	Pass

3.8 Frequency Stability Measurement

3.8.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within ±0.00025% (±2.5ppm) of the center frequency.

3.8.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.8.3 Test Procedures for Temperature Variation

1. The testing follows FCC KDB 971168 v02r01 Section 9.0.
2. The EUT was set up in the thermal chamber and connected with the system simulator.
3. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
4. With power OFF, the temperature was raised in 10°C steps up to 50°C. The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

3.8.4 Test Procedures for Voltage Variation

1. The testing follows FCC KDB 971168 v02r01 Section 9.0.
2. The EUT was placed in a temperature chamber at 25±5° C and connected with the system simulator.
3. The power supply voltage to the EUT was varied from BEP to 115% of the nominal value measured at the input to the EUT.
4. The variation in frequency was measured for the worst case.

3.8.5 Test Setup



3.8.6 Test Result of Temperature Variation

Band :	GSM 850	Channel :	189
Limit (ppm) :	2.5	Frequency :	836.4 MHz

Temperature (°C)	GSM		Result
	Freq. Dev. (Hz)	Deviation (ppm)	
-30	-18	0.0347	PASS
-20	-16	0.0323	
-10	20	0.0108	
0	19	0.0096	
10	15	0.0048	
20(Ref.)	11	0.0000	
30	13	0.0024	
40	20	0.0108	
50	27	0.0191	

Band :	GSM 1900	Channel :	661
Limit (ppm) :	within authorized band	Frequency :	1880.0 MHz

Temperature (°C)	GSM		Result
	Freq. Dev. (Hz)	Deviation (ppm)	
-30	-26	0.0202	PASS
-20	-22	0.0181	
-10	-16	0.0149	
0	20	0.0043	
10	15	0.0016	
20(Ref.)	12	0.0000	
30	10	0.0011	
40	16	0.0021	
50	21	0.0048	

Note: The frequency fundamental emissions stay within the authorized frequency block based on the frequency deviation measured is small.

Band :	WCDMA Band V	Channel :	4182
Limit (ppm) :	2.5	Frequency :	836.4 MHz

Temperature (°C)	RMC 12.2Kbps		Result
	Freq. Dev. (Hz)	Deviation (ppm)	
-30	-25	0.0478	PASS
-20	-16	0.0371	
-10	-10	0.0299	
0	16	0.0012	
10	14	0.0012	
20(Ref.)	15	0.0000	
30	11	0.0048	
40	17	0.0024	
50	22	0.0084	

Band :	WCDMA Band II	Channel :	9400
Limit (ppm) :	within authorized band	Frequency :	1880.0 MHz

Temperature (°C)	RMC 12.2Kbps		Result
	Freq. Dev. (Hz)	Deviation (ppm)	
-30	-33	0.0287	PASS
-20	-23	0.0234	
-10	-16	0.0197	
0	25	0.0021	
10	24	0.0016	
20(Ref.)	21	0.0000	
30	31	0.0053	
40	35	0.0074	
50	40	0.0101	

Note: The frequency fundamental emissions stay within the authorized frequency block based on the frequency deviation measured is small.

3.8.7 Test Result of Voltage Variation

Band & Channel	Mode	Voltage (Volt)	Freq. Dev. (Hz)	Deviation (ppm)	Limit (ppm)	Result
GSM 850 CH189	GSM	3.8	11	0.0000	within authorized band	PASS
		BEP	20	0.0108		
		4.35	13	0.0024		
GSM 1900 CH661	GSM	3.8	12	0.0000		
		BEP	23	0.0059		
		4.35	14	0.0011		
WCDMA Band V CH4182	RMC 12.2Kbps	3.8	15	0.0000		
		BEP	20	0.0060		
		4.35	12	0.0036		
WCDMA Band II CH9400	RMC 12.2Kbps	3.8	21	0.0000		
		BEP	26	0.0027		
		4.35	22	0.0005		

Note:

1. Normal Voltage = 3.8V.
2. Battery End Point (BEP) = 3.5 V.
3. The frequency fundamental emissions stay within the authorized frequency block based on the frequency deviation measured is small.

4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101078	10Hz~40GHz	May 08, 2014	Sep. 04, 2014~ Sep. 11, 2014	May 07, 2015	Conducted (TH01-SZ)
Thermal Chamber	Hongzhangroup	LP-150U	HD20120425	-40℃~150℃	Feb. 21, 2014	Sep. 04, 2014~ Sep. 11, 2014	Feb. 20, 2015	Conducted (TH01-SZ)
EMI Test Receiver	R&S	ESCI	100534	9kHz~3GHz	Nov. 05, 2013	Sep. 03, 2014	Nov. 04, 2014	Radiation (03CH01-KS)
Spectrum Analyzer	R&S	FSP30	101399	9kHz~30GHz	May 04, 2014	Sep. 03, 2014	May 03, 2015	Radiation (03CH01-KS)
Bilog Antenna	SCHAFFNER	CBL6112D	23182	25MHz~2GHz	Jan. 08, 2014	Sep. 03, 2014	Jan. 07, 2015	Radiation (03CH01-KS)
Double Ridge Horn Antenna	ETS-Lindgren	3117	75959	1GHz~18GHz	Jan. 08, 2014	Sep. 03, 2014	Jan. 07, 2015	Radiation (03CH01-KS)
Active Horn Antenna	com-power	AHA-118	701030	1GHz~18GHz	Nov. 18, 2013	Sep. 03, 2014	Nov. 17, 2014	Radiation (03CH01-KS)
SHF-EHF Horn	Schwarzbeck	BBHA 9170	BBHA170249	15GHz~40GHz	Mar. 10, 2014	Sep. 03, 2014	Mar. 09, 2015	Radiation (03CH01-KS)
Amplifier	com-power	PA-103A	161073	1MHz~1GHz	May 04, 2014	Sep. 03, 2014	May 03, 2015	Radiation (03CH01-KS)
Amplifier	Agilent	8449B	3008A02371	1GHz~26.5GHz	Dec. 10, 2013	Sep. 03, 2014	Dec. 09, 2014	Radiation (03CH01-KS)
AC Power Source	Chroma	61601	F104090004	N/A	NCR	Sep. 03, 2014	NCR	Radiation (03CH01-KS)
Turn Table	MF	MF7802	N/A	0~360 degree	NCR	Sep. 03, 2014	NCR	Radiation (03CH01-KS)
Antenna Mast	MF	MF7802	N/A	1 m~4 m	NCR	Sep. 03, 2014	NCR	Radiation (03CH01-KS)

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSP 7	100819	9kHz~7GHz	May 04, 2014	Aug. 28, 2014	May 03, 2015	ERP/EIRP (OTA01-KS)
Switch Control Manframe	Agilent	3499A	MY42005452	N/A	N/A	Aug. 28, 2014	N/A	ERP/EIRP (OTA01-KS)
Dual 1-to-6(4) MW MUX	Agilent	N2276A	MY42000841	N/A	N/A	Aug. 28, 2014	N/A	ERP/EIRP (OTA01-KS)
Microwave Switch	Agilent	44476A	MY42002573	N/A	N/A	Aug. 28, 2014	N/A	ERP/EIRP (OTA01-KS)
Microwave Switch	Agilent	44476A	MY42002586	N/A	N/A	Aug. 28, 2014	N/A	ERP/EIRP (OTA01-KS)
Diagonal Dual Polarized Horn	ETS-Lindgren	3164-04	00066993	700MHz~6GHz	N/A	Aug. 28, 2014	N/A	ERP/EIRP (OTA01-KS)
Multi-Devices Controller	ETS-Lindgren	2090-OPT1	00066604	N/A	N/A	Aug. 28, 2014	N/A	ERP/EIRP (OTA01-KS)
Conical Log Spiral (Small)	ETS-Lindgren	3102	00066951	1~10GHz	N/A	Aug. 28, 2014	N/A	ERP/EIRP (OTA01-KS)
Turn Table	ETS-Lindgren	2088	N/A	Resolution : 0.1degree	N/A	Aug. 28, 2014	N/A	ERP/EIRP (OTA01-KS)
Limiting Amplifier	ETS-lindgren	109643	920326	10MHz~2.5GHz	N/A	Aug. 28, 2014	N/A	ERP/EIRP (OTA01-KS)
EMQuest	ETS-Lindgren	EMQ-100	1125	N/A	N/A	Aug. 28, 2014	N/A	ERP/EIRP (OTA01-KS)
Medium Duty Holder	ETS-Lindgren	2015	N/A	N/A	N/A	Aug. 28, 2014	N/A	ERP/EIRP (OTA01-KS)

5 Uncertainty of Evaluation

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	**2.5**