EMC TEST REPORT

SIEMIC
GLOBAL TESTING & CERTIFICATIONS
YOUR CHOICE FOR- TCB FCB CB NB CAB RCB

Report No.: 16071342-FCC-E

Supersede Report No: N/A

Applicant	BLU Products, Inc.
Product Name	Smartphone
Model No.	LIFE ONE X2 MINI
Serial No.	N/A
Test Standard	FCC Part 15 Subpart B Class B:2015, ANSI C63.4: 2014
Test Date	November 26 to December 12, 2016
Issue Date	December 13, 2016
Test Result	☑ Pass ☐ Fail
Equipment complied with the specification	☑
Equipment did not comply with the specification	☐

Loren Luo	David Huang	
Loren Luo Test Engineer	David Huang Checked By	

This test report may be reproduced in full only

Test result presented in this test report is applicable to the tested sample only

Issued by:

SIEMIC (SHENZHEN-CHINA) LABORATORIES

Zone A, Floor 1, Building 2 Wan Ye Long Technology Park

South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108

Phone: +86 0755 2601 4629801 Email: China@siemic.com.cn

Laboratories Introduction

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.

In addition to testing and certification, SIEMIC provides initial design reviews and compliance management throughout a project. Our extensive experience with China, Asia Pacific, North America, European, and International compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the global markets.

Accreditations for Conformity Assessment

Country/Region	Scope
USA	EMC, RF/Wireless, SAR, Telecom
Canada	EMC, RF/Wireless, SAR, Telecom
Taiwan	EMC, RF, Telecom, SAR, Safety
Hong Kong	RF/Wireless, SAR, Telecom
Australia	EMC, RF, Telecom, SAR, Safety
Korea	EMI, EMS, RF, SAR, Telecom, Safety
Japan	EMI, RF/Wireless, SAR, Telecom
Singapore	EMC, RF, SAR, Telecom
Europe	EMC, RF, SAR, Telecom, Safety

This page has been left blank intentionally.

CONTENTS

1. REPORT REVISION HISTORY 5

2. CUSTOMER INFORMATION 5

3. TEST SITE INFORMATION 5

4. EQUIPMENT UNDER TEST (EUT) INFORMATION 6

5. TEST SUMMARY 9

6. MEASUREMENTS, EXAMINATION AND DERIVED RESULTS 10

6.1 AC POWER LINE CONDUCTED EMISSIONS 10

6.2 RADIATED EMISSIONS 16

ANNEX A. TEST INSTRUMENT 21

ANNEX B. EUT AND TEST SETUP PHOTOGRAPHS 22

ANNEX C. TEST SETUP AND SUPPORTING EQUIPMENT 27

ANNEX D. USER MANUAL / BLOCK DIAGRAM / SCHEMATICS / PARTLIST 30

ANNEX E. DECLARATION OF SIMILARITY 31

1. Report Revision History

Report No.	Report Version	Description	Issue Date
16071342-FCC-E	NONE	Original	December 13, 2016

2. Customer information

Applicant Name	BLU Products, Inc.
Applicant Add	10814 NW 33rd St # 100 Doral, FL 33172
Manufacturer	BLU Products, Inc.
Manufacturer Add	10814 NW 33rd St # 100 Doral, FL 33172

3. Test site information

Lab performing tests	SIEMIC (Shenzhen-China) LABORATORIES
Lab Address	Zone A, Floor 1, Building 2 Wan Ye Long Technology Park South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108
FCC Test Site No.	718246
IC Test Site No.	4842E-1
Test Software	Radiated Emission Program-To Shenzhen v2.0

4. Equipment under Test (EUT) Information

Description of EUT:	Smartphone
Main Model:	LIFE ONE X2 MINI
Serial Model:	N/A
Antenna Gain:	GSM850: -0.5dBi PCS1900: 0.5dBi UMTS-FDD Band V: -0.5dBi UMTS-FDD Band IV: 0.5dBi UMTS-FDD Band II: 0.5dBi LTE Band II: 0.5dBi LTE Band IV: 0.5dBi LTE Band VII: 0.8dBi LTE Band XII: -0.5dBi LTE Band XVII: -0.5dBi WIFI: 1.6dBi Bluetooth/BLE:1.6dBi GPS: 0.5dBi
Antenna Type:	PIFA antenna
Input Power:	Adapter: Model: US-BM-1500 Input: AC 100-240V,50/60Hz, 0.25A Output: DC5V,1550mA Battery: Model: C705904300P Spec: 3.84V,3000mAh,11.52Wh Charging Limited Voltage: 4.4V
Equipment Category：	JBP

Type of Modulation:	GSM / GPRS: GMSK EGPRS: GMSK,8PSK UMTS-FDD: QPSK LTE Band: QPSK, 16QAM 802.11b/g/n: DSSS, OFDM Bluetooth: GFSK, π /4DQPSK, 8DPSK BLE: GFSK GPS:BPSK
RF Operating Frequency (ies):	GSM850 TX: 824.2 ~ 848.8 MHz; RX: 869.2 ~ 893.8 MHz PCS1900 TX: 1850.2 ~ 1909.8 MHz; RX: 1930.2 ~ 1989.8 MHz UMTS-FDD Band V TX: 826.4 ~ 846.6 MHz; RX: 871.4 ~ 891.6 MHz UMTS-FDD Band IV TX:1712.4 ~ 1752.6 MHz; RX : 2112.4 ~ 2152.6 MHz UMTS-FDD Band II TX:1852.4 ~ 1907.6 MHz; RX: 1932.4 ~ 1987.6 MHz LTE Band II TX: 1850.7 ~ 1909.3MHz; RX : 1930.7 ~ 1989.3 MHz LTE Band IV TX: 1710.7 ~ 1754.3 MHz; RX : 2110.7~ 2154.3 MHz LTE Band VII TX: 2502.5 ~ 2567.5 MHz; RX : 2622.5 ~ 2687.5 MHz LTE Band XII TX:699.7 ~ 715.3 MHz; RX : 729.7~ 745.3MHz LTE Band XVII TX: 706.5 ~ 713.5 MHz; RX : 736.5 ~ 743.5 MHz WIFI: 802.11b/g/n(20M): 2412-2462 MHz WIFI: 802.11n(40M): 2422-2452 MHz Bluetooth& BLE: 2402-2480 MHz GPS: 1575.42 MHz
Number of Channels:	GSM 850: 124CH PCS1900: 299CH UMTS-FDD Band V: 102CH UMTS-FDD Band IV: 202CH UMTS-FDD Band II: 277CH WIFI :802.11b/g/n(20M): 11CH WIFI :802.11n(40M): 7CH Bluetooth: 79CH BLE: 40CH GPS:1CH
Port:	USB Port, Earphone Port

Trade Name :	BLU
FCC ID:	YHLBLULOX2MN
Date EUT received:	November 25, 2016
Test Date(s):	November 26 to December 12, 2016

5. Test Summary

The product was tested in accordance with the following specifications.

All testing has been performed according to below product classification:

FCC Rules	Description of Test	Result
§15.107; ANSI C63.4: 2014	AC Power Line Conducted Emissions	Compliance
§15.109; ANSI C63.4: 2014	Radiated Emissions	Compliance

Measurement Uncertainty

Emissions		
Test Item	**Description**	**Uncertainty**
Band Edge and Radiated Spurious Emissions	Confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2 (for EUTs < 0.5m X 0.5m X 0.5m)	+5.6dB/-4.5dB
-	-	-

6. Measurements, Examination And Derived Results

6.1 AC Power Line Conducted Emissions

Temperature	24℃
Relative Humidity	53%
Atmospheric Pressure	1001mbar
Test date :	December 01, 2016
Tested By :	Loren Luo

Requirement(s):

<table>
<tr><th>Spec</th><th>Item</th><th>Requirement</th><th>Applicable</th></tr>
<tr><td>47CFR§15.107</td><td>a)</td><td>For Low-power radio-frequency devices that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 [mu] H/50 ohms line impedance stabilization network (LISN). The lower limit applies at the boundary between the frequencies ranges.
<table>
<tr><th rowspan="2">Frequency ranges (MHz)</th><th colspan="2">Limit (dBμV)</th></tr>
<tr><th>QP</th><th>Average</th></tr>
<tr><td>0.15 ~ 0.5</td><td>66 – 56</td><td>56 – 46</td></tr>
<tr><td>0.5 ~ 5</td><td>56</td><td>46</td></tr>
<tr><td>5 ~ 30</td><td>60</td><td>50</td></tr>
</table></td><td>☑</td></tr>
<tr><td>Test Setup</td><td colspan="3"> 

Note: 1.Support units were connected to second LISN.
2.Both of LISNs (AMN) are 80cm from EUT and at least 80cm from other units and other metal planes support units.</td></tr>
<tr><td>Procedure</td><td colspan="3">1. The EUT and supporting equipment were set up in accordance with the requirements of the standard on top of a 1.5m x 1m x 0.8m high, non-metallic table.
2. The power supply for the EUT was fed through a 50Ω /50mH EUT LISN, connected to filtered mains.</td></tr>
</table>

	3. The RF OUT of the EUT LISN was connected to the EMI test receiver via a low-loss coaxial cable. 4. All other supporting equipment were powered separately from another main supply. 5. The EUT was switched on and allowed to warm up to its normal operating condition. 6. A scan was made on the NEUTRAL line (for AC mains) or Earth line (for DC power) over the required frequency range using an EMI test receiver. 7. High peaks, relative to the limit line, The EMI test receiver was then tuned to the selected frequencies and the necessary measurements made with a receiver bandwidth setting of 10 kHz. 8. Step 7 was then repeated for the LIVE line (for AC mains) or DC line (for DC power).
Remark	
Result	☑ Pass ☐ Fail

Test Data ☑ Yes ☐ N/A

Test Plot ☑ Yes (See below) ☐ N/A

Test Mode :	USB Mode



Test Data

Phase Line Plot at 120Vac, 60Hz

No.	P/L	Frequency	Reading	Detector	Corrected	Result	Limit	Margin
		(MHz)	(dBuV)		(dB}	(dBuV)	(dBuV)	(dB)
1	L1	0.1524	45.02	QP	10.03	55.05	65.87	-10.82
2	L1	0.1524	27.27	AVG	10.03	37.30	55.87	-18.57
3	L1	0.1890	37.51	QP	10.03	47.54	64.08	-16.54
4	L1	0.1890	14.13	AVG	10.03	24.16	54.08	-29.92
5	L1	0.5127	42.50	QP	10.03	52.53	56.00	-3.47
6	L1	0.5127	30.92	AVG	10.03	40.95	46.00	-5.05
7	L1	0.7155	35.91	QP	10.03	45.94	56.00	-10.06
8	L1	0.7155	20.10	AVG	10.03	30.13	46.00	-15.87
9	L1	2.4042	36.26	QP	10.05	46.31	56.00	-9.69
10	L1	2.4042	24.69	AVG	10.05	34.74	46.00	-11.26
11	L1	13.0425	32.17	QP	10.20	42.37	60.00	-17.63
12	L1	13.0425	23.70	AVG	10.20	33.90	50.00	-16.10

Test Mode :	USB Mode



Test Data

Phase Neutral Plot at 120Vac, 60Hz

No.	P/L	Frequency	Reading	Detector	Corrected	Result	Limit	Margin
		(MHz)	(dBuV)		(dB}	(dBuV)	(dBuV)	(dB)
1	N	0.1656	42.02	QP	10.02	52.04	65.18	-13.14
2	N	0.1656	26.58	AVG	10.02	36.60	55.18	-18.58
3	N	0.3021	38.11	QP	10.02	48.13	60.18	-12.05
4	N	0.3021	24.64	AVG	10.02	34.66	50.18	-15.52
5	N	0.5049	42.90	QP	10.02	52.92	56.00	-3.08
6	N	0.5049	29.48	AVG	10.02	39.50	46.00	-6.50
7	N	0.6843	36.69	QP	10.02	46.71	56.00	-9.29
8	N	0.6843	22.95	AVG	10.02	32.97	46.00	-13.03
9	N	1.0665	35.83	QP	10.03	45.86	56.00	-10.14
10	N	1.0665	21.97	AVG	10.03	32.00	46.00	-14.00
11	N	13.1127	32.83	QP	10.18	43.01	60.00	-16.99
12	N	13.1127	26.30	AVG	10.18	36.48	50.00	-13.52

Test Mode :	USB Mode



Test Data

Phase Line Plot at 240Vac, 60Hz

No.	P/L	Frequency	Reading	Detector	Corrected	Result	Limit	Margin
		(MHz)	(dBuV)		(dB}	(dBuV)	(dBuV)	(dB)
1	L1	0.1578	43.85	QP	10.03	53.88	65.58	-11.70
2	L1	0.1578	23.64	AVG	10.03	33.67	55.58	-21.91
3	L1	0.4863	43.99	QP	10.03	54.02	56.23	-2.21
4	L1	0.4863	32.96	AVG	10.03	42.99	46.23	-3.24
5	L1	0.5205	43.82	QP	10.03	53.85	56.00	-2.15
6	L1	0.5205	32.90	AVG	10.03	42.93	46.00	-3.07
7	L1	0.8988	35.91	QP	10.03	45.94	56.00	-10.06
8	L1	0.8988	27.09	AVG	10.03	37.12	46.00	-8.88
9	L1	1.5540	35.14	QP	10.04	45.18	56.00	-10.82
10	L1	1.5540	26.00	AVG	10.04	36.04	46.00	-9.96
11	L1	10.6089	31.53	QP	10.16	41.69	60.00	-18.31
12	L1	10.6089	24.47	AVG	10.16	34.63	50.00	-15.37

Test Mode :	USB Mode



Test Data

Phase Neutral Plot at 240Vac,60Hz

No.	P/L	Frequency	Reading	Detector	Corrected	Result	Limit	Margin
		(MHz)	(dBuV)		(dB}	(dBuV)	(dBuV)	(dB)
1	N	0.1734	41.78	QP	10.02	51.80	64.80	-13.00
2	N	0.1734	31.97	AVG	10.02	41.99	54.80	-12.81
3	N	0.4698	43.48	QP	10.02	53.50	56.52	-3.02
4	N	0.4698	30.93	AVG	10.02	40.95	46.52	-5.57
5	N	0.5283	44.23	QP	10.02	54.25	56.00	-1.75
6	N	0.5283	31.51	AVG	10.02	41.53	46.00	-4.47
7	N	0.8715	38.09	QP	10.03	48.12	56.00	-7.88
8	N	0.8715	28.92	AVG	10.03	38.95	46.00	-7.05
9	N	1.1952	37.21	QP	10.03	47.24	56.00	-8.76
10	N	1.1952	28.57	AVG	10.03	38.60	46.00	-7.40
11	N	9.9225	33.55	QP	10.14	43.69	60.00	-16.31
12	N	9.9225	26.65	AVG	10.14	36.79	50.00	-13.21

6.2 Radiated Emissions

Temperature	24℃
Relative Humidity	53%
Atmospheric Pressure	1001mbar
Test date :	December 01, 2016
Tested By :	Loren Luo

Requirement(s):

<table>
<tr><th>Spec</th><th>Item</th><th>Requirement</th><th>Applicable</th></tr>
<tr><td>47CFR§15.109(d)</td><td>a)</td><td>Except higher limit as specified elsewhere in other section, the emissions from the low-power radio-frequency devices shall not exceed the field strength levels specified in the following table and the level of any unwanted emissions shall not exceed the level of the fundamental emission. The tighter limit applies at the band edges
<table>
<tr><th>Frequency range (MHz)</th><th>Field Strength (μV/m)</th></tr>
<tr><td>30 – 88</td><td>100</td></tr>
<tr><td>88 – 216</td><td>150</td></tr>
<tr><td>216 960</td><td>200</td></tr>
<tr><td>Above 960</td><td>500</td></tr>
</table></td><td>☑</td></tr>
<tr><td>Test Setup</td><td colspan="3"> 
</td></tr>
<tr><td>Procedure</td><td colspan="3">1. The EUT was switched on and allowed to warm up to its normal operating condition.
2. The test was carried out at the selected frequency points obtained from the EUT characterization. Maximization of the emissions, was carried out by rotating the EUT, changing the antenna polarization, and adjusting the antenna height in the following manner:
a. Vertical or horizontal polarization (whichever gave the higher emission level</td></tr>
</table>

	over a full rotation of the EUT) was chosen. b. The EUT was then rotated to the direction that gave the maximum emission. c. Finally, the antenna height was adjusted to the height that gave the maximum emission. 3. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasiy Peak detection at frequency below 1GHz. 4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz with Peak detection for Peak measurement at frequency above 1GHz. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth with Peak detection for Average Measurement as below at frequency above 1GHz. ■ 1 kHz (Duty cycle < 98%) □ 10 Hz (Duty cycle > 98%) 5. Steps 2 and 3 were repeated for the next frequency point, until all selected frequency points were measured.
Remark	
Result	☑ Pass ☐ Fail

Test Data ☑ Yes ☐ N/A

Test Plot ☑ Yes (See below) ☐ N/A

Test Mode :	USB Mode

Below 1GHz



Test Data

Horizontal Polarity Plot @3m

No.	P/L	Frequency	Reading	Detector	Corrected	Result	Limit	Margin	Height	Degree
		(MHz)	(dBuV/m)		(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	(cm)	(°)
1	H	67.4382	48.76	QP	-13.79	34.97	40.00	-5.03	100	155
2	H	161.4742	44.94	peak	-8.40	36.54	43.50	-6.96	100	99
3	H	236.6447	52.85	QP	-9.06	43.79	46.00	-2.21	100	324
4	H	420.5803	38.78	peak	-3.80	34.98	46.00	-11.02	100	291
5	H	560.6928	32.04	peak	-0.64	31.40	46.00	-14.60	100	107
6	H	875.2470	31.83	peak	4.25	36.08	46.00	-9.92	100	226

Below 1GHz



Test Data

Vertical Polarity Plot @3m

No.	P/L	Frequency	Reading	Detector	Corrected	Result	Limit	Margin	Height	Degree
		(MHz)	(dBuV/m)		(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	(cm)	(°)
1	V	53.5052	52.19	QP	-13.59	38.60	40.00	-1.40	100	96
2	V	66.9669	51.94	QP	-13.82	38.12	40.00	-1.88	100	234
3	V	88.9639	49.22	peak	-13.40	35.82	43.50	-7.68	100	318
4	V	141.8262	42.02	peak	-8.52	33.50	43.50	-10.00	100	64
5	V	413.2706	35.02	peak	-3.97	31.05	46.00	-14.95	100	157
6	V	560.6928	33.06	peak	-0.64	32.42	46.00	-13.58	100	112

Above 1GHz

Frequency (MHz)	Amplitude (dBμV/m)	Azimuth	Height (cm)	Polarity (H/V)	Factors (dB)	Limit (dBμV/m)	Margin (dB)	Detector (PK/AV)
1534.15	50.48	90	150	V	-22.35	74	-23.5	PK
2086.35	50.32	66	127	V	-21.42	74	-23.7	PK
1652.72	49.55	45	143	V	-22.68	74	-24.5	PK
2186.48	50.36	77	110	H	-22.88	74	-23.6	PK
2893.21	49.72	55	108	H	-22.74	74	-24.3	PK
1876.38	50.66	88	115	H	-22.69	74	-23.3	PK

*Note1: The highest frequency of the EUT is 2480 MHz, so the testing has been conformed to 5*2480MHz=12,400GHz.*

Note2: The frequency that above 3GHz is mainly from the environment noise.

Note3: The AV measurement performed, more than 20dB below limit so AV test data was not presented.

Annex A. TEST INSTRUMENT

Instrument	Model	Serial #	Cal Date	Cal Due	In use
AC Line Conducted Emissions					
EMI test receiver	ESCS30	8471241027	09/16/2016	09/15/2017	☑
Line Impedance Stabilization Network	LI-125A	191106	09/24/2016	09/23/2017	☑
Line Impedance Stabilization Network	LI-125A	191107	09/24/2016	09/23/2017	☑
LISN	ISN T800	34373	09/24/2016	09/23/2017	☑
Transient Limiter	LIT-153	531118	08/31/2016	08/30/2017	☑
Radiated Emissions					
EMI test receiver	ESL6	100262	09/16/2016	09/15/2017	☑
OPT 010 AMPLIFIER (0.1-1300MHz)	8447E	2727A02430	08/31/2016	08/30/2017	☑
Microwave Preamplifier (1 ~ 26.5GHz)	8449B	3008A02402	03/24/2016	03/23/2017	☑
Bilog Antenna (30MHz~6GHz)	JB6	A110712	09/20/2016	09/19/2017	☑
Double Ridge Horn Antenna	AH-118	71259	09/23/2016	09/22/2017	☑

Annex B. EUT And Test Setup Photographs

Annex B.i. Photograph: EUT External Photo

Whole Package View



Adapter - Front View

EUT - Front View

EUT - Rear View



EUT - Top View



EUT - Bottom View



EUT - Left View



EUT - Right View

Annex B.ii. Photograph: EUT Internal Photo

Cover Off - Top View

Battery - Front View



Battery - Rear View



Mainboard with Shielding - Front View



Mainboard without Shielding - Front View



Mainboard with Shielding – Rear View



Mainboard without Shielding - Rear View

LCD – Front View

LCD – Rear View

GSM/PCS/UMTS-FDD Antenna View

LTE - Antenna View



WIFI/BT/BLE/GPS - Antenna View

Annex B.iii. Photograph: Test Setup Photo

Conducted Emissions Test Setup – Front View

Conducted Emissions Test Setup – Side View



Radiated Emissions Test Setup Below 1GHz



Radiated Emissions Test Setup Above 1GHz

Annex C. TEST SETUP AND SUPPORTING EQUIPMENT

Annex C.ii. TEST SET UP BLOCK

Block Configuration Diagram for Conducted Emissions



Block Configuration Diagram for Radiated Emissions



Annex C. iI. SUPPORTING EQUIPMENT DESCRIPTION

The following is a description of supporting equipment and details of cables used with the EUT.

Supporting Equipment:

Manufacturer	Equipment Description	Model	Serial No
Lenovo	Laptop	E40	LR-1EHRX
GOLDWEB	Router	R102	1202032094
Lenovo	AC Adapter	42T4416	21D9JU
HP	Printer	VCVRA-1003	CN36M19JWX
DELL	Mouse	E100	912NMTUT41481
BULL	Socket	GN-403	GN201203

Supporting Cable:

Cable type	Shield Type	Ferrite Core	Length	Serial No
USB Cable	Un-shielding	No	2m	JX120051274
USB Cable	Un-shielding	No	2m	CBA3000AH0C1
RJ45 Cable	Un-shielding	No	2m	KX156327541
Router Power cable	Un-shielding	No	2m	13274630Z
Printer Power cable	Un-shielding	No	2m	127581031
Power Cable	Un-shielding	No	0.8m	GT211032

Annex D. User Manual / Block Diagram / Schematics / Partlist

Please see the attachment

Annex E. DECLARATION OF SIMILARITY

N/A