FCC RF Test Report

APPLICANT	:	CT Asia
EQUIPMENT	:	Mobile phone
BRAND NAME	:	BLU
MODEL NAME	:	Life Play Mini
FCC ID	:	YHLBLULPMINI
STANDARD	:	FCC 47 CFR Part 2, 22(H), 24(E)
CLASSIFICATION	:	PCS Licensed Transmitter Held to Ear (PCE)

The product was received on Sep. 19, 2014 and testing was completed on Oct. 01, 2014. We, SPORTON INTERNATIONAL (KUNSHAN) INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures given in ANSI / TIA / EIA-603-C-2004 and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL (KUNSHAN) INC., the test report shall not be reproduced except in full.

Reviewed by: Joseph Lin / Supervisor

Approved by: Jones Tsai / Manager

Testing Laboratory
2627

SPORTON INTERNATIONAL (KUNSHAN) INC.
No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P.R.C.

TABLE OF CONTENTS

SUMMARY OF TEST RESULT 4

1 GENERAL DESCRIPTION 5

1.1 Applicant 5
1.2 Manufacturer 5
1.3 Product Feature of Equipment Under Test 5
1.4 Product Specification subjective to this standard 6
1.5 Modification of EUT 7
1.6 Maximum ERP/EIRP Power, Frequency Tolerance, and Emission Designator 7
1.7 Testing Location 7
1.8 Applicable Standards 7

2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST 8

2.1 Test Mode 8
2.2 Connection Diagram of Test System 11
2.3 Support Unit used in test configuration 12
2.4 Measurement Results Explanation Example 12

3 TEST RESULT 13

3.1 Conducted Output Power Measurement 13
3.2 Peak-to-Average Ratio 15
3.3 Effective Radiated Power and Effective Isotropic Radiated Power Measurement 21
3.4 99% Occupied Bandwidth and 26dB Bandwidth Measurement 25
3.5 Band Edge Measurement 39
3.6 Conducted Spurious Emission Measurement 49
3.7 Field Strength of Spurious Radiation Measurement 60
3.8 Frequency Stability Measurement 66

4 LIST OF MEASURING EQUIPMENT 71

5 UNCERTAINTY OF EVALUATION 73

APPENDIX A. SETUP PHOTOGRAPHS

REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FG491909	Rev. 01	Initial issue of report	Oct. 11, 2014

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	§2.1046	Conducted Output Power	N/A	PASS	-
3.2	§24.232(d)	Peak-to-Average Ratio	<13 dB	PASS	-
3.3	§22.913(a)(2)	Effective Radiated Power	< 7 Watts	PASS	-
	§24.232(c)	Equivalent Isotropic Radiated Power	< 2 Watts	PASS	-
3.4	§2.1049 §22.917(b) §24.238(b)	Occupied Bandwidth	N/A	PASS	-
3.5	§2.1051 §22.917(a) §24.238(a)	Band Edge Measurement	< $43+10\log_{10}$(P[Watts])	PASS	-
3.6	§2.1051 §22.917(a) §24.238(a)	Conducted Spurious Emission	< $43+10\log_{10}$(P[Watts])	PASS	-
3.7	§2.1053 §22.917(a) §24.238(a)	Field Strength of Spurious Radiation	< $43+10\log_{10}$(P[Watts])	PASS	Under limit 14.97 dB at 7521.000 MHz
3.8	§2.1055 §22.355	Frequency Stability for Temperature & Voltage	< 2.5 ppm	PASS	-
	§2.1055 §24.235		within authorized band		

1 General Description

1.1 Applicant

CT Asia
Unit 01, 15/F, Seaview Centre, 139-141 Hoi bun road, Kwun Tong, Kowloon, Hongkong

1.2 Manufacturer

Ragentek Technology Group
Building D10-D11, No. 58-60, Lane 3188, Xiupu Road, PuDong District, Shanghai, P.R.C.

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Mobile phone
Brand Name	BLU
Model Name	Life Play Mini
FCC ID	YHLBLULPMINI
EUT supports Radios application	GSM/GPRS/EDGE(Downlink only)/WCDMA/HSPA/ WLAN 2.4GHz 802.11b/g/n HT20 Bluetooth v3.0 + EDR/Bluetooth v4.0 LE
HW Version	1.4
SW Version	J503_BLU_A1_V1.2.2_S0916
EUT Stage	Production Unit

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Product Specification subjective to this standard

Product Specification subjective to this standard	
Tx Frequency	GSM850: 824.2 MHz ~ 848.8 MHz GSM1900: 1850.2 MHz ~ 1909.8MHz WCDMA Band V: 826.4 MHz ~ 846.6 MHz WCDMA Band II: 1852.4 MHz ~ 1907.6 MHz
Rx Frequency	GSM850: 869.2 MHz ~ 893.8 MHz GSM1900: 1930.2 MHz ~ 1989.8 MHz WCDMA Band V: 871.4 MHz ~ 891.6 MHz WCDMA Band II: 1932.4 MHz ~ 1987.6 MHz
Maximum Output Power to Antenna	GSM850 : 32.72 dBm GSM1900 : 29.33 dBm WCDMA Band V : 23.42 dBm WCDMA Band II : 22.83 dBm
Antenna Type	PIFA Antenna
Type of Modulation	GSM: GMSK GPRS: GMSK EDGE: GMSK/8PSK(Downlink only) WCDMA: QPSK (Uplink) HSDPA: QPSK (Uplink) HSUPA: QPSK (Uplink)

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Maximum ERP/EIRP Power, Frequency Tolerance, and Emission Designator

FCC Rule	System	Type of Modulation	Maximum ERP/EIRP (W)	Frequency Tolerance (ppm)	Emission Designator
Part 22	GSM850 GSM	GMSK	0.8691	0.0096 ppm	249KGXW
Part 22	WCDMA Band V RMC 12.2Kbps	QPSK	0.1122	0.0036 ppm	4M18F9W
Part 24	GSM1900 GSM	GMSK	1.5153	0.0043 ppm	247KGXW
Part 24	WCDMA Band II RMC 12.2Kbps	QPSK	0.4838	0.0016 ppm	4M18F9W

1.7 Testing Location

Test Site	SPORTON INTERNATIONAL (KUNSHAN) INC.			
Test Site Location	No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P.R.C. TEL: +86-0512-5790-0158 FAX: +86-0512-5790-0958			
Test Site No.	**Sporton Site No.**			**FCC Registration No.**
	TH01-KS	03CH01-KS	OTA01-KS	149928

1.8 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC 47 CFR Part 2, 22(H), 24(E)
- ANSI / TIA / EIA-603-C-2004
- FCC KDB 971168 D01 Power Meas. License Digital Systems v02r01

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

2.1 Test Mode

Antenna port conducted and radiated test items were performed according to KDB 971168 D01 Power Meas. License Digital Systems v02r01 with maximum output power.

Radiated measurements were performed with rotating EUT in different three orthogonal test planes to find the maximum emission.

Frequency range investigated for radiated emission: 30MHz to 10th harmonic.

Test Modes		
Band	**Radiated TCs**	**Conducted TCs**
GSM 850	■ GSM Link	■ GSM Link
GSM 1900	■ GSM Link	■ GSM Link
WCDMA Band V	■ RMC 12.2Kbps Link	■ RMC 12.2Kbps Link
WCDMA Band II	■ RMC 12.2Kbps Link	■ RMC 12.2Kbps Link

Conducted Power Measurement Results:

SIM 1：

Conducted Power (*Unit: dBm)						
Band	**GSM850**			**GSM1900**		
Channel	**128**	**189**	**251**	**512**	**661**	**810**
Frequency	**824.2**	**836.4**	**848.8**	**1850.2**	**1880.0**	**1909.8**
GSM	32.65	**32.72**	32.67	29.15	29.23	**29.33**
GPRS class 8	32.60	32.65	32.64	29.09	29.18	29.31
GPRS class 10	31.58	31.66	31.63	28.06	28.17	28.35
GPRS class 11	29.67	29.71	29.69	26.15	26.28	26.51
GPRS class 12	28.84	28.90	28.87	25.32	25.46	25.69

Conducted Power (*Unit: dBm)						
Band	**WCDMA Band V**			**WCDMA Band II**		
Channel	**4132**	**4182**	**4233**	**9262**	**9400**	**9538**
Frequency	**826.4**	**836.4**	**846.6**	**1852.4**	**1880.0**	**1907.6**
AMR 12.2Kbps	23.19	23.40	23.02	22.82	22.81	22.73
RMC 12.2K	23.20	**23.42**	23.03	**22.83**	22.82	22.74
HSDPA Subtest-1	22.74	22.83	22.62	22.32	22.35	22.18
HSDPA Subtest-2	22.71	22.88	22.65	22.31	22.35	22.20
HSDPA Subtest-3	22.24	22.40	22.19	21.83	21.91	21.73
HSDPA Subtest-4	22.24	22.38	22.20	21.84	21.89	21.72
HSUPA Subtest-1	20.79	20.87	20.66	20.34	20.38	20.27
HSUPA Subtest-2	20.77	20.90	20.16	20.30	20.38	20.25
HSUPA Subtest-3	21.75	21.90	21.64	21.33	21.37	21.24
HSUPA Subtest-4	20.25	20.33	20.18	19.82	19.85	19.72
HSUPA Subtest-5	22.80	22.80	22.60	22.30	22.40	22.20

SIM 2:

Conducted Power (*Unit: dBm)						
Band	**GSM850**			**GSM1900**		
Channel	**128**	**189**	**251**	**512**	**661**	**810**
Frequency	**824.2**	**836.4**	**848.8**	**1850.2**	**1880.0**	**1909.8**
GSM	32.64	**32.69**	32.66	29.13	29.22	**29.31**
GPRS class 8	32.58	32.63	32.61	29.08	29.16	29.28
GPRS class 10	31.57	31.64	31.59	28.04	28.14	28.32
GPRS class 11	29.64	29.69	29.68	26.12	26.25	26.49
GPRS class 12	28.82	28.87	28.84	25.29	25.44	25.67

Conducted Power (*Unit: dBm)						
Band	**WCDMA Band V**			**WCDMA Band II**		
Channel	**4132**	**4182**	**4233**	**9262**	**9400**	**9538**
Frequency	**826.4**	**836.4**	**846.6**	**1852.4**	**1880.0**	**1907.6**
AMR 12.2Kbps	23.02	23.39	22.98	22.80	22.79	22.70
RMC 12.2K	23.04	**23.40**	23.00	**22.81**	22.80	22.71
HSDPA Subtest-1	22.70	22.82	22.61	22.30	22.34	22.16
HSDPA Subtest-2	22.68	22.85	22.62	22.30	22.32	22.20
HSDPA Subtest-3	22.23	22.39	22.18	21.82	21.90	21.72
HSDPA Subtest-4	22.22	22.37	22.20	21.82	21.87	21.71
HSUPA Subtest-1	20.77	20.85	20.65	20.33	20.36	20.25
HSUPA Subtest-2	20.76	20.88	20.14	20.30	20.37	20.24
HSUPA Subtest-3	21.73	21.90	21.62	21.30	21.35	21.23
HSUPA Subtest-4	20.22	20.32	20.15	19.80	19.84	19.70
HSUPA Subtest-5	22.78	22.78	22.60	22.26	22.40	22.18

2.2 Connection Diagram of Test System

<22H Tx Mode>



<24E Tx Mode>



2.3 Support Unit used in test configuration

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU 200	N/A	N/A	Unshielded, 1.8 m
2.	DC Power Supply	GW INSTEK	GPS-3030D	N/A	N/A	Unshielded, 1.8 m

2.4 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between RF conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level will be exactly the RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

The following shows an offset computation example with RF cable loss 7 dB and a 10dB attenuator.

Example :

Offset(dB) = RF cable loss(dB) + attenuator factor(dB).

= 7 + 10 = 17 (dB)

3 Test Result

3.1 Conducted Output Power Measurement

3.1.1 Description of the Conducted Output Power Measurement

A system simulator was used to establish communication with the EUT. Its parameters were set to enforce EUT transmitting at the maximum power. The measured power in the radio frequency on the transmitter output terminals shall be reported.

3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedures

1. The transmitter output port was connected to the system simulator.
2. Set EUT at maximum power through system simulator.
3. Select lowest, middle, and highest channels for each band and different modulation.
4. Measure the maximum burst average power for GSM and maximum average power for other modulation signal.

3.1.4 Test Setup



3.1.5 Test Result of Conducted Output Power

Cellular Band						
Modes	**GSM850 (GSM)**			**WCDMA Band V (RMC 12.2Kbps)**		
Channel	**128 (Low)**	**189 (Mid)**	**251 (High)**	**4132 (Low)**	**4182 (Mid)**	**4233 (High)**
Frequency (MHz)	**824.2**	**836.4**	**848.8**	**826.4**	**836.4**	**846.6**
Conducted Power (dBm)	32.65	32.72	32.67	23.20	23.42	23.03
Conducted Power (Watts)	1.84	1.87	1.85	0.21	0.22	0.20

PCS Band						
Modes	**GSM1900 (GSM)**			**WCDMA Band II (RMC 12.2Kbps)**		
Channel	**512 (Low)**	**661 (Mid)**	**810 (High)**	**9262 (Low)**	**9400 (Mid)**	**9538 (High)**
Frequency (MHz)	**1850.2**	**1880**	**1909.8**	**1852.4**	**1880**	**1907.6**
Conducted Power (dBm)	29.15	29.23	29.33	22.83	22.82	22.74
Conducted Power (Watts)	0.82	0.84	0.86	0.19	0.19	0.19

Note: Maximum burst average power for GSM and maximum average power for WCDMA.

3.2 Peak-to-Average Ratio

3.2.1 Description of the PAR Measurement

The peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.2.3 Test Procedures

1. The testing follows FCC KDB 971168 v02r01 Section 5.7.1.
2. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
3. For GSM/EGPRS operating modes:
   a. Set EUT in maximum power output.
   b. Set the RBW = 1MHz, VBW = 3MHz, Peak detector on spectrum analyzer for first trace.
   c. Set the RBW = 1MHz, VBW = 3MHz, RMS detector on spectrum analyzer for second trace.
   d. The wanted burst signal is triggered by spectrum analyzer, and measured respectively the peak level and Mean level without burst-off time, after system simulator has synchronized with the spectrum analyzer.
4. For UMTS operating modes:
   a. Set the CCDF (Complementary Cumulative Distribution Function) option on the spectrum analyzer.
   b. The highest RF powers were measured and recorded the maximum PAPR level associated with a probability of 0.1 %.
5. Record the deviation as Peak to Average Ratio.

3.2.4 Test Setup



3.2.5 Test Result of Peak-to-Average Ratio

PCS Band						
Modes	GSM1900 (GSM)			WCDMA Band II (RMC 12.2Kbps)		
Channel	512 (Low)	661 (Mid)	810 (High)	9262 (Low)	9400 (Mid)	9538 (High)
Frequency (MHz)	1850.2	1880	1909.8	1852.4	1880	1907.6
Peak-to-Average Ratio (dB)	0.25	0.28	0.33	2.67	2.49	2.55

3.2.6 Test Result (Plots) of Peak-to-Average Ratio

Band :	GSM 1900	Test Mode :	GSM Link (GMSK)

Peak-to-Average Ratio on Channel 512 (1850.2 MHz)



Date: 25.SEP.2014 07:17:42

Peak-to-Average Ratio on Channel 661 (1880.0 MHz)



Date: 25.SEP.2014 07:18:05

Peak-to-Average Ratio on Channel 810 (1909.8 MHz)



Date: 25.SEP.2014 07:18:36

Band :	WCDMA Band II	Test Mode :	RMC 12.2Kbps Link (QPSK)

Peak-to-Average Ratio on Channel 9262 (1852.4 MHz)



Date: 23.SEP.2014 08:43:35

Peak-to-Average Ratio on Channel 9400 (1880.0 MHz)



Date: 23.SEP.2014 08:43:04

Peak-to-Average Ratio on Channel 9538 (1907.6 MHz)



Date: 23.SEP.2014 08:42:35

3.3 Effective Radiated Power and Effective Isotropic Radiated Power Measurement

3.3.1 Description of the ERP/EIRP Measurement

The substitution method, in ANSI / TIA / EIA-603-C-2004, was used for ERP/EIRP measurement, and the spectrum analyzer configuration follows KDB 971168 D01 Power Meas. License Digital Systems v02r01. The ERP of mobile transmitters must not exceed 7 Watts and the EIRP of mobile transmitters are limited to 2 Watts.

3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.3.3 Test Procedures

1. The testing follows FCC KDB 971168 v02r01 Section 5.2.1. (for CDMA/WCDMA), Section 5.2.2.2 (for GSM/GPRS/EDGE) and ANSI / TIA-603-C-2004 Section 2.2.17.
2. The EUT was placed on a turntable 1.5 meters high in a fully anechoic chamber.
3. The EUT was placed 3 meters from the receiving antenna, which was mounted on the antenna tower.
4. GSM operating modes: Set RBW= 1MHz, VBW= 3MHz, RMS detector over burst;
   UMTS operating modes: Set RBW= 100 kHz, VBW= 300 kHz, RMS detector over frame, and use channel power option with bandwidth=5MHz, per KDB 971168 D01.
5. The table was rotated 360 degrees to determine the position of the highest radiated power.
6. The height of the receiving antenna is adjusted to look for the maximum ERP/EIRP.
7. Taking the record of maximum ERP/EIRP.
8. A dipole antenna was substituted in place of the EUT and was driven by a signal generator.
9. The conducted power at the terminal of the dipole antenna is measured.
10. Repeat step 3 to step 5 to get the maximum ERP/EIRP of the substitution antenna.
11. ERP/EIRP = Ps + Et – Es + Gs = Ps + Rt – Rs + Gs
    Ps (dBm)：Input power to substitution antenna.
    Gs (dBi or dBd)：Substitution antenna Gain.
    Et = Rt + AF
    Es = Rs + AF
    AF (dB/m)：Receive antenna factor
    Rt：The highest received signal in spectrum analyzer for EUT.
    Rs：The highest received signal in spectrum analyzer for substitution antenna.

3.3.4 Test Setup



3.3.5 Test Result of ERP

GSM850 (GSM) Radiated Power ERP						
Horizontal Polarization						
Frequency (MHz)	**Rt (dBm)**	**Rs (dBm)**	**Ps (dBm)**	**Gs (dBd)**	**ERP (dBm)**	**ERP (W)**
824.20	-18.52	-48.12	0.00	-1.08	28.52	0.7111
836.40	-18.48	-48.28	0.00	-0.93	28.87	0.7713
848.80	-18.20	-48.35	0.00	-0.76	29.39	0.8691
Vertical Polarization						
Frequency (MHz)	**Rt (dBm)**	**Rs (dBm)**	**Ps (dBm)**	**Gs (dBd)**	**ERP (dBm)**	**ERP (W)**
824.20	-32.58	-47.97	0.00	-1.08	14.31	0.0270
836.40	-32.52	-48.01	0.00	-0.93	14.56	0.0286
848.80	-31.97	-48.05	0.00	-0.76	15.32	0.0340

WCDMA Band V (RMC 12.2Kbps) Radiated Power ERP						
Horizontal Polarization						
Frequency (MHz)	**Rt (dBm)**	**Rs (dBm)**	**Ps (dBm)**	**Gs (dBd)**	**ERP (dBm)**	**ERP (W)**
826.40	-26.78	-48.12	0.00	-1.08	20.26	0.1063
836.40	-26.85	-48.28	0.00	-0.93	20.50	0.1122
846.60	-27.48	-48.35	0.00	-0.76	20.11	0.1027
Vertical Polarization						
Frequency (MHz)	**Rt (dBm)**	**Rs (dBm)**	**Ps (dBm)**	**Gs (dBd)**	**ERP (dBm)**	**ERP (W)**
826.40	-40.91	-47.97	0.00	-1.08	5.98	0.0040
836.40	-40.80	-48.01	0.00	-0.93	6.28	0.0042
846.60	-41.04	-48.05	0.00	-0.76	6.25	0.0042

3.3.6 Test Result of EIRP

GSM1900 (GSM) Radiated Power EIRP						
Horizontal Polarization						
Frequency (MHz)	**Rt (dBm)**	**Rs (dBm)**	**Ps (dBm)**	**Gs (dBi)**	**EIRP (dBm)**	**EIRP (W)**
1850.20	-22.04	-51.88	0.00	1.96	31.80	1.5142
1880.00	-23.63	-52.99	0.00	2.00	31.36	1.3692
1909.80	-25.52	-54.28	0.00	1.98	30.74	1.1858
Vertical Polarization						
Frequency (MHz)	**Rt (dBm)**	**Rs (dBm)**	**Ps (dBm)**	**Gs (dBi)**	**EIRP (dBm)**	**EIRP (W)**
1850.20	-22.28	-52.13	0.00	1.96	31.81	1.5153
1880.00	-23.83	-53.17	0.00	2.00	31.34	1.3603
1909.80	-25.30	-54.13	0.00	1.98	30.81	1.2038

WCDMA Band II (RMC 12.2Kbps) Radiated Power EIRP						
Horizontal Polarization						
Frequency (MHz)	**Rt (dBm)**	**Rs (dBm)**	**Ps (dBm)**	**Gs (dBi)**	**EIRP (dBm)**	**EIRP (W)**
1852.40	-26.99	-51.88	0.00	1.96	26.85	0.4838
1880.00	-29.19	-52.99	0.00	2.00	25.80	0.3800
1907.60	-31.41	-54.28	0.00	1.98	24.85	0.3058
Vertical Polarization						
Frequency (MHz)	**Rt (dBm)**	**Rs (dBm)**	**Ps (dBm)**	**Gs (dBi)**	**EIRP (dBm)**	**EIRP (W)**
1852.40	-27.45	-52.13	0.00	1.96	26.64	0.4612
1880.00	-29.39	-53.17	0.00	2.00	25.78	0.3783
1907.60	-31.24	-54.13	0.00	1.98	24.87	0.3067

3.4 99% Occupied Bandwidth and 26dB Bandwidth Measurement

3.4.1 Description of 99% Occupied Bandwidth and 26dB Bandwidth Measurement

The 99% occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The emission bandwidth is defined as the width of the signal between two points, located at the 2 sides of the carrier frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.

3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.4.3 Test Procedures

1. The testing follows FCC KDB 971168 v02r01 Section 4.2.
2. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
3. The RF output of the EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
4. The 99% occupied bandwidth were measured, set RBW= 1% of span, VBW= 3*RBW, sample detector, trace maximum hold.
5. The 26dB bandwidth were measured, set RBW= 1% of EBW, VBW= 3*RBW, peak detector, trace maximum hold.

3.4.4 Test Setup



3.4.5 Test Result of Occupied Bandwidth and 26dB Bandwidth

Cellular Band			
Modes	**GSM850 (GSM)**		
Channel	**128(Low)**	**189(Mid)**	**251(High)**
Frequency (MHz)	**824.2**	**836.4**	**848.8**
99% OBW (MHz)	246.02	248.91	244.57
26dB BW (MHz)	306.80	308.20	308.20

PCS Band			
Modes	**GSM1900 (GSM)**		
Channel	**512(Low)**	**661(Mid)**	**810(High)**
Frequency (MHz)	**1850.2**	**1880**	**1909.8**
99% OBW (MHz)	247.47	246.02	247.47
26dB BW (MHz)	311.10	308.20	305.40

Cellular Band			
Modes	**WCDMA Band V (RMC 12.2Kbps)**		
Channel	**4132 (Low)**	**4182 (Mid)**	**4233 (High)**
Frequency (MHz)	**826.4**	**836.4**	**846.6**
99% OBW (MHz)	4.17	4.15	4.18
26dB BW (MHz)	4.72	4.72	4.69

PCS Band			
Modes	**WCDMA Band II (RMC 12.2Kbps)**		
Channel	**9262 (Low)**	**9400 (Mid)**	**9538 (High)**
Frequency (MHz)	**1852.4**	**1880**	**1907.6**
99% OBW (MHz)	4.14	4.18	4.17
26dB BW (MHz)	4.69	4.70	4.67

3.4.6 Test Result (Plots) of Occupied Bandwidth and 26dB Bandwidth

Band :	GSM 850	Test Mode :	GSM Link (GMSK)

99% Occupied Bandwidth Plot on Channel 128 (824.2 MHz)



Date: 23.SEP.2014 07:44:41

26dB Bandwidth Plot on Channel 128 (824.2 MHz)



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	824.2116 MHz	24.22 dBm	ndB down	306.8 kHz
T1		1	824.0466 MHz	-1.26 dBm	ndB	26.00 dB
T2		1	824.3534 MHz	-1.81 dBm	Q factor	2686.5

Date: 23.SEP.2014 07:41:10

99% Occupied Bandwidth Plot on Channel 189 (836.4 MHz)



Date: 23.SEP.2014 07:43:40

26dB Bandwidth Plot on Channel 189 (836.4 MHz)



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	836.4014 MHz	25.29 dBm	ndB down	308.2 kHz
T1		1	836.2466 MHz	0.37 dBm	ndB	26.00 dB
T2		1	836.5548 MHz	-1.04 dBm	Q factor	2713.4

Date: 23.SEP.2014 07:40:32

99% Occupied Bandwidth Plot on Channel 251 (848.8 MHz)



Date: 23.SEP.2014 07:42:50

26dB Bandwidth Plot on Channel 251 (848.8 MHz)



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	848.8 MHz	24.41 dBm	ndB down	308.2 kHz
T1		1	848.6466 MHz	-0.66 dBm	ndB	26.00 dB
T2		1	848.9548 MHz	-2.44 dBm	Q factor	2753.6

Date: 23.SEP.2014 07:41:45

Band :	GSM 1900	Test Mode :	GSM Link (GMSK)

99% Occupied Bandwidth Plot on Channel 512 (1850.2 MHz)



Date: 24.SEP.2014 05:40:28

26dB Bandwidth Plot on Channel 512 (1850.2 MHz)



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	1.8501855 GHz	22.44 dBm	ndB down	311.1 kHz
T1		1	1.8500437 GHz	-4.01 dBm	ndB	26.00 dB
T2		1	1.8503548 GHz	-3.45 dBm	Q factor	5946.4

Date: 24.SEP.2014 05:41:56

99% Occupied Bandwidth Plot on Channel 661 (1880.0 MHz)



Date: 24.SEP.2014 05:39:46

26dB Bandwidth Plot on Channel 661 (1880.0 MHz)



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	1.8800666 GHz	21.94 dBm	ndB down	308.2 kHz
T1		1	1.8798466 GHz	-3.04 dBm	ndB	26.00 dB
T2		1	1.8801548 GHz	-4.75 dBm	Q factor	6099.2

Date: 24.SEP.2014 05:42:31

99% Occupied Bandwidth Plot on Channel 810 (1909.8 MHz)



Date: 24.SEP.2014 05:38:21

26dB Bandwidth Plot on Channel 810 (1909.8 MHz)



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	1.9098188 GHz	22.84 dBm	ndB down	305.4 kHz
T1		1	1.9096495 GHz	-3.07 dBm	ndB	26.00 dB
T2		1	1.9099548 GHz	-4.65 dBm	Q factor	6254.4

Date: 24.SEP.2014 05:43:20

Band :	WCDMA Band V	Test Mode :	RMC 12.2Kbps Link (QPSK)

99% Occupied Bandwidth Plot on Channel 4132 (826.4 MHz)



Date: 23.SEP.2014 08:18:57

26dB Bandwidth Plot on Channel 4132 (826.4 MHz)



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	825.532 MHz	19.33 dBm	ndB down	4.718 MHz
T1		1	824.041 MHz	-7.01 dBm	ndB	26.00 dB
T2		1	828.759 MHz	-5.79 dBm	Q factor	175.0

Date: 23.SEP.2014 08:22:18

99% Occupied Bandwidth Plot on Channel 4182 (836.4 MHz)



Date: 23.SEP.2014 08:19:32

26dB Bandwidth Plot on Channel 4182 (836.4 MHz)



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	835.517 MHz	19.12 dBm	ndB down	4.718 MHz
T1		1	834.041 MHz	-6.48 dBm	ndB	26.00 dB
T2		1	838.759 MHz	-7.04 dBm	Q factor	177.1

Date: 23.SEP.2014 08:21:28

99% Occupied Bandwidth Plot on Channel 4233 (846.6 MHz)



Date: 23.SEP.2014 08:20:01

26dB Bandwidth Plot on Channel 4233 (846.6 MHz)



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	845.732 MHz	19.46 dBm	ndB down	4.689 MHz
T1		1	844.256 MHz	-6.77 dBm	ndB	26.00 dB
T2		1	848.944 MHz	-7.18 dBm	Q factor	180.4

Date: 23.SEP.2014 08:20:44

Band :	WCDMA Band II	Test Mode :	RMC 12.2Kbps Link (QPSK)

99% Occupied Bandwidth Plot on Channel 9262 (1852.4 MHz)



Date: 23.SEP.2014 08:38:56

26dB Bandwidth Plot on Channel 9262 (1852.4 MHz)



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	1.851532 GHz	19.56 dBm	ndB down	4.689 MHz
T1		1	1.850056 GHz	-6.54 dBm	ndB	26.00 dB
T2		1	1.854744 GHz	-6.54 dBm	Q factor	394.9

Date: 23.SEP.2014 08:34:27

99% Occupied Bandwidth Plot on Channel 9400 (1880.0 MHz)



Date: 23.SEP.2014 08:38:19

26dB Bandwidth Plot on Channel 9400 (1880.0 MHz)



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	1.879132 GHz	19.58 dBm	ndB down	4.703 MHz
T1		1	1.877656 GHz	-5.94 dBm	ndB	26.00 dB
T2		1	1.882359 GHz	-7.37 dBm	Q factor	399.5

Date: 23.SEP.2014 08:36:13

99% Occupied Bandwidth Plot on Channel 9538 (1907.6 MHz)



Date: 23.SEP.2014 08:37:33

26dB Bandwidth Plot on Channel 9538 (1907.6 MHz)



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	1.906732 GHz	19.75 dBm	ndB down	4.674 MHz
T1		1	1.905256 GHz	-5.63 dBm	ndB	26.00 dB
T2		1	1.90993 GHz	-5.81 dBm	Q factor	407.9

Date: 23.SEP.2014 08:36:49

3.5 Band Edge Measurement

3.5.1 Description of Band Edge Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least 43 + 10 log (P) dB.

3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.5.3 Test Procedures

1. The testing follows FCC KDB 971168 v02r01 Section 6.0.
2. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by an RF cable and attenuator. The path loss was compensated to the results for each measurement.
4. The band edges of low and high channels for the highest RF powers were measured.
5. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
6. The limit line is derived from 43 + 10log(P) dB below the transmitter power P(Watts)
   = P(W) - [43 + 10log(P)] (dB)
   = [30 + 10log(P)] (dBm) - [43 + 10log(P)] (dB)
   = -13dBm.

3.5.4 Test Setup

<Conducted Band Edge >



3.5.5 Test Result (Plots) of Conducted Band Edge

Band :	GSM850	**Test Mode :**	GSM Link (GMSK)
Correction Factor :	0.12dB	**Maximum 26dB Bandwidth :**	0.308MHz
Band Edge :	-16.07dBm	**Measurement Value :**	-16.19dBm

Lower Band Edge Plot on Channel 128 (824.2 MHz)



1. Correction Factor(dB)= 10log(1% Emission BW/RBW)

2. Band Edge= Measurement Value + Correction Factor(dB)

Band :	GSM850	Test Mode :	GSM Link (GMSK)
Correction Factor :	0.12dB	Maximum 26dB Bandwidth :	0.308MHz
Band Edge :	-17.14dBm	Measurement Value :	-17.26dBm

Higher Band Edge Plot on Channel 251 (848.8 MHz)



Date: 23.SEP.2014 07:46:52

1. Correction Factor(dB)= 10log(1% Emission BW/RBW)

2. Band Edge= Measurement Value + Correction Factor(dB)

Band :	GSM1900	Test Mode :	GSM Link (GMSK)
Correction Factor :	0.16dB	Maximum 26dB Bandwidth :	0.311MHz
Band Edge :	-19.69dBm	Measurement Value :	-19.85dBm

Lower Band Edge Plot on Channel 512 (1850.2 MHz)



1. Correction Factor(dB)= 10log(1% Emission BW/RBW)

2. Band Edge= Measurement Value + Correction Factor(dB)

Band :	GSM1900	Test Mode :	GSM Link (GMSK)
Correction Factor :	0.16dB	Maximum 26dB Bandwidth :	0.311MHz
Band Edge :	-19.56dBm	Measurement Value :	-19.72dBm

Higher Band Edge Plot on Channel 810 (1909.8 MHz)



Date: 24.SEP.2014 05:34:52

1. Correction Factor(dB)= 10log(1% Emission BW/RBW)

2. Band Edge= Measurement Value + Correction Factor(dB)

Band :	WCDMA Band V	Test Mode :	RMC 12.2Kbps Link (QPSK)
Correction Factor :	-3.26dB	Maximum 26dB Bandwidth :	4.720MHz
Band Edge :	-24.50dBm	Measurement Value :	-21.24dBm

Lower Band Edge Plot on Channel 4132 (826.4 MHz)



Date: 23.SEP.2014 08:16:45

1. Correction Factor(dB)= 10log(1% Emission BW/RBW)

2. Band Edge= Measurement Value + Correction Factor(dB)

Band :	WCDMA Band V	Test Mode :	RMC 12.2Kbps Link (QPSK)
Correction Factor :	-3.26dB	Maximum 26dB Bandwidth :	4.720MHz
Band Edge :	-27.36dBm	Measurement Value :	-24.10dBm

Higher Band Edge Plot on Channel 4233 (846.6 MHz)



Date: 23.SEP.2014 08:14:28

1. Correction Factor(dB)= 10log(1% Emission BW/RBW)

2. Band Edge= Measurement Value + Correction Factor(dB)

Band :	WCDMA Band II	Test Mode :	RMC 12.2Kbps Link (QPSK)
Correction Factor :	-3.28dB	Maximum 26dB Bandwidth :	4.700MHz
Band Edge :	-26.37dBm	Measurement Value :	-23.09dBm

Lower Band Edge Plot on Channel 9262 (1852.4 MHz)



Date: 23.SEP.2014 08:40:24

1. Correction Factor(dB)= 10log(1% Emission BW/RBW)

2. Band Edge= Measurement Value + Correction Factor(dB)

Band :	WCDMA Band II	Test Mode :	RMC 12.2Kbps Link (QPSK)
Correction Factor :	-3.28dB	Maximum 26dB Bandwidth :	4.700MHz
Band Edge :	-25.61dBm	Measurement Value :	-22.33dBm

Higher Band Edge Plot on Channel 9538 (1907.6 MHz)



1. Correction Factor(dB)= 10log(1% Emission BW/RBW)

2. Band Edge= Measurement Value + Correction Factor(dB)

3.6 Conducted Spurious Emission Measurement

3.6.1 Description of Conducted Spurious Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least 43 + 10 log (P) dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10th harmonic.

3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.6.3 Test Procedures

1. The testing follows FCC KDB 971168 v02r01 Section 6.0.
2. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by an RF cable and attenuator. The path loss was compensated to the results for each measurement.
4. The middle channel for the highest RF power within the transmitting frequency was measured.
5. The conducted spurious emission for the whole frequency range was taken.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
7. The limit line is derived from 43 + 10log(P) dB below the transmitter power P(Watts)
   = P(W) - [43 + 10log(P)] (dB)
   = [30 + 10log(P)] (dBm) - [43 + 10log(P)] (dB)
   = -13dBm.

3.6.4 Test Setup



3.6.5 Test Result (Plots) of Conducted Spurious Emission

Band :	GSM850	Channel :	CH189
Test Mode :	GSM Link (GMSK)	Frequency :	836.4 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz



Conducted Spurious Emission Plot between 1GHz ~ 3GHz



Date: 23.SEP.2014 07:50:33

Conducted Spurious Emission Plot between 3GHz ~ 7GHz



Date: 23.SEP.2014 07:51:48

Conducted Spurious Emission Plot between 7GHz ~ 9GHz



Date: 23.SEP.2014 07:52:50

Band :	GSM1900	Channel :	CH661
Test Mode :	GSM Link (GMSK)	Frequency :	1880.0 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz



Date: 24.SEP.2014 05:30:45

Conducted Spurious Emission Plot between 1GHz ~ 3GHz



Date: 24.SEP.2014 05:27:40

Conducted Spurious Emission Plot between 3GHz ~ 7GHz



Date: 24.SEP.2014 05:25:51

Conducted Spurious Emission Plot between 7GHz ~ 13.6GHz



Date: 24.SEP.2014 05:24:44

Conducted Spurious Emission Plot between 13.6GHz ~ 19.1GHz



Date: 24.SEP.2014 05:23:56

Band :	WCDMA Band V	Channel :	CH4182
Test Mode :	RMC 12.2Kbps Link (QPSK)	Frequency :	836.4 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz



Date: 23.SEP.2014 08:08:36

Conducted Spurious Emission Plot between 1GHz ~ 3GHz



Date: 23.SEP.2014 08:04:19

Conducted Spurious Emission Plot between 3GHz ~ 7GHz



Date: 23.SEP.2014 08:03:28

Conducted Spurious Emission Plot between 7GHz ~ 9GHz



Date: 23.SEP.2014 08:02:37

Band :	WCDMA Band II	Channel :	CH9400
Test Mode :	RMC 12.2Kbps Link (QPSK)	Frequency :	1880.0 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz



Date: 24.SEP.2014 05:15:30

Conducted Spurious Emission Plot between 1GHz ~ 3GHz



Date: 24.SEP.2014 05:29:12

Conducted Spurious Emission Plot between 3GHz ~ 7GHz



Date: 24.SEP.2014 05:18:49

Conducted Spurious Emission Plot between 7GHz ~ 13.6GHz



Date: 24.SEP.2014 05:19:43

Conducted Spurious Emission Plot between 13.6GHz ~ 19.1GHz



Date: 24.SEP.2014 05:20:26

3.7 Field Strength of Spurious Radiation Measurement

3.7.1 Description of Field Strength of Spurious Radiated Measurement

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least 43 + 10 log (P) dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

3.7.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.7.3 Test Procedures

1. The testing follows FCC KDB 971168 v02r01 Section 5.8 and ANSI / TIA-603-C-2004 Section 2.2.12.
2. The EUT was placed on a rotatable wooden table 0.8 meters above the ground.
3. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
4. The table was rotated 360 degrees to determine the position of the highest spurious emission.
5. The height of the receiving antenna is varied between one meter and four meters to search for the maximum spurious emission for both horizontal and vertical polarizations.
6. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking record of maximum spurious emission.
7. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
8. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
9. Taking the record of output power at antenna port.
10. Repeat step 7 to step 8 for another polarization.
11. EIRP (dBm) = S.G. Power – Tx Cable Loss + Tx Antenna Gain
12. ERP (dBm) = EIRP - 2.15
13. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
14. The limit line is derived from 43 + 10log(P) dB below the transmitter power P(Watts)

    = P(W) - [43 + 10log(P)] (dB)

    = [30 + 10log(P)] (dBm) - [43 + 10log(P)] (dB)

    = -13dBm.

3.7.4 Test Setup

For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



3.7.5 Test Result of Field Strength of Spurious Radiated

Band :	GSM850	**Temperature :**	22~23°C
Test Mode :	GSM Link (GMSK)	**Relative Humidity :**	40~41%
Test Engineer :	Jun Liu	**Polarization :**	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		

Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1672	-69.48	-13	-56.48	-60.60	-70.13	0.57	3.37	H	Pass
2510	-59.31	-13	-46.31	-58.73	-61.54	0.78	5.16	H	Pass
3346	-64.17	-13	-51.17	-63.80	-67.81	0.87	6.66	H	Pass
4182	-67.34	-13	-54.34	-67.03	-67.99	0.57	3.37	H	Pass
5018	-64.38	-13	-51.38	-66.02	-66.61	0.78	5.16	H	Pass
5854	-55.40	-13	-42.40	-61.88	-59.04	0.87	6.66	H	Pass
6692	-52.83	-13	-39.83	-61.42	-53.48	0.57	3.37	H	Pass
7528	-45.82	-13	-32.82	-57.02	-48.05	0.78	5.16	H	Pass

Band :	GSM850	**Temperature :**	22~23°C
Test Mode :	GSM Link (GMSK)	**Relative Humidity :**	40~41%
Test Engineer :	Jun Liu	**Polarization :**	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		

Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1672	-52.83	-13	-39.83	-55.01	-53.48	0.57	3.37	V	Pass
2510	-50.94	-13	-37.94	-57.55	-53.17	0.78	5.16	V	Pass
3344	-64.06	-13	-51.06	-65.12	-67.70	0.87	6.66	V	Pass
4182	-65.57	-13	-52.57	-68.25	-66.22	0.57	3.37	V	Pass
5016	-57.76	-13	-44.76	-64.31	-59.99	0.78	5.16	V	Pass
5856	-54.86	-13	-41.86	-61.77	-58.50	0.87	6.66	V	Pass
6692	-51.80	-13	-38.80	-61.50	-52.45	0.57	3.37	V	Pass
7528	-50.47	-13	-37.47	-60.53	-52.70	0.78	5.16	V	Pass

Band :	GSM1900	**Temperature :**	22~23°C
Test Mode :	GSM Link (GMSK)	**Relative Humidity :**	40~41%
Test Engineer :	Jun Liu	**Polarization :**	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3759	-60.86	-13	-47.86	-64.21	-67.24	0.78	7.16	H	Pass
5643	-45.39	-13	-32.39	-58.06	-53.93	1.04	9.58	H	Pass
7521	-29.35	-13	-16.35	-47.48	-39.46	1.35	11.46	H	Pass
9399	-46.72	-13	-33.72	-60.26	-57.78	1.75	12.81	H	Pass
11283	-39.99	-13	-26.99	-60.66	-51.08	2	13.09	H	Pass

Band :	GSM1900	**Temperature :**	22~23°C
Test Mode :	GSM Link (GMSK)	**Relative Humidity :**	40~41%
Test Engineer :	Jun Liu	**Polarization :**	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3759	-56.92	-13	-43.92	-65.32	-63.30	0.78	7.16	V	Pass
5643	-40.41	-13	-27.41	-56.46	-48.95	1.04	9.58	V	Pass
7521	-27.97	-13	-14.97	-47.03	-38.08	1.35	11.46	V	Pass
9399	-50.19	-13	-37.19	-62.72	-61.25	1.75	12.81	V	Pass
11283	-39.58	-13	-26.58	-59.23	-50.67	2	13.09	V	Pass

Band :	WCDMA Band V	**Temperature :**	22~23°C
Test Mode :	RMC 12.2Kbps Link (QPSK)	**Relative Humidity :**	40~41%
Test Engineer :	Jun Liu	**Polarization :**	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		

Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1672	-76.39	-13	-63.39	-67.51	-77.04	0.57	3.37	H	Pass
2508	-69.20	-13	-56.20	-67.87	-71.43	0.78	5.16	H	Pass
3344	-65.72	-13	-52.72	-65.35	-69.36	0.87	6.66	H	Pass

Band :	WCDMA Band V	**Temperature :**	22~23°C
Test Mode :	RMC 12.2Kbps Link (QPSK)	**Relative Humidity :**	40~41%
Test Engineer :	Jun Liu	**Polarization :**	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		

Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1672	-69.64	-13	-56.64	-65.84	-70.29	0.57	3.37	V	Pass
2508	-63.80	-13	-50.80	-66.23	-66.03	0.78	5.16	V	Pass
3344	-64.45	-13	-51.45	-65.51	-68.09	0.87	6.66	V	Pass

Band :	WCDMA Band II	**Temperature :**	22~23°C
Test Mode :	RMC 12.2Kbps Link (QPSK)	**Relative Humidity :**	40~41%
Test Engineer :	Jun Liu	**Polarization :**	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3759	-62.02	-13	-49.02	-65.37	-68.40	0.78	7.16	H	Pass
5640	-57.22	-13	-44.22	-67.28	-65.76	1.04	9.58	H	Pass
7521	-55.19	-13	-42.19	-66.73	-65.30	1.35	11.46	H	Pass

Band :	WCDMA Band II	**Temperature :**	22~23°C
Test Mode :	RMC 12.2Kbps Link (QPSK)	**Relative Humidity :**	40~41%
Test Engineer :	Jun Liu	**Polarization :**	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3759	-57.71	-13	-44.71	-66.11	-64.09	0.78	7.16	V	Pass
5640	-54.49	-13	-41.49	-67.14	-63.03	1.04	9.58	V	Pass
7521	-52.36	-13	-39.36	-66.45	-62.47	1.35	11.46	V	Pass

3.8 Frequency Stability Measurement

3.8.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within ±0.00025% (±2.5ppm) of the center frequency.

3.8.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.8.3 Test Procedures for Temperature Variation

1. The testing follows FCC KDB 971168 v02r01 Section 9.0.
2. The EUT was set up in the thermal chamber and connected with the system simulator.
3. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
4. With power OFF, the temperature was raised in 10°C steps up to 50°C. The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

3.8.4 Test Procedures for Voltage Variation

1. The testing follows FCC KDB 971168 v02r01 Section 9.0.
2. The EUT was placed in a temperature chamber at 25±5° C and connected with the system simulator.
3. The power supply voltage to the EUT was varied from BEP to 115% of the nominal value measured at the input to the EUT.
4. The variation in frequency was measured for the worst case.

3.8.5 Test Setup



3.8.6 Test Result of Temperature Variation

Band :	GSM 850	Channel :	189
Limit (ppm) :	2.5	Frequency :	836.4 MHz

Temperature (°C)	GSM		Result
	Freq. Dev. (Hz)	Deviation (ppm)	
50	26	0.0096	PASS
40	22	0.0048	
30	20	0.0024	
20(Ref.)	18	0.0000	
10	15	0.0036	
0	20	0.0024	
-10	13	0.0060	
-20	16	0.0024	
-30	22	0.0048	

Band :	GSM 1900	Channel :	661
Limit (ppm) :	within authorized band	Frequency :	1880.0 MHz

Temperature (°C)	GSM		Result
	Freq. Dev. (Hz)	Deviation (ppm)	
50	-13	0.0011	PASS
40	-12	0.0016	
30	-18	0.0016	
20(Ref.)	-15	0.0000	
10	-13	0.0011	
0	-17	0.0011	
-10	-20	0.0027	
-20	-19	0.0021	
-30	-23	0.0043	

Note: The frequency fundamental emissions stay within the authorized frequency block based on the frequency deviation measured is small.

Band :	WCDMA Band V	Channel :	4182
Limit (ppm) :	2.5	Frequency :	836.4 MHz

Temperature (°C)	RMC 12.2Kbps		Result
	Freq. Dev. (Hz)	Deviation (ppm)	
50	3	0.0024	PASS
40	3	0.0024	
30	0	0.0012	
20(Ref.)	1	0.0000	
10	-1	0.0024	
0	0	0.0012	
-10	-2	0.0036	
-20	2	0.0012	
-30	3	0.0024	

Band :	WCDMA Band II	Channel :	9400
Limit (ppm) :	within authorized band	Frequency :	1880.0 MHz

Temperature (°C)	RMC 12.2Kbps		Result
	Freq. Dev. (Hz)	Deviation (ppm)	
50	2	0.0005	PASS
40	3	0.0000	
30	2	0.0005	
20(Ref.)	3	0.0000	
10	1	0.0011	
0	0	0.0016	
-10	2	0.0005	
-20	2	0.0005	
-30	4	0.0005	

Note: The frequency fundamental emissions stay within the authorized frequency block based on the frequency deviation measured is small.

3.8.7 Test Result of Voltage Variation

Band & Channel	Mode	Voltage (Volt)	Freq. Dev. (Hz)	Deviation (ppm)	Limit (ppm)	Result
GSM 850 CH189	GSM	3.8	18	0.0000	2.5 (Note 3)	PASS
		BEP	14	0.0048		
		4.35	23	0.0060		
GSM 1900 CH661	GSM	3.8	-15	0.0000		
		BEP	-18	0.0016		
		4.35	-13	0.0011		
WCDMA Band V CH4182	RMC 12.2Kbps	3.8	1	0.0000		
		BEP	-1	0.0024		
		4.35	3	0.0024		
WCDMA Band II CH9400	RMC 12.2Kbps	3.8	3	0.0000		
		BEP	4	0.0005		
		4.35	3	0.0000		

Note:

1. Normal Voltage = 3.8V.
2. Battery End Point (BEP) = 3.2 V.
3. The frequency fundamental emissions stay within the authorized frequency block based on the frequency deviation measured is small.

4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV30	101338	9kHz~30GHz	May 04, 2014	Sep. 23, 2014~ Sep. 25, 2014	May 03, 2015	Conducted (TH01-KS)
Thermal Chamber	Ten Billion	TTC-B3S	TBN-960502	-40~+150°C	Dec. 10, 2013	Sep. 23, 2014~ Sep. 25, 2014	Dec. 09, 2014	Conducted (TH01-KS)
EMI Test Receiver	R&S	ESCI	100534	9kHz~3GHz	Nov. 05, 2013	Oct. 01, 2014	Nov. 04, 2014	Radiation (03CH01-KS)
Spectrum Analyzer	R&S	FSP30	101399	9kHz~30GHz	May 04, 2014	Oct. 01, 2014	May 03, 2015	Radiation (03CH01-KS)
Bilog Antenna	SCHAFFNER	CBL6112D	23182	25MHz~2GHz	Jan. 08, 2014	Oct. 01, 2014	Jan. 07, 2015	Radiation (03CH01-KS)
Double Ridge Horn Antenna	ETS-Lindgren	3117	75959	1GHz~18GHz	Jan. 08, 2014	Oct. 01, 2014	Jan. 07, 2015	Radiation (03CH01-KS)
Active Horn Antenna	com-power	AHA-118	701030	1GHz~18GHz	Nov. 18, 2013	Oct. 01, 2014	Nov. 17, 2014	Radiation (03CH01-KS)
SHF-EHF Horn	Schwarzbeck	BBHA 9170	BBHA170249	15GHz~40GHz	Mar. 10, 2014	Oct. 01, 2014	Mar. 09, 2015	Radiation (03CH01-KS)
Amplifier	com-power	PA-103A	161073	1MHz~1GHz	May 04, 2014	Oct. 01, 2014	May 03, 2015	Radiation (03CH01-KS)
Amplifier	Agilent	8449B	3008A02371	1GHz~26.5GHz	Dec. 10, 2013	Oct. 01, 2014	Dec. 09, 2014	Radiation (03CH01-KS)
AC Power Source	Chroma	61601	F104090004	N/A	NCR	Oct. 01, 2014	NCR	Radiation (03CH01-KS)
Turn Table	MF	MF7802	N/A	0~360 degree	NCR	Oct. 01, 2014	NCR	Radiation (03CH01-KS)
Antenna Mast	MF	MF7802	N/A	1 m~4 m	NCR	Oct. 01, 2014	NCR	Radiation (03CH01-KS)

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSP 7	100819	9kHz~7GHz	May 04, 2014	Sep. 23, 2014~ Sep. 25, 2014	May 03, 2015	ERP/EIRP (OTA01-KS)
Switch Control Manframe	Agilent	3499A	MY42005452	N/A	N/A	Sep. 23, 2014~ Sep. 25, 2014	N/A	ERP/EIRP (OTA01-KS)
Dual 1-to-6(4) MW MUX	Agilent	N2276A	MY42000841	N/A	N/A	Sep. 23, 2014~ Sep. 25, 2014	N/A	ERP/EIRP (OTA01-KS)
Microwave Switch	Agilent	44476A	MY42002573	N/A	N/A	Sep. 23, 2014~ Sep. 25, 2014	N/A	ERP/EIRP (OTA01-KS)
Microwave Switch	Agilent	44476A	MY42002586	N/A	N/A	Sep. 23, 2014~ Sep. 25, 2014	N/A	ERP/EIRP (OTA01-KS)
Diagonal Dual Polarized Horn	ETS-Lindgren	3164-04	00066993	700MHz~6GHz	N/A	Sep. 23, 2014~ Sep. 25, 2014	N/A	ERP/EIRP (OTA01-KS)
Multi-Devices Controller	ETS-Lindgren	2090-OPT1	00066604	N/A	N/A	Sep. 23, 2014~ Sep. 25, 2014	N/A	ERP/EIRP (OTA01-KS)
Conical Log Spiral (Small)	ETS-Lindgren	3102	00066951	1~10GHz	N/A	Sep. 23, 2014~ Sep. 25, 2014	N/A	ERP/EIRP (OTA01-KS)
Turn Table	ETS-Lindgren	2088	N/A	Resolution :0.1deg	N/A	Sep. 23, 2014~ Sep. 25, 2014	N/A	ERP/EIRP (OTA01-KS)
Limiting Amplifier	ETS-lindgren	109643	920326	10MHz~2.5GHz	N/A	Sep. 23, 2014~ Sep. 25, 2014	N/A	ERP/EIRP (OTA01-KS)
EMQuest	ETS-Lindgren	EMQ-100	1125	N/A	N/A	Sep. 23, 2014~ Sep. 25, 2014	N/A	ERP/EIRP (OTA01-KS)
Medium Duty Holder	ETS-Lindgren	2015	N/A	N/A	N/A	Sep. 23, 2014~ Sep. 25, 2014	N/A	ERP/EIRP (OTA01-KS)

5 Uncertainty of Evaluation

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	**2.5**