

FCC RF Test Report


APPLICANT : CT Asia
EQUIPMENT : Smart Phone
BRAND NAME : BLU
MODEL NAME : Selfie
FCC ID : YHLBLUSELFIE
STANDARD : FCC Part 15 Subpart C §15.247
CLASSIFICATION : (DTS) Digital Transmission System

The product was received on Dec. 13, 2014 and testing was completed on Jan. 08, 2015. We, SPORTON INTERNATIONAL (SHENZHEN) INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL (SHENZHEN) INC., the test report shall not be reproduced except in full.



Reviewed by: Joseph Lin / Supervisor



Approved by: Jones Tsai / Manager



SPORTON INTERNATIONAL (SHENZHEN) INC.

1F & 2F, Building A, Morning Business Center, No. 4003 ShiGu Rd., Xili Town,
Nanshan District, Shenzhen, Guangdong, P. R. China



TABLE OF CONTENTS

REVISION HISTORY.....	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION	5
1.1 Applicant.....	5
1.2 Manufacturer.....	5
1.3 Product Feature of Equipment Under Test.....	5
1.4 Product Specification subjective to this standard	5
1.5 Modification of EUT	5
1.6 Testing Location	6
1.7 Applicable Standards.....	6
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST	7
2.1 Carrier Frequency Channel	7
2.2 Pre-Scanned RF Power.....	8
2.3 Test Mode.....	9
2.4 Connection Diagram of Test System.....	10
2.5 Support Unit used in test configuration and system	11
2.6 EUT Operation Test Setup	11
2.7 Measurement Results Explanation Example.....	11
3 TEST RESULT.....	12
3.1 6dB Bandwidth Measurement	12
3.2 Output Power Measurement.....	15
3.3 Power Spectral Density Measurement	18
3.4 Conducted Band Edges and Spurious Emission Measurement	21
3.5 Radiated Band Edges and Spurious Emission Measurement	34
3.6 AC Conducted Emission Measurement.....	38
3.7 Antenna Requirements.....	42
4 LIST OF MEASURING EQUIPMENT	43
5 UNCERTAINTY OF EVALUATION	44
APPENDIX A. RADIATED TEST RESULTS	
APPENDIX B. SETUP PHOTOGRAPHS	



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR4D1301C	Rev. 01	Initial issue of report	Jan. 13, 2015



SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(2)	6dB Bandwidth	$\geq 0.5\text{MHz}$	Pass	-
3.2	15.247(b)	Power Output Measurement	$\leq 30\text{dBm}$	Pass	-
3.3	15.247(e)	Power Spectral Density	$\leq 8\text{dBm}/3\text{kHz}$	Pass	-
3.4	15.247(d)	Conducted Band Edges	$\leq 20\text{dBc}$	Pass	-
		Conducted Spurious Emission		Pass	-
3.5	15.247(d)	Radiated Band Edges and Radiated Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 1.61 dB at 2483.560 MHz
3.6	15.207	AC Conducted Emission	15.207(a)	Pass	Under limit 18.31 dB at 0.400 MHz
3.7	15.203 & 15.247(b)	Antenna Requirement	N/A	Pass	-

1 General Description

1.1 Applicant

CT Asia

Unit 01, 15/F, Seaview Centre, 139-141 Hoi bun road, Kwun Tong, Kowloon, Hongkong

1.2 Manufacturer

Longcheer Technology (Shanghai) Co.,Ltd.

Building 1, No.401, Caobao Rd, Xuhui District, Shanghai, P.R.China

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Smart Phone
Brand Name	BLU
Model Name	Selfie
FCC ID	YHLBLUELFIE
EUT supports Radios application	GSM/GPRS/EGPRS/ WCDMA/HSPA/HSPA+ (Downlink Only)/ WLAN 2.4GHz 802.11b/g/n HT20/HT40 Bluetooth v3.0 + EDR/Bluetooth v4.0 LE
HW Version	LWDM030B
SW Version	BLU-S470A-V01-GENERIC_21-11-2014_16:39
EUT Stage	Production Unit

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Product Specification subjective to this standard

Product Specification subjective to this standard	
Tx/Rx Channel Frequency Range	802.11b/g/n : 2412 MHz ~ 2462 MHz
Maximum (Peak) Output Power to Antenna	802.11b : 19.32 dBm (0.0855 W) 802.11g : 20.62 dBm (0.1153 W) 802.11n HT20 : 20.63 dBm (0.1156 W) 802.11n HT40 : 21.12 dBm (0.1294 W)
Antenna Type	802.11b/g/n : IFA Antenna with gain -3 dBi
Type of Modulation	802.11b : DSSS (DBPSK / DQPSK / CCK) 802.11g/n : OFDM (BPSK / QPSK / 16QAM / 64QAM)

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Testing Location

Test Site	SPORTON INTERNATIONAL (SHENZHEN) INC.	
Test Site Location	1F & 2F,Building A, Morning Business Center, No. 4003 ShiGu Rd., Xili Town, Nanshan District, Shenzhen, Guangdong, P. R. China TEL: +86-755-8637-9589 FAX: +86-755-8637-9595	
Test Site No.	Sporton Site No.	
	TH01-SZ	CO01-SZ

Test Site	SPORTON INTERNATIONAL (SHENZHEN) INC.	
Test Site Location	No. 3 Building, the third floor of south, Shahe River west, Fengzeyuan warehouse, Nanshan District, Shenzhen, Guangdong, P. R. China TEL: +86-755- 3320-2398	
Test Site No.	Sporton Site No.	FCC Registration No.
	03CH01-SZ	831040

1.7 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart C §15.247
- ♦ FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r02
- ♦ ANSI C63.10-2009

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conducted emission (150 kHz to 30 MHz) and radiated emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (Z plane) were recorded in this report.

The final configuration from all the combinations and the worst-case data rates were investigated by measuring the maximum power across all the data rates and modulation modes under section 2.2.

Based on the worst configuration found above, the RF power setting is set individually to meet FCC compliance limit for the final conducted and radiated tests shown in section 2.3.

2.1 Carrier Frequency Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	1	2412	7	2442
	2	2417	8	2447
	3	2422	9	2452
	4	2427	10	2457
	5	2432	11	2462
	6	2437	-	-



2.2 Pre-Scanned RF Power

Preliminary tests were performed in different data rate and data rate associated with the highest power were chosen for full test shown in the following tables.

2.4GHz 802.11b RF Output Power (dBm)						
Power vs. Channel			Power vs. Data Rate			
Channel	Frequency (MHz)	Data Rate 1Mbps	Channel	2Mbps	5.5Mbps	11Mbps
CH 01	2412 MHz	19.01	CH 06	19.30	19.27	19.28
CH 06	2437 MHz	19.32				
CH 11	2462 MHz	19.17				

2.4GHz 802.11g RF Output Power (dBm)										
Power vs. Channel			Power vs. Data Rate							
Channel	Frequency (MHz)	Data Rate	Channel	9Mbps	12Mbps	18Mbps	24Mbps	36Mbps	48Mbps	54Mbps
		6Mbps								
CH 01	2412 MHz	20.59	CH 11	20.54	20.56	20.58	20.57	20.60	20.58	20.59
CH 06	2437 MHz	20.55								
CH 11	2462 MHz	20.62								

2.4GHz 802.11n HT20 RF Output Power (dBm)										
Power vs. Channel			Power vs. MCS Index							
Channel	Frequency (MHz)	MCS Index	Channel	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
		MCS0								
CH 01	2412 MHz	20.47	CH 11	20.45	20.31	20.51	20.55	20.58	20.56	20.58
CH 06	2437 MHz	20.57								
CH 11	2462 MHz	20.63								

2.4GHz 802.11n HT40 RF Output Power (dBm)										
Power vs. Channel			Power vs. MCS Index							
Channel	Frequency (MHz)	MCS Index	Channel	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
		MCS0								
CH 03	2422 MHz	19.88	CH 09	19.14	19.55	19.37	19.35	20.10	19.89	20.08
CH 06	2437 MHz	20.05								
CH 09	2452 MHz	21.12								


2.3 Test Mode

Final results of test modes, data rates and test channels are shown as following table.


Test Cases				
Conducted TCs	Test Items	Mode	Data Rate	Test Channel
	6dB BW Power Spectral Density	802.11b	1 Mbps	1/6/11
		802.11g	6 Mbps	1/6/11
		802.11n HT20	MCS0	1/6/11
		802.11n HT40	MCS0	3/6/9
	Output Power	802.11b	1 Mbps	1/6/11
		802.11g	6 Mbps	1/6/11
		802.11n HT20	MCS0	1/6/11
		802.11n HT40	MCS0	3/6/9
	Conducted Band Edge	802.11b	1 Mbps	1/11
		802.11g	6 Mbps	1/11
		802.11n HT20	MCS0	1/11
		802.11n HT40	MCS0	3/9
	Conducted Spurious Emission	802.11b	1 Mbps	1/6/11
		802.11g	6 Mbps	1/6/11
		802.11n HT20	MCS0	1/6/11
802.11n HT40		MCS0	3/6/9	
Radiated TCs	Radiated Band Edge	802.11b	1 Mbps	1/11
		802.11g	6 Mbps	1/11
		802.11n HT20	MCS0	1/11
		802.11n HT40	MCS0	3/9
	Radiated Spurious Emission	802.11b	1 Mbps	1/6/11
		802.11g	6 Mbps	1/6/11
		802.11n HT20	MCS0	1/6/11
		802.11n HT40	MCS0	3/6/9
AC Conducted Emission	Mode 1 : GSM850 Idle + Bluetooth Link + WLAN Link + USB Cable (Charging from Adapter) + Earphone + Battery			
Remark: For radiated test cases, the tests were performance with adapter, earphone and USB cable.				

2.4 Connection Diagram of Test System

<WLAN Tx Mode>



<AC Conducted Emission Mode>



2.5 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMW 500	N/A	N/A	Unshielded, 1.8 m
2.	WLAN AP	D-Link	DIR-815	KA2IR815A1	N/A	Unshielded, 1.8 m
3.	Notebook	Lenovo	G480	FCC DoC	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
4.	Bluetooth Earphone	Nokia	BH-108	PYAHS-107W	N/A	N/A

2.6 EUT Operation Test Setup

For WLAN function, the engineering test program was provided and enabled to make EUT continuous transmit/receive.

For AC power line conducted emissions, the EUT was set to connect with the WLAN AP under large package sizes transmission.

2.7 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 5 dB and 10dB attenuator.

$$\begin{aligned}
 \text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)}. \\
 &= 5 + 10 = 15 \text{ (dB)}
 \end{aligned}$$

3 Test Result

3.1 6dB Bandwidth Measurement

3.1.1 Limit of 6dB Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.

3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 DTS D01 Meas. Guidance v03r02.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
5. Measure and record the results in the test report.


3.1.4 Test Setup



**3.1.5 Test Result of 6dB Bandwidth**

Test Band :	2.4GHz	Temperature :	24~26℃
Test Engineer :	Mygai Mo	Relative Humidity :	50~53%

Mod.	Data Rate	N_{TX}	Channel	Freq. (MHz)	6dB Bandwidth (MHz)	6dB Bandwidth Min. Limit (MHz)	Pass/Fail
11b	1Mbps	1	1	2412	10.04	0.5	Pass
11b	1Mbps	1	6	2437	9.54	0.5	Pass
11b	1Mbps	1	11	2462	10.00	0.5	Pass
11g	6Mbps	1	1	2412	15.44	0.5	Pass
11g	6Mbps	1	6	2437	15.44	0.5	Pass
11g	6Mbps	1	11	2462	15.32	0.5	Pass
HT20	MCS0	1	1	2412	15.32	0.5	Pass
HT20	MCS0	1	6	2437	15.14	0.5	Pass
HT20	MCS0	1	11	2462	15.12	0.5	Pass
HT40	MCS0	1	3	2422	35.12	0.5	Pass
HT40	MCS0	1	6	2437	35.12	0.5	Pass
HT40	MCS0	1	9	2452	35.12	0.5	Pass



Note : The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

3.2 Output Power Measurement

3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. If transmitting Antenna of directional gain greater than 6dBi are used the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the Antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the Antenna exceeds 6dBi.

3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.2.3 Test Procedures

1. The testing follows the Measurement Procedure of FCC KDB No. 558074 DTS D01 Meas. Guidance v03r02.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power and record the results in the test report.

3.2.4 Test Setup



**3.2.5 Test Result of Peak Output Power**

Test Mode :	2.4GHz	Temperature :	24~26℃
Test Engineer :	Mygai Mo	Relative Humidity :	50~53%

Mod.	Data Rate	N _{TX}	Channel	Freq. (MHz)	RF Output Power (dBm)	Power Limit (dBm)	DG (dBi)	Pass/Fail
11b	1Mbps	1	1	2412	19.01	30	-3.00	Pass
11b	1Mbps	1	6	2437	19.32	30	-3.00	Pass
11b	1Mbps	1	11	2462	19.17	30	-3.00	Pass
11g	6Mbps	1	1	2412	20.59	30	-3.00	Pass
11g	6Mbps	1	6	2437	20.55	30	-3.00	Pass
11g	6Mbps	1	11	2462	20.62	30	-3.00	Pass
HT20	MCS0	1	1	2412	20.47	30	-3.00	Pass
HT20	MCS0	1	6	2437	20.57	30	-3.00	Pass
HT20	MCS0	1	11	2462	20.63	30	-3.00	Pass
HT40	MCS0	1	3	2422	19.88	30	-3.00	Pass
HT40	MCS0	1	6	2437	20.05	30	-3.00	Pass
HT40	MCS0	1	9	2452	21.12	30	-3.00	Pass

Note: Measured power (dBm) has offset with cable loss.

**3.2.6 Test Result of Average output Power (Reporting Only)**

Test Mode :	2.4GHz	Temperature :	24~26℃
Test Engineer :	Mygai Mo	Relative Humidity :	50~53%

Mod.	Data Rate	N _{TX}	Channel	Freq. (MHz)	Duty Factor (dB)	Average Output Power (dBm)	Power Limit (dBm)	DG (dBi)	Pass/Fail
11b	1Mbps	1	1	2412	0.10	16.43	30	-3.00	Pass
11b	1Mbps	1	6	2437	0.10	16.85	30	-3.00	Pass
11b	1Mbps	1	11	2462	0.10	16.63	30	-3.00	Pass
11g	6Mbps	1	1	2412	0.50	12.56	30	-3.00	Pass
11g	6Mbps	1	6	2437	0.50	12.58	30	-3.00	Pass
11g	6Mbps	1	11	2462	0.50	12.80	30	-3.00	Pass
HT20	MCS0	1	1	2412	0.54	12.52	30	-3.00	Pass
HT20	MCS0	1	6	2437	0.54	12.59	30	-3.00	Pass
HT20	MCS0	1	11	2462	0.54	12.79	30	-3.00	Pass
HT40	MCS0	1	3	2422	1.06	10.49	30	-3.00	Pass
HT40	MCS0	1	6	2437	1.06	10.72	30	-3.00	Pass
HT40	MCS0	1	9	2452	1.06	10.82	30	-3.00	Pass

Note: Measured power (dBm) has offset with cable loss and duty factor.

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.


3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.3.3 Test Procedures

1. The testing follows Measurement Procedure 10.2 Method PKPSD of FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r02
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.

3.3.4 Test Setup






3.3.5 Test Result of Power Spectral Density

Test Mode :	2.4GHz	Temperature :	24~26℃
Test Engineer :	Mygai Mo	Relative Humidity :	50~53%

Mod.	Data Rate	N _{TX}	Channel	Freq. (MHz)	Peak Power Density (dBm/3kHz)	Max. Limits (dBm/3kHz)	DG (dBi)	Pass/Fail
11b	1Mbps	1	1	2412	-6.68	8	-3.00	Pass
11b	1Mbps	1	6	2437	-6.11	8	-3.00	Pass
11b	1Mbps	1	11	2462	-5.76	8	-3.00	Pass
11g	6Mbps	1	1	2412	-11.95	8	-3.00	Pass
11g	6Mbps	1	6	2437	-11.14	8	-3.00	Pass
11g	6Mbps	1	11	2462	-12.08	8	-3.00	Pass
HT20	MCS0	1	1	2412	-12.55	8	-3.00	Pass
HT20	MCS0	1	6	2437	-12.25	8	-3.00	Pass
HT20	MCS0	1	11	2462	-11.48	8	-3.00	Pass
HT40	MCS0	1	3	2422	-17.78	8	-3.00	Pass
HT40	MCS0	1	6	2437	-17.01	8	-3.00	Pass
HT40	MCS0	1	9	2452	-17.14	8	-3.00	Pass

Note: Measured power density (dBm) has offset with cable loss.



3.4 Conducted Band Edges and Spurious Emission Measurement

3.4.1 Limit of Conducted Band Edges and Spurious Emission Measurement

In any 100 kHz bandwidth outside of the authorized frequency band, the emissions which fall in the non-restricted bands shall be attenuated at least 20 dB / 30dB relative to the maximum PSD level in 100 kHz by RF conducted measurement and radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).


3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.4.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r02.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB per 15.247(d).
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.4.4 Test Setup






3.4.5 Test Result of Conducted Band Edges and Spurious Emission

Test Mode :	802.11b	Temperature :	24~26℃
Test Band :	2.4GHz Low	Relative Humidity :	50~53%
Test Channel :	01	Test Engineer :	Mygai Mo


WLAN 802.11b Channel 01

100kHz PSD reference Level




Date: 18.DEC.2014 20:28:44

Low Channel Plot




Date: 18.DEC.2014 20:30:20

Spurious Emission 30MHz~3GHz



Date: 18.DEC.2014 20:34:03

Spurious Emission 2GHz~25GHz




Date: 18.DEC.2014 20:34:20



Test Mode :	802.11b	Temperature :	24~26°C
Test Band :	2.4GHz Mid	Relative Humidity :	50~53%
Test Channel :	06	Test Engineer :	Mygai Mo


WLAN 802.11b Channel 06

100kHz PSD reference Level




Date: 18.DEC.2014 20:36:27

Spurious Emission 30MHz~3GHz



Date: 18.DEC.2014 20:37:01

Spurious Emission 2GHz~25GHz




Date: 18.DEC.2014 20:37:19



Test Mode :	802.11b	Temperature :	24~26°C
Test Band :	2.4GHz High	Relative Humidity :	50~53%
Test Channel :	11	Test Engineer :	Mygai Mo


WLAN 802.11b Channel 11

100kHz PSD reference Level




Date: 18.DEC.2014 20:42:51

High Channel Plot




Date: 18.DEC.2014 20:45:18

Spurious Emission 30MHz~3GHz



Date: 18.DEC.2014 20:45:50

Spurious Emission 2GHz~25GHz




Date: 18.DEC.2014 20:46:08



Test Mode :	802.11g	Temperature :	24~26°C
Test Band :	2.4GHz Low	Relative Humidity :	50~53%
Test Channel :	01	Test Engineer :	Mygai Mo


WLAN 802.11g Channel 01

100kHz PSD reference Level




Date: 18.DEC.2014 20:52:18

Low Channel Plot




Date: 18.DEC.2014 20:53:07

Spurious Emission 30MHz~3GHz



Date: 18.DEC.2014 20:53:36

Spurious Emission 2GHz~25GHz




Date: 18.DEC.2014 20:53:53

Test Mode :	802.11g	Temperature :	24~26℃
Test Band :	2.4GHz Mid	Relative Humidity :	50~53%
Test Channel :	06	Test Engineer :	Mygai Mo


WLAN 802.11g Channel 06

100kHz PSD reference Level




Date: 18.DEC.2014 20:57:06

Spurious Emission 30MHz~3GHz



Date: 18.DEC.2014 20:57:46

Spurious Emission 2GHz~25GHz




Date: 18.DEC.2014 20:58:04



Test Mode :	802.11g	Temperature :	24~26°C
Test Band :	2.4GHz High	Relative Humidity :	50~53%
Test Channel :	11	Test Engineer :	Mygai Mo


WLAN 802.11g Channel 11

100kHz PSD reference Level




Date: 18.DEC.2014 21:03:24

High Channel Plot




Date: 18.DEC.2014 21:04:24

Spurious Emission 30MHz~3GHz



Date: 18.DEC.2014 21:04:45

Spurious Emission 2GHz~25GHz




Date: 18.DEC.2014 21:05:03



Test Mode :	802.11n HT20	Temperature :	24~26°C
Test Band :	2.4GHz Low	Relative Humidity :	50~53%
Test Channel :	01	Test Engineer :	Mygai Mo


WLAN 802.11n HT20 Channel 01

100kHz PSD reference Level




Date: 18.DEC.2014 21:26:26

Low Channel Plot




Date: 18.DEC.2014 21:26:46

Spurious Emission 30MHz~3GHz



Date: 18.DEC.2014 21:27:14

Spurious Emission 2GHz~25GHz




Date: 18.DEC.2014 21:27:32



Test Mode :	802.11n HT20	Temperature :	24~26°C
Test Band :	2.4GHz Mid	Relative Humidity :	50~53%
Test Channel :	06	Test Engineer :	Mygai Mo


WLAN 802.11n HT20 Channel 06

100kHz PSD reference Level




Date: 18.DEC.2014 21:14:52

Spurious Emission 30MHz~3GHz



Date: 18.DEC.2014 21:15:16

Spurious Emission 2GHz~25GHz




Date: 18.DEC.2014 21:15:34



Test Mode :	802.11n HT20	Temperature :	24~26°C
Test Band :	2.4GHz High	Relative Humidity :	50~53%
Test Channel :	11	Test Engineer :	Mygai Mo


WLAN 802.11n HT20 Channel 11

100kHz PSD reference Level




Date: 18.DEC.2014 21:19:26

High Channel Plot




Date: 18.DEC.2014 21:21:30

Spurious Emission 30MHz~3GHz



Date: 18.DEC.2014 21:21:53

Spurious Emission 2GHz~25GHz




Date: 18.DEC.2014 21:22:11



Test Mode :	802.11n HT40	Temperature :	24~26°C
Test Band :	2.4GHz Low	Relative Humidity :	50~53%
Test Channel :	03	Test Engineer :	Mygai Mo


WLAN 802.11n HT40 Channel 03

100kHz PSD reference Level




Date: 18.DEC.2014 22:33:57

Low Channel Plot




Date: 18.DEC.2014 22:34:23

Spurious Emission 30MHz~3GHz



Date: 8.JAN.2015 16:23:34

Spurious Emission 2GHz~25GHz




Date: 18.DEC.2014 22:37:29



Test Mode :	802.11n HT40	Temperature :	24~26°C
Test Band :	2.4GHz Mid	Relative Humidity :	50~53%
Test Channel :	06	Test Engineer :	Mygai Mo


WLAN 802.11n HT40 Channel 06

100kHz PSD reference Level




Date: 18.DEC.2014 21:37:45

Spurious Emission 30MHz~3GHz



Date: 18.DEC.2014 21:39:17

Spurious Emission 2GHz~25GHz




Date: 18.DEC.2014 21:39:35



Test Mode :	802.11n HT40	Temperature :	24~26°C
Test Band :	2.4GHz High	Relative Humidity :	50~53%
Test Channel :	09	Test Engineer :	Mygai Mo


WLAN 802.11n HT40 Channel 09

100kHz PSD reference Level




Date: 18.DEC.2014 21:42:22

High Channel Plot




Date: 18.DEC.2014 21:42:47

Spurious Emission 30MHz~3GHz



Date: 8.JAN.2015 16:24:32

Spurious Emission 2GHz~25GHz



Date: 18.DEC.2014 21:49:14

3.5 Radiated Band Edges and Spurious Emission Measurement

3.5.1 Limit of Radiated band edge and Spurious Emission Measurement

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the FCC section 15.209 limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.5.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r02.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 0.8 meter for frequency above 1GHz respectively above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
7. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW=100 kHz for $f < 1$ GHz; VBW $\geq$ RBW; Sweep = auto; Detector function = peak; Trace = max hold;
 - (3) Set RBW = 1 MHz, VBW= 3MHz for $f \geq 1$ GHz for peak measurement.


For average measurement:

 - VBW = 10 Hz, when duty cycle is no less than 98 percent.
 - VBW $\geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.


Band	Duty Cycle(%)	T(ms)	1/T(kHz)	VBW Setting
802.11b	97.67	8.40	0.12	300Hz
802.11g	89.13	1.39	0.72	1kHz
2.4GHz 802.11n HT20	88.29	1.30	0.77	1kHz
2.4GHz 802.11n HT40	78.25	0.64	1.56	3kHz

3.5.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



3.5.5 Test Results of Radiated Spurious Emissions (9kHz ~ 30MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.

3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix A.

3.5.7 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix A.

3.6 AC Conducted Emission Measurement

3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of Emission (MHz)	Conducted Limit (dB μ V)	
	Quasi-Peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.6.3 Test Procedures


1. The EUT was placed 0.4 meter from the conducting wall of the shielding room, and it was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF bandwidth = 9kHz) with Maximum Hold Mode.

3.6.4 Test Setup



3.6.5 Test Result of AC Conducted Emission

Test Mode :	Mode 1	Temperature :	21~22℃
Test Engineer :	Jack Tian	Relative Humidity :	41~42%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	GSM850 Idle + Bluetooth Link + WLAN Link + USB Cable (Charging from Adapter) + Earphone + Battery		




Site : CO01-SZ
Condition: FCC 15C_QP LISN_L_20140304 LINE

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.17	29.75	-25.28	55.03	19.20	0.22	10.33	Average
2	0.17	44.65	-20.38	65.03	34.10	0.22	10.33	QP
3	0.18	29.53	-24.84	54.37	19.00	0.22	10.31	Average
4	0.18	43.43	-20.94	64.37	32.90	0.22	10.31	QP
5	0.20	28.41	-25.04	53.45	17.90	0.22	10.29	Average
6	0.20	41.21	-22.24	63.45	30.70	0.22	10.29	QP
7	0.26	20.87	-30.42	51.29	10.40	0.24	10.23	Average
8	0.26	35.77	-25.52	61.29	25.30	0.24	10.23	QP
9	0.32	26.46	-23.16	49.62	16.01	0.26	10.19	Average
10	0.32	34.26	-25.36	59.62	23.81	0.26	10.19	QP
11 *	0.40	29.55	-18.31	47.86	19.10	0.28	10.17	Average
12	0.40	36.75	-21.11	57.86	26.30	0.28	10.17	QP



Test Mode :	Mode 1	Temperature :	21~22℃
Test Engineer :	Jack Tian	Relative Humidity :	41~42%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	GSM850 Idle + Bluetooth Link + WLAN Link + USB Cable (Charging from Adapter) + Earphone + Battery		



Site : C001-SZ
Condition: FCC 15C_QP LISN_N_20140304 NEUTRAL

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.19	28.22	-25.62	53.84	17.60	0.32	10.30	Average
2	0.19	41.32	-22.52	63.84	30.70	0.32	10.30	QP
3	0.41	24.46	-23.13	47.59	13.90	0.39	10.17	Average
4 *	0.41	37.86	-19.73	57.59	27.30	0.39	10.17	QP
5	0.53	24.04	-21.96	46.00	13.51	0.38	10.15	Average
6	0.53	35.94	-20.06	56.00	25.41	0.38	10.15	QP
7	0.80	20.73	-25.27	46.00	10.30	0.28	10.15	Average
8	0.80	32.13	-23.87	56.00	21.70	0.28	10.15	QP
9	1.15	21.90	-24.10	46.00	11.40	0.34	10.16	Average
10	1.15	32.70	-23.30	56.00	22.20	0.34	10.16	QP
11	1.87	19.65	-26.35	46.00	9.10	0.37	10.18	Average
12	1.87	29.45	-26.55	56.00	18.90	0.37	10.18	QP



3.7 Antenna Requirements

3.7.1 Standard Applicable

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. For the fixed point-to-point operation, the power shall be reduced by one dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the FCC rule.

3.7.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.7.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSP30	101400	9kHz~30GHz	Mar. 03, 2014	Dec. 18, 2014~ Jan. 08, 2015	Mar. 02, 2015	Conducted (TH01-SZ)
Power Meter	Anritsu	ML2495A	1218010	13dBm ~-20dBm	Mar. 03, 2014	Dec. 18, 2014~ Jan. 08, 2015	Mar. 02, 2015	Conducted (TH01-SZ)
Power Sensor	Dare	RPR3006W	TH01SZ00 019	0.3GHz~6GHz	Mar. 14, 2014	Dec. 18, 2014~ Jan. 08, 2015	Mar. 13, 2015	Conducted (TH01-SZ)
ESCIO TEST Receiver	R&S	ESCI	100724	9kHz~3GHz	Feb. 21, 2014	Jan. 07, 2015	Feb. 20, 2015	Radiation (03CH01-SZ)
Spectrum Analyzer	Agilent Technologies	N9038A	MY522601 85	20Hz~26.5GHz	May 26, 2014	Jan. 07, 2015	May 25, 2015	Radiation (03CH01-SZ)
Loop Antenna	R&S	HFH2-Z2	100354	9kHz~30MHz	May 09, 2014	Jan. 07, 2015	May 08, 2015	Radiation (03CH01-SZ)
Bilog Antenna	TESEQ	CBL 6112D	37877	30MHz~2GHz	Oct. 15, 2014	Jan. 07, 2015	Oct. 14, 2015	Radiation (03CH01-SZ)
Double Ridge Horn Antenna	ETS Lindgren	3117	00119436	1GHz~18GHz	Oct. 15, 2014	Jan. 07, 2015	Oct. 14, 2015	Radiation (03CH01-SZ)
Double Ridged Horn Antenna	COM-POWER	AH-840	101073	18GHz~40GHz	Jun. 09, 2014	Jan. 07, 2015	Jun. 08, 2015	Radiation (03CH01-SZ)
Amplifier	ADVANTEST	BB525C	E9007003	9kHz~3000MHz	Feb. 21, 2014	Jan. 07, 2015	Feb. 20, 2015	Radiation (03CH01-SZ)
Amplifier	Yiai	AV3860B	04030	2GHz~26.5GHz	May 08, 2014	Jan. 07, 2015	May 07, 2015	Radiation (03CH01-SZ)
AC Source(AVR)	Chroma	61601	616010001 985	100Vac~250Vac	Mar. 25, 2014	Jan. 07, 2015	Mar. 24, 2015	Radiation (03CH01-SZ)
Turn Table	EM Electronics	EM 1000	N/A	0~360 degree	NCR	Jan. 07, 2015	NCR	Radiation (03CH01-SZ)
Antenna Mast	EM Electronics	EM 1000	N/A	1 m~4 m	NCR	Jan. 07, 2015	NCR	Radiation (03CH01-SZ)
ESCIO TEST Receiver	R&S	ESCI	100724	9kHz~3GHz	Feb. 21, 2014	Dec. 17, 2014	Feb. 20, 2015	Conduction (CO01-SZ)
AC LISN	EMCO	3816/2SH	00103912	9kHz~30MHz	Mar. 04, 2014	Dec. 17, 2014	Mar. 03, 2015	Conduction (CO01-SZ)
AC LISN (for auxiliary equipment)	EMCO	3816/2SH	00103892	9kHz~30MHz	Mar. 04, 2014	Dec. 17, 2014	Mar. 03, 2015	Conduction (CO01-SZ)
AC Power Source	Chroma	61602	616020000 891	100Vac~250Vac	Sep. 29, 2014	Dec. 17, 2014	Sep. 28, 2015	Conduction (CO01-SZ)



5 Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	2.3dB
---	-------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	3.9dB
---	-------



Appendix A. Radiated Spurious Emission

15C 2.4GHz 2400~2483.5MHz

WIFI 802.11b (Band Edge @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b CH 01 2412MHz		2386.23	53.61	-20.39	74	41.67	32.6	8.6	29.26	200	142	P	H
		2387.22	46.45	-7.55	54	34.51	32.6	8.6	29.26	200	142	A	H
	*	2412	100.28	-	-	88.31	32.61	8.6	29.24	200	142	P	H
	*	2412	98.29	-	-	86.32	32.61	8.6	29.24	200	142	A	H
		2386.95	54.05	-19.95	74	42.11	32.6	8.6	29.26	195	138	P	V
		2387.04	46.35	-7.65	54	34.41	32.6	8.6	29.26	195	138	A	V
	*	2412	99.84	-	-	87.87	32.61	8.6	29.24	195	138	P	V
	*	2412	97.98	-	-	86.01	32.61	8.6	29.24	195	138	A	V
802.11b CH 06 2437MHz		2379.66	51.24	-22.76	74	39.37	32.58	8.51	29.22	193	133	P	H
		2382.45	40.13	-13.87	54	28.26	32.58	8.51	29.22	193	133	A	H
	*	2437	100.58	-	-	88.44	32.65	8.69	29.2	193	133	P	H
	*	2437	98.55	-	-	86.41	32.65	8.69	29.2	193	133	A	H
		2488.68	51.53	-22.47	74	39.19	32.7	8.78	29.14	193	133	P	H
		2485.68	40.42	-13.58	54	28.12	32.68	8.78	29.16	193	133	A	H
		2387.67	51.44	-22.56	74	39.5	32.6	8.6	29.26	195	125	P	V
		2379.75	40.49	-13.51	54	28.62	32.58	8.51	29.22	195	125	A	V
	*	2437	99.91	-	-	87.77	32.65	8.69	29.2	195	125	P	V
	*	2437	98.17	-	-	86.03	32.65	8.69	29.2	195	125	A	V
		2491.88	51.55	-22.45	74	39.21	32.7	8.78	29.14	195	125	P	V
		2489.32	40.56	-13.44	54	28.22	32.7	8.78	29.14	195	125	A	V



802.11b CH 11 2462MHz	*	2462	102.66	-	-	90.48	32.67	8.69	29.18	196	133	P	H
	*	2462	100.67	-	-	88.49	32.67	8.69	29.18	196	133	A	H
		2491.28	53.46	-20.54	74	41.12	32.7	8.78	29.14	196	133	P	H
		2486.8	43.39	-10.61	54	31.09	32.68	8.78	29.16	196	133	A	H
	*	2462	95.25	-	-	83.07	32.67	8.69	29.18	198	119	P	V
	*	2462	93.56	-	-	81.38	32.67	8.69	29.18	198	119	A	V
		2486.68	51.67	-22.33	74	39.37	32.68	8.78	29.16	198	119	P	V
		2486.96	40.71	-13.29	54	28.41	32.68	8.78	29.16	198	119	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



15C 2.4GHz 2400~2483.5MHz

WIFI 802.11b (Harmonic @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b		4824	52.69	-21.31	74	56.17	34.4	12.86	50.74	109	312	P	H
CH 01		4824	51.2	-2.8	54	54.68	34.4	12.86	50.74	109	312	A	H
2412MHz		4824	44.51	-29.49	74	47.99	34.4	12.86	50.74	200	360	P	V
802.11b		4874	44.08	-29.92	74	47.31	34.43	12.92	50.58	100	360	P	H
CH 06		7311	42.39	-31.61	74	42.34	36.22	14.71	50.88	174	100	P	H
2437MHz		4874	43.5	-30.5	74	46.73	34.43	12.92	50.58	100	360	P	V
		7311	41.56	-32.44	74	41.51	36.22	14.71	50.88	174	100	P	V
802.11b		4924	39.03	-34.97	74	41.95	34.46	13.04	50.42	146	347	P	H
CH 11		7386	39.52	-34.48	74	39.39	36.26	14.75	50.88	145	274	P	H
2462MHz		4924	39.38	-34.62	74	42.3	34.46	13.04	50.42	146	347	P	V
		7386	40.12	-33.88	74	39.99	36.26	14.75	50.88	145	274	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



15C 2.4GHz 2400~2483.5MHz
WIFI 802.11g (Band Edge @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11g CH 01 2412MHz		2387.49	59.18	-14.82	74	47.24	32.6	8.6	29.26	194	61	P	H
		2389.74	45.3	-8.7	54	33.36	32.6	8.6	29.26	194	61	A	H
	*	2412	101.29	-	-	89.32	32.61	8.6	29.24	194	61	P	H
	*	2412	93.91	-	-	81.94	32.61	8.6	29.24	194	61	A	H
		2389.29	55.39	-18.61	74	43.45	32.6	8.6	29.26	194	59	P	V
		2389.92	43.19	-10.81	54	31.25	32.6	8.6	29.26	194	59	A	V
	*	2412	95.75	-	-	83.78	32.61	8.6	29.24	194	59	P	V
	*	2412	87.83	-	-	75.86	32.61	8.6	29.24	194	59	A	V
802.11g CH 06 2437MHz		2384.61	51.53	-22.47	74	39.57	32.58	8.6	29.22	200	63	P	H
		2383.71	40.9	-13.1	54	29.03	32.58	8.51	29.22	200	63	A	H
	*	2437	101.56	-	-	89.42	32.65	8.69	29.2	200	63	P	H
	*	2437	94.07	-	-	81.93	32.65	8.69	29.2	200	63	A	H
		2491.16	51.94	-22.06	74	39.6	32.7	8.78	29.14	200	63	P	H
		2484.12	41.36	-12.64	54	29.06	32.68	8.78	29.16	200	63	A	H
		2356.98	51.7	-22.3	74	39.81	32.56	8.51	29.18	157	137	P	V
		2378.76	40.91	-13.09	54	29.04	32.58	8.51	29.22	157	137	A	V
	*	2437	100.5	-	-	88.36	32.65	8.69	29.2	157	137	P	V
	*	2437	93.06	-	-	80.92	32.65	8.69	29.2	157	137	A	V
		2483.96	52.15	-21.85	74	39.85	32.68	8.78	29.16	157	137	P	V
		2487.84	41.64	-12.36	54	29.3	32.7	8.78	29.14	157	137	A	V



802.11g CH 11 2462MHz	*	2462	100.96	-	-	88.78	32.67	8.69	29.18	193	356	P	H
	*	2462	92.89	-	-	80.71	32.67	8.69	29.18	193	356	A	H
		2483.52	60.16	-13.84	74	47.86	32.68	8.78	29.16	193	356	P	H
		2483.52	46.86	-7.14	54	34.56	32.68	8.78	29.16	193	356	A	H
	*	2462	101.73	-	-	89.55	32.67	8.69	29.18	112	62	P	V
	*	2462	93.44	-	-	81.26	32.67	8.69	29.18	112	62	A	V
		2483.52	66.21	-7.79	74	53.91	32.68	8.78	29.16	112	62	P	V
		2483.56	48.25	-5.75	54	35.95	32.68	8.78	29.16	112	62	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



15C 2.4GHz 2400~2483.5MHz
WIFI 802.11g (Harmonic @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11g CH 01 2412MHz		4824	38.66	-35.34	74	42.14	34.4	12.86	50.74	110	360	P	H
		4824	38.31	-35.69	74	41.79	34.4	12.86	50.74	110	360	P	V
802.11g CH 06 2437MHz		4874	39.61	-34.39	74	42.84	34.43	12.92	50.58	100	360	P	H
		7311	42.34	-31.66	74	42.29	36.22	14.71	50.88	174	100	P	H
		4874	40.17	-33.83	74	43.4	34.43	12.92	50.58	100	360	P	V
		7311	42.89	-31.11	74	42.84	36.22	14.71	50.88	174	100	P	V
802.11g CH 11 2462MHz		4924	40.03	-33.97	74	42.95	34.46	13.04	50.42	146	347	P	H
		7386	42.51	-31.49	74	42.38	36.26	14.75	50.88	145	274	P	H
		4924	39.65	-34.35	74	42.57	34.46	13.04	50.42	146	347	P	V
		7386	41.69	-32.31	74	41.56	36.26	14.75	50.88	145	274	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



15C 2.4GHz 2400~2483.5MHz

WIFI 802.11n HT20 (Band Edge @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11n HT20 CH 01 2412MHz		2389.38	61.17	-12.83	74	49.23	32.6	8.6	29.26	168	61	P	H
		2389.92	48.15	-5.85	54	36.21	32.6	8.6	29.26	168	61	A	H
	*	2412	101.29	-	-	89.32	32.61	8.6	29.24	168	61	P	H
	*	2412	92.19	-	-	80.22	32.61	8.6	29.24	168	61	A	H
		2389.56	67.91	-6.09	74	55.97	32.6	8.6	29.26	194	77	P	V
		2389.92	51.49	-2.51	54	39.55	32.6	8.6	29.26	194	77	A	V
	*	2412	103.35	-	-	91.38	32.61	8.6	29.24	194	77	P	V
	*	2412	95.88	-	-	83.91	32.61	8.6	29.24	194	77	A	V
802.11n HT20 CH 06 2437MHz		2389.65	53.06	-20.94	74	41.12	32.6	8.6	29.26	200	129	P	H
		2381.1	41.1	-12.9	54	29.23	32.58	8.51	29.22	200	129	A	H
	*	2437	98.88	-	-	86.74	32.65	8.69	29.2	200	129	P	H
	*	2437	91.1	-	-	78.96	32.65	8.69	29.2	200	129	A	H
		2493.84	52.08	-21.92	74	39.74	32.7	8.78	29.14	200	129	P	H
		2487.16	41.21	-12.79	54	28.91	32.68	8.78	29.16	200	129	A	H
		2343.93	51.28	-22.72	74	39.46	32.54	8.43	29.15	200	130	P	V
		2363.37	40.16	-13.84	54	28.27	32.56	8.51	29.18	200	130	A	V
	*	2437	93.48	-	-	81.34	32.65	8.69	29.2	200	130	P	V
	*	2437	85.91	-	-	73.77	32.65	8.69	29.2	200	130	A	V
		2490.04	52.25	-21.75	74	39.91	32.7	8.78	29.14	200	130	P	V
		2495.12	40.73	-13.27	54	28.39	32.7	8.78	29.14	200	130	A	V



802.11n HT20 CH 11 2462MHz	*	2462	97.37	-	-	85.19	32.67	8.69	29.18	184	299	P	H
	*	2462	89.74	-	-	77.56	32.67	8.69	29.18	184	299	A	H
		2484.64	62.03	-11.97	74	49.73	32.68	8.78	29.16	184	299	P	H
		2483.52	47.46	-6.54	54	35.16	32.68	8.78	29.16	184	299	A	H
	*	2462	104.48	-	-	92.3	32.67	8.69	29.18	188	55	P	V
	*	2462	96.37	-	-	84.19	32.67	8.69	29.18	188	55	A	V
		2483.88	69.27	-4.73	74	56.97	32.68	8.78	29.16	188	55	P	V
		2483.56	52.39	-1.61	54	40.09	32.68	8.78	29.16	188	55	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



15C 2.4GHz 2400~2483.5MHz

WIFI 802.11n HT20 (Harmonic @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11n HT20 CH 01 2412MHz		4824	39.87	-34.13	74	43.35	34.4	12.86	50.74	110	360	P	H
		4824	39.8	-34.2	74	43.28	34.4	12.86	50.74	110	360	P	V
802.11n HT20 CH 06 2437MHz		4874	38.98	-35.02	74	42.21	34.43	12.92	50.58	100	360	P	H
		7311	42.08	-31.92	74	42.03	36.22	14.71	50.88	174	100	P	H
		4874	39.6	-34.4	74	42.83	34.43	12.92	50.58	100	360	P	V
		7311	42.23	-31.77	74	42.18	36.22	14.71	50.88	174	100	P	V
802.11n HT20 CH 11 2462MHz		4924	39.13	-34.87	74	42.05	34.46	13.04	50.42	146	347	P	H
		7386	41.04	-32.96	74	40.91	36.26	14.75	50.88	145	274	P	H
		4924	39.89	-34.11	74	42.81	34.46	13.04	50.42	146	347	P	V
		7386	41.72	-32.28	74	41.59	36.26	14.75	50.88	145	274	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



15C 2.4GHz 2400~2483.5MHz

WIFI 802.11n HT40 (Band Edge @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11n HT40 CH 03 2422MHz		2388.48	65.05	-8.95	74	53.11	32.6	8.6	29.26	198	26	P	H
		2388.75	49.15	-4.85	54	37.21	32.6	8.6	29.26	198	26	A	H
	*	2422	94.88	-	-	82.87	32.63	8.6	29.22	198	26	P	H
	*	2422	87.55	-	-	75.54	32.63	8.6	29.22	198	26	A	H
		2488.76	52.49	-21.51	74	40.15	32.7	8.78	29.14	198	26	P	H
		2495.88	42.11	-11.89	54	29.77	32.7	8.78	29.14	198	26	A	H
		2388.21	66.5	-7.5	74	54.56	32.6	8.6	29.26	100	83	P	V
		2388.39	49.76	-4.24	54	37.82	32.6	8.6	29.26	100	83	A	V
	*	2422	97.59	-	-	85.58	32.63	8.6	29.22	100	83	P	V
	*	2422	89.49	-	-	77.48	32.63	8.6	29.22	100	83	A	V
		2485.76	53.06	-20.94	74	40.76	32.68	8.78	29.16	100	83	P	V
		2490.04	42.77	-11.23	54	30.43	32.7	8.78	29.14	100	83	A	V
802.11n HT40 CH 06 2437MHz		2387.4	53.44	-20.56	74	41.5	32.6	8.6	29.26	194	66	P	H
		2388.84	43.29	-10.71	54	31.35	32.6	8.6	29.26	194	66	A	H
	*	2437	95.45	-	-	83.31	32.65	8.69	29.2	194	66	P	H
	*	2437	87.85	-	-	75.71	32.65	8.69	29.2	194	66	A	H
		2485.92	54.13	-19.87	74	41.83	32.68	8.78	29.16	194	66	P	H
		2484.68	43.23	-10.77	54	30.93	32.68	8.78	29.16	194	66	A	H
		2387.49	55.17	-18.83	74	43.23	32.6	8.6	29.26	100	83	P	V
		2389.38	43.56	-10.44	54	31.62	32.6	8.6	29.26	100	83	A	V
	*	2437	96.82	-	-	84.68	32.65	8.69	29.2	100	83	P	V
	*	2437	89.13	-	-	76.99	32.65	8.69	29.2	100	83	A	V
		2483.68	55.91	-18.09	74	43.61	32.68	8.78	29.16	100	83	P	V
		2483.88	43.96	-10.04	54	31.66	32.68	8.78	29.16	100	83	A	V



802.11n HT40 CH 09 2452MHz		2381.73	53.3	-20.7	74	41.43	32.58	8.51	29.22	200	61	P	H
		2382.72	42.16	-11.84	54	30.29	32.58	8.51	29.22	200	61	A	H
	*	2452	96.01	-	-	83.87	32.65	8.69	29.2	200	61	P	H
	*	2452	88.11	-	-	75.97	32.65	8.69	29.2	200	61	A	H
		2484.68	67.51	-6.49	74	55.21	32.68	8.78	29.16	200	61	P	H
		2483.52	51.85	-2.15	54	39.55	32.68	8.78	29.16	200	61	A	H
		2369.76	52.63	-21.37	74	40.76	32.58	8.51	29.22	100	136	P	V
		2388.66	41.99	-12.01	54	30.05	32.6	8.6	29.26	100	136	A	V
	*	2452	96.06	-	-	83.92	32.65	8.69	29.2	100	136	P	V
	*	2452	88.39	-	-	76.25	32.65	8.69	29.2	100	136	A	V
		2484.56	66.41	-7.59	74	54.11	32.68	8.78	29.16	100	136	P	V
		2484.12	50.71	-3.29	54	38.41	32.68	8.78	29.16	100	136	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



15C 2.4GHz 2400~2483.5MHz

WIFI 802.11n HT40 (Harmonic @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11n		4844	40.57	-33.43	74	43.93	34.41	12.92	50.69	100	360	P	H
HT40		7266	42.73	-31.27	74	42.7	36.21	14.7	50.88	200	360	P	H
CH 03		4844	41.16	-32.84	74	44.52	34.41	12.92	50.69	100	360	P	V
2422MHz		7266	42.9	-31.1	74	42.87	36.21	14.7	50.88	200	360	P	V
802.11n		4874	39.6	-34.4	74	42.83	34.43	12.92	50.58	100	163	P	H
HT40		7311	41.9	-32.1	74	41.85	36.22	14.71	50.88	120	360	P	H
CH 06		4874	39.81	-34.19	74	43.04	34.43	12.92	50.58	100	163	P	V
2437MHz		7311	42.03	-31.97	74	41.98	36.22	14.71	50.88	120	360	P	V
802.11n		4904	40.18	-33.82	74	43.22	34.45	12.98	50.47	129	360	P	H
HT40		7356	43.02	-30.98	74	42.93	36.24	14.73	50.88	121	320	P	H
CH 09		4904	39.59	-34.41	74	42.63	34.45	12.98	50.47	129	360	P	V
2452MHz		7356	44.21	-29.79	74	44.12	36.24	14.73	50.88	121	320	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



15C Emission below 1GHz

2.4GHz WIFI 802.11n HT20 (LF)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
2.4GHz 802.11n HT20 LF		138.64	23.55	-19.95	43.5	41.34	11.11	1.82	30.72	-	-	P	H
		232.73	31.87	-14.13	46	49.41	10.67	2.38	30.59	200	0	P	H
		317.12	30.23	-15.77	46	44.5	13.35	2.81	30.43	-	-	P	H
		477.17	24.77	-21.23	46	34.12	17.31	3.49	30.15	-	-	P	H
		742.95	27.32	-18.68	46	32.02	20.39	4.5	29.59	-	-	P	H
		877.78	28.08	-17.92	46	31.64	20.64	4.85	29.05	-	-	P	H
		41.64	26.4	-13.6	40	44.28	11.9	0.98	30.76	-	-	P	V
		232.73	27.07	-18.93	46	44.61	10.67	2.38	30.59	-	-	P	V
		314.21	32.71	-13.29	46	47.16	13.2	2.79	30.44	100	0	P	V
		452.92	24.46	-21.54	46	35.18	16.09	3.41	30.22	-	-	P	V
		749.74	27.28	-18.72	46	31.71	20.6	4.53	29.56	-	-	P	V
		938.89	28.46	-17.54	46	31.17	21.09	5	28.8	-	-	P	V
Remark	1. No other spurious found. 2. All results are PASS against limit line.												

**Note symbol**

*	Fundamental Frequency which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency per 15.209(c).
!	Test result is over limit line.
P/A	P eak or A verage
H/V	H orizontal or V ertical



A calculation example for radiated spurious emission is shown as below:

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1+2		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
CH 01													
2412MHz		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

1. Level(dBμV/m) =

Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

2. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

For Peak Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)

= 55.45 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 55.45(dBμV/m) – 74(dBμV/m)

= -18.55(dB)

For Average Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)

= 43.54 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 43.54(dBμV/m) – 54(dBμV/m)

= -10.46(dB)

Both peak and average measured complies with the limit line, so test result is “PASS”.