FCC RF Test Report

APPLICANT	:	**CT Asia**
EQUIPMENT	:	**Smart phone**
BRAND NAME	:	**BLU**
MODEL NAME	:	**Studio 5.0 LTE**
FCC ID	:	**YHLBLUST50LTE**
STANDARD	:	**47 CFR Part 2, 27(L), 27(M)**
CLASSIFICATION	:	**PCS Licensed Transmitter Held to Ear (PCE)**

The product was received on Jan. 28, 2015 and completely tested on Mar. 18, 2015. We, SPORTON INTERNATIONAL (SHENZHEN) INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures given in ANSI / TIA / EIA-603-C-2004 and the testing has shown the tested sample to be in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL (SHENZHEN) INC., the test report shall not be reproduced except in full.

Reviewed by: Joseph Lin / Supervisor

Approved by: Jones Tsai / Manager

Testing Laboratory
2353

SPORTON INTERNATIONAL (SHENZHEN) INC.
1F & 2F, Building A, Morning Business Center, No. 4003 ShiGu Rd., Xili Town, Nanshan District, Shenzhen, Guangdong, P. R. China

TABLE OF CONTENTS

REVISION HISTORY **4**

SUMMARY OF TEST RESULT **5**

1 GENERAL DESCRIPTION **6**

1.1 Applicant 6
1.2 Manufacturer 6
1.3 Product Feature of Equipment Under Test 6
1.4 Product Specification subjective to this standard 6
1.5 Modification of EUT 7
1.6 Maximum Emission Designator, Frequency Tolerance, and EIRP Power 7
1.7 Testing Location 8
1.8 Applicable Standards 8

2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST **9**

2.1 Test Mode 9
2.2 Connection Diagram of Test System 10
2.3 Support Unit used in test configuration and system 11
2.4 Measurement Results Explanation Example 11

3 CONDUCTED TEST ITEMS **12**

3.1 Measuring Instruments 12
3.2 Test Setup 12
3.3 Test Result of Conducted Test 12
3.4 Conducted Output Power 13
3.5 Peak-to-Average Ratio 13
3.6 99% Occupied Bandwidth and 26dB Bandwidth Measurement 14
3.7 Conducted Band Edge 15
3.8 Conducted Spurious Emission 16
3.9 Frequency Stability 17

4 RADIATED TEST ITEMS **18**

4.1 Measuring Instruments 18
4.2 Test Setup 18
4.3 Test Result of Radiated Test 18
4.4 Effective Isotropic Radiated Power 19
4.5 Radiated Spurious Emission 21

5 LIST OF MEASURING EQUIPMENT **22**

6 UNCERTAINTY OF EVALUATION **23**

APPENDIX A. TEST RESULTS OF CONDUCTED TEST

APPENDIX B. TEST RESULTS OF RADIATED TEST

APPENDIX C. SETUP PHOTOGRAPHS

REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FG512805B	Rev. 01	Initial issue of report	Mar. 25, 2015

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.4	§2.1046	Conducted Output Power	Reporting Only	PASS	-
3.5	N/A	Peak-to-Average Ratio	<13 dB	PASS	-
3.6	§2.1049 §27.53(h)(3) §27.53(m)(6)	Occupied Bandwidth	Reporting Only	PASS	-
3.7	§2.1051 §27.53(g)	Conducted Band Edge Measurement (Band 4)	< 43+10log10(P[Watts])	PASS	-
	§2.1051 §27.53(m)(4)	Conducted Band Edge Measurement (Band 7)	< 5MHz: -10 dBm 5 MHz~6MHz or 26dB(BW): -13 dBm ≥6MHz or 26dB(BW): -25 dBm	PASS	-
3.8	§2.1051 §27.53(g)	Conducted Spurious Emission (Band 4)	< 43+10log10(P[Watts])	PASS	-
	§2.1053 §27.53(m)(4)	Conducted Spurious Emission (Band 7)	< 55+10log$_{10}$(P[Watts])		
3.9	§2.1055 §27.54	Frequency Stability Temperature & Voltage	within authorized band	PASS	-
4.4	§27.50(h)(2)	Equivalent Isotropic Radiated Power (Band 7)	EIRP < 2Watt	PASS	-
	§27.50(d)(4)	Equivalent Isotropic Radiated Power (Band 4)	EIRP < 1Watt		
4.5	§2.1053 §27.53(h)	Radiated Spurious Emission (Band 4)	< 43+10log$_{10}$(P[Watts])	PASS	Under limit 10.00 dB at 12640.000 MHz
	§2.1053 §27.53(m)(4)	Radiated Spurious Emission (Band 7)	< 55+10log$_{10}$(P[Watts])		

1 General Description

1.1 Applicant

CT Asia
Unit 01, 15/F, Seaview Centre, 139-141 Hoi bun road, Kwun Tong, Kowloon, Hongkong

1.2 Manufacturer

Beijing Benywave Wireless Communication Co., Ltd.
NO.55 Jiachang 2 road, OPTO-Mechatronics Industrial Park, Tongzhou district, Beijing 101111

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Smart phone
Brand Name	BLU
Model Name	Studio 5.0 LTE
FCC ID	YHLBLUST50LTE
EUT supports Radios application	GSM/GPRS/EGPRS/WCDMA/HSPA/LTE WLAN2.4GHz 802.11b/g/n HT20 Bluetooth v3.0+EDR
HW Version	TBW5723_P2_002
SW Version	BLU_ Z030Q_V01_GENERIC
EUT Stage	Pre-Production

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Product Specification subjective to this standard

Product Specification subjective to this standard	
Tx Frequency	LTE Band 4 : 1710.7 MHz ~ 1754.3 MHz LTE Band 7 : 2502.5 MHz ~ 2567.5 MHz
Rx Frequency	LTE Band 4 : 2110.7 MHz ~ 2154.3 MHz LTE Band 7 : 2622.5MHz ~ 2687.5 MHz
Bandwidth	LTE Band 4 : 1.4MHz / 3MHz / 5MHz / 10MHz / 15MHz / 20MHz LTE Band 7 : 5MHz/ 10MHz / 15MHz / 20MHz
Maximum Output Power to Antenna	LTE Band 4 : 23.21 dBm LTE Band 7 : 20.77 dBm
Antenna Type	PIFA Antenna
Type of Modulation	QPSK / 16QAM / 64QAM(Downlink only)

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Maximum Emission Designator, Frequency Tolerance, and EIRP Power

LTE Band 4	QPSK			16QAM		
BW(MHz)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum EIRP(W)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum EIRP(W)
1.4	1M10G7D	-	0.3819	1M10W7D	-	0.3090
3	2M72G7D	-	0.3664	2M72W7D	-	0.3199
5	4M51G7D	-	0.3855	4M50W7D	-	0.3034
10	9M09G7D	0.0020	0.3864	9M05W7D	-	0.3126
15	13M5G7D	-	0.3707	13M5W7D	-	0.3289
20	18M4G7D	-	0.3908	18M5W7D	-	0.3062
LTE Band 7	**QPSK**			**16QAM**		
BW(MHz)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum EIRP(W)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum EIRP(W)
5	4M51G7D	-	0.2173	4M50W7D	-	0.1786
10	9M09G7D	0.0024	0.2061	9M03W7D	-	0.1726
15	13M5G7D	-	0.2084	13M5W7D	-	0.1774
20	18M5G7D	-	0.1910	18M4W7D	-	0.1535

1.7 Testing Location

Test Site	SPORTON INTERNATIONAL (SHENZHEN) INC.	
Test Site Location	1F & 2F, Building A, Morning Business Center, No. 4003 ShiGu Rd., Xili Town, Nanshan District, Shenzhen, Guangdong, P. R. China TEL: +86-755-8637-9589 FAX: +86-755-8637-9595	
Test Site No.	**Sporton Site No.**	
	TH01-SZ	OTA02-SZ

Test Site	SPORTON INTERNATIONAL (SHENZHEN) INC.	
Test Site Location	No. 3 Building, the third floor of south, Shahe River west, Fengzeyuan warehouse, Nanshan District, Shenzhen, Guangdong, P. R. China TEL: +86-755- 3320-2398	
Test Site No.	**Sporton Site No.**	**FCC Registration No.**
	03CH02-SZ	831040

1.8 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR Part 2, 27(L), 27(M)
- ANSI / TIA / EIA-603-C-2004
- FCC KDB 971168 D01 Power Meas. License Digital Systems v02r02

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

2.1 Test Mode

Antenna port conducted and radiated test items listed below are performed according to KDB 971168 D01 Power Meas. License Digital Systems v02r02 with maximum output power.

Radiated measurements are performed by rotating the EUT in three different orthogonal test planes to find the maximum emission.

Test Items	Band	Bandwidth (MHz)						Modulation		RB #			Test Channel		
		1.4	3	5	10	15	20	QPSK	16QAM	1	Half	Full	L	M	H
Max. Output Power	4	v	v	v	v	v	v	v	v	v	v	v	v	v	v
	7	-	-	v	v	v	v	v	v	v	v	v	v	v	v
Peak-to-Average Ratio	4						v	v	v	v		v	v	v	v
	7	-	-				v	v	v	v		v	v	v	v
26dB and 99% Bandwidth	4	v	v	v	v	v	v	v	v			v	v	v	v
	7	-	-	v	v	v	v	v	v			v	v	v	v
Conducted Band Edge	4	v	v	v	v	v	v	v	v	v		v	v		v
	7	-	-	v	v	v	v	v	v	v		v	v		v
Conducted Spurious Emission	4	v	v	v	v	v	v	v	v	v			v	v	v
	7	-	-	v	v	v	v	v	v	v			v	v	v
Frequency Stability	4				v			v				v		v	
	7	-	-		v			v				v		v	
E.R.P./ E.I.R.P.	4	v	v	v	v	v	v	v	v	v			v	v	v
	7	-	-	v	v	v	v	v	v	v			v	v	v
Radiated Spurious Emission	4	v	v	v	v	v	v	v		v				v	
	7	-	-	v	v	v	v	v		v				v	
Note	1. The mark "v " means that this configuration is chosen for testing 2. The mark "-" means that this bandwidth is not supported. 3. The device is investigated from 30MHz to 10 times of fundamental signal for radiated spurious emission test under different RB size/offset and modulations in exploratory test. Subsequently, only the worst case emissions are reported.														

2.2 Connection Diagram of Test System



2.3 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	LTE Base Station	Anritsu	MT8820C	N/A	N/A	Unshielded, 1.8 m
2.	DC Power Supply	TOPWORD	3303DR	N/A	N/A	Unshielded, 1.8 m

2.4 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 5 dB and 10dB attenuator.

Example :

Offset(dB) = RF cable loss(dB) + attenuator factor(dB).

= 5 + 10 = 15 (dB)

3 Conducted Test Items

3.1 Measuring Instruments

See list of measuring instruments of this test report.

3.2 Test Setup

3.2.1 Conducted Output Power

3.2.2 Peak-to-Average Ratio, Occupied Bandwidth ,Conducted Band-Edge and Conducted Spurious Emission



3.2.3 Frequency Stability



3.3 Test Result of Conducted Test

Please refer to Appendix A.

3.4 Conducted Output Power

3.4.1 Description of the Conducted Output Power Measurement

A system simulator was used to establish communication with the EUT. Its parameters were set to force the EUT transmitting at maximum output power. The measured power in the radio frequency on the transmitter output terminals shall be reported.

3.4.2 Test Procedures

1. The transmitter output port was connected to the system simulator.
2. Set EUT at maximum power through the system simulator.
3. Select lowest, middle, and highest channels for each band and different modulation.
4. Measure and record the power level from the system simulator.

3.5 Peak-to-Average Ratio

3.5.1 Description of the PAR Measurement

Power Complementary Cumulative Distribution Function (CCDF) curves provide a means for characterizing the power peaks of a digitally modulated signal on a statistical basis. A CCDF curve depicts the probability of the peak signal amplitude exceeding the average power level. Most contemporary measurement instrumentation include the capability to produce CCDF curves for an input signal provided that the instrument's resolution bandwidth can be set wide enough to accommodate the entire input signal bandwidth. In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

3.5.2 Test Procedures

1. The testing follows FCC KDB 971168 v02r02 Section 5.7.1.
2. The EUT was connected to spectrum and system simulator via a power divider.
3. Set the CCDF (Complementary Cumulative Distribution Function) option in spectrum analyzer.
4. The highest RF powers were measured and recorded the maximum PAPR level associated with a probability of 0.1 %.
5. Record the deviation as Peak to Average Ratio.

3.6 99% Occupied Bandwidth and 26dB Bandwidth Measurement

3.6.1 Description of 99% Occupied Bandwidth and 26dB Bandwidth Measurement

The 99% occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The 26 dB emission bandwidth is defined as the frequency range between two points, one above and one below the carrier frequency, at which the spectral density of the emission is attenuated 26 dB below the maximum in-band spectral density of the modulated signal. Spectral density (power per unit bandwidth) is to be measured with a detector of resolution bandwidth equal to approximately 1.0% of the emission bandwidth.

3.6.2 Test Procedures

1. The testing follows FCC KDB 971168 v02r02 Section 4.2.
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.

3.7 Conducted Band Edge

3.7.1 Description of Conducted Band Edge Measurement

27.53 (h) for Band 4

For operations in the 1710 – 1755 MHz band, the FCC limit is 43 + $10\log_{10}$(P[Watts]) dB below the transmitter power P(Watts) in a 1 MHz bandwidth. However, in the 1MHz bands immediately outside and adjacent to the licensee's frequency block, a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.

27.53(m)(4) for Band 7:

For mobile digital stations, the attenuation factor shall be not less than 40 + 10 log (P) dB on all frequencies between the channel edge and 5 megahertz from the channel edge, 43 + 10 log (P) dB on all frequencies between 5 megahertz and X megahertz from the channel edge, and 55 + 10 log (P) dB on all frequencies more than X megahertz from the channel edge, where X is the greater of 6 megahertz or the actual emission bandwidth as defined in paragraph (m)(6) of this section. In addition, the attenuation factor shall not be less that 43 + 10 log (P) dB on all frequencies between 2490.5 MHz and 2496 MHz and 55 + 10 log (P) dB at or below 2490.5 MHz. Mobile Satellite Service licensees operating on frequencies below 2495 MHz may also submit a documented interference complaint against BRS licensees operating on channel BRS Channel 1 on the same terms and conditions as adjacent channel BRS or EBS licensees.

3.7.2 Test Procedures

1. The testing follows FCC KDB 971168 v02r02 Section 6.0.
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The band edges of low and high channels for the highest RF powers were measured. Set RBW >= 1% EBW in the 1MHz band immediately outside and adjacent to the band edge.
4. Set spectrum analyzer with RMS detector.
5. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.8 Conducted Spurious Emission

3.8.1 Description of Conducted Spurious Emission Measurement

For Band 4:

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least 43 + 10 log (P) dB.

For Band 7:

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least 55 + 10 log (P) dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10th harmonic.

3.8.2 Test Procedures

1. The testing follows FCC KDB 971168 v02r02 Section 6.0.
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
4. The middle channel for the highest RF power within the transmitting frequency was measured.
5. The conducted spurious emission for the whole frequency range was taken.
6. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking the record of maximum spurious emission.
7. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
8. The limit line is derived from 43 + 10log(P)dB below the transmitter power P(Watts)
   = P(W)- [43 + 10log(P)] (dB)
   = [30 + 10log(P)] (dBm) - [43 + 10log(P)] (dB)
   = -13dBm.
9. For Band 7
   The limit line is derived from 55 + 10log(P)dB below the transmitter power P(Watts)

3.9 Frequency Stability

3.9.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within ±0.00025% (±2.5ppm) of the center frequency.

3.9.2 Test Procedures for Temperature Variation

1. The EUT was set up in the thermal chamber and connected with the system simulator.
2. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
3. With power OFF, the temperature was raised in 10°C step up to 50°C. The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

3.9.3 Test Procedures for Voltage Variation

1. The testing follows FCC KDB 971168 v02r02 Section 9.0.
2. The EUT was placed in a temperature chamber at 25±5° C and connected with the system simulator.
3. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value measured at the input to the EUT.
4. The variation in frequency was measured for the worst case.

4 Radiated Test Items

4.1 Measuring Instruments

See list of measuring instruments of this test report.

4.2 Test Setup

4.2.1 For radiated test from 30MHz to 1GHz



4.2.2 For radiated test above 1GHz



4.3 Test Result of Radiated Test

Please refer to Appendix B.

4.4 Effective Isotropic Radiated Power

4.4.1 Description of the EIRP Measurement

Equivalent isotropic radiated power output measurements by substitution method according to ANSI / TIA / EIA-603-C-2004, and the spectrum analyzer configuration follows KDB 971168 D01 Power Meas. License Digital Systems v02r02. Mobile and portable (hand-held) stations operating are limited to average EIRP of 2 watts with LTE band 7 and 1 watt with LTE band 4.

4.4.2 Test Procedures

1. The testing follows FCC KDB 971168 v02r02 Section 5.2.1. (for CDMA/WCDMA), Section 5.2.2.2 (for GSM/GPRS/EDGE) and ANSI / TIA-603-C-2004 Section 2.2.17.
2. The EUT was placed on a turntable 1.5 meters high in a fully anechoic chamber.
3. The EUT was placed 3 meters from the receiving antenna, which was mounted on the antenna tower.
4. GSM operating modes: Set RBW= 1MHz, VBW= 3MHz, RMS detector over burst;
   UMTS operating modes: Set RBW= 100 kHz, VBW= 300 kHz, RMS detector over frame, and use channel power option with bandwidth=5MHz, per KDB 971168 D01.
5. The table was rotated 360 degrees to determine the position of the highest radiated power.
6. The height of the receiving antenna is adjusted to look for the maximum ERP/EIRP.
7. Taking the record of maximum ERP/EIRP.
8. A dipole antenna was substituted in place of the EUT and was driven by a signal generator.
9. The conducted power at the terminal of the dipole antenna is measured.
10. Repeat step 3 to step 5 to get the maximum ERP/EIRP of the substitution antenna.
11. ERP/EIRP = Ps + Et – Es + Gs = Ps + Rt – Rs + Gs
    Ps (dBm)：Input power to substitution antenna.
    Gs (dBi or dBd)：Substitution antenna Gain.
    Et = Rt + AF
    Es = Rs + AF
    AF (dB/m)：Receive antenna factor
    Rt：The highest received signal in spectrum analyzer for EUT.
    Rs：The highest received signal in spectrum analyzer for substitution antenna.

4.4.3 Test Setup



4.5 Radiated Spurious Emission

4.5.1 Description of Radiated Spurious Emission

The radiated spurious emission was measured by substitution method according to ANSI / TIA / EIA-603-C-2004. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least 55 + 10 log (P) dB.

For Band 7

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least 55 + 10 log (P) dB.

The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

4.5.2 Test Procedures

1. The testing follows FCC KDB 971168 v02r02 Section 5.8 and ANSI / TIA-603-C-2004 Section 2.2.12.
2. The EUT was placed on a rotatable wooden table with 0.8 meter above ground.
3. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
4. The table was rotated 360 degrees to determine the position of the highest spurious emission.
5. The height of the receiving antenna is varied between one meter and four meters to search the maximum spurious emission for both horizontal and vertical polarizations.
6. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking the record of maximum spurious emission.
7. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
8. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
9. Taking the record of output power at antenna port.
10. Repeat step 7 to step 8 for another polarization.
11. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

    The limit line is derived from 43 + 10log(P)dB below the transmitter power P(Watts)
    = P(W)- [43 + 10log(P)] (dB)
    = [30 + 10log(P)] (dBm) - [43 + 10log(P)] (dB)
    = -13dBm.
    For Band 7:
    The limit line is derived from 55 + 10log(P)dB below the transmitter power P(Watts)
12. EIRP (dBm) = S.G. Power – Tx Cable Loss + Tx Antenna Gain
13. ERP (dBm) = EIRP - 2.15

5 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101078	10Hz~40GHz	May 08, 2014	Jan. 30, 2015~ Mar. 18, 2015	May 07, 2015	Conducted (TH01-SZ)
Thermal Chamber	Hongzhangroup	LP-150U	HD20120425	-40℃~150℃	Jan. 28, 2015	Jan. 30, 2015~ Mar. 18, 2015	Jan. 27, 2016	Conducted (TH01-SZ)
EMI TEST Receiver	R&S	ESCI7	100768	9kHz~3GHz	May 04, 2014	Feb. 12, 2015	May 03, 2015	Radiation (03CH02-SZ)
Spectrum Analyzer	Agilent Technologies	N9038A	MY52260185	20Hz~26.5GHz	May 26, 2014	Feb. 12, 2015	May 25, 2015	Radiation (03CH02-SZ)
Bilog Antenna	TESEQ	CBL 6112D	37877	30MHz~2GHz	Oct. 15, 2014	Feb. 12, 2015	Oct. 14, 2015	Radiation (03CH02-SZ)
Double Ridge Horn Antenna	SCHWARZBECK	BBHA 9120D	9120D-1285	1GHz~18GHz	Jan. 20, 2015	Feb. 12, 2015	Jan. 19, 2016	Radiation (03CH02-SZ)
Double Ridged Horn Antenna	COM-POWER	AH-840	101071	18GHz~40GHz	Sep. 04, 2014	Feb. 12, 2015	Sep. 03, 2015	Radiation (03CH02-SZ)
Amplifier	com-power	PA-103A	161069	1~1000MHz	May 04, 2014	Feb. 12, 2015	May 03, 2015	Radiation (03CH02-SZ)
Amplifier	Agilent	8449B	3008A01023	1GHz~26.5GHz	Oct. 29, 2014	Feb. 12, 2015	Oct. 28, 2015	Radiation (03CH02-SZ)
AC Source(AVR)	CHROMA	61601ACSOURCE	616010002470	100Vac~240Vac	NCR	Feb. 12, 2015	NCR	Radiation (03CH02-SZ)
Turn Table	Qiangdian	3000	N/A	0~360 degree	NCR	Feb. 12, 2015	NCR	Radiation (03CH02-SZ)
Antenna Mast	Qiangdian	3000	N/A	1 m~4 m	NCR	Feb. 12, 2015	NCR	Radiation (03CH02-SZ)
Spectrum Analyzer	R&S	FSP 7	100818	9kHz~7GHz	Jul. 17, 2014	Mar. 17, 2015	Jul. 16, 2015	ERP/EIRP (OTA02-SZ)
Quad-Ridged Horn	ETS-Lindgren	3164-08	00102954	700MHz~10000MHz	N/A	Mar. 17, 2015	N/A	ERP/EIRP (OTA02-SZ)
Multi-Devices Controller	ETS-Lindgren	2090-OPT1	00108147	N/A	N/A	Mar. 17, 2015	N/A	ERP/EIRP (OTA02-SZ)
Switch Control Mainframe	Agilent	3499A	MY42005451	N/A	N/A	Mar. 17, 2015	N/A	ERP/EIRP (OTA02-SZ)

6 Uncertainty of Evaluation

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	**4.5 dB**

Appendix A. Test Results of Conducted Test

LTE Band 4

Conducted Output Power(Average power)

LTE Band 4 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
1.4	1	0	QPSK	22.81	22.93	23.00
1.4	1	2		22.95	23.06	22.99
1.4	1	5		22.90	23.04	23.10
1.4	3	0		22.93	22.98	23.03
1.4	3	1		22.80	23.02	23.04
1.4	3	2		22.81	23.01	22.98
1.4	6	0		21.91	22.07	21.89
1.4	1	0	16-QAM	22.00	22.12	21.91
1.4	1	2		22.15	22.26	22.04
1.4	1	5		22.05	22.16	22.06
1.4	3	0		21.94	22.13	21.98
1.4	3	1		22.06	22.16	21.82
1.4	3	2		22.02	22.13	21.95
1.4	6	0		20.99	21.10	21.11
3	1	0	QPSK	22.94	23.03	23.04
3	1	7		22.93	23.04	23.01
3	1	14		22.92	23.02	23.03
3	8	0		22.05	22.12	21.94
3	8	4		22.00	22.15	21.94
3	8	7		22.15	22.13	21.92
3	15	0		22.05	22.04	21.94
3	1	0	16-QAM	21.80	22.21	22.21
3	1	7		21.90	22.17	22.13
3	1	14		21.86	22.25	22.04
3	8	0		20.91	21.13	20.95
3	8	4		21.04	21.04	20.97
3	8	7		20.94	21.03	21.02

3	15	0		21.10	21.08	21.00

LTE Band 4 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	22.78	23.00	22.97
5	1	12		22.85	22.96	22.95
5	1	24		22.60	23.01	22.95
5	12	0		21.69	22.08	21.87
5	12	6		21.85	22.08	21.89
5	12	11		21.88	22.05	21.87
5	25	0		21.80	22.19	21.90
5	1	0	16-QAM	21.84	22.14	22.24
5	1	12		22.26	22.29	22.15
5	1	24		21.93	22.23	22.03
5	12	0		20.72	21.07	20.92
5	12	6		20.77	21.07	20.95
5	12	11		20.81	20.91	20.91
5	25	0		20.79	20.93	20.93
10	1	0	QPSK	22.80	22.97	23.04
10	1	24		22.93	23.04	23.03
10	1	49		22.85	23.03	23.01
10	25	0		21.84	21.98	21.93
10	25	12		21.87	22.07	21.90
10	25	24		21.88	21.98	21.87
10	50	0		21.83	21.94	21.83
10	1	0	16-QAM	21.63	21.87	22.22
10	1	24		21.70	21.98	21.86
10	1	49		21.64	21.92	21.77
10	25	0		20.76	21.04	21.10
10	25	12		20.80	21.06	21.01
10	25	24		20.76	21.05	20.99
10	50	0		20.80	20.94	20.87

LTE Band 4 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
15	1	0	QPSK	22.67	22.98	23.10
15	1	37		22.74	22.96	23.05
15	1	74		22.81	23.07	23.06
15	36	0		21.90	21.95	21.95
15	36	18		21.81	22.05	22.03
15	36	37		21.85	21.91	21.83
15	75	0		21.74	21.94	21.86
15	1	0	16-QAM	21.60	21.74	21.83
15	1	37		21.57	21.66	21.67
15	1	74		21.64	21.92	21.52
15	36	0		20.71	21.00	21.00
15	36	18		20.75	20.91	20.99
15	36	37		20.76	20.86	21.02
15	75	0		20.72	20.95	20.91
20	1	0	QPSK	22.61	23.02	23.06
20	1	49		22.90	23.06	23.12
20	1	99		23.08	23.10	**23.21**
20	50	0		21.78	21.85	21.96
20	50	24		21.79	21.95	21.98
20	50	49		21.75	21.92	21.86
20	100	0		21.82	22.01	22.04
20	1	0	16-QAM	21.48	21.91	22.02
20	1	49		21.75	21.99	21.99
20	1	99		21.84	21.74	22.41
20	50	0		20.81	20.80	21.03
20	50	24		20.84	20.90	21.07
20	50	49		20.74	20.95	20.97
20	100	0		20.71	20.96	21.10

Peak-to-Average Ratio

Mode	LTE Band 4 / 20MHz				
Mod.	QPSK		16QAM		Limit: 13dB
RB Size	1RB	Full RB	1RB	RB Size	Result
Lowest CH	5.62	5.07	7.01	6.26	PASS
Middle CH	5.1	5.16	5.88	6.14	
Highest CH	5.13	5.22	5.57	6.35	

LTE Band 4 / 20MHz / QPSK

Lowest Channel / 1RB



Lowest Channel / Full RB



Middle Channel / 1RB



Middle Channel / Full RB

Highest Channel / 1RB



Highest Channel / Full RB



LTE Band 4 / 20MHz / 16QAM

Lowest Channel / 1RB



Lowest Channel / Full RB



Middle Channel / 1RB



Middle Channel / Full RB

Highest Channel / 1RB



Highest Channel / Full RB

26dB Bandwidth

Mode	LTE Band 4 : 26dB BW(MHz)											
BW	1.4MHz		3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Lowest CH	1.30	1.30	3.05	3.05	5.01	5.02	9.93	9.87	14.60	14.60	20.18	20.42
Middle CH	1.30	1.30	3.05	3.06	5.04	5.03	10.07	9.93	14.60	14.60	20.34	20.38
Highest CH	1.30	1.30	3.05	3.05	5.03	5.00	10.01	9.95	14.81	14.66	20.30	20.14

LTE Band 4

Lowest Channel / 1.4MHz / QPSK



Lowest Channel / 1.4MHz / 16QAM



Middle Channel / 1.4MHz / QPSK



Middle Channel / 1.4MHz / 16QAM



Highest Channel / 1.4MHz / QPSK



Highest Channel / 1.4MHz / 16QAM



LTE Band 4

Lowest Channel / 3MHz / QPSK



Lowest Channel / 3MHz / 16QAM



Middle Channel / 3MHz / QPSK



Middle Channel /3MHz / 16QAM



Highest Channel /3MHz / QPSK



Highest Channel /3MHz / 16QAM



LTE Band 4

Lowest Channel / 5MHz / QPSK



Lowest Channel / 5MHz / 16QAM



Middle Channel / 5MHz / QPSK



Middle Channel / 5MHz / 16QAM



Highest Channel / 5MHz / QPSK



Highest Channel / 5MHz / 16QAM



LTE Band 4

Lowest Channel / 10MHz / QPSK



Lowest Channel / 10MHz / 16QAM



Middle Channel / 10MHz / QPSK



Middle Channel / 10MHz / 16QAM



Highest Channel / 10MHz / QPSK



Highest Channel / 10MHz / 16QAM



LTE Band 4

Lowest Channel / 15MHz / QPSK



Lowest Channel / 15MHz / 16QAM



Middle Channel / 15MHz / QPSK



Middle Channel / 15MHz / 16QAM



Highest Channel / 15MHz / QPSK



Highest Channel / 15MHz / 16QAM



LTE Band 4

Lowest Channel / 20MHz / QPSK



Lowest Channel / 20MHz / 16QAM



Middle Channel / 20MHz / QPSK



Middle Channel / 20MHz / 16QAM



Highest Channel / 20MHz / QPSK



Highest Channel / 20MHz / 16QAM



Occupied Bandwidth

Mode	LTE Band 4 : 99%OBW(MHz)											
BW	1.4MHz		3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Lowest CH	1.10	1.09	2.72	2.72	4.51	4.49	9.01	9.03	13.43	13.43	18.26	18.22
Middle CH	1.10	1.10	2.72	2.72	4.50	4.49	9.07	9.05	13.49	13.43	18.34	18.34
Highest CH	1.10	1.09	2.72	2.72	4.51	4.5	9.09	9.01	13.46	13.46	18.38	18.46

LTE Band 4

Lowest Channel / 1.4MHz / QPSK



Lowest Channel / 1.4MHz / 16QAM



Middle Channel / 1.4MHz / QPSK



Middle Channel / 1.4MHz / 16QAM



Highest Channel / 1.4MHz / QPSK



Highest Channel / 1.4MHz / 16QAM



LTE Band 4

Lowest Channel / 3MHz / QPSK



Lowest Channel / 3MHz / 16QAM



Middle Channel / 3MHz / QPSK



Middle Channel / 3MHz / 16QAM



Highest Channel / 3MHz / QPSK



Highest Channel / 3MHz / 16QAM



LTE Band 4

Lowest Channel / 5MHz / QPSK



Lowest Channel / 5MHz / 16QAM



Middle Channel / 5MHz / QPSK



Middle Channel / 5MHz / 16QAM



Highest Channel / 5MHz / QPSK



Highest Channel / 5MHz / 16QAM



LTE Band 4

Lowest Channel / 10MHz / QPSK



Lowest Channel / 10MHz / 16QAM



Middle Channel / 10MHz / QPSK



Middle Channel / 10MHz / 16QAM



Highest Channel / 10MHz / QPSK



Highest Channel / 10MHz / 16QAM



LTE Band 4

Lowest Channel / 15MHz / QPSK



Lowest Channel / 15MHz / 16QAM



Middle Channel / 15MHz / QPSK



Middle Channel / 15MHz / 16QAM



Highest Channel / 15MHz / QPSK



Highest Channel / 15MHz / 16QAM



LTE Band 4

Lowest Channel / 20MHz / QPSK



Lowest Channel / 20MHz / 16QAM



Middle Channel / 20MHz / QPSK



Middle Channel / 20MHz / 16QAM



Highest Channel / 20MHz / QPSK



Highest Channel / 20MHz / 16QAM



Conducted Band Edge

LTE Band 4 / 1.4MHz / QPSK

Lowest Band Edge / 1RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
1.700 GHz	1.709 GHz	1.000 MHz	1.70899 GHz	-30.09 dBm	-17.09 dB
1.709 GHz	1.710 GHz	20.000 kHz	1.71000 GHz	-25.55 dBm	-12.55 dB
1.710 GHz	1.712 GHz	100.000 kHz	1.71026 GHz	20.67 dBm	-9.33 dB

Date: 18.MAR.2015 17:07:17

Highest Band Edge / 1RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
1.753 GHz	1.755 GHz	100.000 kHz	1.75478 GHz	21.34 dBm	-8.66 dB
1.755 GHz	1.756 GHz	20.000 kHz	1.75500 GHz	-24.42 dBm	-11.42 dB
1.756 GHz	1.765 GHz	1.000 MHz	1.75601 GHz	-29.78 dBm	-16.78 dB

Date: 18.MAR.2015 17:13:02

Lowest Band Edge / Full RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
1.700 GHz	1.709 GHz	1.000 MHz	1.70899 GHz	-23.27 dBm	-10.27 dB
1.709 GHz	1.710 GHz	20.000 kHz	1.71000 GHz	-31.20 dBm	-18.20 dB
1.710 GHz	1.712 GHz	100.000 kHz	1.71077 GHz	13.17 dBm	-16.83 dB

Date: 18.MAR.2015 17:05:40

Highest Band Edge / Full RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
1.753 GHz	1.755 GHz	100.000 kHz	1.75455 GHz	13.28 dBm	-16.72 dB
1.755 GHz	1.756 GHz	20.000 kHz	1.75500 GHz	-31.50 dBm	-18.50 dB
1.756 GHz	1.765 GHz	1.000 MHz	1.75601 GHz	-22.93 dBm	-9.93 dB

Date: 18.MAR.2015 17:11:34

LTE Band 4 / 1.4MHz / 16QAM

Lowest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
1.700 GHz	1.709 GHz	1.000 MHz	1.70891 GHz	-31.06 dBm	-18.06 dB
1.709 GHz	1.710 GHz	20.000 kHz	1.71000 GHz	-25.74 dBm	-12.74 dB
1.710 GHz	1.712 GHz	100.000 kHz	1.71024 GHz	19.73 dBm	-10.27 dB

Date: 18.MAR.2015 17:08:37

Highest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
1.753 GHz	1.755 GHz	100.000 kHz	1.75474 GHz	20.35 dBm	-9.65 dB
1.755 GHz	1.756 GHz	20.000 kHz	1.75500 GHz	-24.99 dBm	-11.99 dB
1.756 GHz	1.765 GHz	1.000 MHz	1.75610 GHz	-29.88 dBm	-16.88 dB

Date: 18.MAR.2015 17:14:25

Lowest Band Edge / Full RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
1.700 GHz	1.709 GHz	1.000 MHz	1.70894 GHz	-24.96 dBm	-11.96 dB
1.709 GHz	1.710 GHz	20.000 kHz	1.71000 GHz	-32.75 dBm	-19.75 dB
1.710 GHz	1.712 GHz	100.000 kHz	1.71060 GHz	12.15 dBm	-17.85 dB

Date: 18.MAR.2015 17:04:03

Highest Band Edge / Full RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
1.753 GHz	1.755 GHz	100.000 kHz	1.75436 GHz	12.28 dBm	-17.72 dB
1.755 GHz	1.756 GHz	20.000 kHz	1.75500 GHz	-31.75 dBm	-18.75 dB
1.756 GHz	1.765 GHz	1.000 MHz	1.75602 GHz	-22.81 dBm	-9.81 dB

Date: 18.MAR.2015 17:10:12

LTE Band 4 / 3MHz / QPSK

Lowest Band Edge / 1RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
1.700 GHz	1.709 GHz	1.000 MHz	1.70894 GHz	-30.33 dBm	-17.33 dB
1.709 GHz	1.710 GHz	30.000 kHz	1.71000 GHz	-23.52 dBm	-10.52 dB
1.710 GHz	1.713 GHz	100.000 kHz	1.71025 GHz	21.05 dBm	-8.95 dB

Date: 18.MAR.2015 16:54:44

Highest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
1.752 GHz	1.755 GHz	100.000 kHz	1.75476 GHz	21.61 dBm	-8.39 dB
1.755 GHz	1.756 GHz	30.000 kHz	1.75500 GHz	-21.19 dBm	-8.19 dB
1.756 GHz	1.765 GHz	1.000 MHz	1.75605 GHz	-29.92 dBm	-16.92 dB

Date: 18.MAR.2015 16:58:56

Lowest Band Edge / Full RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
1.700 GHz	1.709 GHz	1.000 MHz	1.70881 GHz	-24.92 dBm	-11.92 dB
1.709 GHz	1.710 GHz	30.000 kHz	1.71000 GHz	-30.95 dBm	-17.95 dB
1.710 GHz	1.713 GHz	100.000 kHz	1.71172 GHz	9.28 dBm	-20.72 dB

Date: 18.MAR.2015 16:48:24

Highest Band Edge / Full RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
1.752 GHz	1.755 GHz	100.000 kHz	1.75272 GHz	9.27 dBm	-20.73 dB
1.755 GHz	1.756 GHz	30.000 kHz	1.75500 GHz	-30.09 dBm	-17.09 dB
1.756 GHz	1.765 GHz	1.000 MHz	1.75662 GHz	-23.13 dBm	-10.13 dB

Date: 18.MAR.2015 16:58:00

LTE Band 4 / 3MHz / 16QAM

Lowest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
1.700 GHz	1.709 GHz	1.000 MHz	1.70890 GHz	-31.17 dBm	-18.17 dB
1.709 GHz	1.710 GHz	30.000 kHz	1.71000 GHz	-22.94 dBm	-9.94 dB
1.710 GHz	1.713 GHz	100.000 kHz	1.71023 GHz	19.71 dBm	-10.29 dB

Date: 18.MAR.2015 16:55:50

Highest Band Edge /1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
1.752 GHz	1.755 GHz	100.000 kHz	1.75472 GHz	19.95 dBm	-10.05 dB
1.755 GHz	1.756 GHz	30.000 kHz	1.75500 GHz	-22.68 dBm	-9.68 dB
1.756 GHz	1.765 GHz	1.000 MHz	1.75608 GHz	-30.97 dBm	-17.97 dB

Date: 18.MAR.2015 16:59:50

Lowest Band Edge / Full RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
1.700 GHz	1.709 GHz	1.000 MHz	1.70882 GHz	-25.88 dBm	-12.88 dB
1.709 GHz	1.710 GHz	30.000 kHz	1.71000 GHz	-32.06 dBm	-19.06 dB
1.710 GHz	1.713 GHz	100.000 kHz	1.71172 GHz	8.31 dBm	-21.69 dB

Date: 18.MAR.2015 16:44:15

Highest Band Edge / Full RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
1.752 GHz	1.755 GHz	100.000 kHz	1.75417 GHz	8.78 dBm	-21.22 dB
1.755 GHz	1.756 GHz	30.000 kHz	1.75500 GHz	-30.55 dBm	-17.55 dB
1.756 GHz	1.765 GHz	1.000 MHz	1.75639 GHz	-23.86 dBm	-10.86 dB

Date: 18.MAR.2015 16:57:07

LTE Band 4 / 5MHz / QPSK

Lowest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
1.700 GHz	1.709 GHz	1.000 MHz	1.70868 GHz	-30.05 dBm	-17.05 dB
1.709 GHz	1.710 GHz	50.000 kHz	1.71000 GHz	-23.30 dBm	-10.30 dB
1.710 GHz	1.715 GHz	100.000 kHz	1.71032 GHz	20.53 dBm	-9.47 dB

Date: 18.MAR.2015 16:38:14

Highest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
1.750 GHz	1.755 GHz	100.000 kHz	1.75467 GHz	21.12 dBm	-8.88 dB
1.755 GHz	1.756 GHz	50.000 kHz	1.75500 GHz	-22.54 dBm	-9.54 dB
1.756 GHz	1.765 GHz	1.000 MHz	1.75613 GHz	-26.65 dBm	-13.65 dB

Date: 18.MAR.2015 16:34:34

Lowest Band Edge / Full RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
1.700 GHz	1.709 GHz	1.000 MHz	1.70637 GHz	-26.75 dBm	-13.75 dB
1.709 GHz	1.710 GHz	50.000 kHz	1.70999 GHz	-31.13 dBm	-18.13 dB
1.710 GHz	1.715 GHz	100.000 kHz	1.71279 GHz	7.27 dBm	-22.73 dB

Date: 18.MAR.2015 16:38:51

Highest Band Edge / Full RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
1.750 GHz	1.755 GHz	100.000 kHz	1.75250 GHz	7.23 dBm	-22.77 dB
1.755 GHz	1.756 GHz	50.000 kHz	1.75501 GHz	-30.28 dBm	-17.28 dB
1.756 GHz	1.765 GHz	1.000 MHz	1.75858 GHz	-25.41 dBm	-12.41 dB

Date: 18.MAR.2015 16:35:08

LTE Band 4 / 5MHz / 16QAM

Lowest Band Edge / 1RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
1.700 GHz	1.709 GHz	1.000 MHz	1.70896 GHz	-27.14 dBm	-14.14 dB
1.709 GHz	1.710 GHz	50.000 kHz	1.71000 GHz	-23.60 dBm	-10.60 dB
1.710 GHz	1.715 GHz	100.000 kHz	1.71036 GHz	19.65 dBm	-10.35 dB

Date: 18.MAR.2015 16:37:42

Highest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
1.750 GHz	1.755 GHz	100.000 kHz	1.75466 GHz	20.10 dBm	-9.90 dB
1.755 GHz	1.756 GHz	50.000 kHz	1.75501 GHz	-22.93 dBm	-9.93 dB
1.756 GHz	1.765 GHz	1.000 MHz	1.75602 GHz	-21.84 dBm	-8.84 dB

Date: 18.MAR.2015 16:34:01

Lowest Band Edge / Full RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
1.700 GHz	1.709 GHz	1.000 MHz	1.70888 GHz	-27.12 dBm	-14.12 dB
1.709 GHz	1.710 GHz	50.000 kHz	1.71000 GHz	-32.08 dBm	-19.08 dB
1.710 GHz	1.715 GHz	100.000 kHz	1.71407 GHz	6.16 dBm	-23.84 dB

Date: 18.MAR.2015 16:39:28

Highest Band Edge / Full RB

Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
1.750 GHz	1.755 GHz	100.000 kHz	1.75357 GHz	6.32 dBm	-23.68 dB
1.755 GHz	1.756 GHz	50.000 kHz	1.75500 GHz	-31.01 dBm	-18.01 dB
1.756 GHz	1.765 GHz	1.000 MHz	1.75613 GHz	-25.63 dBm	-12.63 dB

Date: 18.MAR.2015 16:36:19

LTE Band 4 / 10MHz / QPSK

Lowest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
1.700 GHz	1.709 GHz	1.000 MHz	1.70893 GHz	-31.29 dBm	-18.29 dB
1.709 GHz	1.710 GHz	100.000 kHz	1.71000 GHz	-31.64 dBm	-18.64 dB
1.710 GHz	1.720 GHz	100.000 kHz	1.71060 GHz	21.11 dBm	-8.89 dB

Date: 18.MAR.2015 16:27:58

Highest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
1.745 GHz	1.755 GHz	100.000 kHz	1.75442 GHz	21.23 dBm	-8.77 dB
1.755 GHz	1.756 GHz	100.000 kHz	1.75501 GHz	-30.41 dBm	-17.41 dB
1.756 GHz	1.765 GHz	1.000 MHz	1.75610 GHz	-30.45 dBm	-17.45 dB

Date: 18.MAR.2015 16:32:46

Lowest Band Edge / Full RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
1.700 GHz	1.709 GHz	1.000 MHz	1.70888 GHz	-29.96 dBm	-16.96 dB
1.709 GHz	1.710 GHz	100.000 kHz	1.71000 GHz	-35.34 dBm	-22.34 dB
1.710 GHz	1.720 GHz	100.000 kHz	1.71834 GHz	4.09 dBm	-25.91 dB

Date: 18.MAR.2015 16:30:21

Highest Band Edge / Full RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
1.745 GHz	1.755 GHz	100.000 kHz	1.74895 GHz	4.34 dBm	-25.66 dB
1.755 GHz	1.756 GHz	100.000 kHz	1.75501 GHz	-33.25 dBm	-20.25 dB
1.756 GHz	1.765 GHz	1.000 MHz	1.76177 GHz	-27.76 dBm	-14.76 dB

Date: 18.MAR.2015 16:31:12