FCC RF Test Report

APPLICANT	:	CT Asia (HK) Ltd
EQUIPMENT	:	Smartphone
BRAND NAME	:	BLU
MODEL NAME	:	STUDIO 7.0 LTE
MARKETING NAME	:	STUDIO 7.0 LTE
FCC ID	:	YHLBLUST70LTE
STANDARD	:	FCC Part 15 Subpart C §15.247
CLASSIFICATION	:	(DSS) Spread Spectrum Transmitter

The product was received on May 19, 2015 and testing was completed on Jun. 20, 2015. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.

Reviewed by: Joseph Lin / Supervisor

Approved by: Jones Tsai / Manager

Testing Laboratory
1190

SPORTON INTERNATIONAL INC.
No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan District, Tao Yuan City, Taiwan, R.O.C.

TABLE OF CONTENTS

REVISION HISTORY **3**

SUMMARY OF TEST RESULT **4**

1 GENERAL DESCRIPTION **5**

1.1 Applicant 5
1.2 Manufacturer 5
1.3 Product Feature of Equipment Under Test 5
1.4 Product Specification subjective to this standard 6
1.5 Modification of EUT 7
1.6 Testing Location 7
1.7 Applicable Standards 7

2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST **8**

2.1 Descriptions of Test Mode 8
2.2 Test Mode 9
2.3 Connection Diagram of Test System 10
2.4 Support Unit used in test configuration and system 11
2.5 EUT Operation Test Setup 11
2.6 Measurement Results Explanation Example 12

3 TEST RESULT **13**

3.1 Number of Channel Measurement 13
3.2 Hopping Channel Separation Measurement 15
3.3 Dwell Time Measurement 22
3.4 20dB and 99% Bandwidth Measurement 25
3.5 Peak Output Power Measurement 38
3.6 Conducted Band Edges Measurement 40
3.7 Conducted Spurious Emission Measurement 47
3.8 Radiated Band Edges and Spurious Emission Measurement 57
3.9 AC Conducted Emission Measurement 63
3.10 Antenna Requirements 69

4 LIST OF MEASURING EQUIPMENT **70**

5 UNCERTAINTY OF EVALUATION **71**

APPENDIX A. RADIATED TEST RESULTS

APPENDIX B. SETUP PHOTOGRAPHS

REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR551902A	Rev. 01	Initial issue of report	Jul. 30, 2015

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(1)	Number of Channels	≥ 15Chs	Pass	-
3.2	15.247(a)(1)	Hopping Channel Separation	≥ 2/3 of 20dB BW	Pass	-
3.3	15.247(a)(1)	Dwell Time of Each Channel	≤ 0.4sec in 31.6sec period	Pass	-
3.4	15.247(a)(1)	20dB Bandwidth	NA	Pass	-
3.4	-	99% Bandwidth	-	Pass	-
3.5	15.247(b)(1)	Peak Output Power	≤ 125 mW	Pass	-
3.6	15.247(d)	Conducted Band Edges	≤ 20dBc	Pass	-
3.7	15.247(d)	Conducted Spurious Emission	≤ 20dBc	Pass	-
3.8	15.247(d)	Radiated Band Edges and Radiated Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 8.76 dB at 204.690 MHz
3.9	15.207	AC Conducted Emission	15.207(a)	Pass	Under limit 11.3 dB at 0.590 MHz
3.10	15.203 & 15.247(b)	Antenna Requirement	N/A	Pass	-

1 General Description

1.1 Applicant

CT Asia (HK) Ltd
Unit1309-11, 13th Floor 9 Wing Hong Street Cheung Sha Wan Kowloon, Hong Kong

1.2 Manufacturer

QUANTA COMPUTER INC.
211, Wen Hwa 2nd Rd., Guishan Dist., Tao Yuan City 33377, Taiwan

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Smartphone
Brand Name	BLU
Model Name	STUDIO 7.0 LTE
Marketing Name	STUDIO 7.0 LTE
FCC ID	YHLBLUST70LTE
EUT supports Radios application	GSM/GPRS/EGPRS/WCDMA/HSPA/DC-HSDPA/ HSPA+(Downlink only)/LTE WLAN2.4GHz 802.11b/g/n HT20 Bluetooth v3.0+EDR Bluetooth v4.0 LE
IMEI Code	Conducted: N/A Radiation: 357264048640024 Conduction: 357264048640362/357264048642368
HW Version	C
SW Version	BLU-S0010QU 05-29-2015 14:11
EUT Stage	Production Unit

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Product Specification subjective to this standard

Product Specification subjective to this standard	
Tx/Rx Frequency Range	2402 MHz ~ 2480 MHz
Number of Channels	79
Carrier Frequency of Each Channel	2402+n*1 MHz; n=0~78
Maximum Output Power to Antenna	Bluetooth BR(1Mbps) : 10.54 dBm (0.0113 W) Bluetooth EDR (2Mbps) : 10.54 dBm (0.0113 W) Bluetooth EDR (3Mbps) : 10.94 dBm (0.0124 W)
99% Occupied Bandwidth	Bluetooth BR(1Mbps) : 0.888MHz Bluetooth EDR (2Mbps) : 1.168MHz Bluetooth EDR (3Mbps) : 1.148MHz
Antenna Type	Chip Antenna with gain -1 dBi
Type of Modulation	Bluetooth BR (1Mbps) : GFSK Bluetooth EDR (2Mbps) : π/4-DQPSK Bluetooth EDR (3Mbps) : 8-DPSK

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Testing Location

Test Site	SPORTON INTERNATIONAL INC.			
Test Site Location	No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan District, Tao Yuan City, Taiwan, R.O.C. TEL: +886-3-327-3456 FAX: +886-3-328-4978			
Test Site No.	Sporton Site No.			FCC Registration No.
	TH05-HY	CO05-HY	03CH12-HY	TW1022

Note: The test site complies with ANSI C63.4 2009 requirement.

1.7 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC Part 15 Subpart C §15.247
- FCC Public Notice DA 00-705
- ANSI C63.10-2013

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. FCC permits the use of the 1.5 meter table as an alternative in C63.10-2013 through inquiry tracking number 961829.
3. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

2.1 Descriptions of Test Mode

Preliminary tests were performed in different data rates and recorded the RF output power in the following table:

Channel	Frequency	Bluetooth RF Output Power		
		Data Rate / Modulation		
		GFSK	π /4-DQPSK	8-DPSK
		1Mbps	2Mbps	3Mbps
Ch00	2402MHz	9.64 dBm	9.68 dBm	10.09 dBm
Ch39	2441MHz	10.54 dBm	10.54 dBm	**10.94 dBm**
Ch78	2480MHz	9.47 dBm	9.45 dBm	9.90 dBm

Remark:

1. All the test data for each data rate were verified, but only the worst case was reported.
2. The data rate was set in 3Mbps for all the test items due to the highest RF output power.

a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction (150 kHz to 30 MHz), radiation (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). Pre-scanned tests, X, Y, Z in three orthogonal panels, and different data rates were conducted to determine the final configuration (Z plane as worst plane) from all possible combinations, and the worst mode of radiated spurious emissions is Bluetooth 3Mbps mode, and recorded in this report.

b. AC power line Conducted Emission was tested under maximum output power.

2.2 Test Mode

The following summary table is showing all test modes to demonstrate in compliance with the standard.

Summary table of Test Cases			
Test Item	**Data Rate / Modulation**		
	Bluetooth BR 1Mbps GFSK	**Bluetooth EDR 2Mbps π/4-DQPSK**	**Bluetooth EDR 3Mbps 8-DPSK**
Conducted Test Cases	Mode 1: CH00_2402 MHz Mode 2: CH39_2441 MHz Mode 3: CH78_2480 MHz	Mode 4: CH00_2402 MHz Mode 5: CH39_2441 MHz Mode 6: CH78_2480 MHz	Mode 7: CH00_2402 MHz Mode 8: CH39_2441 MHz Mode 9: CH78_2480 MHz
Radiated Test Cases	**Bluetooth EDR 3Mbps 8-DPSK**		
	Mode 1: CH00_2402 MHz Mode 2: CH39_2441 MHz Mode 3: CH78_2480 MHz		
AC Conducted Emission	Mode 1 :GSM850 Link + Bluetooth Link + WLAN Link + Earphone + USB Cable (Charging from Adapter)		

Remark:

1. For radiated test cases, the worst mode data rate 3Mbps was reported only, because this data rate has the highest RF output power at preliminary tests, and no other significantly frequencies found in conducted spurious emission.
2. For Radiated Test Cases, The tests were performance with Adapter, Earphone, and USB Cable.

2.3 Connection Diagram of Test System

<Bluetooth Tx Mode>



<AC Conducted Emission Mode>



2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU 200	N/A	N/A	Unshielded, 1.8 m
2.	BT Base Station	R&S	CBT	N/A	N/A	Unshielded, 1.8 m
3.	WLAN AP	D-Link	DIR-865L	KA2IR865LA1	N/A	Unshielded,1.8m
4.	NOTE BOOK	Dell	Latitude E6320	FCC DoC	N/A	AC I/P : Unshielded, 1.2m DC O/P : Shielded, 1.8m
5.	Bluetooth Earphone	SonyErricsson	MW600	PY700A2029	N/A	N/A
6.	Earphone	Lenovo	SH100	N/A	N/A	N/A

2.5 EUT Operation Test Setup

For Bluetooth function, the engineering test program was provided and enabled to make EUT connect with Bluetooth base station to continuous transmit/receive.

For AC power line conducted emissions, the EUT was set to connect with the WLAN AP under large package sizes transmission.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example:

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 5.4 dB and 20dB attenuator.

Offset(dB) = RF cable loss(dB) + attenuator factor(dB).

= 5.4 + 20 = 25.4 (dB)

3 Test Result

3.1 Number of Channel Measurement

3.1.1 Limits of Number of Hopping Frequency

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.

3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedure

1. The testing follows FCC Public Notice DA 00-705 Measurement Guidelines.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings: Span = the frequency band of operation; RBW ≥ 1% of the span; VBW ≥ RBW; Sweep = auto; Detector function = peak; Trace = max hold.
6. The number of hopping frequency used is defined as the number of total channel.
7. Record the measurement data derived from spectrum analyzer.

3.1.4 Test Setup



3.1.5 Test Result of Number of Hopping Frequency

Test Mode :	3Mbps	**Temperature :**	21~25℃
Test Engineer :	Derek Hsu	**Relative Humidity :**	51~54%

Number of Hopping (Channel)	Adaptive Frequency Hopping (Channel)	Limits (Channel)	Pass/Fail
79	20	> 15	Pass

Number of Hopping Channel Plot on Channel 00 - 78



Date: 3.JUN.2015 20:05:42



Date: 3.JUN.2015 20:06:05

3.2 Hopping Channel Separation Measurement

3.2.1 Limit of Hopping Channel Separation

Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.

3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.2.3 Test Procedures

1. The testing follows FCC Public Notice DA 00-705 Measurement Guidelines.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings:
   Span = wide enough to capture the peaks of two adjacent channels; RBW ≥ 1% of the span; VBW ≥ RBW; Sweep = auto; Detector function = peak; Trace = max hold.
6. Measure and record the results in the test report.

3.2.4 Test Setup



3.2.5 Test Result of Hopping Channel Separation

Test Mode :	1Mbps	**Temperature :**	21~25℃
Test Engineer :	Derek Hsu	**Relative Humidity :**	51~54%

Channel	Frequency (MHz)	Frequency Separation (MHz)	(2/3 of 20dB BW) Limits (MHz)	Pass/Fail
00	2402	1.002	0.6240	Pass
39	2441	1.002	0.6293	Pass
78	2480	1.002	0.6293	Pass

Channel Separation Plot on Channel 00 - 01



Date: 3.JUN.2015 20:31:55

Channel Separation Plot on Channel 39 - 40



Date: 3.JUN.2015 20:34:57

Channel Separation Plot on Channel 77 - 78



Date: 3.JUN.2015 21:03:21

Test Mode :	2Mbps	**Temperature :**	21~25℃
Test Engineer :	Derek Hsu	**Relative Humidity :**	51~54%

Channel	Frequency (MHz)	Frequency Separation (MHz)	(2/3 of 20dB BW) Limits (MHz)	Pass/Fail
00	2402	1.002	0.8440	Pass
39	2441	1.002	0.8440	Pass
78	2480	1.002	0.8400	Pass

Channel Separation Plot on Channel 00 - 01



Date: 3.JUN.2015 20:42:40

Channel Separation Plot on Channel 39 - 40



Date: 3.JUN.2015 20:47:26

Channel Separation Plot on Channel 77 - 78



Date: 3.JUN.2015 20:50:51

Test Mode :	3Mbps	**Temperature :**	21~25℃
Test Engineer :	Derek Hsu	**Relative Humidity :**	51~54%

Channel	Frequency (MHz)	Frequency Separation (MHz)	(2/3 of 20dB BW) Limits (MHz)	Pass/Fail
00	2402	1.008	0.8240	Pass
39	2441	1.002	0.8240	Pass
78	2480	1.002	0.8280	Pass

Channel Separation Plot on Channel 00 - 01



Date: 3.JUN.2015 20:54:43

Channel Separation Plot on Channel 39 - 40



Date: 3.JUN.2015 20:58:18

Channel Separation Plot on Channel 77 - 78



Date: 3.JUN.2015 21:01:37

3.3 Dwell Time Measurement

3.3.1 Limit of Dwell Time

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.3.3 Test Procedures

1. The testing follows FCC Public Notice DA 00-705 Measurement Guidelines.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings: Span = zero span, centered on a hopping channel; RBW = 1 MHz; VBW ≥ RBW; Sweep = as necessary to capture the entire dwell time per hopping channel; Detector function = peak; Trace = max hold.
6. Measure and record the results in the test report.

3.3.4 Test Setup



3.3.5 Test Result of Dwell Time

Test Mode :	3DH5	**Temperature :**	21~25℃
Test Engineer :	Derek Hsu	**Relative Humidity :**	51~54%

Mode	Hopping Channel Number	Hops Over Occupancy Time(hops)	Package Transfer Time (msec)	Dwell Time (sec)	Limits (sec)	Pass/Fail
Normal	79	106.67	2.88	0.31	0.4	Pass
AFH	20	53.33	2.88	0.15	0.4	Pass

Remark:

1. In normal mode, hopping rate is 1600 hops/s with 6 slots in 79 hopping channels.
With channel hopping rate (1600 / 6 / 79) in Occupancy Time Limit (0.4 x 79) (s),
Hops Over Occupancy Time comes to (1600 / 6 / 79) x (0.4 x 79) = 106.67 hops.

2. In AFH mode, hopping rate is 800 hops/s with 6 slots in 20 hopping channels.
With channel hopping rate (800 / 6 / 20) in Occupancy Time Limit (0.4 x 20) (s),
Hops Over Occupancy Time comes to (800 / 6 / 20) x (0.4 x 20) = 53.33 hops.

3. Dwell Time(s) = Hops Over Occupancy Time (hops) x Package Transfer Time

Package Transfer Time Plot



Date: 2.JUN.2015 21:32:49

3.4 20dB and 99% Bandwidth Measurement

3.4.1 Limit of 20dB and 99% Bandwidth

Reporting only

3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.4.3 Test Procedures

1. The testing follows FCC Public Notice DA 00-705 Measurement Guidelines.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Use the following spectrum analyzer settings for 20dB Bandwidth measurement.
   Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hopping channel;
   RBW ≥ 1% of the 20 dB bandwidth; VBW ≥ RBW; Sweep = auto; Detector function = peak;
   Trace = max hold.
5. Use the following spectrum analyzer settings for 99 % Bandwidth measurement.
   For 99% Bandwidth measurement, the RBW=30kHz, and VBW = 100kHz. Sweep = auto ;
   Detector function = sample. Trace = max hold.
6. Measure and record the results in the test report.

3.4.4 Test Setup



3.4.5 Test Result of 20dB Bandwidth

Test Mode :	1Mbps	**Temperature :**	21~25℃
Test Engineer :	Derek Hsu	**Relative Humidity :**	51~54%

Channel	Frequency (MHz)	20dB Bandwidth (MHz)
00	2402	0.936
39	2441	0.944
78	2480	0.944

20 dB Bandwidth Plot on Channel 00



Date: 3.JUN.2015 20:25:08

20 dB Bandwidth Plot on Channel 39



Date: 3.JUN.2015 20:32:31

20 dB Bandwidth Plot on Channel 78



Date: 3.JUN.2015 20:35:39

Test Mode :	2Mbps	**Temperature :**	21~25℃
Test Engineer :	Derek Hsu	**Relative Humidity :**	51~54%

Channel	Frequency (MHz)	20dB Bandwidth (MHz)
00	2402	1.266
39	2441	1.266
78	2480	1.260

20 dB Bandwidth Plot on Channel 00



Date: 3.JUN.2015 20:39:44

20 dB Bandwidth Plot on Channel 39



Date: 3.JUN.2015 20:43:16

20 dB Bandwidth Plot on Channel 78



Date: 3.JUN.2015 20:48:12

Test Mode :	3Mbps	**Temperature :**	21~25℃
Test Engineer :	Derek Hsu	**Relative Humidity :**	51~54%

Channel	Frequency (MHz)	20dB Bandwidth (MHz)
00	2402	1.236
39	2441	1.236
78	2480	1.242

20 dB Bandwidth Plot on Channel 00



Date: 3.JUN.2015 20:52:01

20 dB Bandwidth Plot on Channel 39



Date: 3.JUN.2015 20:55:18

20 dB Bandwidth Plot on Channel 78



Date: 3.JUN.2015 20:58:48

3.4.6 Test Result of 99% Occupied Bandwidth

Test Mode :	1Mbps	**Temperature :**	21~25℃
Test Engineer :	Derek Hsu	**Relative Humidity :**	51~54%

Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)
00	2402	0.888
39	2441	0.884
78	2480	0.888

99% Occupied Bandwidth Plot on Channel 00



Date: 3.JUN.2015 20:26:13

99% Occupied Bandwidth Plot on Channel 39



Date: 3.JUN.2015 20:33:12

99% Occupied Bandwidth Plot on Channel 78



Date: 3.JUN.2015 20:36:48

Test Mode :	2Mbps	**Temperature :**	21~25℃
Test Engineer :	Derek Hsu	**Relative Humidity :**	51~54%

Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)
00	2402	1.168
39	2441	1.168
78	2480	1.168

99% Occupied Bandwidth Plot on Channel 00



Date: 3.JUN.2015 20:40:44

99% Occupied Bandwidth Plot on Channel 39



Date: 3.JUN.2015 20:43:51

99% Occupied Bandwidth Plot on Channel 78



Date: 3.JUN.2015 20:49:06

Test Mode :	3Mbps	**Temperature :**	21~25℃
Test Engineer :	Derek Hsu	**Relative Humidity :**	51~54%

Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)
00	2402	1.148
39	2441	1.148
78	2480	1.148

99% Occupied Bandwidth Plot on Channel 00



Date: 3.JUN.2015 20:53:01

99% Occupied Bandwidth Plot on Channel 39



Date: 3.JUN.2015 20:55:56

99% Occupied Bandwidth Plot on Channel 78



Date: 3.JUN.2015 20:59:44

Note : The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

3.5 Peak Output Power Measurement

3.5.1 Limit of Peak Output Power

Section 15.247 (b) The maximum peak conducted output power of the intentional radiator shall not exceed the following: (1) For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band 0.125 watts.

3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.5.3 Test Procedures

1. The testing follows FCC Public Notice DA 00-705 Measurement Guidelines.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power with cable loss and record the results in the test report.
5. Measure and record the results in the test report.

3.5.4 Test Setup



3.5.5 Test Result of Peak Output Power

Test Mode :	1Mbps	**Temperature :**	21~25℃
Test Engineer :	Derek Hsu	**Relative Humidity :**	51~54%

Channel	Frequency (MHz)	RF Power (dBm)		
		GFSK	Max. Limits (dBm)	Pass/Fail
		1 Mbps		
00	2402	9.64	20.97	Pass
39	2441	10.54	20.97	Pass
78	2480	9.47	20.97	Pass

Test Mode :	2Mbps	**Temperature :**	21~25℃
Test Engineer :	Derek Hsu	**Relative Humidity :**	51~54%

Channel	Frequency (MHz)	RF Power (dBm)		
		π/4-DQPSK	Max. Limits (dBm)	Pass/Fail
		2 Mbps		
00	2402	9.68	20.97	Pass
39	2441	10.54	20.97	Pass
78	2480	9.45	20.97	Pass

Test Mode :	3Mbps	**Temperature :**	21~25℃
Test Engineer :	Derek Hsu	**Relative Humidity :**	51~54%

Channel	Frequency (MHz)	RF Power (dBm)		
		8-DPSK	Max. Limits (dBm)	Pass/Fail
		3 Mbps		
00	2402	10.09	20.97	Pass
39	2441	10.94	20.97	Pass
78	2480	9.90	20.97	Pass

3.6 Conducted Band Edges Measurement

3.6.1 Limit of Band Edges

In any 100 kHz bandwidth outside the intentional radiation frequency band, the radio frequency power shall be at least 20 dB below the highest level of the radiated power. In addition, radiated emissions which fall in the restricted bands must also comply with the radiated emission limits.

3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.6.3 Test Procedures

1. The testing follows the guidelines in Band-edge Compliance of RF Conducted Emissions of FCC Public Notice DA 00-705 Measurement Guidelines.
2. Set to the maximum power setting and enable the EUT transmit continuously.
3. Set RBW = 100kHz (≥ 1% span=10MHz), VBW = 300kHz (≥ RBW). Band edge emissions must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100kHz RBW. The attenuation shall be 30 dB instead of 20 dB when RMS conducted output power procedure is used.
4. Enable hopping function of the EUT and then repeat step 2. and 3.
5. Measure and record the results in the test report.

3.6.4 Test Setup



3.6.5 Test Result of Conducted Band Edges

Test Mode :	1Mbps	**Temperature :**	21~25℃
Test Channel :	00 and 78	**Relative Humidity :**	51~54%
		Test Engineer :	Derek Hsu

Low Band Edge Plot on Channel 00



Date: 3.JUN.2015 20:25:34

High Band Edge Plot on Channel 78



Date: 3.JUN.2015 20:36:06

Test Mode :	2Mbps	**Temperature :**	21~25℃
Test Channel :	00 and 78	**Relative Humidity :**	51~54%
		Test Engineer :	Derek Hsu

Low Band Edge Plot on Channel 00



Date: 3.JUN.2015 20:40:02

High Band Edge Plot on Channel 78



Date: 3.JUN.2015 20:48:31

Test Mode :	3Mbps	**Temperature :**	21~25℃
Test Channel :	00 and 78	**Relative Humidity :**	51~54%
		Test Engineer :	Derek Hsu

Low Band Edge Plot on Channel 00



Date: 3.JUN.2015 20:52:20

High Band Edge Plot on Channel 78



Date: 3.JUN.2015 20:59:08

3.6.6 Test Result of Conducted Hopping Mode Band Edges

Test Mode :	1Mbps	Temperature :	21~25℃
Test Engineer :	Derek Hsu	Relative Humidity :	51~54%

1Mbps Hopping Mode Low Band Edge Plot



Date: 3.JUN.2015 20:23:02

1Mbps Hopping Mode High Band Edge Plot



Date: 3.JUN.2015 20:24:27

Test Mode :	2Mbps	Temperature :	21~25℃
Test Engineer :	Derek Hsu	Relative Humidity :	51~54%

2Mbps Hopping Mode Low Band Edge Plot



Date: 3.JUN.2015 20:18:04

2Mbps Hopping Mode High Band Edge Plot



Date: 3.JUN.2015 20:20:00

Test Mode :	3Mbps	Temperature :	21~25℃
Test Engineer :	Derek Hsu	Relative Humidity :	51~54%

3Mbps Hopping Mode Low Band Edge Plot



Date: 3.JUN.2015 20:07:42

3Mbps Hopping Mode High Band Edge Plot



Date: 3.JUN.2015 20:12:24

3.7 Conducted Spurious Emission Measurement

3.7.1 Limit of Spurious Emission Measurement

In any 100 kHz bandwidth outside the intentional radiation frequency band, the radio frequency power shall be at least 20 dB below the highest level of the radiated power. In addition, radiated emissions which fall in the restricted bands must also comply with the radiated emission limits.

3.7.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.7.3 Test Procedure

1. The testing follows the guidelines in Spurious RF Conducted Emissions of FCC Public Notice DA 00-705 Measurement Guidelines
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW = 300kHz, scan up through 10th harmonic. All harmonics / spurs must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100 kHz RBW.
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.7.4 Test Setup



3.7.5 Test Result of Conducted Spurious Emission

Test Mode :	1Mbps	**Temperature :**	21~25℃
Test Channel :	00	**Relative Humidity :**	51~54%
		Test Engineer :	Derek Hsu

1Mbps CSE Plot on Ch 00 between 30MHz ~ 3 GHz



Date: 3.JUN.2015 20:27:48

1Mbps CSE Plot on Ch 00 between 2 GHz ~ 25 GHz



Date: 3.JUN.2015 20:28:09

Test Mode :	1Mbps	**Temperature :**	21~25℃
Test Channel :	39	**Relative Humidity :**	51~54%
		Test Engineer :	Derek Hsu

1Mbps CSE Plot on Ch 39 between 30MHz ~ 3 GHz



Date: 3.JUN.2015 20:33:36

1Mbps CSE Plot on Ch 39 between 2 GHz ~ 25 GHz



Date: 3.JUN.2015 20:33:58

Test Mode :	1Mbps	**Temperature :**	21~25℃
Test Channel :	78	**Relative Humidity :**	51~54%
		Test Engineer :	Derek Hsu

1Mbps CSE Plot on Ch 78 between 30MHz ~ 3 GHz



Date: 3.JUN.2015 20:38:08

1Mbps CSE Plot on Ch 78 between 2 GHz ~ 25 GHz



Date: 3.JUN.2015 20:38:30

Test Mode :	2Mbps	**Temperature :**	21~25℃
Test Channel :	00	**Relative Humidity :**	51~54%
		Test Engineer :	Derek Hsu

2Mbps CSE Plot on Ch 00 between 30MHz ~ 3 GHz



Date: 3.JUN.2015 20:41:09

2Mbps CSE Plot on Ch 00 between 2 GHz ~ 25 GHz



Date: 3.JUN.2015 20:41:31

Test Mode :	2Mbps	**Temperature :**	21~25℃
Test Channel :	39	**Relative Humidity :**	51~54%
		Test Engineer :	Derek Hsu

2Mbps CSE Plot on Ch 39 between 30MHz ~ 3 GHz



Date: 3.JUN.2015 20:44:14

2Mbps CSE Plot on Ch 39 between 2 GHz ~ 25 GHz



Date: 3.JUN.2015 20:44:36

Test Mode :	2Mbps	**Temperature :**	21~25℃
Test Channel :	78	**Relative Humidity :**	51~54%
		Test Engineer :	Derek Hsu

2Mbps CSE Plot on Ch 78 between 30MHz ~ 3 GHz



Date: 3.JUN.2015 20:49:31

2Mbps CSE Plot on Ch 78 between 2 GHz ~ 25 GHz



Date: 3.JUN.2015 20:49:52

Test Mode :	3Mbps	**Temperature :**	21~25℃
Test Channel :	00	**Relative Humidity :**	51~54%
		Test Engineer :	Derek Hsu

3Mbps CSE Plot on Ch 00 between 30MHz ~ 3 GHz



Date: 3.JUN.2015 20:53:25

3Mbps CSE Plot on Ch 00 between 2 GHz ~ 25 GHz



Date: 3.JUN.2015 20:53:47

Test Mode :	3Mbps	**Temperature :**	21~25℃
Test Channel :	39	**Relative Humidity :**	51~54%
		Test Engineer :	Derek Hsu

3Mbps CSE Plot on Ch 39 between 30MHz ~ 3 GHz



Date: 3.JUN.2015 20:57:05

3Mbps CSE Plot on Ch 39 between 2 GHz ~ 25 GHz



Date: 3.JUN.2015 20:57:26

Test Mode :	3Mbps	**Temperature :**	21~25℃
Test Channel :	78	**Relative Humidity :**	51~54%
		Test Engineer :	Derek Hsu

3Mbps CSE Plot on Ch 78 between 30MHz ~ 3 GHz



Date: 3.JUN.2015 21:00:09

3Mbps CSE Plot on Ch 78 between 2 GHz ~ 25 GHz



Date: 3.JUN.2015 21:00:31

3.8 Radiated Band Edges and Spurious Emission Measurement

3.8.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. In addition, radiated emissions which fall in the restricted bands must also comply with the FCC section 15.209 limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.8.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.8.3 Test Procedures

1. The testing follows the guidelines in Spurious Radiated Emissions of FCC Public Notice DA 00-705 Measurement Guidelines.
2. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
3. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
4. For each suspected emission, the EUT was arranged to its worst case and then tune the Antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level to comply with the guidelines.
5. Set to the maximum power setting and enable the EUT transmit continuously.
6. Use the following spectrum analyzer settings:
   (1) Span shall wide enough to fully capture the emission being measured;
   (2) Set RBW=100 kHz for f < 1 GHz, RBW=1MHz for f>1GHz ; VBW ≥ RBW; Sweep = auto; Detector function = peak; Trace = max hold for peak
   (3) For average measurement: use duty cycle correction factor method per 15.35(c).
   Duty cycle = On time/100 milliseconds
   On time = $N_1*L_1+N_2*L_2+...+N_{n-1}*LN_{n-1}+N_n*L_n$
   Where N_1 is number of type 1 pulses, L_1 is length of type 1 pulses, etc.
   Average Emission Level = Peak Emission Level + 20*log(Duty cycle)
7. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level

Note: The average levels were calculated from the peak level corrected with duty cycle correction factor (-24.79dB) derived from 20log (dwell time/100ms). This correction is only for signals that hop with the fundamental signal, such as band-edge and harmonic. Other spurious signals that are independent of the hopping signal would not use this correction.

3.8.4 Test Setup

For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



3.8.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.

3.8.6 Duty cycle correction factor for average measurement

3DH5 on time (One Pulse) Plot on Channel 39



Date: 19.JUN.2015 23:41:16

3DH5 on time (Count Pulses) Plot on Channel 39



Date: 19.JUN.2015 23:42:21

Note:

1. Worst case Duty cycle = on time/100 milliseconds = 2 * 2.9 / 100 = 5.80 %
2. Worst case Duty cycle correction factor = 20*log(Duty cycle) = -24.73 dB
3. 3DH5 has the highest duty cycle worst case and is reported.

Duty Cycle Correction Factor Consideration for AFH mode:

Bluetooth normal hopping rate is 1600Hz and reduced to 800Hz in AFH mode; due to the reduced number of hopping frequencies, with the same packet configuration the dwell time in each channel frequency within 100msec period is longer in AFH mode than normal mode.

In AFH mode, the minimum hopping frequencies are 20, to get the longest dwell time DH5 packet is observed; the period to have DH5 packet completing one hopping sequence is

2.9 ms x 20 channels = 58.0 ms

There cannot be 2 complete hopping sequences within 100ms period, considering the random hopping behavior, maximum 2 hops can be possibly observed within the period. [100ms / 57.6ms] = 2 hops

Thus, the maximum possible ON time:

2.90 ms x 2 = 5.80 ms

Worst case Duty Cycle Correction factor, which is derived from the maximum possible ON time,

20 x log(5.80 ms/100ms) = -24.73 dB

3.8.7 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix A.

3.8.8 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix A.

3.9 AC Conducted Emission Measurement

3.9.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dBμV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

3.9.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.9.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

3.9.4 Test Setup



3.9.5 Test Result of AC Conducted Emission

Test Mode :	Mode 1	**Temperature :**	21~23℃
Test Engineer :	Jacky Yang	**Relative Humidity :**	41~43%
Test Voltage :	120Vac / 60Hz	**Phase :**	Line
Function Type :	GSM850 Link + Bluetooth Link + WLAN Link + Earphone + USB Cable (Charging from Adapter)		

ENV216 Auto Test



Final Result : Quasi-Peak

Frequency (MHz)	Quasi-Peak (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.150000	43.1	Off	L1	19.5	22.9	66.0
0.182000	41.0	Off	L1	19.5	23.4	64.4
0.590000	42.1	Off	L1	19.5	13.9	56.0
9.878000	43.0	Off	L1	19.9	17.0	60.0
10.078000	43.8	Off	L1	19.9	16.2	60.0
10.542000	44.9	Off	L1	19.9	15.1	60.0
10.910000	44.4	Off	L1	19.8	15.6	60.0
11.310000	44.3	Off	L1	19.9	15.7	60.0
11.638000	43.4	Off	L1	19.9	16.6	60.0
11.886000	42.7	Off	L1	19.9	17.3	60.0

Test Mode :	Mode 1	**Temperature :**	21~23℃
Test Engineer :	Jacky Yang	**Relative Humidity :**	41~43%
Test Voltage :	120Vac / 60Hz	**Phase :**	Line
Function Type :	GSM850 Link + Bluetooth Link + WLAN Link + Earphone + USB Cable (Charging from Adapter)		

ENV216 Auto Test



Final Result : Average

Frequency (MHz)	Average (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.150000	30.0	Off	L1	19.5	26.0	56.0
0.182000	26.1	Off	L1	19.5	28.3	54.4
0.590000	34.7	Off	L1	19.5	11.3	46.0
9.878000	33.9	Off	L1	19.9	16.1	50.0
10.078000	35.1	Off	L1	19.9	14.9	50.0
10.542000	36.0	Off	L1	19.9	14.0	50.0
10.910000	35.6	Off	L1	19.8	14.4	50.0
11.310000	35.5	Off	L1	19.9	14.5	50.0
11.638000	34.7	Off	L1	19.9	15.3	50.0
11.886000	33.9	Off	L1	19.9	16.1	50.0

Test Mode :	Mode 1	**Temperature :**	21~23℃
Test Engineer :	Jacky Yang	**Relative Humidity :**	41~43%
Test Voltage :	120Vac / 60Hz	**Phase :**	Neutral
Function Type :	GSM850 Link + Bluetooth Link + WLAN Link + Earphone + USB Cable (Charging from Adapter)		

ENV216 Auto Test



Final Result : Quasi-Peak

Frequency (MHz)	Quasi-Peak (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.150000	42.5	Off	N	19.5	23.5	66.0
0.246000	34.3	Off	N	19.5	27.6	61.9
0.582000	34.9	Off	N	19.4	21.1	56.0
1.470000	22.1	Off	N	19.6	33.9	56.0
10.030000	42.7	Off	N	19.9	17.3	60.0
10.318000	43.2	Off	N	19.8	16.8	60.0
10.766000	44.8	Off	N	19.8	15.2	60.0
11.262000	44.5	Off	N	20.0	15.5	60.0
11.758000	43.7	Off	N	19.9	16.3	60.0
12.406000	40.9	Off	N	20.0	19.1	60.0

Test Mode :	Mode 1	**Temperature :**	21~23℃
Test Engineer :	Jacky Yang	**Relative Humidity :**	41~43%
Test Voltage :	120Vac / 60Hz	**Phase :**	Neutral
Function Type :	GSM850 Link + Bluetooth Link + WLAN Link + Earphone + USB Cable (Charging from Adapter)		

ENV216 Auto Test



Final Result : Average

Frequency (MHz)	Average (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.150000	27.0	Off	N	19.5	29.0	56.0
0.246000	20.6	Off	N	19.5	31.3	51.9
0.582000	26.6	Off	N	19.4	19.4	46.0
1.470000	15.7	Off	N	19.6	30.3	46.0
10.030000	32.3	Off	N	19.9	17.7	50.0
10.318000	33.0	Off	N	19.8	17.0	50.0
10.766000	33.6	Off	N	19.8	16.4	50.0
11.262000	33.3	Off	N	20.0	16.7	50.0
11.758000	32.6	Off	N	19.9	17.4	50.0
12.406000	30.0	Off	N	20.0	20.0	50.0

3.10 Antenna Requirements

3.10.1 Standard Applicable

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the FCC rule.

3.10.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.10.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.

4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Power Meter	Agilent	E4416A	GB41292344	300MHz~40GHz	Jan. 14, 2015	Jun. 02, 2015 ~ Jun. 04, 2015	Jan. 13, 2016	Conducted (TH05-HY)
Power Sensor	Agilent	E9327A	US40441548	300MHz~40GHz	Jan. 14, 2015	Jun. 02, 2015 ~ Jun. 04, 2015	Jan. 13, 2016	Conducted (TH05-HY)
Spectrum Analyzer	Rohde & Schwarz	FSP40	100057	9kHz-40GHz	Oct. 17, 2014	Jun. 02, 2015 ~ Jun. 04, 2015	Oct. 16, 2015	Conducted (TH05-HY)
EMI Test Receiver	Rohde & Schwarz	ESU26	100472	20Hz~26.5GHz	Jan. 19, 2015	Jun. 17, 2015 ~ Jun. 20, 2015	Jan. 18, 2016	Radiation (03CH12-HY)
Preamplifier	COM-POWER	PA-103A	161075	10MHz~1GHz	Apr. 09, 2015	Jun. 17, 2015 ~ Jun. 20, 2015	Apr. 08, 2016	Radiation (03CH12-HY)
Preamplifier	MITEQ	AMF-7D-00101800-30-10P	1590074	1GHz~18GHz	Jul. 07, 2014	Jun. 17, 2015 ~ Jun. 20, 2015	Jul. 06, 2015	Radiation (03CH12-HY)
Preamplifier	Agilent	8449B	3008A02375	1GHz~26.5GHz	Jan. 15, 2015	Jun. 17, 2015 ~ Jun. 20, 2015	Jan. 14, 2016	Radiation (03CH12-HY)
Bilog Antenna	TESEQ	CBL 6111D	37059	30MHz~1GHz	Sep. 27, 2014	Jun. 17, 2015 ~ Jun. 20, 2015	Sep. 26, 2015	Radiation (03CH12-HY)
Horn Antenna	SCHWARZBECK	BBHA 9120 D	9120D-1241	1GHz ~ 18GHz	Apr. 22, 2015	Jun. 17, 2015 ~ Jun. 20, 2015	Apr. 21, 2016	Radiation (03CH12-HY)
Turn Table	EMEC	TT2000	N/A	0-360 degree	N/A	Jun. 17, 2015 ~ Jun. 20, 2015	N/A	Radiation (03CH12-HY)
Antenna Mast	EMEC	AM-BS-4500-B	N/A	1m~4m	N/A	Jun. 17, 2015 ~ Jun. 20, 2015	N/A	Radiation (03CH12-HY)
EMI Test Receiver	Rohde & Schwarz	ESCS 30	100356	9kHz – 2.75GHz	Dec. 01, 2014	Jun. 09, 2015	Nov. 30, 2015	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100080	9kHz~30MHz	Dec. 02, 2014	Jun. 09, 2015	Dec. 01, 2015	Conduction (CO05-HY)
LISN (for auxiliary equipment)	Rohde & Schwarz	ENV216	100081	9kHz ~ 30MHz	Dec. 08, 2014	Jun. 09, 2015	Dec. 07, 2015	Conduction (CO05-HY)
AC Power Source	ChainTek	APC-1000W	N/A	N/A	N/A	Jun. 09, 2015	N/A	Conduction (CO05-HY)

5 Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	2.3 dB

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	5.4 dB

Appendix A. Radiated Spurious Emission

2.4GHz 2400~2483.5MHz

BT (Band Edge @ 3m)

BT	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
BT CH00 2402MHz		2382.02	47.21	-26.79	74	46.72	27.09	7.38	33.98	100	146	P	H
		2382.02	22.48	-31.52	54	-	-	-	-	-	-	A	H
	*	2402	99.42	-	-	98.91	27.13	7.38	34	100	146	P	H
	*	2402	74.69	-	-	-	-	-	-	-	-	A	H
		2318.19	47.48	-26.52	74	47.22	26.95	7.24	33.93	121	21	P	V
		2318.19	22.75	-31.25	54	-	-	-	-	-	-	A	V
	*	2402	103.99	-	-	103.48	27.13	7.38	34	121	21	P	V
	*	2402	79.26	-	-	-	-	-	-	-	-	A	V
BT CH 39 2441MHz		2344.39	47.32	-26.68	74	46.95	27	7.31	33.94	204	194	P	H
		2344.39	22.59	-31.41	54	-	-	-	-	-	-	A	H
	*	2441	100.14	-	-	99.48	27.27	7.44	34.05	204	194	P	H
	*	2441	75.41	-	-	-	-	-	-	-	-	A	H
		2483.85	46.85	-27.15	74	46.07	27.36	7.5	34.08	204	194	P	H
		2483.85	22.12	-31.88	54	-	-	-	-	-	-	A	H
		2347.24	47.48	-26.52	74	47.11	27	7.31	33.94	100	20	P	V
		2347.24	22.75	-31.25	54	-	-	-	-	-	-	A	V
	*	2441	101.88	-	-	101.22	27.27	7.44	34.05	100	20	P	V
	*	2441	77.15	-	-	-	-	-	-	-	-	A	V
		2487.27	47.14	-26.86	74	46.36	27.36	7.5	34.08	100	20	P	V
		2487.27	22.41	-31.59	54	-	-	-	-	-	-	A	V

BT CH 78 2480MHz	*	2480	94.24	-	-	93.46	27.36	7.5	34.08	199	194	P	H
	*	2480	69.51	-	-	-	-	-	-	-	-	A	H
		2483.5	52.98	-21.02	74	52.2	27.36	7.5	34.08	199	194	P	H
		2483.5	28.25	-25.75	54	-	-	-	-	-	-	A	H
	*	2480	96.48	-	-	95.7	27.36	7.5	34.08	100	360	P	V
	*	2480	71.75	-	-	-	-	-	-	-	-	A	V
		2483.5	54.45	-19.55	74	53.67	27.36	7.5	34.08	100	360	P	V
		2483.5	29.72	-24.28	54	-	-	-	-	-	-	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

2.4GHz 2400~2483.5MHz

BT (Harmonic @ 3m)

BT	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
BT CH 00 2402MHz		4803	47.56	-26.44	74	64.27	31.3	10.63	58.64	100	0	P	H
		4803	22.83	-31.17	54	-	-	-	-	-	-	A	H
		4803	42.59	-31.41	74	59.3	31.3	10.63	58.64	100	0	P	V
		4803	17.86	-36.14	54	-	-	-	-	-	-	A	V
BT CH 39 2441MHz		4881	44.57	-29.43	74	61	31.41	10.68	58.52	100	0	P	H
		4881	19.84	-34.16	54	-	-	-	-	-	-	A	H
		7323	51.61	-22.39	74	60.26	36.26	13.28	58.19	100	0	P	H
		7323	26.88	-27.12	54	-	-	-	-	-	-	A	H
		4881	40.91	-33.09	74	57.34	31.41	10.68	58.52	100	0	P	V
		4881	16.18	-37.82	54	-	-	-	-	-	-	A	V
		7323	50.13	-23.87	74	58.78	36.26	13.28	58.19	100	0	P	V
		7323	25.4	-28.6	54	-	-	-	-	-	-	A	V
BT CH 78 2480MHz		4962	43.74	-30.26	74	59.83	31.54	10.73	58.36	100	0	P	H
		4962	19.01	-34.99	54	-	-	-	-	-	-	A	H
		7440	45.15	-28.85	74	53.67	36.5	13.39	58.41	100	0	P	H
		7440	20.42	-33.58	54	-	-	-	-	-	-	A	H
		4959	38.75	-35.25	74	54.84	31.54	10.73	58.36	100	0	P	V
		4959	14.02	-39.98	54	-	-	-	-	-	-	A	V
		7440	44.35	-29.65	74	52.87	36.5	13.39	58.41	100	0	P	V
		7440	19.62	-34.38	54	-	-	-	-	-	-	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

Emission below 1GHz

2.4GHz BT (LF)

BT	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
2.4GHz BT LF		102.36	32.29	-11.21	43.5	50.65	10.41	1.64	30.41			P	H
		204.69	34.18	-9.32	43.5	53.3	9.08	2.09	30.29	100	0	P	H
		255.99	24.59	-21.41	46	39.08	13.39	2.34	30.22			P	H
		307	34.25	-11.75	46	48.54	13.29	2.56	30.14			P	H
		358.1	23.89	-22.11	46	36.57	14.64	2.76	30.08			P	H
		409.2	26.61	-19.39	46	38.04	15.64	2.94	30.01			P	H
		64.29	27.39	-12.61	40	50.4	6.05	1.39	30.45			P	V
		102.36	27.82	-15.68	43.5	46.18	10.41	1.64	30.41			P	V
		204.69	34.74	-8.76	43.5	53.86	9.08	2.09	30.29	100	0	P	V
		307	25.43	-20.57	46	39.72	13.29	2.56	30.14			P	V
		409.2	20.66	-25.34	46	32.09	15.64	2.94	30.01			P	V
		561.8	22.91	-23.09	46	29.15	20.02	3.46	29.72			P	V
Remark	1. No other spurious found. 2. All results are PASS against limit line.												

Note symbol

*	**Fundamental Frequency** which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is **over limit** line.
P/A	**P**eak or **A**verage
H/V	**H**orizontal or **V**ertical

A calculation example for radiated spurious emission is shown as below:

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1+2		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b CH 01 2412MHz		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

1. Level(dBμV/m) =

Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

2. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

For Peak Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)

= 55.45 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 55.45(dBμV/m) – 74(dBμV/m)

= -18.55(dB)

For Average Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)

= 43.54 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 43.54(dBμV/m) – 54(dBμV/m)

= -10.46(dB)

Both peak and average measured complies with the limit line, so test result is “PASS”.