FCC RF Test Report

APPLICANT	:	**CT Asia (HK) Ltd.**
EQUIPMENT	:	**Smartphone**
BRAND NAME	:	**BLU**
MODEL NAME	:	**STUDIO C 5+5 LTE**
FCC ID	:	**YHLBLUSTC55LTE**
STANDARD	:	**FCC 47 CFR Part 2, 22(H), 24(E),27(L)**
CLASSIFICATION	:	**PCS Licensed Transmitter Held to Ear (PCE)**

The product was received on Jul. 14, 2015 and testing was completed on Jul. 29, 2015. We, SPORTON INTERNATIONAL (SHENZHEN) INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures given in ANSI / TIA / EIA-603-C-2004 and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL (SHENZHEN) INC., the test report shall not be reproduced except in full.

Reviewed by: Joseph Lin / Supervisor

Approved by: Jones Tsai / Manager

Testing Laboratory
2353

SPORTON INTERNATIONAL (SHENZHEN) INC.

1F & 2F, Building A, Morning Business Center, No. 4003 ShiGu Rd., Xili Town, Nanshan District, Shenzhen, Guangdong, P. R. China

TABLE OF CONTENTS

1 GENERAL DESCRIPTION 5
1.1 Applicant 5
1.2 Manufacturer 5
1.3 Product Feature of Equipment Under Test 5
1.4 Product Specification subjective to this standard 6
1.5 Modification of EUT 6
1.6 Maximum ERP/EIRP Power, Frequency Tolerance, and Emission Designator 7
1.7 Testing Location 8
1.8 Applicable Standards 8

2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST 9
2.1 Test Mode 9
2.2 Connection Diagram of Test System 12
2.3 Support Unit used in test configuration 12
2.4 Measurement Results Explanation Example 13

3 TEST RESULT 14
3.1 Conducted Output Power Measurement 14
3.2 Peak-to-Average Ratio 16
3.3 Effective Radiated Power and Effective Isotropic Radiated Power Measurement 32
3.4 99% Occupied Bandwidth and 26dB Bandwidth Measurement 36
3.5 Band Edge Measurement 60
3.6 Conducted Spurious Emission Measurement 68
3.7 Field Strength of Spurious Radiation Measurement 90
3.8 Frequency Stability Measurement 113

4 LIST OF MEASURING EQUIPMENT 119

5 UNCERTAINTY OF EVALUATION 120

APPENDIX A. SETUP PHOTOGRAPHS

REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FG571406A	Rev. 01	Initial issue of report	Sep. 08, 2015

SUMMARY OF TEST RESULT

Report Section	FCC Rule	IC Rule	Description	Limit	Result	Remark
3.1	§2.1046	RSS-132 (5.4) RSS-133 (6.4) RSS-139 (6.5)	Conducted Output Power	Reporting Only	PASS	-
3.2	§24.232(d)	RSS-132 (5.4) RSS-133 (6.4) RSS-139 (6.5)	Peak-to-Average Ratio	< 13 dB	PASS	-
3.3	§22.913(a)(2)	RSS-132(5.4) SRSP-503(5.1.3)	Effective Radiated Power	< 7 Watts	PASS	-
	§24.232(c)	RSS-133 (6.4) SRSP-510(5.1.2)	Equivalent Isotropic Radiated Power	< 2 Watts	PASS	-
	§27.50(d)(4)	RSS-139 (6.5) SRSP-513(5.1.2)	Equivalent Isotropic Radiated Power	< 1 Watts	PASS	-
3.4	§2.1049	RSS-GEN(6.6) RSS-133(6.5) RSS-139 (3.1)	Occupied Bandwidth	Reporting Only	PASS	-
3.5	§2.1051 §22.917(a) §24.238(a) §27.53(h)	RSS-132 (5.5) RSS-133 (6.5) RSS-139 (6.6)	Band Edge Measurement	< 43+10log10(P[Watts])	PASS	-
3.6	§2.1051 §22.917(a) §24.238(a) §27.53(h)	RSS-132 (5.5) RSS-133 (6.5) RSS-139 (6.6)	Conducted Emission	< 43+10log10(P[Watts])	PASS	-
3.7	§2.1053 §22.917(a) §24.238(a) §27.53(h)	RSS-132 (5.5) RSS-133 (6.5) RSS-139 (6.6)	Field Strength of Spurious Radiation	< 43+10log10(P[Watts])	PASS	Under limit 13.83 dB at 5640.000 MHz
3.8	§2.1055 §22.355	RSS-GEN(6.11) RSS-132 (5.3)	Frequency Stability for Temperature & Voltage	< 2.5 ppm for Part 22 Within Authorized Band	PASS	-
	§2.1055 §24.235 §27.54	RSS-GEN(6.11) RSS-133 (6.3) RSS-139 (6.4)				

1 General Description

1.1 Applicant

CT Asia (HK) Ltd.
Unit1309-11, 13th Floor 9 Wing Hong Street Cheung Sha Wan Kowloon, Hong Kong

1.2 Manufacturer

CT Asia (HK) Ltd.
Unit1309-11, 13th Floor 9 Wing Hong Street Cheung Sha Wan Kowloon, Hong Kong

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Smartphone
Brand Name	BLU
Model Name	STUDIO C 5+5 LTE
FCC ID	YHLBLUSTC55LTE
EUT supports Radios application	GSM/GPRS/EGPRS/WCDMA/HSPA/ HSPA+(Downlink Only) /LTE/ WLAN 2.4GHz 802.11b/g/n HT20/HT40/ Bluetooth v3.0+EDR/Bluetooth v4.0 LE
IMEI Code	Conducted: 353919026794424/353924026794424 Radiation: 353919026794374/353924026794374 ERP&EIRP: N/A
HW Version	V1.0
SW Version	BLU_S0050UU_V04.01_GENERIC
EUT Stage	Pre-Production

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Product Specification subjective to this standard

Product Specification subjective to this standard	
Tx Frequency	GSM850: 824.2 MHz ~ 848.8 MHz GSM1900: 1850.2 MHz ~ 1909.8MHz WCDMA Band V: 826.4 MHz ~ 846.6 MHz WCDMA Band IV : 1712.4 MHz ~ 1752.6 MHz WCDMA Band II: 1852.4 MHz ~ 1907.6 MHz
Rx Frequency	GSM850: 869.2 MHz ~ 893.8 MHz GSM1900: 1930.2 MHz ~ 1989.8 MHz WCDMA Band V: 871.4 MHz ~ 891.6 MHz WCDMA Band IV : 2112.4 MHz ~ 2152.6 MHz WCDMA Band II: 1932.4 MHz ~ 1987.6 MHz
Maximum Output Power to Antenna	GSM850 : 31.40 dBm GSM1900 : 28.21 dBm WCDMA Band V : 21.99 dBm WCDMA Band IV : 22.72 dBm WCDMA Band II : 22.48 dBm
Antenna Type	PIFA Antenna
Type of Modulation	GSM: GMSK GPRS: GMSK EDGE: GMSK / 8PSK WCDMA : QPSK (Uplink) HSDPA : QPSK (Uplink) HSUPA : QPSK (Uplink) HSPA+ : 16QAM (Downlink Only)

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Maximum ERP/EIRP Power, Frequency Tolerance, and Emission Designator

FCC Rule	System	Type of Modulation	Maximum ERP/EIRP (W)	Frequency Tolerance (ppm)	Emission Designator
Part 22	GSM850 GSM	GMSK	0.4027	0.0347 ppm	243KGXW
Part 22	GSM850 EDGE class 8	8PSK	0.0968	0.0096 ppm	243KG7W
Part 22	WCDMA Band V RMC 12.2Kbps	QPSK	0.0574	0.0120 ppm	4M14F9W
Part 24	GSM1900 GSM	GMSK	0.9314	0.0043 ppm	245KGXW
Part 24	GSM1900 EDGE class 8	8PSK	0.3614	0.0069 ppm	247KG7W
Part 24	WCDMA Band II RMC 12.2Kbps	QPSK	0.2989	0.0064 ppm	4M15F9W
Part 27	WCDMA Band IV RMC 12.2Kbps	QPSK	0.2955	0.0035 ppm	4M17F9W

1.7 Testing Location

Test Site	SPORTON INTERNATIONAL (SHENZHEN) INC.	
Test Site Location	1F & 2F,Building A, Morning Business Center, No. 4003 ShiGu Rd., Xili Town, Nanshan District, Shenzhen, Guangdong, P. R. China TEL: +86-755-8637-9589 FAX: +86-755-8637-9595	
Test Site No.	**Sporton Site No.**	
	TH01-SZ	

Test Site	SPORTON INTERNATIONAL (SHENZHEN) INC.	
Test Site Location	No. 3 Building, the third floor of south, Shahe River west, Fengzeyuan warehouse, Nanshan District, Shenzhen, Guangdong, P. R. China TEL: +86-755- 3320-2398	
Test Site No.	**Sporton Site No.**	**FCC/IC Registration No.**
	03CH02-SZ	566869/4086F

Note: The test site complies with ANSI C63.4 2009 requirement.

1.8 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR Part 2, 22(H), 24(E), 27(L)
- ANSI / TIA / EIA-603-C-2004
- FCC KDB 971168 D01 Power Meas. License Digital Systems v02r02
- IC RSS-132 Issue 3
- IC RSS-133 Issue 6
- IC RSS-139 Issue 3
- IC RSS-Gen Issue 4

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

2.1 Test Mode

Antenna port conducted and radiated test items were performed according to KDB 971168 D01 Power Meas. License Digital Systems v02r02 with maximum output power.

Radiated measurements were performed with rotating EUT in different three orthogonal test planes to find the maximum emission.

Radiated emissions were investigated as following frequency range:

1. 30 MHz to 10th harmonic for GSM850 and WCDMA Band V.
2. 30 MHz to 10th harmonic for WCDMA Band IV
3. 30 MHz to 10th harmonic for GSM1900 and WCDMA Band II.

All modes and data rates and positions were investigated.

Test modes are chosen to be reported as the worst case configuration below:

Test Modes		
Band	**Radiated TCs**	**Conducted TCs**
GSM 850	■ GSM Link ■ EDGE class 8 Link	■ GSM Link ■ EDGE class 8 Link
GSM 1900	■ GSM Link ■ EDGE class 8 Link	■ GSM Link ■ EDGE class 8 Link
WCDMA Band V	■ RMC 12.2Kbps Link	■ RMC 12.2Kbps Link
WCDMA Band II	■ RMC 12.2Kbps Link	■ RMC 12.2Kbps Link
WCDMA Band IV	■ RMC 12.2Kbps Link	■ RMC 12.2Kbps Link

Note: The maximum power levels are chosen to test as the worst case configuration as follows:

GSM mode for GMSK modulation,

EDGE multi-slot class 8 mode for 8PSK modulation,

RMC 12.2Kbps mode for WCDMA band V and WCDMA band IV,

RMC 12.2Kbps mode for WCDMA band II, only these modes were used for all tests.

Conducted Power Measurement Results:

For SIM1 Card:

Conducted Power (*Unit: dBm)						
Band	**GSM850**			**GSM1900**		
Channel	**128**	**189**	**251**	**512**	**661**	**810**
Frequency	**824.2**	**836.4**	**848.8**	**1850.2**	**1880.0**	**1909.8**
GSM	31.25	**31.40**	31.28	28.12	**28.21**	28.17
GPRS class 8	31.23	31.32	31.27	28.08	28.20	28.14
GPRS class 10	28.67	28.84	28.70	28.01	28.18	28.13
GPRS class 11	27.15	27.23	27.20	26.15	26.20	26.17
GPRS class 12	26.45	26.57	26.54	25.17	25.21	25.18
EGPRS class 8	25.44	25.37	25.35	23.94	23.95	23.96
EGPRS class 10	24.88	24.82	24.72	23.44	23.45	23.46
EGPRS class 11	24.25	24.26	24.15	22.90	22.92	22.95
EGPRS class 12	23.62	23.65	23.60	22.35	22.36	22.39

Conducted Power (*Unit: dBm)									
Band	**WCDMA Band V**			**WCDMA Band II**			**WCDMA Band IV**		
Channel	**4132**	**4182**	**4233**	**9262**	**9400**	**9538**	**1312**	**1413**	**1513**
Frequency	**826.4**	**836.4**	**846.6**	**1852.4**	**1880**	**1907.6**	**1712.4**	**1732.6**	**1752.6**
AMR 12.2K	21.87	21.98	21.80	22.45	22.35	22.38	22.56	22.58	22.70
RMC 12.2K	21.89	**21.99**	21.82	**22.48**	22.36	22.40	22.58	22.59	**22.72**
HSDPA Subtest-1	20.50	20.70	20.56	21.09	20.98	20.91	20.99	21.26	21.45
HSDPA Subtest-2	20.62	20.77	20.37	21.02	20.90	20.85	20.99	21.17	21.40
HSDPA Subtest-3	20.14	20.28	20.16	20.51	20.40	20.42	20.58	20.68	20.91
HSDPA Subtest-4	20.13	20.29	20.16	20.50	20.03	20.40	20.58	20.68	20.90
HSUPA Subtest-1	20.21	20.70	20.16	20.20	20.17	20.54	21.04	21.21	21.28
HSUPA Subtest-2	19.57	19.37	19.55	19.88	19.78	19.86	19.69	19.99	19.80
HSUPA Subtest-3	19.36	19.58	19.34	19.51	19.50	19.51	19.58	19.91	20.00
HSUPA Subtest-4	19.54	19.59	19.96	20.14	20.05	19.78	19.69	20.00	20.29
HSUPA Subtest-5	20.60	20.70	20.60	21.00	21.00	20.90	21.00	21.20	21.30

For SIM2 Card:

Conducted Power (*Unit: dBm)						
Band	**GSM850**			**GSM1900**		
Channel	**128**	**189**	**251**	**512**	**661**	**810**
Frequency	**824.2**	**836.4**	**848.8**	**1850.2**	**1880.0**	**1909.8**
GSM	31.24	**31.35**	31.27	28.08	**28.20**	28.16
GPRS class 8	31.21	31.31	31.25	28.07	28.18	28.13
GPRS class 10	28.65	28.75	28.66	28.00	28.17	28.12
GPRS class 11	27.14	27.17	27.15	26.14	26.18	26.15
GPRS class 12	26.42	26.53	26.50	25.15	25.17	25.16
EGPRS class 8	25.42	25.35	25.34	23.89	23.91	23.95
EGPRS class 10	24.82	24.80	24.71	23.42	23.45	23.44
EGPRS class 11	24.23	24.21	24.14	22.89	22.90	22.94
EGPRS class 12	23.60	23.64	23.51	22.34	22.35	22.37

Conducted Power (*Unit: dBm)									
Band	**WCDMA Band V**			**WCDMA Band II**			**WCDMA Band IV**		
Channel	**4132**	**4182**	**4233**	**9262**	**9400**	**9538**	**1312**	**1413**	**1513**
Frequency	**826.4**	**836.4**	**846.6**	**1852.4**	**1880**	**1907.6**	**1712.4**	**1732.6**	**1752.6**
AMR 12.2K	21.76	21.87	21.72	22.35	22.15	22.34	22.45	22.49	22.61
RMC 12.2K	21.78	**21.88**	21.73	**22.36**	22.17	22.35	22.47	22.52	**22.62**
HSDPA Subtest-1	20.52	20.61	20.53	21.03	20.95	20.90	21.00	21.25	21.43
HSDPA Subtest-2	20.69	20.66	20.34	20.97	20.88	20.53	21.00	21.21	21.41
HSDPA Subtest-3	20.17	20.17	20.10	20.46	20.39	20.33	20.50	20.72	20.93
HSDPA Subtest-4	20.10	20.28	20.10	20.44	20.37	20.31	20.50	20.72	20.92
HSUPA Subtest-1	20.11	20.65	19.86	20.19	20.17	20.33	20.80	21.16	21.14
HSUPA Subtest-2	19.61	19.19	19.46	19.85	19.70	19.86	19.36	19.85	20.39
HSUPA Subtest-3	19.11	19.19	19.08	19.43	19.90	19.41	19.77	19.95	20.02
HSUPA Subtest-4	19.89	20.19	19.64	19.95	19.90	19.90	19.95	20.52	20.67
HSUPA Subtest-5	20.50	20.70	20.50	21.00	20.90	20.90	21.00	21.20	21.30

2.2 Connection Diagram of Test System



2.3 Support Unit used in test configuration

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU 200	N/A	N/A	Unshielded, 1.8 m
2.	DC Power Supply	TOPWORD	3303DR	N/A	N/A	Unshielded, 1.8 m

2.4 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between RF conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level will be exactly the RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

The following shows an offset computation example with RF cable loss 4.5 dB and a 10dB attenuator.

Example :

Offset(dB) = RF cable loss(dB) + attenuator factor(dB).

= 4.5 + 10 = 14.5 (dB)

3 Test Result

3.1 Conducted Output Power Measurement

3.1.1 Description of the Conducted Output Power Measurement

A system simulator was used to establish communication with the EUT. Its parameters were set to enforce EUT transmitting at the maximum power. The measured power in the radio frequency on the transmitter output terminals shall be reported.

3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedures

1. The transmitter output port was connected to the system simulator.
2. Set EUT at maximum power through system simulator.
3. Select lowest, middle, and highest channels for each band and different modulation.
4. Measure the maximum burst average power for GSM and maximum average power for other modulation signal.

3.1.4 Test Setup



3.1.5 Test Result of Conducted Output Power

Cellular Band									
Modes	GSM850 (GSM)			GSM850 (EDGE class 8)			WCDMA Band V (RMC 12.2Kbps)		
Channel	128 (Low)	189 (Mid)	251 (High)	128 (Low)	189 (Mid)	251 (High)	4132 (Low)	4182 (Mid)	4233 (High)
Frequency (MHz)	824.2	836.4	848.8	824.2	836.4	848.8	826.4	836.4	846.6
Conducted Power (dBm)	31.25	31.40	31.28	25.44	25.37	25.35	21.89	21.99	21.82

PCS Band									
Modes	GSM1900 (GSM)			GSM1900 (EDGE class 8)			WCDMA Band II (RMC 12.2Kbps)		
Channel	512 (Low)	661 (Mid)	810 (High)	512 (Low)	661 (Mid)	810 (High)	9262 (Low)	9400 (Mid)	9538 (High)
Frequency (MHz)	1850.2	1880	1909.8	1850.2	1880	1909.8	1852.4	1880	1907.6
Conducted Power (dBm)	28.12	28.21	28.17	23.94	23.95	23.96	22.48	22.36	22.40

AWS Band			
Modes	WCDMA Band IV (RMC 12.2Kbps)		
Channel	1312(Low)	1413 (Mid)	1513 (High)
Frequency (MHz)	1712.4	1732.6	1752.6
Conducted Power (dBm)	22.58	22.59	22.72

Note: maximum burst average power for GSM, and maximum average power for WCDMA.

3.2 Peak-to-Average Ratio

3.2.1 Description of the PAR Measurement

The peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.2.3 Test Procedures

1. The testing follows FCC KDB 971168 v02r02 Section 5.7.1.
2. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
3. For GSM/EGPRS operating modes:
   a. Set EUT in maximum power output.
   b. Set the RBW = 1MHz, VBW = 3MHz, Peak detector on spectrum analyzer for first trace.
   c. Set the RBW = 1MHz, VBW = 3MHz, RMS detector on spectrum analyzer for second trace.
   d. The wanted burst signal is triggered by spectrum analyzer, and measured respectively the peak level and Mean level without burst-off time, after system simulator has synchronized with the spectrum analyzer.
4. For UMTS operating modes:
   a. Set the CCDF (Complementary Cumulative Distribution Function) option on the spectrum analyzer.
   b. The highest RF powers were measured and recorded the maximum PAPR level associated with a probability of 0.1 %.
5. Record the deviation as Peak to Average Ratio.

3.2.4 Test Setup



3.2.5 Test Result of Peak-to-Average Ratio

Cellular Band									
Modes	GSM850 (GSM)			GSM850 (EDGE class 8)			WCDMA Band V (RMC 12.2Kbps)		
Channel	128 (Low)	189 (Mid)	251 (High)	128 (Low)	189 (Mid)	251 (High)	4132 (Low)	4182 (Mid)	4233 (High)
Frequency (MHz)	824.2	836.4	848.8	824.2	836.4	848.8	826.4	836.4	846.6
Peak-to-Average Ratio (dB)	0.29	0.29	0.29	2.56	2.57	2.75	3.04	2.90	3.01

PCS Band									
Modes	GSM1900 (GSM)			GSM1900 (EDGE class 8)			WCDMA Band II (RMC 12.2Kbps)		
Channel	512 (Low)	661 (Mid)	810 (High)	512 (Low)	661 (Mid)	810 (High)	9262 (Low)	9400 (Mid)	9538 (High)
Frequency (MHz)	1850.2	1880	1909.8	1850.2	1880	1909.8	1852.4	1880	1907.6
Peak-to-Average Ratio (dB)	0.28	0.29	0.28	2.52	2.50	2.53	2.93	2.72	2.49

AWS Band			
Modes	WCDMA Band IV (RMC 12.2Kbps)		
Channel	1312(Low)	1413 (Mid)	1513 (High)
Frequency (MHz)	1712.4	1732.6	1752.6
Peak-to-Average Ratio (dB)	2.96	2.43	2.70

3.2.6 Test Result (Plots) of Peak-to-Average Ratio

Band :	GSM 850	Test Mode :	GSM Link (GMSK)

Peak-to-Average Ratio on Channel 128 (824.2 MHz)



Peak-to-Average Ratio on Channel 189 (836.4 MHz)



Peak-to-Average Ratio on Channel 251 (848.8 MHz)



Band :	GSM 850	Test Mode :	EDGE class 8 Link (8PSK)

Peak-to-Average Ratio on Channel 128 (824.2 MHz)



Peak-to-Average Ratio on Channel 189 (836.4 MHz)



Peak-to-Average Ratio on Channel 251 (848.8 MHz)



Band :	GSM 1900	Test Mode :	GSM Link (GMSK)

Peak-to-Average Ratio on Channel 512 (1850.2 MHz)



Peak-to-Average Ratio on Channel 661 (1880.0 MHz)



Peak-to-Average Ratio on Channel 810 (1909.8 MHz)



Band :	GSM 1900	Test Mode :	EDGE class 8 Link (8PSK)

Peak-to-Average Ratio on Channel 512 (1850.2 MHz)



Peak-to-Average Ratio on Channel 661 (1880.0 MHz)



Peak-to-Average Ratio on Channel 810 (1909.8 MHz)



Band :	WCDMA Band V	Test Mode :	RMC 12.2Kbps Link (QPSK)

Peak-to-Average Ratio on Channel 4132 (826.4 MHz)



Date: 16.JUL.2015 19:15:49

Peak-to-Average Ratio on Channel 4182 (836.4 MHz)



Date: 16.JUL.2015 19:16:22

Peak-to-Average Ratio on Channel 4233 (846.6 MHz)



Band :	WCDMA Band IV	Test Mode :	RMC 12.2Kbps Link (QPSK)

Peak-to-Average Ratio on Channel 1312 (1712.4 MHz)



Date: 22.JUL.2015 09:23:02

Peak-to-Average Ratio on Channel 1413 (1732.6 MHz)

Date: 22.JUL.2015 09:24:11

Peak-to-Average Ratio on Channel 1513 (1752.6 MHz)



Band :	WCDMA Band II	Test Mode :	RMC 12.2Kbps Link (QPSK)

Peak-to-Average Ratio on Channel 9262 (1852.4 MHz)



Date: 16.JUL.2015 17:38:38

Peak-to-Average Ratio on Channel 9400 (1880.0 MHz)



Date: 16.JUL.2015 17:37:43

Peak-to-Average Ratio on Channel 9538 (1907.6 MHz)



3.3 Effective Radiated Power and Effective Isotropic Radiated Power Measurement

3.3.1 Description of the ERP/EIRP Measurement

The substitution method, in ANSI / TIA / EIA-603-C-2004, was used for ERP/EIRP measurement, and the spectrum analyzer configuration follows KDB 971168 D01 Power Meas. License Digital Systems v02r02. The ERP of mobile transmitters must not exceed 7 Watts (Cellular Band) and the EIRP of mobile transmitters are limited to 2 Watts (PCS Band) and 1 Watts (AWS Band).

3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.3.3 Test Procedures

1. The testing follows FCC KDB 971168 v02r02 Section 5.2.1. (for CDMA/WCDMA), Section 5.2.2.2 (for GSM/GPRS/EDGE) and ANSI / TIA-603-C-2004 Section 2.2.17.
2. The EUT was placed on a non-conductive rotating platform 0.8 meters high in a semi-anechoic chamber. The radiated emission at the fundamental frequency was measured at 3 m with a test antenna and a spectrum analyzer with RMS detector per section 5. of KDB 971168 D01.
3. During the measurement, the system simulator parameters were set to force the EUT transmitting at maximum output power. The maximum emission was recorded from analyzer power level (LVL) from the 360 degrees rotation of the turntable and the test antenna raised and lowered over a range from 1 to 4 meters in both horizontally and vertically polarized orientations.
4. Effective Isotropic Radiated Power (EIRP) was measured by substitution method according to TIA/EIA-603-C. The EUT was replaced by the substitution antenna at same location, and then a known power from S.G. was applied into the dipole antenna through a Tx cable, and then recorded the maximum Analyzer reading through raised and lowered the test antenna. The correction factor (in dB) = S.G. - Tx Cable loss + Substitution antenna gain - Analyzer reading. Then the EUT's EIRP was calculated with the correction factor, EIRP = LVL + Correction factor and ERP = EIRP - 2.15. Take the record of the output power at substitution antenna.

	GSM/GPRS/EDGE	WCDMA/HSPA
SPAN	500kHz	10MHz
RBW	10kHz	100kHz
VBW	30kHz	300kHz
Detector	RMS	RMS
Trace	Average	Average
Average Type	Power	Power
Sweep Count	100	100

3.3.4 Test Result of ERP

GSM850 (GSM) Radiated Power ERP					
Channel	Frequency (MHz)	Horizontal		Vertical	
		ERP(dBm)	ERP(W)	ERP(dBm)	ERP(W)
Lowest	824.2	25.43	0.3492	14.46	0.0279
Middle	836.4	26.00	0.3980	15.27	0.0337
Highest	848.8	26.05	0.4027	15.85	0.0384
Limit	ERP < 7W	Result		PASS	

GSM850 (EDGE class 8) Radiated Power ERP					
Channel	Frequency (MHz)	Horizontal		Vertical	
		ERP(dBm)	ERP(W)	ERP(dBm)	ERP(W)
Lowest	824.2	18.83	0.0764	7.54	0.0057
Middle	836.4	19.24	0.0840	8.15	0.0065
Highest	848.8	19.86	0.0968	9.14	0.0082
Limit	ERP < 7W	Result		PASS	

WCDMA Band V (RMC 12.2Kbps) Radiated Power ERP					
Channel	Frequency (MHz)	Horizontal		Vertical	
		ERP(dBm)	ERP(W)	ERP(dBm)	ERP(W)
Lowest	826.4	17.25	0.0530	6.28	0.0042
Middle	836.4	17.38	0.0548	6.80	0.0048
Highest	846.6	17.59	0.0574	7.21	0.0053
Limit	ERP < 7W	Result		PASS	

3.3.5 Test Result of EIRP

GSM1900 (GSM) Radiated Power EIRP					
Channel	Frequency (MHz)	Horizontal		Vertical	
		EIRP(dBm)	EIRP(W)	EIRP(dBm)	EIRP(W)
Lowest	1850.2	29.41	0.8731	29.69	0.9314
Middle	1880.0	29.37	0.8646	29.63	0.9178
Highest	1909.8	28.60	0.7251	28.90	0.7764
Limit	EIRP < 2W	Result		PASS	

GSM1900 (EDGE class 8) Radiated Power EIRP					
Channel	Frequency (MHz)	Horizontal		Vertical	
		EIRP(dBm)	EIRP(W)	EIRP(dBm)	EIRP(W)
Lowest	1850.2	25.24	0.3338	25.58	0.3614
Middle	1880.0	25.30	0.3388	25.44	0.3502
Highest	1909.8	24.71	0.2958	24.90	0.3091
Limit	EIRP < 2W	Result		PASS	

WCDMA Band II (RMC 12.2Kbps) Radiated Power EIRP					
Channel	Frequency (MHz)	Horizontal		Vertical	
		EIRP(dBm)	EIRP(W)	EIRP(dBm)	EIRP(W)
Lowest	1852.4	24.50	0.2820	24.76	0.2989
Middle	1880.0	23.94	0.2480	24.14	0.2592
Highest	1907.6	23.39	0.2181	23.62	0.2299
Limit	EIRP < 2W	Result		PASS	

WCDMA Band IV(RMC 12.2Kbps) Radiated Power EIRP					
Channel	Frequency (MHz)	Horizontal		Vertical	
		EIRP(dBm)	EIRP(W)	EIRP(dBm)	EIRP(W)
Lowest	1712.4	23.29	0.2134	23.32	0.2146
Middle	1732.6	23.81	0.2406	23.96	0.2490
Highest	1752.6	24.60	0.2885	24.71	0.2955
Limit	EIRP < 1W	Result		PASS	

3.4 99% Occupied Bandwidth and 26dB Bandwidth Measurement

3.4.1 Description of 99% Occupied Bandwidth and 26dB Bandwidth Measurement

The 99% occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The emission bandwidth is defined as the width of the signal between two points, located at the 2 sides of the carrier frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.

3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.4.3 Test Procedures

5. The testing follows FCC KDB 971168 v02r02 Section 4.2.
6. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
7. The RF output of the EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
8. The 99% occupied bandwidth were measured, set RBW= 1% of span, VBW= 3*RBW, peak detector, trace maximum hold.
9. The 26dB bandwidth were measured, set RBW= 1% of EBW, VBW= 3*RBW, peak detector, trace maximum hold.

3.4.4 Test Setup



3.4.5 Test Result of Occupied Bandwidth and 26dB Bandwidth

Cellular Band						
Modes	GSM850 (GSM)			GSM850 (EDGE class 8)		
Channel	128 (Low)	189 (Mid)	251 (High)	128 (Low)	189 (Mid)	251 (High)
Frequency (MHz)	824.2	836.4	848.8	824.2	836.4	848.8
99% OBW (kHz)	243.13	243.13	243.13	243.13	234.44	238.78
26dB BW (kHz)	316.90	316.90	316.90	315.50	315.50	315.50

PCS Band						
Modes	GSM1900 (GSM)			GSM1900 (EDGE class 8)		
Channel	512 (Low)	661 (Mid)	810 (High)	512 (Low)	661 (Mid)	810 (High)
Frequency (MHz)	1850.2	1880	1909.8	1850.2	1880	1909.8
99% OBW (kHz)	244.57	244.57	244.57	244.57	246.02	247.47
26dB BW (kHz)	315.50	318.40	315.50	315.50	315.50	315.50

Cellular Band			
Modes	WCDMA Band V (RMC 12.2Kbps)		
Channel	4132 (Low)	4182 (Mid)	4233 (High)
Frequency (MHz)	826.4	836.4	846.6
99% OBW (MHz)	4.14	4.14	4.12
26dB BW (MHz)	4.67	4.67	4.69

AWS Band			
Modes	WCDMA Band IV (RMC 12.2Kbps)		
Channel	1312(Low)	1413 (Mid)	1513 (High)
Frequency (MHz)	1712.4	1732.6	1752.6
99% OBW (MHz)	4.15	4.15	4.17
26dB BW (MHz)	4.70	4.73	4.76

PCS Band			
Modes	**WCDMA Band II (RMC 12.2Kbps)**		
Channel	**9262 (Low)**	**9400 (Mid)**	**9538 (High)**
Frequency (MHz)	**1852.4**	**1880**	**1907.6**
99% OBW (MHz)	4.15	4.15	4.15
26dB BW (MHz)	4.75	4.75	4.76

3.4.6 Test Result (Plots) of Occupied Bandwidth and 26dB Bandwidth

Band :	GSM 850	Test Mode :	GSM Link (GMSK)

99% Occupied Bandwidth Plot on Channel 128 (824.2 MHz)



Date: 15.JUL.2015 22:34:33

26dB Bandwidth Plot on Channel 128 (824.2 MHz)



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	824.268 MHz	25.67 dBm	ndB down	316.9 kHz
T1		1	824.0408 MHz	-0.62 dBm	ndB	26.00 dB
T2		1	824.3577 MHz	-0.43 dBm	Q factor	2600.8

Date: 15.JUL.2015 22:29:19

99% Occupied Bandwidth Plot on Channel 189 (836.4 MHz)



26dB Bandwidth Plot on Channel 189 (836.4 MHz)



99% Occupied Bandwidth Plot on Channel 251 (848.8 MHz)



Date: 15.JUL.2015 22:32:07

26dB Bandwidth Plot on Channel 251 (848.8 MHz)



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	848.7855 MHz	25.36 dBm	ndB down	316.9 kHz
T1		1	848.6408 MHz	-1.23 dBm	ndB	26.00 dB
T2		1	848.9577 MHz	-0.45 dBm	Q factor	2678.1

Date: 15.JUL.2015 22:31:03

Band :	GSM 850	Test Mode :	EDGE class 8 Link (8PSK)

99% Occupied Bandwidth Plot on Channel 128 (824.2 MHz)

Date: 15.JUL.2015 23:37:50

26dB Bandwidth Plot on Channel 128 (824.2 MHz)



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	824.1421 MHz	23.41 dBm	ndB down	315.5 kHz
T1		1	824.0423 MHz	-3.51 dBm	ndB	26.00 dB
T2		1	824.3577 MHz	-3.16 dBm	Q factor	2612.3

Date: 15.JUL.2015 23:39:52

99% Occupied Bandwidth Plot on Channel 189 (836.4 MHz)

Date: 15.JUL.2015 23:36:02

26dB Bandwidth Plot on Channel 189 (836.4 MHz)



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	836.3421 MHz	23.54 dBm	ndB down	315.5 kHz
T1		1	836.2423 MHz	-3.38 dBm	ndB	26.00 dB
T2		1	836.5577 MHz	-3.01 dBm	Q factor	2651.0

Date: 15.JUL.2015 23:42:06

99% Occupied Bandwidth Plot on Channel 251 (848.8 MHz)

Date: 15.JUL.2015 23:34:32

26dB Bandwidth Plot on Channel 251 (848.8 MHz)



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	848.7421 MHz	23.58 dBm	ndB down	315.5 kHz
T1		1	848.6423 MHz	-3.32 dBm	ndB	26.00 dB
T2		1	848.9577 MHz	-2.93 dBm	Q factor	2690.3

Date: 15.JUL.2015 23:44:50

Band :	GSM 1900	Test Mode :	GSM Link (GMSK)

99% Occupied Bandwidth Plot on Channel 512 (1850.2 MHz)



Date: 16.JUL.2015 01:31:45

26dB Bandwidth Plot on Channel 512 (1850.2 MHz)



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	1.8501826 GHz	22.56 dBm	ndB down	315.5 kHz
T1		1	1.8500423 GHz	-3.27 dBm	ndB	26.00 dB
T2		1	1.8503577 GHz	-3.11 dBm	Q factor	5864.6

Date: 16.JUL.2015 01:23:25

99% Occupied Bandwidth Plot on Channel 661 (1880.0 MHz)



26dB Bandwidth Plot on Channel 661 (1880.0 MHz)



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	1.8799841 GHz	22.33 dBm	ndB down	318.4 kHz
T1		1	1.8798408 GHz	-3.79 dBm	ndB	26.00 dB
T2		1	1.8801592 GHz	-4.03 dBm	Q factor	5904.9

99% Occupied Bandwidth Plot on Channel 810 (1909.8 MHz)



26dB Bandwidth Plot on Channel 810 (1909.8 MHz)



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	1.9097928 GHz	23.05 dBm	ndB down	315.5 kHz
T1		1	1.9096423 GHz	-2.48 dBm	ndB	26.00 dB
T2		1	1.9099577 GHz	-2.31 dBm	Q factor	6053.5

Band :	GSM 1900	Test Mode :	EDGE class 8 Link (8PSK)

99% Occupied Bandwidth Plot on Channel 512 (1850.2 MHz)



26dB Bandwidth Plot on Channel 512 (1850.2 MHz)



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	1.8501421 GHz	20.22 dBm	ndB down	315.5 kHz
T1		1	1.8500423 GHz	-6.21 dBm	ndB	26.00 dB
T2		1	1.8503577 GHz	-5.77 dBm	Q factor	5864.4

99% Occupied Bandwidth Plot on Channel 661 (1880.0 MHz)



26dB Bandwidth Plot on Channel 661 (1880.0 MHz)



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	1.8799421 GHz	20.11 dBm	ndB down	315.5 kHz
T1		1	1.8798423 GHz	-6.44 dBm	ndB	26.00 dB
T2		1	1.8801577 GHz	-6.04 dBm	Q factor	5958.9

99% Occupied Bandwidth Plot on Channel 810 (1909.8 MHz)



26dB Bandwidth Plot on Channel 810 (1909.8 MHz)



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	1.9097421 GHz	20.04 dBm	ndB down	315.5 kHz
T1		1	1.9096423 GHz	-6.57 dBm	ndB	26.00 dB
T2		1	1.9099577 GHz	-6.20 dBm	Q factor	6053.4

Band :	WCDMA Band V	Test Mode :	RMC 12.2Kbps Link (QPSK)

99% Occupied Bandwidth Plot on Channel 4132 (826.4 MHz)



Date: 16.JUL.2015 19:11:15

26dB Bandwidth Plot on Channel 4132 (826.4 MHz)



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	826.993 MHz	18.70 dBm	ndB down	4.674 MHz
T1		1	824.07 MHz	-6.72 dBm	ndB	26.00 dB
T2		1	828.744 MHz	-7.62 dBm	Q factor	176.9

Date: 7.AUG.2015 05:33:34

99% Occupied Bandwidth Plot on Channel 4182 (836.4 MHz)



Date: 16.JUL.2015 19:10:38

26dB Bandwidth Plot on Channel 4182 (836.4 MHz)



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	835.517 MHz	19.04 dBm	ndB down	4.674 MHz
T1		1	834.056 MHz	-6.66 dBm	ndB	26.00 dB
T2		1	838.73 MHz	-6.53 dBm	Q factor	178.7

Date: 7.AUG.2015 05:32:46

99% Occupied Bandwidth Plot on Channel 4233 (846.6 MHz)



Date: 16.JUL.2015 19:09:26

26dB Bandwidth Plot on Channel 4233 (846.6 MHz)



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	845.732 MHz	18.73 dBm	ndB down	4.689 MHz
T1		1	844.256 MHz	-7.56 dBm	ndB	26.00 dB
T2		1	848.944 MHz	-8.40 dBm	Q factor	180.4

Date: 7.AUG.2015 05:32:06

Band :	WCDMA Band IV	Test Mode :	RMC 12.2Kbps Link (QPSK)

99% Occupied Bandwidth Plot on Channel 1312 (1712.4 MHz)



26dB Bandwidth Plot on Channel 1312 (1712.4 MHz)



99% Occupied Bandwidth Plot on Channel 1413 (1732.6 MHz)

Date: 22.JUL.2015 09:21:42

26dB Bandwidth Plot on Channel 1413 (1732.6 MHz)



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	1.7316449 GHz	18.23 dBm	ndB down	4.732 MHz
T1		1	1.730241 GHz	-7.41 dBm	ndB	26.00 dB
T2		1	1.734973 GHz	-8.46 dBm	Q factor	365.9

Date: 22.JUL.2015 09:20:04

99% Occupied Bandwidth Plot on Channel 1513 (1752.6 MHz)



Date: 22.JUL.2015 09:21:04

26dB Bandwidth Plot on Channel 1513 (1752.6 MHz)



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	1.7516593 GHz	18.11 dBm	ndB down	4.761 MHz
T1		1	1.750227 GHz	-7.81 dBm	ndB	26.00 dB
T2		1	1.754988 GHz	-8.53 dBm	Q factor	367.9

Date: 22.JUL.2015 09:20:33

Band :	WCDMA Band II	Test Mode :	RMC 12.2Kbps Link (QPSK)

99% Occupied Bandwidth Plot on Channel 9262 (1852.4 MHz)



Date: 16.JUL.2015 17:27:54

26dB Bandwidth Plot on Channel 9262 (1852.4 MHz)



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	1.851517 GHz	18.24 dBm	ndB down	4.747 MHz
T1		1	1.850027 GHz	-8.53 dBm	ndB	26.00 dB
T2		1	1.854773 GHz	-7.75 dBm	Q factor	390.1

Date: 16.JUL.2015 17:32:34

99% Occupied Bandwidth Plot on Channel 9400 (1880.0 MHz)



26dB Bandwidth Plot on Channel 9400 (1880.0 MHz)



99% Occupied Bandwidth Plot on Channel 9538 (1907.6 MHz)



26dB Bandwidth Plot on Channel 9538 (1907.6 MHz)



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	1.906717 GHz	18.33 dBm	ndB down	4.761 MHz
T1		1	1.905227 GHz	-7.12 dBm	ndB	26.00 dB
T2		1	1.909988 GHz	-8.15 dBm	Q factor	400.5

3.5 Band Edge Measurement

3.5.1 Description of Band Edge Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least 43 + 10 log (P) dB.

3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.5.3 Test Procedures

1. The testing follows FCC KDB 971168 v02r02 Section 6.0.
2. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by an RF cable and attenuator. The path loss was compensated to the results for each measurement.
4. The band edges of low and high channels for the highest RF powers were measured.
5. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
6. The limit line is derived from 43 + 10log(P) dB below the transmitter power P(Watts)
   = P(W) - [43 + 10log(P)] (dB)
   = [30 + 10log(P)] (dBm) - [43 + 10log(P)] (dB)
   = -13dBm.

3.5.4 Test Setup

<Conducted Band Edge >



3.5.5 Test Result (Plots) of Conducted Band Edge

Band :	GSM850	Test Mode :	GSM Link (GMSK)

Lower Band Edge Plot on Channel 128 (824.2 MHz)



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
820.000 MHz	823.000 MHz	100.000 kHz	822.97453 MHz	-45.90 dBm	-32.90 dB
823.000 MHz	824.000 MHz	3.000 kHz	823.99650 MHz	-16.54 dBm	-3.54 dB
824.000 MHz	824.500 MHz	10.000 kHz	824.19156 MHz	21.64 dBm	-13.36 dB

Date: 15.JUL.2015 22:39:57

Higher Band Edge Plot on Channel 251 (848.8 MHz)



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
848.500 MHz	849.000 MHz	10.000 kHz	848.81593 MHz	22.63 dBm	-12.37 dB
849.000 MHz	850.000 MHz	3.000 kHz	849.02148 MHz	-17.92 dBm	-4.92 dB
850.000 MHz	855.000 MHz	100.000 kHz	851.13137 MHz	-44.85 dBm	-31.85 dB

Date: 15.JUL.2015 22:44:10

Band :	GSM850	Test Mode :	EDGE class 8 Link (8PSK)

Lower Band Edge Plot on Channel 128 (824.2 MHz)



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
820.000 MHz	823.000 MHz	100.000 kHz	822.96553 MHz	-46.50 dBm	-33.50 dB
823.000 MHz	824.000 MHz	3.000 kHz	823.98551 MHz	-22.72 dBm	-9.72 dB
824.000 MHz	824.500 MHz	10.000 kHz	824.14560 MHz	20.08 dBm	-14.92 dB

Date: 15.JUL.2015 23:32:04

Higher Band Edge Plot on Channel 251 (848.8 MHz)



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
848.500 MHz	849.000 MHz	10.000 kHz	848.74201 MHz	20.21 dBm	-14.79 dB
849.000 MHz	850.000 MHz	3.000 kHz	849.01149 MHz	-22.24 dBm	-9.24 dB
850.000 MHz	855.000 MHz	100.000 kHz	851.18631 MHz	-44.37 dBm	-31.37 dB

Date: 15.JUL.2015 23:28:04

Band :	GSM1900	Test Mode :	GSM Link (GMSK)

Lower Band Edge Plot on Channel 512 (1850.2 MHz)



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
1.845 GHz	1.849 GHz	1.000 MHz	1.84895 GHz	-30.55 dBm	-17.55 dB
1.849 GHz	1.850 GHz	3.000 kHz	1.85000 GHz	-19.87 dBm	-6.87 dB
1.850 GHz	1.851 GHz	10.000 kHz	1.85027 GHz	15.95 dBm	-19.05 dB

Date: 16.JUL.2015 01:22:14

Higher Band Edge Plot on Channel 810 (1909.8 MHz)



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
1.909 GHz	1.910 GHz	10.000 kHz	1.90982 GHz	15.61 dBm	-19.39 dB
1.910 GHz	1.911 GHz	3.000 kHz	1.91002 GHz	-20.12 dBm	-7.12 dB
1.911 GHz	1.915 GHz	1.000 MHz	1.91101 GHz	-32.00 dBm	-19.00 dB

Date: 16.JUL.2015 01:16:07

Band :	GSM1900	Test Mode :	EDGE class 8 Link (8PSK)

Lower Band Edge Plot on Channel 512 (1850.2 MHz)



Date: 16.JUL.2015 00:53:29

Higher Band Edge Plot on Channel 810 (1909.8 MHz)



Date: 16.JUL.2015 01:00:00

Band :	WCDMA Band V	Test Mode :	RMC 12.2Kbps Link (QPSK)

Lower Band Edge Plot on Channel 4132 (826.4 MHz)



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
819.000 MHz	823.000 MHz	100.000 kHz	822.84216 MHz	-34.11 dBm	-21.11 dB
823.000 MHz	824.000 MHz	50.000 kHz	823.82867 MHz	-28.02 dBm	-15.02 dB
824.000 MHz	829.000 MHz	100.000 kHz	827.82867 MHz	7.57 dBm	-22.43 dB

Date: 16.JUL.2015 19:13:54

Higher Band Edge Plot on Channel 4233 (846.6 MHz)



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
844.000 MHz	849.000 MHz	100.000 kHz	845.71079 MHz	7.55 dBm	-22.45 dB
849.000 MHz	850.000 MHz	50.000 kHz	849.00050 MHz	-28.59 dBm	-15.59 dB
850.000 MHz	855.000 MHz	100.000 kHz	850.15734 MHz	-34.36 dBm	-21.36 dB

Date: 16.JUL.2015 19:15:02

Band :	WCDMA Band IV	Test Mode :	RMC 12.2Kbps Link (QPSK)

Lower Band Edge Plot on Channel 1312 (1712.4 MHz)



Higher Band Edge Plot on Channel 1513 (1752.6 MHz)



Band :	WCDMA Band II	Test Mode :	RMC 12.2Kbps Link (QPSK)

Lower Band Edge Plot on Channel 9262 (1852.4 MHz)



Date: 16.JUL.2015 17:33:38

Higher Band Edge Plot on Channel 9538 (1907.6 MHz)



Date: 16.JUL.2015 17:35:03

3.6 Conducted Spurious Emission Measurement

3.6.1 Description of Conducted Spurious Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least 43 + 10 log (P) dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10th harmonic.

3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.6.3 Test Procedures

1. The testing follows FCC KDB 971168 v02r02 Section 6.0.
2. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by an RF cable and attenuator. The path loss was compensated to the results for each measurement.
4. The middle channel for the highest RF power within the transmitting frequency was measured.
5. The conducted spurious emission for the whole frequency range was taken.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
7. The limit line is derived from 43 + 10log(P) dB below the transmitter power P(Watts)
   = P(W) - [43 + 10log(P)] (dB)
   = [30 + 10log(P)] (dBm) - [43 + 10log(P)] (dB)
   = -13dBm.

3.6.4 Test Setup



3.6.5 Test Result (Plots) of Conducted Spurious Emission

Band :	GSM850	Channel :	CH128
Test Mode :	GSM Link (GMSK)	Frequency :	824.2 MHz

Conducted Spurious Emission Plot between 30MHz ~ 9GHz



Band :	GSM850	Channel :	CH189
Test Mode :	GSM Link (GMSK)	Frequency :	836.4 MHz

Conducted Spurious Emission Plot between 30MHz ~ 9GHz



Date: 15.JUL.2015 22:46:07

Band :	GSM850	Channel :	CH 251
Test Mode :	GSM Link (GMSK)	Frequency :	848.8 MHz

Conducted Spurious Emission Plot between 30MHz ~ 9GHz



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	820.000 MHz	1.000 MHz	687.14893 MHz	-67.94 dBm	-54.94 dB
855.000 MHz	1.000 GHz	1.000 MHz	911.27622 MHz	-68.39 dBm	-55.39 dB
1.000 GHz	3.000 GHz	1.000 MHz	2.54636 GHz	-47.22 dBm	-34.22 dB
3.000 GHz	7.000 GHz	1.000 MHz	3.39570 GHz	-55.09 dBm	-42.09 dB
7.000 GHz	9.000 GHz	1.000 MHz	7.63959 GHz	-61.62 dBm	-48.62 dB

Band :	GSM850	Channel :	CH128
Test Mode :	EDGE class 8 Link (8PSK)	Frequency :	824.2 MHz

Conducted Spurious Emission Plot between 30MHz ~ 9GHz



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	820.000 MHz	1.000 MHz	779.92754 MHz	-67.73 dBm	-54.73 dB
855.000 MHz	1.000 GHz	1.000 MHz	921.41608 MHz	-68.26 dBm	-55.26 dB
1.000 GHz	3.000 GHz	1.000 MHz	2.47288 GHz	-48.31 dBm	-35.31 dB
3.000 GHz	7.000 GHz	1.000 MHz	3.29671 GHz	-58.46 dBm	-45.46 dB
7.000 GHz	9.000 GHz	1.000 MHz	8.32792 GHz	-63.70 dBm	-50.70 dB

Band :	GSM850	Channel :	CH189
Test Mode :	EDGE class 8 Link (8PSK)	Frequency :	836.4 MHz

Conducted Spurious Emission Plot between 30MHz ~ 9GHz



Date: 15.JUL.2015 22:48:16

Band :	GSM850	Channel :	CH251
Test Mode :	EDGE class 8 Link (8PSK)	Frequency :	848.8 MHz

Conducted Spurious Emission Plot between 30MHz ~ 9GHz



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	820.000 MHz	1.000 MHz	643.32584 MHz	-68.04 dBm	-55.04 dB
855.000 MHz	1.000 GHz	1.000 MHz	901.28122 MHz	-57.91 dBm	-44.91 dB
1.000 GHz	3.000 GHz	1.000 MHz	2.54686 GHz	-54.47 dBm	-41.47 dB
3.000 GHz	7.000 GHz	1.000 MHz	3.39570 GHz	-57.15 dBm	-44.15 dB
7.000 GHz	9.000 GHz	1.000 MHz	8.36141 GHz	-63.20 dBm	-50.20 dB

Band :	GSM1900	Channel :	CH512
Test Mode :	GSM Link (GMSK)	Frequency :	1850.2 MHz

Conducted Spurious Emission Plot between 30MHz ~ 19.1GHz



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	1.000 GHz	1.000 MHz	833.00100 MHz	-67.29 dBm	-54.29 dB
1.000 GHz	1.845 GHz	1.000 MHz	1.69108 GHz	-67.22 dBm	-54.22 dB
1.915 GHz	3.000 GHz	1.000 MHz	2.48245 GHz	-64.22 dBm	-51.22 dB
3.000 GHz	7.000 GHz	1.000 MHz	5.55093 GHz	-41.61 dBm	-28.61 dB
7.000 GHz	13.600 GHz	1.000 MHz	7.40139 GHz	-43.53 dBm	-30.53 dB
13.600 GHz	19.100 GHz	1.000 MHz	15.91704 GHz	-57.56 dBm	-44.56 dB

Band :	GSM1900	Channel :	CH661
Test Mode :	GSM Link (GMSK)	Frequency :	1880.0 MHz

Conducted Spurious Emission Plot between 30MHz ~ 19.1GHz



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	1.000 GHz	1.000 MHz	881.47676 MHz	-67.32 dBm	-54.32 dB
1.000 GHz	1.845 GHz	1.000 MHz	1.04793 GHz	-66.82 dBm	-53.82 dB
1.915 GHz	3.000 GHz	1.000 MHz	2.42279 GHz	-62.83 dBm	-49.83 dB
3.000 GHz	7.000 GHz	1.000 MHz	5.64042 GHz	-38.93 dBm	-25.93 dB
7.000 GHz	13.600 GHz	1.000 MHz	7.52018 GHz	-43.97 dBm	-30.97 dB
13.600 GHz	19.100 GHz	1.000 MHz	18.29832 GHz	-56.95 dBm	-43.95 dB

Band :	GSM1900	Channel :	CH810
Test Mode :	GSM Link (GMSK)	Frequency :	1909.8 MHz

Conducted Spurious Emission Plot between 30MHz ~ 19.1GHz



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	1.000 GHz	1.000 MHz	964.37031 MHz	-67.59 dBm	-54.59 dB
1.000 GHz	1.845 GHz	1.000 MHz	1.54539 GHz	-66.90 dBm	-53.90 dB
1.915 GHz	3.000 GHz	1.000 MHz	2.37868 GHz	-64.15 dBm	-51.15 dB
3.000 GHz	7.000 GHz	1.000 MHz	3.82015 GHz	-35.17 dBm	-22.17 dB
7.000 GHz	13.600 GHz	1.000 MHz	7.63945 GHz	-46.79 dBm	-33.79 dB
13.600 GHz	19.100 GHz	1.000 MHz	18.93377 GHz	-56.83 dBm	-43.83 dB

Band :	GSM1900	Channel :	CH512
Test Mode :	EDGE class 8 Link (8PSK)	Frequency :	1850.2 MHz

Conducted Spurious Emission Plot between 30MHz ~ 19.1GHz



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	1.000 GHz	1.000 MHz	994.42529 MHz	-67.76 dBm	-54.76 dB
1.000 GHz	1.845 GHz	1.000 MHz	1.79960 GHz	-65.87 dBm	-52.87 dB
1.915 GHz	3.000 GHz	1.000 MHz	2.27781 GHz	-64.31 dBm	-51.31 dB
3.000 GHz	7.000 GHz	1.000 MHz	5.55093 GHz	-40.76 dBm	-27.76 dB
7.000 GHz	13.600 GHz	1.000 MHz	7.40092 GHz	-43.32 dBm	-30.32 dB
13.600 GHz	19.100 GHz	1.000 MHz	18.30832 GHz	-56.95 dBm	-43.95 dB

Band :	GSM1900	Channel :	CH661
Test Mode :	EDGE class 8 Link (8PSK)	Frequency :	1880.0 MHz

Conducted Spurious Emission Plot between 30MHz ~ 19.1GHz



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	1.000 GHz	1.000 MHz	949.34283 MHz	-67.06 dBm	-54.06 dB
1.000 GHz	1.845 GHz	1.000 MHz	1.55299 GHz	-67.51 dBm	-54.51 dB
1.915 GHz	3.000 GHz	1.000 MHz	2.23045 GHz	-63.93 dBm	-50.93 dB
3.000 GHz	7.000 GHz	1.000 MHz	5.64042 GHz	-39.03 dBm	-26.03 dB
7.000 GHz	13.600 GHz	1.000 MHz	7.52018 GHz	-43.19 dBm	-30.19 dB
13.600 GHz	19.100 GHz	1.000 MHz	18.30432 GHz	-57.14 dBm	-44.14 dB

Band :	GSM1900	Channel :	CH810
Test Mode :	EDGE class 8 Link (8PSK)	Frequency :	1909.8 MHz

Conducted Spurious Emission Plot between 30MHz ~ 19.1GHz



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	1.000 GHz	1.000 MHz	978.42829 MHz	-67.16 dBm	-54.16 dB
1.000 GHz	1.845 GHz	1.000 MHz	1.79200 GHz	-66.68 dBm	-53.68 dB
1.915 GHz	3.000 GHz	1.000 MHz	2.29444 GHz	-62.69 dBm	-49.69 dB
3.000 GHz	7.000 GHz	1.000 MHz	3.81965 GHz	-35.26 dBm	-22.26 dB
7.000 GHz	13.600 GHz	1.000 MHz	7.63945 GHz	-46.88 dBm	-33.88 dB
13.600 GHz	19.100 GHz	1.000 MHz	18.29282 GHz	-56.81 dBm	-43.81 dB

Band :	WCDMA Band V	Channel :	CH4132
Test Mode :	RMC 12.2Kbps Link (QPSK)	Frequency :	826.4 MHz

Conducted Spurious Emission Plot between 30MHz ~ 9GHz



Band :	WCDMA Band V	Channel :	CH4182
Test Mode :	RMC 12.2Kbps Link (QPSK)	Frequency :	836.4 MHz

Conducted Spurious Emission Plot between 30MHz ~ 9GHz



Date: 16.JUL.2015 19:19:02

Band :	WCDMA Band V	Channel :	CH4233
Test Mode :	RMC 12.2Kbps Link (QPSK)	Frequency :	846.6 MHz

Conducted Spurious Emission Plot between 30MHz ~ 9GHz



Band :	WCDMA Band IV	Channel :	CH1312
Test Mode :	RMC 12.2Kbps Link (QPSK)	Frequency :	1712.4 MHz

Conducted Spurious Emission Plot between 30MHz ~ 18GHz



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	1.000 GHz	1.000 MHz	938.19340 MHz	-67.85 dBm	-54.85 dB
1.000 GHz	1.705 GHz	1.000 MHz	1.42543 GHz	-67.13 dBm	-54.13 dB
1.760 GHz	3.000 GHz	1.000 MHz	2.83823 GHz	-65.60 dBm	-52.60 dB
3.000 GHz	7.000 GHz	1.000 MHz	3.42320 GHz	-50.49 dBm	-37.49 dB
7.000 GHz	13.600 GHz	1.000 MHz	12.21669 GHz	-60.13 dBm	-47.13 dB
13.600 GHz	18.000 GHz	1.000 MHz	16.87250 GHz	-57.55 dBm	-44.55 dB

Band :	WCDMA Band IV	Channel :	CH1413
Test Mode :	RMC 12.2Kbps Link (QPSK)	Frequency :	1732.6 MHz

Conducted Spurious Emission Plot between 30MHz ~ 18GHz



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	1.000 GHz	1.000 MHz	896.01949 MHz	-67.47 dBm	-54.47 dB
1.000 GHz	1.705 GHz	1.000 MHz	1.52232 GHz	-66.77 dBm	-53.77 dB
1.760 GHz	3.000 GHz	1.000 MHz	2.77873 GHz	-65.28 dBm	-52.28 dB
3.000 GHz	7.000 GHz	1.000 MHz	3.46369 GHz	-53.09 dBm	-40.09 dB
7.000 GHz	13.600 GHz	1.000 MHz	11.18811 GHz	-60.68 dBm	-47.68 dB
13.600 GHz	18.000 GHz	1.000 MHz	16.93605 GHz	-57.55 dBm	-44.55 dB

Band :	WCDMA Band IV	Channel :	CH1513
Test Mode :	RMC 12.2Kbps Link (QPSK)	Frequency :	1752.6 MHz

Conducted Spurious Emission Plot between 30MHz ~ 18GHz



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	1.000 GHz	1.000 MHz	950.31234 MHz	-67.64 dBm	-54.64 dB
1.000 GHz	1.705 GHz	1.000 MHz	1.53571 GHz	-67.06 dBm	-54.06 dB
1.760 GHz	3.000 GHz	1.000 MHz	2.82501 GHz	-64.89 dBm	-51.89 dB
3.000 GHz	7.000 GHz	1.000 MHz	3.50769 GHz	-52.85 dBm	-39.85 dB
7.000 GHz	13.600 GHz	1.000 MHz	10.57671 GHz	-60.36 dBm	-47.36 dB
13.600 GHz	18.000 GHz	1.000 MHz	16.56600 GHz	-57.99 dBm	-44.99 dB

Band :	WCDMA Band II	Channel :	CH9262
Test Mode :	RMC 12.2Kbps Link (QPSK)	Frequency :	1852.4MHz

Conducted Spurious Emission Plot between 30MHz ~ 19.1GHz



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	1.000 GHz	1.000 MHz	801.97651 MHz	-67.69 dBm	-54.69 dB
1.000 GHz	1.845 GHz	1.000 MHz	1.78187 GHz	-66.89 dBm	-53.89 dB
1.915 GHz	3.000 GHz	1.000 MHz	2.63430 GHz	-65.03 dBm	-52.03 dB
3.000 GHz	7.000 GHz	1.000 MHz	5.55543 GHz	-43.41 dBm	-30.41 dB
7.000 GHz	13.600 GHz	1.000 MHz	7.40988 GHz	-60.49 dBm	-47.49 dB
13.600 GHz	19.100 GHz	1.000 MHz	18.92677 GHz	-57.15 dBm	-44.15 dB

Band :	WCDMA Band II	Channel :	CH9400
Test Mode :	RMC 12.2Kbps Link (QPSK)	Frequency :	1880.0 MHz

Conducted Spurious Emission Plot between 30MHz ~ 19.1GHz



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	1.000 GHz	1.000 MHz	797.61369 MHz	-67.77 dBm	-54.77 dB
1.000 GHz	1.845 GHz	1.000 MHz	1.31904 GHz	-66.84 dBm	-53.84 dB
1.915 GHz	3.000 GHz	1.000 MHz	2.09198 GHz	-65.53 dBm	-52.53 dB
3.000 GHz	7.000 GHz	1.000 MHz	5.64392 GHz	-43.38 dBm	-30.38 dB
7.000 GHz	13.600 GHz	1.000 MHz	7.52018 GHz	-58.64 dBm	-45.64 dB
13.600 GHz	19.100 GHz	1.000 MHz	18.31082 GHz	-57.41 dBm	-44.41 dB

Band :	WCDMA Band II	Channel :	CH9538
Test Mode :	RMC 12.2Kbps Link (QPSK)	Frequency :	1907.6 MHz

Conducted Spurious Emission Plot between 30MHz ~ 19.1GHz



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	1.000 GHz	1.000 MHz	927.52874 MHz	-66.94 dBm	-53.94 dB
1.000 GHz	1.845 GHz	1.000 MHz	1.65349 GHz	-66.79 dBm	-53.79 dB
1.915 GHz	3.000 GHz	1.000 MHz	1.91554 GHz	-56.61 dBm	-43.61 dB
3.000 GHz	7.000 GHz	1.000 MHz	5.72591 GHz	-44.39 dBm	-31.39 dB
7.000 GHz	13.600 GHz	1.000 MHz	7.63049 GHz	-60.00 dBm	-47.00 dB
13.600 GHz	19.100 GHz	1.000 MHz	16.21501 GHz	-56.65 dBm	-43.65 dB

3.7 Field Strength of Spurious Radiation Measurement

3.7.1 Description of Field Strength of Spurious Radiated Measurement

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least 43 + 10 log (P) dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

3.7.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.7.3 Test Procedures

1. The testing follows FCC KDB 971168 v02r02 Section 5.8 and ANSI / TIA-603-C-2004 Section 2.2.12.
2. The EUT was placed on a rotatable wooden table 0.8 meters above the ground.
3. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
4. The table was rotated 360 degrees to determine the position of the highest spurious emission.
5. The height of the receiving antenna is varied between one meter and four meters to search for the maximum spurious emission for both horizontal and vertical polarizations.
6. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking record of maximum spurious emission.
7. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
8. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
9. Taking the record of output power at antenna port.
10. Repeat step 7 to step 8 for another polarization.
11. EIRP (dBm) = S.G. Power – Tx Cable Loss + Tx Antenna Gain
12. ERP (dBm) = EIRP - 2.15
13. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
14. The limit line is derived from 43 + 10log(P) dB below the transmitter power P(Watts)

    = P(W) - [43 + 10log(P)] (dB)

    = [30 + 10log(P)] (dBm) - [43 + 10log(P)] (dB)

    = -13dBm.

3.7.4 Test Setup

For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



3.7.5 Test Result of Field Strength of Spurious Radiated

Band :	GSM850 for CH128	**Temperature :**	23~25°C
Test Mode :	GSM Link (GMSK)	**Relative Humidity :**	48~52%
Test Engineer :	Sam Li	**Polarization :**	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		

Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1648.4	-50.29	-13	-37.29	-53.52	-54.11	0.53	6.50	H	Pass
2472.6	-51.74	-13	-38.74	-57.13	-54.61	0.68	5.70	H	Pass
3296.8	-54.58	-13	-41.58	-64.60	-59.62	0.81	8.00	H	Pass

Band :	GSM850 for CH128	**Temperature :**	23~25°C
Test Mode :	GSM Link (GMSK)	**Relative Humidity :**	48~52%
Test Engineer :	Sam Li	**Polarization :**	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		

Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1648.4	-48.22	-13	-35.22	-52.91	-52.04	0.53	6.50	V	Pass
2472.6	-51.17	-13	-38.17	-55.95	-54.04	0.68	5.70	V	Pass
3296.8	-56.79	-13	-43.79	-65.80	-61.83	0.81	8.00	V	Pass

Band :	GSM850 for CH189	**Temperature :**	23~25°C
Test Mode :	GSM Link (GMSK)	**Relative Humidity :**	48~52%
Test Engineer :	Sam Li	**Polarization :**	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		

Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1672	-51.42	-13	-38.42	-54.52	-55.24	0.53	6.50	H	Pass
2510	-51.69	-13	-38.69	-57.08	-54.56	0.68	5.70	H	Pass
3346	-54.56	-13	-41.56	-64.58	-59.60	0.81	8.00	H	Pass

Band :	GSM850 for CH189	**Temperature :**	23~25°C
Test Mode :	GSM Link (GMSK)	**Relative Humidity :**	48~52%
Test Engineer :	Sam Li	**Polarization :**	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		

Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1672	-49.89	-13	-36.89	-54.17	-53.71	0.53	6.50	V	Pass
2510	-51.01	-13	-38.01	-55.81	-53.88	0.68	5.70	V	Pass
3346	-55.67	-13	-42.67	-64.68	-60.71	0.81	8.00	V	Pass

Band :	GSM850 for CH251	**Temperature :**	23~25°C
Test Mode :	GSM Link (GMSK)	**Relative Humidity :**	48~52%
Test Engineer :	Sam Li	**Polarization :**	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		

Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1697.6	-53.05	-13	-40.05	-55.71	-56.87	0.53	6.50	H	Pass
2546.4	-49.77	-13	-36.77	-55.31	-52.64	0.68	5.70	H	Pass
3395.2	-55.07	-13	-42.07	-65.09	-60.11	0.81	8.00	H	Pass

Band :	GSM850 for CH251	**Temperature :**	23~25°C
Test Mode :	GSM Link (GMSK)	**Relative Humidity :**	48~52%
Test Engineer :	Sam Li	**Polarization :**	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		

Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1697.6	-52.32	-13	-39.32	-55.84	-56.14	0.53	6.50	V	Pass
2546.4	-49.55	-13	-36.55	-54.74	-52.42	0.68	5.70	V	Pass
3395.2	-56.40	-13	-43.40	-65.41	-61.44	0.81	8.00	V	Pass

Band :	GSM850 for CH128	**Temperature :**	23~25°C
Test Mode :	EDGE class 8 Link (8PSK)	**Relative Humidity :**	48~52%
Test Engineer :	Sam Li	**Polarization :**	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		

Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1648.4	-51.12	-13	-38.12	-54.23	-54.94	0.53	6.50	H	Pass
2472.6	-54.48	-13	-41.48	-59.90	-57.35	0.68	5.70	H	Pass
3296.8	-55.87	-13	-42.87	-65.89	-60.91	0.81	8.00	H	Pass

Band :	GSM850 for CH128	**Temperature :**	23~25°C
Test Mode :	EDGE class 8 Link (8PSK)	**Relative Humidity :**	48~52%
Test Engineer :	Sam Li	**Polarization :**	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		

Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1648.4	-52.76	-13	-39.76	-56.18	-56.58	0.53	6.50	V	Pass
2472.6	-51.97	-13	-38.97	-56.62	-54.84	0.68	5.70	V	Pass
3296.8	-56.97	-13	-43.97	-65.98	-62.01	0.81	8.00	V	Pass

Band :	GSM850 for CH189	**Temperature :**	23~25°C
Test Mode :	EDGE class 8 Link (8PSK)	**Relative Humidity :**	48~52%
Test Engineer :	Sam Li	**Polarization :**	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		

Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1672	-56.49	-13	-43.49	-59.04	-60.31	0.53	6.50	H	Pass
2510	-51.41	-13	-38.41	-56.76	-54.28	0.68	5.70	H	Pass
3346	-55.02	-13	-42.02	-65.04	-60.06	0.81	8.00	H	Pass

Band :	GSM850 for CH189	**Temperature :**	23~25°C
Test Mode :	EDGE class 8 Link (8PSK)	**Relative Humidity :**	48~52%
Test Engineer :	Sam Li	**Polarization :**	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		

Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1672	-56.57	-13	-43.57	-59.48	-60.39	0.53	6.50	V	Pass
2510	-51.28	-13	-38.28	-56.04	-54.15	0.68	5.70	V	Pass
3346	-56.60	-13	-43.60	-65.61	-61.64	0.81	8.00	V	Pass

Band :	GSM850 for CH251	**Temperature :**	23~25°C
Test Mode :	EDGE class 8 Link (8PSK)	**Relative Humidity :**	48~52%
Test Engineer :	Sam Li	**Polarization :**	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		

Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1697.6	-59.17	-13	-46.17	-61.72	-62.99	0.53	6.50	H	Pass
2546.4	-48.53	-13	-35.53	-54.55	-51.40	0.68	5.70	H	Pass
3395.2	-55.05	-13	-42.05	-65.07	-60.09	0.81	8.00	H	Pass

Band :	GSM850 for CH251	**Temperature :**	23~25°C
Test Mode :	EDGE class 8 Link (8PSK)	**Relative Humidity :**	48~52%
Test Engineer :	Sam Li	**Polarization :**	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		

Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1697.6	-53.35	-13	-40.35	-56.69	-57.17	0.53	6.50	V	Pass
2546.4	-49.61	-13	-36.61	-54.77	-52.48	0.68	5.70	V	Pass
3395.2	-56.64	-13	-43.64	-65.65	-61.68	0.81	8.00	V	Pass

Band :	GSM1900 for CH512	Temperature :	23~25°C
Test Mode :	GSM Link (GMSK)	Relative Humidity :	48~52%
Test Engineer :	Sam Li	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3700.40	-36.02	-13	-23.02	-48.28	-47.75	0.87	12.60	H	Pass
5550.60	-32.75	-13	-19.75	-50.31	-44.78	1.07	13.10	H	Pass
7400.80	-45.97	-13	-32.97	-64.29	-55.58	1.69	11.30	H	Pass

Band :	GSM1900 for CH512	Temperature :	23~25°C
Test Mode :	GSM Link (GMSK)	Relative Humidity :	48~52%
Test Engineer :	Sam Li	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3700.40	-33.75	-13	-20.75	-48.03	-45.48	0.87	12.6	V	Pass
5550.60	-29.84	-13	-16.84	-48.25	-41.87	1.07	13.1	V	Pass
7400.80	-47.32	-13	-34.32	-65.54	-56.93	1.69	11.3	V	Pass

Band :	GSM1900 for CH661	**Temperature :**	23~25°C
Test Mode :	GSM Link (GMSK)	**Relative Humidity :**	48~52%
Test Engineer :	Sam Li	**Polarization :**	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3760	-35.24	-13	-22.24	-47.54	-46.97	0.87	12.60	H	Pass
5640	-30.80	-13	-17.80	-48.53	-42.83	1.07	13.10	H	Pass
7520	-47.02	-13	-34.02	-65.34	-56.63	1.69	11.30	H	Pass

Band :	GSM1900 for CH661	**Temperature :**	23~25°C
Test Mode :	GSM Link (GMSK)	**Relative Humidity :**	48~52%
Test Engineer :	Sam Li	**Polarization :**	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3760	-31.76	-13	-18.76	-46.27	-43.49	0.87	12.6	V	Pass
5640	-30.01	-13	-17.01	-48.4	-42.04	1.07	13.1	V	Pass
7520	-44.42	-13	-31.42	-62.64	-54.03	1.69	11.3	V	Pass

Band :	GSM1900 for CH810	**Temperature :**	23~25°C
Test Mode :	GSM Link (GMSK)	**Relative Humidity :**	48~52%
Test Engineer :	Sam Li	**Polarization :**	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3819.6	-40.06	-13	-27.06	-51.70	-51.79	0.87	12.60	H	Pass
5729.4	-31.17	-13	-18.17	-48.88	-43.20	1.07	13.10	H	Pass
7639.2	-47.57	-13	-34.57	-65.89	-57.18	1.69	11.30	H	Pass

Band :	GSM1900 for CH810	**Temperature :**	23~25°C
Test Mode :	GSM Link (GMSK)	**Relative Humidity :**	48~52%
Test Engineer :	Sam Li	**Polarization :**	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3819.6	-35.70	-13	-22.70	-49.71	-47.43	0.87	12.6	V	Pass
5729.4	-33.90	-13	-20.90	-51.65	-45.93	1.07	13.1	V	Pass
7639.2	-47.98	-13	-34.98	-66.2	-57.59	1.69	11.3	V	Pass

Band :	GSM1900 for CH512	**Temperature :**	23~25°C
Test Mode :	EDGE class 8 Link (8PSK)	**Relative Humidity :**	48~52%
Test Engineer :	Sam Li	**Polarization :**	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3700.4	-38.06	-13	-25.06	-50.02	-49.79	0.87	12.60	H	Pass
5550.6	-32.26	-13	-19.26	-49.76	-44.29	1.07	13.10	H	Pass
7400.8	-45.53	-13	-32.53	-63.85	-55.14	1.69	11.30	H	Pass

Band :	GSM1900 for CH512	**Temperature :**	23~25°C
Test Mode :	EDGE class 8 Link (8PSK)	**Relative Humidity :**	48~52%
Test Engineer :	Sam Li	**Polarization :**	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3700.4	-39.57	-13	-26.57	-52.81	-51.30	0.87	12.6	V	Pass
5550.6	-32.17	-13	-19.17	-50.28	-44.20	1.07	13.1	V	Pass
7400.8	-46.37	-13	-33.37	-64.59	-55.98	1.69	11.3	V	Pass

Band :	GSM1900 for CH661	**Temperature :**	23~25°C
Test Mode :	EDGE class 8 Link (8PSK)	**Relative Humidity :**	48~52%
Test Engineer :	Sam Li	**Polarization :**	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3760	-36.03	-13	-23.03	-48.29	-47.76	0.87	12.60	H	Pass
5640	-26.83	-13	-13.83	-44.98	-38.86	1.07	13.10	H	Pass
7520	-46.03	-13	-33.03	-64.35	-55.64	1.69	11.30	H	Pass

Band :	GSM1900 for CH661	**Temperature :**	23~25°C
Test Mode :	EDGE class 8 Link (8PSK)	**Relative Humidity :**	48~52%
Test Engineer :	Sam Li	**Polarization :**	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3760	-36.62	-13	-23.62	-50.51	-48.35	0.87	12.6	V	Pass
5640	-30.71	-13	-17.71	-48.98	-42.74	1.07	13.1	V	Pass
7520	-47.12	-13	-34.12	-65.34	-56.73	1.69	11.3	V	Pass

Band :	GSM1900 for CH810	**Temperature :**	23~25°C
Test Mode :	EDGE class 8 Link (8PSK)	**Relative Humidity :**	48~52%
Test Engineer :	Sam Li	**Polarization :**	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3819.6	-41.41	-13	-28.41	-52.80	-53.14	0.87	12.60	H	Pass
5729.4	-30.99	-13	-17.99	-48.75	-43.02	1.07	13.10	H	Pass
7639.2	-46.87	-13	-33.87	-65.19	-56.48	1.69	11.30	H	Pass

Band :	GSM1900 for CH810	**Temperature :**	23~25°C
Test Mode :	EDGE class 8 Link (8PSK)	**Relative Humidity :**	48~52%
Test Engineer :	Sam Li	**Polarization :**	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3819.6	-35.71	-13	-22.71	-49.72	-47.44	0.87	12.6	V	Pass
5729.4	-33.73	-13	-20.73	-51.55	-45.76	1.07	13.1	V	Pass
7639.2	-48.49	-13	-35.49	-66.71	-58.10	1.69	11.3	V	Pass

Band :	WCDMA Band V for CH4132	**Temperature :**	23~25°C
Test Mode :	RMC 12.2Kbps Link (QPSK)	**Relative Humidity :**	48~52%
Test Engineer :	Sam Li	**Polarization :**	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		

Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1652.8	-60.40	-13	-47.40	-62.95	-64.22	0.53	6.50	H	Pass
2479.2	-58.59	-13	-45.59	-64.01	-61.46	0.68	5.70	H	Pass
3305.6	-55.95	-13	-42.95	-65.97	-60.99	0.81	8.00	H	Pass

Band :	WCDMA Band V for CH4132	**Temperature :**	23~25°C
Test Mode :	RMC 12.2Kbps Link (QPSK)	**Relative Humidity :**	48~52%
Test Engineer :	Sam Li	**Polarization :**	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		

Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1652.8	-59.10	-13	-46.10	-62.01	-62.92	0.53	6.50	V	Pass
2479.2	-60.24	-13	-47.24	-64.56	-63.11	0.68	5.70	V	Pass
3305.6	-56.29	-13	-43.29	-65.30	-61.33	0.81	8.00	V	Pass

Band :	WCDMA Band V for CH4182	**Temperature :**	23~25°C
Test Mode :	RMC 12.2Kbps Link (QPSK)	**Relative Humidity :**	48~52%
Test Engineer :	Sam Li	**Polarization :**	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		

Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1672	-55.46	-13	-42.46	-58.01	-59.28	0.53	6.50	H	Pass
2510	-59.08	-13	-46.08	-64.50	-61.95	0.68	5.70	H	Pass
3346	-54.15	-13	-41.15	-64.17	-59.19	0.81	8.00	H	Pass

Band :	WCDMA Band V for CH4182	**Temperature :**	23~25°C
Test Mode :	RMC 12.2Kbps Link (QPSK)	**Relative Humidity :**	48~52%
Test Engineer :	Sam Li	**Polarization :**	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		

Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1672	-55.02	-13	-42.02	-57.93	-58.84	0.53	6.50	V	Pass
2510	-59.78	-13	-46.78	-64.10	-62.65	0.68	5.70	V	Pass
3346	-54.83	-13	-41.83	-63.84	-59.87	0.81	8.00	V	Pass

Band :	WCDMA Band V for CH4233	**Temperature :**	23~25°C
Test Mode :	RMC 12.2Kbps Link (QPSK)	**Relative Humidity :**	48~52%
Test Engineer :	Sam Li	**Polarization :**	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		

Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1693.2	-59.47	-13	-46.47	-62.02	-63.29	0.53	6.50	H	Pass
2539.8	-58.85	-13	-45.85	-64.27	-61.72	0.68	5.70	H	Pass
3386.4	-54.55	-13	-41.55	-64.57	-59.59	0.81	8.00	H	Pass

Band :	WCDMA Band V for CH4233	**Temperature :**	23~25°C
Test Mode :	RMC 12.2Kbps Link (QPSK)	**Relative Humidity :**	48~52%
Test Engineer :	Sam Li	**Polarization :**	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		

Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1693.2	-55.35	-13	-42.35	-58.26	-59.17	0.53	6.50	V	Pass
2539.8	-59.70	-13	-46.70	-64.02	-62.57	0.68	5.70	V	Pass
3386.4	-56.17	-13	-43.17	-65.18	-61.21	0.81	8.00	V	Pass

Band :	WCDMA Band IV for CH1312	**Temperature :**	23~25°C
Test Mode :	RMC 12.2Kbps Link (QPSK)	**Relative Humidity :**	48~52%
Test Engineer :	Sam Li	**Polarization :**	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3424.8	-46.70	-13	-33.70	-59.53	-53.89	0.81	8.00	H	Pass
5137.2	-50.03	-13	-37.03	-68.56	-59.08	0.95	10.00	H	Pass
6849.6	-46.07	-13	-33.07	-67.41	-58.34	1.13	13.40	H	Pass

Band :	WCDMA Band IV for CH1312	**Temperature :**	23~25°C
Test Mode :	RMC 12.2Kbps Link (QPSK)	**Relative Humidity :**	48~52%
Test Engineer :	Sam Li	**Polarization :**	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3424.8	-46.91	-13	-33.91	-60.25	-58.70	0.81	12.6	V	Pass
5137.2	-49.34	-13	-36.34	-67.97	-61.09	0.95	12.7	V	Pass
6849.6	-46.33	-13	-33.33	-67.32	-56.90	1.13	11.7	V	Pass

Band :	WCDMA Band IV for CH1413	**Temperature :**	23~25°C
Test Mode :	RMC 12.2Kbps Link (QPSK)	**Relative Humidity :**	48~52%
Test Engineer :	Sam Li	**Polarization :**	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3465	-47.84	-13	-34.84	-60.67	-55.03	0.81	8.00	H	Pass
5197.5	-48.99	-13	-35.99	-67.52	-58.04	0.95	10.00	H	Pass
6930	-47.15	-13	-34.15	-68.49	-59.42	1.13	13.40	H	Pass

Band :	WCDMA Band IV for CH1413	**Temperature :**	23~25°C
Test Mode :	RMC 12.2Kbps Link (QPSK)	**Relative Humidity :**	48~52%
Test Engineer :	Sam Li	**Polarization :**	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3465	-46.15	-13	-33.15	-59.49	-57.94	0.81	12.6	V	Pass
5197.5	-49.59	-13	-36.59	-68.22	-61.34	0.95	12.7	V	Pass
6930	-46.39	-13	-33.39	-67.38	-56.96	1.13	11.7	V	Pass

Band :	WCDMA Band IV for CH1513	**Temperature :**	23~25°C
Test Mode :	RMC 12.2Kbps Link (QPSK)	**Relative Humidity :**	48~52%
Test Engineer :	Sam Li	**Polarization :**	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3505.2	-46.86	-13	-33.86	-59.69	-54.05	0.81	8.00	H	Pass
5257.8	-47.89	-13	-34.89	-66.42	-56.94	0.95	10.00	H	Pass
7010.4	-46.71	-13	-33.71	-68.05	-58.98	1.13	13.40	H	Pass

Band :	WCDMA Band IV for CH1513	**Temperature :**	23~25°C
Test Mode :	RMC 12.2Kbps Link (QPSK)	**Relative Humidity :**	48~52%
Test Engineer :	Sam Li	**Polarization :**	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3505.2	-45.39	-13	-32.39	-58.73	-57.18	0.81	12.6	V	Pass
5257.8	-47.46	-13	-34.46	-66.78	-59.21	0.95	12.7	V	Pass
7010.4	-47.44	-13	-34.44	-68.43	-58.01	1.13	11.7	V	Pass

Band :	WCDMA Band II for CH9296	**Temperature :**	23~25°C
Test Mode :	RMC 12.2Kbps Link (QPSK)	**Relative Humidity :**	48~52%
Test Engineer :	Sam Li	**Polarization :**	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3704.8	-47.40	-13	-34.40	-58.65	-59.13	0.87	12.60	H	Pass
5557.2	-45.92	-13	-32.92	-61.80	-57.95	1.07	13.10	H	Pass
7409.6	-49.48	-13	-36.48	-67.80	-59.09	1.69	11.30	H	Pass

Band :	WCDMA Band II for CH9296	**Temperature :**	23~25°C
Test Mode :	RMC 12.2Kbps Link (QPSK)	**Relative Humidity :**	48~52%
Test Engineer :	Sam Li	**Polarization :**	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3704.8	-47.17	-13	-34.17	-59.64	-58.90	0.87	12.6	V	Pass
5557.2	-44.06	-13	-31.06	-60.38	-56.09	1.07	13.1	V	Pass
7409.6	-49.34	-13	-36.34	-67.56	-58.95	1.69	11.3	V	Pass

Band :	WCDMA Band II for CH9400	**Temperature :**	23~25°C
Test Mode :	RMC 12.2Kbps Link (QPSK)	**Relative Humidity :**	48~52%
Test Engineer :	Sam Li	**Polarization :**	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3760	-45.51	-13	-32.51	-56.76	-57.24	0.87	12.60	H	Pass
5640	-43.24	-13	-30.24	-59.12	-55.27	1.07	13.10	H	Pass
7520	-50.08	-13	-37.08	-68.40	-59.69	1.69	11.30	H	Pass

Band :	WCDMA Band II for CH9400	**Temperature :**	23~25°C
Test Mode :	RMC 12.2Kbps Link (QPSK)	**Relative Humidity :**	48~52%
Test Engineer :	Sam Li	**Polarization :**	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3760	-44.28	-13	-31.28	-56.75	-56.01	0.87	12.6	V	Pass
5640	-43.02	-13	-30.02	-59.34	-55.05	1.07	13.1	V	Pass
7520	-49.76	-13	-36.76	-67.98	-59.37	1.69	11.3	V	Pass

Band :	WCDMA Band II for CH9538	**Temperature :**	23~25°C
Test Mode :	RMC 12.2Kbps Link (QPSK)	**Relative Humidity :**	48~52%
Test Engineer :	Sam Li	**Polarization :**	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3815.2	-49.57	-13	-36.57	-60.82	-61.30	0.87	12.60	H	Pass
5722.8	-42.61	-13	-29.61	-58.49	-54.64	1.07	13.10	H	Pass
7630.4	-47.68	-13	-34.68	-66.00	-57.29	1.69	11.30	H	Pass

Band :	WCDMA Band II for CH9538	**Temperature :**	23~25°C
Test Mode :	RMC 12.2Kbps Link (QPSK)	**Relative Humidity :**	48~52%
Test Engineer :	Sam Li	**Polarization :**	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3815.2	-46.65	-13	-33.65	-59.12	-58.38	0.87	12.6	V	Pass
5722.8	-44.39	-13	-31.39	-60.71	-56.42	1.07	13.1	V	Pass
7630.4	-49.40	-13	-36.40	-67.62	-59.01	1.69	11.3	V	Pass

3.8 Frequency Stability Measurement

3.8.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within ±0.00025% (±2.5ppm) of the center frequency.

3.8.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.8.3 Test Procedures for Temperature Variation

1. The testing follows FCC KDB 971168 v02r02 Section 9.0.
2. The EUT was set up in the thermal chamber and connected with the system simulator.
3. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
4. With power OFF, the temperature was raised in 10°C steps up to 50°C. The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

3.8.4 Test Procedures for Voltage Variation

1. The testing follows FCC KDB 971168 v02r02 Section 9.0.
2. The EUT was placed in a temperature chamber at 25±5° C and connected with the system simulator.
3. The power supply voltage to the EUT was varied from BEP to 115% of the nominal value measured at the input to the EUT.
4. The variation in frequency was measured for the worst case.

3.8.5 Test Setup



3.8.6 Test Result of Temperature Variation

Band :	GSM 850	Channel :	189
Limit (ppm) :	2.5	Frequency :	836.4 MHz

Temperature (°C)	GSM	EDGE class 8	Result
	Deviation (ppm)	Deviation (ppm)	
50	0.0060	0.0072	PASS
40	0.0048	0.0036	
30	0.0024	0.0024	
20(Ref.)	0.0000	0.0000	
10	0.0012	0.0012	
0	0.0036	0.0036	
-10	0.0299	0.0060	
-20	0.0323	0.0072	
-30	0.0347	0.0096	

Band :	GSM 1900	Channel :	661
Limit (ppm) :	within authorized band	Frequency :	1880.0 MHz

Temperature (°C)	GSM	EDGE class 8	Result
	Deviation (ppm)	Deviation (ppm)	
50	0.0021	0.0032	PASS
40	0.0016	0.0021	
30	0.0011	0.0011	
20(Ref.)	0.0000	0.0000	
10	0.0005	0.0016	
0	0.0016	0.0032	
-10	0.0027	0.0043	
-20	0.0037	0.0053	
-30	0.0043	0.0069	

Note: The frequency fundamental emissions stay within the authorized frequency block based on the frequency deviation measured is small.

Band :	WCDMA Band V	Channel :	4182
Limit (ppm) :	2.5	Frequency :	836.4 MHz

Temperature (°C)	RMC 12.2Kbps Deviation (ppm)	Result
50	0.0036	PASS
40	0.0024	
30	0.0012	
20(Ref.)	0.0000	
10	0.0012	
0	0.0024	
-10	0.0084	
-20	0.0096	
-30	0.0120	

Band :	WCDMA Band IV	Channel :	1413
Limit (ppm) :	within authorized band	Frequency :	1732.6 MHz

Temperature (°C)	RMC 12.2Kbps Deviation (ppm)	Result
50	0.0017	PASS
40	0.0012	
30	0.0006	
20(Ref.)	0.0000	
10	0.0012	
0	0.0017	
-10	0.0023	
-20	0.0029	
-30	0.0035	

Note: The frequency fundamental emissions stay within the authorized frequency block based on the frequency deviation measured is small.

Band :	WCDMA Band II	Channel :	9400
Limit (ppm) :	within authorized band	Frequency :	1880.0 MHz

Temperature (°C)	RMC 12.2Kbps	Result
	Deviation (ppm)	
50	0.0016	PASS
40	0.0011	
30	0.0005	
20(Ref.)	0.0000	
10	0.0005	
0	0.0043	
-10	0.0048	
-20	0.0053	
-30	0.0064	

Note: The frequency fundamental emissions stay within the authorized frequency block based on the frequency deviation measured is small.

3.8.7 Test Result of Voltage Variation

Band & Channel	Mode	Voltage (Volt)	Deviation (ppm)	Limit (ppm)	Result
GSM 850 CH189	GSM	4.2	0.0012	2.5	PASS
		3.7	0.0000		
		BEP	0.0024		
	EDGE class 8	4.2	0.0012		
		3.7	0.0000		
		BEP	0.0024		
GSM 1900 CH661	GSM	4.2	0.0005	(Note 3.)	
		3.7	0.0000		
		BEP	0.0005		
	EDGE class 8	4.2	0.0011		
		3.7	0.0000		
		BEP	0.0005		
WCDMA Band V CH4182	RMC 12.2Kbps	4.2	0.0012	2.5	
		3.7	0.0000		
		BEP	0.0000		
WCDMA Band IV CH1413	RMC 12.2Kbps	4.2	0.0000	(Note 3.)	
		3.7	0.0000		
		BEP	0.0006		
WCDMA Band II CH9400	RMC 12.2Kbps	4.2	0.0000	(Note 3.)	
		3.7	0.0000		
		BEP	0.0005		

Note:

1. Normal Voltage = 3.7V.
2. Battery End Point (BEP) = 3.5 V.
3. The frequency fundamental emissions stay within the authorized frequency block based on the frequency deviation measured is small.

4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101078	9kHz~40GHz	May 05, 2015	Jul. 15, 2015~ Jul. 22, 2015	May 04, 2016	Conducted (TH01-SZ)
Spectrum Analyzer	R&S	FSP30	101400	9kHz~30GHz	Jan. 28, 2015	Jul. 15, 2015~ Jul. 22, 2015	Jan. 27, 2016	Conducted (TH01-SZ)
Thermal Chamber	Ten Billion	LP-150U	H2014081803	-40~+150°C	Sep. 16, 2014	Jul. 15, 2015~ Jul. 22, 2015	Sep. 15, 2015	Conducted (TH01-SZ)
EMI Test Receiver	R&S	ESR7	101404	9kHz~7GHz; Max 30dBm	Oct. 14, 2014	Jul. 29, 2015	Oct. 13, 2015	Radiation (03CH02-SZ)
Spectrum Analyzer	R&S	FSV40	101041	10kHz~40GHz;Max 30dBm	Oct. 15, 2014	Jul. 29, 2015	Oct. 14, 2015	Radiation (03CH02-SZ)
Bilog Antenna	TeseQ	CBL6112D	23188	30MHz~2GHz	Nov. 07, 2014	Jul. 29, 2015	Nov. 06, 2015	Radiation (03CH02-SZ)
Double Ridge Horn Antenna	SCHWARZBECK	BBHA 9120D	9120D-1285	1GHz~18GHz	Jan. 20, 2015	Jul. 29, 2015	Jan. 19, 2016	Radiation (03CH02-SZ)
SHF-EHF Horn	com-power	AH-840	101071	18GHz~40GHz	Sep. 04, 2014	Jul. 29, 2015	Sep. 03, 2015	Radiation (03CH02-SZ)
Amplifier	ADVANTEST	BB525C	E9007003	9kHz~3000MHz / 30 dB	Jan. 28, 2015	Jul. 29, 2015	Jan. 27, 2016	Radiation (03CH02-SZ)
Amplifier	Agilent	8449B	3008A01023	1GHz~26.5GHz	Oct. 29, 2014	Jul. 29, 2015	Oct. 28, 2015	Radiation (03CH02-SZ)
AC Power Source	Chroma	61601	616010002470	N/A	NCR	Jul. 29, 2015	NCR	Radiation (03CH02-SZ)
Turn Table	Chaintek	T-200	N/A	0~360 degree	NCR	Jul. 29, 2015	NCR	Radiation (03CH02-SZ)
Antenna Mast	Chaintek	MBS-400	N/A	1 m~4 m	NCR	Jul. 29, 2015	NCR	Radiation (03CH02-SZ)

5 Uncertainty of Evaluation

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	**4.5dB**