



FCC PART 27
FCC PART 22H, PART 24E
TEST REPORT

For

BLU Products, Inc.

10814 NW 33rd St # 100 Doral, FL 33172, United States

FCC ID: YHLBLUSTJ8LTE

Report Type: Original Report	Product Type: Mobile Phone
Report Number: RSZ170601004-00D	
Report Date: 2017-07-04	
Oscar Ye	
Reviewed By: Engineer	<i>Oscar Ye</i>
Prepared By: Bay Area Compliance Laboratories Corp. (Kunshan) No.248 Chenghu Road, Kunshan, Jiangsu province, China Tel: +86-0512-86175000 Fax: +86-0512-88934268 www.baclcorp.com.cn	

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp.

TABLE OF CONTENTS

GENERAL INFORMATION.....	3
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	3
OBJECTIVE	3
RELATED SUBMITTAL(S)/GRANT(S).....	3
TEST METHODOLOGY	3
MEASUREMENT UNCERTAINTY.....	4
TEST FACILITY	4
SYSTEM TEST CONFIGURATION.....	5
DESCRIPTION OF TEST CONFIGURATION	5
EQUIPMENT MODIFICATIONS	5
SUPPORT EQUIPMENT LIST AND DETAILS	5
BLOCK DIAGRAM OF TEST SETUP	5
SUMMARY OF TEST RESULTS	6
TEST EQUIPMENT LIST	7
FCC §1.1307 & §2.1093 - RF EXPOSURE.....	8
APPLICABLE STANDARD	8
TEST RESULT	8
FCC §2.1047 - MODULATION CHARACTERISTIC	9
FCC § 2.1046, § 22.913 (A) & § 24.232 (C); §27.50(C) (D) (H) - RF OUTPUT POWER.....	10
APPLICABLE STANDARD	10
TEST PROCEDURE	10
TEST DATA	10
FCC §2.1049, §22.917, §22.905 & §24.238 & §27.53 - OCCUPIED BANDWIDTH.....	37
APPLICABLE STANDARD	37
TEST PROCEDURE	37
TEST DATA	37
FCC §2.1051, §22.917(A) & §24.238(A); §27.53 (H) (M) - SPURIOUS EMISSIONS AT ANTENNA TERMINALS.....	95
APPLICABLE STANDARD	95
TEST PROCEDURE	95
TEST DATA	95
FCC § 2.1053; § 22.917 (A);§ 24.238 (A); §27.53 (H)(M) SPURIOUS RADIATED EMISSIONS.....	133
APPLICABLE STANDARD	133
TEST PROCEDURE	133
TEST DATA	133
FCC § 22.917 (A);§ 24.238 (A); §27.53 (H)(M) - BAND EDGES	137
APPLICABLE STANDARD	137
TEST PROCEDURE	137
TEST DATA	137
FCC § 2.1055; § 22.355; § 24.235; §27.54; - FREQUENCY STABILITY.....	195
APPLICABLE STANDARD	195
TEST PROCEDURE	195
TEST DATA	196

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The *BLU Products, Inc.*'s product, model number: *STUDIO J8 LTE (FCC ID: YHLBLUSTJ8LTE)* in this report is a *Mobile Phone* which was measured approximately: 15.3 cm (L) × 7.4 cm (W) × 0.8 cm (H), rated with input voltage: DC 3.8 V battery or DC 5.0V from adapter.

Adapter information

Model: US-AH-1004

Input: 100-240~50/60Hz 0.2A

Output: 5.0V 1.0A

Notes: This series products model: STUDIO M5 PLUS LTE and STUDIO J8 LTE are identical; they have the identical schematics, only named differently. Model STUDIO J8 LTE was selected for fully testing, the detailed information can be referred to the declaration which was stated and guaranteed by the applicant.

** All measurement and test data in this report was gathered from production sample serial number: 1701210 (Assigned by BACL, Kunshan). The EUT supplied by the applicant was received on 2017-06-01.*

Objective

This test report is prepared on behalf of *BLU Products, Inc.* in accordance with Part 2-Subpart J, Part 22-Subpart H and Part 24-Subpart E and Subpart 27 of the Federal Communication Commissions rules.

The objective is to determine the compliance of the EUT with FCC rules for output power, modulation characteristic, occupied bandwidth, and spurious emission at antenna terminal, spurious radiated emission, frequency stability and band edge.

Related Submittal(s)/Grant(s)

FCC Part 15.247 DTS & DSS and Part 15B JBP submissions with FCC ID: YHLBLUSTJ8LTE.

Test Methodology

All tests and measurements indicated in this document were performed in accordance with the Code of Federal Regulations Title 47 Part 2-Subpart J as well as the following parts:

Part 22 Subpart H - Public Mobile Services

Part 24 Subpart E - Personal Communication Services

Part 27 – Miscellaneous wireless communications services

Applicable Standards: TIA/EIA 603-D.

All radiated and conducted emissions measurements were performed at Bay Area Compliance Laboratories Corp. (Kunshan). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement Uncertainty

Item		Uncertainty
AC Power Lines Conducted Emissions		± 3.26 dB
RF conducted test with spectrum		± 0.9 dB
RF Output Power with Power meter		± 0.5 dB
Radiated emission	30MHz~1GHz	± 5.91 dB
	Above 1G	± 4.92 dB
Occupied Bandwidth		± 0.5 kHz
Temperature		± 1.0 °C
Humidity		$\pm 6\%$

Test Facility

The test site used by Bay Area Compliance Laboratories Corp. (Kunshan) to collect test data is located on the No.248 Chenghu Road, Kunshan, Jiangsu province, China.

Test site at Bay Area Compliance Laboratories Corp. (Kunshan) has been fully described in reports submitted to the Federal Communication Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on November 06, 2014. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2014.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 815570. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The EUT was configured for testing according to TIA/EIA-603-D.

The final qualification test was performed with the EUT operating at normal mode.


Equipment Modifications

No modification was made to the EUT.

Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
Rohde & Schwarz	Wideband Radio Communication Tester	CMW500	1201.002K50-116218-UY
Rohde & Schwarz	Universal Radio Communication Tester	CMU200	110605

Block Diagram of Test Setup



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§1.1307, §2.1093	RF Exposure (SAR)	Compliance*
§2.1046; § 22.913 (a); § 24.232 (c); §27.50 (c) (d) (h)	RF Output Power	Compliance
§ 2.1047	Modulation Characteristics	Not Applicable
§ 2.1049; § 22.905; § 22.917; § 24.238; §27.53	Occupied Bandwidth	Compliance
§ 2.1051; § 22.917 (a); § 24.238 (a); §27.53 (h)(m)	Spurious Emissions at Antenna Terminal	Compliance
§ 2.1053; § 22.917 (a); § 24.238 (a); §27.53 (h)(m)	Field Strength of Spurious Radiation	Compliance
§ 22.917 (a); § 24.238 (a); §27.53 (h)(m)	Band Edge	Compliance
§ 2.1055; § 22.355; § 24.235; §27.54;	Frequency stability	Compliance

Note: * Please refer to SAR report released by BACL, report number: RSZ170601004-20.

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Radiated Emission Test					
Sonoma Instrunent	Amplifier	330	171377	2016-12-12	2017-12-12
Rohde & Schwarz	EMI Test Receiver	ESCI	100195	2016-11-25	2017-11-25
Sunol Sciences	Broadband Antenna	JB3	A090314-2	2016-01-09	2019-01-08
Sunol Sciences	Broadband Antenna	JB3	A090314-1	2016-01-09	2019-01-08
Narda	Pre-amplifier	AFS42-00101800	2001270	2016-09-08	2017-09-08
EMCO	Horn Antenna	3116	00084159	2016-10-18	2019-10-17
Rohde & Schwarz	Signal Analyzer	FSIQ26	100048	2016-11-25	2017-11-25
ETS	Horn Antenna	3115	6229	2016-12-12	2019-12-12
ETS	Horn Antenna	3115	9311-4159	2016-01-11	2019-01-10
R&S	Auto test Software	EMC32	V 09.10.0	NCR	NCR
haojintech	Coaxial Cable	Cable-1	001	2016-12-12	2017-12-12
haojintech	Coaxial Cable	Cable-2	002	2016-12-12	2017-12-12
haojintech	Coaxial Cable	Cable-3	003	2016-12-12	2017-12-12
MICRO-COAX	Coaxial Cable	Cable-4	004	2016-12-12	2017-12-12
MICRO-COAX	Coaxial Cable	Cable-5	005	2016-12-12	2017-12-12
MICRO-COAX	Coaxial Cable	Cable-7	007	2016-12-12	2017-12-12
HP	Signal Generator	8341B	2624A00116	2016-08-29	2017-08-29
RF Conducted test					
BACL	TS 8997 Cable-01	T-KS-EMC086	T-KS-EMC086	2016-12-09	2017-12-08
BACL	RF cable	KS-LAB-012	KS-LAB-012	2016-12-15	2017-12-14
Rohde & Schwarz	Signal Analyzer	FSIQ26	836131/009	2016-09-21	2017-09-21
Rohde & Schwarz	Universal Radio Communication Tester	CMU200	110605	2016-11-25	2017-11-25
HONOVA	Power Splitter	ZFRSC-14-S+	019411452	2017-06-12	2018-06-12
WEINSCHTEL	3dB Attenuator	5326	N/A	2017-06-18	2018-06-18

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Kunshan) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC §1.1307 & §2.1093 - RF EXPOSURE

Applicable Standard

FCC§1.1310 and §2.1093.

Test Result

Compliance, please refer to the SAR report: RSZ170601004-20.

FCC §2.1047 - MODULATION CHARACTERISTIC

According to FCC § 2.1047(d), Part 22H & 24E & 27 there is no specific requirement for digital modulation, therefore modulation characteristic is not presented.

FCC § 2.1046, § 22.913 (a) & § 24.232 (c); §27.50(c) (d) (h) - RF OUTPUT POWER

Applicable Standard

According to FCC §2.1046 and §22.913 (a), the ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 watts.

According to FCC §2.1046 and §24.232 (C), mobile and portable stations are limited to 2 watts EIRP and the equipment must employ a means for limiting power to the minimum necessary for successful communications.

According to §27.50(d), the maximum EIRP must not exceed 1Watts (30dBm) for 1710-1755MHz. The peak-to-average power ratio (PAPR) of the transmitter output power must not exceed 13 dB.

According to §27.50(c), Portable stations (hand-held devices) in the 600 MHz uplink band and the 698-746 MHz band, and fixed and mobile stations in the 600 MHz uplink band are limited to 3 watts ERP.


According to §27.50(d), the maximum EIRP must not exceed 1Watts (30dBm) for 1710-1755MHz.

According to §27.50(h), the maximum EIRP must not exceed 2Watts (33dBm) for 2500-2570MHz.

Test Procedure

Conducted method:

The RF output of the transmitter was connected to the CMW500/CMU200 through sufficient attenuation.



Radiated method:

TIA 603-D section 2.2.17

Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	50 %
ATM Pressure:	101.0 kPa

The testing was performed by Echo Wu on 2017-07-01.

Conducted Power**Cellular Band (Part 22H)**

Mode	Channel	Frequency (MHz)	Average Output Power (dBm)	Limit (dBm)
GSM	128	824.2	31.09	38.45
	190	836.6	31.07	38.45
	251	848.8	31.09	38.45

Mode	Channel	Frequency (MHz)	Average Output Power (dBm)				Limit (dBm)
			1 slot	2 slots	3 slots	4 slots	
GPRS	128	824.2	31.11	30.31	28.87	27.45	38.45
	190	836.6	31.10	30.32	28.89	27.56	38.45
	251	848.8	31.07	30.29	28.91	27.54	38.45

Mode	Channel	Frequency (MHz)	Average Output Power (dBm)				Limit (dBm)
			1 slot	2 slots	3 slots	4 slots	
EGPRS	128	824.2	25.44	23.97	22.07	20.93	38.45
	190	836.6	25.46	23.97	22.07	20.90	38.45
	251	848.8	25.45	23.94	21.97	20.90	38.45

Mode	Test Condition	Test Mode	3GPP Sub Test	Average Output Power (dBm)		
				Low Frequency	Middle Frequency	High Frequency
WCDMA (Band V)	Normal	RMC12.2k		22.12	22.05	22.13
		HSDPA	1	20.69	20.46	20.69
			2	20.63	20.36	20.60
			3	20.82	20.50	20.75
			4	20.60	20.40	20.63
		HSUPA	1	20.69	20.46	20.70
			2	20.58	20.40	20.64
			3	20.77	20.58	20.73
			4	20.65	20.37	20.61
			5	20.77	20.58	20.79

PCS Band (Part 24E)

Mode	Channel	Frequency (MHz)	Average Output Power (dBm)	Limit (dBm)
GSM	512	1850.2	28.83	33
	661	1880.0	28.74	33
	810	1909.8	28.64	33

Mode	Channel	Frequency (MHz)	Average Output Power (dBm)				Limit (dBm)
			1 slot	2 slots	3 slots	4 slots	
GPRS	512	1850.2	28.87	27.90	26.46	25.38	33
	661	1880.0	28.76	27.78	26.36	25.31	33
	810	1909.8	28.68	27.66	26.26	25.25	33

Mode	Channel	Frequency (MHz)	Average Output Power (dBm)				Limit (dBm)
			1 slot	2 slots	3 slots	4 slots	
EGPRS	512	1850.2	25.93	24.57	22.60	21.45	33
	661	1880.0	25.83	24.54	22.55	21.54	33
	810	1909.8	25.70	24.37	22.44	21.23	33

Mode	Test Condition	Test Mode	3GPP Sub Test	Average Output Power (dBm)		
				Low Frequency	Middle Frequency	High Frequency
WCDMA (Band II)	Normal	RMC12.2k		21.12	21.27	21.05
		HSDPA	1	20.63	20.65	20.49
			2	20.55	20.59	20.39
			3	20.71	20.71	20.56
			4	20.51	20.61	20.43
		HSUPA	1	20.66	20.66	20.60
			2	20.55	20.63	20.51
			3	20.72	20.71	20.71
			4	20.55	20.57	20.52
			5	20.72	20.77	20.66

AWS Band (Part 27)

Mode	Test Condition	Test Mode	3GPP Sub Test	Average Output Power (dBm)		
				Low Frequency	Middle Frequency	High Frequency
WCDMA (Band IV)	Normal	RMC12.2k		21.84	21.98	21.82
		HSDPA	1	20.80	20.85	20.65
			2	20.75	20.72	20.59
			3	20.93	20.93	20.72
			4	20.71	20.77	20.62
		HSUPA	1	20.88	20.86	20.68
			2	20.79	20.82	20.64
			3	20.95	20.92	20.75
			4	20.78	20.73	20.61
			5	20.92	20.96	20.77

Peak-to-average ratio (PAR)**Cellular Band**

Mode	Channel	PAR (dB)	Limit (dB)
GSM	Low	0.49	13
	Middle	0.32	13
	High	0.47	13

Mode	Channel	PAR (dB)	Limit (dB)
EGPRS	Low	2.59	13
	Middle	2.47	13
	High	2.54	13

Mode	Channel	PAR (dB)	Limit (dB)
RMC (BPSK)	Low	3.35	13
	Middle	3.24	13
	High	3.37	13
HSDPA (16QAM)	Low	3.38	13
	Middle	3.29	13
	High	3.34	13
HSUPA (BPSK)	Low	3.31	13
	Middle	3.27	13
	High	3.35	13

PCS Band

Mode	Channel	PAR (dB)	Limit (dB)
GSM	Low	0.49	13
	Middle	0.36	13
	High	0.47	13

Mode	Channel	PAR (dB)	Limit (dB)
EGPRS	Low	2.57	13
	Middle	2.46	13
	High	2.54	13

Mode	Channel	PAR (dB)	Limit (dB)
RMC (BPSK)	Low	3.15	13
	Middle	2.95	13
	High	3.14	13
HSDPA (16QAM)	Low	3.18	13
	Middle	2.95	13
	High	3.12	13
HSUPA (BPSK)	Low	3.16	13
	Middle	2.94	13
	High	3.17	13

AWS Band

Mode	Channel	PAR (dB)	Limit (dB)
WCDMA (BPSK)	Low	3.27	13
	Middle	3.18	13
	High	3.26	13
HSDPA (16QAM)	Low	3.23	13
	Middle	3.17	13
	High	3.29	13
HSUPA (BPSK)	Low	3.24	13
	Middle	3.13	13
	High	3.28	13

Radiated Power**GSM Mode:**

Frequency (MHz)	Receiver Reading (dBμV)	Turntable Angle Degree	Rx Antenna		Substituted			Absolute Level (dBm)	FCC Part 22H/24E	
			Height (m)	Polar (H/V)	Level (dBm)	Cable loss (dB)	Antenna Gain (dB)		Limit (dBm)	Margin (dB)
ERP for Cellular Band (Part 22H), Middle Channel										
836.6	96.11	121	2.3	H	26.4	0.26	4.75	30.89	38.45	7.56
836.6	91.63	235	1.9	V	17.9	0.26	4.75	22.39	38.45	16.06
EIRP for PCS Band (Part 24E), Middle Channel										
1880.00	80.59	179	2.3	H	19.1	0.45	8.84	27.49	33	5.51
1880.00	77.72	275	2.5	V	14.0	0.45	8.84	22.39	33	10.61

EDGE Mode:

Frequency (MHz)	Receiver Reading (dBμV)	Turntable Angle Degree	Rx Antenna		Substituted			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Height (m)	Polar (H/V)	Level (dBm)	Cable loss (dB)	Antenna Gain (dB)			
ERP, Cellular Band (Part 22H), Middle Channel										
836.6	89.81	276	2.0	H	20.1	0.26	4.75	24.59	38.45	13.86
836.6	89.53	270	2.5	V	15.8	0.26	4.75	20.29	38.45	18.16
EIRP, PCS Band (Part 24E), Middle Channel										
1880.00	76.49	321	2.0	H	15.0	0.45	8.84	23.39	38.45	15.06
1880.00	74.52	109	2.2	V	10.8	0.45	8.84	19.19	38.45	19.26

WCDMA Mode:

Frequency (MHz)	Receiver Reading (dBμV)	Turntable Angle Degree	Rx Antenna		Substituted			Absolute Level (dBm)	FCC Part 22H/24E/27	
			Height (m)	Polar (H/V)	Level (dBm)	Cable loss (dB)	Antenna Gain (dB)		Limit (dBm)	Margin (dB)
ERP for WCDMA Band V (Part 22H), Middle Channel										
836.6	84.81	212	2.0	H	15.1	0.26	4.75	19.59	38.45	18.86
836.6	83.13	77	1.2	V	9.4	0.26	4.75	13.89	38.45	24.56
EIRP for WCDMA Band II (Part 24E), Middle Channel										
1880.00	73.19	219	1.6	H	11.7	0.45	8.84	20.09	33	12.91
1880.00	70.42	56	1.9	V	6.7	0.45	8.84	15.09	33	17.91
EIRP for WCDMA Band IV (Part 27), Middle Channel										
1732.60	76.07	29	1.7	H	12.5	0.40	8.52	20.62	30	9.38
1732.60	75.24	326	1.0	V	9.7	0.40	8.52	17.82	30	12.18

Note:

Absolute Level = Substituted Level - Cable loss + Antenna Gain

Margin = Limit- Absolute Level

LTE Band 2:**Maximum Output Power**

Bandwidth (MHz)	Modulation	RB size/RB Offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
1.4	QPSK	RB Size=1, RB Offset=0	22.71	23.00	22.54
		RB Size=1, RB Offset=2	22.65	22.96	22.51
		RB Size=1, RB Offset=5	22.81	23.08	22.66
		RB Size=3, RB Offset=0	22.12	22.5	22.17
		RB Size=3, RB Offset=1	22.04	22.37	22.07
		RB Size=3, RB Offset=2	22.18	22.58	22.25
		RB Size=6, RB Offset=0	21.56	21.98	21.67
	16QAM	RB Size=1, RB Offset=0	22.78	22.96	22.73
		RB Size=1, RB Offset=2	22.72	22.88	22.65
		RB Size=1, RB Offset=5	22.90	23.02	22.79
		RB Size=3, RB Offset=0	22.17	22.53	22.27
		RB Size=3, RB Offset=1	22.04	22.47	22.16
		RB Size=3, RB Offset=2	22.30	22.66	22.35
		RB Size=6, RB Offset=0	21.54	21.99	21.63
3.0	QPSK	RB Size=1, RB Offset=0	22.71	22.92	22.84
		RB Size=1, RB Offset=7	22.67	22.84	22.71
		RB Size=1, RB Offset=14	22.84	22.96	22.94
		RB Size=8, RB Offset=0	22.12	22.57	22.32
		RB Size=8, RB Offset=4	22.01	22.54	22.26
		RB Size=8, RB Offset=7	22.18	22.65	22.44
		RB Size=15, RB Offset=0	21.86	22.03	21.84
	16QAM	RB Size=1, RB Offset=0	22.64	22.92	22.82
		RB Size=1, RB Offset=7	22.52	22.85	22.74
		RB Size=1, RB Offset=14	22.69	22.96	22.92
		RB Size=8, RB Offset=0	22.27	22.51	22.35
		RB Size=8, RB Offset=4	22.19	22.47	22.28
		RB Size=8, RB Offset=7	22.37	22.62	22.44
		RB Size=15, RB Offset=0	21.86	22.04	21.76

Bandwidth (MHz)	Modulation	RB size/RB Offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
5.0	QPSK	RB Size=1, RB Offset=0	22.84	23.00	22.54
		RB Size=1, RB Offset=12	22.81	22.93	22.44
		RB Size=1, RB Offset=24	22.88	23.06	22.64
		RB Size=12, RB Offset=0	22.32	22.57	22.37
		RB Size=12, RB Offset=6	22.20	22.52	22.26
		RB Size=12, RB Offset=11	22.36	22.63	22.41
		RB Size=25, RB Offset=0	21.76	22.01	21.77
	16QAM	RB Size=1, RB Offset=0	22.86	23.01	22.72
		RB Size=1, RB Offset=12	22.79	22.94	22.61
		RB Size=1, RB Offset=24	22.96	23.12	22.83
		RB Size=12, RB Offset=0	22.37	22.62	22.43
		RB Size=12, RB Offset=6	22.27	22.55	22.39
		RB Size=12, RB Offset=11	22.46	22.67	22.53
		RB Size=25, RB Offset=0	21.71	22.10	21.81
10.0	QPSK	RB Size=1, RB Offset=0	22.89	23.08	22.77
		RB Size=1, RB Offset=24	22.77	23.00	22.70
		RB Size=1, RB Offset=49	23.01	23.15	22.88
		RB Size=25, RB Offset=0	22.32	22.67	22.46
		RB Size=25, RB Offset=12	22.26	22.58	22.36
		RB Size=25, RB Offset=24	22.42	22.75	22.58
		RB Size=50, RB Offset=0	21.78	22.14	21.84
	16QAM	RB Size=1, RB Offset=0	22.81	23.04	22.74
		RB Size=1, RB Offset=24	22.69	22.95	22.64
		RB Size=1, RB Offset=49	22.91	23.08	22.85
		RB Size=25, RB Offset=0	22.14	22.42	22.27
		RB Size=25, RB Offset=12	22.03	22.33	22.15
		RB Size=25, RB Offset=24	22.21	22.49	22.36
		RB Size=50, RB Offset=0	21.45	21.79	21.57

Bandwidth (MHz)	Modulation	RB size/RB Offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
15.0	QPSK	RB Size=1, RB Offset=0	22.85	23.04	22.92
		RB Size=1, RB Offset=37	22.82	22.93	22.80
		RB Size=1, RB Offset=74	22.89	23.08	23.04
		RB Size=36, RB Offset=0	22.32	22.65	22.42
		RB Size=36, RB Offset=18	22.26	22.60	22.36
		RB Size=36, RB Offset=37	22.40	22.70	22.54
		RB Size=75, RB Offset=0	22.15	22.32	22.04
	16QAM	RB Size=1, RB Offset=0	22.43	22.88	22.34
		RB Size=1, RB Offset=37	22.31	22.85	22.29
		RB Size=1, RB Offset=74	22.48	22.91	22.41
		RB Size=36, RB Offset=0	22.37	22.53	22.36
		RB Size=36, RB Offset=18	22.33	22.48	22.24
		RB Size=36, RB Offset=37	22.47	22.60	22.40
		RB Size=75, RB Offset=0	21.58	21.94	21.63
20.0	QPSK	RB Size=1, RB Offset=0	22.47	22.96	22.54
		RB Size=1, RB Offset=49	22.37	22.87	22.46
		RB Size=1, RB Offset=99	22.57	23.03	22.60
		RB Size=50, RB Offset=0	22.32	22.58	22.34
		RB Size=50, RB Offset=24	22.21	22.50	22.29
		RB Size=50, RB Offset=49	22.42	22.65	22.46
		RB Size=100, RB Offset=0	21.74	22.05	21.84
	16QAM	RB Size=1, RB Offset=0	22.75	23.11	22.84
		RB Size=1, RB Offset=49	22.71	23.03	22.80
		RB Size=1, RB Offset=99	22.79	23.18	22.97
		RB Size=50, RB Offset=0	22.37	22.64	22.42
		RB Size=50, RB Offset=24	22.28	22.58	22.35
		RB Size=50, RB Offset=49	22.46	22.69	22.46
		RB Size=100, RB Offset=0	22.01	22.21	22.05

Peak-to-average ratio (PAR)

Modulation	Middle Channel (dB)	PAR Limit (dB)	Result
16QAM (1RB Size)	10.71	13	Pass
16QAM (100%RB Size)	7.53	13	Pass

QPSK:

Frequency (MHz)	Receiver Reading (dBμV)	Turn table Angle Degree	Rx Antenna		Substituted			Absolute Level (dBm)	Limit (dBm)
			Height (m)	Polar (H/V)	Level (dBm)	Cable Loss (dB)	Antenna Gain (dB)		
Middle Channel									
1.4 MHz Bandwidth									
1880.00	77.39	45	1.2	H	15.9	0.45	8.84	24.29	33
1880.00	78.02	186	1.2	V	14.3	0.45	8.84	22.69	33
3 MHz Bandwidth									
1880.00	76.79	252	1.6	H	15.3	0.45	8.84	23.69	33
1880.00	76.42	145	2.5	V	12.7	0.45	8.84	21.09	33
5 MHz Bandwidth									
1880.00	75.29	24	2.0	H	13.8	0.45	8.84	22.19	33
1880.00	75.62	44	1.0	V	11.9	0.45	8.84	20.29	33
10 MHz Bandwidth									
1880.00	75.39	349	1.3	H	13.9	0.45	8.84	22.29	33
1880.00	74.92	134	1.9	V	11.2	0.45	8.84	19.59	33
15 MHz Bandwidth									
1880.00	74.69	46	1.9	H	13.2	0.45	8.84	21.59	33
1880.00	74.32	58	1.1	V	10.6	0.45	8.84	18.99	33
20 MHz Bandwidth									
1880.00	74.49	25	2.1	H	13.0	0.45	8.84	21.39	33
1880.00	74.02	187	1.8	V	10.3	0.45	8.84	18.69	33

16QAM:

Frequency (MHz)	Receiver Reading (dBμV)	Turn table Angle Degree	Rx Antenna		Substituted			Absolute Level (dBm)	Limit (dBm)
			Height (m)	Polar (H/V)	Level (dBm)	Cable Loss (dB)	Antenna Gain (dB)		
Middle Channel									
1.4 MHz Bandwidth									
1880.00	77.39	295	1.2	H	15.9	0.45	8.84	24.29	33
1880.00	77.72	4	1.7	V	14.0	0.45	8.84	22.39	33
3 MHz Bandwidth									
1880.00	77.09	79	2.0	H	15.6	0.45	8.84	23.99	33
1880.00	77.52	177	1.1	V	13.8	0.45	8.84	22.19	33
5 MHz Bandwidth									
1880.00	76.79	311	1.0	H	15.3	0.45	8.84	23.69	33
1880.00	77.42	275	1.4	V	13.7	0.45	8.84	22.09	33
10 MHz Bandwidth									
1880.00	76.59	192	1.5	H	15.1	0.45	8.84	23.49	33
1880.00	77.32	328	2.3	V	13.6	0.45	8.84	21.99	33
15 MHz Bandwidth									
1880.00	75.39	184	1.4	H	13.9	0.45	8.84	22.29	33
1880.00	76.92	235	1.5	V	13.2	0.45	8.84	21.59	33
20 MHz Bandwidth									
1880.00	75.29	265	2.4	H	13.8	0.45	8.84	22.19	33
1880.00	76.62	144	1.9	V	12.9	0.45	8.84	21.29	33

LTE Band 4:**Maximum Output Power**

Bandwidth (MHz)	Modulation	RB size/RB Offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
1.4	QPSK	RB Size=1, RB Offset=0	23.42	23.77	23.24
		RB Size=1, RB Offset=2	23.31	23.72	23.13
		RB Size=1, RB Offset=5	23.52	23.88	23.28
		RB Size=3, RB Offset=0	22.98	23.25	22.84
		RB Size=3, RB Offset=1	22.85	23.21	22.79
		RB Size=3, RB Offset=2	23.10	23.29	22.96
		RB Size=6, RB Offset=0	22.34	22.79	22.45
	16QAM	RB Size=1, RB Offset=0	23.45	23.76	23.28
		RB Size=1, RB Offset=2	23.32	23.71	23.16
		RB Size=1, RB Offset=5	23.52	23.82	23.34
		RB Size=3, RB Offset=0	23.12	23.32	23.04
		RB Size=3, RB Offset=1	23.07	23.23	23.00
		RB Size=3, RB Offset=2	23.17	23.44	23.15
		RB Size=6, RB Offset=0	22.41	22.79	22.64
3.0	QPSK	RB Size=1, RB Offset=0	23.32	23.75	23.41
		RB Size=1, RB Offset=7	23.20	23.69	23.37
		RB Size=1, RB Offset=14	23.36	23.84	23.46
		RB Size=8, RB Offset=0	23.01	23.27	23.08
		RB Size=8, RB Offset=4	22.98	23.19	23.04
		RB Size=8, RB Offset=7	23.10	23.33	23.12
		RB Size=15, RB Offset=0	22.56	22.89	22.45
	16QAM	RB Size=1, RB Offset=0	23.41	23.75	23.47
		RB Size=1, RB Offset=7	23.29	23.65	23.35
		RB Size=1, RB Offset=14	23.51	23.87	23.53
		RB Size=8, RB Offset=0	23.16	23.41	23.21
		RB Size=8, RB Offset=4	23.13	23.36	23.09
		RB Size=8, RB Offset=7	23.21	23.45	23.27
		RB Size=15, RB Offset=0	22.46	22.90	22.52

Bandwidth (MHz)	Modulation	RB size/RB Offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
5.0	QPSK	RB Size=1, RB Offset=0	23.47	23.90	23.52
		RB Size=1, RB Offset=12	23.40	23.79	23.41
		RB Size=1, RB Offset=24	23.54	23.98	23.63
		RB Size=12, RB Offset=0	23.13	23.48	23.25
		RB Size=12, RB Offset=6	23.03	23.38	23.21
		RB Size=12, RB Offset=11	23.20	23.52	23.35
		RB Size=25, RB Offset=0	22.42	22.88	22.31
	16QAM	RB Size=1, RB Offset=0	23.62	23.90	23.57
		RB Size=1, RB Offset=12	23.57	23.85	23.46
		RB Size=1, RB Offset=24	23.73	23.99	23.66
		RB Size=12, RB Offset=0	23.24	23.43	23.11
		RB Size=12, RB Offset=6	23.14	23.34	23.00
		RB Size=12, RB Offset=11	23.33	23.56	23.18
		RB Size=25, RB Offset=0	22.48	22.86	22.54
10.0	QPSK	RB Size=1, RB Offset=0	23.52	23.88	23.41
		RB Size=1, RB Offset=24	23.46	23.79	23.37
		RB Size=1, RB Offset=49	23.65	23.92	23.52
		RB Size=25, RB Offset=0	23.16	23.47	23.18
		RB Size=25, RB Offset=12	23.05	23.37	23.08
		RB Size=25, RB Offset=24	23.24	23.52	23.23
		RB Size=50, RB Offset=0	22.34	22.93	22.48
	16QAM	RB Size=1, RB Offset=0	23.56	23.83	23.32
		RB Size=1, RB Offset=24	23.51	23.80	23.29
		RB Size=1, RB Offset=49	23.61	23.86	23.36
		RB Size=25, RB Offset=0	23.11	23.34	23.04
		RB Size=25, RB Offset=12	23.07	23.31	22.98
		RB Size=25, RB Offset=24	23.19	23.45	23.13
		RB Size=50, RB Offset=0	22.53	22.91	22.46

Bandwidth (MHz)	Modulation	RB size/RB Offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
15.0	QPSK	RB Size=1, RB Offset=0	23.52	23.93	23.42
		RB Size=1, RB Offset=37	23.45	23.86	23.38
		RB Size=1, RB Offset=74	23.57	24.03	23.47
		RB Size=36, RB Offset=0	23.24	23.62	23.31
		RB Size=36, RB Offset=18	23.16	23.56	23.28
		RB Size=36, RB Offset=37	23.28	23.67	23.38
		RB Size=75, RB Offset=0	23.12	23.34	23.05
	16QAM	RB Size=1, RB Offset=0	23.57	23.86	23.49
		RB Size=1, RB Offset=37	23.52	23.79	23.38
		RB Size=1, RB Offset=74	23.62	23.99	23.59
		RB Size=36, RB Offset=0	23.26	23.47	23.17
		RB Size=36, RB Offset=18	23.16	23.36	23.04
		RB Size=36, RB Offset=37	23.32	23.54	23.26
		RB Size=75, RB Offset=0	22.46	22.95	22.65
20.0	QPSK	RB Size=1, RB Offset=0	23.51	23.81	23.43
		RB Size=1, RB Offset=49	23.41	23.69	23.32
		RB Size=1, RB Offset=99	23.61	23.86	23.49
		RB Size=50, RB Offset=0	23.22	23.43	23.13
		RB Size=50, RB Offset=24	23.18	23.39	23.08
		RB Size=50, RB Offset=49	23.29	23.54	23.19
		RB Size=100, RB Offset=0	22.42	22.91	22.34
	16QAM	RB Size=1, RB Offset=0	23.78	24.03	23.84
		RB Size=1, RB Offset=49	23.73	23.95	23.77
		RB Size=1, RB Offset=99	23.85	24.06	23.95
		RB Size=50, RB Offset=0	23.32	23.65	23.21
		RB Size=50, RB Offset=24	23.22	23.56	23.09
		RB Size=50, RB Offset=49	23.41	23.69	23.30
		RB Size=100, RB Offset=0	23.12	23.31	23.16

Peak-to-average ratio (PAR)

Modulation	Middle Channel (dB)	PAR Limit (dB)	Result
16QAM (1RB Size)	10.40	13	Pass
16QAM (100%RB Size)	7.15	13	Pass

QPSK:

Frequency (MHz)	Receiver Reading (dBμV)	Turn table Angle Degree	Rx Antenna		Substituted			Absolute Level (dBm)	Limit (dBm)
			Height (m)	Polar (H/V)	Level (dBm)	Cable Loss (dB)	Antenna Gain (dB)		
Middle Channel									
1.4 MHz Bandwidth									
1732.50	79.77	315	2.1	H	16.2	0.40	8.52	24.32	30
1732.50	77.74	279	2.0	V	12.2	0.40	8.52	20.32	30
3 MHz Bandwidth									
1732.50	79.37	209	2.0	H	15.8	0.40	8.52	23.92	30
1732.50	77.94	84	1.0	V	12.4	0.40	8.52	20.52	30
5 MHz Bandwidth									
1732.50	77.67	303	1.8	H	14.1	0.40	8.52	22.22	30
1732.50	77.34	51	1.1	V	11.8	0.40	8.52	19.92	30
10 MHz Bandwidth									
1732.50	76.67	0	1.4	H	13.1	0.40	8.52	21.22	30
1732.50	76.44	212	1.9	V	10.9	0.40	8.52	19.02	30
15 MHz Bandwidth									
1732.50	76.27	33	1.5	H	12.7	0.40	8.52	20.82	30
1732.50	75.04	273	1.6	V	9.5	0.40	8.52	17.62	30
20 MHz Bandwidth									
1732.50	75.87	64	1.4	H	12.3	0.40	8.52	20.42	30
1732.50	74.74	138	1.4	V	9.2	0.40	8.52	17.32	30

16QAM:

Frequency (MHz)	Receiver Reading (dBμV)	Turn table Angle Degree	Rx Antenna		Substituted			Absolute Level (dBm)	Limit (dBm)
			Height (m)	Polar (H/V)	Level (dBm)	Cable Loss (dB)	Antenna Gain (dB)		
Middle Channel									
1.4 MHz Bandwidth									
1732.50	79.37	298	2.2	H	15.8	0.40	8.52	23.92	30
1732.50	79.84	30	1.0	V	14.3	0.40	8.52	22.42	30
3 MHz Bandwidth									
1732.50	79.27	161	1.8	H	15.7	0.40	8.52	23.82	30
1732.50	79.94	35	2.0	V	14.4	0.40	8.52	22.52	30
5 MHz Bandwidth									
1732.50	78.87	156	1.0	H	15.3	0.40	8.52	23.42	30
1732.50	79.14	262	1.5	V	13.6	0.40	8.52	21.72	30
10 MHz Bandwidth									
1732.50	78.67	333	1.3	H	15.1	0.40	8.52	23.22	30
1732.50	78.94	137	1.1	V	13.4	0.40	8.52	21.52	30
15 MHz Bandwidth									
1732.50	76.87	17	1.4	H	13.3	0.40	8.52	21.42	30
1732.50	77.04	196	1.8	V	11.5	0.40	8.52	19.62	30
20 MHz Bandwidth									
1732.50	76.37	159	1.6	H	12.8	0.40	8.52	20.92	30
1732.50	76.74	267	1.2	V	11.2	0.40	8.52	19.32	30

LTE Band 7:

Bandwidth (MHz)	Modulation	RB size/RB Offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
5	QPSK	RB Size=1, RB Offset=0	21.63	22.18	21.62
		RB Size=1, RB Offset=12	21.58	22.07	21.50
		RB Size=1, RB Offset=24	21.76	22.27	21.69
		RB Size=12, RB Offset=0	21.26	21.56	21.32
		RB Size=12, RB Offset=6	21.22	21.52	21.24
		RB Size=12, RB Offset=11	21.29	21.64	21.40
		RB Size=25, RB Offset=0	20.68	21.05	20.78
	16QAM	RB Size=1, RB Offset=0	21.76	22.18	21.84
		RB Size=1, RB Offset=12	21.69	22.13	21.73
		RB Size=1, RB Offset=24	21.88	22.28	21.91
		RB Size=12, RB Offset=0	21.42	21.68	21.39
		RB Size=12, RB Offset=6	21.37	21.64	21.31
		RB Size=12, RB Offset=11	21.51	21.72	21.42
		RB Size=25, RB Offset=0	21.03	21.13	20.86
10	QPSK	RB Size=1, RB Offset=0	21.94	22.25	21.88
		RB Size=1, RB Offset=24	21.90	22.16	21.84
		RB Size=1, RB Offset=49	22.03	22.33	21.97
		RB Size=25, RB Offset=0	21.62	21.84	21.52
		RB Size=25, RB Offset=12	21.57	21.71	21.41
		RB Size=25, RB Offset=24	21.71	21.89	21.60
		RB Size=50, RB Offset=0	21.17	21.31	21.21
	16QAM	RB Size=1, RB Offset=0	21.63	22.14	21.81
		RB Size=1, RB Offset=24	21.51	22.01	21.71
		RB Size=1, RB Offset=49	21.68	22.24	21.84
		RB Size=25, RB Offset=0	21.23	21.53	21.34
		RB Size=25, RB Offset=12	21.19	21.47	21.26
		RB Size=25, RB Offset=24	21.31	21.58	21.37
		RB Size=50, RB Offset=0	20.63	21.08	20.75

Bandwidth (MHz)	Modulation	RB size/RB Offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
15	QPSK	RB Size=1, RB Offset=0	21.95	22.58	21.87
		RB Size=1, RB Offset=37	21.84	22.49	21.79
		RB Size=1, RB Offset=74	22.00	22.62	21.99
		RB Size=36, RB Offset=0	21.42	21.87	21.54
		RB Size=36, RB Offset=18	21.29	21.79	21.47
		RB Size=36, RB Offset=37	21.47	21.93	21.61
		RB Size=75, RB Offset=0	21.14	20.9	21.28
	16QAM	RB Size=1, RB Offset=0	21.82	22.14	21.81
		RB Size=1, RB Offset=37	21.70	22.06	21.75
		RB Size=1, RB Offset=74	21.86	22.26	21.87
		RB Size=36, RB Offset=0	21.32	21.63	21.24
		RB Size=36, RB Offset=18	21.25	21.54	21.12
		RB Size=36, RB Offset=37	21.43	21.70	21.37
		RB Size=75, RB Offset=0	21.01	21.23	21.03
20	QPSK	RB Size=1, RB Offset=0	21.88	22.17	21.93
		RB Size=1, RB Offset=49	21.84	22.07	21.84
		RB Size=1, RB Offset=99	21.92	22.28	22.06
		RB Size=50, RB Offset=0	21.37	21.54	21.26
		RB Size=50, RB Offset=24	21.28	21.48	21.17
		RB Size=50, RB Offset=49	21.46	21.60	21.32
		RB Size=100, RB Offset=0	20.85	21.09	20.78
	16QAM	RB Size=1, RB Offset=0	21.94	22.33	21.97
		RB Size=1, RB Offset=49	21.87	22.25	21.93
		RB Size=1, RB Offset=99	22.00	22.44	22.07
		RB Size=50, RB Offset=0	21.31	21.72	21.43
		RB Size=50, RB Offset=24	21.26	21.67	21.37
		RB Size=50, RB Offset=49	21.37	21.84	21.48
		RB Size=100, RB Offset=0	21.01	21.17	21.03

Peak-to-average ratio (PAR)

Modulation	Middle Channel (dB)	PAR Limit (dB)	Result
16QAM (1RB Size)	11.62	13	Pass
16QAM (100%RB Size)	7.51	13	Pass

EIRP:**QPSK:**

Frequency (MHz)	Receiver Reading (dBμV)	Turn table Angle Degree	Rx Antenna		Substituted			Absolute Level (dBm)	Limit (dBm)
			Height (m)	Polar (H/V)	Level (dBm)	Cable Loss (dB)	Antenna Gain (dB)		
Middle Channel									
5 MHz Bandwidth									
2535.00	76.46	40	2.0	H	13.9	0.49	10.10	23.51	33
2535.00	72.47	105	1.3	V	9.2	0.49	10.10	18.81	33
10 MHz Bandwidth									
2535.00	75.66	25	2.5	H	13.1	0.49	10.10	22.71	33
2535.00	70.87	196	2.3	V	7.6	0.49	10.10	17.21	33
15 MHz Bandwidth									
2535.00	74.66	81	2.2	H	12.1	0.49	10.10	21.71	33
2535.00	70.47	160	1.5	V	7.2	0.49	10.10	16.81	33
20 MHz Bandwidth									
2535.00	73.86	16	2.4	H	11.3	0.49	10.10	20.91	33
2535.00	69.77	181	1.7	V	6.5	0.49	10.10	16.11	33

16QAM:

Frequency (MHz)	Receiver Reading (dBμV)	Turn table Angle Degree	Rx Antenna		Substituted			Absolute Level (dBm)	Limit (dBm)
			Height (m)	Polar (H/V)	Level (dBm)	Cable Loss (dB)	Antenna Gain (dB)		
Middle Channel									
5 MHz Bandwidth									
2535.00	76.66	280	1.3	H	14.1	0.49	10.10	23.71	33
2535.00	73.07	182	2.4	V	9.8	0.49	10.10	19.41	33
10 MHz Bandwidth									
2535.00	75.86	70	2.1	H	13.3	0.49	10.10	22.91	33
2535.00	73.27	222	2.5	V	10.0	0.49	10.10	19.61	33
15 MHz Bandwidth									
2535.00	74.56	139	2.1	H	12.0	0.49	10.10	21.61	33
2535.00	73.07	93	2.4	V	9.8	0.49	10.10	19.41	33
20 MHz Bandwidth									
2535.00	73.86	99	1.4	H	11.3	0.49	10.10	20.91	33
2535.00	72.27	280	1.4	V	9.0	0.49	10.10	18.61	33

LTE Band 12:

Bandwidth (MHz)	Modulation	RB size/RB Offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
1.4	QPSK	RB Size=1, RB Offset=0	22.54	23.22	22.84
		RB Size=1, RB Offset=2	22.41	23.16	22.74
		RB Size=1, RB Offset=5	22.61	23.31	22.90
		RB Size=3, RB Offset=0	22.32	22.64	22.24
		RB Size=3, RB Offset=1	22.22	22.60	22.14
		RB Size=3, RB Offset=2	22.43	22.71	22.29
		RB Size=6, RB Offset=0	21.63	21.98	21.57
	16QAM	RB Size=1, RB Offset=0	22.76	23.10	22.89
		RB Size=1, RB Offset=2	22.66	23.02	22.77
		RB Size=1, RB Offset=5	22.85	23.19	22.95
		RB Size=3, RB Offset=0	22.37	22.68	22.46
		RB Size=3, RB Offset=1	22.31	22.57	22.34
		RB Size=3, RB Offset=2	22.41	22.76	22.59
		RB Size=6, RB Offset=0	21.78	22.12	21.86
3	QPSK	RB Size=1, RB Offset=0	22.79	23.07	22.82
		RB Size=1, RB Offset=7	22.73	23.03	22.70
		RB Size=1, RB Offset=14	22.32	22.64	22.38
		RB Size=8, RB Offset=0	22.27	22.52	22.31
		RB Size=8, RB Offset=4	22.38	22.69	22.49
		RB Size=8, RB Offset=7	21.87	22.23	21.95
		RB Size=15, RB Offset=0	21.78	22.09	21.84
	16QAM	RB Size=1, RB Offset=0	22.73	23.07	22.85
		RB Size=1, RB Offset=7	22.70	22.95	22.72
		RB Size=1, RB Offset=14	22.80	23.13	22.90
		RB Size=8, RB Offset=0	22.37	22.69	22.41
		RB Size=8, RB Offset=4	22.25	22.62	22.31
		RB Size=8, RB Offset=7	22.43	22.74	22.53
		RB Size=15, RB Offset=0	22.03	22.22	22.07

Bandwidth (MHz)	Modulation	RB size/RB Offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
5	QPSK	RB Size=1, RB Offset=0	22.78	23.15	22.84
		RB Size=1, RB Offset=12	22.70	23.08	22.72
		RB Size=1, RB Offset=24	22.88	23.26	22.91
		RB Size=12, RB Offset=0	22.41	22.61	22.32
		RB Size=12, RB Offset=6	22.35	22.57	22.25
		RB Size=12, RB Offset=11	22.52	22.71	22.36
		RB Size=25, RB Offset=0	21.03	20.85	21.13
	16QAM	RB Size=1, RB Offset=0	22.74	23.17	22.85
		RB Size=1, RB Offset=12	22.63	23.07	22.73
		RB Size=1, RB Offset=24	22.79	23.25	22.90
		RB Size=12, RB Offset=0	22.46	22.68	22.39
		RB Size=12, RB Offset=6	22.40	22.60	22.29
		RB Size=12, RB Offset=11	22.52	22.77	22.46
		RB Size=25, RB Offset=0	21.78	22.21	21.89
10	QPSK	RB Size=1, RB Offset=0	22.87	23.39	22.96
		RB Size=1, RB Offset=24	22.77	23.35	22.90
		RB Size=1, RB Offset=49	22.97	23.42	23.02
		RB Size=25, RB Offset=0	22.04	22.23	22.01
		RB Size=25, RB Offset=12	21.97	22.18	21.91
		RB Size=25, RB Offset=24	22.13	22.33	22.13
		RB Size=50, RB Offset=0	21.15	20.98	21.27
	16QAM	RB Size=1, RB Offset=0	22.84	23.25	22.92
		RB Size=1, RB Offset=24	22.77	23.14	22.83
		RB Size=1, RB Offset=49	22.91	23.30	23.05
		RB Size=25, RB Offset=0	22.46	22.84	22.52
		RB Size=25, RB Offset=12	22.37	22.76	22.42
		RB Size=25, RB Offset=24	22.50	22.92	22.61
		RB Size=50, RB Offset=0	21.75	22.10	21.84

Peak-to-average ratio (PAR)

Modulation	Middle Channel (dB)	PAR Limit (dB)	Result
16QAM (1RB Size)	2.35	13	Pass
16QAM (100%RB Size)	6.60	13	Pass

EIRP:**QPSK:**

Frequency (MHz)	Receiver Reading (dBμV)	Turn table Angle Degree	Rx Antenna		Substituted			Absolute Level (dBm)	Limit (dBm)
			Height (m)	Polar (H/V)	Level (dBm)	Cable Loss (dB)	Antenna Gain (dB)		
Middle Channel									
1.4 MHz Bandwidth									
707.50	95.31	335	2.0	H	18.0	0.26	4.25	21.99	34.77
707.50	86.87	142	1.4	V	12.6	0.26	4.25	16.59	34.77
3 MHz Bandwidth									
707.50	94.81	297	2.1	H	17.5	0.26	4.25	21.49	34.77
707.50	86.77	214	1.7	V	12.5	0.26	4.25	16.49	34.77
5 MHz Bandwidth									
707.50	94.21	339	1.6	H	16.9	0.26	4.25	20.89	34.77
707.50	86.17	152	1.3	V	11.9	0.26	4.25	15.89	34.77
10 MHz Bandwidth									
707.50	93.11	267	2.4	H	15.8	0.26	4.25	19.79	34.77
707.50	85.87	260	1.1	V	11.6	0.26	4.25	15.59	34.77

16QAM:

Frequency (MHz)	Receiver Reading (dBμV)	Turn table Angle Degree	Rx Antenna		Substituted			Absolute Level (dBm)	Limit (dBm)
			Height (m)	Polar (H/V)	Level (dBm)	Cable Loss (dB)	Antenna Gain (dB)		
Middle Channel									
1.4 MHz Bandwidth									
707.5	95.61	69	2.4	H	18.3	0.26	4.25	22.29	34.77
707.5	86.67	113	1.3	V	12.4	0.26	4.25	16.39	34.77
3 MHz Bandwidth									
707.5	95.11	80	1.6	H	17.8	0.26	4.25	21.79	34.77
707.5	86.67	11	1.1	V	12.4	0.26	4.25	16.39	34.77
5 MHz Bandwidth									
707.5	93.51	282	2.3	H	16.2	0.26	4.25	20.19	34.77
707.5	86.47	278	1.9	V	12.2	0.26	4.25	16.19	34.77
10 MHz Bandwidth									
707.5	93.01	247	1.5	H	15.7	0.26	4.25	19.69	34.77
707.5	86.17	242	2.4	V	11.9	0.26	4.25	15.89	34.77

LTE Band 17:

Bandwidth (MHz)	Modulation	RB size/RB Offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
5.0	QPSK	RB Size=1, RB Offset=0	22.87	23.04	22.97
		RB Size=1, RB Offset=12	22.82	22.95	22.89
		RB Size=1, RB Offset=24	22.98	23.16	23.01
		RB Size=12, RB Offset=0	22.42	22.74	22.43
		RB Size=12, RB Offset=6	22.35	22.67	22.32
		RB Size=12, RB Offset=11	22.47	22.77	22.48
		RB Size=25, RB Offset=0	21.68	22.02	21.72
	16QAM	RB Size=1, RB Offset=0	22.85	23.05	22.91
		RB Size=1, RB Offset=12	22.76	23.01	22.82
		RB Size=1, RB Offset=24	22.95	23.16	23.02
		RB Size=12, RB Offset=0	22.47	22.78	22.38
		RB Size=12, RB Offset=6	22.40	22.75	22.28
		RB Size=12, RB Offset=11	22.51	22.87	22.50
		RB Size=25, RB Offset=0	21.68	22.14	21.75
10.0	QPSK	RB Size=1, RB Offset=0	22.89	23.18	22.95
		RB Size=1, RB Offset=24	22.85	23.12	22.84
		RB Size=1, RB Offset=49	22.95	23.22	22.99
		RB Size=25, RB Offset=0	22.32	22.52	22.24
		RB Size=25, RB Offset=12	22.26	22.43	22.20
		RB Size=25, RB Offset=24	22.42	22.56	22.36
		RB Size=50, RB Offset=0	21.73	22.08	21.78
	16QAM	RB Size=1, RB Offset=0	22.75	23.13	22.63
		RB Size=1, RB Offset=24	22.63	23.07	22.57
		RB Size=1, RB Offset=49	22.88	23.23	22.74
		RB Size=25, RB Offset=0	22.37	22.74	22.29
		RB Size=25, RB Offset=12	22.26	22.71	22.19
		RB Size=25, RB Offset=24	22.50	22.82	22.35
		RB Size=50, RB Offset=0	21.71	22.05	22.65

Peak-to-average ratio (PAR)

Modulation	Middle Channel (dB)	PAR Limit (dB)	Result
16QAM (1RB Size)	3.00	13	Pass
16QAM (100%RB Size)	6.34	13	Pass

ERP:**QPSK:**

Frequency (MHz)	Receiver Reading (dBμV)	Turn table Angle Degree	Rx Antenna		Substituted			Absolute Level (dBm)	Limit (dBm)
			Height (m)	Polar (H/V)	Level (dBm)	Cable Loss (dB)	Antenna Gain (dB)		
Middle Channel									
5 MHz Bandwidth									
710.00	95.01	82	2.0	H	17.7	0.26	4.25	21.69	34.77
710.00	85.87	296	2.4	V	11.6	0.26	4.25	15.59	34.77
10 MHz Bandwidth									
710.00	93.51	316	2.2	H	16.2	0.26	4.25	20.19	34.77
710.00	87.27	260	2.4	V	13.0	0.26	4.25	16.99	34.77

16QAM:

Frequency (MHz)	Receiver Reading (dBμV)	Turn table Angle Degree	Rx Antenna		Substituted			Absolute Level (dBm)	Limit (dBm)
			Height (m)	Polar (H/V)	Level (dBm)	Cable Loss (dB)	Antenna Gain (dB)		
Middle Channel									
5 MHz Bandwidth									
710.00	94.41	254	2.2	H	17.1	0.26	4.25	21.09	34.77
710.00	87.07	57	1.7	V	12.8	0.26	4.25	16.79	34.77
10 MHz Bandwidth									
710.00	94.11	150	1.0	H	16.8	0.26	4.25	20.79	34.77
710.00	86.77	125	1.3	V	12.5	0.26	4.25	16.49	34.77

Note:

All above data were tested with no amplifier

Absolute Level = SG Level - Cable loss + Antenna Gain

Margin = Limit- Absolute Level

FCC §2.1049, §22.917, §22.905 & §24.238 & §27.53 - OCCUPIED BANDWIDTH


Applicable Standard

FCC 47 §2.1049, §22.917, §22.905, §24.238 and §27.53.

Test Procedure

The RF output of the transmitter was connected to the simulator and the spectrum analyzer through sufficient attenuation.

The resolution bandwidth of the spectrum analyzer was set at 1% to 5% of the anticipated emission bandwidth and the 26 dB & 99% bandwidth was recorded.



Test Data

Environmental Conditions

Temperature:	24~25 °C
Relative Humidity:	48~50 %
ATM Pressure:	100.0~101.0 kPa

The testing was performed by Echo Wu from 2017-06-17 to 2017-06-20.

EUT operation mode: Transmitting

Test Result: Compliance. Please refer to the following tables and plots.

Cellular Band (Part 22H)

Mode	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Emission Bandwidth (kHz)
GSM(GMSK)	836.6	248.5	312.6
EGPRS(8PSK)	836.6	252.5	324.6

Mode	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Emission Bandwidth (MHz)
RMC (BPSK)	836.6	4.208	4.850
HSUPA (BPSK)	836.6	4.208	4.870
HSDPA (16QAM)	836.6	4.208	4.890



PCS Band (Part 24E)

Mode	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Emission Bandwidth (kHz)
GSM(GMSK)	1880.0	244.5	316.6
EGPRS(8PSK)	1880.0	256.5	332.7


Mode	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Emission Bandwidth (MHz)
RMC (BPSK)	1880.0	4.208	4.890
HSUPA (BPSK)	1880.0	4.208	4.870
HSDPA (16QAM)	1880.0	4.208	4.890

AWS Band (Part 27)


Mode	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Emission Bandwidth (MHz)
RMC (BPSK)	1880.0	4.188	4.890
HSUPA (BPSK)	1880.0	4.188	4.870
HSDPA (16QAM)	1880.0	4.208	4.890


Cellular Band (Part 22H)**26 dB Emissions & 99% Occupied Bandwidth for GSM (GMSK) Mode****26 dB Emissions & 99% Occupied Bandwidth for EDGE Mode**



26 dB Emissions & 99% Occupied Bandwidth for RMC (BPSK) Mode





26 dB Emissions & 99% Occupied Bandwidth for HSUPA (BPSK) Mode




26 dB Emissions & 99% Occupied Bandwidth for HSDPA (16QAM) Mode

26 dB Emissions & 99% Occupied Bandwidth for EDGE Mode**26 dB Emissions & 99% Occupied Bandwidth for RMC (BPSK) Mode**


26 dB Emissions & 99% Occupied Bandwidth for HSUPA (BPSK) Mode**26 dB Emissions & 99% Occupied Bandwidth for HSDPA (16QAM) Mode**

AWS Band (Part 27)


26 dB Emissions & 99% Occupied Bandwidth for RMC (BPSK) Mode



26 dB Emissions & 99% Occupied Bandwidth for HSUPA (BPSK) Mode




26 dB Emissions & 99% Occupied Bandwidth for HSDPA (16QAM) Mode




LTE Band 2: (Middle Channel)

Bandwidth (MHz)	Modulation	99% Occupied Bandwidth (MHz)	26 dB Emission Bandwidth (MHz)
1.4	QPSK	1.105	1.263
	16QAM	1.089	1.279
3.0	QPSK	2.693	2.886
	16QAM	2.693	2.910
5.0	QPSK	4.549	4.990
	16QAM	4.569	5.070
10.0	QPSK	8.978	9.579
	16QAM	8.978	9.619
15.0	QPSK	13.527	14.910
	16QAM	13.527	14.970
20.0	QPSK	18.036	19.479
	16QAM	17.876	19.399

QPSK (1.4 MHz) - 99% Occupied Bandwidth, Middle channel



QPSK (1.4 MHz) - 26 dB Bandwidth, Middle channel



Ref Lvl 34 dBm
 Marker 1 [T1] 14.33 dBm
 1.88002525 GHz
 RBW 30 kHz
 VBW 100 kHz
 SWT 8 ms
 RF Att 30 dB
 Unit dBm



14 dB Offset
 14.33 dBm
 1.88002525 GHz
 1.08857715 MHz
 7.59 dBm
 1.87946413 GHz
 7.73 dBm
 1.88055271 GHz

-1MAX
 1MAX


Center 1.88 GHz
 280 kHz/
 Span 2.8 MHz

Date: 17. JUN. 2017 11:13:45


[illegible]







16-QAM (3.0 MHz) - 99% Occupied Bandwidth, Middle channel




16-QAM (3.0 MHz) - 26 dB Bandwidth, Middle channel




QPSK (5.0 MHz) - 99% Occupied Bandwidth, Middle channel**QPSK (5.0 MHz) - 26 dB Bandwidth, Middle channel**

16-QAM (5.0 MHz) - 99% Occupied Bandwidth, Middle channel**16-QAM (5.0 MHz) - 26 dB Bandwidth, Middle channel**


QPSK (10.0 MHz) - 99% Occupied Bandwidth, Middle channel




QPSK (10.0 MHz) - 26 dB Bandwidth, Middle channel



16-QAM (10.0 MHz) - 99% Occupied Bandwidth, Middle channel



16-QAM (10.0 MHz) - 26 dB Bandwidth, Middle channel



[illegible]

Ref Lvl 34 dBm

Marker 1 [T1 ndB] 26.00 dB

RBW 300 kHz RF Att 30 dB

VBW 1 MHz

SWT 5 ms Unit dBm

14 dB Offset

15.13 dBm

1.87792585 GHz

ndB 26.00 dB

BW 14.90981964 MHz

▽T1 [T1] -11.56 dBm

▽T2 [T1] -11.73 dBm

1.87257515 GHz

1.88748497 GHz

1MAX

1MA


Center 1.88 GHz

3 MHz/


Span 30 MHz



Date: 17. JUN. 2017 13:40:39



16-QAM (15.0 MHz) - 99% Occupied Bandwidth, Middle channel



16-QAM (15.0 MHz) - 26 dB Bandwidth, Middle channel






16-QAM (20.0 MHz) - 99% Occupied Bandwidth, Middle channel**16-QAM (20.0 MHz) - 26 dB Bandwidth, Middle channel**


LTE Band 4: (Middle Channel)

Bandwidth (MHz)	Modulation	99% Occupied Bandwidth (MHz)	26 dB Emission Bandwidth (MHz)
1.4	QPSK	1.105	1.274
	16QAM	1.099	1.268
3.0	QPSK	2.693	2.898
	16QAM	2.693	2.910
5.0	QPSK	4.549	5.050
	16QAM	4.549	5.010
10.0	QPSK	8.978	9.659
	16QAM	8.978	9.619
15.0	QPSK	13.527	14.790
	16QAM	13.527	14.609
20.0	QPSK	17.956	19.559
	16QAM	17.956	19.319


QPSK (1.4 MHz) - 99% Occupied Bandwidth, Middle channel




QPSK (1.4 MHz) - 26 dB Bandwidth, Middle channel




16-QAM (1.4 MHz) - 99% Occupied Bandwidth, Middle channel




16-QAM (1.4 MHz) - 26 dB Bandwidth, Middle channel




QPSK (3.0 MHz) - 99% Occupied Bandwidth, Middle channel




QPSK (3.0 MHz) - 26 dB Bandwidth, Middle channel







QPSK (5.0 MHz) - 99% Occupied Bandwidth, Middle channel







QPSK (5.0 MHz) - 26 dB Bandwidth, Middle channel






QPSK (10.0 MHz) - 99% Occupied Bandwidth, Middle channel**QPSK (10.0 MHz) - 26 dB Bandwidth, Middle channel**


16-QAM (10.0 MHz) - 99% Occupied Bandwidth, Middle channel**16-QAM (10.0 MHz) - 26 dB Bandwidth, Middle channel**



16-QAM (15.0 MHz) - 99% Occupied Bandwidth, Middle channel



16-QAM (15.0 MHz) - 26 dB Bandwidth, Middle channel



[illegible]



The screenshot displays a spectrum analyzer interface. At the top, a red diamond icon with 'A' and 'S' is visible. The main display area shows a blue trace of a signal with two markers, T1 and T2, indicated by green arrows. The trace shows a signal level around -10 dBm, rising to a peak of approximately 10 dBm between 1.728 GHz and 1.742 GHz, and then falling back to -10 dBm. The background is a grid with a center frequency of 1.7325 GHz and a span of 40 MHz. The y-axis represents power in dBm, ranging from -66 to 34. The x-axis represents frequency in MHz, ranging from 1.7325 to 1.7725. The right side of the screen shows various measurement parameters and their values.

Parameter	Value
Ref Lvl	34 dBm
Marker 1 [T1 ndB]	26.00 dB
BW	19.55911824 MHz
RBW	300 kHz
VBW	1 MHz
SWT	5 ms
RF Att	30 dB
Unit	dBm

Additional measurements and markers shown on the right side of the screen:

- 12.63 dBm
- 1.72869238 GHz
- 26.00 dB
- 19.55911824 MHz
- 16.16 dBm
- 1.7276052 GHz
- 14.55 dBm
- 1.74231964 GHz


At the bottom, the date and time are displayed: 17. JUN. 2017 13:55:17.

16-QAM (20.0 MHz) - 99% Occupied Bandwidth, Middle channel**16-QAM (20.0 MHz) - 26 dB Bandwidth, Middle channel**


LTE Band 7: (Middle Channel)



Bandwidth (MHz)	Modulation	99% Occupied Bandwidth (MHz)	26 dB Emission Bandwidth (MHz)
5.0	QPSK	4.529	4.990
	16QAM	4.549	5.050
10.0	QPSK	8.978	9.579
	16QAM	8.978	9.579
15.0	QPSK	13.527	14.669
	16QAM	13.587	14.850
20.0	QPSK	17.956	19.319
	16QAM	18.036	19.319



QPSK (5.0 MHz) - 99% Occupied Bandwidth, Middle channel





QPSK (5.0 MHz) - 26 dB Bandwidth, Middle channel




16-QAM (5.0 MHz) - 99% Occupied Bandwidth, Middle channel**16-QAM (5.0 MHz) - 26 dB Bandwidth, Middle channel**


QPSK (10.0 MHz) - 99% Occupied Bandwidth, Middle channel**QPSK (10.0 MHz) - 26 dB Bandwidth, Middle channel**







QPSK (15.0 MHz) - 99% Occupied Bandwidth, Middle channel




QPSK (15.0 MHz) - 26 dB Bandwidth, Middle channel




16-QAM (15.0 MHz) - 99% Occupied Bandwidth, Middle channel**16-QAM (15.0 MHz) - 26 dB Bandwidth, Middle channel**

QPSK (20.0 MHz) - 99% Occupied Bandwidth, Middle channel**QPSK (20.0 MHz) - 26 dB Bandwidth, Middle channel**

16-QAM (20.0 MHz) - 99% Occupied Bandwidth, Middle channel




16-QAM (20.0 MHz) - 26 dB Bandwidth, Middle channel



BAND 12:

Bandwidth (MHz)	Modulation	99% Occupied Bandwidth (MHz)	26 dB Emission Bandwidth (MHz)
1.4	QPSK	1.105	1.263
	16QAM	1.094	1.263
3.0	QPSK	2.693	2.910
	16QAM	2.681	2.946
5.0	QPSK	4.509	5.030
	16QAM	4.549	5.010
10.0	QPSK	8.978	9.659
	16QAM	8.978	9.699

QPSK (1.4 MHz) - 99% Occupied Bandwidth, Middle channel**QPSK (1.4 MHz) -26 dB Bandwidth, Middle channel**

[illegible]

Ref Lvl 34 dBm
 Marker 1 [T1 ndB] 26.00 dB
 BW 1.26252505 MHz
 RBW 30 kHz
 VBW 100 kHz
 SWT 8 ms
 RF Att 30 dB
 Unit dBm

14 dB Offset

15.42 dBm
 707.87875752 MHz
 26.00 dB
 1.26252505 MHz
 -11.68 dBm
 706.87434870 MHz
 -11.19 dBm
 708.13687375 MHz



1 BW



1 MAX



1 MA

Center 707.5 MHz 280 kHz/ Span 2.8 MHz


Date: 17. JUN. 2017 14:02:22

QPSK (3.0 MHz) - 99% Occupied Bandwidth, Middle channel**QPSK (3.0 MHz) - 26 dB Bandwidth, Middle channel**


16-QAM (3.0 MHz) - 99% Occupied Bandwidth, Middle channel**16-QAM (3.0 MHz) - 26 dB Bandwidth, Middle channel**



QPSK (5 MHz) - 99% Occupied Bandwidth, Middle channel**QPSK (5 MHz) - 26 dB Bandwidth, Middle channel**

16-QAM (5 MHz) - 99% Occupied Bandwidth, Middle channel



16-QAM (5MHz) - 26 dB Bandwidth, Middle channel




QPSK (10 MHz) - 99% Occupied Bandwidth, Middle channel**QPSK (10 MHz) - 26 dB Bandwidth, Middle channel**


LTE Band 17: (Middle Channel)



Bandwidth (MHz)	Modulation	99% Occupied Bandwidth (MHz)	26 dB Emission Bandwidth (MHz)
5.0	QPSK	4.529	5.050
	16QAM	4.529	5.030
10.0	QPSK	8.978	9.699
	16QAM	8.978	9.739

QPSK (5.0 MHz) - 99% Occupied Bandwidth, Middle channel




QPSK (5.0 MHz) - 26 dB Bandwidth, Middle channel






16-QAM (5.0 MHz) - 99% Occupied Bandwidth, Middle channel**16-QAM (5.0 MHz) - 26 dB Bandwidth, Middle channel**

QPSK (10.0 MHz) - 99% Occupied Bandwidth, Middle channel



QPSK (10.0 MHz) - 26 dB Bandwidth, Middle channel



16-QAM (10.0 MHz) - 99% Occupied Bandwidth, Middle channel**16-QAM (10.0 MHz) - 26 dB Bandwidth, Middle channel**

FCC §2.1051, §22.917(a) & §24.238(a); §27.53 (h) (m) - SPURIOUS EMISSIONS AT ANTENNA TERMINALS


Applicable Standard

FCC §2.1051, §22.917(a) and §24.238(a) and §27.53(h) (m).

The spectrum was to be investigated to the tenth harmonics of the highest fundamental frequency as specified in § 2.1051.

Test Procedure

The RF output of the transceiver was connected to a spectrum analyzer and simulator through appropriate attenuation. The resolution bandwidth of the spectrum analyzer was set at 1MHz. Sufficient scans were taken to show any out of band emissions up to 10th harmonic.



Test Data

Environmental Conditions

Temperature:	21~24 °C
Relative Humidity:	49~50 %
ATM Pressure:	100.0~101.0 kPa

The testing was performed by Echo Wu from 2017-06-17 to 2017-06-20.


Test result: Compliance,

EUT operation mode: transmitting

Please refer to the following plots.


Cellular Band (Part 22H)

30 MHz – 1 GHz (GSM Mode)




Fundamental test


1 GHz – 10 GHz (GSM Mode)



30 MHz – 1 GHz (WCDMA Mode)




1 GHz – 10 GHz (WCDMA Mode)






PCS Band (Part 24E)



30 MHz – 1 GHz (GSM Mode)



1 GHz – 2 GHz (GSM Mode)




2 GHz – 20 GHz (GSM Mode)**30 MHz – 1 GHz (WCDMA Mode)**


1 GHz – 2 GHz (WCDMA Mode)**2 GHz – 20 GHz (WCDMA Mode)**



AWS Band (Part 27)

30 MHz – 1 GHz (WCDMA Mode)




1 GHz – 2 GHz (WCDMA Mode)




2 GHz – 20 GHz (WCDMA Mode)**LTE Band 2:****30 MHz - 1 GHz (1.4 MHz, Middle Channel)**


1 GHz – 2 GHz (1.4 MHz, Middle Channel)




2 GHz – 20 GHz (1.4 MHz, Middle Channel)




30 MHz - 1 GHz (3.0 MHz, Middle Channel)




1 GHz – 2 GHz (3.0 MHz, Middle Channel)




2 GHz – 20 GHz (3.0 MHz, Middle Channel)




30 MHz - 1 GHz (5.0 MHz, Middle Channel)




1 GHz – 2 GHz (5.0 MHz, Middle Channel)




2 GHz – 20 GHz (5.0 MHz, Middle Channel)




30 MHz - 1 GHz (10.0 MHz, Middle Channel)




1 GHz – 2 GHz (10.0 MHz, Middle Channel)




2 GHz – 20 GHz (10.0 MHz, Middle Channel)




30 MHz - 1 GHz (15.0 MHz, Middle Channel)




1 GHz – 2 GHz (15.0 MHz, Middle Channel)




2 GHz – 20 GHz (15.0 MHz, Middle Channel)





30 MHz - 1 GHz (20.0 MHz, Middle Channel)




1 GHz – 2 GHz (20.0 MHz, Middle Channel)




2 GHz –20 GHz (20.0 MHz, Middle Channel)**LTE Band 4:****30 MHz - 1 GHz (1.4 MHz, Middle Channel)**


1 GHz – 2 GHz (1.4 MHz, Middle Channel)




2 GHz – 20 GHz (1.4 MHz, Middle Channel)




30 MHz - 1 GHz (3.0 MHz, Middle Channel)




1 GHz - 2 GHz (3.0 MHz, Middle Channel)




2 GHz – 20 GHz (3.0 MHz, Middle Channel)




30 MHz - 1 GHz (5.0 MHz, Middle Channel)




1 GHz – 2 GHz (5.0 MHz, Middle Channel)




2 GHz – 20 GHz (5.0 MHz, Middle Channel)





30 MHz - 1 GHz (10.0 MHz, Middle Channel)




1 GHz - 2 GHz (10.0 MHz, Middle Channel)




2 GHz – 20 GHz (10.0 MHz, Middle Channel)**30 MHz - 1 GHz (15.0 MHz, Middle Channel)**


1 GHz – 2 GHz (15.0 MHz, Middle Channel)




2 GHz – 20 GHz (15.0 MHz, Middle Channel)





30 MHz - 1 GHz (20.0 MHz, Middle Channel)




1 GHz - 2 GHz (20.0 MHz, Middle Channel)






2 GHz – 20 GHz (20.0 MHz, Middle Channel)**LTE Band 7:****30 MHz – 1 GHz (5.0 MHz, Middle Channel)**

1 GHz – 3.0 GHz (5.0 MHz, Middle Channel)




3.0 GHz – 26 GHz (5.0 MHz, Middle Channel)




30 MHz – 1.0 GHz (10.0 MHz, Middle Channel)**1 GHz – 3 GHz (10.0 MHz, Middle Channel)**

Fundamental test


3 GHz – 26 GHz (10.0 MHz, Middle Channel)




30 MHz – 1 GHz (15.0 MHz, Middle Channel)




1 GHz – 3 GHz (15.0 MHz, Middle Channel)




3 GHz – 26 GHz (15.0 MHz, Middle Channel)





30 MHz – 1 GHz (20.0 MHz, Middle Channel)




1 GHz – 3 GHz (20.0 MHz, Middle Channel)




3 GHz – 26 GHz (20.0 MHz, Middle Channel)**LTE Band 12:****30 MHz - 1 GHz (1.4 MHz, Middle Channel)**

1 GHz – 10 GHz (1.4 MHz, Middle Channel)




30 MHz - 1 GHz (3.0 MHz, Middle Channel)



1 GHz – 10 GHz (3.0 MHz, Middle Channel)




30 MHz - 1 GHz (5.0 MHz, Middle Channel)




1 GHz – 10 GHz (5.0 MHz, Middle Channel)



30 MHz - 1 GHz (10.0 MHz, Middle Channel)




1 GHz – 10 GHz (10.0 MHz, Middle Channel)




LTE Band 17:


30 MHz - 1 GHz (5.0 MHz, Middle Channel)




1 GHz – 10 GHz (5.0 MHz, Middle Channel)



30 MHz - 1 GHz (10.0 MHz, Middle Channel)



1 GHz – 10 GHz (10.0 MHz, Middle Channel)



FCC § 2.1053; § 22.917 (a); § 24.238 (a); § 27.53 (h)(m) SPURIOUS RADIATED EMISSIONS

Applicable Standard

FCC § 2.1053, § 22.917(a) and § 24.238(a) and § 27.53(h)(m)

For mobile digital stations, the attenuation factor shall be not less than $40 + 10 \log (P)$ dB on all frequencies between the channel edge and 5 megahertz from the channel edge, $43 + 10 \log (P)$ dB on all frequencies between 5 megahertz and X megahertz from the channel edge, and $55 + 10 \log (P)$ dB on all frequencies more than X megahertz from the channel edge, where X is the greater of 6 megahertz or the actual emission bandwidth as defined in paragraph (m)(6) of this section. In addition, the attenuation factor shall not be less than $43 + 10 \log (P)$ dB on all frequencies between 2490.5 MHz and 2496 MHz and $55 + 10 \log (P)$ dB at or below 2490.5 MHz. Mobile Satellite Service licensees operating on frequencies below 2495 MHz may also submit a documented interference complaint against BRS licensees operating on channel BRS Channel 1 on the same terms and conditions as adjacent channel BRS or EBS licensees.

Test Procedure

The transmitter was placed on a wooden turntable, and it was transmitting into a non-radiating load which was also placed on the turntable.

The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the receiving antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis.

The frequency range up to tenth harmonic of the fundamental frequency was investigated.

Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution.

Spurious emissions in dB = $10 \lg (\text{TX pwr in Watts}/0.001)$ – the absolute level

Spurious attenuation limit in dB = $43 + 10 \log_{10} (\text{power out in Watts})$

Spurious attenuation limit in dB = $55 + 10 \log_{10} (\text{power out in Watts})$

Test Data

Environmental Conditions

Temperature:	22 °C
Relative Humidity:	48 %
ATM Pressure:	101.0 kPa

The testing was performed by Layne Li on 2017-06-17.

EUT operation mode: Transmitting

Pre-scan with Low, Middle and High channel, the worst case as below:

30 MHz ~ 10 GHz:

Cellular Band (Part 22H)

Frequency (MHz)	Receiver Reading (dBμV)	Turntable Angle Degree	Rx Antenna		Substituted			Absolute Level (dBm)	FCC Part 22H	
			Height (m)	Polar (H/V)	Level (dBm)	Cable Loss (dB)	Antenna Gain (dB)		Limit (dBm)	Margin (dB)
GSM Mode, Middle channel										
242.56	41.28	14	1.7	H	-63.7	0.14	2.05	-61.79	-13	48.79
242.56	41.02	292	2.4	V	-64.4	0.14	2.05	-62.49	-13	49.49
1673.20	39.89	176	1.4	H	-61.9	0.40	8.52	-53.81	-13	40.81
1673.20	44.06	228	1.9	V	-59.7	0.40	8.52	-51.61	-13	38.61
WCDMA Mode, Middle channel										
242.56	41.26	228	2.4	H	-63.7	0.14	2.05	-61.79	-13	48.79
242.56	41.00	154	2.3	V	-64.4	0.14	2.05	-62.49	-13	49.49
1673.20	39.40	189	1.8	H	-62.4	0.40	8.52	-54.28	-13	41.28
1673.20	39.87	197	2.3	V	-63.9	0.40	8.52	-55.78	-13	42.78

30 MHz ~ 20 GHz:**PCS Band (Part 24E & 27)**

Frequency (MHz)	Receiver Reading (dBμV)	Turntable Angle Degree	Rx Antenna		Substituted			Absolute Level (dBm)	FCC Part 24E/27	
			Height (m)	Polar (H/V)	Level (dBm)	Cable Loss (dB)	Antenna Gain (dB)		Limit (dBm)	Margin (dB)
GSM Mode, Middle channel										
242.56	41.57	24	2.3	H	-63.4	0.14	2.05	-61.49	-13	48.49
242.56	40.51	42	1.6	V	-64.9	0.14	2.05	-62.99	-13	49.99
3760.00	39.92	246	1.5	H	-56.1	0.59	9.72	-46.97	-13	33.97
3760.00	40.61	6	2.2	V	-56.5	0.59	9.72	-47.37	-13	34.37
WCDMA Mode Band II, Middle channel										
242.56	41.66	117	2.4	H	-63.3	0.14	2.05	-61.39	-13	48.39
242.56	40.70	144	2.0	V	-64.7	0.14	2.05	-62.79	-13	49.79
3760.00	41.42	175	1.5	H	-54.6	0.59	9.72	-45.47	-13	32.47
3760.00	41.41	196	2.2	V	-55.7	0.59	9.72	-46.57	-13	33.57
WCDMA Mode Band IV, Middle channel										
242.56	41.56	301	1.3	H	-63.4	0.14	2.05	-61.49	-13	48.49
242.56	40.90	149	1.0	V	-64.5	0.14	2.05	-62.59	-13	49.59
3465.20	41.33	108	1.5	H	-55.7	0.54	9.90	-46.34	-13	33.34
3465.20	40.63	50	1.9	V	-57.7	0.54	9.90	-48.34	-13	35.34

LTE Band:*Test mode: Transmitting (Pre-scan with all the bandwidth, and worse case as below)*

Frequency	Receiver	Turntable	Rx Antenna		Substituted			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
(MHz)	Reading (dBμV)	Angle Degree	Height (m)	Polar (H/V)	Level (dBm)	Cable Loss (dB)	Antenna Gain (dB)			
Band 2										
Test frequency range:30 MHz ~ 20 GHz										
178.35	42.29	258	1.5	H	-62.7	0.14	2.05	-60.79	-13	47.79
178.35	40.73	70	2.2	V	-64.7	0.14	2.05	-62.79	-13	49.79
3760.00	37.02	98	1.3	H	-59.0	0.59	9.72	-49.87	-13	36.87
3760.00	37.91	341	1.8	V	-59.2	0.59	9.72	-50.07	-13	37.07
Band 4										
Test frequency range:30 MHz ~ 18 GHz										
178.35	41.89	54	1.8	H	-63.1	0.14	2.05	-61.19	-13	48.19
178.35	40.43	100	1.6	V	-65.0	0.14	2.05	-63.09	-13	50.09
3465.00	39.13	230	1.2	H	-57.9	0.54	9.90	-48.54	-13	35.54
3465.00	40.43	182	2.3	V	-57.9	0.54	9.90	-48.54	-13	35.54
Band 7										
Test frequency range:30 MHz ~ 26 GHz										
178.35	42.69	149	1.7	H	-62.3	0.14	2.05	-60.39	-25	35.39
178.35	40.63	347	2.1	V	-64.8	0.14	2.05	-62.89	-25	37.89
5070.00	38.94	6	2.4	H	-54.2	0.64	10.30	-44.54	-25	19.54
5070.00	40.17	271	1.2	V	-54.5	0.64	10.30	-44.84	-25	19.84
Band 12										
Test frequency range: 30 MHz ~ 10 GHz										
178.35	41.99	104	1.4	H	-63.0	0.14	2.05	-61.09	-13	48.09
178.35	40.43	66	1.0	V	-65.0	0.14	2.05	-63.09	-13	50.09
1415.00	38.87	38	2.3	H	-65.2	0.34	7.92	-57.62	-13	44.62
1415.00	41.30	79	1.5	V	-64.5	0.34	7.92	-56.92	-13	43.92
Band 17										
Test frequency range: 30 MHz ~ 10GHz										
178.35	42.49	1	2.0	H	-62.5	0.14	2.05	-60.59	-13	47.59
178.35	40.53	11	1.9	V	-64.9	0.14	2.05	-62.99	-13	49.99
1420.00	39.37	112	1.0	H	-64.7	0.34	7.92	-57.12	-13	44.12
1420.00	40.00	285	1.4	V	-65.8	0.34	7.92	-58.22	-13	45.22

Note:

- 1) Absolute Level = Substituted Level - Cable loss + Antenna Gain
- 2) Margin = Limit- Absolute Level

FCC § 22.917 (a); § 24.238 (a); § 27.53 (h)(m) - BAND EDGES**Applicable Standard**

According to § 22.917(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

According to § 24.238(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.


According to FCC § 27.53 (h)(m), the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

For mobile digital stations, the attenuation factor shall be not less than $40 + 10 \log(P)$ dB on all frequencies between the channel edge and 5 megahertz from the channel edge, $43 + 10 \log(P)$ dB on all frequencies between 5 megahertz and X megahertz from the channel edge, and $55 + 10 \log(P)$ dB on all frequencies more than X megahertz from the channel edge, where X is the greater of 6 megahertz or the actual emission bandwidth as defined in paragraph (m)(6) of this section. In addition, the attenuation factor shall not be less than $43 + 10 \log(P)$ dB on all frequencies between 2490.5 MHz and 2496 MHz and $55 + 10 \log(P)$ dB at or below 2490.5 MHz. Mobile Satellite Service licensees operating on frequencies below 2495 MHz may also submit a documented interference complaint against BRS licensees operating on channel BRS Channel 1 on the same terms and conditions as adjacent channel BRS or EBS licensees.

Test Procedure

The RF output of the transmitter was connected to the input of the spectrum analyzer through sufficient attenuation.

The center of the spectrum analyzer was set to block edge frequency

**Test Data****Environmental Conditions**


Temperature:	24~25°C
Relative Humidity:	47~50 %
ATM Pressure:	100.0~101.0 kPa

The testing was performed by Echo Wu from 2017-06-17 to 2017-06-20.


EUT operation mode: Transmitting

Test Result: Compliance. Please refer to the following plots.


Cellular Band, Left Band Edge for GSM (GMSK) Mode




Cellular Band, Right Band Edge for GSM (GMSK) Mode







Cellular Band, Left Band Edge for EDGE Mode




Cellular Band, Right Band Edge for EDGE Mode




Cellular Band, Left Band Edge for WCDMA (BPSK) Mode**Cellular Band, Right Band Edge for WCDMA (BPSK) Mode**

Cellular Band, Left Band Edge for HSDPA (16QAM) Mode**Cellular Band, Right Band Edge for HSDPA (16QAM) Mode**


Cellular Band, Left Band Edge for HSUPA (BPSK) Mode




Cellular Band, Right Band Edge for HSUPA (BPSK) Mode




PCS Band, Left Band Edge for GSM (GMSK) Mode




PCS Band, Right Band Edge for GSM (GMSK) Mode




PCS Band, Left Band Edge for EDGE Mode




PCS Band, Right Band Edge for EDGE Mode




PCS Band, Left Band Edge for WCDMA (BPSK) Mode




PCS Band, Right Band Edge for WCDMA (BPSK) Mode




PCS Band, Left Band Edge for HSDPA (16QAM) Mode




PCS Band, Right Band Edge for HSDPA (16QAM) Mode




PCS Band, Left Band Edge for HSUPA (BPSK) Mode




PCS Band, Right Band Edge for HSUPA (BPSK) Mode




AWS Band, Left Band Edge for RMC (BPSK) Mode




AWS Band, Right Band Edge for RMC (BPSK) Mode




AWS Band, Left Band Edge for HSDPA (16QAM) Mode




AWS Band, Right Band Edge for HSDPA (16QAM) Mode



AWS Band, Left Band Edge for HSUPA (BPSK) Mode




AWS Band, Right Band Edge for HSUPA (BPSK) Mode




Band 2:


QPSK (1.4 MHz, FULL RB) - Left Band Edge




QPSK (1.4 MHz, FULL RB) - Right Band Edge




16-QAM (1.4 MHz, FULL RB) - Left Band Edge




16-QAM (1.4 MHz, FULL RB) - Right Band Edge





QPSK (3.0 MHz, FULL RB) - Left Band Edge




QPSK (3.0 MHz, FULL RB) - Right Band Edge






16-QAM (3.0 MHz, FULL RB) - Left Band Edge**16-QAM (3.0 MHz, FULL RB) - Right Band Edge**

QPSK (5.0 MHz, FULL RB) - Left Band Edge




QPSK (5.0 MHz, FULL RB) - Right Band Edge






16-QAM (5.0 MHz, FULL RB) - Left Band Edge**16-QAM (5.0 MHz, FULL RB) - Right Band Edge**

QPSK (10.0 MHz, FULL RB) - Left Band Edge




QPSK (10.0 MHz, FULL RB) - Right Band Edge






16-QAM (10.0 MHz, FULL RB) - Left Band Edge**16-QAM (10.0 MHz, FULL RB) - Right Band Edge**

QPSK (15.0 MHz, FULL RB) - Left Band Edge




QPSK (15.0 MHz, FULL RB) - Right Band Edge




16-QAM (15.0 MHz, FULL RB) - Left Band Edge**16-QAM (15.0 MHz, FULL RB) - Right Band Edge**


QPSK (20.0 MHz, FULL RB) - Left Band Edge




QPSK (20.0 MHz, FULL RB) - Right Band Edge



16-QAM (20.0 MHz, FULL RB) - Left Band Edge




16-QAM (20.0 MHz, FULL RB) - Right Band Edge




Band 4:


QPSK (1.4 MHz, FULL RB) - Left Band Edge




QPSK (1.4 MHz, FULL RB) - Right Band Edge




16-QAM (1.4 MHz, FULL RB) - Left Band Edge




16-QAM (1.4 MHz, FULL RB) - Right Band Edge




QPSK (3.0 MHz, FULL RB) - Left Band Edge




QPSK (3.0 MHz, FULL RB) - Right Band Edge




16-QAM (3.0 MHz, FULL RB) - Left Band Edge




16-QAM (3.0 MHz, FULL RB) - Right Band Edge




QPSK (5.0 MHz, FULL RB) - Left Band Edge




QPSK (5.0 MHz, FULL RB) - Right Band Edge




16-QAM (5.0 MHz, FULL RB) - Left Band Edge




16-QAM (5.0 MHz, FULL RB) - Right Band Edge





QPSK (10.0 MHz, FULL RB) - Left Band Edge




QPSK (10.0 MHz, FULL RB) - Right Band Edge




16-QAM (10.0 MHz, FULL RB) - Left Band Edge**16-QAM (10.0 MHz, FULL RB) - Right Band Edge**


QPSK (15.0 MHz, FULL RB) - Left Band Edge




QPSK (15.0 MHz, FULL RB) - Right Band Edge




16-QAM (15.0 MHz, FULL RB) - Left Band Edge



16-QAM (15.0 MHz, FULL RB) - Right Band Edge




QPSK (20.0 MHz, FULL RB) - Left Band Edge



QPSK (20.0 MHz, FULL RB) - Right Band Edge







16-QAM (20.0 MHz, FULL RB) - Left Band Edge




16-QAM (20.0 MHz, FULL RB) - Right Band Edge




Band 7:**QPSK (5.0 MHz, FULL RB) - Left Band Edge****QPSK (5.0 MHz, FULL RB) - Right Band Edge**

16-QAM (5.0 MHz, FULL RB) - Left Band Edge**16-QAM (5.0 MHz, FULL RB) - Right Band Edge**


QPSK (10.0 MHz, FULL RB) - Left Band Edge




QPSK (10.0 MHz, FULL RB) - Right Band Edge




16-QAM (10.0 MHz, FULL RB) - Left Band Edge




16-QAM (10.0 MHz, FULL RB) - Right Band Edge





QPSK (15 MHz, FULL RB) - Left Band Edge




QPSK (15 MHz, FULL RB) - Right Band Edge




16-QAM (15 MHz, FULL RB) - Left Band Edge**16-QAM (15 MHz, FULL RB) - Right Band Edge**


QPSK (20 MHz, FULL RB) - Left Band Edge




QPSK (20 MHz, FULL RB) - Right Band Edge



16-QAM (20 MHz, FULL RB) - Left Band Edge




16-QAM (20 MHz, FULL RB) - Right Band Edge






Band 12:

QPSK (1.4 MHz, FULL RB) - Left Band Edge




QPSK (1.4 MHz, FULL RB) - Right Band Edge






16-QAM (1.4 MHz, FULL RB) - Left Band Edge**16-QAM (1.4 MHz, FULL RB) - Right Band Edge**

QPSK (3.0 MHz, FULL RB) - Left Band Edge




QPSK (3.0 MHz, FULL RB) - Right Band Edge




16-QAM (3.0 MHz, FULL RB) - Left Band Edge**16-QAM (3.0 MHz, FULL RB) - Right Band Edge**


QPSK (5.0 MHz, FULL RB) - Left Band Edge




QPSK (5.0 MHz, FULL RB) - Right Band Edge




16-QAM (5.0 MHz, FULL RB) - Left Band Edge




16-QAM (5.0 MHz, FULL RB) - Right Band Edge




QPSK (10.0 MHz, FULL RB) - Left Band Edge




QPSK (10.0 MHz, FULL RB) - Right Band Edge



16-QAM (10.0 MHz, FULL RB) - Left Band Edge




16-QAM (10.0 MHz, FULL RB) - Right Band Edge




Band 17:


QPSK (5.0 MHz, FULL RB) - Left Band Edge




QPSK (5.0 MHz, FULL RB) - Right Band Edge




16-QAM (5.0 MHz, FULL RB) - Left Band Edge




16-QAM (5.0 MHz, FULL RB) - Right Band Edge




QPSK (10.0 MHz, FULL RB) - Left Band Edge




QPSK (10.0 MHz, FULL RB) - Right Band Edge



16-QAM (10.0 MHz, FULL RB) - Left Band Edge



16-QAM (10.0 MHz, FULL RB) - Right Band Edge



FCC § 2.1055; § 22.355; § 24.235; §27.54; - FREQUENCY STABILITY

Applicable Standard

FCC § 2.1055, §22.355, §24.235 and §27.54.

According to FCC §2.1055, the frequency stability shall be sufficient to ensure that the fundamental emissions stay within the authorized bands of operation.

According to §22.355, the carrier frequency of each transmitter in the Public Mobile Services must be maintained within the tolerances given in Table below:

Frequency Tolerance for Transmitters in the Public Mobile Services

Frequency Range (MHz)	Base, fixed (ppm)	Mobile ≤ 3 watts (ppm)	Mobile > 3 watts (ppm)
25 to 50	20.0	20.0	50.0
50 to 450	5.0	5.0	50.0
450 to 512	2.5	5.0	5.0
821 to 896	1.5	2.5	2.5
928 to 929.	5.0	N/A	N/A
929 to 960.	1.5	N/A	N/A
2110 to 2220	10.0	N/A	N/A


According to §24.235, the frequency stability shall be sufficient to ensure that the fundamental emissions stays within the authorized frequency block.

Test Procedure

Frequency Stability vs. Temperature: The equipment under test was connected to an external DC power supply and the RF output was connected to communication test set via feed-through attenuators. The EUT was placed inside the temperature chamber. The DC leads and RF output cable exited the chamber through an opening made for the purpose.

After the temperature stabilized for approximately 20 minutes, the frequency output was recorded from the communication test set.

Frequency Stability vs. Voltage: For hand carried, battery powered equipment; reduce primary supply voltage to the battery operating end point which shall be specified by the manufacturer.



Test Data**Environmental Conditions**

Temperature:	22 °C
Relative Humidity:	48 %
ATM Pressure:	101.0 kPa

The testing was performed by Echo Wu on 2017-06-17.

EUT operation mode: Transmitting

Test Result: Compliance. Please refer to the following tables.

Cellular Band (Part 22H)**GSM Mode**

Middle Channel, $f_0=836.6\text{MHz}$				
Temperature (°C)	Power Supplied (V_{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-30	3.8	23	0.02749	2.5
-20		23	0.02749	2.5
-10		22	0.02630	2.5
0		22	0.02630	2.5
10		22	0.02630	2.5
20		21	0.02510	2.5
30		22	0.02630	2.5
40		23	0.02749	2.5
50		25	0.02988	2.5
25	V min.= 3.6	27	0.03227	2.5
25	V max.= 4.3	29	0.03466	2.5

EDGE Mode

Middle Channel, $f_0=836.6\text{MHz}$				
Temperature (°C)	Power Supplied (V_{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-30	3.8	20	0.02391	2.5
-20		20	0.02391	2.5
-10		20	0.02391	2.5
0		16	0.01913	2.5
10		16	0.01913	2.5
20		14	0.01673	2.5
30		18	0.02152	2.5
40		20	0.02391	2.5
50		26	0.03108	2.5
25	V min.= 3.6	28	0.03347	2.5
25	V max.= 4.3	29	0.03466	2.5

WCDMA Mode

Middle Channel, $f_0=836.6\text{MHz}$				
Temperature (°C)	Power Supplied (V_{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-30	3.8	-8	-0.00956	2.5
-20		-8	-0.00956	2.5
-10		-7	-0.00837	2.5
0		-7	-0.00837	2.5
10		-7	-0.00837	2.5
20		-6	-0.00717	2.5
30		-7	-0.00837	2.5
40		-8	-0.00956	2.5
50		-8	-0.00956	2.5
25	V min.= 3.6	-9	-0.01076	2.5
25	V max.= 4.3	-9	-0.01076	2.5

PCS Band (Part 24E)**GSM Mode**

Middle Channel, $f_0=1880.0\text{ MHz}$				
Temperature (°C)	Power Supplied (V_{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Result
-30	3.8	25	0.01330	pass
-20		25	0.01330	pass
-10		25	0.01330	pass
0		24	0.01277	pass
10		24	0.01277	pass
20		22	0.01170	pass
30		24	0.01277	pass
40		30	0.01596	pass
50		32	0.01702	pass
25	V min.= 3.6	35	0.01862	pass
25	V max.= 4.3	37	0.01968	pass

EDGE Mode

Middle Channel, $f_0 = 1880.0$ MHz				
Temperature (°C)	Power Supplied (V_{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Result
-30	3.8	22	0.01170	pass
-20		22	0.01170	pass
-10		22	0.01170	pass
0		20	0.01064	pass
10		20	0.01064	pass
20		18	0.00957	pass
30		20	0.01064	pass
40		22	0.01170	pass
50		24	0.01277	pass
25	V min.= 3.6	25	0.01330	pass
25	V max.= 4.3	26	0.01383	pass

WCDMA Mode

Middle Channel, $f_0 = 1880.0$ MHz				
Temperature (°C)	Power Supplied (V_{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Result
-30	3.8	-6	-0.00319	pass
-20		-6	-0.00319	pass
-10		-6	-0.00319	pass
0		-5	-0.00266	pass
10		-5	-0.00266	pass
20		-4	-0.00213	pass
30		-5	-0.00266	pass
40		-6	-0.00319	pass
50		-8	-0.00426	pass
25	V min.= 3.6	-8	-0.00426	pass
25	V max.= 4.3	-9	-0.00479	pass

AWS Band (Part 27)**WCDMA Mode**

Middle Channel, $f_0=1732.6$ MHz				
Temperature (°C)	Voltage Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-30	3.8	-12	-0.00693	pass
-20		-12	-0.00693	pass
-10		-12	-0.00693	pass
0		-11	-0.00635	pass
10		-11	-0.00635	pass
20		-10	-0.00577	pass
30		-11	-0.00635	pass
40		-13	-0.00750	pass
50		-13	-0.00750	pass
25	V min.= 3.6	-14	-0.00808	pass
25	V max.= 4.3	-14	-0.00808	pass

LTE:

Band 2:

10.0 MHz Middle Channel, $f_0=1880$ MHz				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Result
-30	3.8	5	0.01968	pass
-20		5	0.01596	pass
-10		5	0.00798	pass
0		2	0.00798	pass
10		2	0.00691	pass
20		-1	-0.00053	pass
30		2	0.00106	pass
40		3	0.00160	pass
50		5	0.00266	pass
20	V min.= 3.6	15	0.00798	pass
	V max.= 4.3	19	0.01011	pass

Band 4:

10.0 MHz Middle Channel, $f_0 = 1732.5$ MHz				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Result
-30	3.8	5	0.00289	pass
-20		5	0.00289	pass
-10		5	0.00289	pass
0		3	0.00173	pass
10		3	0.00173	pass
20		2	0.00115	pass
30		3	0.00173	pass
40		4	0.00231	pass
50		5	0.00289	pass
20	V min.= 3.6	7	0.00404	pass
	V max.= 4.3	8	0.00462	pass

Band 7:

10.0 MHz Middle Channel, $f_0 = 2535$ MHz				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-30	3.8	-5	-0.00197	pass
-20		-4	-0.00158	pass
-10		-4	-0.00158	pass
0		-2	-0.00079	pass
10		-2	-0.00079	pass
20		-1	-0.00039	pass
30		-2	-0.00079	pass
40		-3	-0.00118	pass
50		-4	-0.00158	pass
20	V min.= 3.6	-5	-0.00197	pass
	V max.= 4.3	-6	-0.00237	pass

Band 12:

10.0 MHz Middle Channel, $f_o = 707.5$ MHz				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Result
-30	3.8	-5	-0.00707	pass
-20		-5	-0.00707	pass
-10		-4	-0.00565	pass
0		-2	-0.00283	pass
10		-2	-0.00283	pass
20		-1	-0.00141	pass
30		-2	-0.00283	pass
40		-3	-0.00424	pass
50		-3	-0.00424	pass
20	V min.= 3.6	-5	-0.00707	pass
	V max.= 4.3	-6	-0.00848	pass

Band 17:

10.0 MHz Middle Channel, $f_o = 710$ MHz				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Result
-30	3.8	-6	-0.00845	pass
-20		-4	-0.00563	pass
-10		-4	-0.00563	pass
0		-2	-0.00282	pass
10		-2	-0.00282	pass
20		-1	-0.00141	pass
30		-2	-0.00282	pass
40		-3	-0.00423	pass
50		-4	-0.00563	pass
25	V min.= 3.6	-6	-0.00845	pass
25	V max.= 4.3	-7	-0.00986	pass

***** END OF REPORT *****