



FCC RF Test Report

APPLICANT : BLU Products, Inc.
EQUIPMENT : Mobile phone
BRAND NAME : BLU
MODEL NAME : STUDIO C HD
FCC ID : YHLBLUSTUCHD
STANDARD : FCC Part 15 Subpart C §15.247
CLASSIFICATION : (DTS) Digital Transmission System

The product was received on Oct. 30, 2015 and testing was completed on Dec. 11, 2015. We, SPORTON INTERNATIONAL (SHENZHEN) INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL (SHENZHEN) INC., the test report shall not be reproduced except in full.

Prepared by: Andy Yeh / Manager

Approved by: Jones Tsai / Manager



SPORTON INTERNATIONAL (SHENZHEN) INC.

**1F & 2F, Building A, Morning Business Center, No. 4003 ShiGu Rd., Xili Town,
Nanshan District, Shenzhen, Guangdong, P. R. China**



TABLE OF CONTENTS

REVISION HISTORY	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION	5
1.1 Applicant	5
1.2 Manufacturer	5
1.3 Product Feature of Equipment Under Test	5
1.4 Product Specification subjective to this standard	6
1.5 Modification of EUT	7
1.6 Testing Location	7
1.7 Applicable Standards	8
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST	9
2.1 Carrier Frequency Channel	9
2.2 Pre-Scanned RF Power	10
2.3 Test Mode	11
2.4 Connection Diagram of Test System	12
2.5 Support Unit used in test configuration and system	13
2.6 EUT Operation Test Setup	13
2.7 Measurement Results Explanation Example	13
3 TEST RESULT	14
3.1 6dB and 99% Bandwidth Measurement	14
3.2 Output Power Measurement	16
3.3 Power Spectral Density Measurement	18
3.4 Conducted Band Edges and Spurious Emission Measurement	20
3.5 Radiated Band Edges and Spurious Emission Measurement	33
3.6 AC Conducted Emission Measurement	37
3.7 Antenna Requirements	41
4 LIST OF MEASURING EQUIPMENT	42
5 UNCERTAINTY OF EVALUATION	43
APPENDIX A. CONDUCTED TEST RESULTS	
APPENDIX B. RADIATED TEST RESULTS	
APPENDIX C. SETUP PHOTOGRAPHS	



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR5O3009C	Rev. 01	Initial issue of report	Dec. 18, 2015

SUMMARY OF TEST RESULT

Report Section	FCC Rule	IC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(2)	RSS-247 5.2(1)	6dB Bandwidth	$\geq 0.5\text{MHz}$	Pass	-
3.1	-	RSS-Gen 6.6	99% Bandwidth	-	Pass	-
3.2	15.247(b)	RSS-247 A5.4(4)	Power Output Measurement	$\leq 30\text{dBm}$	Pass	-
3.3	15.247(e)	RSS-247 5.2(2)	Power Spectral Density	$\leq 8\text{dBm}/3\text{kHz}$	Pass	-
3.4	15.247(d)	RSS-247 5.5	Conducted Band Edges	$\leq 20\text{dBc}$	Pass	-
			Conducted Spurious Emission		Pass	-
3.5	15.247(d)	RSS-247 5.5	Radiated Band Edges and Radiated Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 3.28 dB at 2483.520 MHz
3.6	15.207	RSS-GEN 8.8	AC Conducted Emission	15.207(a)	Pass	Under limit 6.58 dB at 0.370 MHz
3.7	15.203 & 15.247(b)	N/A	Antenna Requirement	N/A	Pass	-



1 General Description

1.1 Applicant

BLU Products, Inc.

10814 NW 33rd St # 100 Doral, FL 33172

1.2 Manufacturer

BLU Products, Inc.

10814 NW 33rd St # 100 Doral, FL 33172

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Mobile phone
Brand Name	BLU
Model Name	STUDIO C HD
FCC ID	YHLBLUSTUCHD
EUT supports Radios application	GSM/GPRS/WCDMA/HSPA/ HSPA+(16QAM uplink is not supported)/ WLAN2.4GHz 802.11b/g/n HT20/HT40/ Bluetooth v3.0+EDR/Bluetooth v4.0 LE
IMEI Code	Conducted: 868455018653912/868455018653920 Conduction: 868455018653714/868455018653722 Radiation: 868455018653755/868455018653763
HW Version	V1.2
SW Version	D5192_BLU_G1_V0.3.5_S1016
EUT Stage	Pre-Production

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.



1.4 Product Specification subjective to this standard

Product Specification subjective to this standard	
Tx/Rx Channel Frequency Range	802.11b/g/n : 2412 MHz ~ 2462 MHz
Maximum (Peak) Output Power to Antenna	802.11b : 15.98 dBm (0.0396 W) 802.11g : 19.00 dBm (0.0794 W) 802.11n HT20 : 18.54 dBm (0.0714 W) 802.11n HT40 : 17.61 dBm (0.0577 W)
99% Occupied Bandwidth	802.11b : 12.65MHz 802.11g : 17.55MHz 802.11n HT20 : 18.35MHz 802.11n HT40 : 36.30MHz
Antenna Type/Gain	802.11b/g/n : PIFA Antenna with gain -4.00 dBi
Type of Modulation	802.11b : DSSS (DBPSK / DQPSK / CCK) 802.11g/n : OFDM (BPSK / QPSK / 16QAM / 64QAM)



1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Testing Location

Test Site	SPORTON INTERNATIONAL (SHENZHEN) INC.	
Test Site Location	1F & 2F, Building A, Morning Business Center, No. 4003 ShiGu Rd., Xili Town, Nanshan District, Shenzhen, Guangdong, P. R. China TEL: +86-755-8637-9589 FAX: +86-755-8637-9595	
Test Site No.	Sporton Site No.	
	TH01-SZ	CO01-SZ

Test Site	SPORTON INTERNATIONAL (SHENZHEN) INC.	
Test Site Location	No. 3 Building, the third floor of south, Shahe River west, Fengzeyuan warehouse, Nanshan District, Shenzhen, Guangdong, P. R. China TEL: +86-755- 3320-2398	
Test Site No.	Sporton Site No.	FCC/IC Registration No.
	03CH01-SZ	831040/4086F

Note: The test site complies with ANSI C63.4 2009 requirement.



1.7 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart C §15.247
- ♦ FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r03
- ♦ ANSI C63.10-2013
- ♦ IC RSS-247 Issue 1
- ♦ IC RSS-Gen Issue 4

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conducted emission (150 kHz to 30 MHz) and radiated emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (Z plane) were recorded in this report.

The final configuration from all the combinations and the worst-case data rates were investigated by measuring the maximum power across all the data rates and modulation modes under section 2.2.

Based on the worst configuration found above, the RF power setting is set individually to meet FCC compliance limit for the final conducted and radiated tests shown in section 2.3.

2.1 Carrier Frequency Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	1	2412	7	2442
	2	2417	8	2447
	3	2422	9	2452
	4	2427	10	2457
	5	2432	11	2462
	6	2437	-	-



2.2 Pre-Scanned RF Power

Preliminary tests were performed in different data rate and data rate associated with the highest power were chosen for full test shown in the following tables.

2.4GHz 802.11b RF Output Power (dBm)						
Power vs. Channel			Power vs. Data Rate			
Channel	Frequency (MHz)	Data Rate 1Mbps	Channel	2Mbps	5.5Mbps	11Mbps
CH 01	2412 MHz	15.98	CH 01	15.97	15.84	15.89
CH 06	2437 MHz	15.38				
CH 11	2462 MHz	15.70				

2.4GHz 802.11g RF Output Power (dBm)										
Power vs. Channel			Power vs. Data Rate							
Channel	Frequency (MHz)	Data Rate 6Mbps	Channel	9Mbps	12Mbps	18Mbps	24Mbps	36Mbps	48Mbps	54Mbps
CH 01	2412 MHz	18.71	CH 06	18.58	18.70	18.57	18.68	18.74	18.95	18.98
CH 06	2437 MHz	19.00								
CH 11	2462 MHz	18.07								

2.4GHz 802.11n HT20 RF Output Power (dBm)										
Power vs. Channel			Power vs. MCS Index							
Channel	Frequency (MHz)	MCS Index MCS0	Channel	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
CH 01	2412 MHz	18.54	CH 01	17.66	17.69	17.73	17.66	18.52	18.45	18.50
CH 06	2437 MHz	17.34								
CH 11	2462 MHz	17.25								

2.4GHz 802.11n HT40 RF Output Power (dBm)										
Power vs. Channel			Power vs. MCS Index							
Channel	Frequency (MHz)	MCS Index MCS0	Channel	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
CH 03	2422 MHz	17.61	CH 03	16.91	16.51	16.67	16.55	17.59	17.49	17.56
CH 06	2437 MHz	17.35								
CH 09	2452 MHz	17.23								

2.3 Test Mode

Final test mode of conducted test items and radiated spurious emissions are considering the modulation and worse data rates from the power table described in section 2.2.


<2.4GHz>

Modulation	Data Rate
802.11b	1 Mbps
802.11g	6 Mbps
802.11n HT20	MCS0
802.11n HT40	MCS0


Test Cases	
AC Conducted Emission	Mode 1: GSM850 Idle + Bluetooth Link + WLAN Link + Earphone + USB Cable (Charging from Adapter) + SIM 1

2.4 Connection Diagram of Test System

<WLAN Tx Mode>



<AC Conducted Emission Mode>



2.5 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	Anritsu	MT8820C	N/A	N/A	Unshielded, 1.8 m
2.	WLAN AP	D-link	DIR-628	KA2DIR628A2	N/A	Unshielded, 1.8 m
3.	Notebook	Lenovo	E540	FCC DoC	N/A	shielded cable DC O/P 1.8 m unshielded AC I/P cable 1.2 m
4.	Bluetooth Earphone	Nokia	BH-108	PYAHS-107W	N/A	N/A

2.6 EUT Operation Test Setup

For WLAN function, the engineering test program was provided and enabled to make EUT continuous transmit/receive.

For AC power line conducted emissions, the EUT was set to connect with the Notebook under large package sizes transmission.

2.7 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 5.0 dB and 10dB attenuator.

$$\begin{aligned}\text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)} \\ &= 5.0 + 10 = 15.0 \text{ (dB)}\end{aligned}$$

3 Test Result

3.1 6dB and 99% Bandwidth Measurement

3.1.1 Limit of 6dB and 99% Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.


3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 DTS D01 Meas. Guidance v03r03.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
5. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) = 1MHz and set the Video bandwidth (VBW) = 3MHz.
6. Measure and record the results in the test report.


3.1.4 Test Setup





3.1.5 Test Result of 6dB and 99% Occupied Bandwidth

Please refer to Appendix A of this test report.



Note : The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

3.2 Output Power Measurement

3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. If transmitting Antenna of directional gain greater than 6dBi are used the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the Antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the Antenna exceeds 6dBi.


3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.2.3 Test Procedures

1. The testing follows the Measurement Procedure of FCC KDB No. 558074 DTS D01 Meas. Guidance v03r03 section 9.1.2 PKPM1 Peak power meter method.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power and record the results in the test report.

3.2.4 Test Setup





3.2.5 Test Result of Peak Output Power

Please refer to Appendix A of this test report.

3.2.6 Test Result of Average output Power (Reporting Only)

Please refer to Appendix A of this test report.

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.


3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.3.3 Test Procedures

1. The testing follows Measurement Procedure 10.2 Method PKPSD of FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r03
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.


3.3.4 Test Setup





3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A of this test report.



3.4 Conducted Band Edges and Spurious Emission Measurement

3.4.1 Limit of Conducted Band Edges and Spurious Emission Measurement

In any 100 kHz bandwidth outside of the authorized frequency band, the emissions which fall in the non-restricted bands shall be attenuated at least 20 dB / 30dB relative to the maximum PSD level in 100 kHz by RF conducted measurement and radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).


3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.4.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r03.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB per 15.247(d).
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.


3.4.4 Test Setup





3.4.5 Test Result of Conducted Band Edges and Spurious Emission

Test Mode :	802.11b	Temperature :	24~26℃
Test Band :	2.4GHz Low	Relative Humidity :	50~53%
Test Channel :	01	Test Engineer :	Bruce Huang






Test Mode :	802.11b	Temperature :	24~26°C
Test Band :	2.4GHz Mid	Relative Humidity :	50~53%
Test Channel :	06	Test Engineer :	Bruce Huang


WLAN 802.11b Channel 06

100kHz PSD reference Level




Date: 3.NOV.2015 09:49:23

Spurious Emission 30MHz~3GHz



Date: 3.NOV.2015 09:49:46

Spurious Emission 2GHz~25GHz




Date: 3.NOV.2015 09:49:54



Test Mode :	802.11b	Temperature :	24~26°C
Test Band :	2.4GHz High	Relative Humidity :	50~53%
Test Channel :	11	Test Engineer :	Bruce Huang


WLAN 802.11b Channel 11

100kHz PSD reference Level




Date: 3.NOV.2015 10:07:04

High Channel Plot




Date: 3.NOV.2015 10:08:22

Spurious Emission 30MHz~3GHz



Date: 3.NOV.2015 10:09:32

Spurious Emission 2GHz~25GHz




Date: 3.NOV.2015 10:09:40



Test Mode :	802.11g	Temperature :	24~26°C
Test Band :	2.4GHz Low	Relative Humidity :	50~53%
Test Channel :	01	Test Engineer :	Bruce Huang


WLAN 802.11g Channel 01

100kHz PSD reference Level




Date: 3.NOV.2015 10:17:34

Low Channel Plot




Date: 3.NOV.2015 10:18:18

Spurious Emission 30MHz~3GHz



Date: 3.NOV.2015 10:18:38

Spurious Emission 2GHz~25GHz




Date: 3.NOV.2015 10:18:46



Test Mode :	802.11g	Temperature :	24~26°C
Test Band :	2.4GHz Mid	Relative Humidity :	50~53%
Test Channel :	06	Test Engineer :	Bruce Huang


WLAN 802.11g Channel 06

100kHz PSD reference Level




Date: 3.NOV.2015 10:23:41

Spurious Emission 30MHz~3GHz



Date: 3.NOV.2015 10:23:53

Spurious Emission 2GHz~25GHz




Date: 3.NOV.2015 10:24:01



Test Mode :	802.11g	Temperature :	24~26°C
Test Band :	2.4GHz High	Relative Humidity :	50~53%
Test Channel :	11	Test Engineer :	Bruce Huang


WLAN 802.11g Channel 11

100kHz PSD reference Level




Date: 3.NOV.2015 10:28:10

High Channel Plot




Date: 3.NOV.2015 10:28:50

Spurious Emission 30MHz~3GHz



Date: 3.NOV.2015 10:29:07

Spurious Emission 2GHz~25GHz




Date: 3.NOV.2015 10:29:15



Test Mode :	802.11n HT20	Temperature :	24~26°C
Test Band :	2.4GHz Low	Relative Humidity :	50~53%
Test Channel :	01	Test Engineer :	Bruce Huang


WLAN 802.11n HT20 Channel 01

100kHz PSD reference Level




Date: 3.NOV.2015 10:34:15

Low Channel Plot




Date: 3.NOV.2015 10:35:19

Spurious Emission 30MHz~3GHz



Date: 3.NOV.2015 10:36:11

Spurious Emission 2GHz~25GHz




Date: 3.NOV.2015 10:36:20



Test Mode :	802.11n HT20	Temperature :	24~26°C
Test Band :	2.4GHz Mid	Relative Humidity :	50~53%
Test Channel :	06	Test Engineer :	Bruce Huang


WLAN 802.11n HT20 Channel 06

100kHz PSD reference Level




Date: 3.NOV.2015 10:41:11

Spurious Emission 30MHz~3GHz



Date: 3.NOV.2015 10:41:23

Spurious Emission 2GHz~25GHz




Date: 3.NOV.2015 10:41:31



Test Mode :	802.11n HT20	Temperature :	24~26°C
Test Band :	2.4GHz High	Relative Humidity :	50~53%
Test Channel :	11	Test Engineer :	Bruce Huang


WLAN 802.11n HT20 Channel 11

100kHz PSD reference Level




Date: 3.NOV.2015 10:49:22

High Channel Plot




Date: 3.NOV.2015 10:49:52

Spurious Emission 30MHz~3GHz



Date: 3.NOV.2015 10:50:32


Spurious Emission 2GHz~25GHz




Date: 3.NOV.2015 10:50:41




Test Mode :	802.11n HT40	Temperature :	24~26°C
Test Band :	2.4GHz Low	Relative Humidity :	50~53%
Test Channel :	03	Test Engineer :	Bruce Huang

WLAN 802.11n HT40 Channel 03**100kHz PSD reference Level**


Date: 3.NOV.2015 10:57:05

Low Channel Plot

Date: 3.NOV.2015 10:57:25

Spurious Emission 30MHz~3GHz

Date: 3.NOV.2015 10:58:07

Spurious Emission 2GHz~25GHz


Date: 3.NOV.2015 10:58:15



Test Mode :	802.11n HT40	Temperature :	24~26°C
Test Band :	2.4GHz Mid	Relative Humidity :	50~53%
Test Channel :	06	Test Engineer :	Bruce Huang


WLAN 802.11n HT40 Channel 06

100kHz PSD reference Level




Date: 3.NOV.2015 11:01:57

Spurious Emission 30MHz~3GHz



Date: 3.NOV.2015 11:05:29

Spurious Emission 2GHz~25GHz




Date: 3.NOV.2015 11:05:37



Test Mode :	802.11n HT40	Temperature :	24~26°C
Test Band :	2.4GHz High	Relative Humidity :	50~53%
Test Channel :	09	Test Engineer :	Bruce Huang


WLAN 802.11n HT40 Channel 09

100kHz PSD reference Level




Date: 3.NOV.2015 11:10:38

High Channel Plot




Date: 3.NOV.2015 11:11:13

Spurious Emission 30MHz~3GHz



Date: 3.NOV.2015 11:23:53

Spurious Emission 2GHz~25GHz



Date: 3.NOV.2015 11:21:43

3.5 Radiated Band Edges and Spurious Emission Measurement

3.5.1 Limit of Radiated band edge and Spurious Emission Measurement

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the FCC section 15.209 limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.5.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r03.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
7. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW=100 kHz for $f < 1$ GHz; VBW $\geq$ RBW; Sweep = auto; Detector function = peak; Trace = max hold;
 - (3) Set RBW = 1 MHz, VBW= 3MHz for $f \geq 1$ GHz for peak measurement.


For average measurement:

 - VBW = 10 Hz, when duty cycle is no less than 98 percent.
 - VBW $\geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.


Band	Duty Cycle(%)	T(ms)	1/T(kHz)	VBW Setting
802.11b	100.00	–	–	10Hz
802.11g	97.20	1.39	0.72	1kHz
2.4GHz 802.11n HT20	97.33	1.31	0.76	1kHz
2.4GHz 802.11n HT40	94.19	0.65	1.54	3kHz

3.5.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



3.5.5 Test Results of Radiated Spurious Emissions (9kHz ~ 30MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.

3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix B.

3.5.7 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix B.

3.6 AC Conducted Emission Measurement

3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of Emission (MHz)	Conducted Limit (dB μ V)	
	Quasi-Peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.6.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room, and it was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF bandwidth = 9kHz) with Maximum Hold Mode.


3.6.4 Test Setup





3.6.5 Test Result of AC Conducted Emission

Test Mode :	Mode 1	Temperature :	21~23℃
Test Engineer :	Jacky Yang	Relative Humidity :	41~43%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	GSM850 Idle + Bluetooth Link + WLAN Link + Earphone + USB Cable (Charging from Adapter) + SIM 1		




Site : C001-SZ
Condition: FCC 15C_QP LISN_L_20150304 LINE

Mode : Mode 1
IMEI : 868455018653714/868455018653722

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.31	40.86	-9.11	49.97	30.09	0.57	10.20	Average
2	0.31	47.76	-12.21	59.97	36.99	0.57	10.20	QP
3 *	0.37	42.03	-6.58	48.61	31.30	0.55	10.18	Average
4	0.37	48.13	-10.48	58.61	37.40	0.55	10.18	QP
5	0.50	35.12	-10.88	46.00	24.29	0.67	10.16	Average
6	0.50	43.42	-12.58	56.00	32.59	0.67	10.16	QP
7	1.09	31.36	-14.64	46.00	20.71	0.50	10.15	Average
8	1.09	40.46	-15.54	56.00	29.81	0.50	10.15	QP
9	1.44	32.55	-13.45	46.00	21.90	0.48	10.17	Average
10	1.44	40.45	-15.55	56.00	29.80	0.48	10.17	QP
11	1.65	33.25	-12.75	46.00	22.60	0.47	10.18	Average
12	1.65	41.05	-14.95	56.00	30.40	0.47	10.18	QP



Test Mode :	Mode 1	Temperature :	21~23°C
Test Engineer :	Jacky Yang	Relative Humidity :	41~43%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	GSM850 Idle + Bluetooth Link + WLAN Link + Earphone + USB Cable (Charging from Adapter) + SIM 1		



Site : CO01-SZ
Condition: FCC 15C_QP LISN_N_20150304 NEUTRAL

Mode : Mode 1
IMEI : 868455018653714/868455018653722

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.31	39.68	-10.34	50.02	28.89	0.59	10.20	Average
2	0.31	45.48	-14.54	60.02	34.69	0.59	10.20	QP
3 *	0.36	40.15	-8.63	48.78	29.40	0.57	10.18	Average
4	0.36	46.15	-12.63	58.78	35.40	0.57	10.18	QP
5	0.49	33.46	-12.68	46.14	22.69	0.61	10.16	Average
6	0.49	39.36	-16.78	56.14	28.59	0.61	10.16	QP
7	0.79	28.70	-17.30	46.00	18.00	0.55	10.15	Average
8	0.79	34.80	-21.20	56.00	24.10	0.55	10.15	QP
9	1.54	31.34	-14.66	46.00	20.60	0.57	10.17	Average
10	1.54	37.54	-18.46	56.00	26.80	0.57	10.17	QP
11	1.64	33.05	-12.95	46.00	22.30	0.57	10.18	Average
12	1.64	39.55	-16.45	56.00	28.80	0.57	10.18	QP



3.7 Antenna Requirements

3.7.1 Standard Applicable

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. For the fixed point-to-point operation, the power shall be reduced by one dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the FCC rule.

3.7.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.7.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSP30	101400	9kHz~30GHz	Jan. 28, 2015	Nov. 03, 2015	Jan. 27, 2016	Conducted (TH01-SZ)
Pulse Power Sensor	Anritsu	MA2411B	1207253	30MHz~40GHz	Jan. 28, 2015	Nov. 03, 2015	Jan. 27, 2016	Conducted (TH01-SZ)
Power Meter	Anritsu	ML2495A	1218010	50MHz Bandwidth	Jan. 28, 2015	Nov. 03, 2015	Jan. 27, 2016	Conducted (TH01-SZ)
EMI Test Receiver&SA	Agilent Technologies	N9038A	MY52260185	20Hz~26.5GHz	May 26, 2015	Nov. 17, 2015	May 25, 2016	Radiation (03CH01-SZ)
Spectrum Analyzer	KEYSIGHT	N9010A	MY55150213	10Hz~44GHz;Max 30dBm	Jun. 07, 2015	Nov. 17, 2015	Jun. 06, 2016	Radiation (03CH01-SZ)
Loop Antenna	R&S	HFH2-Z2	100354	9kHz~30MHz	May 06, 2015	Nov. 17, 2015	May 05, 2016	Radiation (03CH01-SZ)
Bilog Antenna	TeseQ	CBL6112D	23188	30MHz-2GHz	Oct. 17, 2015	Nov. 17, 2015	Oct. 16, 2016	Radiation (03CH01-SZ)
Double Ridge Horn Antenna	ETS Lindgren	3117	00119436	1GHz~18GHz	Oct. 17, 2015	Nov. 17, 2015	Oct. 16, 2016	Radiation (03CH01-SZ)
SHF-EHF Horn	com-power	AH-840	101071	18GHz~40GHz	Aug. 19, 2015	Nov. 17, 2015	Aug. 18, 2016	Radiation (03CH01-SZ)
Amplifier	ADVANTEST	BB525C	E9007003	9kHz~3000MHz / 30 dB	Jan. 28, 2015	Nov. 17, 2015	Jan. 27, 2016	Radiation (03CH01-SZ)
Amplifier	Yiai	AV3860B	04030	2GHz~26.5GHz	May 05, 2015	Nov. 17, 2015	May 04, 2016	Radiation (03CH01-SZ)
Amplifier	Agilent Technologies	83017A	MY39501302	500MHz~26.5GHz	Jan. 28, 2015	Nov. 17, 2015	Jan. 27, 2016	Radiation (03CH01-SZ)
AC Power Source	Chroma	61601	616010001985	N/A	NCR	Nov. 17, 2015	NCR	Radiation (03CH01-SZ)
Turn Table	EM	EM1000	N/A	0~360 degree	NCR	Nov. 17, 2015	NCR	Radiation (03CH01-SZ)
Antenna Mast	EM	EM1000	N/A	1 m~4 m	NCR	Nov. 17, 2015	NCR	Radiation (03CH01-SZ)
EMI Receiver	R&S	ESC17	100724	9kHz~3GHz;	Jan 28, 2015	Dec. 11, 2015	Jan 27, 2016	Conduction (CO01-SZ)
AC LISN	EMCO	3816/2SH	103892	9kHz~30MHz	Feb. 02, 2015	Dec. 11, 2015	Feb. 01, 2016	Conduction (CO01-SZ)
AC LISN (for auxiliary equipment)	MessTec	AN3016	16850	9kHz~30MHz	Feb. 02, 2015	Dec. 11, 2015	Feb. 01, 2016	Conduction (CO01-SZ)
AC Power Source	Chroma	61602	616020000891	100Vac~250Vac	Aug. 07, 2015	Dec. 11, 2015	Aug. 06, 2016	Conduction (CO01-SZ)
Pulse Limiter	COM-POWER	LIT-153 Transient Limiter	53139	150kHz~30MHz	Oct. 20, 2015	Dec. 11, 2015	Oct. 19, 2016	Conduction (CO01-SZ)



5 Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150kHz ~ 30MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.3 dB
---	--------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.8 dB
---	--------



Appendix A. Conducted Test Results

A1 - DTS Part

Test Engineer:	Bruce Huang	Temperature:	24~26	°C
Test Date:	2015/11/3	Relative Humidity:	50~53	%

TEST RESULTS DATA
6dB and 99% Occupied Bandwidth

2.4GHz Band								
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
11b	1Mbps	1	1	2412	12.45	9.52	0.50	Pass
11b	1Mbps	1	6	2437	12.45	10.00	0.50	Pass
11b	1Mbps	1	11	2462	12.65	10.00	0.50	Pass
11g	6Mbps	1	1	2412	17.50	15.44	0.50	Pass
11g	6Mbps	1	6	2437	17.55	15.44	0.50	Pass
11g	6Mbps	1	11	2462	17.55	15.32	0.50	Pass
HT20	MCS0	1	1	2412	18.25	15.52	0.50	Pass
HT20	MCS0	1	6	2437	18.35	15.44	0.50	Pass
HT20	MCS0	1	11	2462	18.25	15.60	0.50	Pass
HT40	MCS0	1	3	2422	36.20	35.16	0.50	Pass
HT40	MCS0	1	6	2437	36.30	35.16	0.50	Pass
HT40	MCS0	1	9	2452	36.20	35.12	0.50	Pass

TEST RESULTS DATA
Peak Power Table

2.4GHz Band										
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
11b	1Mbps	1	1	2412	15.98	30.00	-4.00	11.98	36.00	Pass
11b	1Mbps	1	6	2437	15.38	30.00	-4.00	11.38	36.00	Pass
11b	1Mbps	1	11	2462	15.70	30.00	-4.00	11.70	36.00	Pass
11g	6Mbps	1	1	2412	18.71	30.00	-4.00	14.71	36.00	Pass
11g	6Mbps	1	6	2437	19.00	30.00	-4.00	15.00	36.00	Pass
11g	6Mbps	1	11	2462	18.07	30.00	-4.00	14.07	36.00	Pass
HT20	MCS0	1	1	2412	18.54	30.00	-4.00	14.54	36.00	Pass
HT20	MCS0	1	6	2437	17.34	30.00	-4.00	13.34	36.00	Pass
HT20	MCS0	1	11	2462	17.25	30.00	-4.00	13.25	36.00	Pass
HT40	MCS0	1	3	2422	17.61	30.00	-4.00	13.61	36.00	Pass
HT40	MCS0	1	6	2437	17.35	30.00	-4.00	13.35	36.00	Pass
HT40	MCS0	1	9	2452	17.23	30.00	-4.00	13.23	36.00	Pass

TEST RESULTS DATA
Average Power Table
(Reporting Only)

2.4GHz Band						
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power (dBm)
11b	1Mbps	1	1	2412	0.00	13.06
11b	1Mbps	1	6	2437	0.00	12.39
11b	1Mbps	1	11	2462	0.00	12.85
11g	6Mbps	1	1	2412	0.12	10.00
11g	6Mbps	1	6	2437	0.12	10.65
11g	6Mbps	1	11	2462	0.12	10.02
HT20	MCS0	1	1	2412	0.12	8.35
HT20	MCS0	1	6	2437	0.12	7.60
HT20	MCS0	1	11	2462	0.12	8.07
HT40	MCS0	1	3	2422	0.26	7.02
HT40	MCS0	1	6	2437	0.26	6.69
HT40	MCS0	1	9	2452	0.26	6.85

TEST RESULTS DATA
Peak Power Density

2.4GHz Band								
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
11b	1Mbps	1	1	2412	-10.96	-4.00	8.00	Pass
11b	1Mbps	1	6	2437	-9.93	-4.00	8.00	Pass
11b	1Mbps	1	11	2462	-10.50	-4.00	8.00	Pass
11g	6Mbps	1	1	2412	-13.82	-4.00	8.00	Pass
11g	6Mbps	1	6	2437	-15.17	-4.00	8.00	Pass
11g	6Mbps	1	11	2462	-14.99	-4.00	8.00	Pass
HT20	MCS0	1	1	2412	-16.77	-4.00	8.00	Pass
HT20	MCS0	1	6	2437	-16.19	-4.00	8.00	Pass
HT20	MCS0	1	11	2462	-17.58	-4.00	8.00	Pass
HT40	MCS0	1	3	2422	-20.40	-4.00	8.00	Pass
HT40	MCS0	1	6	2437	-19.33	-4.00	8.00	Pass
HT40	MCS0	1	9	2452	-18.89	-4.00	8.00	Pass



Appendix B. Radiated Test Results

15C 2.4GHz 2400~2483.5MHz

WIFI 802.11b (Band Edge @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b CH 01 2412MHz		2389.11	49.45	-24.55	74	41.09	32.6	5.1	29.34	158	23	P	H
		2389.38	40.97	-13.03	54	32.61	32.6	5.1	29.34	158	23	A	H
	*	2412	102.81	-	-	94.48	32.61	5.1	29.38	158	23	P	H
	*	2412	100.72	-	-	92.39	32.61	5.1	29.38	158	23	A	H
		2387.49	52.74	-21.26	74	44.38	32.6	5.1	29.34	152	103	P	V
		2389.38	43.7	-10.3	54	35.34	32.6	5.1	29.34	152	103	A	V
	*	2412	104.71	-	-	96.38	32.61	5.1	29.38	152	103	P	V
	*	2412	102.51	-	-	94.18	32.61	5.1	29.38	152	103	A	V
802.11b CH 06 2437MHz		2389.02	47.15	-26.85	74	38.79	32.6	5.1	29.34	150	23	P	H
		2379.93	35.75	-18.25	54	27.45	32.58	5.06	29.34	150	23	A	H
	*	2437	102.85	-	-	94.41	32.65	5.14	29.35	150	23	P	H
	*	2437	100.71	-	-	92.27	32.65	5.14	29.35	150	23	P	H
		2484.32	47.89	-26.11	74	39.31	32.68	5.21	29.31	150	23	P	H
		2491.64	36.51	-17.49	54	27.91	32.7	5.21	29.31	150	23	A	H
		2325.93	47.89	-26.11	74	39.6	32.53	5.03	29.27	153	84	P	V
		2388.57	36.13	-17.87	54	27.77	32.6	5.1	29.34	153	84	A	V
	*	2437	105.27	-	-	96.83	32.65	5.14	29.35	153	84	P	V
	*	2437	103.14	-	-	94.7	32.65	5.14	29.35	153	84	A	V
		2484.88	48.69	-25.31	74	40.11	32.68	5.21	29.31	153	84	P	V
		2491.52	37.2	-16.8	54	28.6	32.7	5.21	29.31	153	84	A	V



802.11b CH 11 2462MHz	*	2462	104.82	-	-	96.31	32.67	5.17	29.33	163	25	P	H
	*	2462	102.58	-	-	94.07	32.67	5.17	29.33	163	25	A	H
		2483.6	50.47	-23.53	74	41.89	32.68	5.21	29.31	163	25	P	H
		2483.52	41.27	-12.73	54	32.69	32.68	5.21	29.31	163	25	A	H
	*	2462	105.92	-	-	97.41	32.67	5.17	29.33	150	105	P	V
	*	2462	103.86	-	-	95.35	32.67	5.17	29.33	150	105	A	V
		2483.52	52.08	-21.92	74	43.5	32.68	5.21	29.31	150	105	P	V
		2483.52	43.94	-10.06	54	35.36	32.68	5.21	29.31	150	105	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



15C 2.4GHz 2400~2483.5MHz

WIFI 802.11b (Harmonic @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b CH 01 2412MHz		4824	49.15	-24.85	74	65.69	34.4	7.45	58.39	185	255	P	H
		4824	46.77	-27.23	74	63.31	34.4	7.45	58.39	185	255	P	V
802.11b CH 06 2437MHz		4874	46.07	-27.93	74	62.8	34.43	7.5	58.66	165	106	P	H
		7311	49.76	-24.24	74	62.45	36.22	9.71	58.62	174	100	P	H
		4874	44.44	-29.56	74	61.17	34.43	7.5	58.66	165	106	P	V
		7311	48.62	-25.38	74	61.31	36.22	9.71	58.62	174	100	P	V
802.11b CH 11 2462MHz		4924	46.96	-27.04	74	63.5	34.46	7.52	58.52	150	285	P	H
		7386	49.47	-24.53	74	61.96	36.26	9.79	58.54	155	274	P	H
		4924	45.29	-28.71	74	61.83	34.46	7.52	58.52	150	285	P	V
		7386	48.68	-25.32	74	61.17	36.26	9.79	58.54	155	274	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



15C 2.4GHz 2400~2483.5MHz
WIFI 802.11g (Band Edge @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11g CH 01 2412MHz		2389.47	56.94	-17.06	74	48.58	32.6	5.1	29.34	158	31	P	H
		2389.92	45.24	-8.76	54	36.92	32.6	5.1	29.38	158	31	A	H
	*	2412	102.16	-	-	93.83	32.61	5.1	29.38	158	31	P	H
	*	2412	94.93	-	-	86.6	32.61	5.1	29.38	158	31	A	H
		2389.83	57.4	-16.6	74	49.08	32.6	5.1	29.38	182	108	P	V
		2389.83	45.26	-8.74	54	36.94	32.6	5.1	29.38	182	108	A	V
	*	2412	104.58	-	-	96.25	32.61	5.1	29.38	182	108	P	V
	*	2412	96.58	-	-	88.25	32.61	5.1	29.38	182	108	A	V
802.11g CH 06 2437MHz		2383.44	48.12	-25.88	74	39.78	32.58	5.1	29.34	150	33	P	H
		2357.07	37.86	-16.14	54	29.55	32.56	5.06	29.31	150	33	A	H
	*	2437	103.55	-	-	95.11	32.65	5.14	29.35	150	33	P	H
	*	2437	95.44	-	-	87	32.65	5.14	29.35	150	33	A	H
		2486.68	50.92	-23.08	74	42.34	32.68	5.21	29.31	150	33	P	H
		2491.36	39.8	-14.2	54	31.2	32.7	5.21	29.31	150	33	A	H
		2389.92	49.3	-24.7	74	40.98	32.6	5.1	29.38	152	103	P	V
		2356.98	39.27	-14.73	54	30.96	32.56	5.06	29.31	152	103	A	V
	*	2437	105.73	-	-	97.29	32.65	5.14	29.35	152	103	P	V
	*	2437	98.22	-	-	89.78	32.65	5.14	29.35	152	103	A	V
		2483.88	51.46	-22.54	74	42.88	32.68	5.21	29.31	152	103	P	V
		2484.32	41.41	-12.59	54	32.83	32.68	5.21	29.31	152	103	A	V



802.11g CH 11 2462MHz	*	2462	105.36	-	-	96.85	32.67	5.17	29.33	163	33	P	H
	*	2462	97.19	-	-	88.68	32.67	5.17	29.33	163	33	A	H
		2483.64	62.57	-11.43	74	53.99	32.68	5.21	29.31	163	33	P	H
		2483.56	47.12	-6.88	54	38.54	32.68	5.21	29.31	163	33	A	H
	*	2462	105.44	-	-	96.93	32.67	5.17	29.33	150	120	P	V
	*	2462	97.49	-	-	88.98	32.67	5.17	29.33	150	120	A	V
		2483.6	68.03	-5.97	74	59.45	32.68	5.21	29.31	150	120	P	V
		2483.52	50.72	-3.28	54	42.14	32.68	5.21	29.31	150	120	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



15C 2.4GHz 2400~2483.5MHz
WIFI 802.11g (Harmonic @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11g CH 01 2412MHz		4824	45.34	-28.66	74	61.88	34.4	7.45	58.39	185	255	P	H
		4824	45.59	-28.41	74	62.13	34.4	7.45	58.39	185	255	P	V
802.11g CH 06 2437MHz		4874	44.61	-29.39	74	61.34	34.43	7.5	58.66	165	106	P	H
		7311	47.69	-26.31	74	60.38	36.22	9.71	58.62	174	100	P	H
		4874	44.3	-29.7	74	61.03	34.43	7.5	58.66	165	106	P	V
		7311	47.54	-26.46	74	60.23	36.22	9.71	58.62	174	100	P	V
802.11g CH 11 2462MHz		4924	45.11	-28.89	74	61.65	34.46	7.52	58.52	150	285	P	H
		7386	45.83	-28.17	74	58.32	36.26	9.79	58.54	155	274	P	H
		4924	45.38	-28.62	74	61.92	34.46	7.52	58.52	150	285	P	V
		7386	45.24	-28.76	74	57.73	36.26	9.79	58.54	155	274	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



15C 2.4GHz 2400~2483.5MHz

WIFI 802.11n HT20 (Band Edge @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11n HT20 CH 01 2412MHz		2389.92	56.95	-17.05	74	48.63	32.6	5.1	29.38	159	31	P	H
		2389.74	42.96	-11.04	54	34.6	32.6	5.1	29.34	159	31	A	H
	*	2412	100.86	-	-	92.53	32.61	5.1	29.38	159	31	P	H
	*	2412	92.83	-	-	84.5	32.61	5.1	29.38	159	31	A	H
		2389.83	59.39	-14.61	74	51.07	32.6	5.1	29.38	154	122	P	V
		2389.92	45.31	-8.69	54	36.99	32.6	5.1	29.38	154	122	A	V
	*	2412	102.91	-	-	94.58	32.61	5.1	29.38	154	122	P	V
	*	2412	95.14	-	-	86.81	32.61	5.1	29.38	154	122	A	V
802.11n HT20 CH 06 2437MHz		2386.14	47.5	-26.5	74	39.14	32.6	5.1	29.34	150	32	P	H
		2389.74	37.2	-16.8	54	28.84	32.6	5.1	29.34	150	32	A	H
	*	2437	101.23	-	-	92.79	32.65	5.14	29.35	150	32	P	H
	*	2437	93.24	-	-	84.8	32.65	5.14	29.35	150	32	A	H
		2490.28	49.9	-24.1	74	41.3	32.7	5.21	29.31	150	32	P	H
		2490.84	38.71	-15.29	54	30.11	32.7	5.21	29.31	150	32	A	H
		2380.65	48.36	-25.64	74	40.06	32.58	5.06	29.34	152	104	P	V
		2389.83	38.09	-15.91	54	29.77	32.6	5.1	29.38	152	104	A	V
	*	2437	103.62	-	-	95.18	32.65	5.14	29.35	152	104	P	V
	*	2437	95.65	-	-	87.21	32.65	5.14	29.35	152	104	A	V
		2492.4	51.01	-22.99	74	42.38	32.7	5.21	29.28	152	104	P	V
		2483.52	39.62	-14.38	54	31.04	32.68	5.21	29.31	152	104	A	V



802.11n HT20 CH 11 2462MHz	*	2462	102.89	-	-	94.38	32.67	5.17	29.33	162	32	P	H
	*	2462	95.34	-	-	86.83	32.67	5.17	29.33	162	32	A	H
		2484.52	60.11	-13.89	74	51.53	32.68	5.21	29.31	162	32	P	H
		2483.56	44.57	-9.43	54	35.99	32.68	5.21	29.31	162	32	A	H
	*	2462	103.74	-	-	95.23	32.67	5.17	29.33	150	121	P	V
	*	2462	95.57	-	-	87.06	32.67	5.17	29.33	150	121	A	V
		2484	64.19	-9.81	74	55.61	32.68	5.21	29.31	150	121	P	V
		2483.52	47.41	-6.59	54	38.83	32.68	5.21	29.31	150	121	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



15C 2.4GHz 2400~2483.5MHz

WIFI 802.11n HT20 (Harmonic @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11n HT20 CH 01 2412MHz		4824	45.26	-28.74	74	61.8	34.4	7.45	58.39	185	255	P	H
		4824	44.65	-29.35	74	61.19	34.4	7.45	58.39	185	255	P	V
802.11n HT20 CH 06 2437MHz		4874	44.45	-29.55	74	61.18	34.43	7.5	58.66	165	106	P	H
		7311	46.49	-27.51	74	59.18	36.22	9.71	58.62	174	100	P	H
		4874	44.21	-29.79	74	60.94	34.43	7.5	58.66	165	106	P	V
		7311	46.44	-27.56	74	59.13	36.22	9.71	58.62	174	100	P	V
802.11n HT20 CH 11 2462MHz		4924	44.94	-29.06	74	61.48	34.46	7.52	58.52	150	285	P	H
		7386	47.33	-26.67	74	59.82	36.26	9.79	58.54	155	274	P	H
		4924	45.19	-28.81	74	61.73	34.46	7.52	58.52	150	285	P	V
		7386	45.56	-28.44	74	58.05	36.26	9.79	58.54	155	274	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



15C 2.4GHz 2400~2483.5MHz

WIFI 802.11n HT40 (Band Edge @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11n HT40 CH 03 2422MHz		2389.56	61.11	-12.89	74	52.75	32.6	5.1	29.34	183	52	P	H
		2389.47	44.94	-9.06	54	36.58	32.6	5.1	29.34	183	52	A	H
	*	2422	96.75	-	-	88.33	32.63	5.14	29.35	183	52	P	H
	*	2422	89.12	-	-	80.7	32.63	5.14	29.35	183	52	A	H
		2494.48	51.72	-22.28	74	43.09	32.7	5.21	29.28	183	52	P	H
		2484.48	38.41	-15.59	54	29.83	32.68	5.21	29.31	183	52	A	H
		2388.12	64.74	-9.26	74	56.38	32.6	5.1	29.34	150	78	P	V
		2388.3	48.44	-5.56	54	40.08	32.6	5.1	29.34	150	78	A	V
	*	2422	98.57	-	-	90.15	32.63	5.14	29.35	150	78	P	V
	*	2422	90.67	-	-	82.25	32.63	5.14	29.35	150	78	A	V
		2490.96	53.02	-20.98	74	44.42	32.7	5.21	29.31	150	78	P	V
		2485.56	39.33	-14.67	54	30.75	32.68	5.21	29.31	150	78	A	V
802.11n HT40 CH 06 2437MHz		2389.92	48.87	-25.13	74	40.55	32.6	5.1	29.38	208	52	P	H
		2389.65	38.51	-15.49	54	30.15	32.6	5.1	29.34	208	52	A	H
	*	2437	98.39	-	-	89.95	32.65	5.14	29.35	208	52	P	H
	*	2437	90.18	-	-	81.74	32.65	5.14	29.35	208	52	A	H
		2486.76	54.9	-19.1	74	46.32	32.68	5.21	29.31	208	52	P	H
		2484	40.33	-13.67	54	31.75	32.68	5.21	29.31	208	52	A	H
		2384.7	49.71	-24.29	74	41.37	32.58	5.1	29.34	166	78	P	V
		2381.1	38.46	-15.54	54	30.16	32.58	5.06	29.34	166	78	A	V
	*	2437	98.3	-	-	89.86	32.65	5.14	29.35	166	78	P	V
	*	2437	90.17	-	-	81.73	32.65	5.14	29.35	166	78	A	V
		2492.16	55.44	-18.56	74	46.81	32.7	5.21	29.28	166	78	P	V
		2485.04	40.32	-13.68	54	31.74	32.68	5.21	29.31	166	78	A	V



802.11n HT40 CH 09 2452MHz		2381.55	47.03	-26.97	74	38.73	32.58	5.06	29.34	150	52	P	H
		2386.59	37.24	-16.76	54	28.88	32.6	5.1	29.34	150	52	A	H
	*	2452	99.03	-	-	90.54	32.65	5.17	29.33	150	52	P	H
	*	2452	91.22	-	-	82.73	32.65	5.17	29.33	150	52	A	H
		2484.72	68.59	-5.41	74	60.01	32.68	5.21	29.31	150	52	P	H
		2484.52	48.37	-5.63	54	39.79	32.68	5.21	29.31	150	52	A	H
		2388.66	48.96	-25.04	74	40.6	32.6	5.1	29.34	150	81	P	V
		2389.47	38.13	-15.87	54	29.77	32.6	5.1	29.34	150	81	A	V
	*	2452	99.8	-	-	91.31	32.65	5.17	29.33	150	81	P	V
	*	2452	91.76	-	-	83.27	32.65	5.17	29.33	150	81	A	V
		2484.32	69.41	-4.59	74	60.83	32.68	5.21	29.31	150	81	P	V
		2484.4	48.95	-5.05	54	40.37	32.68	5.21	29.31	150	81	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



15C 2.4GHz 2400~2483.5MHz
WIFI 802.11n HT40 (Harmonic @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11n		4844	45.08	-28.92	74	61.67	34.41	7.48	58.48	150	350	P	H
HT40		7266	47.21	-26.79	74	59.91	36.21	9.62	58.53	200	360	P	H
CH 03		4844	45.47	-28.53	74	62.06	34.41	7.48	58.48	150	350	P	V
2422MHz		7266	49.02	-24.98	74	61.72	36.21	9.62	58.53	200	360	P	V
802.11n		4874	44.41	-29.59	74	61.14	34.43	7.5	58.66	150	360	P	H
HT40		7311	46.51	-27.49	74	59.2	36.22	9.71	58.62	150	360	P	H
CH 06		4874	44.35	-29.65	74	61.08	34.43	7.5	58.66	150	360	P	V
2437MHz		7311	46.16	-27.84	74	58.85	36.22	9.71	58.62	150	360	P	V
802.11n		4904	44.49	-29.51	74	61.16	34.45	7.52	58.64	150	360	P	H
HT40		7356	47.07	-26.93	74	59.65	36.24	9.75	58.57	150	360	P	H
CH 09		4904	44.76	-29.24	74	61.43	34.45	7.52	58.64	150	360	P	V
2452MHz		7356	46.19	-27.81	74	58.77	36.24	9.75	58.57	150	360	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



15C Emission below 1GHz

2.4GHz WIFI 802.11g (LF)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
2.4GHz 802.11g LF		82.38	33.47	-6.53	40	47.73	10.26	1.33	25.85	100	360	P	H
		131.85	35.31	-8.19	43.5	45.02	14.18	1.72	25.61	-	-	P	H
		182.29	29.2	-14.3	43.5	41.02	11.51	2.01	25.34	-	-	P	H
		442.25	24.46	-21.54	46	30.06	17.09	3.34	26.03	-	-	P	H
		671.17	28	-18	46	29.77	20.13	4.49	26.39	-	-	P	H
		928.22	29.8	-16.2	46	28.51	21.49	5.46	25.66	-	-	P	H
		30	36.26	-3.74	40	35.97	25.6	0.76	26.07	100	0	P	V
		94.02	38.8	-4.7	43.5	52.21	10.98	1.41	25.8	-	-	P	V
		201.69	24.52	-18.98	43.5	35.99	11.63	2.15	25.25	-	-	P	V
		486.87	24.34	-21.66	46	28.17	18.86	3.58	26.27	-	-	P	V
		657.59	27.41	-18.59	46	29.34	20.04	4.43	26.4	-	-	P	V
		798.24	30.28	-15.72	46	29.03	22.46	4.96	26.17	-	-	P	V
Remark	1. No other spurious found. 2. All results are PASS against limit line.												

**Note symbol**

*	Fundamental Frequency which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency per 15.209(c).
!	Test result is over limit line.
P/A	P eak or A verage
H/V	H orizontal or V ertical



A calculation example for radiated spurious emission is shown as below:

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1+2		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
CH 01													
2412MHz		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

1. Level(dBμV/m) =

Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

2. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

For Peak Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)

= 55.45 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 55.45(dBμV/m) – 74(dBμV/m)

= -18.55(dB)

For Average Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)

= 43.54 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 43.54(dBμV/m) – 54(dBμV/m)

= -10.46(dB)

Both peak and average measured complies with the limit line, so test result is “PASS”.