EMC TEST REPORT

Report No.: 17070764-FCC-E

Supersede Report No: N/A

Applicant	BLU Products, Inc.
Product Name	Mobile Phone
Model No.	STUDIO G3
Serial No.	N/A
Test Standard	FCC Part 15 Subpart B Class B:2016, ANSI C63.4: 2014
Test Date	August 19 to September 05, 2017
Issue Date	September 06, 2017
Test Result	☑ Pass ☐ Fail
Equipment complied with the specification	☑
Equipment did not comply with the specification	☐

Evans He	David Huang	
Evans He Test Engineer	David Huang Checked By	

This test report may be reproduced in full only

Test result presented in this test report is applicable to the tested sample only

Issued by:

SIEMIC (SHENZHEN-CHINA) LABORATORIES

Zone A, Floor 1, Building 2 Wan Ye Long Technology Park

South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108

Phone: +86 0755 2601 4629801 Email: China@siemic.com.cn

Laboratories Introduction

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.

In addition to testing and certification, SIEMIC provides initial design reviews and compliance management throughout a project. Our extensive experience with China, Asia Pacific, North America, European, and International compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the global markets.

Accreditations for Conformity Assessment

Country/Region	Scope
USA	EMC, RF/Wireless, SAR, Telecom
Canada	EMC, RF/Wireless, SAR, Telecom
Taiwan	EMC, RF, Telecom, SAR, Safety
Hong Kong	RF/Wireless, SAR, Telecom
Australia	EMC, RF, Telecom, SAR, Safety
Korea	EMI, EMS, RF, SAR, Telecom, Safety
Japan	EMI, RF/Wireless, SAR, Telecom
Singapore	EMC, RF, SAR, Telecom
Europe	EMC, RF, SAR, Telecom, Safety

This page has been left blank intentionally.

CONTENTS

1. REPORT REVISION HISTORY 5

2. CUSTOMER INFORMATION 5

3. TEST SITE INFORMATION 5

4. EQUIPMENT UNDER TEST (EUT) INFORMATION 6

5. TEST SUMMARY 8

6. MEASUREMENTS, EXAMINATION AND DERIVED RESULTS 9

6.1 AC POWER LINE CONDUCTED EMISSIONS 9

6.2 RADIATED EMISSIONS 15

ANNEX A. TEST INSTRUMENT 20

ANNEX B. EUT AND TEST SETUP PHOTOGRAPHS 21

ANNEX C. TEST SETUP AND SUPPORTING EQUIPMENT 32

ANNEX D. USER MANUAL / BLOCK DIAGRAM / SCHEMATICS / PARTLIST 35

ANNEX E. DECLARATION OF SIMILARITY 36

1. Report Revision History

Report No.	Report Version	Description	Issue Date
17070764-FCC-E	NONE	Original	September 06, 2017

2. Customer information

Applicant Name	BLU Products, Inc.
Applicant Add	10814 NW 33rd St # 100 Doral, FL 33172
Manufacturer	BLU Products, Inc.
Manufacturer Add	10814 NW 33rd St # 100 Doral, FL 33172

3. Test site information

Lab performing tests	SIEMIC (Shenzhen-China) LABORATORIES
Lab Address	Zone A, Floor 1, Building 2 Wan Ye Long Technology Park South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108
FCC Test Site No.	535293
IC Test Site No.	4842E-1
Test Software of Radiated Emission	Radiated Emission Program-To Shenzhen v2.0
Test Software of Conducted Emission	EZ-EMC(ver.lcp-03A1)

4. Equipment under Test (EUT) Information

Description of EUT:	Mobile Phone
Main Model:	STUDIO G3
Serial Model:	N/A
Antenna Gain:	GSM850: -3.7dBi PCS1900: -3.5dBi UMTS-FDD Band V: -3.0dBi UMTS-FDD Band IV: -2.5dBi UMTS-FDD Band II: -2.5dBi WIFI: -4.13dBi Bluetooth/BLE: -4.13dBi GPS: -3.2dBi
Antenna Type:	PIFA antenna
Input Power:	Adapter: Model: US-BB-1000 Input: AC100-240V~50/60Hz,0.2A Output: DC 5.0V,1.0A Battery: Model: C745343205L Spec: 3.8V, 2050mAh, 7.79Wh
Equipment Category：	JBP
Type of Modulation:	GSM / GPRS: GMSK EGPRS: GMSK,8PSK UMTS-FDD: QPSK 802.11b/g/n: DSSS, OFDM Bluetooth: GFSK, π /4DQPSK, 8DPSK BLE: GFSK GPS:BPSK
RF Operating Frequency (ies):	GSM850 TX: 824.2 ~ 848.8 MHz; RX: 869.2 ~ 893.8 MHz PCS1900 TX: 1850.2 ~ 1909.8 MHz; RX: 1930.2 ~ 1989.8 MHz

	UMTS-FDD Band V TX: 826.4 ~ 846.6 MHz; RX: 871.4 ~ 891.6 MHz UMTS-FDD Band IV TX:1712.4 ~ 1752.6 MHz; RX : 2112.4 ~ 2152.6 MHz UMTS-FDD Band II TX:1852.4 ~ 1907.6 MHz; RX: 1932.4 ~ 1987.6 MHz WIFI: 802.11b/g/n(20M): 2412-2462 MHz WIFI: 802.11n(40M): 2422-2452 MHz Bluetooth& BLE: 2402-2480 MHz GPS: 1575.42 MHz
Number of Channels:	GSM 850: 124CH PCS1900: 299CH UMTS-FDD Band V: 102CH UMTS-FDD Band IV: 202CH UMTS-FDD Band II: 277CH WIFI :802.11b/g/n(20M): 11CH WIFI :802.11n(40M): 7CH Bluetooth: 79CH BLE: 40CH GPS:1CH
Port:	USB Port, Earphone Port
Trade Name :	BLU
FCC ID:	YHLBLUSTUDIOG3
GPRS/ EGPRS Multi-slot class	8/10/12
Date EUT received:	August 18, 2017
Test Date(s):	August 19 to September 05, 2017

5. Test Summary

The product was tested in accordance with the following specifications.

All testing has been performed according to below product classification:

FCC Rules	Description of Test	Result
§15.107; ANSI C63.4: 2014	AC Power Line Conducted Emissions	Compliance
§15.109; ANSI C63.4: 2014	Radiated Emissions	Compliance

Measurement Uncertainty

Parameter	Uncertainty
AC Power Line Conducted Emissions (150kHz~30MHz)	±3.11dB
Radiated Emission(30MHz~1GHz)	±5.12dB
Radiated Emission(1GHz~6GHz)	±5.34dB

6. Measurements, Examination And Derived Results

6.1 AC Power Line Conducted Emissions

Temperature	26 °C
Relative Humidity	57%
Atmospheric Pressure	1025mbar
Test date :	August 25, 2017
Tested By :	Evans He

Requirement(s):

<table>
<tr><th>Spec</th><th>Item</th><th>Requirement</th><th>Applicable</th></tr>
<tr><td>47CFR§15.107</td><td>a)</td><td>For Low-power radio-frequency devices that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 [mu] H/50 ohms line impedance stabilization network (LISN). The lower limit applies at the boundary between the frequencies ranges.
<table>
<tr><th rowspan="2">Frequency ranges (MHz)</th><th colspan="2">Limit (dBμV)</th></tr>
<tr><th>QP</th><th>Average</th></tr>
<tr><td>0.15 ~ 0.5</td><td>66 – 56</td><td>56 – 46</td></tr>
<tr><td>0.5 ~ 5</td><td>56</td><td>46</td></tr>
<tr><td>5 ~ 30</td><td>60</td><td>50</td></tr>
</table></td><td>☑</td></tr>
<tr><td>Test Setup</td><td colspan="3"> 

Note: 1.Support units were connected to second LISN.
2.Both of LISNs (AMN) are 80cm from EUT and at least 80cm from other units and other metal planes support units.</td></tr>
<tr><td>Procedure</td><td colspan="3">1. The EUT and supporting equipment were set up in accordance with the requirements of the standard on top of a 1.5m x 1m x 0.8m high, non-metallic table.
2. The power supply for the EUT was fed through a 50Ω /50mH EUT LISN, connected to filtered mains.</td></tr>
</table>

	3. The RF OUT of the EUT LISN was connected to the EMI test receiver via a low-loss coaxial cable. 4. All other supporting equipment were powered separately from another main supply. 5. The EUT was switched on and allowed to warm up to its normal operating condition. 6. A scan was made on the NEUTRAL line (for AC mains) or Earth line (for DC power) over the required frequency range using an EMI test receiver. 7. High peaks, relative to the limit line, The EMI test receiver was then tuned to the selected frequencies and the necessary measurements made with a receiver bandwidth setting of 10 kHz. 8. Step 7 was then repeated for the LIVE line (for AC mains) or DC line (for DC power).
Remark	
Result	☑ Pass ☐ Fail

Test Data ☑ Yes ☐ N/A

Test Plot ☑ Yes (See below) ☐ N/A

Test Mode :	USB Mode



Test Data

Phase Line Plot at 120Vac, 60Hz

No.	P/L	Frequency	Reading	Detector	Corrected	Result	Limit	Margin
		(MHz)	(dBuV)		(dB}	(dBuV)	(dBuV)	(dB)
1	L1	0.5166	30.25	QP	10.03	40.28	56.00	-15.72
2	L1	0.5166	19.70	AVG	10.03	29.73	46.00	-16.27
3	L1	0.7428	24.80	QP	10.03	34.83	56.00	-21.17
4	L1	0.7428	14.15	AVG	10.03	24.18	46.00	-21.82
5	L1	1.2810	23.90	QP	10.03	33.93	56.00	-22.07
6	L1	1.2810	14.36	AVG	10.03	24.39	46.00	-21.61
7	L1	2.3262	22.95	QP	10.05	33.00	56.00	-23.00
8	L1	2.3262	13.27	AVG	10.05	23.32	46.00	-22.68
9	L1	2.8020	22.38	QP	10.05	32.43	56.00	-23.57
10	L1	2.8020	12.71	AVG	10.05	22.76	46.00	-23.24
11	L1	3.3120	21.92	QP	10.06	31.98	56.00	-24.02
12	L1	3.3120	11.45	AVG	10.06	21.51	46.00	-24.49

Test Mode:	USB Mode



Test Data

Phase Neutral Plot at 120Vac, 60Hz

No.	P/L	Frequency	Reading	Detector	Corrected	Result	Limit	Margin
		(MHz)	(dBuV)		(dB}	(dBuV)	(dBuV)	(dB)
1	N	0.5088	33.56	QP	10.02	43.58	56.00	-12.42
2	N	0.5088	23.14	AVG	10.02	33.16	46.00	-12.84
3	N	0.7428	27.06	QP	10.02	37.08	56.00	-18.92
4	N	0.7428	16.68	AVG	10.02	26.70	46.00	-19.30
5	N	1.2537	26.31	QP	10.03	36.34	56.00	-19.66
6	N	1.2537	16.81	AVG	10.03	26.84	46.00	-19.16
7	N	1.8192	25.35	QP	10.04	35.39	56.00	-20.61
8	N	1.8192	16.18	AVG	10.04	26.22	46.00	-19.78
9	N	2.3379	24.85	QP	10.04	34.89	56.00	-21.11
10	N	2.3379	15.09	AVG	10.04	25.13	46.00	-20.87
11	N	2.7825	24.09	QP	10.05	34.14	56.00	-21.86
12	N	2.7825	14.42	AVG	10.05	24.47	46.00	-21.53

Test Mode :	USB Mode



Test Data

Phase Line Plot at 240Vac, 60Hz

No.	P/L	Frequency	Reading	Detector	Corrected	Result	Limit	Margin
		(MHz)	(dBuV)		(dB}	(dBuV)	(dBuV)	(dB)
1	L1	0.2553	31.46	QP	10.03	41.49	61.58	-20.09
2	L1	0.2553	18.63	AVG	10.03	28.66	51.58	-22.92
3	L1	0.3684	22.69	QP	10.03	32.72	58.54	-25.82
4	L1	0.3684	9.81	AVG	10.03	19.84	48.54	-28.70
5	L1	0.5088	31.46	QP	10.03	41.49	56.00	-14.51
6	L1	0.5088	22.54	AVG	10.03	32.57	46.00	-13.43
7	L1	0.7272	25.59	QP	10.03	35.62	56.00	-20.38
8	L1	0.7272	15.56	AVG	10.03	25.59	46.00	-20.41
9	L1	2.1741	21.50	QP	10.04	31.54	56.00	-24.46
10	L1	2.1741	11.30	AVG	10.04	21.34	46.00	-24.66
11	L1	2.9151	21.80	QP	10.05	31.85	56.00	-24.15
12	L1	2.9151	12.35	AVG	10.05	22.40	46.00	-23.60

Test Mode :	USB Mode



Test Data

Phase Neutral Plot at 240Vac, 60Hz

No.	P/L	Frequency	Reading	Detector	Corrected	Result	Limit	Margin
		(MHz)	(dBuV)		(dB}	(dBuV)	(dBuV)	(dB)
1	N	0.3684	23.08	QP	10.03	33.11	58.54	-25.43
2	N	0.3684	8.31	AVG	10.03	18.34	48.54	-30.20
3	N	0.5010	27.02	QP	10.03	37.05	56.00	-18.95
4	N	0.5010	19.22	AVG	10.03	29.25	46.00	-16.75
5	N	0.6999	22.80	QP	10.03	32.83	56.00	-23.17
6	N	0.6999	11.54	AVG	10.03	21.57	46.00	-24.43
7	N	1.3668	20.82	QP	10.03	30.85	56.00	-25.15
8	N	1.3668	11.88	AVG	10.03	21.91	46.00	-24.09
9	N	2.1702	16.50	QP	10.04	26.54	56.00	-29.46
10	N	2.1702	8.02	AVG	10.04	18.06	46.00	-27.94
11	N	23.5608	15.54	QP	10.37	25.91	60.00	-34.09
12	N	23.5608	3.70	AVG	10.37	14.07	50.00	-35.93

6.2 Radiated Emissions

Temperature	26 °C
Relative Humidity	56%
Atmospheric Pressure	1022mbar
Test date :	August 26, 2017
Tested By :	Evans He

Requirement(s):

<table>
<tr><th>Spec</th><th>Item</th><th>Requirement</th><th>Applicable</th></tr>
<tr><td>47CFR§15.109(d)</td><td>a)</td><td>Except higher limit as specified elsewhere in other section, the emissions from the low-power radio-frequency devices shall not exceed the field strength levels specified in the following table and the level of any unwanted emissions shall not exceed the level of the fundamental emission. The tighter limit applies at the band edges
<table>
<tr><th>Frequency range (MHz)</th><th>Field Strength (μV/m)</th></tr>
<tr><td>30 – 88</td><td>100</td></tr>
<tr><td>88 – 216</td><td>150</td></tr>
<tr><td>216 - 960</td><td>200</td></tr>
<tr><td>Above 960</td><td>500</td></tr>
</table></td><td>☑</td></tr>
<tr><td>Test Setup</td><td colspan="3"> 
</td></tr>
<tr><td>Procedure</td><td colspan="3">1. The EUT was switched on and allowed to warm up to its normal operating condition.
2. The test was carried out at the selected frequency points obtained from the EUT characterization. Maximization of the emissions, was carried out by rotating the EUT, changing the antenna polarization, and adjusting the antenna height in the following manner:
a. Vertical or horizontal polarization (whichever gave the higher emission level</td></tr>
</table>

	over a full rotation of the EUT) was chosen. b. The EUT was then rotated to the direction that gave the maximum emission. c. Finally, the antenna height was adjusted to the height that gave the maximum emission. 3. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasiy Peak detection at frequency below 1GHz. 4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz with Peak detection for Peak measurement at frequency above 1GHz. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth with Peak detection for Average Measurement as below at frequency above 1GHz. ■ 1 kHz (Duty cycle < 98%) □ 10 Hz (Duty cycle > 98%) 5. Steps 2 and 3 were repeated for the next frequency point, until all selected frequency points were measured.
Remark	
Result	☑ Pass ☐ Fail

Test Data ☑ Yes ☐ N/A

Test Plot ☑ Yes (See below) ☐ N/A

Test Mode :	USB Mode

Below 1GHz



Test Data

Horizontal Polarity Plot @3m

No.	P/L	Frequency	Reading	Detector	Ant_F	PA_G	Cab_L	Result	Limit	Margin	Height	Degree
		(MHz)	(dBuV/m)		(dB/m)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	(cm)	( )
1	H	64.8865	47.14	peak	7.54	22.40	0.88	33.16	40.00	-6.84	100	174
2	H	166.0680	40.94	peak	12.11	22.26	1.37	32.16	43.50	-11.34	100	129
3	H	232.5318	43.50	peak	11.64	22.32	1.64	34.46	46.00	-11.54	100	96
4	H	332.5187	38.81	peak	14.28	22.20	1.95	32.84	46.00	-13.16	100	119
5	H	485.6093	30.22	peak	17.41	21.84	2.34	28.13	46.00	-17.87	100	118
6	H	833.3171	35.90	peak	21.77	21.06	2.90	39.51	46.00	-6.49	100	295

Below 1GHz



Test Data

Vertical Polarity Plot @3m

No.	P/L	Frequency	Reading	Detector	Ant_F	PA_G	Cab_L	Result	Limit	Margin	Height	Degree
		(MHz)	(dBuV/m)		(dB/m)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	(cm)	( )
1	V	57.9993	51.57	QP	7.52	22.40	0.76	37.45	40.00	-2.55	100	79
2	V	65.3432	51.14	QP	7.57	22.39	0.89	37.21	40.00	-2.79	100	141
3	V	165.4867	45.82	peak	12.16	22.26	1.37	37.09	43.50	-6.41	100	320
4	V	232.5318	52.02	QP	11.64	22.32	1.64	42.98	46.00	-3.02	100	169
5	V	485.6093	35.65	peak	17.41	21.84	2.34	33.56	46.00	-12.44	100	22
6	V	830.4002	32.23	peak	21.73	21.07	2.91	35.80	46.00	-10.20	100	65

Above 1GHz

Frequency (MHz)	Read_level (dBμV/m)	Azimuth	Height (cm)	Polarity (H/V)	Level (dBμV/m)	Factors (dB)	Limit (dBμV/m)	Margin (dB)	Detector (PK/AV)
1579.5	67.06	331	100	V	-18.55	48.51	74	-25.49	PK
1684.4	62.33	242	100	V	-17.51	44.82	74	-29.18	PK
2364.3	59.17	276	100	V	-14.18	44.99	74	-29.01	PK
1655.5	68.08	271	100	H	-17.26	50.82	74	-23.18	PK
2170	64.05	196	100	H	-14.7	49.35	74	-24.65	PK
2850.3	62.98	116	100	H	-13.15	49.83	74	-24.17	PK

*Note1: The highest frequency of the EUT is 2480 MHz, so the testing has been conformed to 5*2480MHz=12,400MHz.*

Note2: The frequency that above 3GHz is mainly from the environment noise.

Note3: The AV measurement performed, more than 20dB below limit so AV test data was not presented.

Annex A. TEST INSTRUMENT

Instrument	Model	Serial #	Cal Date	Cal Due	In use
AC Line Conducted Emissions					
EMI test receiver	ESCS30	8471241027	09/16/2016	09/15/2017	☑
Line Impedance Stabilization Network	LI-125A	191106	09/24/2016	09/23/2017	☑
Line Impedance Stabilization Network	LI-125A	191107	09/24/2016	09/23/2017	☑
ISN	ISN T800	34373	09/24/2016	09/23/2017	☐
Transient Limiter	LIT-153	531118	08/30/2017	08/29/2018	☑
Radiated Emissions					
EMI test receiver	ESL6	100262	09/16/2016	09/15/2017	☑
OPT 010 AMPLIFIER (0.1-1300MHz)	8447E	2727A02430	08/30/2017	08/29/2018	☑
Microwave Preamplifier (1 ~ 26.5GHz)	8449B	3008A02402	03/23/2017	03/22/2018	☑
Bilog Antenna (30MHz~6GHz)	JB6	A110712	09/20/2016	09/19/2017	☑
Double Ridge Horn Antenna	AH-118	71259	09/23/2016	09/22/2017	☑

Annex B. EUT And Test Setup Photographs

Annex B.i. Photograph: EUT External Photo

Whole Package View

Adapter View



EUT - Front View

EUT - Rear View

EUT - Top View



EUT - Bottom View



EUT - Left View



EUT - Right View



Annex B.ii. Photograph: EUT Internal Photo

Cover Off - Top View 1

Cover Off - Top View 2

Battery - Front View



Battery - Rear View

Mainboard with Shielding – Front View



Mainboard with Shielding – Rear View



Mainboard without Shielding – Rear View



LCD – Front View

LCD – Rear View

GSM/PCS/UMTS-FDD - Antenna View



WIFI/BT/BLE/GPS - Antenna View

Annex B.iii. Photograph: Test Setup Photo

Conducted Emissions Test Setup – Front View



Conducted Emissions Test Setup – Side View



Radiated Emissions Test Setup Below 1GHz



Radiated Emissions Test Setup Above 1GHz

Annex C. TEST SETUP AND SUPPORTING EQUIPMENT

Annex C.ii. TEST SET UP BLOCK

Block Configuration Diagram for Conducted Emissions



Block Configuration Diagram for Radiated Emissions



Annex C. iI. SUPPORTING EQUIPMENT DESCRIPTION

The following is a description of supporting equipment and details of cables used with the EUT.

Supporting Equipment:

Manufacturer	Equipment Description	Model	Serial No
Lenovo	Laptop	E40	LR-1EHRX
GOLDWEB	Router	R102	1202032094
Lenovo	AC Adapter	42T4416	21D9JU
HP	Printer	VCVRA-1003	CN36M19JWX
DELL	Mouse	E100	912NMTUT41481
BULL	Socket	GN-403	GN201203
SAMSUNG	headset	HS330	N/A

Supporting Cable:

Cable type	Shield Type	Ferrite Core	Length	Serial No
USB Cable	Un-shielding	No	2m	JX120051274
USB Cable	Un-shielding	No	2m	CBA3000AH0C1
RJ45 Cable	Un-shielding	No	2m	KX156327541
Router Power cable	Un-shielding	No	2m	13274630Z
Printer Power cable	Un-shielding	No	2m	127581031
Power Cable	Un-shielding	No	0.8m	GT211032
Earphone Cables	Un-shielding	No	0.5m	N/A

Annex D. User Manual / Block Diagram / Schematics / Partlist

Please see the attachment

Annex E. DECLARATION OF SIMILARITY

N/A