RF TEST REPORT

Report No.: 17071152-FCC-R1

Supersede Report No.: N/A

Applicant	BLU Products, Inc.
Product Name	Mobile Phone
Model No.	STUDIO VIEW
Serial No.	N/A
Test Standard	FCC Part 22(H):2016 ;FCC Part 24(E):2016; FCC Part 27:2016; ANSI/TIA-603-D: 2010
Test Date	October 31 to November 19, 2017
Issue Date	November 20, 2017
Test Result	☑ Pass ☐ Fail
Equipment complied with the specification	☑
Equipment did not comply with the specification	☐

Loren Luo	David Huang	
Loren Luo Test Engineer	David Huang Checked By	

This test report may be reproduced in full only

Test result presented in this test report is applicable to the tested sample only

Issued by:

SIEMIC (SHENZHEN-CHINA) LABORATORIES

Zone A, Floor 1, Building 2 Wan Ye Long Technology Park

South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108

Phone: +86 0755 2601 4629801 Email: China@siemic.com.cn

Laboratories Introduction

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.

In addition to testing and certification, SIEMIC provides initial design reviews and compliance management throughout a project. Our extensive experience with China, Asia Pacific, North America, European, and International compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the global markets.

Accreditations for Conformity Assessment

Country/Region	Scope
USA	EMC, RF/Wireless, SAR, Telecom
Canada	EMC, RF/Wireless, SAR, Telecom
Taiwan	EMC, RF, Telecom, SAR, Safety
Hong Kong	RF/Wireless, SAR, Telecom
Australia	EMC, RF, Telecom, SAR, Safety
Korea	EMI, EMS, RF, SAR, Telecom, Safety
Japan	EMI, RF/Wireless, SAR, Telecom
Singapore	EMC, RF, SAR, Telecom
Europe	EMC, RF, SAR, Telecom, Safety

This page has been left blank intentionally.

CONTENTS

1. REPORT REVISION HISTORY 5

2. CUSTOMER INFORMATION 5

3. TEST SITE INFORMATION 5

4. EQUIPMENT UNDER TEST (EUT) INFORMATION 6

5. TEST SUMMARY 9

6. MEASUREMENTS, EXAMINATION AND DERIVED RESULTS 10

6.1 RF EXPOSURE (SAR) 10

6.2 RF OUTPUT POWER 11

6.3 PEAK-AVERAGE RATIO 24

6.4 OCCUPIED BANDWIDTH 29

6.5 SPURIOUS EMISSIONS AT ANTENNA TERMINALS 44

6.6 SPURIOUS RADIATED EMISSIONS 60

6.7 BAND EDGE 67

6.8 FREQUENCY STABILITY 81

ANNEX A. TEST INSTRUMENT 86

ANNEX B. EUT AND TEST SETUP PHOTOGRAPHS 88

ANNEX C. TEST SETUP AND SUPPORTING EQUIPMENT 101

ANNEX C.II. EUT OPERATING CONKITIONS 103

ANNEX D. USER MANUAL / BLOCK DIAGRAM / SCHEMATICS / PARTLIST 104

ANNEX E. DECLARATION OF SIMILARITY 105

1. Report Revision History

Report No.	Report Version	Description	Issue Date
17071152-FCC-R1	NONE	Original	November 20, 2017

2. Customer information

Applicant Name	BLU Products, Inc.
Applicant Add	10814 NW 33rd St # 100 Doral, FL 33172
Manufacturer	BLU Products, Inc.
Manufacturer Add	10814 NW 33rd St # 100 Doral, FL 33172

3. Test site information

Test Lab A:

Lab performing tests	SIEMIC (Shenzhen-China) LABORATORIES
Lab Address	Zone A, Floor 1, Building 2 Wan Ye Long Technology Park South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108
FCC Test Site No.	535293
IC Test Site No.	4842E-1
Test Software	Radiated Emission Program-To Shenzhen v2.0

Test Lab B:

Lab performing tests	SIEMIC (Nanjing-China) Laboratories
Lab Address	2-1 Longcang Avenue Yuhua Economic and Technology Development Park, Nanjing, China
FCC Test Site No.	694825
IC Test Site No.	4842B-1
Test Software	EZ_EMC(ver.lcp-03A1)

Note: We just perform Radiated Spurious Emission above 18GHz in the test Lab. B.

4. Equipment under Test (EUT) Information

Description of EUT:	Mobile Phone
Main Model:	STUDIO VIEW
Serial Model:	N/A
Date EUT received:	October 30, 2017
Test Date(s):	October 31 to November 19, 2017
Equipment Category :	PCE
Antenna Gain:	GSM850: -3.8dBi PCS1900: -2.5dBi UMTS-FDD Band V: -3.8dBi UMTS-FDD Band IV: -2.3dBi UMTS-FDD Band II: -2.7dBi WIFI: -3.6dBi Bluetooth/BLE: -3.3dBi GPS: -3.3dBi
Antenna Type:	PIFA antenna
Type of Modulation:	GSM / GPRS: GMSK EGPRS: GMSK UMTS-FDD: QPSK 802.11b/g/n: DSSS, OFDM Bluetooth: GFSK, π /4DQPSK, 8DPSK BLE: GFSK GPS:BPSK
RF Operating Frequency (ies):	GSM850 TX: 824.2 ~ 848.8 MHz; RX: 869.2 ~ 893.8 MHz PCS1900 TX: 1850.2 ~ 1909.8 MHz; RX: 1930.2 ~ 1989.8 MHz UMTS-FDD Band V TX: 826.4 ~ 846.6 MHz; RX: 871.4 ~ 891.6 MHz UMTS-FDD Band IV TX:1712.4 ~ 1752.6 MHz; RX : 2112.4 ~ 2152.6 MHz UMTS-FDD Band II TX:1852.4 ~ 1907.6 MHz; RX: 1932.4 ~ 1987.6 MHz

	WIFI: 802.11b/g/n(20M): 2412-2462 MHz WIFI: 802.11n(40M): 2422-2452 MHz Bluetooth& BLE: 2402-2480 MHz GPS: 1575.42 MHz
Maximum Conducted AV Power to Antenna:	GSM Vioce:GSM850: 32.18 dBm PCS1900: 29.28 dBm GPRS:GSM850: 32.16 dBm PCS1900: 29.24 dBm EGPRS(MCS1):GSM850: 32.08 dBm PCS1900: 29.27 dBm RMC:UMTS-FDD Band V: 22.85 dBm UMTS-FDD Band II: 22.75 dBm UMTS-FDD Band IV: 23.52 dBm HSDPA:UMTS-FDD Band V: 22.29 dBm UMTS-FDD Band II: 22.25 dBm UMTS-FDD Band IV: 22.93 dBm HSUPA:UMTS-FDD Band V: 22.27 dBm UMTS-FDD Band II: 22.10 dBm UMTS-FDD Band IV: 22.99 dBm
ERP/EIRP:	GSM Vioce:GSM850: 26.23 dBm / ERP PCS1900: 26.78 dBm / EIRP GPRS:GSM850: 26.21 dBm / ERP PCS1900: 26.74 dBm / EIRP EGPRS(MCS1):GSM850: 26.13 dBm / ERP PCS1900: 26.77 dBm / EIRP RMC:UMTS-FDD Band V: 16.15 dBm / ERP UMTS-FDD Band II: 19.50 dBm / EIRP UMTS-FDD Band IV: 19.79 dBm / EIRP HSDPA:UMTS-FDD Band V: 15.56 dBm / ERP UMTS-FDD Band II: 18.94 dBm / EIRP UMTS-FDD Band IV: 19.13 dBm / EIRP HSUPA:UMTS-FDD Band V: 15.54 dBm / ERP UMTS-FDD Band II: 18.88 dBm / EIRP UMTS-FDD Band IV: 19.28 dBm / EIRP

Number of Channels:	GSM 850: 124CH PCS1900: 299CH UMTS-FDD Band V: 102CH UMTS-FDD Band IV: 202CH UMTS-FDD Band II: 277CH WIFI :802.11b/g/n(20M): 11CH WIFI :802.11n(40M): 7CH Bluetooth: 79CH BLE: 40CH GPS:1CH
Port:	USB Port, Earphone Port
Input Power:	Adapter: Model: TPA-46050150UU Input: AC100-240V~50/60Hz,0.3A Output: DC 5.0V,1.5A Battery: Model: C765640280P Spec: 3.8V, 2850mAh, 10.83Wh
Trade Name :	BLU
GPRS/ EGPRS Multi-slot class	8/10/11/12
FCC ID:	YHLBLUSTUDIOVIEW

5. Test Summary

The product was tested in accordance with the following specifications.

All testing has been performed according to below product classification:

FCC Rules	Description of Test	Result
§ 1.1307; § 2.1093	RF Exposure (SAR)	Compliance
§2.1046; § 22.913(a); § 24.232(c); § 27.50(c.10) ; § 27.50(d.4)	RF Output Power	Compliance
§ 24.232 (d) ; § 27.50(d)	Peak-Average Ratio	Compliance
§ 2.1049; § 22.905; § 22.917; § 24.238; § 27.53(a.5)	99% & -26 dB Occupied Bandwidth	Compliance
§ 2.1051; § 22.917(a); § 24.238(a); § 27.53(h)	Spurious Emissions at Antenna Terminal	Compliance
§ 2.1053; § 22.917(a); § 24.238(a); § 27.53(h)	Field Strength of Spurious Radiation	Compliance
§ 22.917(a); § 24.238(a); § 27.53(h)	Out of band emission, Band Edge	Compliance
§ 2.1055; § 22.355; § 24.235; § 27.5(h); § 27.54	Frequency stability vs. temperature Frequency stability vs. voltage	Compliance

Note: Testing was performed by configuring EUT to maximum output power status, the declared output power class for different

Measurement Uncertainty

Emissions		
Test Item	**Description**	**Uncertainty**
Band Edge and Radiated Spurious Emissions	Confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2 (for EUTs < 0.5m X 0.5m X 0.5m)	+5.6dB/-4.5dB
-	-	-

6. MEASUREMENTS, EXAMINATION AND DERIVED RESULTS

6.1 RF Exposure (SAR)

Test Result: Pass

The EUT is a portable device, thus requires SAR evaluation;

Please refer to RF Exposure Evaluation Report: 17071152-FCC-H.

6.2 RF Output Power

Temperature	24 °C
Relative Humidity	53%
Atmospheric Pressure	1010mbar
Test date :	November 15, 2017
Tested By :	Loren Luo

Requirement(s):

Spec	Item	Requirement	Applicable
§22.913 (a)	a)	ERP:38.45dBm	☑
§24.232 (c)	b)	EIRP:33dBm	☑
§27.50 (c)	c)	EIRP: 30dBm	☑
Test Setup			
Test Procedure	For Conducted Power: - The transmitter output port was connected to base station. - Set EUT at maximum power through base station. - Select lowest, middle, and highest channels for each band and different test mode. For ERP/EIRP: According with KDB 971168 v02r02 - The transmitter was placed on a wooden turntable, and it was transmitting into a non-radiating load which was also placed on the turntable. - The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis. - The frequency range up to tenth harmonic of the fundamental		

	frequency was investigated. - Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution. - Spurious emissions in dB = 10 log (TX power in Watts/0.001) – the absolute level - Spurious attenuation limit in dB = 43 + 10 Log10 (power out in Watts.
Remark	
Result	☑ Pass ☐ Fail

Test Data ☑ Yes ☐ N/A

Test Plot ☐ Yes (See below) ☑ N/A

Conducted Power

GSM Mode:

Burst Average Power (dBm);								
Band	GSM850				PCS1900			
Channel	128	190	251	Tune up Power tolerant	512	661	810	Tune up Power tolerant
Frequency (MHz)	824.2	836.6	848.8	/	1850.2	1880	1909.8	/
GSM Voice (1 uplink),GMSK	**32.18**	32.09	32.02	32±1	29.25	29.24	**29.28**	29±1
GPRS Multi-Slot Class 8 (1 uplink),GMSK	**32.16**	32.05	31.97	32±1	**29.24**	29.23	29.03	29±1
GPRS Multi-Slot Class 10 (2 uplink) GMSK	31.56	31.35	31.29	31±1	28.64	28.43	28.02	28±1
GPRS Multi-Slot Class 11 (3 uplink) GMSK	30.24	30.02	29.96	30±1	27.15	26.63	27.02	27±1
GPRS Multi-Slot Class 12 (4 uplink) GMSK	29.69	29.53	29.45	29±1	26.49	25.83	26.2	26±1
EGPRS Multi-Slot Class 8 (1 uplink) GMSK MCS1	**32.08**	32.01	31.96	32±1	**29.27**	29.25	29.01	29±1
EGPRS Multi-Slot Class 10 (2 uplink) GMSK MCS1	31.52	31.39	31.26	31±1	28.64	28.43	28.27	28±1
EGPRS Multi-Slot Class 11 (3 uplink) GMSK MCS1	30.22	30.02	29.91	30±1	27.14	26.64	27.01	27±1
EGPRS Multi-Slot Class 12 (4 uplink) GMSK MCS1	29.61	29.45	29.42	29±1	26.49	25.88	26.15	26±1
Remark : GPRS, CS1 coding scheme. EGPRS, MCS1 coding scheme.								

Multi-Slot Class 8 , Support Max 4 downlink, 1 uplink , 5 working link
Multi-Slot Class 10 , Support Max 4 downlink, 2 uplink , 5 working link
Multi-Slot Class 12 , Support Max 4 downlink, 4 uplink , 5 working link

UMTS Mode:

UMTS-FDD Band V

Band/ Time Slot configuration	Channel	Frequency	Average power (dBm)	Tune up Power tolerant
RMC 12.2kbps	4132	826.4	22.83	23±1
	4175	835	**22.85**	23±1
	4233	846.6	22.42	23±1
HSDPA Subtest1	4132	826.4	22.18	22±1
	4175	835	22.19	22±1
	4233	846.6	21.64	22±1
HSDPA Subtest2	4132	826.4	22.19	22±1
	4175	835	**22.29**	22±1
	4233	846.6	21.9	22±1
HSDPA Subtest3	4132	826.4	22.09	22±1
	4175	835	22.1	22±1
	4233	846.6	21.82	22±1
HSDPA Subtest4	4132	826.4	22.27	22±1
	4175	835	22.17	22±1
	4233	846.6	21.77	22±1
HSUPA Subtest1	4132	826.4	22.04	22±1
	4175	835	22.13	22±1
	4233	846.6	21.8	22±1
HSUPA Subtest2	4132	826.4	22.12	22±1
	4175	835	22.18	22±1
	4233	846.6	21.69	22±1
HSUPA Subtest3	4132	826.4	22.13	22±1
	4175	835	22.08	22±1
	4233	846.6	21.77	22±1
HSUPA Subtest4	4132	826.4	21.9	22±1
	4175	835	21.88	22±1
	4233	846.6	21.59	22±1
HSUPA Subtest5	4132	826.4	22.18	22±1
	4175	835	**22.27**	22±1
	4233	846.6	21.76	22±1

UMTS-FDD Band II

Band/ Time Slot configuration	Channel	Frequency	Average power (dBm)	Tune up Power tolerant
RMC 12.2kbps	9262	1852.4	22.62	23±1
	9400	1880	**22.75**	23±1
	9538	1907.6	22.61	23±1
HSDPA Subtest1	9262	1852.4	21.92	22±1
	9400	1880	22.08	22±1
	9538	1907.6	22.01	22±1
HSDPA Subtest2	9262	1852.4	22.04	22±1
	9400	1880	**22.25**	22±1
	9538	1907.6	21.92	22±1
HSDPA Subtest3	9262	1852.4	21.9	22±1
	9400	1880	21.96	22±1
	9538	1907.6	21.83	22±1
HSDPA Subtest4	9262	1852.4	22.06	22±1
	9400	1880	22.11	22±1
	9538	1907.6	21.95	22±1
HSUPA Subtest1	9262	1852.4	21.9	22±1
	9400	1880	21.98	22±1
	9538	1907.6	21.94	22±1
HSUPA Subtest2	9262	1852.4	21.84	22±1
	9400	1880	21.84	22±1
	9538	1907.6	21.79	22±1
HSUPA Subtest3	9262	1852.4	21.82	22±1
	9400	1880	22.02	22±1
	9538	1907.6	21.93	22±1
HSUPA Subtest4	9262	1852.4	21.7	22±1
	9400	1880	22.04	22±1
	9538	1907.6	21.85	22±1
HSUPA Subtest5	9262	1852.4	22.03	22±1
	9400	1880	**22.1**	22±1
	9538	1907.6	22.02	22±1

UMTS-FDD Band IV

Band/ Time Slot configuration	Channel	Frequency	Average power (dBm)	Tune up Power tolerant
RMC 12.2kbps	1313	1712.6	23.28	23.3±1
	1413	1732.6	**23.52**	23.3±1
	1512	1752.4	23.22	23.3±1
HSDPA Subtest1	1313	1712.6	22.51	22.5±1
	1413	1732.6	22.77	22.5±1
	1512	1752.4	22.48	22.5±1
HSDPA Subtest2	1313	1712.6	22.72	22.5±1
	1413	1732.6	22.83	22.5±1
	1512	1752.4	22.65	22.5±1
HSDPA Subtest3	1313	1712.6	22.6	22.5±1
	1413	1732.6	22.81	22.5±1
	1512	1752.4	22.53	22.5±1
HSDPA Subtest4	1313	1712.6	22.67	22.5±1
	1413	1732.6	**22.93**	22.5±1
	1512	1752.4	22.58	22.5±1
HSUPA Subtest1	1313	1712.6	22.65	22.5±1
	1413	1732.6	22.9	22.5±1
	1512	1752.4	22.51	22.5±1
HSUPA Subtest2	1313	1712.6	22.38	22.5±1
	1413	1732.6	22.59	22.5±1
	1512	1752.4	22.41	22.5±1
HSUPA Subtest3	1313	1712.6	22.53	22.5±1
	1413	1732.6	22.76	22.5±1
	1512	1752.4	22.43	22.5±1
HSUPA Subtest4	1313	1712.6	22.36	22.5±1
	1413	1732.6	22.57	22.5±1
	1512	1752.4	22.36	22.5±1
HSUPA Subtest5	1313	1712.6	22.74	22.5±1
	1413	1732.6	**22.99**	22.5±1
	1512	1752.4	22.6	22.5±1

ERP & EIRP

GSM Voice

ERP for Cellular Band (Part 22H)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
824.2	20.66	V	6.1	0.53	**26.23**	38.45
824.2	18.88	H	6.1	0.53	24.45	38.45
836.6	20.47	V	6.2	0.53	26.14	38.45
836.6	19.41	H	6.2	0.53	25.08	38.45
848.8	20.4	V	6.2	0.53	26.07	38.45
848.8	18.8	H	6.2	0.53	24.47	38.45

EIRP for PCS Band (Part 24E)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
1850.2	19.59	V	7.88	0.72	26.75	33
1850.2	18.73	H	7.88	0.72	25.89	33
1880	19.58	V	7.88	0.72	26.74	33
1880	18.85	H	7.88	0.72	26.01	33
1909.8	19.64	V	7.86	0.72	**26.78**	33
1909.8	18.76	H	7.86	0.72	25.9	33

GPRS:

ERP for Cellular Band (Part 22H)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
824.2	20.64	V	6.1	0.53	**26.21**	38.45
824.2	18.88	H	6.1	0.53	24.45	38.45
836.6	20.43	V	6.2	0.53	26.1	38.45
836.6	18.69	H	6.2	0.53	24.36	38.45
848.8	20.35	V	6.2	0.53	26.02	38.45
848.8	18.93	H	6.2	0.53	24.6	38.45

EIRP for PCS Band (Part 24E)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
1850.2	19.58	V	7.88	0.72	**26.74**	33
1850.2	18.47	H	7.88	0.72	25.63	33
1880	19.57	V	7.88	0.72	26.73	33
1880	18.8	H	7.88	0.72	25.96	33
1909.8	19.39	V	7.86	0.72	26.53	33
1909.8	17.83	H	7.86	0.72	24.97	33

EGPRS (MCS1):

ERP for Cellular Band (Part 22H)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
824.2	20.56	V	6.1	0.53	**26.13**	38.45
824.2	19.82	H	6.1	0.53	25.39	38.45
836.6	20.39	V	6.2	0.53	26.06	38.45
836.6	19.3	H	6.2	0.53	24.97	38.45
848.8	20.34	V	6.2	0.53	26.01	38.45
848.8	19.43	H	6.2	0.53	25.1	38.45

EIRP for PCS Band (Part 24E)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
1850.2	19.61	V	7.88	0.72	**26.77**	33
1850.2	18.87	H	7.88	0.72	26.03	33
1880	19.59	V	7.88	0.72	26.75	33
1880	18.64	H	7.88	0.72	25.8	33
1909.8	19.37	V	7.86	0.72	26.51	33
1909.8	17.54	H	7.86	0.72	24.68	33

RMC

ERP for UMTS-FDD Band V (Part 22H)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
826.4	10.53	V	6.1	0.53	16.1	38.45
826.4	9.38	H	6.1	0.53	14.95	38.45
835	10.48	V	6.2	0.53	**16.15**	38.45
835	9.22	H	6.2	0.53	14.89	38.45
846.6	10.45	V	6.2	0.53	16.12	38.45
846.6	9.41	H	6.2	0.53	15.08	38.45

EIRP for UMTS-FDD Band II (Part 24E)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
1852.4	12.34	V	7.88	0.72	**19.5**	33
1852.4	10.48	H	7.88	0.72	17.64	33
1880	12.32	V	7.88	0.72	19.48	33
1880	10.81	H	7.88	0.72	17.97	33
1907.6	12.29	V	7.86	0.72	19.43	33
1907.6	10.32	H	7.86	0.72	17.46	33

EIRP for UMTS-FDD Band IV (Part 27H)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
1712.4	12.48	V	7.95	0.69	19.74	30
1712.4	11.62	H	7.95	0.69	18.88	30
1740	12.55	V	7.93	0.69	**19.79**	30
1740	11	H	7.93	0.69	18.24	30
1752.6	12.48	V	7.92	0.69	19.71	30
1752.6	10.83	H	7.92	0.69	18.06	30

HSDPA

ERP for UMTS-FDD Band V (Part 22H)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
826.4	9.99	V	6.1	0.53	15.56	38.45
826.4	8.98	H	6.1	0.53	14.55	38.45
835	9.89	V	6.2	0.53	**15.56**	38.45
835	8.13	H	6.2	0.53	13.8	38.45
846.6	9.82	V	6.2	0.53	15.49	38.45
846.6	8.72	H	6.2	0.53	14.39	38.45

EIRP for UMTS-FDD Band II (Part 24E)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
1852.4	11.78	V	7.88	0.72	**18.94**	33
1852.4	10.68	H	7.88	0.72	17.84	33
1880	11.72	V	7.88	0.72	18.88	33
1880	10.95	H	7.88	0.72	18.11	33
1907.6	11.74	V	7.86	0.72	18.88	33
1907.6	10.54	H	7.86	0.72	17.68	33

EIRP for UMTS-FDD Band IV (Part 27H)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
1712.4	11.87	V	7.95	0.69	**19.13**	30
1712.4	9.87	H	7.95	0.69	17.13	30
1740	11.86	V	7.93	0.69	19.1	30
1740	10.04	H	7.93	0.69	17.28	30
1752.6	11.9	V	7.92	0.69	19.13	30
1752.6	10.65	H	7.92	0.69	17.88	30

HSUPA

ERP for UMTS-FDD Band V (Part 22H)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
826.4	9.85	V	6.1	0.53	15.42	38.45
826.4	7.87	H	6.1	0.53	13.44	38.45
835	9.87	V	6.2	0.53	**15.54**	38.45
835	8.9	H	6.2	0.53	14.57	38.45
846.6	9.8	V	6.2	0.53	15.47	38.45
846.6	8.06	H	6.2	0.53	13.73	38.45

EIRP for UMTS-FDD Band II (Part 24E)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
1852.4	11.68	V	7.88	0.72	18.84	33
1852.4	10.29	H	7.88	0.72	17.45	33
1880	11.72	V	7.88	0.72	**18.88**	33
1880	10.53	H	7.88	0.72	17.69	33
1907.6	11.65	V	7.86	0.72	18.79	33
1907.6	10.86	H	7.86	0.72	18	33

EIRP for UMTS-FDD Band IV (Part 27H)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
1712.4	11.86	V	7.95	0.69	19.12	30
1712.4	10.29	H	7.95	0.69	17.55	30
1740	12.04	V	7.93	0.69	**19.28**	30
1740	11.01	H	7.93	0.69	18.25	30
1752.6	11.88	V	7.92	0.69	19.11	30
1752.6	10.03	H	7.92	0.69	17.26	30

6.3 Peak-Average Ratio

Temperature	24 °C
Relative Humidity	53%
Atmospheric Pressure	1010mbar
Test date :	November 15, 2017
Tested By :	Loren Luo

Requirement(s):

Spec	Item	Requirement	Applicable
§24.232(d) § 27.50(d)	a)	The peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.	☑

Test Setup



Test Procedure

According with KDB 971168 v02r02

5.7.2 Alternate procedure for PAPR

5.1.2 Peak power measurements with a peak power meter

The total peak output power may be measured using a broadband peak RF power meter. The power meter must have a video bandwidth that is greater than or equal to the emission bandwidth and utilize a fast-responding diode detector.

5.2.3 Average power measurement with average power meter

As an alternative to the use of a spectrum/signal analyzer or EMI receiver to perform a measurement of the total in-band average output power, a wideband RF average power meter with a thermocouple detector or equivalent can be used under certain conditions

If the EUT can be configured to transmit continuously (i.e., the burst duty cycle ≥ 98%) and at all times the EUT is transmitting at is maximum output

	power level, then a conventional wide-band RF power meter can be used. If the EUT cannot be configured to transmit continuously (i.e., the burst duty cycle < 98%), then there are two options for the use of an average power meter. First, a gated average power meter can be used to perform the measurement if the gating parameters can be adjusted such that the power is measured only over active transmission bursts at maximum output power levels. A conventional average power meter can also be used if the measured burst duty cycle is constant (i.e., duty cycle variations are less than ± 2 percent) by performing the measurement over the on/off burst cycles and then correcting (increasing) the measured level by a factor equal to 10log(1/duty cycle)
Remark	
Result	☑ Pass ☐ Fail

Test Data ☑ Yes ☐ N/A

Test Plot ☐ Yes (See below) ☑ N/A

GSM : GSM 1900 PK-AV POWER (PART 24E)

Frequency (MHz)	Conducted power(dBm)		Peak-Average Ratio(PAR)
	Peak	Average	
1850.2	30.22	29.25	0.97
1880	30.51	29.24	1.27
1909.8	30.34	29.28	1.06

GPRS 1900 PK-AV POWER (PART 24E)

Frequency (MHz)	Conducted power(dBm)		Peak-Average Ratio(PAR)
	Peak	Average	
1850.2	30.11	29.24	0.87
1880	30.16	29.23	0.93
1909.8	30.25	29.03	1.22

EGPRS (MCS1) 1900 PK-AV POWER (PART 24E)

Frequency (MHz)	Conducted power(dBm)		Peak-Average Ratio(PAR)
	Peak	Average	
1850.2	30.16	29.27	0.89
1880	30.18	29.25	0.93
1909.8	30.26	29.01	1.25

RMC ：UMTS-FDD Band II PK-AV POWER (PART 24E)

Frequency (MHz)	Conducted power(dBm)		Peak-Average Ratio(PAR)
	Peak	Average	
1852.4	25.11	22.62	2.49
1880	24.8	22.75	2.05
1907.6	24.9	22.61	2.29

UMTS-FDD Band IV PK-AV POWER (PART 24E)

Frequency (MHz)	Conducted power(dBm)		Peak-Average Ratio(PAR)
	Peak	Average	
1712.6	25.33	23.28	2.05
1732.6	25.62	23.52	2.1
1752.4	25.16	23.22	1.94

HSUPA ：UMTS-FDD Band II PK-AV POWER (PART 24E)

Frequency (MHz)	Conducted power(dBm)		Peak-Average Ratio(PAR)
	Peak	Average	
1852.4	23.66	21.9	1.76
1880	23.51	21.98	1.53
1907.6	23.42	21.94	1.48

UMTS-FDD Band IV PK-AV POWER (PART 24E)

Frequency (MHz)	Conducted power(dBm)		Peak-Average Ratio(PAR)
	Peak	Average	
1712.6	24.52	22.65	1.87
1732.6	24.32	22.9	1.42
1752.4	24.26	22.51	1.75

HSDPA ：UMTS-FDD Band II PK-AV POWER (PART 24E)

Frequency (MHz)	Conducted power(dBm)		Peak-Average Ratio(PAR)
	Peak	Average	
1852.4	23.26	21.92	1.34
1880	23.27	22.08	1.19
1907.6	23.39	22.01	1.38

UMTS-FDD Band IV PK-AV POWER (PART 24E)

Frequency (MHz)	Conducted power(dBm)		Peak-Average Ratio(PAR)
	Peak	Average	
1712.6	24.32	22.51	1.81
1732.6	24.19	22.77	1.42
1752.4	24.45	22.48	1.97

6.4 Occupied Bandwidth

Temperature	24 °C
Relative Humidity	53%
Atmospheric Pressure	1010mbar
Test date :	November 15, 2017
Tested By :	Loren Luo

Requirement(s):

Spec	Item	Requirement	Applicable
§2.1049, §22.917, §22.905 §24.238 §27.53(a)	a)	99% Occupied Bandwidth(kHz)	☑
	b)	26 dB Bandwidth(kHz)	☑
Test Setup			
Test Procedure	- The EUT was connected to Spectrum Analyzer and Base Station via power divider. - The 99% and 26 dB occupied bandwidth (BW) of the middle channel for the highest RF powers.		
Remark			
Result	☑ Pass ☐ Fail		

Test Data ☑ Yes ☐ N/A

Test Plot ☑ Yes (See below) ☐ N/A

GSM Voice:

Cellular Band (Part 22H) result

Channel	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Bandwidth (kHz)
128	824.2	244.5860	320.355
190	836.6	246.3270	319.186
251	848.8	245.0778	319.882

PCS Band (Part 24E) result

Channel	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Bandwidth (kHz)
512	1850.2	246.3312	320.456
661	1880.0	241.6931	319.777
810	1909.8	245.9215	320.921

GPRS:

Cellular Band (Part 22H) result

Channel	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Bandwidth (kHz)
128	824.2	246.6110	320.005
190	836.6	242.9623	321.044
251	848.8	244.3027	319.661

PCS Band (Part 24E) result

Channel	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Bandwidth (kHz)
512	1850.2	244.1156	321.099
661	1880.0	245.8602	319.65
810	1909.8	245.3539	320.425

EGPRS (MCS1):

Cellular Band (Part 22H) result

Channel	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Bandwidth (kHz)
128	824.2	249.0023	320.086
190	836.6	245.5722	321.005
251	848.8	248.1849	319.690

PCS Band (Part 24E) result

Channel	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Bandwidth (kHz)
512	1850.2	245.4936	321.184
661	1880.0	247.2806	320.533
810	1909.8	247.5573	320.928

RMC:

UMTS-FDD Band V (Part 22H)

Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
4132	826.4	4.1515	4.725
4175	835.0	4.1561	4.694
4233	846.6	4.1602	4.715

UMTS-FDD Band II (Part 24E)

Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
9262	1852.4	4.1635	4.731
9400	1880.0	4.1627	4.728
9538	1907.6	4.171	4.76

UMTS-FDD Band IV (Part 27)

Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
1313	1713	4.1613	4.718
1413	1733	4.1615	4.71
1512	1752	4.1575	4.727

HSDPA:

UMTS-FDD Band V (Part 22H)

Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
4132	826.6	4.1543	4.712
4175	835.0	4.1525	4.7
4233	846.6	4.1602	4.709

UMTS-FDD Band II (Part 24E)

Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
9262	1852.4	4.1612	4.724
9400	1880.0	4.162	4.743
9538	1907.6	4.1629	4.746

UMTS-FDD Band IV (Part 27)

Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
1313	1713	4.1647	4.728
1413	1733	4.1659	4.727
1512	1752	4.1714	4.723

HSUPA:

UMTS-FDD Band V (Part 22H)

Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
4132	826.4	4.1676	4.721
4175	835.0	4.1417	4.705
4233	846.6	4.1518	4.711

UMTS-FDD Band II (Part 24E)

Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
9262	1852.4	4.1589	4.743
9400	1880.0	4.1723	4.747
9538	1907.6	4.1643	4.756

UMTS-FDD Band IV (Part 27)

Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
1313	1713	4.1631	4.716
1413	1733	4.1675	4.726
1512	1752	4.1728	4.725

Test Plots

GMS Voice:



GSM 850 BW - Low CH 824.2MHz



GSM 850 BW - Mid CH 836.6MHz



GSM 850 BW - High CH 848.8MHz



PCS 1900 BW - Low CH 1850.2MHz



PCS 1900 BW - Mid CH 1880MHz



PCS 1900 BW - High CH 1910MHz

GPRS:



GSM 850 BW - Low CH 824.2MHz



GSM 850 BW - Mid CH 836.6MHz



GSM 850 BW - High CH 848.8MHz



PCS 1900 BW - Low CH 1850.2MHz



PCS 1900 BW - Mid CH 1880MHz



PCS 1900 BW - High CH 1910MHz

EGPRS:



GSM 850 BW - Low CH 824.2MHz



GSM 850 BW - Mid CH 836.6MHz



GSM 850 BW - High CH 848.8MHz



PCS 1900 BW - Low CH 1850.2MHz



PCS 1900 BW - Mid CH 1880MHz



PCS 1900 BW - High CH 1910MHz

RMC:



Band V BW - Low CH 826.6 MHz



Band V BW - Mid CH 835.0 MHz



Band V BW - High CH 846.6 MHz



Band II BW - Low CH 1853MHz



Band II BW - Mid CH 1880MHz



Band II BW - High CH 1907MHz



Band IV BW - Low CH 1713MHz



Band IVBW - Mid CH 1733MHz



Band IV BW - High CH 1752MHz

HSDPA:



Band V BW - Low CH 826.6 MHz



Band V BW - Mid CH 835.0 MHz



Band V BW - High CH 846.4 MHz



Band II BW - Low CH 1852.4MHz



Band II BW - Mid CH 1880MHz



Band II BW - High CH 1907MHz



Band IV BW - Low CH 1713MHz



Band IVBW - Mid CH 1733MHz



Band IV BW - High CH 1752MHz

HSUPA:



Band V BW - Low CH 826.6 MHz



Band V BW - Mid CH 835.0 MHz



Band V BW - High CH 846.4 MHz



Band II BW - Low CH 1853MHz



Band II BW - Mid CH 1880MHz



Band II BW - High CH 1907MHz



Band IV BW - Low CH 1713MHz



Band IVBW - Mid CH 1733MHz



Band IV BW - High CH 1752MHz

6.5 Spurious Emissions at Antenna Terminals

Temperature	25 °C
Relative Humidity	58%
Atmospheric Pressure	1016mbar
Test date :	November 16, 2017
Tested By :	Loren Luo

Requirement(s):

Spec	Item	Requirement	Applicable
§2.1051, §22.917(a)& §24.238(a) § 27.53(h)	a)	The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least 43 + 10 log (P) dB	☑
Test Setup			
Test Procedure	- The EUT was connected to Spectrum Analyzer and Base Station via power divider. - The Band Edges of low and high channels for the highest RF powers were measured. - Setting RBW as roughly BW/100.		
Remark			
Result	☑ Pass ☐ Fail		

Test Data ☑ Yes ☐ N/A

Test Plot ☑ Yes (See below) ☐ N/A

Test Plots

GSM Voice:

Cellular Band (Part 22H) result



GSM 850 - Low Channel-1



GSM 850 - Low Channel-2



GSM 850 Middle Channel-1



GSM 850 Middle Channel-2



GSM 850 - High Channel-1



GSM 850 - High Channel-2

PCS Band (Part24E) result



PCS1900 - Low Channel-1



PCS 1900 - Low Channel-2



PCS1900 - Middle Channel-1



PCS 1900 - Middle Channel-2



PCS1900 - High Channel-1



PCS 1900 - High Channel-2

GPRS:

Cellular Band (Part 22H) result



GSM 850 - Low Channel-1



GSM 850 - Low Channel-2



GSM 850 Middle Channel-1



GSM 850 Middle Channel-2



GSM 850 - High Channel-1



GSM 850 - High Channel-2

PCS Band (Part24E) result



PCS1900 - Low Channel-1



PCS 1900 - Low Channel-2



PCS1900 - Middle Channel-1



PCS 1900 - Middle Channel-2



PCS1900 - High Channel-1



PCS 1900 - High Channel-2

EGPRS (MCS1):

Cellular Band (Part 22H) result



GSM 850 - Low Channel-1



GSM 850 - Low Channel-2



GSM 850 Middle Channel-1



GSM 850 Middle Channel-2



GSM 850 - High Channel-1



GSM 850 - High Channel-2

PCS Band (Part24E) result



PCS1900 - Low Channel-1



PCS 1900 - Low Channel-2



PCS1900 - Middle Channel-1



PCS 1900 - Middle Channel-2



PCS1900 - High Channel-1



PCS 1900 - High Channel-2

RMC

UMTS-FDD Band V (Part 22H)



Band V - Low Channel-1



Band V - Low Channel-2



Band V - Middle Channel-1



Band V - Middle Channel-2



Band V - High Channel-1



Band V - High Channel-2

UMTS-FDD Band II (Part 24E)



Band II - Low Channel-1



Band II - Low Channel-2



Band II - Middle Channel-1



Band II - Middle Channel-2



Band II - High Channel-1



Band II - High Channel-2

UMTS-FDD Band IV (Part 27)



Band IV - Low Channel-1



Band IV - Low Channel-2



Band IV - Middle Channel-1



Band IV - Middle Channel-2



Band IV - High Channel-1



Band IV - High Channel-2

HSUPA:

UMTS-FDD Band V (Part 22H)



Band V - Low Channel-1



Band V - Low Channel-2



Band V - Middle Channel-1



Band V - Middle Channel-2



Band V - High Channel-1



Band V - High Channel-2

UMTS-FDD Band II (Part 24E)



Band II - Low Channel-1



Band II - Low Channel-2



Band II - Middle Channel-1



Band II - Middle Channel-2



Band II - High Channel-1



Band II - High Channel-2

UMTS-FDD Band IV (Part 27)



Band IV - Low Channel-1



Band IV - Low Channel-2



Band IV - Middle Channel-1



Band IV - Middle Channel-2



Band IV - High Channel-1



Band IV - High Channel-2

HSDPA:

UMTS-FDD Band V (Part 22H)



Band V - Low Channel-1



Band V - Low Channel-2



Band V - Middle Channel-1



Band V - Middle Channel-2



Band V - High Channel-1



Band V - High Channel-2

UMTS-FDD Band II (Part 24E)



Band II - Low Channel-1



Band II - Low Channel-2



Band II - Middle Channel-1



Band II - Middle Channel-2



Band II - High Channel-1



Band II - High Channel-2

UMTS-FDD Band IV (Part 27)



Band IV - Low Channel-1



Band IV - Low Channel-2



Band IV - Middle Channel-1



Band IV - Middle Channel-2



Band IV - High Channel-1



Band IV - High Channel-2

6.6 Spurious Radiated Emissions

Temperature	25 °C
Relative Humidity	56%
Atmospheric Pressure	1018mbar
Test date :	November 09, 2017
Tested By :	Loren Luo

Requirement(s):

Spec	Item	Requirement	Applicable
§2.1053, §22.917 & §24.238 § 27.53(h)	a)	The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least 43 + 10 log (P) dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.	☑
Test setup			
Test Procedure	1. The transmitter was placed on a wooden turntable, and it was transmitting into a non-radiating load which was also placed on the turntable. 2. The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis. 3. Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution. Sample Calculation: EUT Field Strength = Raw Amplitude (dBμV/m) – Amplifier Gain (dB) + Antenna Factor (dB) + Cable Loss (dB) + Filter Attenuation (dB, if used)		

Remark	
Result	☑ Pass ☐ Fail

Test Data ☑ Yes ☐ N/A

Test Plot ☐ Yes (See below) ☑ N/A

Cellular Band (Part 22H) result

Low channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
1648.4	-43.32	V	7.95	0.67	-36.04	-13	-23.04
1648.4	-45.06	H	7.95	0.67	-37.78	-13	-24.78
921.6	-52.17	V	6.16	0.47	-46.48	-13	-33.48
935.7	-53.54	H	6.21	0.42	-47.75	-13	-34.75

Middle channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
1673.2	-42.99	V	7.95	0.67	-35.71	-13	-22.71
1673.2	-43.22	H	7.95	0.67	-35.94	-13	-22.94
209.5	-52.93	V	3.65	0.2	-49.48	-13	-36.48
154.7	-53.44	H	3.73	0.2	-49.91	-13	-36.91

High channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
1697.6	-42.64	V	7.95	0.68	-35.37	-13	-22.37
1697.6	-42.94	H	7.95	0.68	-35.67	-13	-22.67
803.6	-51.84	V	6.15	0.42	-46.11	-13	-33.11
710.5	-52.76	H	6.1	0.39	-47.05	-13	-34.05

Note:

*1, The testing has been conformed to 10*848.8MHz=8,488MHz*
2, All other emissions more than 30 dB below the limit
3,GSM voice , GPRS and EGPRS mode were investigated. The results above show only the worse cases
4, X-Axis, Y-Axis and Z-Axis were investigated. The results above show only the worst case.
5, The radiated spurious test above 18GHz is subcontracted to SIEMIC (Nanjing-China) Laboratories. and found 30dB below the limit at least.

PCS Band (Part24E) result

Low channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3700.4	-49.41	V	10.25	1	-40.16	-13	-27.16
3700.4	-49.55	H	10.25	1	-40.3	-13	-27.3
433.4	-52.88	V	5.97	0.3	-47.21	-13	-34.21
768.9	-53.25	H	6.12	0.41	-47.54	-13	-34.54

Middle channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3760	-48.34	V	10.25	1.01	-39.1	-13	-26.1
3760	-48.88	H	10.25	1.01	-39.64	-13	-26.64
331	-53.07	V	3.66	0.21	-49.62	-13	-36.62
604.2	-54.5	H	6.13	0.38	-48.75	-13	-35.75

High channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3819.6	-48.54	V	10.36	1.02	-39.2	-13	-26.2
3819.6	-48.57	H	10.36	1.02	-39.23	-13	-26.23
782.8	-53.02	V	6.06	0.42	-47.38	-13	-34.38
826.7	-52.03	H	6.11	0.45	-46.37	-13	-33.37

Note:

*1, The testing has been conformed to 10*1909.8MHz=19,098MHz*
2, All other emissions more than 30 dB below the limit
3,GSM voice , GPRS and EGPRS mode were investigated. The results above show only the worse cases
4, X-Axis, Y-Axis and Z-Axis were investigated. The results above show only the worst case.
5, The radiated spurious test above 18GHz is subcontracted to SIEMIC (Nanjing-China) Laboratories. and found 30dB below the limit at least.

UMTS-FDD Band V (Part 22H)

Low channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
1652.8	-46.91	V	7.95	0.67	-39.63	-13	-26.63
1652.8	-45.22	H	7.95	0.67	-37.94	-13	-24.94
252.6	-53.43	V	3.69	0.18	-49.92	-13	-36.92
629.2	-53.35	H	6.11	0.4	-47.64	-13	-34.64

Middle channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
1670	-45.57	V	7.95	0.67	-38.29	-13	-25.29
1670	-45.97	H	7.95	0.67	-38.69	-13	-25.69
201.1	-51.81	V	3.66	0.17	-48.32	-13	-35.32
475.4	-51.89	H	6.8	0.37	-45.46	-13	-32.46

High channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
1693.2	-47.11	V	7.95	0.68	-39.84	-13	-26.84
1693.2	-44.86	H	7.95	0.68	-37.59	-13	-24.59
630.4	-51.61	V	6.14	0.37	-45.84	-13	-32.84
215.2	-53.19	H	3.66	0.18	-49.71	-13	-36.71

Note:

*1, The testing has been conformed to 10*846.6MHz=8,466MHz*
2, All other emissions more than 30 dB below the limit
3,RMC , HSUPA and HSDPA mode were investigated. The results above show only the worse cases
4, X-Axis, Y-Axis and Z-Axis were investigated. The results above show only the worst case.
5, The radiated spurious test above 18GHz is subcontracted to SIEMIC (Nanjing-China) Laboratories. and found 30dB below the limit at least.

UMTS-FDD Band II (Part 24E)

Low channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3704.8	-48.41	V	10.25	1	-39.16	-13	-26.16
3704.8	-50.31	H	10.25	1	-41.06	-13	-28.06
119.1	-54.28	V	-0.08	0.13	-54.49	-13	-41.49
613.1	-52.85	H	6.15	0.39	-47.09	-13	-34.09

Middle channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3760	-49.58	V	10.25	1.01	-40.34	-13	-27.34
3760	-50.41	H	10.25	1.01	-41.17	-13	-28.17
678	-52.64	V	6.05	0.42	-47.01	-13	-34.01
887.1	-53.73	H	6.11	0.45	-48.07	-13	-35.07

High channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3815.2	-48.47	V	10.36	1.02	-39.13	-13	-26.13
3815.2	-49.2	H	10.36	1.02	-39.86	-13	-26.86
923	-52.98	V	6.23	0.41	-47.16	-13	-34.16
836.8	-53.47	H	6.07	0.42	-47.82	-13	-34.82

Note:

*1, The testing has been conformed to 10*1907.6MHz=19,076MHz*
2, All other emissions more than 30 dB below the limit
3,RMC , HSUPA and HSDPA mode were investigated. The results above show only the worse cases
4, X-Axis, Y-Axis and Z-Axis were investigated. The results above show only the worst case
5, The radiated spurious test above 18GHz is subcontracted to SIEMIC (Nanjing-China) Laboratories. and found 30dB below the limit at least.

UMTS-FDD Band IV (Part 27)

Low channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3424.8	-42.94	V	10.07	0.96	-33.83	-13	-20.83
3424.8	-44.48	H	10.07	0.96	-35.37	-13	-22.37
619.2	-52.49	V	6.08	0.36	-46.77	-13	-33.77
765.6	-53.77	H	6.11	0.36	-48.02	-13	-35.02

Middle channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3480	-44.07	V	10.09	0.96	-34.94	-13	-21.94
3480	-44.33	H	10.09	0.96	-35.2	-13	-22.2
260.3	-53.49	V	5.86	0.25	-47.88	-13	-34.88
670.7	-51.83	H	6.09	0.36	-46.1	-13	-33.1

High channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3505.2	-44.21	V	10.09	0.97	-35.09	-13	-22.09
3505.2	-43.76	H	10.09	0.97	-34.64	-13	-21.64
910.7	-52.78	V	6.18	0.44	-47.04	-13	-34.04
360.9	-51.96	H	5.94	0.31	-46.33	-13	-33.33

Note:

*1, The testing has been conformed to 10*1752.6MHz=17,526MHz*
2, All other emissions more than 30 dB below the limit
3,RMC , HSUPA and HSDPA mode were investigated. The results above show only the worse cases.
4, X-Axis, Y-Axis and Z-Axis were investigated. The results above show only the worst case.
5, The radiated spurious test above 18GHz is subcontracted to SIEMIC (Nanjing-China) Laboratories. and found 30dB below the limit at least.

6.7 Band Edge

Temperature	25 °C
Relative Humidity	56%
Atmospheric Pressure	1018mbar
Test date :	November 09, 2017
Tested By :	Loren Luo

Requirement(s):

Spec	Item	Requirement	Applicable
§22.917(a) §24.238(a) § 27.53(h)	a)	The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least 43 + 10 log (P) dB.	☑
Test setup			
Procedure	- The EUT was connected to Spectrum Analyzer and Base Station via power divider. - The Band Edges of low and high channels for the highest RF powers were measured. Setting RBW as roughly BW/100.		
Remark			
Result	☑ Pass ☐ Fail		

Test Data ☑ Yes ☐ N/A

Test Plot ☑ Yes (See below) ☐ N/A

GSM Voice:

Cellular Band (Part 22H) result

Frequency (MHz)	Emission (dBm)	Limit (dBm)
823.995	-15.73	-13
849.0025	-15.99	-13

PCS Band (Part24E) result

Frequency (MHz)	Emission (dBm)	Limit (dBm)
1849.9975	-16.32	-13
1910.0225	-17.23	-13

GPRS:

Cellular Band (Part 22H) result

Frequency (MHz)	Emission (dBm)	Limit (dBm)
823.9975	-14.22	-13
849.0225	-15.98	-13

PCS Band (Part24E) result

Frequency (MHz)	Emission (dBm)	Limit (dBm)
1849.9975	-16.8	-13
1910.005	-17.39	-13

EGPRS (MCS1):

Cellular Band (Part 22H) result

Frequency (MHz)	Emission (dBm)	Limit (dBm)
823.9975	-16.26	-13
849.015	-17.39	-13

PCS Band (Part24E) result

Frequency (MHz)	Emission (dBm)	Limit (dBm)
1849.9975	-15.97	-13
1910.02	-17.42	-13

RCM:

UMTS-FDD Band V (Part 22H)

Frequency (MHz)	Emission (dBm)	Limit (dBm)
823.125	-23.25	-13
850.125	-27.07	-13

UMTS-FDD Band II (Part 24E)

Frequency (MHz)	Emission (dBm)	Limit (dBm)
1849.175	-21.81	-13
1910.05	-19.74	-13

UMTS-FDD Band IV (Part 27)

Frequency (MHz)	Emission (dBm)	Limit (dBm)
1708.775	-23.99	-13
1755.275	-22.95	-13

HSUPA:

UMTS-FDD Band V (Part 22H)

Frequency (MHz)	Emission (dBm)	Limit (dBm)
823.025	-23.56	-13
850.05	-26.78	-13

UMTS-FDD Band II (Part 24E)

Frequency (MHz)	Emission (dBm)	Limit (dBm)
1849.2	-20.57	-13
1910.05	-19.35	-27.66

UMTS-FDD Band IV (Part 27)

Frequency (MHz)	Emission (dBm)	Limit (dBm)
1709.875	-24.13	-13
1756	-23.18	-13

HSDPA:

UMTS-FDD Band V (Part 22H)

Frequency (MHz)	Emission (dBm)	Limit (dBm)
823.1	-24.14	-13
849.85	-26.82	-13

UMTS-FDD Band II (Part 24E)

Frequency (MHz)	Emission (dBm)	Limit (dBm)
1849.125	-20.31	-13
1910.05	-20.39	-13

UMTS-FDD Band IV (Part 27)

Frequency (MHz)	Emission (dBm)	Limit (dBm)
1709.075	-24.70	-13
1755.1	-22.48	-13

GSM Voice:

Test Plots



Cellular Band - Low Channel

Note: Offset=Cable loss (4.0) + 10log (3.20/3)=4.0+0.3=4.3dB



Cellular Band - High Channel

Note: Offset=Cable loss (4.0) + 10log (3.19/3)=4.0+0.3=4.3dB



PCS Band - Low Channel

Note: Offset=Cable loss (4.0) + 10log (3.20/3)=4.5+0.3=4.8dB



PCS Band - High Channel

Note: Offset=Cable loss (4.0) + 10log (3.20/3)=4.5+0.3=4.8dB

GPRS:

Test Plots



Cellular Band - Low Channel

Note: Offset=Cable loss (4.0) + 10log (3.20/3)=4.0+0.3=4.3dB



Cellular Band - High Channel

Note: Offset=Cable loss (4.0) + 10log (3.19/3)=4.0+0.3=4.3dB



PCS Band - Low Channel

Note: Offset=Cable loss (4.5) + 10log (3.21/3)=4.5+0.3=4.8dB



PCS Band - High Channel

Note: Offset=Cable loss (4.5) + 10log (3.20/3)=4.5+0.3=4.8dB

EGPRS (MCS1):

Test Plots



Cellular Band - Low Channel

Note: Offset=Cable loss (4.0) + 10log (3.20/3)=4.0+0.3=4.3dB



Cellular Band - High Channel

Note: Offset=Cable loss (4.0) + 10log (3.19/3)=4.0+0.3=4.3dB



PCS Band - Low Channel

Note: Offset=Cable loss (4.5) + 10log (3.21/3)=4.5+0.3=4.8dB



PCS Band - High Channel

Note: Offset=Cable loss (4.5) + 10log (3.20/3)=4.5+0.3=4.8dB

RMC:



UMTS-FDD Band V - Low Channel

Note: Offset=Cable loss (4.0) + 10log (47.25/30)=4.0+2.0=6.0 dB



UMTS-FDD Band V - High Channel

Note: Offset=Cable loss (4.0) + 10log (47.15/30)=4.0+2.0=6.0dB



UMTS-FDD Band II - Low Channel

Note: Offset=Cable loss (4.5) + 10log (47.31/30)=4.5+2.0=6.5 dB



UMTS-FDD Band II - High Channel

Note: Offset=Cable loss (4.5) + 10log (47.60/30)=4.5+2.0=6.5 dB



UMTS-FDD Band IV - Low Channel

Note: Offset=Cable loss (4.5) + 10log (47.18/30)=4.5+2.0=6.5dB



UMTS-FDD Band IV - High Channel

Note: Offset=Cable loss (4.0) + 10log (47.27/30)=4.5+2.0=6.5dB

HSUPA:



UMTS-FDD Band V - Low Channel

Note: Offset=Cable loss (4.0) + 10log (47.21/30)=4.0+2.0=6.0 dB



UMTS-FDD Band V - High Channel

Note: Offset=Cable loss (4.0) + 10log (47.11/30)=4.0+2.0=6.0 dB



UMTS-FDD Band II - Low Channel

Note: Offset=Cable loss (4.5) + 10log (47.43/30)=4.5+2.0=6.5 dB



UMTS-FDD Band II - High Channel

Note: Offset=Cable loss (4.5) + 10log (47.56/30)=4.5+2.0=6.5 dB



UMTS-FDD Band IV - Low Channel

Note: Offset=Cable loss (4.5) + 10log (47.16/30)=4.5+2.0=6.5 dB



UMTS-FDD Band IV - High Channel

Note: Offset=Cable loss (4.5) + 10log (47.25/30)=4.5+2.0=6.5 dB

HSDPA:



UMTS-FDD Band V - Low Channel

Note: Offset=Cable loss (4.0) + 10log (47.12/30)=4.0+2.0=5.9 dB



UMTS-FDD Band V - High Channel

Note: Offset=Cable loss (4.0) + 10log (47.09/30)=4.0+2.0=6.0 dB



UMTS-FDD Band II - Low Channel

Note: Offset=Cable loss (4.5) + 10log (47.24/30)=4.5+2.0=6.5 dB



UMTS-FDD Band II - High Channel

Note: Offset=Cable loss (4.5) + 10log (47.46/30)=4.5+2.0=6.5 dB



UMTS-FDD Band IV - Low Channel

Note: Offset=Cable loss (4.5) + 10log (47.28/30)=4.5+2.0=6.5 dB



UMTS-FDD Band IV - High Channel

Note: Offset=Cable loss (4.5) + 10log (47.23/30)=4.5+2.0=6.5 dB

6.8 Frequency Stability

Temperature	24 °C
Relative Humidity	53%
Atmospheric Pressure	1010mbar
Test date :	November 15, 2017
Tested By :	Loren Luo

Requirement(s):

Spec	Item	Requirement	Applicable
§2.1055, §22.355 & §24.235 § 27.5(h); § 27.54	a)	According to §22.355, the carrier frequency of each transmitter in the Public Mobile Services must be maintained within the tolerances given in Table below: Frequency Tolerance for Transmitters in the Public Mobile Services	☑

Frequency Range (MHz)	Base, fixed (ppm)	Mobile ≤ 3 watts (ppm)	Mobile ≤ 3 watts (ppm)
25 to 50	20.0	20.0	50.0
50 to 450	5.0	5.0	50.0
45□to 512	2.5	5.0	□0
821 to 896	1.5	2.5	2.5
928 to □29.	5.0	N/A	N/A
929 to 960.	1.5	N/A	N/A
2110 to 2220	10.0	N/A	N/A

According to §24.235, the frequency stability shall be sufficient to ensure that the fundamental emissions stay within the authorized frequency block.

Test setup



Procedure	A communication link was established between EUT and base station. The frequency error was monitored and measured by base station under variation of ambient temperature and variation of primary supply voltage. Limit: The frequency stability of the transmitter shall be maintained within ±0.00025% (±2.5ppm) of the center frequency.
Remark	
Result	☑ Pass ☐ Fail

Test Data ☑ Yes ☐ N/A

Test Plot ☐ Yes (See below) ☑ N/A

GSM Voice:

Cellular Band (Part 22H) result

Middle Channel, f_o = 836.6 MHz				
Temperature (℃)	Power Supplied (V_{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-10	3.7	19	0.0227	2.5
0		16	0.0191	2.5
10		17	0.0203	2.5
20		16	0.0191	2.5
30		16	0.0191	2.5
40		15	0.0179	2.5
50		19	0.0227	2.5
55		20	0.0239	2.5
25	4.2	21	0.0251	2.5
	3.5	19	0.0227	2.5

PCS Band (Part 24E) result

Middle Channel, f_o = 1880 MHz				
Temperature (℃)	Power Supplied (V_{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-10	3.7	12	0.0064	2.5
0		12	0.0064	2.5
10		15	0.0080	2.5
20		11	0.0059	2.5
30		13	0.0069	2.5
40		16	0.0085	2.5
50		18	0.0096	2.5
55		16	0.0085	2.5
25	4.2	16	0.0085	2.5
	3.5	20	0.0106	2.5

RMC:

UMTS-FDD Band V (Part 22H)

Middle Channel, f_o = 835 MHz				
Temperature (°C)	Power Supplied (V_{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-10	3.7	17	0.0204	2.5
0		14	0.0168	2.5
10		16	0.0192	2.5
20		16	0.0192	2.5
30		15	0.0180	2.5
40		10	0.0120	2.5
50		21	0.0251	2.5
55		16	0.0192	2.5
25	4.2	18	0.0216	2.5
	3.5	13	0.0156	2.5

UMTS-FDD Band II (Part 24E)

Middle Channel, f_o = 1880 MHz				
Temperature (°C)	Power Supplied (V_{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-10	3.7	14	0.0074	2.5
0		13	0.0069	2.5
10		15	0.0080	2.5
20		13	0.0069	2.5
30		15	0.0080	2.5
40		9	0.0048	2.5
50		19	0.0101	2.5
55		16	0.0085	2.5
25	4.2	14	0.0074	2.5
	3.5	12	0.0064	2.5

UMTS-FDD Band IV (Part 27)

Middle Channel, f_o = 1733 MHz				
Temperature (°C)	Power Supplied (V_{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-10	3.7	13	0.0156	2.5
0		13	0.0156	2.5
10		13	0.0156	2.5
20		12	0.0144	2.5
30		16	0.0192	2.5
40		16	0.0192	2.5
50		14	0.0168	2.5
55		15	0.0180	2.5
25	4.2	17	0.0204	2.5
	3.5	22	0.0263	2.5

Annex A. TEST INSTRUMENT

Instrument	Model	Serial #	Cal Date	Cal Due	In use
RF Conducted Test					
Agilent ESA-E SERIES SPECTRUM ANALYZER	E4407B	MY45108319	09/14/2017	09/13/2018	☑
Power Splitter	1#	1#	08/30/2017	08/29/2018	☑
Universal Radio Communication Tester	CMU200	121393	09/23/2017	09/22/2018	☑
Temperature/Humidity Chamber	UHL-270	001	10/07/2017	10/06/2018	☑
DC Power Supply	E3640A	MY40004013	09/15/2017	09/14/2018	☑
RF Power Sensor	Dare RPR3006C/P/W	AY554013	09/15/2017	09/14/2018	☑
Radiated Emissions					
EMI test receiver	ESL6	100262	09/15/2017	09/14/2018	☑
OPT 010 AMPLIFIER (0.1-1300MHz)	8447E	2727A02430	08/30/2017	08/29/2018	☑
Horn Antenna	BBHA9170	3145226D1	09/27/2017	09/26/2018	☑
Microwave Preamplifier (1 ~ 26.5GHz)	8449B	3008A02402	03/23/2017	03/22/2018	☑
Bilog Antenna (30MHz~6GHz)	JB6	A110712	09/19/2017	09/18/2018	☑
Bilog Antenna (30MHz~2GHz)	JB1	A112017	09/19/2017	09/18/2018	☑
Double Ridge Horn Antenna (1 ~18GHz)	AH-118	71259	09/22/2017	09/21/2018	☑
Double Ridge Horn Antenna (1 ~18GHz)	AH-118	71283	09/22/2017	09/21/2018	☑
SYNTHESIZED SIGNAL GENERATOR	8665B	3744A01293	09/15/2017	09/14/2018	☑
Power Amplifier	SMC150D	R1553-0313	03/08/2017	03/07/2018	☑
Power Amplifier	S41-25D	R1553-0314	05/26/2017	05/25/2018	☑

Tunable Notch Filter	3NF-800/1000-S	AA4	08/30/2017	08/29/2018	☑
Tunable Notch Filter	3NF-1000/2000-S	AM 4	08/30/2017	08/29/2018	☑

Annex B. EUT And Test Setup Photographs

Annex B.i. Photograph: EUT External Photo

Whole Package View

Adapter View

EUT - Front View

EUT - Rear View

EUT - Top View



EUT - Bottom View



EUT - Left View



EUT - Right View



Annex B.ii. Photograph: EUT Internal Photo

Cover Off - Top View 1

Cover Off - Top View 2



Battery - Front View



Battery - Rear View



Mainboard with Shielding – Front View



Mainboard with Shielding – Rear View



Mainboard without Shielding – Rear View



Mainboard without Shielding – Rear View



Mainboard without Shielding – Front View



Mainboard without Shielding – Rear View



Small Mainboard – Front View



Small Mainboard – Rear View



LCD – Front View

LCD – Rear View

GSM/PCS/UMTS-FDD - Antenna View



WIFI/BT/BLE/GPS - Antenna View

Annex B.iii. Photograph: Test Setup Photo

	
Radiated Spurious Emissions Test Setup Below 1GHz	Radiated Spurious Emissions Test Setup Above 1GHz

Annex C. TEST SETUP AND SUPPORTING EQUIPMENT

Annex C.ii. TEST SET UP BLOCK

Block Configuration Diagram for Radiated Emissions



Annex C. il. SUPPORTING EQUIPMENT DESCRIPTION

The following is a description of supporting equipment and details of cables used with the EUT.

Supporting Equipment:

Manufacturer	Equipment Description	Model	Serial No
BLU Products, Inc.	Adapter	US-WT-1500	N/A
SAMSUNG	headset	HS330	N/A

Supporting Cable:

Cable type	Shield Type	Ferrite Core	Length	Serial No
USB Cable	Un-shielding	No	0.8m	N/A

Annex C.ii. EUT OPERATING CONKITIONS

N/A

Annex D. User Manual / Block Diagram / Schematics / Partlist

Please see the attachment

Annex E. DECLARATION OF SIMILARITY

N/A