

RF TEST REPORT

Test Equipment : Remote Control Unit
Model Name : FGSC33-TT-04
FCC ID : YI5SC33TT04
IC : 9065A-SC33TT04
Date of receipt : 2021-12-07
Test duration : 2021-12-14 ~ 2021-12-15
Date of issue : 2022-01-27

Applicant : Celadon, Inc.

58 Paul Drive, Suite D, San Rafael, CA 94903 United States

Test Laboratory : Lab-T, Inc.

2182-42, Baegok-daero, Mohyeon-eup, Cheoin-gu, Yongin-si
Gyeonggi-do 17036, Korea (Republic of)

Test specification : FCC Part 15 Subpart C 15.231
RSS-210 Issue 10 A1(2020-04)
RSS-GEN Issue 5 A2(2021-02)

RF Output Power : 89.10 dBμV/m

Test result : Pass

The above equipment was tested by Lab-T Testing Laboratory for compliance
with the requirements of FCC / ISED Rules and Regulations.

The test results presented in this test report are limited only to the sample supplied by applicant
and the use of this test report is inhibited other than its purpose.


This test report shall not be reproduced except in full, without the written approval of Lab-T, Inc
This test report is not related to KOLAS.

Tested by:



Engineer
SungSin Kim

Reviewed by:



Technical Manager
SangHoon Yu

CONTENTS

1. Revision history.....	3
2. Information	4
2.1 Applicant Information	4
2.2 Test Laboratory information.....	4
2.3 Test Site.....	4
3. Information About Test Equipment	5
3.1 Equipment Information	5
3.2 Antenna Information	5
3.3 Test Frequency.....	5
3.4 Operating conditions for the EUT.....	5
4. Test Report.....	6
4.1 Summary	6
4.2 Measurement Uncertainty.....	6
4.4 Transmitter Requirements	7
4.4.1 Antenna Requirement.....	7
4.4.2 Transmitter Deactivation.....	8
4.4.3 Field Strength of Emissions.....	9
4.4.4 Emission Bandwidth.....	11
4.4.5 Spurious Emission and Restricted bands.....	13
4.4.6 Conducted Emission	17
4.4.7 Duty cycle.....	18
APPENDIX I.....	19

1. Revision history

Test Report No.	Date	Description
TRRFCC22-0003	2022-01-27	Initial issue

2. Information

2.1 Applicant Information

Applicant name	Celadon, Inc.
Address	58 Paul Drive, Suite D, San Rafael, CA 94903 United States
Telephone No.	415-472-1177 x201
Person in charge	Robert Retzlaff / retzlaff@celadon.com
Manufacturer	Celadon, Inc.
Address	58 Paul Drive, Suite D, San Rafael, CA 94903 United States

2.2 Test Laboratory information

Corporate name	Lab-T, Inc.
Representative	Duke (Jongyoung) Kim
Address	2182-42 Baegok-daero, Mohyeon-eup, Cheoin-gu, Yongin-si, Gyeonggi-do 17036, Korea(Republic of)
Telephone	+82-31-322-6767
Fax	+82-31-322-6768
E-mail	info@lab-t.net
FCC Designation No.	KR0159
FCC Registration No.	133186
IC Registration No.	22000

2.3 Test Site

Test Site	used	Address
Building L	☒	2182-40 Baegok-daero, Mohyeon-eup, Cheoin-gu, Yongin-si, Gyeonggi-do 17036, Korea(Republic of)
Building T	☒	2182-42 Baegok-daero, Mohyeon-eup, Cheoin-gu, Yongin-si, Gyeonggi-do 17036, Korea(Republic of)
Building A	☐	2182-44 Baegok-daero, Mohyeon-eup, Cheoin-gu, Yongin-si, Gyeonggi-do 17036, Korea(Republic of)

3. Information About Test Equipment

3.1 Equipment Information

Equipment type	Remote Control Unit
Model name	FGSC33-TT-04 (P/N : 700194-004)
Variant model name	-
Frequency	433.92 MHz
Modulation type	FSK
Power supply	DC 3.0 V
H/W version	1.0A
S/W version	1.0A

NOTE1: The above EUT information was declared by the manufacturer.

3.2 Antenna Information

Type	Model No.	Gain	Note.
PCB Pattern Antenna	-	-14.108 dBi	-

3.3 Test Frequency

Test mode	Test frequency (MHz)		
	Lowest frequency	Middle frequency	Highest frequency
FSK	-	433.92	-

3.4 Operating conditions for the EUT

Firmware state		1.0A
Test software name(version)		Used native test mode(-)
Test power setting		default
Serial number (Setup mode)	EUT #1	#1 (Conducted Emission)
	EUT #2	#2 (Radiated Emission)

4. Test Report

4.1 Summary

FCC Part 15 & RSS-GEN Issue 5 A2 & RSS-210 Issue 10 A1				
FCC Rule	IC Rule	Parameter	Clause	Status
Transmitter Requirements				
15.203	-	Antenna Requirement	4.4.1	C
15.231(a)(1)	RSS-210 A.1.1(a)	Transmitter Deactivation	4.4.2	C
15.231(b)	RSS-210 A.1.2(b)	Field Strength of Emissions	4.4.3	C
15.231(c)	RSS-210 A.1.3	Emission Bandwidth	4.4.4	C
15.231(b) 15.205(a) 15.209(a)	RSS-210 A.1.2(b) RSS-GEN 8.9 RSS-GEN 8.10	Spurious Emission and Restricted bands	4.4.5	C
15.207(a)	RSS-GEN 8.8	Conducted Emissions	4.4.6	N/A ^{Note2}
-	-	Duty cycle	4.4.7	-
Note 1 : C = Comply N/C = Not Comply N/T = Not Tested N/A = Not Applicable Note 2 : This device gets power supply from only Alkaline battery(AAA 2EA, DC 3.0 V).				

* The general test methods used to test this device is ANSI C63.10:2020

4.2 Measurement Uncertainty

Mesurement items	Expanded Uncertainty
Occupied Channel Bandwidth	17.25 kHz (The confidence level is about 95 %, k=2)
Conducted Spurious Emissions	0.40 dB (The confidence level is about 95 %, k=2)
Radiated Spurious Emissions (1 GHz under)	4.80 dB (The confidence level is about 95 %, k=2)
Radiated Spurious Emissions (Above 1 GHz)	5.96 dB (The confidence level is about 95 %, k=2)

4.4 Transmitter Requirements

4.4.1 Antenna Requirement

4.4.1.1 Regulation

According to §15.203 An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

4.4.1.2 Result

Comply

(The transmitter has a internal PCB Pattern Antenna. The directional peak gain of the antenna is -14.108 dBi.)

4.4.2 Transmitter Deactivation

4.4.2.1 Regulation

According to §15.231(a)(1) A manually operated transmitter shall employ a switch that will automatically deactivate the transmitter within not more than 5 seconds of being released.

According to RSS-210 A.1.1(a) A manually operated transmitter shall be equipped with a push-to-operate switch and be under manual control at all times during transmission. When released, the transmitter shall cease transmission within no more than 5 seconds of being released.

4.4.2.2 Measurement Procedure

ANSI C63.10 § 7.4 determining compliance of unlicensed wireless devices having periodic operation


4.4.2.3 Result

Comply

4.4.2.4 Measurement data

Test mode : GFSK

Frequency(MHz)	Condition	Pulse on time(s)	Limit(s)
433.92	Manually operation	< 5	0.50



4.4.3 Field Strength of Emissions

4.4.3.1 Regulation

According to §15.231(b) In addition to the provisions of § 15.205, the field strength of emissions from intentional radiators operated under this section shall not exceed the following:

Fundamental frequency (MHz)	Field strength of fundamental (microvolts/meter)	Field strength of spurious emissions (microvolts/meter)
40.66-40.70	2,250	225
70-130	1,250	125
130-174	¹ 1,250 to 3,750	¹ 125 to 375
174-260	3,750	375
<u>260-470</u>	<u>¹ 3,750 to 12,500</u>	¹ 375 to 1,250
Above 470	12,500	1,250

¹ Linear interpolations.

According to RSS-210 A.1.2 Following are the requirements for field strength of emissions::

Fundamental frequency (MHz), excluding restricted frequency bands specified in RSS-Gen	Field strength of the fundamental emissions (µV/m at 3 m)
70-130	1,250
130-174	1,250 to 3,750*
174-260**	3,750
<u>260-470**</u>	<u>3,750 to 12,500*</u>
Above 470	12,500

* Linear interpolation with frequency, f, in MHz:

- For 130-174 MHz: Field Strength (µV/m) = (56.82 x f)-6136
- For 260-470 MHz: Field Strength (µV/m) = (41.67 x f)-7083

** Frequency bands 225-328.6 MHz and 335.4-399.9 MHz are designated for the exclusive use of the Government of Canada. Manufacturers should be aware of possible harmful interference and degradation of their licence-exempt radio equipment in these frequency bands.

4.4.3.2 Measurement Procedure

ANSI C63.10 § 4.1.4 FFT-based measurement instrument

ANSI C63.10 § 6.5 Radiated emissions from unlicensed wireless devices in the frequency range of 30 MHz to 1000 MHz

4.4.3.3 Result

Comply (measurement data : refer to the next page)

4.4.3.4 Measurement data

Frequency (MHz)	Detector	Pol. (V/H)	Reading (dBμV)	Factor (dB)	Duty factor (dB)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
433.92	PK	H	92.60	-3.50	-	89.10	100.83	11.73
	AV	H	92.60	-3.50	-12.10	77.00	80.83	3.83
433.92	PK	V	83.60	-3.50	-	80.10	100.83	20.73
	AV	V	83.60	-3.50	-12.10	68.00	80.83	12.83

Note 1 : Measured distance : 3 m

Note 2 : Peak Result : Peak Reading + Factor

Duty factor : $20 \times \log(\text{Duty cycle})$ dB, refer to 4.4.7.7

Average Result : Peak Reading + Factor + Duty factor

4.4.4 Emission Bandwidth

4.4.4.1 Regulation

According to §15.231(c) The bandwidth of the emission shall be no wider than 0.25% of the center frequency for devices operating above 70 MHz and below 900 MHz. For devices operating above 900 MHz, the emission shall be no wider than 0.5% of the center frequency. Bandwidth is determined at the points 20 dB down from the modulated carrier.

According to RSS-210 A.1.3 The occupied bandwidth of momentarily operated devices shall be less than or equal to 0.25% of the centre frequency for devices operating between 70 MHz and 900 MHz. For devices operating above 900 MHz, the occupied bandwidth shall be less than or equal to 0.5% of the centre frequency.

4.4.4.2 Measurement Procedure

ANSI C63.10 § 6.9.2 Occupied bandwidth-relative measurement procedure

ANSI C63.10 § 6.9.2 Occupied bandwidth-power bandwidth (99%) measurement procedure

4.4.4.3 Result


Comply

4.4.4.4 Measurement data


Frequency (MHz)	20 dB Bandwidth (MHz)	Occupied Bandwidth (99 % Bandwidth)(MHz)	Limit (MHz)
433.92	0.016 8	0.039 8	1.084 8

4.4.4.5 Test Plot

20 dB Bandwidth



Occupied Bandwidth(99 % Bandwidth)



4.4.5 Spurious Emission and Restricted bands

4.4.5.1 Regulation

According to §15.231(b) In addition to the provisions of § 15.205, the field strength of emissions from intentional radiators operated under this section shall not exceed the following:

Fundamental frequency (MHz)	Field strength of fundamental (microvolts/meter)	Field strength of spurious emissions (microvolts/meter)
40.66-40.70	2,250	225
70-130	1,250	125
130-174	¹ 1,250 to 3,750	¹ 125 to 375
174-260	3,750	375
<u>260-470</u>	¹ 3,750 to 12,500	¹ <u>375 to 1,250</u>
Above 470	12,500	1,250

¹ Linear interpolations.

(1) The above field strength limits are specified at a distance of 3 meters. The tighter limits apply at the band edges.

(2) Intentional radiators operating under the provisions of this section shall demonstrate compliance with the limits on the field strength of emissions, as shown in the above table, based on the average value of the measured emissions. As an alternative, compliance with the limits in the above table may be based on the use of measurement instrumentation with a CISPR quasi-peak detector. The specific method of measurement employed shall be specified in the application for equipment authorization. If average emission measurements are employed, the provisions in § 15.35 for averaging pulsed emissions and for limiting peak emissions apply. Further, compliance with the provisions of § 15.205 shall be demonstrated using the measurement instrumentation specified in that section.

(3) The limits on the field strength of the spurious emissions in the above table are based on the fundamental frequency of the intentional radiator. Spurious emissions shall be attenuated to the average (or, alternatively, CISPR quasi-peak) limits shown in this table or to the general limits shown in § 15.209, whichever limit permits a higher field strength.

According to RSS-210 A.1.2(b) Unwanted emissions shall be 10 times below the fundamental emissions field strength limits in table A1 or comply with the limits specified in RSS-Gen, whichever is less stringent.

Table A1— Permissible field strength limits for momentarily operated devices

Fundamental frequency (MHz), excluding restricted frequency bands specified in RSS-Gen	Field strength of the fundamental emissions (µV/m at 3 m)
70-130	1,250
130-174	1,250 to 3,750*
174-260**	3,750
<u>260-470**</u>	<u>3,750 to 12,500*</u>
Above 470	12,500

* Linear interpolation with frequency, f, in MHz:

- For 130-174 MHz: Field Strength (µV/m) = (56.82 x f)-6136
- For 260-470 MHz: Field Strength (µV/m) = (41.67 x f)-7083

** Frequency bands 225-328.6 MHz and 335.4-399.9 MHz are designated for the exclusive use of the Government of Canada. Manufacturers should be aware of possible harmful interference and degradation of their licence-exempt radio equipment in these frequency bands.

According to §15.209(a) and RSS-GEN §8.9 Except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009 - 0.490	$2\,400/F(\text{kHz})$	300
0.490 - 1.705	$24\,000/F(\text{kHz})$	30
1.705 - 30.0	30	30
30 - 88	100**	3
88 - 216	150**	3
216 - 960	200**	3
Above 960	500	3

** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54–72 MHz, 76–88 MHz, 174–216 MHz or 470–806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§15.231 and 15.241.

According to §15.205(a),(b) and RSS-GEN §8.10 only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.009 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
0.495 - 0.505	16.694 75 - 16.695 25	608 - 614	5.35 - 5.46
2.173 5 - 2.190 5	16.804 25 - 16.804 75	960 – 1 240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1 300 – 1 427	8.025 - 8.5
4.177 25 - 4.177 75	37.5 - 38.25	1 435 – 1 626.5	9.0 - 9.2
4.207 25 - 4.207 75	73 - 74.6	1 645.5 – 1 646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1 660 – 1 710	10.6 - 12.7
6.267 75 - 6.268 25	108 - 121.94	1 718.8 – 1 722.2	13.25 - 13.4
6.311 75 - 6.312 25	123 - 138	2 200 – 2 300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2 310 – 2 390	15.35 - 16.2
8.362 - 8.366	156.524 75 - 156.525 25	2 483.5 – 2 500	17.7 - 21.4
8.376 25 - 8.386 75	156.7 - 156.9	2 690 – 2 900	22.01 - 23.12
8.414 25 - 8.414 75	162.012 5 - 167.17	3 260 – 3 267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3 332 – 3 339	31.2 - 31.8
12.519 75 - 12.520 25	240 - 285	3 345.8 – 3 358	36.43 - 36.5
12.576 75 - 12.577 25	322 - 335.4	3 600 – 4 400	Above 38.6
13.36 - 13.41			

The field strength of emissions appearing within these frequency bands shall not exceed the limits shown in §15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in §15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in §15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in §15.35 apply to these measurement

4.4.5.2 Measurement Procedure

ANSI C63.10 § 6.4 Radiated emissions from unlicensed wireless devices below 30 MHz
ANSI C63.10 § 6.5 Radiated emissions from unlicensed wireless devices in the frequency range of 30 MHz to 1000 MHz
ANSI C63.10 § 6.6 Radiated emissions from unlicensed wireless devices from 1 GHz to 40 GHz

4.4.5.3 Result

Comply

4.4.5.4 Measurement data

Frequency (MHz)	Detector	Pol. (V/H)	Reading (dBμV)	Factor (dB)	Duty factor (dB)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
868.024	PK	H	62.40	4.20	-	66.60	80.83	14.23
	AV	H	62.40	4.20	-12.10	54.50	60.83	6.33
868.024	PK	V	55.30	4.20	-	59.50	80.83	25.53
	AV	V	55.30	4.20	-12.10	43.20	60.83	17.63
2169.50	PK	V	60.10	-5.70	-	54.36	80.83	26.47
	AV	V	60.10	-5.70	-12.10	42.26	60.83	18.57

NOTE1 : The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Peak detection (PK) and Quasi-peak detection (QP) at frequency below 1 GHz.

NOTE2 : The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1 MHz for Peak detection and frequency above 1 GHz.

NOTE3 : EUT height : 0.8 m is for below 1 GHz testing, and 1.5 m is for above 1 GHz testing

NOTE4 : Below 1 GHz Measured distance : 3 m, Above 1 GHz Measured distance : 1 m

Above 1 GHz Distance Factor = $20\log(1/3) = -9.54$

NOTE5 : Factor : Ant Factor + Cable loss - Amp gain + Distance Factor


NOTE6 : Peak Result : Peak Reading + Factor

Duty factor : $20 \times \log(\text{Duty cycle})$ dB, refer to 4.4.7.7


Average Result : Peak Reading + Factor + Duty factor

4.4.5.5 Measurement Plot


Test mode : 9 kHz ~ 30 MHz



Test mode : 30 MHz ~ 1 GHz



Test mode : 1 GHz ~ 5 GHz



4.4.6 Conducted Emission

4.4.6.1 Regulation

According to §15.207(a) and RSS-GEN §8.8 for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 μ H/50 Ω line impedance stabilization network (LISN).

Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15 – 0.5	66 to 56 *	56 to 46 *
0.5 – 5	56	46
5 - 30	60	50

* Decreases with the logarithm of the frequency.

According to §15.107(a), for unintentional device, except for Class A digital devices, line conducted emission limits are the same as the above table.

4.4.6.2 Measurement Procedure

1) The EUT was placed on a wooden table of size, 1 m by 1.5 m, raised 80 cm in which is located 40 cm away from the vertical wall and 1.5 m away from the side wall of the shielded room.

2) Each current-carrying conductor of the EUT power cord was individually connected through a 50 Ω /50 μ H LISN, which is an input transducer to a Spectrum Analyzer or an EMI/Field Intensity Meter, to the input power source.

3) Exploratory measurements were made to identify the frequency of the emission that had the highest amplitude relative to the limit by operating the EUT in a range of typical modes of operation, cable position, and with a typical system equipment configuration and arrangement. Based on the exploratory tests of the EUT, the one EUT cable configuration and arrangement and mode of operation that had produced the emission with the highest amplitude relative to the limit was selected for the final measurement.

4) The final test on all current-carrying conductors of all of the power cords to the equipment that comprises the EUT (but not the cords associated with other non-EUT equipment is the system) was then performed over the frequency range of 0.15 MHz to 30 MHz.

5) The measurements were made with the detector set to PEAK amplitude within a bandwidth of 10 kHz or to QUASIPeak and AVERAGE within a bandwidth of 9 kHz. The EUT was in transmitting mode during the measurements.

4.4.6.3 Result

Not Applicable(This device gets power supply from only Alkaline battery(AAA 2EA, DC 3.0 V).)


4.4.7 Duty cycle

The duty cycle de-rating factor used in the calculation of average radiated limits (per CFR 15.209 and 15.35(c)) is described below.


Period(ms)	Ontime(ms)	Duty cycle(%)	Duty cycle factor(dB)
108.02	26.82	24.83	-12.10

Duty cycle factor(dB) : 20log(on time/period)

Period



Ontime



Ontime : 9ms + (0.54ms x 33) = 26.82 ms

APPENDIX I

TEST EQUIPMENT USED FOR TESTS

To facilitate inclusion on each page of the test equipment used for related tests, each item of test equipment.

Equipment	Manufacturer	Model	Serial No.	Cal. Date (yy.mm.dd)	Next Cal.Date (yy.mm.dd)
FSV Signal Analyzer	ROHDE&SCHWARZ	FSV40	101010	2021-04-20	2022-04-20
DC Power Supply	AGILENT	E3632A	MY51160055	2021-04-21	2022-04-21
EMI Test Receiver	ROHDE&SCHWARZ	ESU40	100445	2021-09-10	2022-09-10
BiLog Antenna	Schwarzbeck	VULB9168	00821	2021-03-31	2023-03-31
Attenuator	JFW	50F-006	6 dB-3	2021-04-22	2022-04-22
Preamplifier	TSJ	MLA-10k01- b01-27	1870367	2021-04-21	2022-04-21
Antenna Mast(10 m)	TOKIN	5977	-	-	-
Controller(10 m)	TOKIN	5909L	141909L-1	-	-
Turn Table(10 m)	TOKIN	5983-1.5	-	-	-
10 m Semi-Anechoic Chamber	SY CORPORATION	-	-	-	-
Active Loop H-Field	ETS	6502	00150598	2021-05-25	2023-05-25
Double Ridge Horn Antenna	ETS	3117	00168719	2020-08-23	2022-08-23
PREAMPLIFIER	Agilent	8449B	3008A02110	2021-01-11	2022-01-11