



Global Product Certification
EMC-EMF Safety Approvals

EMC Technologies Pty Ltd

ABN 82 057 105 549
176 Harrick Road, Keilor Park
Victoria 3042, Australia

Ph: +61 (0)3 9365 1000
Fax: +61 (0)3 9331 7455
E-mail: sales@emctech.com.au

**RADIO REPORT FOR CERTIFICATION
to
FCC Part 15 Subpart C (Section 15.247)**

FCC ID: YIY-PROD10602

Device under Test: Collison Avoidance System
Personnel Protection Belt Unit

Model Number: PROD10602

Tested For: GE Mining Australia

Report Number: M161022-3R2

Issue Date: 02 May 2017

EMC Technologies Pty Ltd reports apply only to the specific samples tested under stated test conditions. It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical components. EMC Technologies Pty Ltd shall have no liability for any deductions, inferences or generalisations drawn by the client or others from EMC Technologies Pty Ltd issued reports. This report shall not be used to claim, constitute or imply product endorsement by EMC Technologies Pty Ltd.



Accreditation No.5292



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

Except for the certificate of page 3 this document may only be reproduced in full.

RADIO REPORT FOR CERTIFICATION

FCC PART 15 Subpart C (Section 15.247)

CONTENTS

1.0	INTRODUCTION
2.0	GENERAL INFORMATION
3.0	TEST RESULTS
3.1	§15.203 Antenna Requirement
3.2	§15.205 Restricted Bands of Operation
3.3	§15.207 Conducted Limits
3.4	§15.209 Radiated Emission Limits; General Requirements
3.5	§15.247(a) Channel Bandwidth
3.6	§15.247(b) Peak Output Power
3.7	§15.247(d) Out of Band Emissions
3.8	§15.247(e) Power Spectral Density
3.9	§15.247(i) Radio Frequency Exposure (Hazard) Information
3.10	§2.1049 Occupied bandwidth – 99% power
4.0	COMPLIANCE STATEMENT
5.0	MEASUREMENT UNCERTAINTY



Accreditation No.5292



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

Except for the certificate of page 3 this document may only be reproduced in full.



RADIO REPORT **FOR CERTIFICATION**

Issued by: EMC Technologies Pty. Ltd.,
176 Harrick Road, Keilor Park, VIC 3042, Australia.
Phone: +61 3 9365 1000, **E-mail:** sales@emctech.com.au, **Web:** www.emctech.com.au
FCC registration number: 90560 and ISED Canada iOATS number: IC 3569B

Device under Test: Collison Avoidance System
Personnel Protection Belt Unit
Model Number: PROD 10602
Manufacturer: GE Mining Australia

FCC ID: YIY-PROD10602
Equipment Type: Intentional Radiator (900 MHz Transmitter)

Tested for: GE Mining Australia
Address: 3 Co-Wyn Close, Fountaindale, NSW, 2258, Australia
Phone: +612 4336 1800
Contact: Neil Mosley
Email: neil.mosley@ge.com

Standard: **CFR FCC Part 15** – Radio Frequency Devices
Subpart C – Intentional Radiators
Section 15.247 – Operation within the bands 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz

Test Dates: 7 November 2016 to 30 January 2017
Issue Date: 02 May 2017

Attestation: I hereby certify that the device(s) described herein were tested as described in this report and that the data included is that which was obtained during such testing.

Test Engineer: 
Mahan Ghassempouri

Authorised Signatory: 
Chris Zombolas
Technical Director
EMC TECHNOLOGIES PTY. LTD.



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

Except for the certificate of page 3 this document may only be reproduced in full.

RADIO REPORT FOR CERTIFICATION to FCC PART 15 SUBPART C (section 15.247)

1.0 INTRODUCTION

Test results and procedures were performed in accordance with the following Federal Communications Commission (FCC) standards/regulations:

47 CFR, Part 15, Subpart C:	Rules for intentional radiators
Section 15.203:	Antenna requirements
Section 15.205:	Restricted bands of operation
Section 15.207:	Conducted Limits
Section 15.209:	Radiated Emission Limits (General requirements)
Section 15.247:	Operation in the bands 902-928 MHz, 2400-2483.5 MHz, 5725-5850 MHz

The sample **complied** with the applicable requirements of 47 CFR, Part 15 Subpart C – Section 15.247.

1.1 Test Procedure

Radio measurements were performed in accordance with the procedures of ANSI C63.10: 2013. KDB 558074 v03r05 - Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247 was used to demonstrate compliance with FCC part 47CFR15.247.

1.2 Summary of Results

FCC Part 15 Subpart C	Test Performed	Results
15.203	Antenna requirement	Complied
15.205	Restricted bands of operation	Complied
15.207	Conducted limits	Complied
15.209	Radiated emissions limits; general requirements	Complied
15.247 (a)	Channel Bandwidth	Complied
15.247 (b)	Peak Output Power	Complied
15.247 (c)	Antenna Gain > 6 dBi	Not Applicable. Antenna gain < 6 dBi
15.247 (d)	Out of Band Emissions	Complied
15.247 (e)	Peak Power Spectral Density	Complied
15.247 (f)	*Hybrid Systems	Not Applicable. Did not employ a hybrid system
15.247 (g)	Frequency Hopping System with Transmitter and Receiver	Not Applicable. Did not employ frequency hopping
15.247 (h)	Simultaneous occupancy of individual hopping frequencies	Not Applicable. Did not employ frequency hopping
15.247 (i)	Radio Frequency Hazard	M160204F - Complied
2.1049	Occupied Bandwidth	1.053 MHz

1.3 Modifications by EMC Technologies

No modifications were performed.



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

Except for the certificate of page 3 this document may only be reproduced in full.

2.0 GENERAL INFORMATION

(Information supplied by the Client)

2.1 EUT (Transmitter) Details

The RF transmitter was a Short Range Device (SRD) operating in 920 MHz band. The EUT used a PCB antenna. A temporary SMA connector was mounted on the device to provide a means for measuring conducted output power. Transmitter specifications are shown in below table.

Test Sample:	Collision Avoidance System CAS-GPS-PPU, Personnel Protection Belt Unit PROD10602
Model Number:	PROD10602
Operating Frequency Band:	902 MHz to 928 MHz
Frequency Range:	Single Channel at 920 MHz
Modulation:	4GFSK
Number of Channels:	1
Nominal Output Power:	20 dBm
Antenna:	Taoglas PC91.07.0100A.db
Maximum Gain of Antenna Assembly:	2.42 dBi
DC Supply Port Voltage Rating:	3.7 VDC (Internal Li-Ion battery)
Operating Temperature Range:	-20 °C to 55 °C

2.2 EUT (Host) Details

The CAS-GPS PPU is a two part 'wearable technology' device designed to give CAS-GPS (Collision Awareness System) enabled fleet situational awareness of the device wearer. The CAS-GPS PPU will provide warnings of potentially unsafe interactions between personnel and machinery. The CAS-GPS PPU utilises a GNSS receiver for global positioning, Triaxially Diversified Magnetoquasistatic Pick-Up for near field sensing in low permeability atmospheres and a short range digital transceiver for fleet and remote alarm connectivity.

2.3 Test Configuration

Testing was performed with the EUT set to continuously transmit (with modulation applied). Conducted measurements were made at both antenna ports, results from the one having the worst levels for each test are reported. Radiated spurious emission measurements were performed while transmitting from the port selected for conducted spurious emissions.

2.4 Test Facility

2.4.1 General

EMC Technologies Pty Ltd is listed by the FCC as a test laboratory able to perform compliance testing for the public. EMC Technologies is listed as an FCC part 47CFR2.948 test lab and may perform the testing required under Parts 15 and 18 – **FCC Registration Number 90560**

EMC Technologies Pty Ltd has also been accredited as a Conformity Assessment Body (CAB) by Australian Communications and Media Authority (ACMA) under the APECTEL MRA and is designated to perform compliance testing on equipment subject to Declaration of Conformity (DoC) and Certification under Parts 15 and 18 of the FCC Commission's rules – **Registration Number 494713 & Designation number AU0001.**

EMC Technologies indoor open area test site (iOATS) have been accepted by Industry Canada for the performance of radiated measurements in accordance with RSS-Gen, Issue 8 - **Industry Canada iOATS number - IC 3569B**

Measurements in this report were performed at EMC Technologies' laboratory in Keilor Park, Victoria Australia.



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

Except for the certificate of page 3 this document may only be reproduced in full.

2.4.2 NATA Accreditation

NATA is the Australian National laboratory accreditation body and has accredited EMC Technologies to operate to the IEC/ISO17025 requirements. A major requirement for accreditation is the assessment of the company and its personnel as being technically competent in testing to the standards. This requires fully documented test procedures, continued calibration of all equipment to the National Standard at the National Measurements Institute (NMI) and an internal quality system to ISO 9002. NATA has mutual recognition agreements with the National Voluntary Laboratory Accreditation Program (NVLAP) and the American Association for Laboratory Accreditation (A²LA).

EMC Technologies is accredited in Australia by the National Association of Testing Authorities (NATA). All testing in this report has been conducted in accordance with EMC Technologies' scope of NATA accreditation.

The current full scope of accreditation can be found on the NATA website: www.nata.asn.au

2.5 Test Equipment Calibration

Measurement instrumentation and transducers were calibrated in accordance with the applicable standards by an independent NATA registered laboratory such as Agilent Technologies (Australia) Pty Ltd or the National Measurement Institute (NMI) or in-house. All equipment calibration is traceable to Australian national standards at the National Measurements Institute.

Equipment Type	Make/Model/Serial Number	Last Cal. dd/mm/yyyy	Due Date dd/mm/yyyy	Cal. Interval
Chamber	Frankonia SAC-10-2 (R-139)	11/05/2016	11/05/2017	1 Year, *1
EMI Receiver	R&S ESU40 20 Hz – 40 GHz Sn: 100182 (R-037)	18/02/2016	18/02/2017	1 Year, *2
Antennas	EMCO 6502 Active Loop 9 kHz – 30 MHz Sn. 9311-2801 (A-231)	20/07/2015	20/07/2018	3 Year, *2
	SUNOL JB6 Biconilog 30 – 6000 MHz Sn. A012312 (A-363)	26/05/2016	26/05/2018	2 Year, *2
	EMCO 3115 Double Ridge Horn 1 – 18 GHz Sn: 8908-3282 (A-004)	15/07/2016	15/07/2019	3 Year, *1
Cables	Room 12 inbuilt cable Panel 1 to 10 m (C-422)	09/05/2016	09/05/2017	1 Year, *1
	Room 12 inbuilt cable Panel 1 to 3 m (C-421)	09/05/2016	09/05/2017	1 Year, *1
	Room 12 Antenna cable (C-437)	09/05/2016	09/05/2017	1 Year, *1

Note *1. Internal NATA calibration.

Note *2. External NATA / A2LA calibration



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

Except for the certificate of page 3 this document may only be reproduced in full.

3.0 TEST RESULTS

3.1 §15.203 Antenna Requirement

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

EUT used a permanently attached PCB antenna therefore considered sufficient to comply with the provisions of this section. There was no external antenna connector available to the user.

3.2 §15.205 Restricted Bands of Operation

The limits of §15.205 were applied as applicable during the spurious emission tests.

3.3 §15.207 Conducted Limits

3.3.1 Test Procedure

The arrangement specified in ANSI C63.10: 2013 was adhered to for the conducted EMI measurements. The EUT was placed in the RF screened enclosure and a CISPR EMI Receiver as defined in ANSI C63.2: 2009 was used to perform the measurements.

The EMI Receiver was operated under program control using the Max-Hold function and automatic frequency scanning, measurement and data logging techniques. The specified 0.15 MHz to 30 MHz frequency range was sub-divided into sub-ranges to ensure that all short duration peaks were captured.

3.3.2 Peak Maximising Procedure

The various operating modes of the system were investigated. For each of the sub-ranges, the EMI receiver was set to continuous scan with the Peak detector set to Max-Hold mode. The Quasi-Peak detector and the Average detector were then invoked to measure the actual Quasi-Peak and Average level of the most significant peaks, which were detected.

3.3.3 Calculation of Voltage Levels

The voltage levels were automatically measured in software and compared to the test limit. The method of calculation was as follows:

$$V_{EMI} = V_{Rx} + L$$

Where:

V_{EMI}	= The Measured EMI voltage in dBμV to be compared to the limit.
V_{Rx}	= The Voltage in dBμV read directly at the EMI receiver.
L	= The insertion loss in dB of the LISN, cables and transient Limiter.

3.3.4 Plotting of Conducted Emission Measurement Data

The measurement data pertaining to each frequency sub-range were concatenated to form a single graph of (peak) amplitude versus frequency. This was performed for both Active and Neutral lines and the composite graph was subsequently plotted. A list of the highest relevant peaks and the respective Quasi-Peak and Average values were also plotted on the graph.

3.3.5 Test Climatic Conditions

Shielded Room Temperature:	23°C
Relative Humidity:	58%




Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

Except for the certificate of page 3 this document may only be reproduced in full.

3.3.6 Results of Conducted Emission Measurements

Active Line, 0.15 - 30 MHz



Peak	Frequency [MHz]	Line	Quasi-Peak			Average		
			Level [dBμV]	Limit [dBμV]	Margin [±dB]	Level [dBμV]	Limit [dBμV]	Margin [±dB]
1	0.776	Active	33.9	56.0	-22.1	29.1	46.0	-16.9
2	0.362	Active	36.3	58.7	-22.4	31.6	48.7	-17.1
3	0.203	Active	27.1	63.5	-36.4	23.0	53.5	-30.5
4	0.169	Active	24.9	65.0	-40.1	19.8	55.0	-35.2



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

Except for the certificate of page 3 this document may only be reproduced in full.

Neutral Line, 0.15 - 30 MHz

GE Mining
Conducted emission
120 VAC 60 Hz

Limit1: FCC_BQPN
Limit2: FCC_BAVN

FCC Part 15.107 Class B - Quasi-Peak Limit (Conducted)
FCC Part 15.107 Class B - Average Limit (Conducted)


Trace 2: Neutral Line

FCC 15B/15C
Conducted Emissions (dBuV)
~ = QP Value * = CISPR Av

Job No: M161022
Test Date: 12/02/2017

Test Officer: Mahan Ghassempouri-Plot date: 02-12-2017 11:45:41 Wtst: 32-Wplt: 160 Rev: 13-Rx: Rohde & Schwarz, E!
t: L0220918 c1: C3990118 c2: C4440118 p: NONE a: L0170717
Site ID: Room#12(iOATS), 176 Harrick Rd, Keilor Park, Vic

Graph No. 2



Peak	Frequency [MHz]	Line	Quasi-Peak			Average		
			Level [dBμV]	Limit [dBμV]	Margin [±dB]	Level [dBμV]	Limit [dBμV]	Margin [±dB]
1	0.774	Neutral	34.9	56.0	-21.1	30.4	46.0	-15.6
2	0.254	Neutral	36.4	61.6	-25.2	28.4	51.6	-23.2
3	0.385	Neutral	30.4	58.2	-27.8	23.1	48.2	-25.1
4	4.257	Neutral	24.2	56.0	-31.8	16.2	46.0	-29.8
5	1.161	Neutral	23.5	56.0	-32.5	18.6	46.0	-27.4
6	0.638	Neutral	20.6	56.0	-35.4	16.9	46.0	-29.1

The worst case conducted EMI occurred at 0.774 MHz on the neutral line and complied with the §15.207 quasi-peak and average limits by margins of 21.1 dB and 15.6 dB respectively.

3.4 §15.209 Radiated emission limits; general requirements

The limits given in §15.247 applied, however attenuation below the general levels was not required.



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.


Except for the certificate of page 3 this document may only be reproduced in full.

3.5 §15.247(a) Channel Bandwidth

In the band 902 - 928 MHz, the minimum 6 dB bandwidth is to be at least 500 kHz. The 6 dB bandwidth was measured while the device was transmitting with typical modulation applied.

The resolution bandwidth of 100 kHz and the video bandwidth of 300 kHz were utilised when measuring the bandwidth.

Centre Frequency [MHz]	Measured 6 dB Bandwidth [kHz]	Limit [kHz]	Result
920	947	> 500	Complied



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.


Except for the certificate of page 3 this document may only be reproduced in full.

3.6 §15.247(b) Peak Output power

A sample with a temporary antenna connector on the PCB was supplied and the test was performed using conducted measurement. Maximum peak conducted power method (clause 9.1.1 of KDB 558074 v03r05) was used for measurement. Cable loss between connector and spectrum analyser were accounted for in reading.

3.6.1 Results

Measurement results are shown in the following graph.



Frequency (MHz)	Conducted Power		Limit (W)	Margin (W)	Result
	(dBm)	(W)			
920	19.51	0.089	1	0.911	Complied



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

Except for the certificate of page 3 this document may only be reproduced in full.


3.7 §15.247(d) Out of Band Emissions

3.7.1 Band-Edge Emission Measurements

Emissions within 2 MHz of an authorised band edge were measured using the marker-delta method. The in-band emission level of section 3.6 was used while applying marker-delta method. Emissions were measured using conducted method.

All emissions above and below the edge of the authorised band were more than 20 dB below the in band intentional emission.

Lower Band Edge:




Vertical marker F1 were positioned at 902 MHz. Marker 1 shows the peak in band emission and marker 2 shows the peak band edge emission.

In Band Emission (dBm)	Delta (dB)	Band Edge Emission (dBm)	Limit (dBm)	Margin (dB)	Result
19.51	51.18	-31.67	-0.49	-31.18	Pass



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

Except for the certificate of page 3 this document may only be reproduced in full.

Upper Band Edge:

Vertical marker F1 positioned at 928 MHz. Marker 1 shows the peak in band emission and marker 2 shows the peak band edge emission.

In Band Emission (dBm)	Delta (dB)	Band Edge Emission (dBm)	Limit (dBm)	Margin (dB)	Result
19.51	-49.52	-30.01	-0.49	-29.52	Pass



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.


Except for the certificate of page 3 this document may only be reproduced in full.

3.7.2 Conducted Spurious Measurements

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power. Conducted method was used according to clause 11 of KDB 558074 D01.

Results

No emissions were detected within 20 dB of the limit.



Peak	Frequency (MHz)	SA Reading (dBm)	Limit (dBm)
1	919.87	18.85	-1.15

Reference level measurement (in band emission)




Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

Except for the certificate of page 3 this document may only be reproduced in full.




*RBW 200 Hz Marker 1 [T1]
*VBW 300 kHz -90.54 dBm
*SWT 150 s 150.000000000 kHz



Conducted spurious emissions, 9 kHz-150 kHz



*RBW 10 kHz Marker 1 [T1]
*VBW 300 kHz -67.98 dBm
*SWT 150 s 150.995000000 kHz





Conducted spurious emissions, 150 kHz-30 MHz



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

Except for the certificate of page 3 this document may only be reproduced in full.

**Conducted spurious emissions, 30 MHz-1 GHz****Conducted spurious emissions, 1 GHz-10 GHz**

Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

Except for the certificate of page 3 this document may only be reproduced in full.

3.7.3 Radiated Spurious Measurements

Radiated EMI tests were performed in a semi-anechoic chamber compliant with ANSI C63.4: 2014.

The test frequency range was sub-divided into smaller bands with sufficient frequency resolution to permit reliable display and identification of possible EMI peaks. Measurements between 9 kHz and 30 MHz were made at 10 metres using a 0.6 metre loop antenna and calibrated Biconilog antenna for measurements between 30 MHz and 1000 MHz. Calibrated EMCO 3115, EMCO 3116 and ETS standard gain horn antennas were used for measurements between 1 to 25 GHz as applicable.

The EUT was slowly rotated with the spectrum analyser was set to Max-Hold. This was performed for two antenna heights. When an emission was located, it was positively identified and its maximum level found by rotating the automated turntable and by varying the antenna height. The procedure was repeated with the device orientated in three orthogonal axis to further maximise the emission.

Each significant peak was investigated with the Peak/Average Detectors. The measurement data for each frequency range was corrected for cable losses, antenna factors and preamplifier gain. This process was performed for both horizontal and vertical antenna polarisations.

Calculation of field strength

The field strength was calculated automatically by the software using all the pre-stored calibration data. The method of calculation is shown below:

$$E = V + AF - G + L$$

Where:

- E** = Radiated Field Strength in dB μ V/m.
- V** = EMI Receiver Voltage in dB μ V. (measured value)
- AF** = Antenna Factor in dB. (stored as a data array)
- G** = Preamplifier Gain in dB. (stored as a data array)
- L** = Cable loss in dB. (stored as a data array of Insertion Loss versus frequency)

Limit outside restricted bands

Measured conducted power	= 19.5 dBm
Antenna gain	= 2.4 dBi
E.I.R.P.	= 19.5 + 2.4 = 21.9 dBm
	= 107 dB μ V/m at 10 metres
	= 117 dB μ V/m at 3 metres
Limit	= 87 dB μ V/m at 10 metres
	= 97 dB μ V/m at 3 metres




Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

Except for the certificate of page 3 this document may only be reproduced in full.

Frequency Band: 9 kHz - 30 MHz

Measurements were made at a distance of 10 metres. The measurement of emissions between 9 kHz – 150 kHz were made with a resolution bandwidth (RBW) of 200 Hz and the video bandwidth (VBW) of 3 kHz, 150 kHz – 30 MHz were measured with the resolution bandwidth (RBW) of 9 kHz and the video bandwidth (VBW) of 30 kHz.



No emissions were detected above the noise floor of the measuring system and therefore complied with the FCC §15.205 and §15.209 average and quasi-peak limits.




Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

Except for the certificate of page 3 this document may only be reproduced in full.

Frequency Band: 30 - 1000 MHz

Measurements were made at a distance of 10 metres. The measurement of emissions between 30 - 1000 MHz were made with a resolution bandwidth (RBW) of 120 kHz and the video bandwidth (VBW) of 300 kHz.

No emissions detected above the 15.209 limit.



Note: Peak 1 and 2 were the transmitter frequency and not subject to the 15.209 limit.




Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

Except for the certificate of page 3 this document may only be reproduced in full.

Frequency Band: 1000 MHz – 10 GHz

Measurements were made at a distance of 3 metres. The measurement of emissions between 1000 MHz - 10 GHz were made with a resolution bandwidth (RBW) of 1000 kHz and the video bandwidth (VBW) of 1000 kHz for peak and a video bandwidth (VBW) of 10 Hz for average.

Vertical Average Detector Emissions



Point	Frequency (MHz)	Antenna Polarisation	Average (dBuV/m)	Limit (dBuV/m)	Margin (dB)
1	8278.78	Vertical	48.4	54	-5.6
2	3679.58	Vertical	39.3	54	-14.7
3	4599.33	Vertical	38.7	54	-15.3
4	7360.96	Vertical	33.8	54	-20.2
5	1839.47	Vertical	56.6	97	-40.4
6	9200.06	Vertical	35.9	97	-61.1
7	5519.18	Vertical	35.0	97	-62.0



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

Except for the certificate of page 3 this document may only be reproduced in full.

Horizontal Average Detector Emissions


GE Mining - Belt unit
Radiated electric field, 1 GHz - 10 GHz
FCC 15.205 limits
Average detector, Horizontal
FCC 15.247
Radiated Emissions (dBuV/m)
= Ambient ~ = AV Value

Job No: M161022
Test Date: 21/01/2017

Limit1: FCC15205Av3 FCC PART 15.205, 1-40GHz@3mtr

Test Officer: Mahan Ghassempouri-Plot date: 02-07-2017 13:21:35 Wkst: 32-Wplt: 160 Rev: 13-Rx: Rohde&Schwarz, E!
t: A0040719 c1: C3370716 c2: NONE p: A2880516 a:
Site ID: Room#12(iOATS), 176 Harrick Rd, Keilor Park, Vic

Graph No. 6



Point	Frequency (MHz)	Antenna Polarisation	Average (dBuV/m)	Limit (dBuV/m)	Margin (dB)
1	8279.79	Horizontal	40.0	54	-14.0
2	4598.21	Horizontal	39.3	54	-14.7
3	3679.41	Horizontal	38.4	54	-15.6
4	1839.49	Horizontal	51.4	97	-45.6
5	9201.22	Horizontal	35.0	97	-62.0
6	5519.11	Horizontal	34.5	97	-62.5
7	8279.79	Horizontal	40.0	54	-14.0



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

Except for the certificate of page 3 this document may only be reproduced in full.

Vertical Peak Detector Emissions

GE Mining - Belt unit
Radiated electric field, 1 GHz - 10 GHz
FCC 15.205 limits
Peak detector, Vertical
FCC 15.247
Radiated Emissions (dB μ V/m)
= Ambient ~ = Peak Value


Job No: M161022
Test Date: 21/01/2017

Limit1: FCC15205PK3 FCC PART 15.205, 1-40GHz@3mtr

Trace 2: Vertical

Test Officer: Mahan Ghassempouri-Plot date: 02-07-2017 13:00:47 Wkst: 32-Wplt: 160 Rev: 13-Rx: Rohde & Schwarz, E1
t: A0040719 c1: C3370716 c2: NONE p: A2880516 a:
Site ID: Room#12(IQATS), 176 Harrick Rd, Keilor Park, Vic

Graph No. 3



Point	Frequency (MHz)	Antenna Polarisation	Peak (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
1	8276.37	Vertical	62.4	74	-11.6
2	9196.06	Vertical	54.5	74	-19.5
3	3679.83	Vertical	51.1	74	-22.9
4	4601.79	Vertical	50.8	74	-23.2
5	2760.93	Vertical	48.8	74	-25.2
6	1839.3	Vertical	61.9	117	-55.1
7	5519.07	Vertical	47.9	117	-69.1



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

Except for the certificate of page 3 this document may only be reproduced in full.

Horizontal Peak Detector Emissions

GE Mining - Belt unit
Radiated electric field, 1 GHz - 10 GHz
FCC 15.205 limits
Peak detector, Horizontal

FCC 15.247
Radiated Emissions (dBuV/m)
= Ambient ~ = Peak Value


Job No: M161022
Test Date: 21/01/2017

Limit1: FCC15205PK3 FCC PART 15.205, 1-40GHz@3mtr

Trace 2: Horizontal

Test Officer: Mahan Ghassempouri-Plot date: 02-07-2017 13:08:04 Wkst: 32-Wplt: 160 Rev: 13-Rx: Rohde & Schwarz, E1
t: A0040719 c1: C3370716 c2: NONE p: A2880516 a:
Site ID: Room#12(IQATS), 176 Harrick Rd, Keilor Park, Vic

Graph No. 4



Point	Frequency (MHz)	Antenna Polarisation	Peak (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
1	8276.23	Horizontal	56.4	74	-17.6
2	4601.92	Horizontal	53.3	74	-20.7
3	3681.55	Horizontal	51.1	74	-22.9
4	9199.72	Horizontal	49.2	74	-24.8
5	1839.85	Horizontal	59.0	117	-58.0
6	5517.64	Horizontal	47.8	117	-69.2

Conclusion

The spurious emissions complied with the general limits of FCC §15.205 and §15.209 by a margin of 5.6 dB.



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.


Except for the certificate of page 3 this document may only be reproduced in full.

3.8 §15.247(e) Power Spectral Density

The PKPSD method according to KDB 558074 was used to demonstrate compliance.

3.8.1 Results

Measurement results are shown in the following graphs.



Peak PSD (dBm/3 kHz)	Limit (dBm)	Margin (dB)	Result
3.3	8	-4.7	Pass



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

Except for the certificate of page 3 this document may only be reproduced in full.


3.9 §15.247(i) Maximum Permissible Exposure

The EUT complies with FCC requirements for human exposure. Refer to EMC Technologies test report No. M160204F.

3.10 §2.1049 Occupied bandwidth – 99% power

The bandwidth containing 99% power of the transmitted signal was measured using the procedure from ANSI C63.10 section 6.9.

The 99% power bandwidth was **1.053 MHz**.



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

Except for the certificate of page 3 this document may only be reproduced in full.

4.0 COMPLIANCE STATEMENT

The PROD10602 Personnel Protection Belt Unit tested on behalf of GE Mining Australia **complied** with the requirements of 47 CFR, Part 15 Subpart C - Rules for Radio Frequency Devices (intentional radiators).

Results were as follows:

FCC Part 15 Subpart C	Test Performed	Results
15.203	Antenna requirement	Complied
15.205	Restricted bands of operation	Complied
15.207	Conducted limits	Complied
15.209	Radiated emissions limits; general requirements	Complied
15.247 (a)	Channel Bandwidth	Complied
15.247 (b)	Peak Output Power	Complied
15.247 (c)	Antenna Gain > 6 dBi	Not Applicable. Antenna gain < 6 dBi
15.247 (d)	Out of Band Emissions	Complied
15.247 (e)	Peak Power Spectral Density	Complied
15.247 (f)	Hybrid Systems	Not Applicable. Did not employ a hybrid system
15.247 (g)	Frequency Hopping System with Transmitter and Receiver	Not Applicable. Did not employ frequency hopping
15.247 (h)	Simultaneous occupancy of individual hopping frequencies	Not Applicable. Did not employ frequency hopping
15.247 (i)	Radio Frequency Hazard	M160204F - Complied
2.1049	Occupied Bandwidth	1.053 MHz

5.0 MEASUREMENT UNCERTAINTY

EMC Technologies has evaluated the equipment and the methods used to perform the emissions testing. The estimated measurement uncertainties for emissions tests shown within this report are as follows:

Conducted Emissions: 9 kHz to 30 MHz ± 3.2 dB

Radiated Emissions:

9 kHz to 30 MHz	± 4.1 dB
30 MHz to 300 MHz	± 5.1 dB
300 MHz to 1000 MHz	± 4.7 dB
1 GHz to 18 GHz	± 4.6 dB

Peak Output Power: ± 1.5 dB

Peak Power Spectral Density: ± 1.5 dB

The above expanded uncertainties are based on standard uncertainties multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95%.



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

Except for the certificate of page 3 this document may only be reproduced in full.