

Test Report

Report No. : MTi260327008-0101E2
Date of Issue : 2026-04-23
Applicant : Superior communications
Product : 2 in 1 Universal Watch Charger Cable
Model(s) : 06912BK, 06927BK, 4709U
FCC ID : YJW-06912BK

Shenzhen Microtest Co., Ltd.

TEST REPORT

Report No.: MTi260327008-0101E2

Table of contents

1	General Description	4
1.1	Description of the EUT	4
1.2	Description of test modes	5
1.3	Description of support units	6
2	Measurement uncertainty	6
2.1	Test laboratory	7
3	Test facilities and accreditations.....	8
4	List of test equipment	8
5	Test result	9
5.2	Test setup	10
5.3	Test Procedures.....	10
5.4	Information of test equipment.....	11
5.5	Test results.....	12
	Photographs of the Test Setup.....	14
	Photographs of the EUT	15

TEST REPORT

Report No.: MTi260327008-0101E2

Test Result Certification		
Applicant	Superior communications	
Applicant Address	5027 Irwindale Ave, Suite 900, Irwindale Ave, California, United States	
Manufacturer	Shenzhen Powerqi Technology Co.,Ltd	
Manufacturer Address	Room 201, 302, 401 of A4 Building, Block A, Fangxing Science and Technology Park, No. 13 of Baonan Road, Longgang District, Shenzhen, China	
Factory1	Shenzhen Powerqi Technology Co.,Ltd	
Factory Address	Room 201, 302, 401 of A4 Building, Block A, Fangxing Science and Technology Park, No. 13 of Baonan Road, Longgang District, Shenzhen, China	
Factory2	SEOSIN ELECTRONICS VINA CO., LTD.	
Factory Address	Chau Son Park, Le Chan road, Le Hong Phong Ward, Phu Ly City, Ha Nam Province, Viet Nam	
Product description		
Product name	2 in 1 Universal Watch Charger Cable	
Trademark	AT&T 	
Model name	06912BK	
Series Model(s)	06927BK,4709U	
Standards	FCC CFR 47 PART 1, § 1.1310 FCC CFR 47 Part 2.1091	
Test Method	KDB 680106 D01 Wireless Power Transfer v04	
Testing Information		
Date of test	2026-04-10 to 2026-04-20	
Test result	Pass	
Prepared by:	Yanice Xie	
Reviewed by:	David Lee	
Approved by:	Lewis Lian	

TEST REPORT

Report No.: MTi260327008-0101E2

1 General Description

1.1 Description of the EUT

Product name:	2 in 1 Universal Watch Charger Cable
Model name:	06912BK
Series Model(s):	06927BK,4709U
Model difference:	All the models are the same circuit and module, except the model name and factory. 06912BK is made in China, 06927BK and 4709U are made in Viet Nam.
Electrical rating:	Input: 65W Output: Apple/Samsung Watch: 2.5W Max
Accessories:	N/A
Hardware version:	V1.0
Software version:	V1.0
Test sample(s) number:	MTi260327008-01-R001
RF specification:	
Operating frequency range:	115-205kHz(Samsung watch 2.5W)&300-350kHz(Apple watch 2.5W)
Modulation type:	ASK
Antenna type:	Coil

TEST REPORT

Report No.: MTi260327008-0101E2

1.2 Description of test modes

All the test modes were carried out with the EUT in normal operation, the final test mode of the EUT was the worst test mode for emission test, which was shown in this report and defined as:

No.	Emission test modes
Mode1	Wireless Output(Apple watch, Power by C cable)
Mode2	Wireless Output(Apple watch, Power by C port)
Mode3	Wireless Output(Samsung watch 2.5W, Power by C cable)
Mode4	Wireless Output(Samsung watch 2.5W, Power by C port)
Mode5	Stand by

TEST REPORT

Report No.: MTi260327008-0101E2

1.3 Description of support units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Support equipment list			
Description	Model	Serial No.	Manufacturer
Watch	Samsung Galaxy	/	Samsung
Watch	Apple Watch SE	FH7PP6BAG91J6	Apple
HUAWEI QUICK CHARGE(65W)	HW-200325CP1	FL8606P8500764	HUAWEI
Support cable list			
Description	Length (m)	From	To
/	/	/	/

2 Measurement uncertainty

Parameter	Expanded Uncertainty
Magnetic field measurements(3kHz~10MHz)	$\pm 14.8\%$
Electric field measurements(3kHz~10MHz)	$\pm 17.5\%$

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

TEST REPORT

Report No.: MTi260327008-0101E2

2.1 Test laboratory

Test laboratory:	Shenzhen Microtest Co., Ltd.
Test site location:	101, No. 7, Zone 2, Xinxing Industrial Park, Fuhai Avenue, Xinhe Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China
Telephone:	(86-755)88850135
Fax:	(86-755)88850136
CNAS Registration No.:	CNAS L5868
FCC Registration No.:	448573

TEST REPORT

Report No.: MTI260327008-0101E2

3 Test facilities and accreditations

4 List of test equipment

No.	Equipment	Manufacturer	Model	Serial No.	Cal. date	Cal. Due
MTI-E143	Near-field Electric and Magnetic Field Sensor System	SPEAG	MAGPy-8H3 D+E3D	3101	2024/3/12	2027/3/11

No.	Equipment	Manufacturer	Model	Software version:	Cal. date	Cal. Due
MTI-E016S	MPE test software	SPEAG	MAGPY 2.6	2.6	/	/

TEST REPORT

Report No.: MTI260327008-0101E2

5 Test result

5.1.1 Requirement

§1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in §1.1307(b), except in the case of portable devices which shall be evaluated according to the provisions of FCC part 2.1093 of this chapter.

Table 1 to §1.1310(e)(1) - Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(i) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*(100)	≤6
3.0-30	1842/f	4.89/f	*(900/f ²)	<6
30-300	61.4	0.163	1.0	<6
300-1500			f/300	<6
1500-100000			5	<6
(ii) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	<30
1.34-30	824/f	2.19/f	*(180/f ²)	<30
30-300	27.5	0.073	0.2	<30
300-1500			f/1500	<30
1500-100000			1.0	<30

f = frequency in MHz

* = Plane-wave equivalent power density


Note 1: Occupational/controlled exposure limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure.

Note 2: General population/uncontrolled exposure limits apply in situations in which the general public may be exposed, or in which persons who are exposed as a consequence of their employment may not be fully aware of the potential for exposure or cannot exercise control over their exposure.

TEST REPORT

Report No.: MTi260327008-0101E2

5.2 Test setup



Note: tips mode of the test probe is used for 0cm measurement.

5.3 Test Procedures

- The RF exposure test was performed in anechoic chamber.
- E and H-field measurements should be made with these devices considered to meet the § 2.1091-Mobile conditions ("generally be used in such a way that a separation distance of at least 20 centimeters is normally maintained between the RF source's radiating structure(s) and [the nearest person]").
- The highest emission level was recorded and compared with limit.
- The EUT was measured according to the dictates of KDB 680106 D01 Wireless Power Transfer v04.

TEST REPORT

Report No.: MTI260327008-0101E2

5.4 Information of test equipment

Test equipment: MAGPy-8H3D+E3D	
Diameter	60mm
8 isotropic H-field sensors	Concentric loops of 1cm ² arranged at the corner of a cube of 22mm side length
1 isotropic E-field sensor	Orthogonal dipole/monopole (arm length: 50mm)
Measurement center	18.5mm from the probe tip
Dimensions	110*635*35mm (MAGPy-8H3D+E3D V2 & MAGPy-DAS V2)
	
Test probe, without the casing	

Item	Specification
Test frequency range:	3kHz ~ 10MHz
Probe sensitivity	E-field: 0.08-2000 V/m H-field: 0.1-3200 A/m
Probe level response	E-field: ± 1 dB H-field: ± 1 dB
linearity error	E-field: ± 0.3 dB H-field: ± 0.3 dB
Isotropy	E-field: ± 0.8 dB H-field: ± 0.6 dB

TEST REPORT

Report No.: MTI260327008-0101E2

5.5 Test results

Test condition 1: Mode 1 operating mode with client device (1 % battery status of client device)

Probe Position	E –field (V/m)			H–field (A/m)		
	Measurement	Limit	Percentage (%)	Measurement	Limit	Percentage (%)
Top	0.4	614	0.07%	0.02	1.63	1.23%
Bottom	0.28			0.02		
Left	0.37			0.02		
Right	0.34			0.02		
Front	0.36			0.02		
Back	0.41			0.02		

Test condition 2: Mode 1 operating mode with client device (50 % battery status of client device)

Probe Position	E –field (V/m)			H–field (A/m)		
	Measurement	Limit	Max. Percentage (%)	Measurement	Limit	Max. Percentage (%)
Top	0.32	614	0.05%	0.02	1.63	0.98%
Bottom	0.22			0.01		
Left	0.30			0.01		
Right	0.27			0.02		
Front	0.29			0.02		
Back	0.33			0.01		

Test condition 3: Mode 1 operating mode with client device (99 % battery status of client device)

Probe Position	E –field (V/m)			H–field (A/m)		
	Measurement	Limit	Percentage (%)	Measurement	Limit	Percentage (%)
Top	0.26	614	0.04%	0.01	1.63	0.80%
Bottom	0.18			0.009		
Left	0.24			0.01		
Right	0.22			0.01		
Front	0.23			0.01		
Back	0.27			0.008		

TEST REPORT

Report No.: MTi260327008-0101E2

Test condition 1: Mode 3 operating mode with client device (1 % battery status of client device)

Probe Position	E –field (V/m)			H–field (A/m)		
	Measurement	Limit	Percentage (%)	Measurement	Limit	Percentage (%)
Top	0.61	614	0.10%	0.02	1.63	1.23%
Bottom	0.42			0.02		
Left	0.4			0.02		
Right	0.46			0.02		
Front	0.57			0.02		
Back	0.44			0.02		

Test condition 2: Mode 3 operating mode with client device (50 % battery status of client device)

Probe Position	E –field (V/m)			H–field (A/m)		
	Measurement	Limit	Max. Percentage (%)	Measurement	Limit	Max. Percentage (%)
Top	0.49	614	0.08%	0.02	1.63	0.98%
Bottom	0.34			0.01		
Left	0.32			0.02		
Right	0.37			0.02		
Front	0.46			0.02		
Back	0.35			0.01		

Test condition 3: Mode 3 operating mode with client device (99 % battery status of client device)

Probe Position	E –field (V/m)			H–field (A/m)		
	Measurement	Limit	Percentage (%)	Measurement	Limit	Percentage (%)
Top	0.40	614	0.06%	0.009	1.63	0.80%
Bottom	0.27			0.008		
Left	0.26			0.01		
Right	0.30			0.01		
Front	0.37			0.01		
Back	0.29			0.007		

TEST REPORT

Report No.: MTI260327008-0101E2

Photographs of the Test Setup

See the Appendix - Test Setup Photos.

TEST REPORT

Report No.: MTi260327008-0101E2

Photographs of the EUT

See the Appendix - EUT Photos.

TEST REPORT

Report No.: MTi260327008-0101E2

Statement

1. This report is invalid without the seal and signature of the laboratory.
2. The test results of this report are only responsible for the samples submitted. Client shall be responsible for representativeness of the sample and authenticity of the material.
3. The report shall not be partially reproduced without the written consent of the Laboratory.
4. This report is invalid if transferred, altered or tampered with in any form without authorization.
5. The observations or tests with special mark fall outside the scope of accreditation, and are only used for purpose of commission, research, training, internal quality control etc.
6. Any objection to this report shall be submitted to the laboratory within 15 days from the date of receipt of the report.

***** END OF REPORT *****