



Radio Frequency Exposure Evaluation Report

FOR:
Virscient Limited

Model Name:
Trimble Comm board Tornado

Product Description:
WIFI/BT Module

FCC ID: YK5-73350047
IC ID: -----

Applied Rules and Standards:
CFR Part 1 (1.1307 & 1.1310), Part 2 (2.1091),
FCC KDB 447498 D01 General RF Exposure Guidance v06
Industry Canada RSS-102, Issue 5 of March 2015

Report number: EMC_VIRSC-001-17001_MPE
DATE: 2018-10-15



A2LA Accredited

IC recognized #
3462B-2

CETECOM Inc.

411 Dixon Landing Road • Milpitas, CA 95035 • U.S.A.

Phone: + 1 (408) 586 6200 • Fax: + 1 (408) 586 6299 • E-mail: info@cetecom.com • <http://www.cetecom.com>
CETECOM Inc. is a Delaware Corporation with Corporation number: 2905571

1. Assessment

This RF Exposure evaluation report provides information about compliance of the below identified device with the RF Exposure limits for mobile devices as defined in FCC CFR Part 1 (1.1307 & 1.1310), Part 2 (2.1091), and IC standard RSS-102, under given conditions (measured or rated RF output power, antenna gain, distance towards human body of more than 20cm and multiple transmitter information as presented by the applicant). In addition, maximum antenna gain or minimum distance towards the human body is calculated respectively, where relevant.

The device was assessed based on the Bluetooth/BTLE/WLAN 2.4GHz/WLAN 5GHz (UNII-3), the other UNII bands of WLAN 5GHz are not covered in this report


The device meets the limits as stipulated by the above given FCC rule parts based on available specifications.

Company Name	Product Description	Model #
Virscient Limited	WIFI/BT Module	V0009F

Responsible for Testing Laboratory:

2019-02-08	Compliance	Cindy Li (EMC Lab Manager)	 Digitally signed by Cindy Li DN: cn=Cindy Li, o=Cetecom Inc., ou=EMC, email=cindy.li@cetecom.com, c=US Date: 2019.02.08 16:04:42 +08'00'
Date	Section	Name	Signature

Responsible for the Report:

2019-02-08	Compliance	Kevin Wang (Senior EMC Engineer)	 Digitally signed by: kevin. wang@cetecom.com DN: cn = kevin, wang@cetecom.com Date: 2019.02.08 15:32: 54 +08'00'
Date	Section	Name	Signature

The test results of this test report relate exclusively to the test item specified in Section 3.

CETECOM Inc. USA does not assume responsibility for any conclusions and generalizations drawn from the test results with regard to other specimens or samples of the type of the equipment represented by the test item. The test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written approval of CETECOM Inc. USA.

Contents

1. Assessment	2
2. Administrative Data.....	4
2.1. Identification of the Testing Laboratory Issuing the Test Report.....	4
2.2. Identification of the Client.....	4
2.3. Identification of the Manufacturer	4
3. Equipment under Assessment	5
4. RF Exposure Limits and FCC	6
4.1. Power Density Limits acc. to FCC 1.1310(e).....	6
4.2. Power Density Limits acc. To RSS-102.....	6
4.3. Routine Environmental Evaluation Categorical Exclusion Limits acc. to FCC 2.1091(c) ...	6
4.4. Exemption Limits for Routine Evaluation — RF Exposure Evaluation RSS-102	6
4.5. RF Exposure Estimation (MPE Estimation).....	7
5. Evaluations	8
5.1. Routine Environmental Evaluation Applicability Stand Alone transmission	8
5.2. Compliance with MPE (Power Density) limits	8
6. Routine Environmental Evaluation Applicability Simultaneous Transmission.....	9
7. Revision History	10

2. Administrative Data

2.1. Identification of the Testing Laboratory Issuing the Test Report

Company Name:	CETECOM Inc.
Department:	Compliance
Street Address:	411 Dixon Landing Road
City/Zip Code	Milpitas, CA 95035
Country	USA
Telephone:	+1 (408) 586 6200
Fax:	+1 (408) 586 6299
Compliance Manager:	Cindy Li
Responsible Project Leader:	Rami Saman

2.2. Identification of the Client

Applicant's Name:	Virscient Limited
Street Address:	Ruakura Research Centre, 10 Bisley Road
City/Zip Code	Hamilton/3214
Country	New Zealand

2.3. Identification of the Manufacturer

Manufacturer's Name:	Trimble Jena GmbH
Manufacturers Address:	Carl-Zeiss-Promenade 10
City/Zip Code	Jena/07745
Country	Germany

3. Equipment under Assessment

Model No	Trimble Comm board Tornado
HW Version	F
SW Version	v4.5.10.016.DFS
FCC-ID	YK5-73350047
IC-ID	-----
HVIN	-----
PMN	-----
Product Description	WIFI/BT Module
Transceiver Technology / Type(s) of Modulation	IEEE802.11 a/b/g/n/ac, OFDM Bluetooth BR/EDR / GFSK, $\pi/4$ DQPSK, 8DPSKa Bluetooth Low Energy / GFSK
Frequency Range	WLAN 5GHz: 5150-5250MHz; 5250-5350MHz; 5470-5725MHz; 5725-5850MHz; 5805-5845MHz WLAN 2.4GHz/Bluetooth/BTLE: 2400-2483.5 MHz
Max. declared antenna gain	Two same antenna, Pulse W3334B0150 2.4G 4dBi 5G 5.5dBi
Co-located Transmitters/ Antennas?	No
Power Supply/ Rated Operating Voltage Range	USB 5VDC/ 4.75VDC - 5.5VDC
Operating Temperature Range	-20 °C – 70 °C
Sample Revision	☐ Prototype ☒ Production ☐ Pre-Production
Device Category	☒ Fixed Installation ☐ Mobile ☐ Portable
Exposure Category	☐ Occupational/ Controlled ☒ General Population/ Uncontrolled

4. RF Exposure Limits and FCC

For the specific described radio apparatus the following basic limits and rules apply

4.1. Power Density Limits acc. to FCC 1.1310(e)

Frequency Range (MHz)	Power density (mW/cm ²)	Averaging time (minutes)
300 – 1500	$f \text{ (MHz)} / 1500$	30
1500 – 100.000	1.0	30

4.2. Power Density Limits acc. To RSS-102

Frequency Range (MHz)	Power density (W/m ²)	Averaging time (minutes)
300 – 6000	$0.02619 f^{0.6834}$	6

4.3. Routine Environmental Evaluation Categorical Exclusion Limits acc. to FCC 2.1091(c)

Mobile devices that operate in the Commercial Mobile Radio Services pursuant to part 20 of this chapter; the Cellular Radiotelephone Service pursuant to part 22 of this chapter; the Personal Communications Services pursuant to part 24 of this chapter; the Satellite Communications Services pursuant to part 25 of this chapter; the Miscellaneous Wireless Communications Services pursuant to part 27 of this chapter; the Maritime Services (ship earth station devices only) pursuant to part 80 of this chapter; the Specialized Mobile Radio Service, and the 3650 MHz Wireless Broadband Service pursuant to part 90 of this chapter; and the Citizens Broadband Radio Service pursuant to part 96 of this chapter are subject to routine environmental evaluation for RF exposure prior to equipment authorization or use if:

- (i) They operate at frequencies of 1.5 GHz or below and their effective radiated power (ERP) is 1.5 watts or more, or
- (ii) They operate at frequencies above 1.5 GHz and their ERP is 3 watts or more.

4.4. Exemption Limits for Routine Evaluation — RF Exposure Evaluation RSS-102

RF exposure evaluation is required if the separation distance between the user and/or bystander and the device's radiating element is greater than 20 cm, except when the device operates as follows:

- At or above 300 MHz and below 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than $1.31 \times 10^{-2} f^{0.6834} \text{ W}$ (adjusted for tune-up tolerance), where f is in MHz;

4.5. RF Exposure Estimation (MPE Estimation)

Having available the source based average output power and peak antenna gain or the ERP/EIRP of the specified device and for a known minimum distance of its radiating structures from the body of persons according to its use cases (at least 20cm) the power density at that distance can be estimated by the following formula for plane-wave equivalent conditions (far-field conditions), when ground reflection is neglected.

$$S = \frac{PG}{4\pi R^2}$$

Where: S = power density (mW/cm² or W/m²)

P = power input to the antenna (mW or W)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the centre of radiation of the antenna (cm or m)

The objective of the measurements done by CETECOM Inc. was to assess the performance of the EUT according to the relevant requirements specified in FCC rules Part 15.247 of Title 47 of the Code of Federal Regulations and Radio Standard Specification RSS-247 of ISED Canada.

Testing procedures are based on 558074 D01 DTS Meas Guidance v04 – “GUIDANCE FOR PERFORMING COMPLIANCE MEASUREMENTS ON DIGITAL TRANSMISSION SYSTEMS (DTS) OPERATING UNDER SECTION 15.247” - April 5, 2017, by the Federal Communications Commission, Office of Engineering and Technology, Laboratory Division.

5. Evaluations

5.1. Routine Environmental Evaluation Applicability Stand Alone transmission

Transmission Mode	EIRP dBm	Duty Cycle %	Limits for Routine Environmental Evaluation Applicability, EIRP dBm	Exempt from Routine evaluation (Yes/No)
WLAN UNII-3	18.04	0.96	< 34.77	Yes
WLAN 2.4GHz	27.20	0.95	< 34.29	Yes
BT	11.19	0.77	< 34.27	Yes
BTLE	2.97	0.67	< 34.27	Yes

Note1: EIRP power calculation is based on the maximum conducted output power and antenna gain for each transmission band

5.2. Compliance with MPE (Power Density) limits

Power Density Calculation							
Band of Operation MHz	EIRP dBm	Maximum Duty Cycle %	Distance cm	Power Density mW/cm ²	FCC / IC Limit mW/cm ²	percentage of limit used up	Verdict
WLAN UNII-3	18.04	0.96	20	0.0122	1.00/0.97	1.26	Pass
WLAN 2.4GHz	27.20	0.95	20	0.0992	1.00/0.54	18.49	Pass
BT	11.19	0.77	20	0.0020	1.00/0.53	0.38	Pass
BTLE	2.97	0.67	20	0.0003	1.00/0.53	0.05	Pass

6. Routine Environmental Evaluation Applicability Simultaneous Transmission

WLAN and Bluetooth radios share antenna via RF switch so no simultaneous transmission.

7. Revision History

Date	Report Name	Changes to report	Report prepared by
2019-02-05	EMC_VIRSC-001-17001_MPE	Initial Version	Kevin Wang