



**FCC Part 15.209, Subpart C Test Report
on**

**Electromagnetic Swinghandle with Integrated RFID Reader Module
and CANBus Module
Model: H3-EM**

Customer Name:	<u>Southco, Inc.</u>
Customer P.O.:	<u>7500016855</u>
Date of Report Rev.:	<u>January 8, 2018</u>
Test Report No.:	<u>R-2612P-1, Rev. A</u>
Test Start Date:	<u>January 12, 2017</u>
Test Finish Date:	<u>January 12, 2017</u>
Test Technician:	<u>D. Fiore, M. Nowak</u>
Test Engineer:	<u>D. Rybicki</u>
Laboratory Supervisor:	<u>C. Reitz</u>
Results Prepared By:	<u>P. Harris</u>
FCC ID:	<u>YKRGH3EM99521</u>

Our letters, procedures and reports are for the exclusive use of the customer to whom they are addressed and their communication or the use of the name of Retlif Testing Laboratories must receive our prior written approval. Our letters, procedures and reports apply only to the sample tested and are not necessarily indicative of the qualities of apparently identical or similar products. The letters, procedures and reports and the name of Retlif Testing Laboratories or insignia are not to be used under any circumstances in advertising to the public. This report shall not be reproduced, except in full, without the prior written approval of Retlif Testing Laboratories. The only official copy of this document is the signed original provided by Retlif Testing Laboratories.

Certification and Signatures

We certify that these Test Results are true results obtained from the tests of the equipment stated, and relates only to the equipment tested. We further certify that the measurements shown in this Test Results package were made in accordance with the procedures indicated and vouch for the qualifications of all Retlif Testing Laboratories personnel taking them.



David M. Rybicki
EMC Test Engineer
NVLAP Approved Signatory



Colleen T. Reitz
Laboratory Supervisor
NVLAP Approved Signatory

Non-Warranty Provision

The testing services have been performed, findings obtained and reports prepared in accordance with generally accepted laboratory principles and practices. This warranty is in lieu of all others, either expressed or implied.

Non-Endorsement

This test report contains only findings and results arrived at after employing the specific test procedures and standards listed herein. It is not intended to constitute a recommendation, endorsement or certification of the product or material tested. This test report may not be used by the client to claim product endorsement by NVLAP, NIST or any agency of the U.S. Government.



Retlif Testing Laboratories

Report No. R-2612P-1, Rev. A

Revision History

Revisions to this document are listed below; the latest revised document supersedes all previous issues of this document.

Revision	Date	Pages Affected
-	December 11, 2017	Original Release
A	January 8, 2018	Global Changes: • Test Report R-2612P-1 changed to R-2612P-1, Rev. A
		4: • Removed 13.56 MHz from Operating frequency • Changed Equipment Class from DXT to DCD • Removed FCC Registered Test Site Number and Added FCC Accreditation Designation Number: US5342
		5-6: • Changed Fundamental Frequency from 13.56 MHz to 125 kHz
		7: • Radiated Emissions test results revised
		8: • Add note under Equipment List



Retlif Testing Laboratories

Report No. R-2612P-1, Rev. A

Test Program Summary

Report Number:	R-2612P-1, Rev. A		
Customer:	Southco, Inc.		
Address:	210 N. Brinton Lake Road		
	Concordville, PA 19331		
Test Sample:	Electromagnetic Swinghandle with Integrated RFID Reader Module and CANBus Module Consisting Of:		
System Components:	Electromagnetic Swinghandle with Integrated RFID Reader Module	CANBus Module	Door Switch Kit
Part Numbers:	H3-EM-99-521	EA-99-223	EA-99-240
Model Numbers:	H3-EM	N/A	N/A
Manufactured By:	Southco Mfg. Ltd.	Vexos EMS	Vexos EMS
Type:	Low Power Transceiver		
Power Requirements:	5 VDC Provided by CANBus Module		
Frequency of Operation:	125 kHz		
Equipment Class:	DCD		
Equipment Use:	Fixed Mount, < 20 cm		

Test Specification:

FCC Rules and Regulations Part 15, Subpart C, Paragraph 15.209

Test Procedure:

ANSI C63.10:2013

Test Site:

ANSI C63.4:2014

Test Facility:

Retlif Testing Laboratories
3131 Detwiler Road
Harleysville, PA 19438

FCC Accreditation Designation Number: US5342



Retlif Testing Laboratories

Report No. R-2612P-1, Rev. A

Purpose:

The purpose of this test program was to demonstrate compliance of the Electromagnetic Swinghandle with Integrated RFID Reader Module to the requirements of FCC Part 15.209.

Test Methods:

The following table detailed the test method performed on the EUT and the corresponding test results:

Testing Date	Test Method	Test Results
January 12, 2017	15.209, Radiated Emissions (9 kHz to 1 GHz)	Complied

Test Sample Operation:

The EUT is an Electromagnetic Swinghandle with Integrated RFID Reader Module and CANBus Module. The EUT is installed in rack panels which are used in datacenters, industrial enclosures, and secure storage.

Test Sample/Test Program:

- 15.203 Antenna Requirements -The device uses a permanently attached internal antenna. The antenna is totally enclosed inside the case.
- 15.205 Restricted Bands - No emissions were observed from the EUT
- 15.209 Radiated Emissions-Fundamental Frequency 125 kHz, Harmonic/Spurious Emissions 9 kHz to 1000 MHz
- No harmonic or spurious emissions were observed within 10 dB of the specified limit at test distances of 3 meters.
- Radiated Emissions from the EUT were measured in all three axis. The attached Radiated Emissions test data shows the maximized fundamental emission of each orientation.



Retlif Testing Laboratories

Report No. R-2612P-1, Rev. A

Determination of Field Strength Limits:

The field strength limits shown below are derived from Section 15.209.

Fundamental Frequency: 124 kHz

Frequency (MHz)	Field Strength ($\mu\text{V/m}$)	Measurement Distance (m)
0.009 to 0.490	$2400 / F(\text{kHz})$	300
0.490 to 1.705	$24000 / F(\text{kHz})$	30
1.705 to 30	30	30
30 to 88	100	3
88 to 216	150	3
216 to 960	200	3
960 to 1000	500	3

Distance Factor:

Testing was performed at a 3 meter distance and the field strength reading extrapolated to 300 meters for comparison to the 300 meter limit. The field strength reading was extrapolated using the extrapolation (distance) factor of 40dB/decade as specified in 15.31 (f) (2) for frequencies below 30MHz.

Distance Factor from 300 meters to 3 meters (2 decades) = -80dB



Retlif Testing Laboratories

Report No. R-2612P-1, Rev. A

Test Methods:

15.209 Radiated Emissions

The test sample was placed on an 80cm high wooden test stand which was located 3 meters from the test antenna on an FCC listed open area test site. Emissions from the EUT were maximized by rotating the test sample and adjusting the test sample orientation and antenna polarization.

Test Results:

The maximized peak field strength at 13.56 MHz was 4.02uV/M (12.10 dBμV/M) and met the limit specified in 15.209. All harmonic/spurious emissions observed at 3 meter test distances met the limit specified in 15.209. The maximized corrected peak field strength was calculated as follows:

$$R_C = M_R + C_F - D_F$$

Where:

R_C = Corrected Reading in dBμV/M

M_R = Uncorrected Meter Reading in dBμV

C_F = Correction Factor in dB (Antenna Factor + Cable Loss)

D_F = Distance Factor in dB

$$M_R = 43.40 \text{ dB}\mu\text{V}$$

$$C_F = 8.70 \text{ dB}$$

$$D_F = 40 \text{ dB}$$

$$R_C = 43.40\text{dB}\mu\text{V} + 8.7\text{dB} - 40\text{dB} = 12.10 \text{ dB}\mu\text{V/M}$$



Retlif Testing Laboratories

Report No. R-2612P-1, Rev. A

Equipment List Radiated Emissions

EN	Manufacturer	Description	Range	Model No.	Cal Date	Due Date
127A	ETS / EMCO	ANTENNA, BICONICAL	20 - 200 MHz	3104	3/24/2016	9/30/2017
8016	ETS / EMCO	ANTENNA, LOG PERIODIC	200 MHz - 1 GHz	3146	7/18/2016	1/31/2018
8079	ROHDE & SCHWARZ	RECEIVER, EMI	9 kHz - 30 MHz	ESH3	6/15/2016	6/30/2017
8080	ROHDE & SCHWARZ	RECEIVER, EMI	20 - 1300 MHz	354-3000.56ESVP	8/26/2016	8/31/2017
8300	RETLIF	OPEN AREA TEST SITE, ATTENUATION	3/10 Meter OATS	RPA	8/7/2014	8/31/2017
8300C	UNKNOWN	CABLE, COAXIAL	3/10 METER	3 METER CABLE	10/25/2016	10/31/2017
8322	ETS / EMCO	ANTENNA, LOOP	10 KHz - 30 MHz	6512	4/19/2016	4/30/2018
8411	SONOMA INSTRUMENT	PRE-AMPLIFIER	9 KHz - 1 GHz	310N	9/19/2016	9/30/2017
8644	AGILENT / HP	ANALYZER, SPECTRUM	100 Hz - 22 GHz	85662A	7/21/2016	7/31/2017
8644A	AGILENT / HP	ANALYZER, SPECTRUM	100 Hz - 22.5 GHz	8566B	7/21/2016	7/31/2017

Note: Testing was performed January 12, 2017, therefore all equipment listed above was within calibration at the time of test.



Retlif Testing Laboratories

Report No. R-2612P-1, Rev. A

**FCC Part 15, Subpart B, Class B, Radiated Emissions, 9 kHz to 1 GHz
Paragraph 15.209(a)
Test Data**



Retlif Testing Laboratories

Report No. R-2612P-1, Rev. A



Report No. R-2612P-1, Rev. A

40.68	H/1.00	180.0	2.30	13.33	0	15.63	6.05	100
*54.24	V/1.00	180.0	8.50	12.40	0	20.90	11.09	
*54.24	H/1.00	180.0	10.7	12.40	0	23.10	14.29	
*67.80	V/1.00	180.0	11.80	9.65	0	21.45	11.82	
*67.80	H/1.00	180.0	9.40	9.65	0	19.05	8.96	
*81.36	V/1.00	180.0	9.5	8.46	0	17.96	7.91	
*81.36	H/1.00	180.0	9.0	8.46	0	17.46	7.46	
88.00								100
88.00								150
*94.92	V/1.00	180.0	9.80	11.78	0	21.58	11.99	
*94.92	H/1.00	180.0	9.50	11.78	0	21.28	11.59	
108.48	V/1.00	201.5	9.60	13.69	0	23.29	14.60	
108.48	H/2.00	180.0	6.40	13.69	0	20.09	10.10	
122.04	V/1.00	263.3	11.90	13.95	0	25.85	19.61	
122.04	H/1.00	194.1	5.69	13.95	0	19.64	9.59	
135.63	V/1.00	319.6	24.40	13.85	0	38.25	81.75	
135.63	H/3.63	189.6	23.35	13.85	0	37.20	72.44	
143.98	V/1.00	204.2	17.80	14.80	0	32.60	42.66	
143.98	H/3.15	178.4	16.80	14.80	0	31.60	38.02	
149.18	V/1.04	170.7	18.40	15.87	0	34.27	51.70	
149.18	H/2.86	178.7	21.63	15.87	0	37.50	74.99	
203.37	V/1.00	189.6	18.20	13.70	0	31.90	39.36	
203.37	H/1.15	174.5	14.40	13.70	0	28.10	25.41	
216								150
216								200
271.22	V/1.00	235.0	14.40	16.14	0	30.54	33.65	
271.22	H/1.10	188.1	18.30	16.14	0	34.44	52.72	
298.34	V/1.00	82.2	14.9	17.62	0	32.52	42.27	
298.34	H/1.00	190.6	15.10	17.62	0	32.72	43.25	
366.10	V/1.00	74.7	18.80	18.55	0	37.35	73.71	
366.10	H/1.00	189.6	24.60	18.55	0	43.15	143.71	
447.51	V/1.00	153.3	16.60	20.67	0	37.27	73.03	
447.51	H/1.00	188.9	19.60	20.67	0	40.27	103.16	
474.62	V/1.00	203.9	14.50	21.91	0	36.41	66.14	
474.62	H/1.00	213.7	18.1	21.91	0	40.01	100.11	
960.00								200
960.00								500
1000.0								500
The frequency range was scanned from 9kHz to 1 GHz.								
The emissions observed from the EUT do not exceed the specified limits.								
Emissions not recorded were more than 20dB under the specified limit.								
*This represents the minimum sensitivity of measurement system.								



Retlif Testing Laboratories

Report No. R-2612P-1, Rev. A