Radio Exposure Evaluation Report

FCC ID	:	**YL6-143V716**
Equipment	:	**Alarm.com Outdoor 1080p Wi-Fi Video Camera**
Brand Name	:	**ALARM.COM**
Model Name	:	**ADC-V716**
Applicant	:	**Alarm.com Incorporated 8281 Greensboro Drive, Suite 100, Tysons, VA 22102, United States**
Manufacturer	:	**Alarm.com Incorporated 8281 Greensboro Drive, Suite 100, Tysons, VA 22102, United States**
Standard	:	**47 CFR FCC Part 2 Subpart J, section 2.1091**

The product was received on Jun. 05, 2026, and testing was started from Jun. 25, 2026 and completed on Jul. 16, 2026. We, SPORTON INTERNATIONAL INC. Hsinhua Laboratory, would like to declare that the tested sample has been evaluated in accordance with the procedures given in 47 CFR FCC Part 2 Subpart J, section 2.1091 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. Hsinhua Laboratory, the test report shall not be reproduced except in full.

Approved by: Jackson Tsai

SPORTON INTERNATIONAL INC. Hsinhua Laboratory
No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333411, Taiwan (R.O.C.)

Table of Contents

HISTORY OF THIS TEST REPORT 3
SUMMARY OF TEST RESULT 4
1 GENERAL DESCRIPTION 5
1.1 Information 5
1.2 Applicable Standards 8
1.3 Testing Location 8
2 MAXIMUM PERMISSIBLE EXPOSURE 9
2.1 Limit of Maximum Permissible Exposure 9
2.2 RF Exposure Exempt Measurement 10
2.3 Multiple RF Sources Exposure 11
2.4 MPE Calculation Method 12
2.5 Calculated Result and Limit 13

Photographs of EUT V01

History of this test report

Report No.	Version	Description	Issued Date
FA660507	01	Initial issue of report	Aug. 11, 2026

Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
2	-	Exposure evaluation	PASS	-

Declaration of Conformity:
The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.
Comments and Explanations:
None

Reviewed by: Ben Tseng

Report Producer: Amber Chiu

1 General Description

1.1 Information

1.1.1 EUT General Information

RF General Information			
Evaluation Mode	**Frequency Range (MHz)**	**Operating Frequency (MHz)**	**Modulation Type**
2.4GHz WLAN	2400-2483.5	2412-2462	802.11b: DSSS (DBPSK, DQPSK, CCK) 802.11g/n: OFDM (BPSK, QPSK, 16QAM, 64QAM) VHT: OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM)
5GHz WLAN	5150-5250 5250-5350 5470-5725 5725-5850	5180-5240 5260-5320 5500-5700 5745-5825	802.11a/n: OFDM (BPSK, QPSK, 16QAM, 64QAM) 802.11ac: OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM)
Bluetooth	2400-2483.5	2402-2480	BR / EDR: FHSS (GFSK / π/4-DQPSK / 8DPSK) LE: DSSS (GFSK)
LORA	902-928	902.3-914.9 903-927.5	LoRa (125kHz) LoRa (500kHz)

1.1.2 Antenna Information

Ant.	Port	Brand	Model Name	Antenna Type	Connector	Support	Source
1	1	INPAQ	WA-F-LB-02-399	dipole	I-Pex	2.4G+5G	1
2	2	INPAQ	WA-F-LB-01-138	dipole	I-Pex	2.4G+5G+BT	
3	1	INPAQ	WA-F-LORA-05-001	monopole	I-Pex	Lora	

Ant.	Port	Gain (dBi)						
		2.4G	5G				BT	Lora
			UNII-1	UNII-2A	UNII-2C	UNII-3		
1	1	3.78	3.82	3.81	3.39	3.52	-	-
2	2	3.89	3.65	3.85	3.69	3.74	3.89	-
3	1	-	-	-	-	-	-	1.69

Note 1: The EUT has three antennas.
For 2.4GHz function:
For IEEE 802.11 b/g/n mode (2TX/2RX)
Ant. 1 (port 1) and Ant. 2 (port 2) could transmit/receive simultaneously.
For 5GHz function:
For IEEE 802.11 a/n/ac mode (2TX/2RX)
Ant. 1 (port 1) and Ant. 2 (port 2) could transmit/receive simultaneously.
For BT function:
For IEEE 802.15.1 Bluetooth mode (1TX/1RX)
Ant. 2 (port 2) could transmit/receive.
For Lora function:
For Lora mode (1TX/1RX)
Ant. 3 (port 1) could transmit/receive.
Note 2: Directional gain information

	Maximum Output Power	Power Spectral Density
Non-BF	Directional gain = Max.gain + array gain. For power measurements on IEEE 802.11 devices Array Gain = 0 dB (i.e., no array gain) for N ANT ≤ 4	$DirectionalGain = 10 \cdot \log\left[\frac{\sum_{j=1}^{N_{sp}}\left\{\sum_{k=1}^{N_{ant}} g_{j,k}\right\}^2}{N_{ANT}}\right]$
BF	$DirectionalGain = 10 \cdot \log\left[\frac{\sum_{j=1}^{N_{sp}}\left\{\sum_{k=1}^{N_{ant}} g_{j,k}\right\}^2}{N_{ANT}}\right]$	$DirectionalGain = 10 \cdot \log\left[\frac{\sum_{j=1}^{N_{sp}}\left\{\sum_{k=1}^{N_{ant}} g_{j,k}\right\}^2}{N_{ANT}}\right]$

1.1.3 Accessories

Accessories				
AC Adapter	Brand Name	PYS High-Tech Co., LTD	Model Name	PYS-12UP120100U
	Manufacturer	PYS High-Tech Co., LTD	SN	-
	Power Rating	I/P: 100-240Vac, 0.5 A, O/P: 12Vdc, 1 A		
	Power Cord	3 meter, non-shielded cable, w/o ferrite core		

Reminder: Regarding to more detail and other information, please refer to user manual.

1.2 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR FCC Part 2 Subpart J, section 2.1091
- KDB 447498 D04 Interim General RF Exposure Guidance v01

The following reference test guidance is not within the scope of accreditation of TAF.

- 47 CFR Part 1.1307
- 47 CFR Part 1.1310

1.3 Testing Location

Test Lab.：Sporton International Inc. Hsinhua Laboratory		
☒ Hsinhua **(TAF:** 3785**)**	**ADD:** No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333411, Taiwan (R.O.C.)	
	TEL: 886-3-327-3456	**FAX:** 886-3-327-0973
Test site Designation No. TW3785 with FCC.		

2 Maximum Permissible Exposure

2.1 Limit of Maximum Permissible Exposure

(A) Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm²)	Averaging Time |E|²,|H|² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f^2)*	6
30-300	61.4	0.163	1.0	6
300-1500	-	-	F/300	6
1500-100,000	-	-	5	6

(B) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm²)	Averaging Time |E|²,|H|² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f^2)*	30
30-300	27.5	0.073	0.2	30
300-1500	-	-	F/1500	30
1500-100,000	-	-	1.0	30

Note: f = frequency in MHz ; *Plane-wave equivalent power density

Multiple Transmitters Condition
Co-location as simultaneously transmitting (co-transmitting) and the evaluation shall be consider that simultaneous transmissions from co-located devices the individual transmitters are evaluated separately. After sum of the individual value (basic restriction / reference level) are measured/calculated also have to under basic restriction / reference level.
Co-transmitting mode:
WLAN 2.4GHz + LORA
WLAN 5GHz + LORA

2.2 RF Exposure Exempt Measurement

Option	Refer Std.	Exemption Exposure Thresholds (TL)
A	§1.1307(b)(3)(i)(A)	Available maximum time-averaged power is no more than 1 mW
B	§1.1307(b)(3)(i)(B)	$\mathrm{P}th(mW) = \begin{cases} ERP_{20cm}(d/20cm)^x \rightarrow d \le 20cm \\ ERP_{20cm} \rightarrow 20cm < d \le 40cm \end{cases}$ $x = -\log_{10}\left(\frac{60}{ERP_{20cm}\sqrt{f}}\right)$ and f is in GHz $\begin{cases} ERP_{20cm} : 0.3GHz \le f < 1.5GHz \rightarrow 2040\ f(mW) \\ ERP_{20cm} : 1.5GHz \le f \le 6GHz \rightarrow 3060\,(mW) \end{cases}$
C	§1.1307(b)(3)(i)(C)	$\begin{cases} 0.3 \sim 1.34MHz \rightarrow ERP(\mathrm{W}) = 1920\,R^2 \\ 1.34 \sim 30MHz \rightarrow ERP(\mathrm{W}) = 3450\,R^2 / f^2 \\ 30 \sim 300MHz \rightarrow ERP(\mathrm{W}) = 3.83R^2 \\ 300 \sim 1500MHz \rightarrow ERP(\mathrm{W}) = 0.0128\,R^2 f \\ 1500 \sim 100000\,MHz \rightarrow ERP(\mathrm{W}) = 19.2R^2 \end{cases}$ f is in MHz; R is in m; $\mathrm{R} > \lambda / 2\pi$

2.3 Multiple RF Sources Exposure

Refer Std.	Exemption Exposure Thresholds (TL)
§1.1307(b)(3)(ii)(A)	The available maximum time-averaged power of each source is no more than 1 mW and there is a separation distance of two centimeters between any portion of a radiating structure operating and the nearest portion of any other radiating structure in the same device, except if the sum of multiple sources is less than 1 mW during the time-averaging period, in which case they may be treated as a single source (separation is not required)
§1.1307(b)(3)(ii)(B)	$\sum_{i=1}^{a}\frac{P_i}{P_{th,i}}+\sum_{j=1}^{b}\frac{ERP_j}{ERP_{th,j}}+\sum_{k=1}^{c}\frac{Evaluated_k}{ExposureLimit_k}\le 1$ a = number of fixed, mobile, or portable RF sources claiming exemption using paragraph §1.1307(b)(3)(i)(B) of this section for P , including existing exempt transmitters and those being added. b = number of fixed, mobile, or portable RF sources claiming exemption using paragraph §1.1307(b)(3)(i)(C) of this section for Threshold ERP, including existing exempt transmitters and those being added. c = number of existing fixed, mobile, or portable RF sources with known evaluation for the specified minimum distance including existing evaluated transmitters. P_i = the available maximum time-averaged power or the ERP, whichever is greater, for fixed, mobile, or portable RF source i at a distance between 0.5 cm and 40 cm (inclusive). $P_{th,i}$ = the exemption threshold power (P_{th}) according to paragraph §1.1307(b)(3)(i)(B) of this section for fixed, mobile, or portable RF source i. ERP_j = the ERP of fixed, mobile, or portable RF source j. $ERP_{th,j}$ = exemption threshold ERP for fixed, mobile, or portable RF source j, at a distance of at least λ/2π according to the applicable formula of paragraph §1.1307 (b)(3)(i)(C) of this section. $Evaluated_k$ = the maximum reported SAR or MPE of fixed, mobile, or portable RF source k either in the device or at the transmitter site from an existing evaluation at the location of exposure. $Evaluated\ Limit_k$ = either the general population/uncontrolled maximum permissible exposure (MPE) or specific absorption rate (SAR) limit for each fixed, mobile, or portable RF source k, as applicable from § 1.1310 of this chapter.

2.4 MPE Calculation Method

The MPE was calculated at 20 cm to show compliance with the power density limit.
The following formula was used to calculate the Power Density:

E (V/m) = $\frac{\sqrt{30 \times P \times G}}{d}$ Power Density: *Pd* (W/m²) = $\frac{E^2}{377}$

E = Electric field (V/m)

P = RF output power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

Pd = $\frac{30 \times P \times G}{377 \times d^2}$

2.5 Calculated Result and Limit

Exposure Environment: General Population / Uncontrolled Exposure

WLAN 2.4GHz

Mode	DG (dBi)	Power (dBm)	ERP (dBm)	Tolerance (dB)	Tune-up ERP (mW)	Distance (cm)	Option	TL ERP (mW)	TL Ratio
2.4G;G1D	3.89	23.13	24.87	0.50	344.350	20	B	3060.0	0.1126
2.4G;D1D	3.89	22.87	24.61	0.50	324.340	20	B	3060.0	0.1060

WLAN 5GHz

Mode	DG (dBi)	Power (dBm)	ERP (dBm)	Tolerance (dB)	Tune-up ERP (mW)	Distance (cm)	Option	TL ERP (mW)	TL Ratio
5.2G;D1D	3.82	22.21	23.88	0.50	274.157	20	B	3060.0	0.0896
5.3G;D1D	3.85	21.60	23.30	0.50	239.883	20	B	3060.0	0.0784
5.6G;D1D	3.69	21.77	23.31	0.50	240.436	20	B	3060.0	0.0786
5.8G;D1D	3.74	22.87	24.46	0.50	313.329	20	B	3060.0	0.1024

Bluetooth

Mode	DG (dBi)	Power (dBm)	ERP (dBm)	Tolerance (dB)	Tune-up ERP (mW)	Distance (cm)	Option	TL ERP (mW)	TL Ratio
2.4G;BT-LE	3.89	5.92	7.66	0.50	6.546	20	B	3060.0	0.0021
2.4G;BT-BR	3.89	6.41	8.15	0.50	7.328	20	B	3060.0	0.0024
2.4G;BT-EDR	3.89	6.32	8.06	0.50	7.178	20	B	3060.0	0.0023

LORA

Mode	DG (dBi)	Power (dBm)	ERP (dBm)	Tolerance (dB)	Tune-up ERP (mW)	Distance (cm)	Option	TL ERP (mW)	TL Ratio
0.9G;LoRa-500	1.69	21.53	21.07	0.50	143.549	20	B	1842.1	0.0779
0.9G;LoRa-125	1.69	21.54	21.08	0.50	143.880	20	B	1840.7	0.0782
0.9G;LoRa-125	1.69	5.83	5.37	0.50	3.864	20	B	1866.4	0.0021

Note 1: Option A, B and C refer as clause 2.2
Note 2: For option B, Pth(mW) convert to TL ERP(mW); For option C, ERP(W) convert to TL ERP(mW)
Note 3: TL Ratio=Tune-up ERP(mW)/TL ERP(mW)

Simultaneous Transmission Analysis Mode:

WLAN 2.4GHz + LORA

Mode	DG (dBi)	Power (dBm)	ERP (dBm)	Tolerance (dB)	Tune-up ERP (mW)	Distance (cm)	Option	TL ERP (mW)	TL Ratio
2.4G;G1D	3.89	23.13	24.87	0.50	344.350	20	B	3060.0	0.1126
0.9G;LoRa-125	1.69	21.54	21.08	0.50	143.880	20	B	1840.7	0.0782
Sum TL Ratio_B	0.1908								
Ratio Limit	1								

WLAN 5GHz + LORA

Mode	DG (dBi)	Power (dBm)	ERP (dBm)	Tolerance (dB)	Tune-up ERP (mW)	Distance (cm)	Option	TL ERP (mW)	TL Ratio
5.8G;D1D	3.74	22.87	24.46	0.50	313.329	20	B	3060.0	0.1024
0.9G;LoRa-125	1.69	21.54	21.08	0.50	143.880	20	B	1840.7	0.0782
Sum TL Ratio_B	0.1806								
Ratio Limit	1								

Note 1: Option A, B and C refer as clause 2.2
Note 2: For option B, Pth(mW) convert to TL ERP(mW); For option C, ERP(W) convert to TL ERP(mW)
Note 3: TL Ratio=Tune-up ERP(mW)/TL ERP(mW)
Note 4: Refer as clause 2.3 Multiple RF Sources Exposure. Please follow below option and sum TL ration table.

Option	Sum TL Ratio_B	Option	Sum TL Ratio_C	Option	Sum TL Ratio_E
B	$\sum_{i=1}^{a} \frac{P_i}{P_{th,i}}$	C	$\sum_{j=1}^{b} \frac{ERP_j}{ERP_{th,j}}$	E	$\sum_{k=1}^{c} \frac{Evaluated_k}{ExposureLimit_k}$

Note: The above antenna gain was declared by manufacturer.

———THE END———