

## **Appendix A: FCC Part 1.1307, 1.1310, 2.1091, 2.1093; IC RSS-102: RF Exposure**

According to KDB 447498 D01 General RF Exposure Guidance v05 4.3.1. Standalone SAR test exclusion considerations, unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

### **Limits**

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}]$   
 $\leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where

- $f(\text{GHz})$  is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before the calculation
- The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is  $\leq 50$  mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion

### **EUT RF Exposure**

Source-based time averaged worst-case duty cycle is 12.5% per Alarm.com specifications

Peak EIRP = 28 mW

Average EIRP (based on source-based time averaging) =  $28 \text{ mW} \cdot 0.125 = 3.5 \text{ mW}$

General RF Exposure =  $(3.5 \text{ mW} / 5 \text{ mm}) \cdot \sqrt{0.928 \text{ GHz}} = 0.7$

Therefore, SAR test is not required since the result is below the  $\leq 3.0$  1-g SAR limit.

### **IC RSS-102 Issue 5 Technical Brief**

Per section 2.5.1 Table 1, this device is exempt from SAR as the output power is less than the Exemption Limits at a separation distance of less than or equal to 5 mm.