

INTERTEK TESTING SERVICES

RF Exposure

The Equipment under Test (EUT) is a transceiver for the 10670 - PJ MASKS -WALKIE TALKIES operating at 2.4GHz band. It is powered by DC 9.0V (1 x 9.0V 6LR61 battery). For more detail information pls. refer to the user manual.

Antenna Type: Integral antenna.

Antenna Gain: 0dBi.

The normal radiated output power (e.i.r.p) is: 6.0dBm (tolerance: +/- 3dB).

The normal conducted output power is 6.0dBm (tolerance: +/- 3dB).

Modulation Type: GFSK.

According to the KDB 447498:

The Maximum peak radiated emission for the EUT is 102.6dB μ V/m at 3m in the frequency 2443MHz

The EIRP = $[(FS \cdot D)^2 / 30]$ mW = 7.37dBm

which is within the production variation.

The Minimum peak radiated emission for the EUT is 102.2dB μ V/m at 3m in the frequency 2407MHz

The EIRP = $[(FS \cdot D)^2 / 30]$ mW = 6.97dBm

which is within the production variation.

The maximum conducted output power specified is 9dBm = 7.9mW

The source- based time-averaging conducted output power

= 7.9* Duty cycle mW <7.9 mW(Duty cycle <100%)

The SAR Exclusion Threshold Level:

= 3.0 * (min. test separation distance, mm) / sqrt(freq. in GHz)

= 3.0 * 5 / sqrt (2.477) mW

= 9.53 mW

Since the source-based time-averaging conducted output power is well below the SAR low threshold level, so the EUT is considered to comply with SAR requirement without testing.

The duty cycle is simply the on-time divided by the period:

The duration of one cycle = 24.2754ms

Effective period of the cycle = 362.3 μ s = 0.3623ms

DC = 0.3623ms / 24.2754ms = 0.0149 or 1.49%