

FCC Test Report

Report No.: RFBDQY-WTW-P21070082

FCC ID: YOR-RT6600AX

Test Model: RT6600ax

Received Date: Jul. 01, 2021

Test Date: Oct. 19 ~ Nov. 22, 2021

Issued Date: Dec. 17, 2021

Applicant: Synology Incorporated

Address: 9F., No. 1, Yuandong Rd., Banqiao Dist., New Taipei City 220632

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Lin Kou Laboratories

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

Test Location (1): No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City
33383, TAIWAN

FCC Registration / 788550 / TW0003
Designation Number:

Test Location (2): No. 70, Wenming Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C.)

FCC Registration / 281270 / TW0032
Designation Number:



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.

Table of Contents

Release Control Record	4
1 Certificate of Conformity	5
2 Summary of Test Results	6
2.1 Measurement Uncertainty	6
2.2 Modification Record	6
3 General Information	7
3.1 General Description of EUT	7
3.2 Description of Test Modes	8
3.2.1 Test Mode Applicability and Tested Channel Detail	9
3.3 Duty Cycle of Test Signal	11
3.4 Description of Support Units	12
3.4.1 Configuration of System under Test	12
3.5 General Description of Applied Standards and References	12
4 Test Types and Results	13
4.1 Radiated Emission and Bandedge Measurement	13
4.1.1 Limits of Radiated Emission and Bandedge Measurement	13
4.1.2 Test Instruments	14
4.1.3 Test Procedures	15
4.1.4 Deviation from Test Standard	15
4.1.5 Test Setup	16
4.1.6 EUT Operating Conditions	17
4.1.7 Test Results	18
4.2 Conducted Emission Measurement	32
4.2.1 Limits of Conducted Emission Measurement	32
4.2.2 Test Instruments	32
4.2.3 Test Procedures	33
4.2.4 Deviation from Test Standard	33
4.2.5 Test Setup	33
4.2.6 EUT Operating Conditions	33
4.2.7 Test Results	34
4.3 6dB Bandwidth Measurement	36
4.3.1 Limits of 6dB Bandwidth Measurement	36
4.3.2 Test Setup	36
4.3.3 Test Instruments	36
4.3.4 Test Procedure	36
4.3.5 Deviation from Test Standard	36
4.3.6 EUT Operating Conditions	36
4.3.7 Test Result	37
4.4 Conducted Output Power Measurement	39
4.4.1 Limits of Conducted Output Power Measurement	39
4.4.2 Test Setup	39
4.4.3 Test Instruments	39
4.4.4 Test Procedures	39
4.4.5 Deviation from Test Standard	39
4.4.6 EUT Operating Conditions	39
4.4.7 Test Results	40
4.5 Power Spectral Density Measurement	44
4.5.1 Limits of Power Spectral Density Measurement	44
4.5.2 Test Setup	44
4.5.3 Test Instruments	44
4.5.4 Test Procedure	44
4.5.5 Deviation from Test Standard	44
4.5.6 EUT Operating Condition	44

4.5.7 Test Results	45
4.6 Conducted Out of Band Emission Measurement.....	48
4.6.1 Limits of Conducted Out of Band Emission Measurement	48
4.6.2 Test Setup.....	48
4.6.3 Test Instruments	48
4.6.4 Test Procedure	48
4.6.5 Deviation from Test Standard	48
4.6.6 EUT Operating Condition	48
4.6.7 Test Results	48
Annex A - Band Edge Measurement	57
5 Pictures of Test Arrangements.....	63
Appendix – Information of the Testing Laboratories	64

Release Control Record

Issue No.	Description	Date Issued
RFBDQY-WTW-P21070082	Original release	Dec. 17, 2021

1 Certificate of Conformity

Product: 802.11ax Wireless Router

Brand: Synology

Test Model: RT6600ax

Sample Status: Engineering sample

Applicant: Synology Incorporated

Test Date: Oct. 19 ~ Nov. 22, 2021

Standards: 47 CFR FCC Part 15, Subpart C (Section 15.247)
ANSI C63.10:2013

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

Prepared by : Celine Chou , **Date:** Dec. 17, 2021
Celine Chou / Senior Specialist

Approved by : Jeremy Lin , **Date:** Dec. 17, 2021
Jeremy Lin / Project Engineer

2 Summary of Test Results

47 CFR FCC Part 15, Subpart C (Section 15.247)			
FCC Clause	Test Item	Result	Remarks
15.207	AC Power Conducted Emission	Pass	Meet the requirement of limit. Minimum passing margin is -8.25dB at 0.46200MHz.
15.205 / 15.209 / 15.247(d)	Radiated Emissions and Band Edge Measurement	Pass	Meet the requirement of limit. Minimum passing margin is -0.1dB at 2483.50MHz.
15.247(d)	Antenna Port Emission	Pass	Meet the requirement of limit.
15.247(a)(2)	6dB bandwidth	Pass	Meet the requirement of limit.
15.247(b)	Conducted power	Pass	Meet the requirement of limit.
15.247(e)	Power Spectral Density	Pass	Meet the requirement of limit.
15.203	Antenna Requirement	Pass	Antenna connector is ipex(MHF) not a standard connector.

Note:

- For 2.4G band compliance with rule 15.247(d) of the band-edge items, the test plots were recorded in Annex A. Test Procedures refer to report 4.1.3.
- Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Frequency	Expanded Uncertainty (k=2) (±)
Conducted Emissions at mains ports	150kHz ~ 30MHz	2.79 dB
Radiated Emissions up to 1 GHz	9kHz ~ 30MHz	3.00 dB
	30MHz ~ 200MHz	2.91 dB
	200MHz ~ 1000MHz	2.93 dB
Radiated Emissions above 1 GHz	1GHz ~ 18GHz	1.76 dB
	18GHz ~ 40GHz	1.77 dB

2.2 Modification Record

There were no modifications required for compliance.

3 General Information

3.1 General Description of EUT

Product	802.11ax Wireless Router
Brand	Synology
Test Model	RT6600ax
Sample Status	Engineering sample
Power Supply Rating	12Vdc from adapter
Modulation Type	CCK, DQPSK, DBPSK for DSSS 256QAM, 64QAM, 16QAM, QPSK, BPSK for OFDM 1024QAM, 256QAM, 64QAM, 16QAM, QPSK, BPSK for OFDMA
Modulation Technology	DSSS, OFDM, OFDMA
Transfer Rate	802.11b: 11/5.5/2/1Mbps 802.11g: 54/48/36/24/18/12/9/6Mbps 802.11n: up to 400Mbps 802.11ax: up to 574Mbps
Operating Frequency	2412 ~ 2462MHz
Number of Channel	802.11b, 802.11g, 802.11n (HT20), VHT20, 802.11ax (HE20): 11 802.11n (HT40), VHT40, 802.11ax (HE40): 7
Output Power	CDD Mode: 862.745mW Beamforming Mode: 338.819mW
Antenna Type	Refer to note
Antenna Connector	Refer to note
Accessory Device	Adapter
Cable Supplied	0.93m non-shielded RJ45 cable without core

Note:

1. The EUT incorporates a MIMO function. Physically, the EUT provides 2 completed transmitters and 2 receivers.

Modulation Mode	Beamforming Mode	TX Function
802.11b	Not Support	2TX
802.11g	Not Support	2TX
802.11n (HT20)	Support	2TX
802.11n (HT40)	Support	2TX
VHT20	Support	2TX
VHT40	Support	2TX
802.11ax (HE20)	Support	2TX
802.11ax (HE40)	Support	2TX

* The bandwidth and modulation are similar for HT20/HT40 on 802.11n mode and VHT20/VHT40 on 802.11n mode and HE20/HE40 on 802.11ax mode. Therefore the investigated worst case is the representative mode in test report. (Final test mode refer section 3.2.1)

* CDD mode is the worst case for final tests after pretesting CDD mode and Beamforming Mode mode except output power test.

2. There are three radios for the EUT.

Radio	Brand	Model	Function	TX/RX Function
1	Qualcomm	QCN5022	2412 ~ 2462MHz	2x2
2	Qualcomm	QCN5052	5180 ~ 5240MHz	2x2
3	Qualcomm	QCN9024	5745 ~ 5825MHz	4x4

3. The EUT consumes power from the following adapter.

Adapter	
Brand	CWT
Model	2AEJ042FC
Input Power	100-240Vac, 50-60Hz, 1.3A
Output Power	12Vdc, 3.5A, 42.0W
Power Line	1.5m cable without core attached on adapter

4. The antenna information is listed as below.

No.	Brand	Model	Type	Connector	Gain (dBi)			
					2412-2462 MHz	5180-5320 MHz	5500-5825 MHz	5845-5885 MHz
1	LYNwave	ALX21X-221031-00	Dipole	ipex(MHF)	2.00	3.00	-	-
2	LYNwave	ALX21X-221032-00	Dipole	ipex(MHF)	2.00	3.00	-	-
3	LYNwave	ALX21X-221033-00	Dipole	ipex(MHF)	-	-	3.00	3.30
4	LYNwave	ALX21X-221034-00	Dipole	ipex(MHF)	-	-	3.00	3.30
5	LYNwave	ALX21X-221035-00	Dipole	ipex(MHF)	-	-	3.00	3.30
6	LYNwave	ALX21X-221036-00	Dipole	ipex(MHF)	-	-	3.00	3.30

* The above Antenna information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications, the laboratory shall not be held responsible.

3.2 Description of Test Modes

11 channels are provided for 802.11b, 802.11g, 802.11n (HT20), VHT20, 802.11ax (HE20):

Channel	Frequency	Channel	Frequency
1	2412MHz	7	2442MHz
2	2417MHz	8	2447MHz
3	2422MHz	9	2452MHz
4	2427MHz	10	2457MHz
5	2432MHz	11	2462MHz
6	2437MHz		

7 channels are provided for 802.11n (HT40), VHT40, 802.11ax (HE40):

Channel	Frequency	Channel	Frequency
3	2422MHz	7	2442MHz
4	2427MHz	8	2447MHz
5	2432MHz	9	2452MHz
6	2437MHz		

3.2.1 Test Mode Applicability and Tested Channel Detail

EUT Configure Mode	Applicable to				Description
	RE≥1G	RE<1G	PLC	APCM	
-	√	√	√	√	-

Where RE≥1G: Radiated Emission above 1GHz & Bandedge Measurement
PLC: Power Line Conducted Emission

RE<1G: Radiated Emission below 1GHz
APCM: Antenna Port Conducted Measurement

Note:

1. The EUT had been pre-tested on the positioned of each 3 axis. The worst case was found when positioned on **Z-plane**.
2. Radiated emission test (below 1GHz) and power line conducted emission test items chosen the worst maximum power.

Radiated Emission Test (Above 1GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
-	802.11b	1 to 11	1, 6, 11	DSSS	DBPSK	1.0
-	802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6.0
-	802.11ax (HE20)	1 to 11	1, 6, 11	OFDMA	BPSK	MCS0
-	802.11ax (HE40)	3 to 9	3, 6, 9	OFDMA	BPSK	MCS0

Radiated Emission Test (Below 1GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
-	802.11b	1 to 11	6	DSSS	DBPSK	1.0

Power Line Conducted Emission Test:

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
-	802.11b	1 to 11	6	DSSS	DBPSK	1.0

Bandwidth, Power Spectral Density and Conducted Out of Band Emission Measurement:

- ☒ This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
-	802.11b	1 to 11	1, 6, 11	DSSS	DBPSK	1.0
-	802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6.0
-	802.11ax (HE20)	1 to 11	1, 6, 11	OFDMA	BPSK	MCS0
-	802.11ax (HE40)	3 to 9	3, 6, 9	OFDMA	BPSK	MCS0

Conducted Output Power Measurement:

- ☒ This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
-	802.11b	1 to 11	1, 6, 11	DSSS	DBPSK	1.0
-	802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6.0
-	VHT20	1 to 11	1, 6, 11	OFDM	BPSK	MCS0
-	VHT40	3 to 9	3, 6, 9	OFDM	BPSK	MCS0
-	802.11ax (HE20)	1 to 11	1, 6, 11	OFDMA	BPSK	MCS0
-	802.11ax (HE40)	3 to 9	3, 6, 9	OFDMA	BPSK	MCS0

Test Condition:

Applicable to	Environmental Conditions	Input Power	Tested by
RE$\geq$1G	23 deg. C, 68% RH	120Vac, 60Hz	Edison Lee
RE$<$1G	23 deg. C, 68% RH	120Vac, 60Hz	Raymond Lee
PLC	21 deg. C, 68% RH	120Vac, 60Hz	Tim Chen
APCM	25 deg. C, 60% RH	120Vac, 60Hz	Alan Wu

3.3 Duty Cycle of Test Signal


Duty cycle of test signal is < 98%, duty factor is required.

802.11b: Duty cycle = $0.687/1.190 = 0.577$, Duty factor = $10 * \log(1/0.577) = 2.39$

802.11g: Duty cycle = $1.960/2.152 = 0.911$, Duty factor = $10 * \log(1/0.911) = 0.41$

802.11ax (HE20): Duty cycle = $5.467/5.761 = 0.949$, Duty factor = $10 * \log(1/0.949) = 0.23$

802.11ax (HE40): Duty cycle = $5.441/5.712 = 0.953$, Duty factor = $10 * \log(1/0.953) = 0.21$



3.4 Description of Support Units


The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

ID	Product	Brand	Model No.	Serial No.	FCC ID	Remarks
A.	Notebook	DELL	E5430	2RL3YW1	FCC DoC Approved	-
B.	Load	NA	NA	NA	FCC DoC Approved	-
C.	USB Dongle	D-Link	DWM-157	RD0S1F9000417	NA	-

Note: All power cords of the above support units are non-shielded (1.8m).

ID	Cable Descriptions	Qty.	Length (m)	Shielding (Yes/No)	Cores (Qty.)	Remarks
1.	LAN Cable	1	0.93	N	0	Accessory of EUT
2.	LAN Cable	1	6	N	0	RJ45, Cat5e
3.	LAN Cable	4	1.5	N	0	RJ45, Cat5e

3.4.1 Configuration of System under Test



3.5 General Description of Applied Standards and References

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards and references:

Test standard:

FCC Part 15, Subpart C (15.247)

ANSI C63.10:2013

All test items have been performed and recorded as per the above standards.

References Test Guidance:

KDB 558074 D01 15.247 Meas Guidance v05r02

KDB 662911 D01 Multiple Transmitter Output v02r01

All test items have been performed as a reference to the above KDB test guidance.

4 Test Types and Results

4.1 Radiated Emission and Bandedge Measurement

4.1.1 Limits of Radiated Emission and Bandedge Measurement

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 30dB below the highest level of the desired power:

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

Note:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

4.1.2 Test Instruments

Description & Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Due
Test Receiver Rohde & Schwarz	ESR3	102783	Dec. 21, 2020	Dec. 20, 2021
Spectrum Analyzer KEYSIGHT	N9020B	MY60110513	Dec. 21, 2020	Dec. 20, 2021
BILOG Antenna SCHWARZBECK	VULB9168	1214	Nov. 04, 2020 Oct. 28, 2021	Nov. 03, 2021 Oct. 27, 2022
HORN Antenna RF SPIN	DRH18-E	210104A18E	Jan. 08, 2021	Jan. 07, 2022
HORN Antenna SCHWARZBECK	BBHA 9170	9170-1049	Dec. 09, 2020	Dec. 08, 2021
Preamplifier EMCI	EMC330N	980798	Jan. 12, 2021	Jan. 11, 2022
Preamplifier EMCI	EMC118A45SE	980809	Jan. 12, 2021	Jan. 11, 2022
Preamplifier EMCI	EMC184045SE	980786	Jan. 12, 2021	Jan. 11, 2022
RF signal cable EMCI	EMC104-SM-SM-(9000+2000+1000)	201244+ 201232+ 210103	Jan. 12, 2021	Jan. 11, 2022
RF signal cable EMCI	EMCCFD400-NM-N M-(9000+300+500)	201251+ 201249+ 201248	Jan. 12, 2021	Jan. 11, 2022
RF signal cable EMCI	EMC101G-KM-KM-(5000+3000+2000)	201261+201258+201249	Jan. 12, 2021	Jan. 11, 2022
Software BV ADT	ADT_Radiated_V7.6.15.9.5	NA	NA	NA
Antenna Tower Max-Full	MFA-515BSN	NA	NA	NA
Turn Table Max-Full	MFT-201SS	NA	NA	NA
Turn Table Controller Max-Full	MF-7802BS	MF780208676	NA	NA
Peak Power Analyzer KEYSIGHT	8990B	MY51000485	Jan. 19, 2021	Jan. 18, 2022
Wideband Power Sensor KEYSIGHT	N1923A	MY58020002	Jan. 11, 2021	Jan. 10, 2022

Note: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in WM Chamber 9.

4.1.3 Test Procedures

For Radiated emission below 30MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. Parallel, perpendicular, and ground-parallel orientations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

Note:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9kHz at frequency below 30MHz.

For Radiated emission above 30MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters (for 30MHz ~ 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

Note:


1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is $\geq 1/T$ (Duty cycle $< 98\%$) or 10Hz (Duty cycle $\geq 98\%$) for Average detection (AV) at frequency above 1GHz. (802.11b: RBW = 1MHz, VBW = 3kHz; 802.11g: RBW = 1MHz, VBW = 1kHz; 802.11ax (HE20): RBW = 1MHz, VBW = 1kHz; 802.11ax (HE40): RBW = 1MHz, VBW = 1kHz)
4. All modes of operation were investigated and the worst-case emissions are reported.

4.1.4 Deviation from Test Standard


No deviation.

4.1.5 Test Setup


For Radiated emission below 30MHz



For Radiated emission 30MHz to 1GHz



For Radiated emission above 1GHz



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.1.6 EUT Operating Conditions

- Placed the EUT on the testing table.
- Prepared a notebook to act as a communication partner and placed it outside of testing area.
- The communication partner connected with EUT via a RJ45 cable and ran a test program (provided by manufacturer) to enable EUT under transmission condition continuously at specific channel frequency.
- The communication partner sent data to EUT by command.

4.1.7 Test Results

Above 1GHz Data:

RF Mode	TX 802.11b	Channel	CH 1 : 2412 MHz
Frequency Range	1GHz ~ 25GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	61.4 PK	74.0	-12.6	1.85 H	202	29.7	31.7
2	2390.00	49.1 AV	54.0	-4.9	1.85 H	202	17.4	31.7
3	*2412.00	113.5 PK			1.85 H	202	81.7	31.8
4	*2412.00	111.0 AV			1.85 H	202	79.2	31.8
5	4824.00	49.8 PK	74.0	-24.2	2.69 H	7	45.9	3.9
6	4824.00	42.9 AV	54.0	-11.1	2.69 H	7	39.0	3.9
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	62.0 PK	74.0	-12.0	2.06 V	315	30.3	31.7
2	2390.00	53.3 AV	54.0	-0.7	2.06 V	315	21.6	31.7
3	*2412.00	119.1 PK			2.06 V	315	87.3	31.8
4	*2412.00	117.9 AV			2.06 V	315	86.1	31.8
5	4824.00	51.1 PK	74.0	-22.9	1.72 V	300	47.2	3.9
6	4824.00	45.2 AV	54.0	-8.8	1.72 V	300	41.3	3.9

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m).
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB).
3. Margin value = Emission Level – Limit value.
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

RF Mode	TX 802.11b	Channel	CH 6 : 2437 MHz
Frequency Range	1GHz ~ 25GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2437.00	113.9 PK			3.71 H	181	82.1	31.8
2	*2437.00	112.7 AV			3.71 H	181	80.9	31.8
3	4874.00	49.5 PK	74.0	-24.5	2.23 H	33	45.5	4.0
4	4874.00	44.2 AV	54.0	-9.8	2.23 H	33	40.2	4.0
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2437.00	121.9 PK			2.02 V	318	90.1	31.8
2	*2437.00	120.6 AV			2.02 V	318	88.8	31.8
3	4874.00	51.4 PK	74.0	-22.6	1.71 V	318	47.4	4.0
4	4874.00	45.6 AV	54.0	-8.4	1.71 V	318	41.6	4.0

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m).
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB).
3. Margin value = Emission Level – Limit value.
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency.

RF Mode	TX 802.11b	Channel	CH 11 : 2462 MHz
Frequency Range	1GHz ~ 25GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	110.0 PK			2.37 H	205	78.1	31.9
2	*2462.00	108.8 AV			2.37 H	205	76.9	31.9
3	2483.50	61.5 PK	74.0	-12.5	2.37 H	205	29.6	31.9
4	2483.50	48.7 AV	54.0	-5.3	2.37 H	205	16.8	31.9
5	4924.00	48.8 PK	74.0	-25.2	2.49 H	26	44.6	4.2
6	4924.00	44.1 AV	54.0	-9.9	2.49 H	26	39.9	4.2
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	119.4 PK			1.96 V	320	87.5	31.9
2	*2462.00	118.2 AV			1.96 V	320	86.3	31.9
3	2483.50	63.9 PK	74.0	-10.1	1.96 V	320	32.0	31.9
4	2483.50	53.4 AV	54.0	-0.6	1.96 V	320	21.5	31.9
5	4924.00	51.1 PK	74.0	-22.9	1.64 V	299	46.9	4.2
6	4924.00	46.9 AV	54.0	-7.1	1.64 V	299	42.7	4.2

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m).
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB).
3. Margin value = Emission Level – Limit value.
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency.

RF Mode	TX 802.11g	Channel	CH 1 : 2412 MHz
Frequency Range	1GHz ~ 25GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	60.3 PK	74.0	-13.7	1.70 H	143	28.6	31.7
2	2390.00	48.7 AV	54.0	-5.3	1.70 H	143	17.0	31.7
3	*2412.00	114.9 PK			1.70 H	143	83.1	31.8
4	*2412.00	105.7 AV			1.70 H	143	73.9	31.8
5	4824.00	48.4 PK	74.0	-25.6	2.31 H	28	44.5	3.9
6	4824.00	38.1 AV	54.0	-15.9	2.31 H	28	34.2	3.9
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	64.3 PK	74.0	-9.7	2.27 V	21	32.6	31.7
2	2390.00	53.1 AV	54.0	-0.9	2.27 V	21	21.4	31.7
3	*2412.00	121.0 PK			2.27 V	21	89.2	31.8
4	*2412.00	111.8 AV			2.27 V	21	80.0	31.8
5	4824.00	48.7 PK	74.0	-25.3	1.35 V	70	44.8	3.9
6	4824.00	38.0 AV	54.0	-16.0	1.35 V	70	34.1	3.9

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m).
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB).
3. Margin value = Emission Level – Limit value.
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency.

RF Mode	TX 802.11g	Channel	CH 6 : 2437 MHz
Frequency Range	1GHz ~ 25GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2437.00	118.1 PK			1.63 H	144	86.3	31.8
2	*2437.00	108.9 AV			1.63 H	144	77.1	31.8
3	4874.00	49.0 PK	74.0	-25.0	2.33 H	32	45.0	4.0
4	4874.00	38.0 AV	54.0	-16.0	2.33 H	32	34.0	4.0
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2437.00	124.4 PK			2.01 V	24	92.6	31.8
2	*2437.00	115.1 AV			2.01 V	24	83.3	31.8
3	4837.00	48.7 PK	74.0	-25.3	1.38 V	75	44.7	4.0
4	4837.00	37.5 AV	54.0	-16.5	1.38 V	75	33.5	4.0

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m).
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB).
3. Margin value = Emission Level – Limit value.
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency.

RF Mode	TX 802.11g	Channel	CH 11 : 2462 MHz
Frequency Range	1GHz ~ 25GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	114.1 PK			1.52 H	140	82.2	31.9
2	*2462.00	104.8 AV			1.52 H	140	72.9	31.9
3	2483.50	60.7 PK	74.0	-13.3	1.52 H	140	28.8	31.9
4	2483.50	48.1 AV	54.0	-5.9	1.52 H	140	16.2	31.9
5	4924.00	49.0 PK	74.0	-25.0	2.36 H	29	44.8	4.2
6	4924.00	37.7 AV	54.0	-16.3	2.36 H	29	33.5	4.2
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	119.7 PK			2.18 V	13	87.8	31.9
2	*2462.00	110.8 AV			2.18 V	13	78.9	31.9
3	2483.50	65.0 PK	74.0	-9.0	2.18 V	13	33.1	31.9
4	2483.50	51.5 AV	54.0	-2.5	2.18 V	13	19.6	31.9
5	4924.00	49.4 PK	74.0	-24.6	1.30 V	76	45.2	4.2
6	4924.00	37.6 AV	54.0	-16.4	1.30 V	76	33.4	4.2

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m).
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB).
3. Margin value = Emission Level – Limit value.
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency.

RF Mode	TX 802.11ax (HE20)	Channel	CH 1 : 2412 MHz
Frequency Range	1GHz ~ 25GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	59.0 PK	74.0	-15.0	1.45 H	145	27.3	31.7
2	2390.00	47.6 AV	54.0	-6.4	1.45 H	145	15.9	31.7
3	*2412.00	117.4 PK			1.45 H	145	85.6	31.8
4	*2412.00	105.1 AV			1.45 H	145	73.3	31.8
5	4824.00	49.0 PK	74.0	-25.0	2.42 H	20	45.1	3.9
6	4824.00	38.0 AV	54.0	-16.0	2.42 H	20	34.1	3.9
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	65.8 PK	74.0	-8.2	2.30 V	22	34.1	31.7
2	2390.00	52.7 AV	54.0	-1.3	2.30 V	22	21.0	31.7
3	*2412.00	122.8 PK			2.30 V	22	91.0	31.8
4	*2412.00	112.0 AV			2.30 V	22	80.2	31.8
5	4824.00	48.6 PK	74.0	-25.4	1.33 V	72	44.7	3.9
6	4824.00	38.1 AV	54.0	-15.9	1.33 V	72	34.2	3.9

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m).
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB).
3. Margin value = Emission Level – Limit value.
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency.

RF Mode	TX 802.11ax (HE20)	Channel	CH 6 : 2437 MHz
Frequency Range	1GHz ~ 25GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2437.00	120.2 PK			1.59 H	140	88.4	31.8
2	*2437.00	108.1 AV			1.59 H	140	76.3	31.8
3	2483.50	60.7 PK	74.0	-13.3	1.59 H	140	28.8	31.9
4	2483.50	47.6 AV	54.0	-6.4	1.59 H	140	15.7	31.9
5	4874.00	48.0 PK	74.0	-26.0	2.28 H	20	44.0	4.0
6	4874.00	37.6 AV	54.0	-16.4	2.28 H	20	33.6	4.0
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2437.00	126.5 PK			2.32 V	10	94.7	31.8
2	*2437.00	114.7 AV			2.32 V	10	82.9	31.8
3	2483.50	67.5 PK	74.0	-6.5	2.32 V	10	35.6	31.9
4	2483.50	53.6 AV	54.0	-0.4	2.32 V	10	21.7	31.9
5	4874.00	48.9 PK	74.0	-25.1	1.31 V	68	44.9	4.0
6	4874.00	37.7 AV	54.0	-16.3	1.31 V	68	33.7	4.0

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m).
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB).
3. Margin value = Emission Level – Limit value.
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

RF Mode	TX 802.11ax (HE20)	Channel	CH 11 : 2462 MHz
Frequency Range	1GHz ~ 25GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	117.5 PK			1.57 H	141	85.6	31.9
2	*2462.00	105.4 AV			1.57 H	141	73.5	31.9
3	2483.50	63.5 PK	74.0	-10.5	1.57 H	141	31.6	31.9
4	2483.50	49.9 AV	54.0	-4.1	1.57 H	141	18.0	31.9
5	4924.00	49.4 PK	74.0	-24.6	2.32 H	27	45.2	4.2
6	4924.00	37.7 AV	54.0	-16.3	2.32 H	27	33.5	4.2
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	122.5 PK			2.23 V	22	90.6	31.9
2	*2462.00	110.6 AV			2.23 V	22	78.7	31.9
3	2483.50	67.1 PK	74.0	-6.9	2.23 V	22	35.2	31.9
4	2483.50	53.8 AV	54.0	-0.2	2.23 V	22	21.9	31.9
5	4924.00	49.1 PK	74.0	-24.9	1.40 V	71	44.9	4.2
6	4924.00	37.6 AV	54.0	-16.4	1.40 V	71	33.4	4.2

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m).
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB).
3. Margin value = Emission Level – Limit value.
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

RF Mode	TX 802.11ax (HE40)	Channel	CH 3 : 2422 MHz
Frequency Range	1GHz ~ 25GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	60.4 PK	74.0	-13.6	1.56 H	142	28.7	31.7
2	2390.00	48.2 AV	54.0	-5.8	1.56 H	142	16.5	31.7
3	*2422.00	110.7 PK			1.56 H	142	78.9	31.8
4	*2422.00	98.7 AV			1.56 H	142	66.9	31.8
5	4844.00	48.9 PK	74.0	-25.1	2.39 H	26	44.9	4.0
6	4844.00	37.9 AV	54.0	-16.1	2.39 H	26	33.9	4.0
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	64.6 PK	74.0	-9.4	2.01 V	23	32.9	31.7
2	2390.00	53.3 AV	54.0	-0.7	2.01 V	23	21.6	31.7
3	*2422.00	116.6 PK			2.01 V	23	84.8	31.8
4	*2422.00	104.9 AV			2.01 V	23	73.1	31.8
5	4844.00	48.7 PK	74.0	-25.3	1.30 V	77	44.7	4.0
6	4844.00	38.0 AV	54.0	-16.0	1.30 V	77	34.0	4.0

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m).
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB).
3. Margin value = Emission Level – Limit value.
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency.

RF Mode	TX 802.11ax (HE40)	Channel	CH 6 : 2437 MHz
Frequency Range	1GHz ~ 25GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	57.8 PK	74.0	-16.2	1.51 H	139	26.1	31.7
2	2390.00	46.7 AV	54.0	-7.3	1.51 H	139	15.0	31.7
3	*2437.00	111.4 PK			1.51 H	139	79.6	31.8
4	*2437.00	99.0 AV			1.51 H	139	67.2	31.8
5	2483.50	60.8 PK	74.0	-13.2	1.51 H	139	28.9	31.9
6	2483.50	48.2 AV	54.0	-5.8	1.51 H	139	16.3	31.9
7	4874.00	48.9 PK	74.0	-25.1	2.39 H	35	44.9	4.0
8	4874.00	37.6 AV	54.0	-16.4	2.39 H	35	33.6	4.0
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	62.4 PK	74.0	-11.6	1.91 V	22	30.7	31.7
2	2390.00	50.3 AV	54.0	-3.7	1.91 V	22	18.6	31.7
3	*2437.00	117.4 PK			1.91 V	20	85.6	31.8
4	*2437.00	105.7 AV			1.91 V	20	73.9	31.8
5	2483.50	65.4 PK	74.0	-8.6	1.91 V	20	33.5	31.9
6	2483.50	53.9 AV	54.0	-0.1	1.91 V	20	22.0	31.9
7	4874.00	48.9 PK	74.0	-25.1	1.43 V	74	44.9	4.0
8	4874.00	37.4 AV	54.0	-16.6	1.43 V	74	33.4	4.0

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m).
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB).
3. Margin value = Emission Level – Limit value.
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

RF Mode	TX 802.11ax (HE40)	Channel	CH 9 : 2452 MHz
Frequency Range	1GHz ~ 25GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2452.00	111.1 PK			1.53 H	142	79.2	31.9
2	*2452.00	99.1 AV			1.53 H	142	67.2	31.9
3	2483.50	62.2 PK	74.0	-11.8	1.53 H	142	30.3	31.9
4	2483.50	49.7 AV	54.0	-4.3	1.53 H	142	17.8	31.9
5	4904.00	48.7 PK	74.0	-25.3	2.37 H	25	44.5	4.2
6	4904.00	37.3 AV	54.0	-16.7	2.37 H	25	33.1	4.2
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2452.00	116.8 PK			2.07 V	16	84.9	31.9
2	*2452.00	104.7 AV			2.07 V	16	72.8	31.9
3	2483.50	65.6 PK	74.0	-8.4	2.07 V	16	33.7	31.9
4	2483.50	53.8 AV	54.0	-0.2	2.07 V	16	21.9	31.9
5	4904.00	48.8 PK	74.0	-25.2	1.41 V	81	44.6	4.2
6	4904.00	37.4 AV	54.0	-16.6	1.41 V	81	33.2	4.2

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m).
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB).
3. Margin value = Emission Level – Limit value.
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency.


Below 1GHz worst-case data:

RF Mode	TX 802.11b	Channel	CH 6 : 2437 MHz
Frequency Range	30MHz ~ 1GHz	Detector Function	Quasi-Peak (QP)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	86.26	30.4 QP	40.0	-9.6	1.99 H	309	54.4	-24.0
2	125.06	32.3 QP	43.5	-11.2	1.51 H	267	52.4	-20.1
3	246.31	34.6 QP	46.0	-11.4	1.01 H	248	54.3	-19.7
4	267.65	37.5 QP	46.0	-8.5	1.01 H	162	56.5	-19.0
5	347.19	38.7 QP	46.0	-7.3	1.01 H	11	55.4	-16.7
6	767.20	35.0 QP	46.0	-11.0	1.99 H	149	43.1	-8.1

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m).
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB).
3. The other emission levels were very low against the limit of frequency range 30MHz ~ 1000MHz.
4. Margin value = Emission Level – Limit value.
5. The emission levels were very low against the limit of frequency range 9kHz ~ 30MHz: the amplitude of spurious emissions attenuated more than 20 dB below the permissible value to be report.




RF Mode	TX 802.11b	Channel	CH 6 : 2437 MHz
Frequency Range	30MHz ~ 1GHz	Detector Function	Quasi-Peak (QP)

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	125.06	36.4 QP	43.5	-7.1	1.00 V	149	56.5	-20.1
2	348.16	39.7 QP	46.0	-6.3	1.49 V	282	56.3	-16.6
3	378.23	36.2 QP	46.0	-9.8	1.49 V	196	52.0	-15.8
4	411.21	35.5 QP	46.0	-10.5	1.00 V	196	50.7	-15.2
5	521.79	36.9 QP	46.0	-9.1	1.00 V	2	49.5	-12.6
6	626.55	33.0 QP	46.0	-13.0	1.00 V	155	43.4	-10.4

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m).
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB).
3. The other emission levels were very low against the limit of frequency range 30MHz ~ 1000MHz.
4. Margin value = Emission Level – Limit value.
5. The emission levels were very low against the limit of frequency range 9kHz ~ 30MHz: the amplitude of spurious emissions attenuated more than 20 dB below the permissible value to be report.



4.2 Conducted Emission Measurement

4.2.1 Limits of Conducted Emission Measurement

Frequency (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15 - 0.5	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30.0	60	50

Note: 1. The lower limit shall apply at the transition frequencies.

2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

4.2.2 Test Instruments

Description & Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Due
Test Receiver ROHDE & SCHWARZ	ESR3	102783	Dec. 21, 2020	Dec. 20, 2021
RF signal cable (with 10dB PAD) Woken	5D-FB	Cable-cond2-01	Sep. 04, 2021	Sep. 03, 2022
LISN ROHDE & SCHWARZ (EUT)	ESH2-Z5	100100	Jan. 28, 2021	Jan. 27, 2022
LISN ROHDE & SCHWARZ (Peripheral)	ESH3-Z5	100312	Sep. 17, 2021	Sep. 16, 2022
Software ADT	BV ADT_Conc_ V7.3.7.4	NA	NA	NA

Note: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

2. The test was performed in HwaYa Shielded Room 2.

3. The VCCI Site Registration No. is C-12047.

4.2.3 Test Procedures


- The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.

Note: The resolution bandwidth and video bandwidth of test receiver is 9kHz for quasi-peak detection (QP) and average detection (AV) at frequency 0.15MHz-30MHz.

4.2.4 Deviation from Test Standard

No deviation.

4.2.5 Test Setup



Note: 1.Support units were connected to second LISN.

For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.2.6 EUT Operating Conditions

Same as 4.1.6.

4.2.7 Test Results

Worst-case data:


802.11b

Phase	Line (L)	Detector Function	Quasi-Peak (QP) / Average (AV)
-------	----------	-------------------	--------------------------------

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15800	10.11	39.83	21.34	49.94	31.45	65.57	55.57	-15.63	-24.12
2	0.20200	10.13	37.21	18.97	47.34	29.10	63.53	53.53	-16.19	-24.43
3	0.46936	10.14	32.78	24.98	42.92	35.12	56.53	46.53	-13.61	-11.41
4	0.69000	10.15	27.50	17.61	37.65	27.76	56.00	46.00	-18.35	-18.24
5	11.35800	10.35	24.72	16.63	35.07	26.98	60.00	50.00	-24.93	-23.02
6	17.13800	10.43	19.39	9.59	29.82	20.02	60.00	50.00	-30.18	-29.98

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.




Phase	Neutral (N)	Detector Function	Quasi-Peak (QP) / Average (AV)
-------	-------------	-------------------	--------------------------------

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.17000	10.12	38.17	22.55	48.29	32.67	64.96	54.96	-16.67	-22.29
2	0.22200	10.13	36.13	21.97	46.26	32.10	62.74	52.74	-16.48	-20.64
3	0.46200	10.15	32.68	28.26	42.83	38.41	56.66	46.66	-13.83	-8.25
4	0.91000	10.18	25.73	15.20	35.91	25.38	56.00	46.00	-20.09	-20.62
5	6.17400	10.33	21.29	10.22	31.62	20.55	60.00	50.00	-28.38	-29.45
6	11.74200	10.46	24.26	16.69	34.72	27.15	60.00	50.00	-25.28	-22.85

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.




4.3 6dB Bandwidth Measurement

4.3.1 Limits of 6dB Bandwidth Measurement

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

4.3.2 Test Setup



4.3.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.3.4 Test Procedure

- Set resolution bandwidth (RBW) = 100kHz.
- Set the video bandwidth (VBW) $\geq 3 \times$ RBW, Detector = peak.
- Trace mode = max hold.
- Sweep = auto couple.
- Measure the maximum width of the emission that is constrained by the frequencies associated with the two amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

4.3.5 Deviation from Test Standard

No deviation.

4.3.6 EUT Operating Conditions

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

4.3.7 Test Result

802.11b

Channel	Frequency (MHz)	6dB Bandwidth (MHz)		Minimum Limit (MHz)	Pass / Fail
		Chain 0	Chain 1		
1	2412	8.08	8.09	0.50	Pass
6	2437	8.08	8.08	0.50	Pass
11	2462	7.56	7.57	0.50	Pass

802.11g

Channel	Frequency (MHz)	6dB Bandwidth (MHz)		Minimum Limit (MHz)	Pass / Fail
		Chain 0	Chain 1		
1	2412	15.68	16.08	0.50	Pass
6	2437	16.27	16.06	0.50	Pass
11	2462	16.05	16.07	0.50	Pass

802.11ax (HE20)


Channel	Frequency (MHz)	6dB Bandwidth (MHz)		Minimum Limit (MHz)	Pass / Fail
		Chain 0	Chain 1		
1	2412	18.40	18.07	0.50	Pass
6	2437	18.19	18.28	0.50	Pass
11	2462	17.97	17.84	0.50	Pass

802.11ax (HE40)


Channel	Frequency (MHz)	6dB Bandwidth (MHz)		Minimum Limit (MHz)	Pass / Fail
		Chain 0	Chain 1		
3	2422	37.73	37.93	0.50	Pass
6	2437	37.72	37.83	0.50	Pass
9	2452	37.21	37.77	0.50	Pass

Spectrum Plot of Worst Value


802.11b




802.11g



802.11ax (HE20)



802.11ax (HE40)



4.4 Conducted Output Power Measurement

4.4.1 Limits of Conducted Output Power Measurement


For systems using digital modulation in the 2400–2483.5 MHz bands: 1 Watt (30dBm)

Per KDB 662911 D01 Multiple Transmitter Output Method of conducted output power measurement on IEEE 802.11 devices,

- Array Gain = 0 dB (i.e., no array gain) for $N_{ANT} \leq 4$;
- Array Gain = 0 dB (i.e., no array gain) for channel widths ≥ 40 MHz for any N_{ANT} ;
- Array Gain = $5 \log(N_{ANT}/N_{SS})$ dB or 3 dB, whichever is less for 20-MHz channel widths with $N_{ANT} \geq 5$.

For power measurements on all other devices: Array Gain = $10 \log(N_{ANT}/N_{SS})$ dB.

4.4.2 Test Setup



4.4.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.4.4 Test Procedures

Average power sensor was used to perform output power measurement, trigger and gating function of wide band power meter is enabled to measure max output power of TX on burst. Duty factor is not added to measured value.

4.4.5 Deviation from Test Standard

No deviation.

4.4.6 EUT Operating Conditions

Same as item 4.3.6.

4.4.7 Test Results

CDD Mode

802.11b

Channel	Frequency (MHz)	Average Power (dBm)		Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1				
1	2412	24.34	24.03	524.574	27.20	30.00	Pass
6	2437	26.52	26.17	862.745	29.36	30.00	Pass
11	2462	23.73	23.45	457.357	26.60	30.00	Pass

802.11g

Channel	Frequency (MHz)	Average Power (dBm)		Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1				
1	2412	22.45	22.02	335.013	25.25	30.00	Pass
6	2437	25.61	25.17	692.767	28.41	30.00	Pass
11	2462	20.33	20.21	212.849	23.28	30.00	Pass

802.11n (HT20)

Channel	Frequency (MHz)	Average Power (dBm)		Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1				
1	2412	21.63	21.30	280.442	24.48	30.00	Pass
6	2437	25.41	25.00	663.764	28.22	30.00	Pass
11	2462	21.62	21.38	282.615	24.51	30.00	Pass

802.11n (HT40)

Channel	Frequency (MHz)	Average Power (dBm)		Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1				
3	2422	18.55	18.01	134.856	21.30	30.00	Pass
6	2437	18.89	18.59	149.723	21.75	30.00	Pass
9	2452	18.24	17.98	129.487	21.12	30.00	Pass

VHT20

Channel	Frequency (MHz)	Average Power (dBm)		Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1				
1	2412	21.66	21.35	283.013	24.52	30.00	Pass
6	2437	25.47	25.08	674.478	28.29	30.00	Pass
11	2462	21.63	21.40	283.584	24.53	30.00	Pass

VHT40

Channel	Frequency (MHz)	Average Power (dBm)		Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1				
3	2422	18.60	18.10	137.009	21.37	30.00	Pass
6	2437	19.00	18.65	152.715	21.84	30.00	Pass
9	2452	18.36	18.02	131.936	21.20	30.00	Pass

802.11ax (HE20)

Channel	Frequency (MHz)	Average Power (dBm)		Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1				
1	2412	21.69	21.37	284.659	24.54	30.00	Pass
6	2437	25.49	25.10	677.591	28.31	30.00	Pass
11	2462	21.66	21.42	285.230	24.55	30.00	Pass

802.11ax (HE40)

Channel	Frequency (MHz)	Average Power (dBm)		Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1				
3	2422	18.62	18.15	138.091	21.40	30.00	Pass
6	2437	19.04	18.68	153.958	21.87	30.00	Pass
9	2452	18.39	18.04	132.704	21.23	30.00	Pass

Beamforming Mode

802.11n (HT20)

Channel	Frequency (MHz)	Average Power (dBm)		Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1				
1	2412	18.62	18.29	140.231	21.47	30.00	Pass
6	2437	22.40	21.99	331.905	25.21	30.00	Pass
11	2462	18.61	18.37	141.317	21.50	30.00	Pass

Note: Directional gain = $2\text{dBi} + 10\log(2) = 5.01\text{dBi} < 6\text{dBi}$, so the power limit not need to reduce.

802.11n (HT40)

Channel	Frequency (MHz)	Average Power (dBm)		Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1				
3	2422	15.54	15.00	67.432	18.29	30.00	Pass
6	2437	15.88	15.58	74.867	18.74	30.00	Pass
9	2452	15.23	14.97	64.748	18.11	30.00	Pass

Note: Directional gain = $2\text{dBi} + 10\log(2) = 5.01\text{dBi} < 6\text{dBi}$, so the power limit not need to reduce.

VHT20

Channel	Frequency (MHz)	Average Power (dBm)		Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1				
1	2412	18.65	18.34	141.516	21.51	30.00	Pass
6	2437	22.46	22.07	337.262	25.28	30.00	Pass
11	2462	18.62	18.39	141.802	21.52	30.00	Pass

Note: Directional gain = $2\text{dBi} + 10\log(2) = 5.01\text{dBi} < 6\text{dBi}$, so the power limit not need to reduce.

VHT40

Channel	Frequency (MHz)	Average Power (dBm)		Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1				
3	2422	15.59	15.09	68.509	18.36	30.00	Pass
6	2437	15.99	15.64	76.363	18.83	30.00	Pass
9	2452	15.35	15.01	65.972	18.19	30.00	Pass

Note: Directional gain = $2\text{dBi} + 10\log(2) = 5.01\text{dBi} < 6\text{dBi}$, so the power limit not need to reduce.

802.11ax (HE20)

Channel	Frequency (MHz)	Average Power (dBm)		Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1				
1	2412	18.68	18.36	142.339	21.53	30.00	Pass
6	2437	22.48	22.09	338.819	25.30	30.00	Pass
11	2462	18.65	18.41	142.625	21.54	30.00	Pass

Note: Directional gain = $2\text{dBi} + 10\log(2) = 5.01\text{dBi} < 6\text{dBi}$, so the power limit not need to reduce.

802.11ax (HE40)

Channel	Frequency (MHz)	Average Power (dBm)		Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1				
3	2422	15.61	15.14	69.050	18.39	30.00	Pass
6	2437	16.03	15.67	76.984	18.86	30.00	Pass
9	2452	15.38	15.03	66.356	18.22	30.00	Pass


Note: Directional gain = $2\text{dBi} + 10\log(2) = 5.01\text{dBi} < 6\text{dBi}$, so the power limit not need to reduce.

4.5 Power Spectral Density Measurement

4.5.1 Limits of Power Spectral Density Measurement

The Maximum of Power Spectral Density Measurement is 8dBm in any 3 kHz.

4.5.2 Test Setup



4.5.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.5.4 Test Procedure

- a. Measure the duty cycle (x).
- b. Set instrument center frequency to DTS channel center frequency.
- c. Set span to at least 1.5 times the OBW.
- d. Set RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- e. Set VBW $\geq 3 \times \text{RBW}$.
- f. Detector = power averaging (RMS) or sample detector (when RMS not available).
- g. Ensure that the number of measurement points in the sweep $\geq 2 \times \text{span}/\text{RBW}$.
- h. Sweep time = auto couple.
- i. Do not use sweep triggering. Allow sweep to “free run”.
- j. Employ trace averaging (RMS) mode over a minimum of 100 traces.
- k. Use the peak marker function to determine the maximum amplitude level.
- l. Add $10 \log (1/x)$, where x is the duty cycle measured in step (a, to the measured PSD to compute the average PSD during the actual transmission time.

4.5.5 Deviation from Test Standard

No deviation.

4.5.6 EUT Operating Condition

Same as item 4.3.6

4.5.7 Test Results

802.11b

TX chain	Channel	Frequency (MHz)	PSD w/o Duty Factor (dBm/3kHz)	10 log (N=2) dB	Duty Factor (dB)	Total PSD With Duty Factor (dBm/3kHz)	Limit (dBm/3kHz)	Pass / Fail
0	1	2412	-12.81	3.01	2.39	-7.41	8.00	Pass
	6	2437	-11.52	3.01	2.39	-6.12	8.00	Pass
	11	2462	-12.52	3.01	2.39	-7.12	8.00	Pass
1	1	2412	-13.48	3.01	2.39	-8.08	8.00	Pass
	6	2437	-11.36	3.01	2.39	-5.96	8.00	Pass
	11	2462	-13.84	3.01	2.39	-8.44	8.00	Pass

Note:

1. Method E) 2) c) of power density measurement of KDB 662911 is using for calculating total power density, Measure value and add $10 \log (N_{ANT})$ dB.
2. Directional gain = $2\text{dBi} + 10\log(2) = 5.01\text{dBi} < 6\text{dBi}$, so the power density limit not need to reduce.
3. Refer to section 3.3 for duty cycle spectrum plot.

802.11g

TX chain	Channel	Frequency (MHz)	PSD w/o Duty Factor (dBm/3kHz)	10 log (N=2) dB	Duty Factor (dB)	Total PSD With Duty Factor (dBm/3kHz)	Limit (dBm/3kHz)	Pass / Fail
0	1	2412	-15.62	3.01	0.41	-12.20	8.00	Pass
	6	2437	-11.65	3.01	0.41	-8.23	8.00	Pass
	11	2462	-16.13	3.01	0.41	-12.71	8.00	Pass
1	1	2412	-15.08	3.01	0.41	-11.66	8.00	Pass
	6	2437	-12.01	3.01	0.41	-8.59	8.00	Pass
	11	2462	-16.50	3.01	0.41	-13.08	8.00	Pass

Note:

1. Method E) 2) c) of power density measurement of KDB 662911 is using for calculating total power density, Measure value and add $10 \log (N_{ANT})$ dB.
2. Directional gain = $2\text{dBi} + 10\log(2) = 5.01\text{dBi} < 6\text{dBi}$, so the power density limit not need to reduce.
3. Refer to section 3.3 for duty cycle spectrum plot.

802.11ax (HE20)

TX chain	Channel	Frequency (MHz)	PSD w/o Duty Factor (dBm/3kHz)	10 log (N=2) dB	Duty Factor (dB)	Total PSD With Duty Factor (dBm/3kHz)	Limit (dBm/3kHz)	Pass / Fail
0	1	2412	-17.89	3.01	0.23	-14.65	8.00	Pass
	6	2437	-14.04	3.01	0.23	-10.80	8.00	Pass
	11	2462	-17.24	3.01	0.23	-14.00	8.00	Pass
1	1	2412	-16.66	3.01	0.23	-13.42	8.00	Pass
	6	2437	-13.64	3.01	0.23	-10.40	8.00	Pass
	11	2462	-17.28	3.01	0.23	-14.04	8.00	Pass

Note:

1. Method E) 2) c) of power density measurement of KDB 662911 is using for calculating total power density, Measure value and add $10 \log (N_{ANT})$ dB.
2. Directional gain = $2\text{dBi} + 10\log(2) = 5.01\text{dBi} < 6\text{dBi}$, so the power density limit not need to reduce.
3. Refer to section 3.3 for duty cycle spectrum plot.

802.11ax (HE40)


TX chain	Channel	Frequency (MHz)	PSD w/o Duty Factor (dBm/3kHz)	10 log (N=2) dB	Duty Factor (dB)	Total PSD With Duty Factor (dBm/3kHz)	Limit (dBm/3kHz)	Pass / Fail
0	3	2422	-23.53	3.01	0.21	-20.31	8.00	Pass
	6	2437	-23.61	3.01	0.21	-20.39	8.00	Pass
	9	2452	-23.91	3.01	0.21	-20.69	8.00	Pass
1	3	2422	-22.79	3.01	0.21	-19.57	8.00	Pass
	6	2437	-23.11	3.01	0.21	-19.89	8.00	Pass
	9	2452	-23.70	3.01	0.21	-20.48	8.00	Pass

Note:


1. Method E) 2) c) of power density measurement of KDB 662911 is using for calculating total power density, Measure value and add $10 \log (N_{ANT})$ dB.
2. Directional gain = $2\text{dBi} + 10\log(2) = 5.01\text{dBi} < 6\text{dBi}$, so the power density limit not need to reduce.
3. Refer to section 3.3 for duty cycle spectrum plot.

Spectrum Plot of Worst Value


802.11b




802.11g



802.11ax (HE20)



802.11ax (HE40)




4.6 Conducted Out of Band Emission Measurement

4.6.1 Limits of Conducted Out of Band Emission Measurement

Below -30dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

4.6.2 Test Setup



4.6.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.6.4 Test Procedure

MEASUREMENT PROCEDURE REF

- Set the RBW = 100 kHz.
- Set the VBW $\geq$ 300 kHz.
- Detector = peak.
- Sweep time = auto couple.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.

MEASUREMENT PROCEDURE OOB

- Set RBW = 100 kHz.
- Set VBW $\geq$ 300 kHz.
- Detector = peak.
- Sweep = auto couple.
- Trace Mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum amplitude level.

4.6.5 Deviation from Test Standard

No deviation.

4.6.6 EUT Operating Condition

Same as item 4.3.6



4.6.7 Test Results

The conducted emission test is performed on each TX port of operating mode without summing or adding 10log (N) since the limit is relative emission limit.



The spectrum plots are attached on the following pages. D1 line indicates the highest level, and D2 line indicates the 30dB offset below D1. It shows compliance with the requirement.

802.11b_Chain 0



CH 1




CH 6




CH 11



CH 1 Band edge





CH 11 Band edge





802.11b_Chain 1



CH 1




CH 6




CH 11



CH 1 Band edge





CH 11 Band edge





802.11g_Chain 0



CH 1




CH 6




CH 11



CH 1 Band edge





CH 11 Band edge





802.11g_Chain 1



CH 1




CH 6




CH 11



CH 1 Band edge





CH 11 Band edge





802.11ax (HE20)_Chain 0



CH 1




CH 6




CH 11



CH 1 Band edge





CH 11 Band edge





802.11ax (HE20)_Chain 1



CH 1




CH 6




CH 11



CH 1 Band edge




CH 11 Band edge




802.11ax (HE40)_Chain 0


CH 3




CH 6



CH 9





CH 3 Band edge





802.11ax (HE40)_Chain 1



CH 3




CH 6




CH 9



CH 3 Band edge




CH 9 Band edge




Annex A - Band Edge Measurement

802.11b Channel 1


Horizontal (Peak)




Horizontal (Average)



Vertical (Peak)




Vertical (Average)




802.11b Channel 11


Horizontal (Peak)




Horizontal (Average)



Vertical (Peak)




Vertical (Average)




802.11g Channel 1


Horizontal (Peak)




Horizontal (Average)



Vertical (Peak)




Vertical (Average)




802.11g Channel 11


Horizontal (Peak)




Horizontal (Average)



Vertical (Peak)




Vertical (Average)




802.11ax (HE20) Channel 1


Horizontal (Peak)




Horizontal (Average)



Vertical (Peak)




Vertical (Average)




802.11ax (HE20) Channel 6


Horizontal (Peak)




Horizontal (Average)



Vertical (Peak)




Vertical (Average)




802.11ax (HE20) Channel 11


Horizontal (Peak)




Horizontal (Average)



Vertical (Peak)




Vertical (Average)




802.11ax (HE40) Channel 3


Horizontal (Peak)




Horizontal (Average)



Vertical (Peak)




Vertical (Average)




802.11ax (HE40) Channel 6


Horizontal (Peak)




Horizontal (Average)



Vertical (Peak)




Vertical (Average)




802.11ax (HE40) Channel 9


Horizontal (Peak)




Horizontal (Average)



Vertical (Peak)



Vertical (Average)



5 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo).

Appendix – Information of the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are FCC recognized accredited test firms and accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Lin Kou EMC/RF Lab

Tel: 886-2-26052180

Fax: 886-2-26051924

Hsin Chu EMC/RF/Telecom Lab

Tel: 886-3-6668565

Fax: 886-3-6668323

Hwa Ya EMC/RF/Safety Lab

Tel: 886-3-3183232

Fax: 886-3-3270892

Email: service.adt@tw.bureauveritas.com

Web Site: www.bureauveritas-adt.com

The address and road map of all our labs can be found in our web site also.

--- END ---